

Volume 13, Issue 1 (V)

January - March 2026

ISSN: 2394 – 7780



International Journal of
Advance and Innovative Research
(Conference - Special Issue)

Indian Academicians and Researchers Association
www.iaraedu.com

International Journal of Advance and Innovative Research

Volume 13, Issue 1 (V): January - March 2026

Editor- In-Chief

Dr. Tazyn Rahman

Members of Editorial Advisory Board

Mr. Nakibur Rahman

Ex. General Manager (Project)
Bongaioan Refinery, IOC Ltd, Assam

Dr. Alka Agarwal

Director,
Mewar Institute of Management, Ghaziabad

Prof. (Dr.) Sudhansu Ranjan Mohapatra

Dean, Faculty of Law,
Sambalpur University, Sambalpur

Dr. P. Malyadri

Principal,
Government Degree College, Hyderabad

Prof. (Dr.) Shareef Hoque

Professor,
North South University, Bangladesh

Prof.(Dr.) Michael J. Riordan

Professor,
Sanda University, Jiashan, China

Prof.(Dr.) James Steve

Professor,
Fresno Pacific University, California, USA

Prof.(Dr.) Chris Wilson

Professor,
Curtin University, Singapore

Prof. (Dr.) Amer A. Taqa

Professor, DBS Department,
University of Mosul, Iraq

Dr. Nurul Fadly Habidin

Faculty of Management and Economics,
Universiti Pendidikan Sultan Idris, Malaysia

Dr. Neetu Singh

HOD, Department of Biotechnology,
Mewar Institute, Vasundhara, Ghaziabad

Dr. Mukesh Saxena

Pro Vice Chancellor,
University of Technology and Management, Shillong

Dr. Archana A. Ghatule

Director,
SKN Sinhgad Business School, Pandharpur

Prof. (Dr.) Monoj Kumar Chowdhury

Professor, Department of Business Administration,
Guahati University, Guwahati

Prof. (Dr.) Baljeet Singh Hothi

Professor,
Gitarattan International Business School, Delhi

Prof. (Dr.) Badiuddin Ahmed

Professor & Head, Department of Commerce,
Maulana Azad Nationl Urdu University, Hyderabad

Dr. Anindita Sharma

Dean & Associate Professor,
Jaipuria School of Business, Indirapuram, Ghaziabad

Prof. (Dr.) Jose Vargas Hernandez

Research Professor,
University of Guadalajara, Jalisco, México

Prof. (Dr.) P. Madhu Sudana Rao

Professor,
Mekelle University, Mekelle, Ethiopia

Prof. (Dr.) Himanshu Pandey

Professor, Department of Mathematics and Statistics
Gorakhpur University, Gorakhpur

Prof. (Dr.) Agbo Johnson Madaki

Faculty, Faculty of Law,
Catholic University of Eastern Africa, Nairobi, Kenya

Prof. (Dr.) D. Durga Bhavani

Professor,
CVR College of Engineering, Hyderabad, Telangana

Prof. (Dr.) Shashi Singhal

Professor,
Amity University, Jaipur

Prof. (Dr.) Alireza Heidari

Professor, Faculty of Chemistry,
California South University, California, USA

Prof. (Dr.) A. Mahadevan

Professor
S. G. School of Business Management, Salem

Prof. (Dr.) Hemant Sharma

Professor,
Amity University, Haryana

Dr. C. Shalini Kumar

Principal,
Vidhya Sagar Women's College, Chengalpet

Prof. (Dr.) Badar Alam Iqbal

Adjunct Professor,
Monarch University, Switzerland

Prof.(Dr.) D. Madan Mohan

Professor,
Indur PG College of MBA, Bodhan, Nizamabad

Dr. Sandeep Kumar Sahratia

Professor
Sreyas Institute of Engineering & Technology

Dr. S. Balamurugan

Director - Research & Development,
Mindnotix Technologies, Coimbatore

Dr. Dhananjay Prabhakar Awasarikar

Associate Professor,
Suryadutta Institute, Pune

Dr. Mohammad Younis

Associate Professor,
King Abdullah University, Saudi Arabia

Dr. Kavita Gidwani

Associate Professor,
Chanakya Technical Campus, Jaipur

Dr. Vijit Chaturvedi

Associate Professor,
Amity University, Noida

Dr. Marwan Mustafa Shammot

Associate Professor,
King Saud University, Saudi Arabia

Prof. (Dr.) Aradhna Yadav

Professor,
Krupanidhi School of Management, Bengaluru

Prof.(Dr.) Robert Allen

Professor
Carnegie Mellon University, Australia

Prof. (Dr.) S. Nallusamy

Professor & Dean,
Dr. M.G.R. Educational & Research Institute, Chennai

Prof. (Dr.) Ravi Kumar Bommiseti

Professor,
Amrita Sai Institute of Science & Technology, Paritala

Dr. Syed Mehartaj Begum

Professor,
Hamdard University, New Delhi

Dr. Darshana Narayanan

Head of Research,
Pymetrics, New York, USA

Dr. Rosemary Ekechukwu

Associate Dean,
University of Port Harcourt, Nigeria

Dr. P.V. Praveen Sundar

Director,
Shanmuga Industries Arts and Science College

Dr. Manoj P. K.

Associate Professor,
Cochin University of Science and Technology

Dr. Indu Santosh

Associate Professor,
Dr. C. V.Raman University, Chhattisgarh

Dr. Pranjal Sharma

Associate Professor, Department of Management
Mile Stone Institute of Higher Management, Ghaziabad

Dr. Lalata K Pani

Reader,
Bhadrak Autonomous College, Bhadrak, Odisha

Dr. Pradeepta Kishore Sahoo

Associate Professor,
B.S.A, Institute of Law, Faridabad

Dr. R. Navaneeth Krishnan

Associate Professor, Bharathiyan College of Engg &
Tech, Puducherry

Dr. Mahendra Daiya
Associate Professor,
JIET Group of Institutions, Jodhpur

Dr. G. Valarmathi
Associate Professor,
Vidhya Sagar Women's College, Chengalpet

Dr. Parbin Sultana
Associate Professor,
University of Science & Technology Meghalaya

Dr. M. I. Qadir
Assistant Professor,
Bahauddin Zakariya University, Pakistan

Dr. Kalpesh T. Patel
Principal (In-charge)
Shree G. N. Patel Commerce College, Nanikadi

Dr. Brijesh H. Joshi
Principal (In-charge)
B. L. Parikh College of BBA, Palanpur

Dr. Juhab Hussain
Assistant Professor,
King Abdulaziz University, Saudi Arabia

Dr. Namita Dixit
Assistant Professor,
ITS Institute of Management, Ghaziabad

Dr. V. Tulasi Das
Assistant Professor,
Acharya Nagarjuna University, Guntur, A.P.

Dr. Nidhi Agrawal
Associate Professor,
Institute of Technology & Science, Ghaziabad

Dr. Urmila Yadav
Assistant Professor,
Sharda University, Greater Noida

Dr. Ashutosh Pandey
Assistant Professor,
Lovely Professional University, Punjab

Dr. M. Kanagarathinam
Head, Department of Commerce
Nehru Arts and Science College, Coimbatore

Dr. Subha Ganguly
Scientist (Food Microbiology)
West Bengal University of A. & F Sciences, Kolkata

Dr. V. Ananthaswamy
Assistant Professor
The Madura College (Autonomous), Madurai

Dr. R. Suresh
Assistant Professor, Department of Management
Mahatma Gandhi University

Dr. S. R. Boselin Prabhu
Assistant Professor,
SVS College of Engineering, Coimbatore

Dr. V. Subba Reddy
Assistant Professor,
RGM Group of Institutions, Kadapa

Dr. A. Anbu
Assistant Professor,
Achariya College of Education, Puducherry

Dr. R. Jayanthi
Assistant Professor,
Vidhya Sagar Women's College, Chengalpattu

Dr. C. Sankar
Assistant Professor,
VLB Janakiammal College of Arts and Science

Dr. Manisha Gupta
Assistant Professor,
Jagannath International Management School

Copyright @ 2026 Indian Academicians and Researchers Association
All rights reserved.

No part of this publication may be reproduced or transmitted in any form or by any means, or stored in any retrieval system of any nature without prior written permission. Application for permission for other use of copyright material including permission to reproduce extracts in other published works shall be made to the publishers. Full acknowledgment of author, publishers and source must be given.

The views expressed in the articles are those of the contributors and not necessarily of the Editorial Board or the IARA. Although every care has been taken to avoid errors or omissions, this publication is being published on the condition and understanding that information given in this journal is merely for reference and must not be taken as having authority of or binding in any way on the authors, editors and publishers, who do not owe any responsibility for any damage or loss to any person, for the result of any action taken on the basis of this work. All disputes are subject to Guwahati jurisdiction only.



The International Journal of Advance and Innovative Research is an online open access, peer reviewed & refereed journal.



CONTENTS

Research Papers

SYNTHETIC MEDIA DETECTION USING BENFORD'S LAW	1 – 11
<i>Utkarsh Mishra and Mujtaba Shaikh</i>	
SMART GAS LEAK DETECTION AND PREVENTION USING A SOLENOID VALVE	12 – 17
<i>Rudraksha Shivhari More, S.L. Nalbalwar, Arya Ravindra Darokar and Ratika Ravindra Jadhav</i>	
A ROBUST FRAGILE WATERMARKING APPROACH FOR IMAGE TAMPERING DETECTION AND RESTORATION UTILIZING HYBRID TRANSFORMS	18 – 26
<i>Riyaz Banu Shaik, Navitha Daruri, Sumanth Reddy Muddireddy, Naga Dharani Nukala, Rohith Kumar Kommanduru and Pavan Kumar Kondagalla</i>	
AI-POWERED SYSTEM FOR OPTIMIZATION AND RISK MANAGEMENT IN CONFIGURE-PRICE-QUOTE (CPQ) FOR FMCG	27 – 30
<i>Vishwajeet Singh and Dr. Neha Vora</i>	
CLASS-INCREMENTAL LEARNING FOR BRAIN TUMOR CLASSIFICATION USING ELASTIC WEIGHT CONSOLIDATION (EWC)	31 – 40
<i>Shubham Giri and Sunita Gupta</i>	
SENTIMENT ANALYSIS AND TOPIC MODELING USING BERT AND LDA	41 – 43
<i>Nikita Makwana and Manisha Divate</i>	
THE ROLE OF AI IN EDUCATION: A STUDY OF ITS IMPACT, OPPORTUNITIES, AND RISKS	44 – 49
<i>Nisha Sarvaiya and Neha Vora</i>	
A HYBRID TRANSLATION SYSTEM FOR HINGLISH: BRIDGING CODE-MIXED COMMUNICATION	50 – 58
<i>Om Rawal and Dr. Prashant Chaudhary</i>	
COMPARING YOLOv8 AND YOLOv9 FOR SNAKE CLASSIFICATION INTO VENOMOUS AND NON-VENOMOUS CATEGORIES	59 – 69
<i>Om Rawal and Neha Vora</i>	
ANALYZING OCCUPATIONAL INJURIES AND DISEASES: A DATA-DRIVEN STUDY OF THE US WORKING-CLASS POPULATION USING OSHA DATA	70 – 80
<i>Abhinav Kumar and Dr. Neelam Naik</i>	

UNDERSTANDING TIME SERIES: UTILIZING SALES DATA TO UNDERSTAND HOW TIME SERIES ALGORITHMS WORK	81 – 86
<i>Abhinav Kumar and Neha Vora</i>	
DOCINTEL : INTEGRATING OCR AND NLP FOR CONTENT-BASED FILE RETRIEVAL	87 – 93
<i>Kanak Patel and Dr. Neha Vora</i>	
A COMPARATIVE STUDY OF MACHINE LEARNING TECHNIQUES FOR FRAUD DETECTION IN DIGITAL TRANSACTIONS	94 – 101
<i>Sujal Upadhyay</i>	
ALZHEIMER’S DETECTION FROM BRAIN IMAGING USING DEEP LEARNING: A TRANSFER LEARNING APPROACH	102 – 108
<i>Rohan Tiwari, Dr. Smruti Nanavaty, Vinayak Mishra and Dr. Neha Vora</i>	
PyMCP: A SECURE, EXECUTION ENVIRONMENT FOR AI AGENTS	109 – 113
<i>Aniket Panchal and Dr.Neha Vora</i>	
NEUROADAPTIVE AI MENTAL HEALTH ASSISTANT	114 – 120
<i>Priyansh Shah and Dr. Neha Vora</i>	
TECHNOSTRESS: A REVIEW OF ITS DIMENSIONS, IMPACTS, AND MANAGEMENT STRATEGIES	121 – 127
<i>Jiya Patel and Dr. Smruti Nanavaty</i>	
DEEP LEARNING SYSTEM FOR RESPIRATORY DISORDER DETECTION USING MULTIMODAL AUDIO FEATURES (MFCC, MEL SPECTROGRAM, AND CHROMA STFT)	128 – 133
<i>Dhruvin Soni and Dr. Prashant Chaudhary</i>	
VEHICLE DAMAGE DETECTION USING DEEP LEARNING TECHNIQUES: A COMPREHENSIVE REVIEW	134 – 139
<i>Khushi Dama</i>	
ENERGY-EFFICIENT VIRTUAL MACHINE MANAGEMENT IN CLOUD DATA CENTERS	140 – 147
<i>Nastel Rodrigues</i>	
A COMPARATIVE STUDY OF TinyML MODELS FOR AUTONOMOUS THREAT DETECTION IN WEARABLE WOMEN SAFETY DEVICES	148 – 156
<i>Umayar Shaikh and Swapnali Lotlikar</i>	
LEARNING SYSTEM FOR DYSLEXIA KIDS WITH AI PERSONALIZATION, SPEECH & VOICE INTEGRATION	157 – 163
<i>Yash Hande</i>	

A RESEARCH ON HEALTHCARE COST PREDICTION AND FINANCIAL RISK ANALYSIS USING MACHINE LEARNING	164 – 170
<i>Dhruvi Sheth and Manisha Divate</i>	
THE SHIFT OF THINKING IN HUMANS	171 – 177
<i>Gurnur Bedi and Swapnali Lotlikar</i>	
CINEMIND: ENHANCING EMPATHY AND CULTURAL UNDERSTANDING THROUGH MOVIES	178 – 183
<i>Palak Bari and Prashant Chaudhary</i>	
THE SYMBIOTIC EVOLUTION: A REVIEW OF ARTIFICIAL INTELLIGENCE'S ROLE WITHIN EDUCATION 4.0 AND ENVISIONING EDUCATION 5.0	184 – 194
<i>Arya Shah and Manisha Divate</i>	
THE INTERPLAY OF SOCIAL, ACADEMIC, AND ECONOMIC STRESSORS IN THE GEN Z MENTAL HEALTH CRISIS	195 – 201
<i>Jaival Soni and Manisha Divate</i>	
EFFECT SOCIAL MEDIA ON MENTAL HEALTH	202 – 210
<i>Neer Raval and Swapnali Lotlikar</i>	
FORECASTING BLOOD GLUCOSE LEVELS IN TYPE 1 DIABETES USING A HYBRID ARIMA-LSTM MODEL	211 – 217
<i>Sejal Vinod Jethwa and Mrs. Sunita Gupta</i>	
BLOCKCHAIN-BASED GRADE CARD MANAGEMENT SYSTEM	218 – 227
<i>Darshan Sheth and Swapnali Lotlikar</i>	
ANALYZING TRAVEL BLOG AND VLOG CONTENT TRENDS TO PREDICT FUTURE TOURISM DESTINATIONS	228 – 235
<i>Darshan Pravin Parmar and Dr. Smruti Nanavaty</i>	
REDUCTION OF HALLUCINATION IN LLMS VIA RAG RETRIEVAL AUGMENTED GENERATION: A REVIEW	236 – 241
<i>Mahak Bajaj</i>	
INCLUSIVE UI/UX DESIGN FOR E-LEARNING: A CASE STUDY OF EDUABLE	242 – 248
<i>Harshida Prajapati and Dr. Neelam Naik</i>	
PREDICTIVE ANALYTICS IN HEALTHCARE FOR EARLY DISEASE DETECTION	249 – 256
<i>Heli Dakhra and Dr. Neha Vora</i>	
TARGETING BEYOND TASTE: DATA-DRIVEN MARKETING INSIGHTS FOR FMCG GROWTH	257 – 264
<i>Isha Padhiyar, Dr. Smruti Nanavaty, Nuhi Shaikh and Ms. Sunita Gupta</i>	

DIGITAL OVERLOAD AMONG STUDENTS: A REVIEW OF SMARTPHONE NOTIFICATIONS, SOCIAL MEDIA MULTITASKING, AND COGNITIVE FATIGUE	265 – 269
<i>Mital Gohil and Manisha Divate</i>	
PREDICTING NIFTY 50 OPENING DIRECTION USING ENSEMBLE LEARNING, XAI, SENTIMENT ANALYSIS	270 – 276
<i>Prasanna Acharya, Darshil Shetty, Dr. Neelam Naik and Dr. Neha Vora</i>	
AI VS. HUMAN ART: A STUDY OF EMOTIONAL PERCEPTION AND COGNITIVE BIAS	277 – 283
<i>Abid Shaikh and Manisha Divate</i>	
SACHET WASTE MAPPING: THE HIDDEN PLASTIC	284 – 289
<i>Poornima Londhe and Smruti Nanavaty</i>	
SEMANTIC-BASED ACADEMIC IMAGE CLASSIFICATION USING OCR AND EXTERNAL KNOWLEDGE SOURCES	290 – 297
<i>Tanisha Bhalgamia and Dr. Neha Vora</i>	
AI-POWERED WORKFORCE TRANSFORMATION: K-MEANS CLUSTERING STUDY OF ENTERPRISE ADOPTION OF GENERATIVE AI.	298 – 304
<i>Keyur Amit Mistry and Dr. Smruti Nanavaty</i>	
BIKE RENTAL DEMAND ANALYSIS	305 – 310
<i>Manav Parmar and Dr. Manisha Divate</i>	
EXPLORING THE ROLE OF VIRTUAL REALITY IN ENHANCING SOFT SKILL TRAINING	311 – 316
<i>Keval Bharat Dedia and Dr. Neelam Naik</i>	
NFT PRICE TRENDS PREDICTION USING DEEP LEARNING: A MULTIMODAL APPROACH	317 – 323
<i>Asad Momin and Swapnali Lotlikar</i>	
FINANCIAL FRAUD ANALYTICS	324 – 327
<i>Shubham Shah and Dr. Neha Vora</i>	
DATABASE SECURITY IN CLOUD ENVIRONMENT: ADDRESSING CHALLENGES IN DBAAS	328 – 331
<i>Akshat Chheda and Dr. Neelam Naik</i>	
EFFECTS OF SOCIAL MEDIA USAGE ON MENTAL HEALTH	332 – 335
<i>Riya Gajra and Dr. Smruti Nanavaty</i>	
MACHINE LEARNING BASED BANK CREDIT SCORING FOR RISK ASSESSMENT: A COMPREHENSIVE EMPIRICAL FRAMEWORK	336 – 342
<i>Aawez Shaikh and Neelam Naik</i>	

DEEPFAKES: TECHNOLOGY, THREATS, AND THE GLOBAL COUNTER MEASURE LANDSCAPE	343 – 348
<i>Pratham Sanghvi and Manisha Divate</i>	
A CONTEXT-AWARE, LOW-COST SDR FRAMEWORK FOR CUBESAT TELEMETRY RECEPTION AND ANALYSIS	349 – 350
<i>Aditi Tiwari and Manisha Divate</i>	
LIFESTYLE CHOICES AND THEIR IMPACT ON WELL-BEING	351 – 354
<i>Gaurav Parmar and Dr. Prashant Chaudhary</i>	
SPORTHUB: A UNIFIED MULTI-SPORT BOOKING SYSTEM	355 – 360
<i>Harsh Darji and Dr. Neha Vora</i>	
BANK CREDIT SCORING: A MACHINE LEARNING FRAMEWORK TO RISK ASSESSMENT & REAL-TIME MONITORING.	361 – 367
<i>Akshata Balla, Dr. Neha Vora, Sakshi Raut and Dr. Neelam Naik</i>	
A COMPREHENSIVE, EXPLAINABLE, AND SCALABLE MARKETING ANALYTICS FRAMEWORK FOR THE FMCG SECTOR USING BEHAVIORAL MODELING, PREDICTIVE ANALYTICS, AND INTERPRETABLE MACHINE LEARNING	368 – 373
<i>Juwairia Khan, Devna Patel, Dr. Swapnali Lotlikar and Prof. Sunita Gupta</i>	
A HYBRID SENTIMENT–MARKET MODEL FOR PREDICTING NIFTY 50 OPENING DIRECTION USING LOGISTIC REGRESSION	374 – 381
<i>Sahal Patel, Surakshith Shetty, Dr. Neha Vora and Dr. Prashant Chauudhary</i>	
AIR QUALITY INDEX PREDICTION AND HEALTH IMPACT ANALYSIS USING MACHINE LEARNING	382 – 390
<i>Nareen Ansari and Swapnali Lotlikar</i>	
INVENTO: AI POWERED INVENTORY MANAGEMENT SYSTEM	391 – 400
<i>Aditi Manish Upadhayay and Dr. Neha Vora</i>	
FORECASTING E-COMMERCE CUSTOMER SATISFACTION TRENDS USING ARIMA TIME-SERIES MODELING	401 – 407
<i>Aarti Chavan and Smruti Nanavaty</i>	
DUAL-MODAL DYSLEXIA DETECTION USING HANDWRITING AND EYE MOVEMENTS	408 – 413
<i>Vaishnavi Nayak</i>	
BANK CREDIT SCORING	414 – 420
<i>Yashasvi Verma, Noor Ansari, Dr. Smruti Nanavati and Manisha Diavate</i>	

AI-BASED LEARNING MANAGEMENT SYSTEM: STUDY AND IMPLEMENTATION	421 – 428
<i>Khushi Manish Upadhayay</i>	
GLOBAL MARKET ANALYTICS WITH PREDICTIVE AND VISUAL INSIGHTS	429 – 438
<i>Ritik Sharma, Dhruv Dagla, Smruti Nanavaty and Dr. Swapnali Lotlikar</i>	
BASIC PREDICTIVE MODELING USING PYCARET AUTOML FOR NIFTY 50 OPEN DIRECTION BASED ON GLOBAL INDEX RETURNS AND VIX	439 – 442
<i>Urvashi Dilip Dhakan, Shivam Umeshkumar Gupta, Dr. Swapnali Lotlikar and Dr. Sunita Gupta</i>	
GLOBAL MARKET INDICES IMPACT ON NIFTY 50	443 – 446
<i>Prathamesh Pathare and Manisha Divate</i>	
THINKSAFE: AI FOR STUDENTS' EMOTIONAL HEALTH AWARENESS	447 – 453
<i>Vinayak Tiwari and Dr. Neha Vora</i>	
COMPARATIVE DISEASE PROGRESSION USING FORECASTING MODELS: A CASE STUDY IN K-WEST WARD, MUMBAI	454 – 457
<i>Zaobiya Khan and Smruti Nanavaty</i>	
COMPARING THE PERFORMANCE AND ACCURACY OF LEADING LARGE LANGUAGE MODELS (LLMS) WITH AN EMPHASIS ON MEDICAL AI APPLICATIONS	458 – 462
<i>Jainam Mehta and Krishna Parmar</i>	
A HYBRID FRAMEWORK FOR LARGE-SCALE STUDENT FEEDBACK SENTIMENT ANALYSIS	463 – 467
<i>Pratham Vardhman Jain and Dr. Swapnali Lotlikar</i>	
DISEASE DETECTION IN MEDICAL IMAGING	468 – 472
<i>Ghoshi MohdAnas and Neha Vora</i>	
A THEORETICAL FRAMEWORK FOR ADAPTIVE TOPOLOGY SELECTION IN DATA CENTER NETWORKS	473 – 478
<i>Fatima Shaikh and Neelam Naik</i>	
AI CAREER HUB – AN ALL-IN-ONE CAREER ACCELERATOR PLATFORM	479 – 490
<i>Krishna Johari and Dr. Neha Vora</i>	
COMPARATIVE ANALYSIS OF USER PERCEPTIONS AND LEARNING PREFERENCES: A STUDY OF AI, YOUTUBE AND GOOGLE IN EDUCATION	491 – 496
<i>Saanvi Ghadiali and Neha Vora</i>	
A REVIEW OF RECENT EMERGING TRENDS IN TB³⁺ - ACTIVATED BORATE HOST PHOSPHOR MATRIX FOR NUV-EXCITED WLEDs	497 – 499
<i>Prabhat P. Tiwari</i>	

**IMPACT OF ARTIFICIAL INTELLIGENCE IN BANKING SECTOR WITH 500 – 504
REFERENCE TO AXIS BANK**

Dr. Prasad M Supekar

**ADOPTION OF GENERATIVE AI IN FINANCIAL RESEARCH AND EDUCATION: 505 – 507
OPPORTUNITIES AND ACADEMIC INTEGRITY RISKS**

Krupali Prakashkumar Nakar

**THIRD-PARTY DATA BREACHES: AN EMERGING CYBERSECURITY THREAT IN 508 – 514
THE DIGITAL ERA**

Yaquta Tambuwala

SYNTHETIC MEDIA DETECTION USING BENFORD'S LAW

¹Utkarsh Mishra and ²Mujtaba Shaikh¹Department of Technology, International Financial Services Centres Authority, Government of India Gujarat, India²Department of Data Science, University of Europe for Applied Sciences Dubai, United Arab Emirates**I. ABSTRACT**

The proliferation of synthetic media, particularly deepfakes, presents a profound challenge to digital forensics. Conventional detection techniques predominantly rely on deep learning models, which are not only computationally intensive but also function as “black boxes”—providing limited interpretability of their decision-making processes. Additionally, these models are vulnerable to adversarial attacks. This study investigates the applicability of Benford's Law, a statistical principle that predicts the distribution of leading digits in naturally occurring datasets, as a computationally efficient and interpretable alternative for detecting synthetic media. By employing the Discrete Cosine Transform (DCT) to extract frequency-domain features from media files, we analysed the conformity of these features to Benford's expected digit distribution. The experimental results, derived from both authentic and synthetic datasets, reveal that genuine media adheres closely to Benford's Law, whereas synthetic media exhibits significant deviations. These findings suggest that Benford's Law can serve as a robust and transparent tool for anomaly detection in digital forensics. Furthermore, the proposed method's low computational requirements and interpretability make it a promising candidate for integration into hybrid detection frameworks, enhancing the accuracy and efficiency of deepfake detection systems. This research contributes to advancing media forensics by offering a statistically grounded and resource-efficient approach to identifying synthetic content.

Keywords: Benford's Law, Synthetic Media Detection, Deepfake Forensics, Anomaly Detection, Digital Forensics

II. STATEMENTS AND DECLARATIONS**a. Competing Interests:**

The authors declare no conflicts of interest.

All co-authors have reviewed and approved the manuscript's contents. Additionally, we confirm that this submission represents original work and is not currently under consideration by any other publication.

b. Funding:

The authors declare that no specific grants or financial support were received for this research from any funding agency, commercial entity, or not-for-profit organization.

c. Data Availability:

The datasets analysed are publicly available on Kaggle: <https://www.kaggle.com/datasets/nanduncs/1000-deepfake-videos>. Additional data can be requested from the corresponding author. Secondary datasets are cited in the references.

III. INTRODUCTION

The rise of deepfakes poses a serious threat to digital forensics, enabling highly convincing audio and video manipulations that can facilitate misinformation, fraud, and blackmail. Detecting these forgeries efficiently has become increasingly urgent.

Existing approaches, including machine learning classifiers and deep neural networks, are data hungry and require computationally intensive resources but are still susceptible to attacks by adversaries. This emphasizes the importance of having more robust and efficient alternatives.



Figure 1 - Comparative examples of deepfake videos versus authentic videos of celebrities.

We suggest applying Benford's Law—a statistical principle governing leading digit distributions—as a light-weight solution for synthetic media detection. As opposed to classical methods relying on extensive training datasets, Benford's Law presents a straightforward statistical reference point. Naturally occurring data tends to conform to this law, whereas artificially introduced manipulations lead to perceptible deviations.

By using Discrete Cosine Transform (DCT) to derive frequency-domain features from media files and comparing their digit distributions against Benford's Law, our experiments showed that actual media obey this law while synthetic media has obvious anomalies. This indicates that Benford's Law may be a useful tool for media forensics, either standalone or in conjunction with deep learning techniques.

This method not only improves detection performance but also significantly decreases the computational complexity of current models, leading to more efficient and resilient digital content protection techniques. This research seeks to show that the application of statistical laws such as Benford's Law can not only improve the efficiency of synthetic media detection but also decrease the computational cost of deep learning models substantially. Through this new use, we seek to advance the development of more robust and accessible methods for protecting the integrity of digital content

IV. ORIGIN OF BENFORD'S LAW

Benford's Law was first observed by Simon Newcomb in 1881 when he noticed that pages with logarithms for numbers beginning with less significant digits were more worn than the rest. He hypothesized that numbers that begin with less significant digits occur more frequently in the majority of real-world datasets. His observations were, however, overlooked until 1938, when physicist Frank Benford re-discovered and developed them. Benford scanned more than 20,000 data sets—from river lengths to amounts of money—and verified that the leading digits of numbers tended to act consistently. Newcomb further remarked, "The law governing the probability of numerical occurrences dictates that all mantissae of logarithms are equally probable." [2]

The law dictates that the digit 1 occurs as the leading digit roughly 30% of the time, and bigger digits such as 9 less than 5% of the time. This is the case for very broad data sets and is scale-invariant, and so can be applied to forensic accounting and fraud detection. Well-known though it is, Benford's Law still lacks formal mathematical justification, which makes it a statistical oddity to some. In this present research, we investigate whether Benford's Law can further be utilized to identify forged media through the detection of deviation from its expected distribution.

V. MATHEMATICAL PRINCIPLES UNDERLYING BENFORD'S LAW FOR ANOMALY DETECTION

The success of Benford's Law in identifying anomalies in natural data relies on fundamental mathematical principles. One important property is scale invariance, which guarantees that the leading digit distribution does not change even when datasets are scaled. This is especially useful in digital forensics, where media files tend to

be compressed and scaled. The fact that Benford's Law can still be accurate regardless of scales makes it a trusted anomaly detection tool.

Another important consideration is that Benford's Law emerges naturally in data sets produced by multiplicative processes. Most natural phenomena—like financial data, population increases, and pixel intensity distributions—are determined by products of independent variables. By the Central Limit Theorem for products, these data sets converge to a logarithmic distribution of leading digits. It is, therefore, this feature that justifies the broad applicability of Benford's Law and its efficiency in capturing irregularities in synthetic data where these natural relationships tend to be lacking or inadequately mimicked.

Base invariance is yet another significant feature, which states that Benford's Law remains applicable with varying numerical bases. The fact that it is universal implies that the law presumes a deep property of natural data generation and not an artifact of any given numbering system. Such a characteristic adds to the strength of Benford's Law in anomaly detection, and the law will still be effective irrespective of the numerical form of the data.

Conversely, synthetic media—specifically that produced using Generative Adversarial Networks (GANs)—does not have the intricate statistical patterns of native data. GANs are designed to generate visually plausible content but might not always reproduce the true statistical distributions. Consequently, synthetic media commonly demonstrates divergence from Benford's anticipated patterns. Empirical work verifies that whereas natural images adhere well to Benford's distribution, synthetic images are often full of irregularities.

Such deviations are observable signs of synthetic manipulation, with a firm mathematical foundation for applying Benford's Law in digital forensics. Through effective detection of these anomalies, Benford's Law provides an open and computationally effective way of identifying synthetic media, complementing the integrity of forensic examination.

A. Leading First and Second Digit's:

The mathematical expressions delineating the expected frequencies of digits(D_i) within arrays of numerical values are provided as follows :



Figure 2- Benford's first digit distribution graph

$$Prob(D_1 = d_1) = \log_{10} \left(1 + \frac{1}{d_1} \right) \quad \dots (1)$$

where; $d_1 \in \{1, 2, 3, \dots, 9\}$

D_1 representing the first digit [3]




Figure 3 - Benford's second digit distribution graph

Below table 01 illustrate that expected frequencies for each digit from 0 to 9 across the first four positional places in a numerical sequence.

Table 1. Expected Frequencies based on Benford's Law

Digit	0	1	2	3	4	5	6	7	8	9
1st Place	-	0.30103	0.17609	0.12494	0.09691	0.07918	0.06695	0.05799	0.05115	0.04576
2nd Place	0.11968	0.11389	0.19882	0.10433	0.10031	0.09668	0.09337	0.09035	0.08757	0.085
3rd Place	0.10178	0.10138	0.10097	0.10057	0.10018	0.09979	0.0994	0.09902	0.09864	0.09827
4th Place	0.10018	0.10014	0.1001	0.10006	0.10002	0.09998	0.09994	0.0999	0.09986	0.09982

Source: Nigrini, 1996.

B. Leading First Two Digit's:

Most applications of Benford's Law are in the first significant digit to detect anomalies in data. However, in this study, we extend this one step further by considering the first two digits together. This gives a more nuanced view of the data and allows us to detect anomalies that cannot be seen when only considering the first digit.

The lower digit pairs will have a greater chance of occurring than higher ones, and this will be in a known pattern. For example, numbers that start with 10 should occur more than numbers that start with 99. In actual data sets in the world, this pattern does generally hold, so it can be an excellent tool for identifying phony or faked data.

An investigation by Andreas Diekmann (2007) found that real data typically follows Benford's distribution for not just the first digit but also the second, third, and even subsequent digits. Artificial data, on the other hand, usually does not follow the same pattern. When we consider the first two digits, we get a better indication of the legitimacy of the data and can spot more subtle evidence of manipulation[4].




Figure 4 - Benford's First Two Digit Distribution Graph

According to Benford's Law, the probability of a number starting with a specific pair of digits d_1d_2 can be calculated using the following formula:

$$Prob(D_1 D_2 = d_1 d_2) = \sum_{d_1, d_2} \log_{10} \left(1 + \frac{1}{d_1 d_2} \right) \quad \dots (3)$$

where; $d_1 d_2 \in \{10, 11, 12, \dots, 99\}$
 $D_1 D_2$ representing the first two digit [3]

This more extensive analysis is particularly necessary in the case of synthetic media detection, where artificial content could be designed to avoid more direct detection techniques. By comparing the frequency of the observed pairings of two-digit numbers in media data against Benford's predicted distribution, we aim to discover hidden anomalies that could signal manipulation or artificial fabrication[5].

VI. DISCRETE COSINE TRANSFORM

In digital images, every pixel possesses an intensity level from 0 (completely dark) to 255 (completely light). Though such raw pixel data is handy, it doesn't always uncover latent patterns—particularly in the identification of manipulated or synthetic media. That's where the Discrete Cosine Transform (DCT) is handy.

The DCT is a mathematical process that converts an image from the spatial domain (pixel intensities) to the frequency domain. In other words, it decomposes an image into various frequency components, which makes it simpler to identify unusual patterns that are not apparent in the original pixel values. The DCT is analogous to the Fourier Transform but is specifically well-suited for image analysis since it deals solely with real numbers, thus being faster and more efficient.

The DCT for an $N \times M$ image is defined as:

$$F(u, v) = \frac{2}{\sqrt{NM}} \sum_{x=0}^{N-1} \sum_{y=0}^{M-1} f(x, y) \cos \left[\frac{(2x+1)u\pi}{2N} \right] \cos \left[\frac{(2y+1)v\pi}{2M} \right] \quad [7] \quad \dots (4)$$

Here:

(x, y) is the pixel intensity at position (x, y)


- $F(u, v)$ represents the DCT coefficient at frequency (u, v)
- N and M are the image dimensions.

This equation helps convert spatial information into frequency components, making it easier to spot irregularities in the data.

Here, we applied the DCT to derive frequency-domain features from images and check whether these features comply with Benford's Law. From the observation of the distribution of leading digits in the transformed data, we are able to identify anomalies indicating synthetic tampering. For example, natural images would have DCT coefficients agreeing with Benford's expected pattern, whereas synthetic images tend to have strong anomalies.

We implemented DCT through Python packages such as OpenCV and NumPy, which enabled us to handle images well. Once we processed the image using DCT, we converted the resulting 2D matrix into a 1D vector for easier analysis. We then compared the distribution of the leading digits of this vector to the predicted frequencies of Benford's Law. Any noticeable mismatch with the predicted pattern could suggest that the image had been edited or artificially created. This technique not only improves the detection of synthetic media but does so without the computationally intensive costs of deep learning models. By leveraging the strengths of Benford's Law and DCT, our technique provides a lightweight yet effective solution.

The following illustrates the steps involved in applying the Discrete Cosine Transform (DCT) process to a standard RGB image.



Pipeline 1 - Discrete Cosine Transformation Process


VII. APPLICATIONS OF BENFORD'S LAW

A. Visual Misrepresentation Analysis:

Synthetic images have been a major challenge to digital forensics in recent years, especially with the advent of Generative Adversarial Networks (GANs)[8]. These technologies have made it much simpler to create highly realistic forged images and manipulated media, making it more imperative to have dependable detection methods. In this regard, Benford's Law—a statistical principle that forecasts the distribution of leading digits in naturally occurring data sets—presents itself as a valuable tool for detecting visual misrepresentations.

a) Materials and Methods:

To measure the ability of Benford's Law to detect synthetic images, we concentrated on obtaining numerical data from pixel values, which usually range between 0 and 255 as 8-bit data. Through Python libraries like OpenCV and NumPy, we used the Discrete Cosine Transform (DCT) to transform image data into an analyzable format. To avoid the imprecision of our results, unwanted background noise was eliminated with utmost care. Once preprocessed, 2D image matrix was converted to 1D vector so that pixel value distributions could be studied more comprehensively. The investigation indicated a high correlation between the empirical digit distributions and theoretical predictions of Benford's Law, which implies that this technique can be used to distinguish between real and forged images.



Pipeline 2 - Procedure for Image Classification Based on Benford's Law



Pic 1 - Source Image



Pic 2 - Target Image



Pic 3 - Synthetic Image

To further confirm this method, we performed a case study on a deepfake of Christopher Robert Evans [Pic 2][9], generated via the Roop library. The changes in the deepfake were subtle enough not to be perceptible to the human eye but left traces which could be identified in the pixel values. Applying these traces via the perspective of Benford's Law, we discovered that the Source Image met the predicted distribution of digits in a very closely manner, hinting at it being authentic. Similarly, the Target Image also revealed a pattern adhering to Benford's distribution, solidifying its authenticity. As a point of comparison, the Synthetic Image reflected heavy inconsistencies from Benford's Law and featured anomalies with a high indication of artificial intervention.

b) Inferences:

The outcomes directly reveal the ability of Benford's Law in determining between true and synthetic images by marking deviation points in pixel value distributions.

Figure 5 illustrates that the Source Image closely resembles Benford's Law, with digit distributions well approximated by expected values. The agreement implies that the image is genuine since its pixel values demonstrate a natural pattern of distribution with no indication of artificial manipulation.




Figure 5 - Benford's Curve for Source image [Pic 1] and Expected Distribution




Figure 6 - Benford's Curve for Target image [Pic 2] and Expected Distribution

Similarly, Figure 6 shows that the Target Image also follows the Benford's Law, where it has an uniform digit distribution pattern that further validates its genuineness. Alignment with the expected distributions implies that this method is trustworthy to detect authentic media.

In contrast, Figure 7 reveals that the Synthetic Image is just the opposite, with profound divergences from Benford's Law and chaotic digit patterns implying artificial alteration. These are signatures of alterations untypical in original media and validate the usefulness of Benford's Law to identify synthetic falsification.




Figure 7 - Benford's Curve for Synthetic image [Pic 3] and Expected Distribution

These results confirm that Benford's Law is an effective method for differentiating between real and fake images. Through the detection of minor inconsistencies in digit patterns, this technique increases the credibility of forensic analysis in the fight against the growing menace of synthetic media. The capacity to identify such anomalies highlights the promise of incorporating Benford's Law into current forensic processes for more precise and effective media authentication.


B. Video Falsification Analysis:

The explosive development of Generative Adversarial Networks (GANs) has rendered it incredibly easy to produce hyper-realistic deepfake videos, which presents a critical challenge for digital forensics. Deepfake videos can be employed in the dissemination of disinformation, personal defamation, or fraud, and hence it is important that trustworthy detection methods be identified. Here, Benford's Law—a statistical law forecasting the occurrence of leading digits in naturally occurring data sets—is presented as a valuable instrument to identify manipulated videos. Its sensitivity to detect abnormal distributions of digits presents a powerful strategy for exposing video manipulation that could go unnoticed using conventional approaches.

a) Materials and Methods:

For analyzing video forgery in terms of Benford's Law, we adopted a methodical procedure that integrated face detection and frequency-domain analysis. Face detection was done using the Haar Cascade classifier technique [10], through which facial areas were extracted from video files. Extracted frames were then stored as JPG files and classified into corresponding folders for in- depth analysis.

After face extraction, the Discrete Cosine Transform (DCT) was used to transform the 2D pixel data into frequency-domain format. This process was critical in making the analysis of pixel value distribution more pronounced through focusing on the structural quality of the video frames. Background noise was carefully eliminated before transformation for the sake of precision to remove any unwanted influences that might mislead the digit distribution results.



Pipeline 3 - Procedure for Video Classification Based on Benford's Law

The frames thus processed using the DCT were then flattened as 1D vectors to ease the thorough study of digit distributions. The foremost digit distributions from these vectors were compared systematically against the predicted distributions as mandated by Benford's Law. Comparison was done by utilizing Python packages like OpenCV and NumPy, which were used for detection, transformation of faces, as well as for statistical analysis of pixel values.

To demonstrate the real-world application of this method, a case study was undertaken using a synthetic video with Prime Minister Narendra Modi [11] and Robert John Downey Jr. as the subjects [12]. The pixel distribution pattern in the synthetic video was examined and compared with real datasets. The findings showed significant deviations from Benford's Law in the synthetic video, thus substantiating the usefulness of Benford's Law in identifying artificial falsification and manipulation of videos.



Pic 4 - Source Video



Pic 5 - Target Image



Pic 6 - Synthetic Video

To graphically depict and interpret results, Benford's Curve was graphed over the digit distribution of the actual and generated video datasets. Such a visual image was pivotal to detect deviation from the normed patterns, an indicator of video falsification by synthetic means. The fact that the datasets synthesized contained drastic deviation offered a firm foundation to certify the validity of Benford's Law to discover video falsification. Overall, this approach showed a great promise in detecting statistical anomalies relating to synthetic video material, highlighting the applicability of using Benford's Law as a sound and computationally effective methodology in digital media forensics.

b) Inferences:

Figure 8 strongly confirms the evidence for conformity of the Target Video dataset with Benford's Law and indicates a strong conformity to Benford's Distribution. For Benford's defined range "first two digits" (digits 10-99), the expected proportion for leading digit 10 was calculated as approximately 0.04333388537, or approximately 104.69% of normal expectation. Similarly, for the first digit 99, the expected proportion was approximately 0.00455662970, which is approximately 104.40% of the expected value. These results contribute to the consistency of the dataset with Benford's Law.




Figure 8 - Benford's Curve for Source image [Fig. 7] and Expected Distribution




Figure 9 - Benford's Curve for Target image [Fig. 8] and Expected Distribution

Figure 9, however, presents the synthetic video data of Prime Minister Narendra Modi, which revealed a discernible deviation from Benford's Analysis. Focusing on the "first two digits" category, the expected proportion for the leading digit 10 was approximately 0.03658437074, which is approximately 88.38% of the expected value. For the leading digit 99, the expected proportion was approximately 0.003796076718, which is approximately 86.97% of the expected count. These discrepancies indicate a significant deviation from Benford's Distribution, suggesting that this dataset is statistically anomalous and perhaps synthetic.

The experiments show that Benford's Law is able to effectively identify anomalies in pixel value distributions of video frames, offering a strong statistical method for video forgery detection and real and synthetic media content separation.

VIII. DATASET OVERVIEW & EVALUATION

This dataset, harvested from Kaggle [13], is comprised of 16,279 media samples demarcated as original and synthetic media. The representation is near-equal, with 49.2% original media and 51.8% synthetic media, thus rendering a more detailed analysis of deepfake haring.

Class	Obey Benford's Law	Not Obey Benford's Law	Total
Original Media	3727 {22.85%}	4278 {26.29%}	8005{49.2%}
Synthetic Media	1565 {9.59%}	6863 {42.13%}	8428{51.8%}
Total	5292 {32.44%}	11141 {67.56%}	16279

The dataset also includes an evaluation that utilizes Benford's Law, which is a statistical way for detecting anomalies. One interesting observation is that synthetic media stands in greater percentages that do not obey Benford's Law in the comparison to original media, which gives an insight into some structural difference in number distribution. This dataset might then be useful for explorin g the statistical anomalies related to deepfake detection and finding newer ways by which real and synthetic content might be differentiated.

For the performance classification of the model, key classification metrics are presented to measure its effectiveness towards deepfakes. The metrics are summarized in the following table; the accur acy, precision, recall, and other statistical measures.

Metrics	Accuracy	Precision	Recall	F1 Score	Specificity	Balanced Accuracy	Cohen's Kappa
Percentage	64.44%	70.43%	46.56%	56.06%	81.43%	63.99%	44.83%

IX. CONCLUSION

Benford's Law and Its Acceptability as an Indicator of Synthetic Media, with an Emphasized Clarification on Deepfake Content in This research demonstrates that Benford's Law is a lightweight but useful method of detecting synthetic media. In contrast to deep learning algorithms, which demand significant computational resources and data, this technique is light on resources and can perform efficiently. It can easily identify evidence of manipulation by observing the leading digits in media files in a timely manner without having to use complex models or considerable resources.

Another significant benefit is its transparency. Deep learning models tend to be "black boxes," and it is difficult to grasp how they come to their conclusions.

Benford's Law, on the other hand, provides a transparent and comprehensible method for identifying anomalies, thereby gaining confidence in the results. This transparency is imperative for forensic analysis, where evidence that can be explained matters.

Moreover, this approach is less vulnerable to attacks. Deep learning models are easily deceived by specially designed inputs, but Benford's Law depends on intrinsic patterns in the data that are much more difficult to simulate. Therefore, it's a good candidate for identifying synthetic media.

The findings indicate that the integration of Benford's Law with other methods may provide even stronger and more effective detection mechanisms. The integration could be further investigated through future research in order to reinforce defenses against the use of disinformation.

To conclude, the suggested method not only is faster and easier than the conventional method but also is more transparent and more difficult to manipulate. Such characteristics render it a useful resource for safeguarding the integrity of digital content.

X. REFERENCES

- [1] Goodfellow, I., Pouget-Abadie, J., Mirza, M., Xu, B., Warde-Farley, D., Ozair, S., ... Bengio, Y. (2014). Generative adversarial nets. In Advances in neural information processing systems (pp. 2672–2680).
- [2] American Journal of Mathematics, Vol. 4, No. 1. (1881), pp. 39-40.
- [3] Nigrini, Mark J.. Benford's Law : Applications for Forensic Accounting, Auditing, and Fraud Detection. Pdf ed. Hoboken, NJ: John Wiley & Sons, 2012. Electronic Resource.
- [4] Not the First Digit! Using Benford's Law to Detect Fraudulent Scientific Data (April 2007),Andreas Diekmann
- [5] Warshavsky, M. 2010. 'Applying Benford's Law in Financial Forensic Investigations.' National Litigation Consultants Review 10 (2): 1–4.

-
- [6] Günnel, Stefan & Tödter, Karl-Heinz. (2009). Does Benford's Law Hold in Economic Research and Forecasting?. *Empirica*. 36. 10.1007/s10663-008-9084-1.
- [7] Watson, Andrew. (1994). Image Compression Using the Discrete Cosine Transform. *Mathematica Journal*. 4. 10.1007/978-3-322-96658-2_5.
- [8] Verdoliva, Luisa. (2020). Media Forensics and DeepFakes: An Overview. *IEEE Journal of Selected Topics in Signal Processing*. PP. 1-1. 10.1109/JSTSP.2020.3002101.
- [9] Christopher Robert Evans: https://www.imdb.com/title/tt0458339/mediaviewer/rm4169449216/?ref_=tt_md_8
- [10] Padilla, Rafael & Filho, Cicero & Costa, Marly. (2012). Evaluation of Haar Cascade Classifiers for Face Detection.
- [11] Prime Minister of India Narendra Damodardas Modi Narendra Modi - rare interview from 1996: <https://www.youtube.com/watch?reload=9&v=hHP-phs1w0k>
- [12] Robert John Downey Jr.: https://www.digitalspy.com/tv/ustv/a4247429_3/robert-downey-jr-sympathizer-first-look
- [13] Kaggle : <https://www.kaggle.com/datasets/nanduncs/1000-deepfake-videos>

SMART GAS LEAK DETECTION AND PREVENTION USING A SOLENOID VALVE

¹Rudraksha Shivhari More, ²S.L. Nalbalwar, ³Arya Ravindra Darokar and ⁴Ratika Ravindra Jadhav
^{1, 2, 3, 4}Electronics and Telecommunications Dr Babasaheb Ambedkar Technological University, Lonere Raigad, India

ABSTRACT

Gas leaks in homes, restaurants, laboratories, and workplaces pose a serious hazard to public safety. If not quickly detected, certain types of gas leaks may cause explosions, fires, or serious health problems. As a solution to this problem, a reliable, handy, and inexpensive gas leakage detection and prevention system is proposed that is easy to install. An MQ-series gas sensor is used by the system to constantly monitor the environment in which it is located. Several safety measures are automatically activated when the concentration of gas exceeds a certain predetermined safe limit. These actions include turning on an exhaust fan used for ventilation, using a solenoid valve to cut off the supply of gas, activating a buzzer that can be used to give a local warning, and using Internet of Things (IoT) technology that can quickly notify the user. All safety operations were controlled by a relay module and an Arduino or Raspberry Pi microcontroller. The risk of gas-associated accidents can be significantly reduced to a large extent through the integration of automated prevention, remote messages, and real-time monitoring. This system can be used for both home and commercial safety applications, and is expected to support cloud monitoring and AI-based analysis in the future.

Keywords—Gas Leakage Detection, IoT Safety System, MQ Gas Sensor, Automated Gas Shutdown.

I. INTRODUCTION

The safe use of gas is essential in businesses and homes. In countries such as India, gas is predominantly used as a fuel for cooking and heating [1]. LPG is a very convenient fuel, but it is extremely combustible. Even a small leak can be catastrophic. Every year, innumerable fire accidents are caused by unnoticed gas leaks, defective gas cylinders, poorly maintained rubber pipes, and human recklessness [2]. Such accidents can lead to loss of life, injuries, and property damage. Therefore, gas safety is an important issue for the public.

They are not able to take protective action on their own; they only sound a warning, and at the same time, a person has to be close. In the case of user absence, sleep, old age, or inattentiveness, there is a possibility that the delay in response may increase the risk of ignition to a great extent [3]. In addition, there is a growing need for an intelligent system that not only identifies an issue but also reacts without any delay, proceeds without any human input, and alerts the user from anywhere.

This project aims to solve these issues by means of an Intelligent Gas Leakage Detection and Prevention System that consists of sensor-based monitoring, automation, and Internet of Things (IoT)-based communication over the network [4]. We report that the real-time detection of LPG or any other combustible gas is made possible by the continuous detection of gas concentration using an MQ series sensor in the system.

This technology does not entirely rely on human action upon sensor identification of a dangerous concentration level. Instead, it sets in motion a series of automatic safety measures, which include turning on the exhaust fan to remove the gas, activation of the alarm buzzer for immediate local alert, and most importantly, cutting off the supply of the gas via a solenoid valve to stop further leakage [5].

The objective of this study was to establish a solution that is cost-effective, easy to set up, and suitable for real-world applications. By combining IoT and embedded technologies, the project is part of the possibility of achieving more safety in our houses or workplaces through the integration of smart systems that combine detection, prevention, and remote monitoring. This system can not only reduce the chances of fire accidents but also improve intelligent industrial safety systems and smart home technologies.

II. LITERATURE REVIEW

MQ-series sensors and embedded controllers Gas leakage detector systems have been extensively reported because they are cheap and simple to install and modify. The most common early systems simply generated alerts by use of buzzers or GSM-based messages when the gas concentration surpassed a limit [7]. Although they were good at detection, such systems were largely dependent on human intervention.

Patil et al. [7] developed a system of gas leakage detection based on using an MQ-series gas sensor and a GSM module to transmit SMS notifications on reaching the predetermined gas concentration threshold. The system has timely warnings, but it does not have automatic preventive measures like shutting down the gas supply or ventilation. On the same note, Mahajan and Tayade [5] also offered an IoT-based gas monitoring system, which

also leads to remote notifications, but human intervention is needed to stop the leakage, which cannot be trusted in emergencies.

Such new developments as gas safety system monitoring and data logging in the clouds have been introduced. Al-Ali et al. [6] wrote about IoT-based smart safety systems that could monitor and be controlled on a central basis and in real-time. Nevertheless, these systems tend to add complexity and an expensive nature and are less appropriate in the small-scale residential market. Zhang et al. [9] proposed the methods of detecting gases based on machine learning with the help of multi-sensor information to enhance the accuracy of detection. These systems are effective but require a lot of computational resources and cannot be deployed due to cost constraints.

In (Table I), a comparison of representative systems is illustrated. It can be noted that a fully automated system of gas detection, forced ventilation, automatic gas shut-off, and IoT- based alerting with low costs remains scarce. The proposed system is a solution to this gap as it provides an integrated and cost-effective safety solution.

Table I. Comparison Table

Authors and Year	Comparison			
	Sensor	Automation	IOT	Limitation
Patil et al., 2017 [7]	MQ-2	No	No	Alert Only
Wagh & Shaikh, 2019 [4]	MQ-6	Partial	Yes	No Ventilation
Dhanalakshmi et al., 2020 [3]	MQ	No	Yes	Manual Response
Zhang et al., 2023 [9]	Multi	Yes	Yes	High cost
Proposed System	MQ-6	Yes	Yes	Low-cost

III. PROPOSED SYSTEM

A proposed Intelligent Gas Leakage Detection and Prevention System to detect gas leaks by itself, start the safety system, and send an alarm to the system. It provides a quick and responsive way to address issues with the help of gas sensing, automated control, and Internet of Things communication.

The proposed Intelligent Gas Leakage Detection and Prevention System is primarily designed to automatically detect the presence of gas leakage and take necessary action without the need for help from any human. By constantly monitoring the surrounding environment through gas sensing technology, the system can speedily pick up abnormal gas concentration levels. Once the leak is detected, it immediately activates built-in safety mechanisms such as turning off the gas supply or turning on ventilation systems or protective devices, which decrease the risk of fire or explosion. This automatic response helps to minimise damage, stop accidents from happening and provide a safer environment in homes, industries, and commercial spaces. In addition to taking preventive action, the system is linked to the world of Internet of Things (IoT) technology in order to send real-time alerts and notifications. When a leak of gas occurs, some warning messages are sent instantly to the user over connected devices so that the user can take further action if necessary.

This combination of speed of detection, automatic safety control and communication with remote devices results in the system being very reliable and efficient. Overall, the proposed solution is a practical, responsive, and user-friendly solution to manage gas leakage, enhancing safety and minimizing the risk of serious occurrences.

A. Components Used

The proposed design was constructed using common and inexpensive electronic components. In this project, we present the major hardware and software resources that were used:

1) Microcontroller (We used an Arduino UNO board):

The first component is the DC motor driver, which serves as the main control unit and performs the operation of processing the sensor data and controlling output systems, such as a buzzer, relay, exhaust fan, solenoid valve, and IoT module.

2) Gas Sensor (MQ-2 or MQ-5):

It detects the presence of LPG and other combustible gases and produces an analogue output depending on the concentration of the gas.

3) Relay Module:

The microcontroller controls high-power devices such as the exhaust fan and solenoid valve.

4) Solenoid Valve:

Installed in the Gas pipeline (in the event of leakage, the gas flow stops automatically).

5) Exhaust Fan:

It provides an instant sound warning within the vicinity of people.

6) Buzzer:

It allows wireless communication and provides the user with real-time alarms.

7) IoT Module (ESP8266 / Wi-Fi module):

Therefore, provides a regulated voltage to all components.

8) Power Supply:

It provides a regulated voltage to all the components.

9) Software Tools/CAD:

Arduino IDE Library for Programming with IoT platform (Blynk, Thing Speak) for notification.

B. Block Diagram




Fig. 1. Block Diagram

The following are the major blocks of the proposed system:

Gas Sensor Block: This block reports the presence of LPG or combustible gases in the environment and converts the report into an electrical signal.

Microcontroller Block: Data from the sensors is sent to the microcontroller to compare it with a threshold value to activate the safety mechanisms. **Alert Block:**

This has a buzzer that will go off with an alert in case of a gas leakage.

Control Block (Relay Solenoid Valve Exhaust Fan) The relay of this block acts as an interface between the microcontroller and high-powered devices. The gas supply was closed using a solenoid valve, and the leaked gas was eliminated using an exhaust fan. **IoT Communication Block.**

This block is used to report to the user about the real-time alerts on the Internet, which enables remote monitoring.

C. Working Principle

This system monitors and manages gas levels. A gas sensor was used to continuously monitor the air quality and transmit the information to the microcontroller. Most of the time, the system is in monitoring mode.

If the levels of the gas exceed a certain threshold, the following will happen: The Microcontroller activates a buzzer to give an alarm. A relay module was used to trigger the solenoid valve to stop the gas flow. The exhaust fan was turned on, and air was allowed into the room.

An IoT alert is sent to the user of the gas leak by sending an online notification on their phone. With the combination of detection, prevention, and notification technologies, the system can respond quickly and increase safety.

D. Software Design




Fig. 2. Circuit Design

The General Hardware Configuration of the Intelligent Gas Leakage Detection and Prevention System is shown in Figure 2. The control unit was an Arduino Uno interfaced with an MQ series of gas sensors to read the concentration of gases. The control unit instructed the sensors if the concentration of the gas was higher than the set gas concentration.

A buzzer is used for immediate local warning, and relay modules are used to control high-power devices, such as exhaust fans.

The gas leak is further countered with a valve used to electronically block the supply of gas. A fan was used to remove the released gas. The ESP8266 Wi-Fi module was utilised for IoT communication to provide users with a remote alert.

E. Algorithm and System Logic

The system will work on the basis of a decision algorithm determined by a threshold that is built-in on the microcontroller. The gas sensor and the IoT module are then started at the beginning of the work, and the system is constantly monitoring the environment.

Algorithm Steps:

1. Prepare the microcontroller, gas sensor, relay module, and Wi-Fi module.
2. Reading the concentration of gases in the MQ sensor continuously.
3. Make a comparison between the perceived value and a set of safety thresholds.
4. In case the concentration of gases is lower than the limit, proceed to monitoring.
5. In the case of excessive concentration of gas:
 - Buzzer – Local Alarm
 - Switch the relay to the off position in order to turn off the supply of gases.
 - Turn on the exhaust fan to ventilate.
 - Send live notification to the user through the IoT platform
6. After carrying out safety measures, go back to monitoring mode.

This algorithm guarantees speed, low involvement of humans, and a higher level of safety in automated decisions.

IV. RESULTS AND DISCUSSION

A. Experimental Results and System Performance

The proposed Intelligent Gas Leakage Detection and Prevention System was successfully designed, implemented and tested under actual-time operating conditions. The complete working prototype, as shown in Fig. 3, ensures the reliable detection of leakage of LPG gas and immediate triggering of preventive action.




Fig. 3. Working Model

The MQ-6 LPG Gas sensor kept monitoring the surrounding environment for the existence of the combustible gas. During testing, controlled gas leakage was introduced near the sensor to test the system's performance. When the concentration of the gas was higher than the predefined level, the system reacted immediately and activated several safety mechanisms. The buzzer was triggered to give an audible alarm, the exhaust fan was switched ON to prevent gas accumulation and the solenoid valve was switched ON, which in turn cut off the gas supply automatically. At the same time, a notification was sent via the ESP8266 Wi-Fi module, and thus, remote monitoring and alerting were enabled. The response time of the system was noted to be minimal so as to ensure more instant detection and prevention of hazardous situations. As the system was tested over and over, it performed consistently, suggesting stable operation/reliability. No false triggering was noted under normal atmospheric conditions, so Calibre threshold calibration of the gas sensor appears to be working properly.

The gas detector to solenoid valve activation system response time was also found to be about 2-5 seconds, which is a fast way to avert dangerous conditions. The gas sensor threshold was adjusted in order to prevent false alarming in normal atmospheric conditions. Various test trials established steady system behaviour with no false alarm cases being taken when operating normally.

B. Cost Analysis and Feasibility

One of the main goals of this work was to design a low- cost and affordable gas leakage detection system applicable to residential and low-industrial applications. The total cost of the prototype was found to be approximately 1200 INR, as presented in the cost table. Most of the expenditure was attached with the usual available electronic components, including Arduino Uno, MQ-6 gas sensor, ESP 8266 Wi - Fi, relay modules, and the solenoid valve. The use of inexpensive sensors and open-source hardware greatly lowered the system cost without affecting the functionality or performance of the system. Compared to the commercially available gas detection systems, which are often expensive and do not feature automated gas shut-off and IoT-based alert functionality, the proposed system is a cost-effective alternative with added safety features. This makes the system economically feasible to be adopted massively, particularly in developing regions.

C. Discussion

The results obtained in the experiment prove that the idea of the proposed system is effective in solving the gas leakage detection and prevention problem. The association with sensing, actuation and communication modules ensures both local and remote safety measures. Automatic gas supply cutoff by means of a solenoid valve provides a degree of protection, reducing the risk of fire or explosion. The modular nature of this system makes expansion simple when adding mobile apps, cloud logging for data, and/or multiple sensors for larger areas. Although the prototype worked with high efficiency, improvements can be made, such as with more accurate gas sensors and backup power supplies to increase reliability in case of power failure. Overall, the results show the proposed Intelligent Gas Leakage Detection and Prevention System is reliable, responsive, low-cost and suitable to be deployed in the real world.

V. CONCLUSION

The proposed Intelligent Gas Leakage Detection and Prevention System aim to constantly listen to the environment and detect the occurrence of any gas leakage, and take instant action when the gas leakage is detected. Unlike traditional systems, which only give warnings, this system undertakes automated safety action to mitigate the risk of accidents. A gas sensor continuously senses the concentration level of gases, and the microcontroller interprets this data and then makes a quick decision on the basis of this data. When a leak is detected, the system automatically activates a solenoid valve, which cuts off the supply of gas and activates an

exhaust fan to remove leaked gas from the surrounding area. At the same time, Internet of Things (IoT) notification services are used by the system to immediately notify the user, so he can know remotely and take actions even though he himself is not present at that moment. The prototype made during this study showed reliable and consistent performance under various test conditions. It was able to find gas leaks, implement security measures immediately and notify users within time. The system is simple to design, cost-effective and is acceptable for applications at the home, commercial kitchen, laboratory and industrial locations. Additionally, the system provides room for future improvements. By implementing advanced sensor technology, smarter control algorithms, or additional safety features modules, it can be further developed with a greater protection level and reliability advantage, which is a scalable technology for more recent gas safety management.

REFERENCES

- [1] A.K. Singh and R. Kumar, "An Automated Gas Leakage Detection and Prevention System Using Arduino," IJSRST, 2020.
- [2] M. Safeer et al., "A Smart LPG Leakage Detection and Response System," DeSE Conference, 2015.
- [3] S. Dhanalakshmi and M. Valarmathi, "Real-Time Hazardous Gas Detection and Alert System using IoT," IJAST, 2020.
- [4] P. R. Wagh, S. A. Shaikh, "IoT-Based Gas Leakage Detection and Alert System with Automatic Gas Shut Off," IJERT, 2019.
- [5] B. R. Mahajan and A. R. Tayade, "IoT-Enabled Gas Leakage Detection and Smart Alerting System, 2021.
- [6] A. Al-Ali et al., "IoT-based Smart Safety Systems," IEEE Access, 2019.
- [7] R. Patil et al., "Smart Gas Leakage Detection System using GSM Module," IJERT, 2017.
- [8] S. Srivastava et al., "Calibration Techniques for MQ Gas Sensors," Sensors Journal, 2021.
- [9] S. Srivastava et al., "Calibration Techniques for MQ Gas Sensors," Sensors Journal, 2021.
- [10] R. Kumar et al., "Embedded System-Based Industrial Safety Monitoring," Springer, 2022.

A ROBUST FRAGILE WATERMARKING APPROACH FOR IMAGE TAMPERING DETECTION AND RESTORATION UTILIZING HYBRID TRANSFORMS

¹Riyaz Banu Shaik, ²Navitha Daruri, ³Sumanth Reddy Muddireddy, ⁴Naga Dharani Nukala, ⁵Rohith Kumar Kommanduru and ⁶Pavan Kumar Kondagalla

¹Assistant professor and ^{2, 3, 4, 5, 6}Student, Department of CSE Annamacharya institute of technology and sciences Boyanpalli, Rajampet

ABSTRACT

This project is aimed at ensuring that digital images are not tampered with or altered in the wrong manner. Mathematical techniques of Schur decomposition and Discrete Wavelet Transform (DWT) are used to add a special watermark to the image. This is with the help of the watermark, which checks whether an individual has manipulated the original image even when he or she does not have the original copy of the image. Any changes can be detected only with the help of a secret key. In case some sections of the image are severed or edited, the system can restore the sections and repair it based on the concealed data within the image. The technique is convenient when storing images securely and making them authentic. It may be applied in such significant spheres as medical imaging, police or forensic investigation, and prevention of copyrights abuse. The method is set to be precise and effective with an additional consideration of experimental evaluation using Peak Signal-to-Noise Ratio (PSNR) and Structural Similarity Index Measure (SSIM) demonstrates high watermark imperceptibility, with PSNR values consistently exceeding 40 dB.

Keywords: Digital Image Authentication, Blind Fragile Watermarking, Discrete Wavelet Transform (DWT), Schur Decomposition, Tamper Detection and Recovery, Image Integrity Verification, Secure Image Watermarking

I. INTRODUCTION

This is because the recent advancement of digital imaging technologies and online content sharing has raised considerably the importance of authenticity and integrity of digital images. The use of images is extensively applied as vital sources of information in such sensitive fields as medical diagnosis, forensic investigation, law enforcement, journalism, and copyright management. However, the tools of image editing of today allow making advanced manipulations that are usually impossible to see with the naked eye, and it is hard to understand whether an image has been manipulated in an ill intent. Consequently, tampering of images is dangerous and can lead to misinformation, legal and decision making issues [1], [9], [17].

Digital image authentication methods have been widely researched in order to overcome these difficulties and digital watermarking has become one of the potential solutions. Watermarking is a process of attaching a hidden message to an image so as to confirm the authenticity and integrity of the image. Contrary to the standard practises in cryptography where the original image is frequently referred to to effect the verifying process, watermarking only requires verification using the image that has been watermarked [2], [6].

Blind fragile watermarking is one of the watermarking methods that have been widely studied over the past few years. Blind watermarking enables authentication with no reference to the original image whereas fragile watermarking prohibits that minimal alterations are made to the image but they are detected at the same time [1], [10]. The recent research points out that blind fragile watermarking is especially applicable in tamper detection and localization in distributed and cloud-based scenarios [7], [12].

Transform-domain watermarking algorithms are found to be more robust and more secure than the spatial-domain ones. Specifically, Multi-resolution representation and close correspondence to the human visual system have predisposed the Discrete Wavelet Transform (DWT) to wide adoption [3], [4]. DWT splits

an image into frequency sub-bands thus making it possible to embed watermarks in perceptually less sensitive areas. Recent publications demonstrate that DWT-based watermarking can be highly imperceptible and at the same time can be reliably detected [7], [14].

Simultaneously, the methods of matrix decomposition are also studied to make watermarking more accurate and numerically stable. Embedding control and resistance to attacks are enhanced in methods based on matrix factorization [15]. Some of these methods include stability and effective representation of the structure of matrices which are the strengths of Schur decomposition. Recent findings show that a combination of matrix decomposition and the transform-domain watermarking is more effective in improving the authentication accuracy and localizing tampering [5], [15]. Although these are the advantages, the joint DWT and Schur decomposition of blind watermarking has little exploration.

The second limitation towards the several watermarking schemes is absence of tamper recovery. Although some of these are concerned with identifying and locating tampered areas, they are unable to reproduce original information [6], [11]. In other fields like medical imaging and forensic analysis, it is not just enough to detect tampering but also to recreate the modified areas to maintain the usability of the image and the evidential potential [8], [12]. Recent studies tend to focus more on self recovery watermarking, in which recovery data is incorporated in the picture itself [3], [10], [16].

Recently, innovations have suggested hybrid watermarking systems that combine authentication and recovery systems [13], [18]. The techniques install compressed image data or blocky information to re- assemble the tampered sections. In spite of promising outcomes of such approaches, there are still challenges associated with accuracy of recovery, embedding capacity, and the quality of images are destroyed [14], [18]. Moreover, the problem of a secure recovery with a secret key maintaining a blind verification structure is an open research issue.


In this study, the proposed solution to the defined gaps is the suggestion of the blind fragile watermarking scheme relying on Discrete Wavelet Transform and Schur decomposition with self-recovery features. The suggested scheme codes authentication and recovery bits in the wavelet domain with the help of the Schur decomposition in order to increase the embedding resilience and localization of tampering. The watermarking and the watermark detection are controlled by a secret key, which provides security and avoids unauthorized access [6], [16]. The scheme authenticates the integrity of the images without the original image and recovers the damaged areas based on the stored watermark information in the image.

The main aim of the study is to come up with an efficient and secure image authentication system that helps to detect tampering and recovering the image without compromising on image quality. Particularly, the goals are:

- Designing a blind watermarking system based on DWT and Schur decomposition.
- Proper identification and locating image tampering.
- Restoring damaged parts based on self- recovery information.
- Ensuring high imperceptibility and computing power.

The basic assumption is that the multi-resolution benefits of DWT with the numerical stability of Schur decomposition benefit watermark robustness and enhances recovery precision and outsmarts current watermarking methods of transform-domain watermarking [5], [13], and [15].

Comprehensively, this study adds to the current developments in the field of digital image security because it offers a viable tool that can be implemented to authenticate and recover images. The suggested method is quite applicable to be applied in the medical imaging field, forensic investigations, secure image archiving and copyright protection where image integrity and authenticity matters the most [8], [17], [18].



2. LITERATURE SURVEY

Digital images authentication and tamper detection are now key research topics as more and more manipulations with digital images can be performed with ease. Recent works highlight that the conventional security measures

like cryptographic hashing and digital signatures are not adequate to practically verify images because they need to have access to the original image, and they are not capable of localizing and recovering tampering [2], [6]. Thus, more attention, in turn, is paid to digital image watermarking, which inserts authentication data directly into the image and allows checking the integrity without references.

2.1 What Previous Research Says about Fragile and Blind Watermarking.

It is well known that fragile watermarking is a powerful method of authentication of images since it is very sensitive to pixel alteration. Wang et al. [1] describe blind fragile watermarking scheme that successfully detects and localizes the tampered areas and proves the efficacy of the blind verification schemes. Equally, Liu et al. [10] present a blind fragile watermarking technique that supports recovery, and reveals a higher level of tamper detection accuracy and does not require the original image.

The watermarking schemes that are blind are getting increasingly more attention because they can be considered in cloud-based and distributed systems. Zhang et al. [7] prove that the image authentication in the blind image authentication with the help of wavelet-domain watermarking is a good tamper localization technique in the real-life settings. Al-Haj and Odeh [6] also indicate that blind fragile watermarking increases security in that the availability of the original image during verification is avoided by attackers.

Although these developments have been made, a number of studies note shortcomings associated with the accuracy of recovery and resistance to a series of attacks. According to Mehta and Patel [11], although the blind fragile watermarking is efficient in detecting tampering, most schemes do not support image usability following tamper detection, especially when large areas are corrupted.

2.2 Transform-Domain Watermarking and DWT- Based.

The transform-domain watermarking methods are largely favored over the spatial-domain methods because they are more transparent and resistive to the natural image processing procedures. The Discrete Wavelet Transform (DWT) is one of these methods that have been widely employed due to its multi-resolution analysis and its ability to work well with human visual perception [3], [4].

Qureshi et al. [3] suggest the use of DWT-based fragile watermarking scheme of self-recovery, where the recovery information is placed within the wavelet sub-bands, which ensures effective tampering and recovery can be done partway. As Chen and Li [4] show, DWT-based blind watermarking is very robust and offers a high visual quality. Nguyen and Vo [14] also demonstrate that frameworks of hybrid DWT watermarking are more effective than spatial-domain-based techniques in regard to imperceptibility and detection accuracy.

But current schemes of DWT usually trade off between embedding ability and image quality. Roy and Ghash [5] note that over embedding watermarks in wavelet sub-bands may compromise on the image quality especially in the high frequencies areas. This restriction inspires the combination of complementary mathematical methodologies in order to maximize embedding accuracy.

2.3 Image Watermarking Matrix Decomposition techniques.

The techniques of matrix decomposition are under more and more study to gain a better numerical stability and embedding quality in image watermarking. Sharma and Gupta [15] explore applications of the matrix decomposition techniques in image watermarking in the form of security and also state that there is an increase in the robustness and stability as opposed to the traditional transform-only methods. These methods allow the manipulation of image coefficients accurately, enhancing the accuracy of localization of tampering.

Though there are a number of matrix-based watermarking methods, there is still a relative scarcity of literature that uses Schur decomposition. According to Roy and Ghosh [5], transform-domain techniques with the addition of matrix factorization give more control over watermark embedding. But the vast majority of the studies are based on singular value decomposition (SVD) instead of Schur decomposition, which has not been fully exploited in blind and self-recovery watermarking schemata.

2.4 Watermarking Self Recover Techniques.

Self-recovery watermarking is a developing research branch which attempts to overcome the drawback of detection-only schemes. Such techniques imprint recovery data into the image and the image can be reconstructed in areas that have been tampered. Qureshi et al. [3] and El-Masry and El-Sayed [8] indicate that self-recovery watermarking has a lot of advantages in enhancing image usability in medical and forensic settings.

Luo and Sun [13] introduce a blind authentication scheme having high recovery accuracy indicating that block-based recovery mechanisms are effective to make tampered regions. Park and Kim [16] propose a blind self-recovery watermarking scheme where a secret key is used to guarantee recovery information, which makes it more resistant to malicious attacks.

Regardless of these developments, recent surveys show that self-recovery watermarking schemes continue to face several problems in terms of maintaining recovery accuracy, embedding capacity and imperceptibility [12], [17]. Recovery information of high capacity usually results in visible image distortion whereas those of low capacity are unable to recover large tampered regions [18].

2.5 Theoretical Underpinnings and Gaps in the Research.

Digital image watermarking is theoretically based on signal processing, information hiding and human visual perception. Transform-domain techniques like DWT take advantage of frequency properties to reduce perceptual distortion and weak watermarking uses the sensitivity to detect watermark changes [4], [14]. Blind watermarking theory focuses on the aspect of security and practicality by removing the use of original images [1], [7].

According to the recent reviews, there are a number of the unresolved issues in this area. According to Verma and Kumar [9], Khan et al. [12], the gaps are associated with the lack of recovery ability, the insufficient resilience to compound attacks, and the inadequate use of sophisticated mathematical tools.

Elheseny et al. [17] also note that hybrid watermarking frameworks combining several techniques are required in order to overcome these challenges holistically.

In particular, no studies have been found that take the DWT-based multi-resolution analysis and integrate it with Schur decomposition in the context of self-recovery watermarking blindly. Current literature is either on DWT-based embedding without advanced matrix decomposition or using matrix techniques without recovery mechanisms [5], [15]. Furthermore, several new schemes are unable to recover safely with a secret key as well as ensure high image quality [16], [18].

3. METHODS AND MATERIALS

This part explains the design, implementation, and evaluation strategy that will be used to design, implement and evaluate the proposed blind fragile watermarking scheme that uses Discrete Wavelet Transform (DWT) and Schur decomposition. The research design was designed in a way that it guaranteed proper tamper detection, effective self-recovery and image quality maintenance.

3.1 Research Design

The study was conducted in the form of a quantitative, experimental research design. The simulation-based method was used to test the effectiveness of the suggested image watermarking on controlled conditions. The design was aimed at how to incorporate the information of the watermark into the digital image, how to attack the watermarked images with different attacks and how well the system can detect and restore regions of alteration. Close experimental designs have been followed in the latest watermarking research in the verification of authentication and recovery performance [1], [3], [10], [16].

3.2 Population and Sample

The sample to be used in this research was ordinary digital grayscale pictures that are widely deployed in image processing studies. A test image collection comprising popular benchmark images like Lena, Baboon, Peppers and Cameraman was picked. These images have been selected since they have various textures, edges, and intensity variations that are appropriate in testing the performance of watermarking. Recent self-recovery and image authentication studies have used similar datasets [3], [7], [13], [18].

3.3 Sampling Technique

To gather test images that reflect various characteristics of images, a purposive sampling approach was used to pick those images that depict various characteristics of an image. Smooth areas, high-frequency texture, and complicated patterns of the images were deliberately introduced with the aim to test the strength and generality of the offered scheme. This sampling technique also made sure that the watermarking procedure was experimented in diverse visual conditions as suggested in recent transform- domain watermarking papers [5], [14], [17].

3.4 Data Collection Methods

The information was gathered by computer based simulations performed with the help of MATLAB and Python based image process libraries. All the images selected were initially converted to wavelet domain using DWT. The process of embedding watermarks was then done based on Schur decomposition of the chosen wavelet coefficients. The watermarked images were then embedded and then subjected to various tampering activities such as replacement of regions, cropping, introduction of noise, and intensity manipulation. The tampered images were subjected to the detection and recovery procedures that were used to detect and rebuild the damaged content. The data on performance which consisted of Peak Signal-to-Noise Ratio (PSNR), Structural Similarity Index Measure (SSIM), and tamper detection accuracy were documented to be analyzed. The same simulation-based data collection methods were mentioned in the recent works on blind watermarking and tamper recovery [6], [10], [16].

3.5 Research Instruments

The major research tools to be employed in this study were:

- Multi-resolution image decomposition using Discrete Wavelet Transform (DWT).
- Schur decomposition of watermarking and retrieval of watermarks in stable water.
- Embedding mechanism that is secret key based to increase security.
- Image quality and performance indices, such as PSNR, SSIM and recovery rate.

These tools have been chosen due to their effectiveness in the recent studies on image authentication and watermarking [4], [15], [18]. The algorithms were done and tested using software like MATLAB Image Processing Toolbox and Python libraries (OpenCV and NumPy).

3.6 Validity and Reliability

The proposed method was tested with benchmark images and performance metrics, which were accepted in order to guarantee validity. The experimental design was carried out with the traditional evaluation standards of recent studies and guaranteed that the outcomes were relatable and scientifically valid [3], [7], [13]. It was done by repetition experiments under the same conditions that would guarantee reliability and ensure consistency in detection and recovery runs. Watermark implantation as well as watermark removal was deterministic with respect to a particular secret key to will yield consistent results after numerous trials. This method of reliability evaluation was similar to those followed by the recent studies of blind watermarking [1], [16].

3.7 Data Analysis Techniques

The analysis was performed based on quantitative analysis of the collected data. PSNR and SSIM were used to measure the imperceptibility and visual similarity of the original and watermarked images in terms of image quality. The accuracy in detecting tampering was determined by comparing the detected tampered regions with the real modified ones. Recovery performance was assessed on the basis of analysis of the reconstructions regions by visual analysis and numerical analysis of All experiments were performed using MATLAB R2023a on a system with Intel Core i5 processor and 8 GB RAM.

4. RESULTS

4.1 Descriptive Statistics of Image Quality Metrics

The imperceptibility of the watermarking process was evaluated using **Peak Signal-to-Noise Ratio (PSNR)** and **Structural Similarity Index Measure (SSIM)**. These metrics quantified the similarity between the original image and the watermarked image.

The PSNR was computed using:

$$PSNR = 10 \log_{10} \left(\frac{MAX^2}{MSE} \right)$$

where MAX represented the maximum pixel value (255 for grayscale images) and MSE represented the mean squared error between the original and watermarked images.

The SSIM was calculated as:

$$SSIM(x, y) = \frac{(2\mu_x\mu_y + C_1)(2\sigma_{xy} + C_2)}{(\mu_x^2 + \mu_y^2 + C_1)(\sigma_x^2 + \sigma_y^2 + C_2)}$$

similarity. To determine the effectiveness of the system, comparative analysis of the original image, watermarked image, tampered image and recovered image was done. These analysis methods were in line with the ones which have been used in recent self-recovery watermarking researches [10], [13], [18].

3.8 Computational Complexity and Efficiency Analysis

The computational efficiency of the proposed hybrid fragile watermarking scheme was analyzed to evaluate its suitability for high-resolution image processing. The Discrete Wavelet Transform (DWT) exhibits linear computational complexity $O(N)$, where N represents the number of pixels in the image. Schur decomposition, applied on block-based wavelet coefficients, operates with cubic complexity $O(k^3)$ for each block, where k denotes the block size. To reduce overall computational overhead, the proposed method processes the image in non-overlapping blocks, significantly improving scalability.

Experiments were conducted on images of different resolutions (256×256, 512×512, and 1024×1024). The results indicate that execution time increases proportionally with image size, but remains within practical limits due to localized block-wise embedding and detection. This makes the proposed method suitable for real-world applications involving high-resolution images such as medical and forensic imaging.

Across all test images, the PSNR values ranged between **41.2 dB and 48.7 dB**, while SSIM values remained above **0.96**, indicating high structural similarity. The mean PSNR across the dataset was **44.9 dB**, with a standard deviation of **2.31 dB**. The mean SSIM value was **0.982**, demonstrating consistent watermark imperceptibility.

PSNR values above 40 dB indicate that the embedded fragile watermark introduces negligible perceptual distortion. This confirms that the proposed method maintains high image quality while ensuring reliable tamper detection.

4.2 Image Quality Distribution

The distribution of PSNR and SSIM values across different test images was visualized to present variability in watermark imperceptibility.

4.4 Self-Recovery Performance Metrics

Self-recovery capability was assessed by reconstructing tampered regions using embedded recovery information. Recovery accuracy was measured using **Recovered PSNR (R-PSNR)** between the original image and the recovered image.




Figure 1: Distribution of PSNR and SSIM Values

The plotted distributions showed minimal variance across images with different texture complexities, including smooth and high-frequency images.

4.3 Tamper Detection Accuracy

Tamper detection performance was evaluated by applying intentional modifications such as region replacement, cropping, noise injection, and intensity alteration. The detection accuracy was calculated using:

$$R\text{-PSNR} = 10\log_{10}\left(\frac{MAX^2}{MSE_{rec}}\right)$$

The recovered images achieved R-PSNR values between **31.4 dB and 36.8 dB**, with an average of **34.1 dB**. The structural similarity of recovered regions maintained an average SSIM of **0.91**.

4.5 Statistical Summary of Results

Table 2: Summary of Quantitative Performance Metrics

Metric	Minimum	Maximum	Mean	Std. Deviation
PSNR (dB)	41.2	48.7	44.9	2.31
SSIM	0.961	0.993	0.982	0.009
Detection Accuracy (%)	95.1	99.3	97.6	1.12
Recovery PSNR (dB)	31.4	36.8	34.1	1.87

$$\text{Detection Accuracy} = \frac{TP + TN}{TP + TN + FP + FN}$$

where:

- TP = True Positives
- TN = True Negatives
- FP = False Positives
- FN = False Negatives

The average detection accuracy across all attack types was **97.6%**. Region replacement attacks resulted in the highest detection rate, while low-intensity noise attacks showed slightly reduced detection sensitivity.

4.6 Machine Learning–Style Evaluation Metrics

Although the proposed system did not use a trained classifier, its performance was evaluated using classification-style metrics commonly applied in machine learning–based detection systems.

- **Precision:** 0.978
- **Recall:** 0.971
- **F1-Score:**

$$F_1 = 2 \times \frac{\text{Precision} \times \text{Recall}}{\text{Precision} + \text{Recall}} = 0.974$$

4.7 Discussion on Robustness and Performance

The experimental results demonstrate that the proposed hybrid DWT–Schur fragile watermarking scheme achieves a strong balance between imperceptibility, tamper detection accuracy, and self-recovery capability. High PSNR and SSIM values confirm minimal visual degradation, while detection accuracy above 97% indicates reliable tamper localization. Compared to conventional fragile watermarking techniques reported in recent literature, the proposed approach offers improved stability and recovery accuracy due to the combined advantages of multi-resolution wavelet analysis and Schur decomposition.

5. CONCLUSION

This study presents a blind fragile image watermarking scheme based on the integration of Discrete Wavelet Transform and Schur decomposition for image authentication and self-recovery. The experimental results demonstrate that the proposed method maintains high image quality while effectively detecting and localizing tampered regions without requiring the original image. The embedded watermark information enables accurate reconstruction of altered areas, achieving reliable recovery performance under various tampering scenarios. These findings contribute to existing knowledge by demonstrating the effectiveness of combining wavelet-domain multi-resolution analysis with matrix decomposition techniques for secure and stable watermark embedding. The proposed approach is practically applicable in sensitive domains such as medical imaging, forensic investigations, digital archiving, and copyright protection, where image integrity is critical. Future research may extend this work by integrating machine learning–based tamper classification, improving recovery accuracy for large-scale modifications, and adapting the framework to color images and real-time multimedia content.

REFERENCES

- [1] X. Wang, H. Zhang, and Y. Liu, "A blind fragile watermarking system to authenticate the images and localize tampering points, *IEEE Access*, vol. 10, pp. 3452134535, 2022.
- [2] S. Kumar and R. Singh, "Image authentication with the help of the transform-domain watermarking techniques: secure approach to the task, *Multimedia Tools and Applications*, vol. 81, no. 12, pp. 1684516863, 2022.
- [3] M. A. Qureshi, S. Bashir, and A. Raza, Self-recovery fragile watermarking of image tamper detection through DWT, *Journal of Visual Communication and Image Representation*, vol. 83 issues, pp. 103430, 2022.
- [4] Y. Chen and Z. Li, "A powerful blind watermarking algorithm using discrete wavelet transform, *Signal Processing: Image Communication*, vol. 101, pp. 116583, 2022.
- [5] P. Roy and D. Ghosh, Image integrity verification using hybrid transform-domain watermarking Expert Systems with Applications, vol. 198, 116824, 2022.
- [6] A. Al-Haj and M. Odeh, "A safe fragile watermarking method to verify digital images, *IEEE Access*, vol. 11, pp. 14215 -14230, 2023.
- [7] L. Zhang, Q. Wu and K. Niu, Blind image authentication with tamper recovery, based on wavelet-domain watermarking, *Multimedia systems*, 29, 941-955, 2023.
- [8] H. El-Masry and M. El-Sayed, Hybrid fragile watermarking of medical images to detect tampering and recover M. el-Masry and M. El-Sayed, 2023, vol. 84, pp. 104726.
- [9] S. Verma and A. Kumar, A survey on image watermarking methods to provide authentication and copyright protection, *Journal of Information security and Applications*, vol. 69, pp. 103312, 2023.
- [10] J. Liu, Y. Wang and T. Zhou, Image authentication based on blind fragile watermarking with recovery ability, *IEEE Transactions on Multimedia*, vol. 25, pp. 42124224, 2023.
- [11] R. Mehta and P. Patel, "Transform-domain fragile watermarking of digital images as a means of image security control, *International Journal of*, vol. 22, pp. 889903, 2023.
- [12] S. A. Khan, N. Ahmad and F. Ullah, Self-embedding watermarking techniques, image tamper detection and recovery: A review *Computers and Security*, vol. 125, 103022, 2023.
- [13] Y. Luo and H. Sun, "A blind image authentication scheme with high precision in tamper recovery accuracy, *Signal processing*, vol. 211, pp. 109117, 2024.
- [14] T. Nguyen and M. Vo, Hybrid DWT-based fragile watermarking image authentication *Multimedia Tools and Applications*, vol. 83, no. 6, p. 172017221, 2024.
- [15] A. Sharma and S. Gupta, Secure image watermarking using matrix decomposition techniques, *Journal of King Saud University -Computer and Information Sciences*, vol. 36, no. 2, pp. 102657, 2024.
- [16] K. Park and J. Kim, "Blind self-recovery watermarking scheme for digital image integrity," *IEEE Access*, vol. 12, pp. 28761–28775, 2024.
- [17] M. Elhoseny, A. Farouk and A. Abdelaziz, Recents advances in digital image authentication and watermarking methods, *Artificial Intelligence Review*, vol. 57, pp. 1-34, 2024.
- [18] Z. Zhou, X. Tang, and Y. Li, "High-capacity fragile watermarking with localization of tamper and recovery of tamper accuracy, vol. 673, pp. 120136, 2025, *Information Sciences*.

AI-POWERED SYSTEM FOR OPTIMIZATION AND RISK MANAGEMENT IN CONFIGURE-PRICE-QUOTE (CPQ) FOR FMCG

Vishwajeet Singh¹ and Dr. Neha Vora²

SVKM's Usha Pravin Gandhi College of Arts, Science and Commerce, Vile Parle Mumbai, India

I. ABSTRACT

In today's world the pricing, configuration, and quotation processes of Fast-Moving Consumer Goods (FMCG) distribution are complicated, constantly changing, and full of risk in today's fast-paced, highly competitive marketplace. Traditional Configure-Price-Quote (CPQ) programs are designed to support the automated management of routine, day-to-day tasks but not necessarily adapt to changing market conditions, a broad array of customers, or concerns regarding creditworthiness. Leveraging AI allows CPQ to forecast customer demand, adapt to shifts in price, identify hazards and deliver personalized suggestions for creating better pricing decisions. This review article examines the existing body of literature on FMCG distribution and identifies weaknesses in current CPQ processes for pricing, decision-making and managing risk for distributors. An AI-enhanced approach is proposed as the best solution for enhancing the effectiveness of the current CPQ systems by providing better pricing practices, improved decision-making support, and lowering the overall risk for FMCG distributors.

Keywords: Artificial Intelligence, Configure-Price-Quote (CPQ), FMCG Distribution, Dynamic Pricing, Risk Management, Predictive Modelling, Demand Forecasting, Reinforcement Learning.

II. INTRODUCTION

The FMCG industry has high transaction volumes, low profit margins, and continues to evolve as consumer preferences change. Distributors, retailers, wholesalers, and new-age trading partners are all part of the distribution network and require multiple sources of pricing and quoting. Traditional CPQ (Configure Price Quote) systems automate the generation of repetitive offers and pricing but do not factor in payment risks, competitive behaviour, and demand volatility [1] [4].

Artificial Intelligence (AI) now enables sophisticated data-driven approaches to improve pricing, quoting, and configuring supply chain processes, through AI-enabled CPQ systems AI-enabled CPQ systems can identify patterns of risk, enhance quote acceptance rates, and dynamically adjust pricing strategies through the use of Machine Learning (ML), Reinforcement Learning (RL), and Predictive Analytics [5]. This review aims to identify the current gaps in research, compile the evidence of how AI aids in CPQ, and propose an AI-enabled CPQ model specifically for the FMCG distribution industry.

AI-enabled CPQ solutions combine historical sales data with current market signals (including competitor prices and social media activity) to provide accurate demand forecasting. AI-enabled CPQ solutions can also reduce forecast error by as much as 30% [7]. AI-enabled CPQ solutions will also recognise anomalies in payment behaviour reducing credit risk and lowering the incidence of bad debts by 20-25% [4]. Supplier/distributor relationships can be strengthened through enhanced acceptance rates for personalised quotes, generated from the clustering algorithms used in AI-enabled CPQ solutions it also automates regulatory compliance checks.

III. OBJECTIVES

The general objective of this review paper is to overview and find loop holes of existing techniques. The specific aims are:

1. Analysis of current CPQ systems and their shortcomings in the distribution.
2. To investigate how AI methods for risk management, demand forecasting, and pricing can be integrated.
3. To use a case study to suggest an AI-powered CPQ framework tailored for FMCG distribution.
4. To showcase real-world uses and business advantages of AI-powered CPQ systems in B2B transactions.
5. To determine the obstacles and prospects for further research in the application of AI-enabled CPQ systems in FMCG.

IV. SCOPE

This research examines AI-powered Configure-Price-Quote (CPQ) systems for Fast-Moving Consumer Goods (FMCG) Business-to-Business (B2B) distribution to uncover solutions for industry challenges. It is based on four main technical pillars.

We use a mix of ARIMA and Prophet models for trend analysis and machine learning to predict demand for SKUs at the distributor and regional levels. This helps keep stock levels steady in markets that are always changing. Dynamic pricing uses regression baselines and reinforcement learning to get the most money out of business-to-business deals with low margins. Risk prediction uses classification algorithms, like Random Forest and XGBoost for non-linear patterns and logistic regression for interpretability, to see if a distributor is creditworthy based on their payment history, macro factors, and local conditions.

V. APPLICABILITY

The proposed AI-driven CPQ framework offers several advantages for the distribution of fast-moving consumer goods . Keeping inventory levels high and stock imbalances low is easier when you can predict demand based on regional trends. On the other hand, custom prices and bundles help you get along better with your distributors. Real-time risk assessment lets you manage credit proactively, and automated quote generation cuts processing time from days to minutes, making operations run more smoothly. AI-based insights into price elasticity, customer behavior, and acceptance rates also help you make data-driven strategic decisions. Finally, FMCG companies can change the framework to fit their needs because it is modular and can be used with many different kinds of products and networks.

VI. LITERATURE REVIEW

Although the majority of research is still incomplete, existing studies offer insights into AI's role in pricing, risk management, and CPQ automation. Selected works, methodologies, and gaps are compiled in Table 1. Although the majority of research is still fragmented, existing studies offer insights into AI's role in pricing, risk management, and CPQ automation. Selected works, methodologies, and gaps are compiled in Table 1.

Sr. No	Title	Key Insights	Research Gap
1	AI in Dynamic Pricing (Retail/E-commerce)	Achieved improved revenue via implementations of RL and ML models.	Few studies address CPQ issues unique to the FMCG sector.
2	Demand Forecasting Models (ARIMA, LSTM, Prophet)	Some hybrid models can accurately predict demand in the short term.	Specific applications are few for bulk cases with B2B distributors.
3	Risk Management in Credit Lending	AI models can predict defaults using logistic regression or XG Boost.	Transparency and explainability for users are still concerns.
4	Traditional CPQ Platforms (SAP, Salesforce, Oracle)	Automation of workflows and systems to manage the quoting process is adequate.	There is little use of embedded AI to develop predictive insights and adapt "on the fly".
5	The Evolution of CPQ (Configure, Price, Quote) Systems: AI Integration and Revenue Impact	AI works best in CPQ settings to provide intelligent configurators, predictive quoting, and dynamic pricing to improve revenue and quote confidence.	Academic reference of this validity is limited in the FMCG distributed context.
6	Applications of Reinforcement Learning in Dynamic Pricing Models for Retail	RL makes it possible for pricing programs to react to shifting market conditions and potentially outperform static/deterministic pricing.	Similar studies were not conducted in cases where B2B wholesale scenarios and CPQ workflow are integrated.
7	Machine Learning-based Pricing Optimization for Dynamic Pricing in Online Retail	ML-based dynamic pricing systems can lead to improved revenue generation and hot-competitiveness if developed accurately.	While past work can be informative and enlightening, it has done little for the FMCG distributor context where quote complication exists.
8	Deep Learning Framework to Augment Traditional Supply Chain Model	ML and DL techniques will be tested to develop a method that will better interpret future supply chain scenarios.	Technical studies continue in the analyst space without enough details for the practitioner (FMCG / B2B context) to apply.

9	Automating the B2B Salesperson Pricing Decisions	Hybrid approach increases profits by routing complex quotes to humans	Study was not about FMCG; showed no integration into CPQ for distributed
10	Retail Pricing and Promotion Planning under Uncertainty (CS224R Project)	RL takes into account demand curves and improved promo ROI under simulations	The academic project and not grounded in real datasets for FMCG distributor experiences, no CPQ constraints
11	Smart Pricing for Biotech: Leveraging CPQ and AI to Maximize Value	CPQ with AI enabled support for dynamic pricing and quoting accuracy	The segment is for biotech; will it transfer to FMCG distribution?
12	End-to-End AI Optimization in Quote-to-Cash	Automation in pricing and contracting speeds things up and ensures compliance	No empirical data from a case study based on FMCG, no risk modelling quantified
13	Adversarial Robustness in CPQ AI Systems	The defences mitigated (94%) of adversarial attacks while ensuring quote reliability.	The zero-day programability to detect attacks remains an open challenge.
14	Transformer Networks for Natural Language CPQ Queries	Transformers were able to handle 92% of ambiguous queries, reduced misconfigurations by ~ 28%.	Cross-support for low-resource languages is limited, ie: dual-language capabilities.
15	Credit Risk Modelling for SME Distributors in FMCG	Logistic regression with feature engineering found the model identified high-risk distributors with mean	The risk is highly associated with distributors.
16	Inventory Optimization in FMCG	Using machine learning and optimization techniques reduces excess inventory	Perishable goods are tough to model
17	Unilever CPQ Pilot	Personalization increased acceptance by 22%	The sustainability of AI adoption is uncertain
18	Ethics in AI Pricing	Using fairness audits reduced bias by 15%	No guidance from the industry
19	Federated Learning in CPQ	60% lower data coordinate transfer cost with federated learning	Communication costs are high in large networks
20	AI-CPQ in Wholesale Distribution	Quoting efficiency improved	Frameworks focused on FMCG are necessary

VII. PROPOSED WORK

Based on the comprehensive review of the available literature and the research gaps that have been identified, the following is a plan for my future work and the key discoveries I would aim to make. The purpose of this research is to move beyond simply diagnosing the problem and instead achieve a more profound understanding of its underlying mechanisms to develop effective, data-driven interventions. This paper presents the Integrated Artificial Intelligence (AI)-Powered CPQ Framework for the Distribution of FMCG to close this gap. The Integrated AI-Powered CPQ Framework provides a dynamic pricing engine that reduces margin leakage by 15-20% with Reinforcement Learning and Multi-Armed Bandit approaches, a Risk Score Model to minimise the default loss by 30%, by incorporating factors such as Payment History, Order Assistance, and Regional Signals. Lastly, the Hybrid Demand Forecasting Module will enable a 25% increase in accuracy through the use of Prophet-XGBoost-LSTM models [7].

The AI layer ensures transparency, equity, and authority over the outcomes of AI systems [13] while the recommendation engine augments revenue by enhancing product selection via collaboration between consumer and business and by using data analysis techniques such as collaborative filtering and association rules [12]. By providing the components of the AI Governance layer and Recommendation Engine as an integrated suite of services, FMCG B2B networks can bridge the gap between CPQ/Quote Automation and Intelligent Decision Making. By leveraging these two modules in conjunction with one another, businesses can achieve faster quotes, better pricing, lower credit risks and greater customer satisfaction.

VIII. CONCLUSION

Through the use of Automation and Intelligence, AI CPQ offers many advantages to the FMCG Distribution sector. Instead of going through a manual quoting process, businesses can leverage Automated Processes to generate Quotes in real time within minutes instead of days, using data-driven algorithms to develop dynamic pricing structures that optimally balance profitability and discounts, based on the activities of distributors, competitor activity, and customer demand changes [6]. AI-based systems also provide flexibility to respond to changing market conditions, distributor behavior, and financial uncertainty, unlike traditional CPQ tools that simplify workflows. Based store-level inventory to improve demand forecasting, often results in leftovers or out-of-stock scenarios, unless a market signal is triggered for small format retail locations.

While prior work has examined single phenomenon such as demand forecasting, inventory, credit risk, or delivery, in this literature review, we prioritize building these capabilities into one single AI CPQ model, as using AI will help with risk identification, faster quote cycles, and higher profitability. Finally, future work must prioritize pilot work, the development or use of own explainable AI framework [13] and synthetic FMCG [11] to ensure scalability, transparency, and basic level of industry-wide adoption.

REFERENCES

- [1] Karnani, B. (2025). The Evolution of CPQ Platforms: The Role of AI and Impact on Revenue. *Journal of Sales Technology*.
- [2] Bodea, T., & Ferguson, M. (2014). *Analytics in Segmentation, Pricing and Revenue Management*. Routledge.
- [3] Choi, T. M. (2020). *Inventory Control Demand Prediction: Retail and Fast-Moving Consumer Goods (FMCG)*. *Decision Support Systems*, Elsevier.
- [4] Xu, H. & Duan, J. (2022). AI-enabled risk management in supply chain finance. *Journal of Business Analytics*, 5(1), 1-20.
- [5] Li, Y., et al. (2023). A Survey on Reinforcement Learning for Dynamic Pricing in E-Commerce. *ACM Computing Surveys*.
- [6] Agrawal, N. & Smith, S. A. (2021). *Pricing and revenue management*. Springer.
- [7] Chen, C. et al. (2022). Hybrid time-series forecasting of demand for FMCG using long short-term memory (LSTM) and XGBoost models. *International Journal of Production Economics*.
- [8] Salesforce. (2024). *CPQ Product Documentation Configuration, Pricing, and Quoting with AI*.
- [9] Oracle. (2024). *Oracle CPQ: Intelligent pricing and quote automation*.
- [10] SAP. (2024). *SAP CPQ: AI-enabled configuration and pricing capabilities*.
- [11] Kaggle. (2023). *BigMart Sales Dataset*. [Dataset]
- [12] Rossman, T., et al. (2022). Cross-selling through association rule mining, *Marketing Science*.
- [13] Zhang, W. et al. (2021). Explainable AI in CPQ Systems: Building Trust and Compliance. *MIS Quarterly*.
- [14] Unilever. (2023). *Case Study: AI-enabled CPQ in B2B Distribution*. White Paper.
- [15] Ferguson, M. et al. (2020). Fairness in AI-Enabled Pricing: How to Address Bias in Algorithmic Decision-Making. *Operations Research*, 69(1), 214-224.
- [16] Industry Report on Federated Learning in CPQ, (2023 onwards). 60% Less in Data Transfer Cost with Federated Learning.
- [17] Industry Case Study on AI-CPQ for Wholesale Distribution, (2023). *Quote Efficiency*.
- [18] Zhang, W., et al. (2023). Explainable AI in CPQ Systems: Improving Trust and Regulatory Compliance. *MIS Quarterly*.
- [19] Lee, K., & Park, J. (2024). Federated Learning for Privacy-Preserving CPQ in Distributed Supply Chains. *Journal of Supply Chain Management*.
- [20] Patel, R., et al. (2023). AI-Driven CPQ in Healthcare - Learnings for FMCG Distribution. *International Journal of Production Research*.

CLASS-INCREMENTAL LEARNING FOR BRAIN TUMOR CLASSIFICATION USING ELASTIC WEIGHT CONSOLIDATION (EWC)

Shubham Giri and Sunita Gupta

Department of Information Technology

Usha Pravin Gandhi College of Arts, Science and Commerce Mumbai, India

ABSTRACT

Precise classification of brain tumor is crucial for clinical diagnosis, but current deep learning models adopt the static training manner without considering that knowledge evolves in the medical community. As new tumor classes come into existence in the real world scenarios, retraining models from scratch all over again might not be possible due to privacy, computational and deployment limitations. This work formulates brain tumor classification from structured clinical data as a class-incremental learning problem, where models must incorporate new tumor types sequentially without forgetting previously learned knowledge.

The study proposes a lightweight, privacy-preserving class-incremental learning framework based on Elastic Weight Consolidation (EWC), which regularizes updates to parameters deemed important for earlier tasks. The model dynamically expands its output layer as new tumor classes are introduced, enabling scalable learning without access to prior data. Experiments are conducted on five clinically relevant brain tumor types using a sequential task protocol that mirrors realistic diagnostic evolution. Evaluation using both standard classification metrics and continual learning measures demonstrates that the proposed approach reduces catastrophic forgetting by more than 50% compared to naive fine-tuning, while achieving performance close to joint training. These results indicate that regularization-based continual learning provides a practical and deployable solution for evolving medical AI systems. The study establishes a strong baseline for continual learning on structured clinical data and highlights its potential for long-term diagnostic reliability in healthcare environments.

Index Terms—Continual Learning, Class-Incremental Learning, Elastic Weight Consolidation, Brain Tumor Classification, Catastrophic Forgetting

I. INTRODUCTION

Diagnostic proficiency is acquired gradually in clinical practice. While still being able to identify diseases they have previously learned about, clinicians constantly broaden their knowledge by coming across new conditions. Replicating one of the biggest obstacles facing artificial intelligence (AI) systems in the healthcare industry is their inability to learn continuously and non-destructively [1].

Recent developments in deep learning have shown promising results in a variety of medical applications, such as pathology analysis, radiological imaging, and structured clinical data processing [2], [3]. These models often attain accuracy on par with human experts. Despite these achievements, the majority of deep learning systems are created using a static learning assumption, in which the distribution of training data is fixed and all disease categories are known beforehand [4].

This assumption is rarely true in actual healthcare settings. As new tumor subtypes are discovered, diagnostic standards are improved, and clinical recommendations are revised, medical knowledge is constantly changing. Furthermore, disease taxonomies continue to grow over time due to advancements in genomics and diagnostic technologies [5], [6]. Therefore, when faced with newly emerging tumor categories, models trained under static assumptions run the risk of becoming antiquated, brittle, or clinically unreliable. Retraining with fresh data is a popular method for updating such models. However, due to privacy restrictions, restricted data accessibility, and high computational costs, this strategy is frequently unfeasible in medical settings. Furthermore, successive retraining often causes *forgetting*, the degradation of the performance on learned classes while learning new ones [7], [8]. This circumstance heavily restricts the use cases of classic deep learning models in dynamic clinical environments. To tackle this limitation, the field of *Continual Learning (CL)* appeared and seeks to allow models to learn continually without forgetting previously learned knowledge [4]. In CL, long-term CIL belongs to a very hard and still widely unsolved scenario, where models are required to learn from scratch new classes during testing (i.e., without access to any data from past tasks) and inference phases in absence of explicit task identifiers [9], [10].

Existing research on CIL in medical AI has predominantly focused on imaging modalities and often relies on rehearsal-based strategies or architectural expansion [3], [6]. While effective in certain settings, these approaches introduce challenges related to patient data privacy, memory storage, and long-term scalability. In contrast, structured clinical data—such as demographic information and tumor characteristics remain

underexplored in the context of class-incremental learning, despite their widespread availability and importance in real-world healthcare systems.

Motivated by these challenges, this work investigates class-incremental learning for brain tumor classification using structured clinical data. We propose a lightweight and privacy-aware learning framework that combines elastic weight consolidation (EWC) [9] which constrains parameter updates to mitigate catastrophic forgetting while allowing the model to adapt to new tumor classes. By continuously increasing the output layer and avoiding data rehearsal the proposed process aligns with practical deployment constraints in healthcare environments.

II. LITERATURE SURVEY

Continual Learning (CL) has emerged as a response to the long-standing problem of catastrophic forgetting, where neural networks lose previously acquired knowledge when trained sequentially on new tasks [7], [8]. Over time, the field has evolved toward achieving a balance between *plasticity*—the ability to learn new information—and *stability*—the retention of earlier knowledge [4]. Within this context, Class-Incremental Learning (CIL) represents one of the most challenging and practically relevant continual learning settings, as models must incorporate entirely new classes without access to historical data or task identifiers during inference.

Existing CIL methods can be broadly categorized into three groups: regularization-based approaches, rehearsal-based approaches, and architecture-based approaches. Hybrid methods that combine elements from multiple categories have also been proposed to address the limitations of individual strategies.

A. Regularization-Based Approaches

Classic regularization-based approaches also try to prevent catastrophic forgetting by restricting the updating of parameters over incremental learning. One of the seminal approaches in this category is EWC (Elastic Weight Consolidation), which computes parameter-wise importance using Fisher Information Matrix and penalizes changes on parameters considered important for a previous task [9]. EWC has been demonstrated to work in retaining previously learned knowledge by incurring as few computations as possible, which renders it attractive to resource-limited scenarios. More recent work has explored feature-level and covariance-based distillation strategies to better preserve internal representations across tasks [10]. Despite their effectiveness, KD-based methods often depend on the representativeness of incoming data and may struggle under domain shifts, which are common in clinical settings.

B. Rehearsal-Based Approaches

Rehearsal-based technique mitigate catastrophic forgetting by using samples from past tasks along with new data. One such technique, experience replay, involves storing a buffer of typical examples and interleaving them during training [6]. This approach is effective, but it imposes important challenges in medical fields since the storage of raw patient data can potentially conflict with privacy laws.

To address this problem, generative replay methods have been proposed, in which artificial sample points are generated by models like VAEs [10]. While generative replay mitigates the need for storing all data directly, the quality and diversity of generated samples are still daunting issues. Furthermore, typically the rehearsal-based methods in medical AI confront a *double imbalance* problem that is both the original dataset and replay buffer suffer from class imbalance. Hao et al.

[11] addressed this issue through a balanced loss formulation, though the approach does not eliminate the reliance on replay mechanisms.

C. Architecture-Based Approaches

Architecture-based methods alleviate forgetting by reworking the network topology to concentrate or diffuse parameters into new tasks. Dynamic expansion approaches address this by adding new parameters as new tasks come in, so that it does not interfere with the prior knowledge [12]. Nevertheless, these methods risk too large growth of the model which undermines scalability and deployability.

On the other hand, parameter isolation approaches allocate different parameters for each task in each layer so that catastrophic forgetting is mitigated, while they need separate task indicators during inference [3]. Such a requirement is unrealistic in practical class-incremental tasks, which commonly the task identity of new arriving samples are not available.

D. Hybrid Approaches and Research Gaps

Hybrids aim to make use of the advantages offered by different strategies. For instance, iCaRL combines exemplar replay with knowledge distillation, while Li et al. [13] combine multi-scale spatial distillation with

pseudo-labeling for brain tumor segmentation. While these methods have shown improvements in the stability of learning, they generally suffer from increased complexity and are not applicable when it comes to classification tasks with structured data.

Although substantial achievements have been made, there are still some gaps. A large number of CIL approaches are tested on idealistic benchmarks which do not reflect the complexity found in real medical data streams. Privacy leaks have restricted the use of rehearsal based methods, and architecture-based ones may suffer from low-efficiency or non-scalability. What is more, the majority of medical CIL studies consider imaging data without tapping into structured clinical datasets. These limitations highlight the need for lightweight, privacy-preserving class-incremental learning frameworks tailored to realistic healthcare settings.

E. Summary of Key Studies

Table I summarizes representative studies in medical continual learning, highlighting their core approaches, strengths, limitations, and the research gaps they leave unaddressed.

III. METHODOLOGY

A. Problem Definition

Brain tumor grading is an important clinical procedure where the right patient outcome is closely related to prompt and reliable diagnosis. Traditional deep learning-based classifiers are usually trained with static data assumption where all tumor categories are known a priori. When new tumor categories or datasets are added, these models needed to refit the entire dataset which is not practical in clinical area, and impossible due to issues of privacy protection, data access as well as cost.

Table I: Summary of Key Studies in Continual Learning for Medical AI

Ref.	Author(s)	Focus & Approach	Strengths & Limitations	Research Gap
[10]	Yavari & Furst	Hybrid approach: Generative Replay (VAE) + Knowledge Distillation (KD) + Metric Learning	Strengths: Preserves feature structure; privacy-friendly. Limitations: Generated samples often have low fidelity; scalability issues.	Scalability and quality of generative replay need improvement.
[6]	Perkonigg et al.	Rehearsal-based CL: Dynamic memory with style-based diversity metric	Strengths: Handles domain shifts effectively. Limitations: Requires raw data storage; memory-size dependent.	Ignores class imbalance and privacy concerns.
[13]	Li et al.	Hybrid: Multi-scale spatial distillation + pseudo-labeling (segmentation)	Strengths: Preserves spatial information; reduces labeling effort. Limitations: Noisy pseudo-labels; limited to segmentation tasks.	Not applicable to classification problems.
[11]	Hao et al.	Regularization-based CL: Balanced CIL loss (logit adjustment + margin loss)	Strengths: Addresses class imbalance; improves class separation. Limitations: Lacks rehearsal mechanism.	Requires integration with replay-based methods.
[3]	Kumari et al.	Survey of Continual Learning techniques in Medical AI	Strengths: Comprehensive categorization; highlights challenges. Limitations: No new method proposed.	Need for standardized benchmarks and supervised CL methods.
[5]	Singh et al.	Comparative study: MAS, DER, and Replay methods	Strengths: Demonstrates cross-specialty reuse. Limitations: Small CNN models; limited generalization analysis.	Task-order effects and scalability remain unexplored.

Further, sequential retraining suffers from catastrophic forgetting i.e., the model's performance on previously learned tumor classes drops substantially while learning new classes [7], [8]. To overcome this issue, we model the brain tumor classification problem as a *class-incremental learning* problem. In this setting, the model is trained sequentially on a series of tasks, each introducing one or more new tumor classes, without access to data from earlier tasks.

B. Dataset Description and Preprocessing

The dataset used in this study is a publicly available structured clinical dataset obtained from the Kaggle repository. It consists of tabular records, where each entry corresponds to an individual patient case described using de-identified clinical attributes. The dataset includes both numerical and categorical features commonly used in brain tumor assessment. Numerical attributes include patient age and tumor size, while categorical attributes include tumor location, tumor grade, and patient gender. The target variable represents the tumor type, with five clinically relevant classes considered in this work: Glioblastoma, Meningioma, Oligodendroglioma, Ependymoma, and Astrocytoma.

The class distribution reflects moderate imbalance typical of real-world medical datasets. Specifically, Glioblastoma accounts for 21.0% of the samples, followed by Oligodendroglioma (20.6%), Ependymoma (20.4%), Meningioma (19.0%), and Astrocytoma (19.0%). This distribution motivates the use of macro-averaged evaluation metrics and continual learning measures to ensure fair performance assessment across classes.

Prior to training, missing values in numerical features were handled using median imputation, while categorical variables with missing entries were treated as a separate category where applicable. Categorical features were transformed using one-hot encoding, and numerical attributes were standardized using z-score normalization to promote stable and efficient optimization.

The dataset was divided into training (60%), validation (20%), and test (20%) subsets, ensuring consistent class distributions across all splits. Incremental learning tasks were constructed from these sets to simulate realistic diagnostic evolution, where new tumor classes are introduced sequentially (one after another) over time.

C. Incremental Task Construction

To simulate a realistic diagnostic evolution, the data set is divided into a sequence of incremental tasks. The task sequence is defined as follows:

- Task 1: Glioblastoma, Meningioma
- Task 2: Task 1 + Oligodendroglioma
- Task 3: Task 2 + Ependymoma
- Task 4: Task 3 + Astrocytoma

At each stage the model is trained only on data from the new class introduced in current task, without access to samples from previous tasks. After completing each task, model performance is evaluated on all classes encountered so far.

D. Model Architecture

The classifying model is formed of a feedforward neural network that is suited to structured clinical data. It has three fully connected hidden layers with 128, 64, and 32 neurons in order. The activation functions are ReLU in all the hidden layers. The model avoids overfitting via dropout regularization. The output layer is dynamically extended as new tumor types are introduced in each task. For example, during Task 1 the output layer contains two neurons corresponding to the initial classes, and additional neurons are appended in subsequent tasks. Parameters associated with previously learned classes are retained, while newly introduced neurons are randomly initialized.

E. Elastic Weight Consolidation

To mitigate catastrophic forgetting, Elastic Weight Consolidation (EWC) is employed as a regularization mechanism tasks encountered so far. These metrics collectively capture the stability-plasticity trade-off of the proposed framework.

The forgetting index for task k is defined as: during incremental learning [9]. After completing each task, the importance of model parameters is estimated using the Fisher Information Matrix, which approximates the sensitivity of the loss function to changes in each parameter.

During training on a new task, updates to parameters that were important for previous tasks are penalized by adding a

$$F_k = \max_{t < k} A_t^{(t)} - A_t^{(k)}$$

where $A_t^{(k)}$ denotes the accuracy on task t after learning task

k . The incremental average accuracy is defined as:

regularization term to the loss function. The overall objective function is defined as:

$$IAA = \frac{1}{K} \sum_{k=1}^K A^{(k)}$$

$$L = L_{task} + \lambda \sum_i F_i (\theta_i - \theta_i^*)^2 \quad (1)$$

where L_{task} denotes the classification loss for the current task, θ_i represents the current value of parameter i , θ_i^* is the parameter value after training the previous task, F_i denotes the corresponding Fisher information, and λ controls the stability– plasticity trade-off. A higher λ emphasizes knowledge re-tention, while a lower value allows greater adaptation to new classes. In this work, the diagonal approximation of the Fisher Information Matrix is used, computed on the training data of the completed task, following standard practice for computational efficiency.

F. Training Procedure and Implementation Details

Training process: The model is trained sequentially across incremental tasks using the Adam optimizer and setting the learning rate to 1×10^{-3} and a batch size of 32. Each incremental task is trained for 40 epochs with early stopping based on validation loss used to reduce overfitting. After training on Whereas for each task, the Fisher information is computed and stored during subsequent stages of learning as part of the Elastic Weight Consolidation mechanism.

The regularization strength for EWC was set to $\lambda = 1000$ and selected empirically using validation performance. All hyperparameters were kept fixed across tasks to ensure fair comparison between incremental learning stages and baseline methods.

To ensure reproducibility, all experiments were conducted using single deterministic run with a fixed random seed to ensure reproducibility(random seed of 42 for Python, NumPy, and PyTorch).Model training and evaluation were implemented using the PyTorch framework and executed on a single NVIDIA CUDA-enabled GPU using the Google Colab platform.

G. Evaluation Metrics

Model performance is evaluated using both standard classification metrics and continual learning–specific measures. Standard metrics include accuracy, precision, recall, and F1- score, computed in a macro-averaged manner to account for class imbalance. To assess continual learning behavior, the forgetting index is computed as the reduction in accuracy on earlier tasks after training new ones, and incremental average accuracy is calculated by averaging performance across all

SYSTEM OVERVIEW AND ARCHITECTURE

A. System Architecture

Our suggested framework operates in a lifelong learning environment in which novel brain tumor classes are added one after another. Our suggested framework contrasts with other traditional classifier models in that it does not demand total training when new classes arise.

For this model, we have implemented a feed-forward architecture with three hidden layers comprising of 128, 64, and 32 neurons. There is also a use of dropout regularization. All the hidden layers involve the application of ReLU function. Dropout regularization is also added. As far as the output is concerned, it is designed such that when there is a need to classify a new type of tumor, a new neuron is added. For instance, if we consider a problem where there is a need to classify two types of tumors, namely Glioblastoma and Meningioma, we

will have two neurons in the output layer. Later on, two more neurons representing the remaining three types of tumors will be added.

In order to address the catastrophic forgetting issue, an "Elastic Weight Consolidation" component is incorporated within the learning model. After each learning stage consisting of given tasks, the relative importance of the model's parameters is calculated using the "Fisher Information Matrix". Then, the learned model's parameters that are important for the earlier stages are controlled while learning the later stages. Using this approach, the proposed model becomes more stable while learning the introduction of the new classes of tumors. A description of the workflow of the proposed system and the interaction between the various components of the proposed approach are depicted in Fig. 1.

B. Core Components

The proposed framework has been decomposed to a number of conceptual elements that enable class-incremental learning collectively, as illustrated in Fig. 1.

- 1) **Data Preprocessing Component:** This component prepares structured clinical data for training by transforming categorical variables using one-hot encoding, applying z-score normalization to numerical features and performing Stratified data splitting. Each of these steps standardizes the necessary input data, and balanced class distributions across incremental tasks
- 2) **Incremental Model Training Component:** This component implements the feed-forward neural network and manages sequential training across tasks. As new classes of tumors are identified, introduced, the output layer is expanded while parameters associated with previously learned classes are retained. Training proceeds incrementally without access to any history task data.
- 3) **EWC Regularization Component (EWC):** This component computes parameter importance by using the Fisher Information Matrix and employs EWC-based regularisation during for the subsequent tasks. The regularization strength λ determines the familiar "stability-plasticity" trade-off, enabling the knowledge retention and adaptation to new tumor classes.
- 4) **Component for Evaluation and Reporting:** It computes common classification metrics and -continual learning-specific measures, including: forgetting index and incremental average accuracy. Task-wise performance summaries and learning curves will support analysis of stability-plasticity behaviour and enhance reproducibility.

A system-level design enables scalable and privacy-preserving adaptation to new tumor classes without sacrificing prior diagnostic knowledge and puts it in line with real-world requirements of medical continual learning.




Fig. 1: Overview of the proposed class-incremental learning framework for brain tumor classification. The workflow includes data preprocessing, incremental model training, EWC-based regularization, and evaluation.

IV. RESULTS AND DISCUSSION

A. Experimental Setup

Experiments were conducted on a structured tabular dataset comprising five brain tumor classes—Glioblastoma, Meningioma, Oligodendroglioma, Ependymoma, and Astrocytoma. The dataset was stratified into training (60%), validation (20%), and testing (20%) splits to maintain balanced class distributions. Incremental tasks were created to reflect realistic diagnostic evolution as follows: Task 1 (Glioblastoma, Meningioma), Task 2 (+Oligodendroglioma), Task 3 (+Ependymoma), and Task 4 (+Astrocytoma).

The baseline classifier was a feed-forward neural network trained using the Adam optimizer (learning rate = 0.001, batch size = 32) with early stopping based on validation loss. Class-incremental learning incorporated Elastic Weight Consolidation (EWC), with the regularization coefficient λ tuned empirically in the range 10^2 to 10^4 using validation performance.

Performance was compared against two reference baselines:

- **Naive Fine-Tuning:** Sequential training without any continual learning mechanism, serving as a lower bound.
- **Joint Training:** Training on data from all classes simultaneously, serving as an upper bound that assumes full data availability.

B. Classification Performance

Across incremental tasks, the EWC-enabled model consistently outperformed naive fine-tuning in terms of accuracy and F1-score while approaching the performance of joint training. Representative results are reported in Table II.

TABLE II: Task-wise Classification Metrics (Macro- Averaged).

Task	Accuracy	Precision	Recall	F1
Naive T1	82.3%	81.7%	82.0%	81.8%
Naive T4	65.4%	63.1%	61.8%	62.4%
EWC T1	83.5%	82.6%	83.1%	82.8%
EWC T4	77.9%	76.8%	76.5%	76.6%
Joint	81.2%	80.4%	80.7%	80.5%

Notably, EWC preserved earlier task performance significantly better than naive fine-tuning. For example, accuracy on Task 1 dropped by only approximately 6% under EWC after learning all tasks, compared to nearly 17% under naive fine-tuning. This highlights the effectiveness of EWC in retaining prior knowledge while learning new tumor classes.

C. Continual Learning Metrics

To explicitly quantify the stability–plasticity trade-off, continual learning metrics were computed across all tasks. Table III presents the forgetting index and incremental average accuracy (IAA) for each method. Note that the forgetting index is not applicable to joint training, as all classes are learned simultaneously and no sequential task overwriting occurs; joint training therefore serves only as an upper-bound reference for achievable performance.

EWC reduced the forgetting index by more than half compared to naive fine-tuning, demonstrating effective memory preservation. The incremental average accuracy achieved by EWC remained close to that of joint training, despite operating under strict class-incremental and privacy-preserving constraints. The evolution of forgetting behavior across incremental tasks is further illustrated in Fig. 2, which shows that EWC consistently mitigates performance degradation on earlier tasks as new tumor classes are introduced, whereas naive fine-tuning exhibits a steeper decline in accuracy.

TABLE III: Continual Learning Metrics (All Tasks).

Method	Forgetting Index	IAA
Naive Fine-tuning	21.3%	68.2%
EWC	9.5%	76.3%
Joint Training	—	80.1%




Fig. 2: Forgetting behavior across incremental tasks. The EWC-based model exhibits substantially lower forgetting compared to naive fine-tuning as new tumor classes are introduced.

D. Error Analysis

Analysis of confusion matrix showed that misclassifications were most often made between histologically similar tumor types, e.g Glioblastoma and Astrocytoma. This implies that feature values are likely to overlap between tumor types in the context of structured clinical data, and that we may be missing out on finegrained differentiation by using tabular representations. Including adjunctive modalities (consideration of MRI imaging) might mitigate against such errors. Training dynamics also showed that while naive finetuning quickly adjusts parameter values to perform new tasks, the training is at odds with the preservation of previously learned

knowledge. In contrast, EWC adds a well-controlled regularizing effect, which results in smoother learning process and more stable performance over new tasks.

E. Discussion

Overall, the results indicate that class-incremental learning using EWC greatly enhances the robustness of classification in dynamic diagnostic conditions when applied to brain tumor. While EWC does not fully match the performance of joint training, it provides a reasonable trade-off when saving past experiences or retraining from scratch is impractical. Such findings are in line with previous work that pointed out that regularization-based techniques are effective for avoiding catastrophic forgetting [4], [9]. The proposed scheme has less threats for privacy protection than rehearsal-based methods due to avoiding the preservation of patient data, which is highly promising for practical medical applications. Results stand in favor of using EWC as a robust deployable baseline for continual learning on structured clinical data.

V. CONCLUSION AND FUTURE WORK

This study investigated class-incremental learning for brain tumor classification under realistic clinical constraints, where diagnostic categories evolve over time and access to historical patient data is limited. By formulating brain tumor classification from structured clinical data as a class-incremental learning problem, the work highlights the limitations of conventional static training approaches in dynamic healthcare environments.

A privacy-preserving continual learning framework based on Elastic Weight Consolidation (EWC) was implemented and evaluated across sequential diagnostic tasks. Experimental results showed that EWC substantially reduces catastrophic forgetting compared to naive fine-tuning, while achieving performance close to joint training without requiring data rehearsal or full retraining. These findings demonstrate that regularization-based continual learning provides a practical and deployable solution for evolving medical AI systems.

It seems promising that future research can be extended to incorporating additional data types like MRI Imaging or genomics to enhance differentiation of clinically similar tumor types. Other possible extensions consist of hybrid continual learning (i.e., online learning combining several approaches, where task embeddings are learned online during the update procedure and adapted off-line) or supervised pre-training strategies, task-order robustness analyses, and privacy-preserving distributed and federated learning frameworks for health care at scale.

REFERENCES

- [1] G. Parisi, R. Kemker, J. Part, C. Kanan, and S. Wermter, "Continual lifelong learning with neural networks: A review," *Neural Networks*, vol. 113, pp. 54–71, 2019.
- [2] M. Qazi, A. Hashmi, S. Sanjeev, I. Almakky, N. Saeed, C. Gonzalez, and M. Yaqub, "Continual learning in medical imaging: A survey and practical analysis," *arXiv preprint arXiv:2405.13482*, 2024.
- [3] P. Kumari, J. Chauhan, A. Bozorgpour, B. Huang, R. Azad, and D. Merhof, "Continual learning in medical image analysis: A comprehensive review of recent advancements and future prospects," *arXiv preprint arXiv:2312.17004*, 2024.
- [4] M. De Lange, R. Aljundi, M. Masana, S. Parisot, X. Jia, A. Leonardis, G. Slabaugh, and T. Tuytelaars, "A continual learning survey: Defying forgetting in classification tasks," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 44, no. 7, pp. 3366–3385, 2022.
- [5] A. Singh, S. Gantha, M. Gurbuz, and P. Jasti, "Class-incremental continual learning for general purpose healthcare models," *arXiv preprint arXiv:2311.04301*, 2023.
- [6] M. Perkonigg, J. Hofmanninger, C. Herold, J. Brink, O. Pinykh, Prosch, and G. Langs, "Dynamic memory to alleviate catastrophic forgetting in continual learning with medical imaging," *Nature Communications*, vol. 12, no. 1, p. 5678, 2021.
- [7] R. French, "Catastrophic forgetting in connectionist networks," *Trends in Cognitive Sciences*, vol. 3, no. 4, pp. 128–135, 1999.
- [8] M. McCloskey and N. Cohen, "Catastrophic interference in connectionist networks: The sequential learning problem," in *Psychology of Learning and Motivation*, G. Bower, Ed. Elsevier, 1989, vol. 24, pp. 109–165.

-
- [9] J. Kirkpatrick, R. Pascanu, N. Rabinowitz, J. Veness, G. Desjardins, Rusu, K. Milan, J. Quan, T. Ramalho, A. Grabska-Barwinska, D. Hassabis, C. Clopath, D. Kumaran, and R. Hadsell, "Overcoming catastrophic forgetting in neural networks," *Proceedings of the National Academy of Sciences*, vol. 114, no. 13, pp. 3521–3526, 2017.
- [10] S. Yavari and J. Furst, "Mitigating catastrophic forgetting in the incremental learning of medical images," *arXiv preprint arXiv:2504.20033*, 2025.
- [11] X. Hao, W. Ni, X. Jiang, W. Tan, and B. Yan, "Addressing imbalance for class incremental learning in medical image classification," *arXiv preprint arXiv:2407.13768*, 2024.
- [12] D. Zhou, F. Wang, H. Ye, and D. Zhan, "Pycil: a python toolbox for class-incremental learning," *Science China Information Sciences*, vol. 66, no. 9, p. 197101, 2023.
- [13] R. Li, J. Ye, Y. Huang, W. Jin, P. Xu, and L. Guo, "A continuous learning approach to brain tumor segmentation: integrating multi-scale spatial distillation and pseudo-labeling strategies," *Frontiers in Oncology*, vol. 13, p. 1247603, 2024.

SENTIMENT ANALYSIS AND TOPIC MODELING USING BERT AND LDA

Nikita Makwana¹ and Manisha Divate²^{1,2}Department of Artificial Intelligence & Data Science, SVKM's Usha Pravin Gandhi College of Arts, Commerce and Science, Vile Parle, Mumbai, Maharashtra 400056, India**ABSTRACT**

Sentiment analysis has become a crucial task in Natural Language Processing (NLP) due to the rapid growth of user-generated textual content across digital platforms. This research paper presents a comprehensive sentiment analysis and topic modeling framework implemented using Streamlit and advanced NLP techniques. The system utilizes a multilingual BERT-based sentiment classifier to capture contextual sentiment information and integrates Latent Dirichlet Allocation (LDA) to uncover latent thematic structures in textual data. In addition to polarity detection, the framework performs aspect-based sentiment analysis, review-length evaluation, and visual analytics such as word clouds and statistical plots. The proposed system demonstrates high flexibility, usability, and interpretability, making it suitable for real-world applications such as customer feedback analysis, product review mining, and opinion monitoring systems.

I. INTRODUCTION

The exponential growth of online platforms such as e-commerce websites, social media, and review forums has resulted in massive volumes of textual data. Organizations increasingly rely on sentiment analysis to extract meaningful insights from this unstructured information. Sentiment analysis aims to determine the emotional tone behind a body of text, enabling businesses to understand customer satisfaction, public opinion, and market trends.

Traditional sentiment analysis techniques were primarily based on lexicon-driven approaches or classical machine learning algorithms such as Naïve Bayes and Support Vector Machines. Although effective to some extent, these methods often fail to capture contextual dependencies and semantic nuances present in natural language. The emergence of transformer-based models such as BERT (Bidirectional Encoder Representations from Transformers) has significantly improved sentiment classification performance by modeling bidirectional contextual relationships.

This paper proposes an interactive sentiment analysis system that combines BERT-based sentiment classification, aspect-based sentiment analysis, topic modeling using LDA, and visual analytics within a Streamlit application. The system allows users to upload textual datasets, perform preprocessing, and obtain detailed analytical insights through an intuitive interface.

II RELATED WORK

Extensive research has been conducted in the field of sentiment analysis and opinion mining. Early approaches relied on manually crafted sentiment lexicons and rule-based techniques. While these methods offered interpretability, they lacked robustness and scalability for large datasets. Machine learning-based methods improved classification accuracy by learning patterns from labeled data but were limited by feature engineering requirements.

Recent advancements in deep learning have transformed NLP research. Models such as Word2Vec, GloVe, and fastText enabled distributed word representations, while transformer-based architectures like BERT introduced attention mechanisms that capture long-range dependencies. Several studies have demonstrated that BERT significantly outperforms traditional models in sentiment analysis tasks.

Topic modeling techniques, particularly Latent Dirichlet Allocation, remain widely used for discovering hidden themes in document collections. LDA has been successfully applied to customer reviews, social media analysis, and news categorization. Additionally, Streamlit has emerged as a lightweight framework for deploying interactive data science applications, enabling rapid prototyping and visualization.

III.PROPOSED WORK

The proposed system is implemented in Python and deployed using Streamlit to provide an interactive user interface. The workflow begins with loading a pretrained multilingual BERT sentiment analysis pipeline. Users upload a CSV file containing textual data and select the relevant text column for analysis.

Data preprocessing plays a vital role in improving analytical accuracy. The system provides multiple preprocessing options, including duplicate removal, missing value elimination, whitespace trimming, lowercase conversion, and filtering of short texts. These steps ensure data cleanliness and consistency before analysis.

Sentiment classification is performed using the nlptown/bert-base-multilingual-uncased- sentiment model. The model assigns ratings on a scale of 1 to 5, which are subsequently mapped to sentiment labels: positive, neutral, or negative. Additional features such as word count and review length categories are computed to support deeper analysis.

Aspect-based sentiment analysis is conducted using a predefined list of domain-specific aspects. Each review is examined to identify mentions of these aspects, allowing sentiment distribution analysis across different product attributes. Topic modeling is implemented using Latent Dirichlet Allocation applied to a document-term matrix generated via CountVectorizer. Visualization techniques include bar charts, sentiment distributions, and word clouds.




Fig 1: Aspect base sentiment distribution

IV RESULTS AND DISCUSSION

The experimental evaluation demonstrates that the proposed system effectively classifies sentiment across multilingual datasets. BERT- based sentiment analysis provides high contextual accuracy, especially in complex sentence structures. Aspect-based sentiment analysis reveals sentiment variations associated with specific product features such as quality, price, and performance.

LDA successfully identifies dominant topics within the dataset, enabling users to understand recurring discussion themes. Review-length analysis indicates a correlation between verbosity and sentiment polarity, with longer reviews often expressing stronger opinions. Visualizations generated by the system enhance interpretability and support data-driven decision-making.

V. CONCLUSION

This research presents a robust and interactive sentiment analysis framework that integrates deep learning, topic modeling, and visual analytics. The use of BERT significantly enhances sentiment classification accuracy, while LDA provides meaningful topic insights. The Streamlit-based interface ensures usability and accessibility for non-technical users. Future work may focus on real-time data integration, domain- specific fine-tuning, and multilingual expansion to further enhance system capabilities.

REFERENCES

1. Devlin et al., "BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding," NAACL, 2019.
2. D. M. Blei et al., "Latent Dirichlet Allocation," Journal of Machine Learning Research, 2003.
3. Vaswani et al., "Attention Is All You Need," NeurIPS, 2017.
4. T. Mikolov et al., "Efficient Estimation of Word Representations in Vector Space," ICLR, 2013.
5. J. Pennington et al., "GloVe: Global Vectors for Word Representation," EMNLP, 2014.
6. H. Schütze et al., "Introduction to Information Retrieval," Cambridge University Press, 2008.

-
7. S. Bird et al., "Natural Language Processing with Python," O'Reilly Media, 2009.
 8. Scikit-learn Developers, "Machine Learning in Python," JMLR, 2011.
 9. Streamlit Inc., "Streamlit Documentation," 2024.
 10. Y. Liu et al., "RoBERTa: A Robustly Optimized BERT Pretraining Approach," arXiv, 2019.

THE ROLE OF AI IN EDUCATION: A STUDY OF ITS IMPACT, OPPORTUNITIES, AND RISKS

Nisha Sarvaiya¹ and Neha Vora²¹Student and ²Assistant Professor, Department of Information Technology, SVKM's Usha Pravin Gandhi College of Arts, Science and Commerce, Mumbai, India**ABSTRACT**

AI is everywhere in education now. Tools like ChapGPT, Grammarly, Quillbot, etc makes life easier for students as well as for teachers. This tools saves time, help to fix mistakes, and also even offer personalized support. But not everything is perfect there are some problems like plagiarism, cheating, less critical thinking, and sometimes spreading wrong informations. This study asks students and teachers what they think about Artificial Intelligence (AI) in education, how much they used it, how much they are aware of this tools, and what worries they have. We got the answers from both students as well as teachers through a questionnaire, after that Chi-Square test are used to find if factors like age, gender, qualifications, and roles could be related on their views on AI or not.

Keywords - Artificial Intelligence, Education, AI tools, Academic Integrity, Ethical Concerns,, Regulations.

1. INTRODUCTION

One after another AI (Artificial Intelligence) technologies are rapidly becoming influencing factors on peoples lives and work all over the work. Also AI in education has positive impact on both teachers as well as students, largely through enhanced personalized support and administrative efficiency. Based on-demand educational support, ChatGPT gives direct answers and explanations, Grammarly automatically fixes errors on grammar and style, while Quillbot provides users with a easy way of working through their writing by paraphrasing and summarizing. These inventions are no longer optional aids but are becoming the integral part of everyday educational activities.

AI could save a lot of time for teachers so that teachers get more time to guide students and do their research. Students will be able to get individual feedback instantly, so that they will be able to determine their own learning rate and can even choose other resources apart from the books. Users are in a better position to recognize the advantages, but they still lack understanding of the ethical risks and how to lawfully integrate AI into their academic work [3].

1.2. PROBLEM STATEMENT

The implementation of artificial intelligence (AI) systems that support teaching and learning is a significant challenge that raises many issues and advantages of AI simultaneously. While some positive impacts of AI in education have been acknowledged, concerns about plagiarism and cheating in academics have been voiced. This is because the technology is very adaptable at generating texts without actually thinking. If students excessively rely on AI, their critical thinking and problem-solving skills may be weakened. In general, most institutions do not have well-defined policies that regulate the use of technology, especially artificial intelligence. not only students but also educators are frequently uncertain of what is right. The absence of such clarity can cause the uneven use of AI, which may differ quite a lot not only between various tools but also among different classrooms.

Besides that, the problem of the technology has to be acknowledged before it can be used in a responsible way. Most students know that AI-based tools are available, but only a handful are aware of the ethical dilemmas involved in their usage. In the same way, employees may be inclined to use the AI method for the sake of efficiency while at the same time being unaware of the correct ways of utilizing the technology without falling into the trap of misuse.

1.3. OBJECTIVES OF THE STUDY

The paper is with the ambition to:

- Ascertain the mindfulness level and frequency with which AI tools are used by students and educators.
- Point out the AI tools that are mostly supported and the reasons that caused most people to choose them.
- Delve into the user mood with regard to the potential advantages such as efficiency, time-saving, and personal support.
- Unravel the negative side of what seems to be an ethical issue concerning plagiarism, disinformation, and the possible diminution of creativity.

- Conduct demographic studies that consist of the correlation of the perception of AI with indices of chi-square testing.
- Make suggestions about the steps to be taken by educational institutions for integrating AI in a responsible manner.

1.4. RESEARCH GAP

Large numbers of results focus on the uses of AI in teaching, they often only outline the idea or describe it briefly. Besides such investigations that apply rigorous statistical procedures for the clarifying the impact of demographics on understanding of AI are rare. This study, combining field data collection and chi-square analysis, goes beyond descriptive insights to actual proof.

2. RELATED WORK

Use of Artificial Intelligence (AI) in the education sector is a major research focus, which changes very fast. The present review of literature combines the research to the four interrelated parts: first, knowledge and use of AI; second, the promising of AI to improve educational process; third, ethical risks and academic integrity problems; and fourth, the consequent demand for institutional policy and governance.

2.1. STUDENTS UNDERSTANDING AND EXPERIENCE WITH CHATGPT/ AI

Several studies have explored that how students observe and use ChatGPT in learning. Ngo (2023) [1] found that mostly all universities students viewed ChatGPT as a helpful for generating ideas, improving writing, and understanding the concepts. However concerns about plagiarism, overusing AI, and also losing critical thinking skills were raised, highlighting the importance of eithical guidelines and teachers supervision. Similarly, Blahopoulou & Ortiz-Bonnin (2025) [2] compared students who use ChatGPT and those who do not. Users of ChatGPT reported that it saves time, improve writing and made learning easier, while non users were concerned about academic dishonesty and shallow learnings. Chan and Hu (2023) [7] also highlighted that the student appreciation for instant feedback, personalized support, and language assistance, though they concerned about plagiarism, accuracy, and data privacy issues. Lastly Chan and Lee

[10] explored that a AI generation gap, showing that Gen Z students were more comfortable using ChatGPT, while older teachers were unsure, underscoring the need for AI training programs.

2.2. AI IN EDUCATION: REVIEW AND FRAMEWORK

These studies focus on understanding AI role in education more widely. Chen, Chen, and Lin[3] reviewd that AI tools such as adaptive learning systems and intelligent tutoring, noting that AI improves personalized instruction, engagement and feedback systems, but also raises privacys,, ethical and training concerns Zhai

[4] reviewed a decades of AI research, showing that AI evolved from simple automation to smart, adaptive systems capable of supporting complex learning environments. They highlighted ongoing challenges like equity, accessibility, and teachers preparations, positioning ChapGPT as part of the next generation of AI in education. Crompton and Burke(2023) [8] add to these findings in a global reviews, showing that the AI improves adaptive learning, grading, and analytics, with ChatGPT marking a step towards interactive and generative learning. They highlight the importance of teacher training, ethical policies and curriculam adaptation to maximize benefits.

2.3. INSTITUTIONAL AND FACULTY PERSPECTIVES

Many studies examined that how AI affects institutions and faculty. Javkhedkar, Shrungarkar, and Kulkarni (2024) [5] studied AI in an Indian higher education, finding that the AI tools improved students engagement, learning efficiency, and the concepts of understanding, but institutional preparation. Cambra- Fierro et al. (2025) [6] studied faculty well-being showing that though ChatGPT enhances teaching innovation and reduces workload, but it can also create a job insecurity and ethical dilemmas. Clear policies and continues professional development were recommended to ensure responsible and sustainable AI use.

2.4. AI TOOLS AND THEIR TRANSFORMATIVE POTENTIAL

Adiguzel, Kaya, and Cansu [9] they found that the ChatGPT helps both student and teacher with content creation, personalized learning, and collaboration. At the same time, they warned about risks like bias, data misuse, and overreliance, suggesting that a human-AI partnership models is essentials where AI supports but does not replace human judgment.

2. RESEARCH METHODOLOGY

2.1. RESEARCH DESIGN

This study has taken a descriptive survey research design. This design was preferred as it allows the researcher not only to collect quantitative data of awareness, perceptions, and concerns about AI in educational processes

but also to find out if there are any associations between demographic factors and these perceptions. The descriptive method is useful since it aims at identifying the existing state without changing variables, thus, it is possible to get the true opinions of the stakeholders.

2.2. DATA COLLECTION PROCEDURE

The questionnaire was shared online through Google Forms for two weeks. Survey participation was offered voluntarily and anonymity was guaranteed. Participants received information about the study's goal, and permission was obtained prior to the survey. In order to reduce the bias of answers, the directions emphasized that no right or wrong answers existed.

3.3. VARIABLES

- Independent variables: Gender, Age, Educational level, Position, Frequency of AI usage.
- Dependent variables: Awareness, Perceived Benefits, Ethical Concerns,, Regulation Preferences.

3.4. STATISTICAL ANALYSIS

The data collection was subjected to chi-square tests for determining of relationships between categorical variables. The rationale behind selecting chi-square is that it is an appropriate method for testing the associations between categorical variables such as demographics and perceptions. The level of significance set at $p < 0.05$.

Hypothesis 1: Age and Frequency of AI Usage

H0: Age does not affect the frequency of AI usage

H1: Age affects the frequency if AI Usage

Hypothesis 2: Age and Preception of AI Making Learning Easier

H0: Age has no effect on the preception of AI making learning easier

H1: Age affects the preception of AI making learning easier

3.5. DATA ANALYSIS

In line with the survey implementation, a total of 111 people responded to the questionnaire. Those who responded were from various age groups and educational levels and held different positions in the field of education. The research was majorly undertaken to know the extent to which the participants are mixed, up with AI tools in education and how they perceive the advantages.

The survey results uncovered that the usage of AI tools is at the peak among the youngest respondents, particularly those who fall into the 18, 25 years age bracket, and who have indicated that they use AI tools very often for their study and academic work. Respondents who were in the older age groups exhibited a relatively lower frequency of AI usage. This suggests a significant difference in the pattern of AI usage by age groups.

Further analysis also revealed that a significant percentage of respondents were of the opinion that AI tools indeed help save time in various activities such as writing, concept understanding, and finishing academic tasks. Nonetheless, the intensity of agreement changed with different age groups implying that the idea of AI's time, saving advantages is not the same for all the respondents.

By and large, the figures indicate that age is a decisive factor in determining not only how often AI is used but also how AI tools are perceived as time, saving devices. Such results offer a very good base for the usage of Chi, square tests to check the relations between demographic variables and the perceptions of AI in education.

3.6. DATA INTERPRETATION

Hypothesis 1: Age and Frequency of AI Usage

H0: Age does not affect the frequency of AI usage

H1: Age affects the frequency if AI Usage

Observed Values							
Age / Frequency	Daily	Weekly	Rarely	Never	Yes, Frequently	Yes, Occasionally	Total
Below 18	4	0	2	1	3	6	16
18-25	14	6	4	1	37	11	73
26-35	1	0	3	3	4	3	14
36-45	1	0	0	0	0	4	5
50+	0	0	1	1	1	0	3
Total	20	6	10	6	45	24	111

Expected Values = (Row Total × Column Total) / Grand Total							
Age / Frequency	Daily	Weekly	Rarely	Never	Yes, Frequently	Yes, Occasionally	
Below 18	2.88	0.86	1.44	0.86	6.49	3.46	
18-25	13.15	3.94	6.57	3.94	29.59	15.81	
26-35	2.52	0.76	1.26	0.76	5.67	3.03	
36-45	0.90	0.27	0.45	0.27	2.02	1.08	
50+	0.54	0.16	0.27	0.16	1.21	0.65	

Chi-Square Table = $(O - E)^2 / E$							
Age / Frequency	Daily	Weekly	Rarely	Never	Yes, Frequently	Yes, Occasionally	
Below 18	0.0545	2.1994	1.0095	1.0692	1.8530	1.4499	
18-25	0.9189	6.6496	2.3970	0.7568	0.4947	0.0002	
26-35	0.0109	0.2703	0.4505	0.2703	2.0270	7.8811	
36-45	0.5405	4.3288	1.9703	0.1622	0.0384	0.6486	
50+	0.4329	0.0211	0.2164	0.8649	1.8740	1.8657	

Degrees of Freedom = $(r-1)(c-1) = 20$

P-value	0.00222	Significance Level	0.05
Test Statistic (χ^2)	42.7267	Critical Value	31.4104

Since the test statistic is greater than the critical value and the p-value is less than 0.05, we reject the null hypothesis.

There is a significant relation between age and frequency of AI usage.

Hypothesis 2: Age and Preception of AI Making Learning Easier

H0: Age has no effect on the preception of AI making learning easier

H1: Age affects the preception of AI making learning easier

Observed Values						
Age / Perception	Agree	Disagree	Neutral	Strongly Agree	Strongly Disagree	Total
Below 18	8	0	2	6	0	16
18-25	33	1	9	29	1	73
26-35	7	1	3	3	0	14
36-45	3	0	1	1	0	5
50+	1	1	0	0	1	3
Total	52	3	15	39	3	111

Expected Values = (Row Total × Column Total) / Grand Total						
Age / Perception	Agree	Disagree	Neutral	Strongly Agree	Strongly Disagree	
Below 18	7.50	0.43	2.16	5.62	0.43	
18-25	34.19	1.97	10.14	25.67	1.97	
26-35	6.56	0.38	1.89	4.92	0.38	
36-45	2.34	0.13	0.68	1.75	0.13	
50+	1.41	0.08	0.41	1.05	0.08	

Chi-Square Table = $(O - E)^2 / E$					
Age / Perception	Agree	Disagree	Neutral	Strongly Agree	Strongly Disagree
Below 18	0.033	0.430	0.012	0.026	0.430
18-25	0.042	0.482	0.136	0.442	0.482
26-35	0.030	1.017	0.672	0.747	0.380
36-45	0.182	0.135	0.156	0.321	0.135
50+	0.120	10.125	0.410	1.050	10.125

Degrees of Freedom = $(r-1)(c-1) = 16$

P-value	0.00536	Significance Level	0.05
Test Statistic (χ^2)	34.0407	Critical Value	26.2962

Since the test statistic is greater than the critical value and the p-value is less than 0.05, we reject the null hypothesis.

There is a significant relation between age and the perception that AI tools save time.

4. DISCUSSION

The research indicates that AI is a double-edged sword, having as much a positive as a negative impact in the field of education. It was found that the gender and role of participants had an effect on their viewpoint, thereby confirming that demographic variables have an impact on the acceptance and attitude of AI (Chan & Lee, 2023) [10]. Influences of age and qualification on the matter were quite limited in several areas, which would imply that the attraction and apprehensions of AI go beyond the usual demographic boundaries.

Benefits: AI tools were seen as a timesaver, a way to simplify and personalize learning and support. The heavy use of ChatGPT signals the tools efficiency in providing one-side explanations and encouraging the problem solution process. Grammarly and QuillBot assist in raising writing quality and comprehension levels.

Concerns: Writings produced by AI became the source of problems such as plagiarism, excessive use of AI, and deficiency in the development of the students' critical thinking ability. These problems are very much in line with the observations made. The possibility of misuses is much higher when there is no providing of directions and setting of rules by management.

IMPLICATIONS:

- Employing AI literacy programs is the main approach institutions can take to educate students about AI use in ethics, checking for the correctness of AI solutions, and application of AI in the right way.
- Rules and regulations should be drawn to control the use of AI in tasks that inherently include the occurrence of phenomena such as plagiarism, originality, and proper referencing.
- Moreover, the teacher has to employ the aid of AI in combination with maintaining the fostered skills of critical thinking and the students autonomy in learning.

LIMITATION:

The sampling was done in the way to make it convenient of the participants and that is why its findings are not widely applicable.

The data is based on participants self-perception which might reflect some degree of bias.

Chi-square test is good in detecting the existing relationships between variables but this statistical method cannot confirm any of them as causal.

5. CONCLUSION AND FUTURE SCOPE

Machines have been employed thoroughly in education and have been praised for their effectiveness and the help they bring to the learning process. However, the ethics of the matter still linger, the main problems being copying, lowering of creativity, and excessive reliance on the tool. Using the technology in a socially acceptable way requires among other things strict regulations, training, and support from institutions.

FUTURE SCOPE:

- Samples that are larger and more diverse from the different regions and institutions.
- Comparative studies among different cultures and education systems.
- Experimental studies to identify the causal effects on AI the learning outcomes.

6. REFERENCES

- [1] Thi Thuy An Ngo “The Perception by University Students of the Use of ChatGPT in Education” *International Journal of Emerging Technologies in Learning (Online)*: Vienna Vol. 18, Iss. 17, (2023) <https://www.proquest.com/openview/8fa819963571b15f4092d8ba787c10b9/1?pq-origsite=gscholar&cbl=5452619>
- [2] Joanna Blahopoulou & Silvia Ortiz-Bonnin “Student perceptions of ChatGPT: benefits, costs, and attitudinal differences between users and non-users toward AI integration in higher education” *Volume 30*, pages 19741–19764, (2025) <https://link.springer.com/article/10.1007/s10639-025-13575-9>
- [3] Lijia Chen; Pingping Chen; Zhijian Lin “Artificial Intelligence in Education: A Review” <https://ieeexplore.ieee.org/abstract/document/9069875/authors#authors>
- [4] Xuesong Zhai, Xiaoyan Chu, Ching Sing Chai, Morris Siu Yung Jong, Andreja Istenic, Michael Spector, Jia- Bao Liu, Jing Yuan, Yan Li “Review of Artificial Intelligence (AI) in Education from 2010 to 2020” <https://onlinelibrary.wiley.com/doi/full/10.1155/2021/8812542>
- [5] Dr. Sarang R. Javkhedkar, Dr. Anjali Shrugarkar, Dr. Atul P. Kulkarni “The Impact of Artificial Intelligence on Current Education System: A Case Study” https://www.researchgate.net/profile/Sarang-Javkhedkar/publication/381744787_The_Impact_of_Artificial_Intelligence_on_Current_Education_System_A_Case_Study/links/683ed1476b5a287c3048f149/The-Impact-of-Artificial-Intelligence-on-Current-Education-System-A-Case-Study.pdf
- [6] Jesús J. Cambra-Fierro, María Fuentes Blasco, María-Eugenia Eugenia López-Pérez & Andreea Trifu “ChatGPT adoption and its influence on faculty well-being: An empirical research in higher education” *Volume 30*, pages 1517–1538, (2025) <https://link.springer.com/article/10.1007/s10639-024-12871-0#Sec2>
- [7] Cecilia Ka Yuk Chan & Wenjie Hu “Students’ voices on generative AI: perceptions, benefits, and challenges in higher education” <https://link.springer.com/article/10.1186/S41239-023-00411-8>
- [8] Helen Crompton & Diane Burke “Artificial intelligence in higher education: the state of the field” *International Journal of Educational Technology in Higher Education* *Volume 20*, article number 22, (2023) <https://link.springer.com/article/10.1186/S41239-023-00392-8#Bib1>
- [9] Adiguzel, Tufan; Kaya, Mehmet Haldun; Cansu, Fatih Kursat “Revolutionizing Education with AI: Exploring the Transformative Potential of ChatGPT” <https://eric.ed.gov/?id=EJ1395102>
- [10] Cecilia Ka Yuk Chan, Katherine K. W. Lee “The AI generation gap: Are Gen Z students more interested in adopting generative AI such as ChatGPT in teaching and learning than their Gen X and Millennial Generation teachers?” <https://arxiv.org/abs/2305.02878>

A HYBRID TRANSLATION SYSTEM FOR HINGLISH: BRIDGING CODE-MIXED COMMUNICATION

¹Om Rawal and ²Dr. Prashant Chaudhary¹Student MscIT and ²Co-ordinator Department of Information Technology Usha Pravin Gandhi College of Arts, Science and Commerce, SVKM, Mumbai, Maharashtra 400056**ABSTRACT**

The increasing use of multilingual communication on digital platforms has led to the frequent occurrence of code-mixed text, particularly Hinglish, which blends Hindi and English within a single utterance. Such mixed-language input presents persistent difficulties for conventional Natural Language Processing systems due to irregular grammatical patterns, phonetic spelling variations, and the limited availability of standardized linguistic resources. Most existing machine translation approaches are designed for monolingual input and are therefore inadequate for handling simultaneous translation from code-mixed text into multiple target languages.

This paper proposes a hybrid translation framework for converting Hinglish text into standard Hindi and English. The approach incorporates a structured preprocessing pipeline for text normalization and employs transformer-based models supported by cross-lingual embeddings to capture semantic consistency across languages. Experimental results indicate effective translation performance, with BLEU scores of 0.82 for Hindi and 0.80 for English. The integration of rule-based, statistical, and neural components enables robust performance across diverse datasets, demonstrating the suitability of the proposed system for practical code-mixed language translation tasks.

Index Terms—Code-Mixed Language, Hinglish, Machine Translation, Natural Language Processing, Transformer Models, Hybrid Translation System, Cross-lingual Embeddings

I. INTRODUCTION**A. Background**

In the fast growing digital era where the online platform of communication such as texting apps, social media or blogs etc, the Indian people are interacting with each other via multilingual languages. An important outcome of this transformation is the popularity of code-mixed languages, like Hinglish (involving Hindi and English). Knowing how to use English in conjunction with Hindi requires vocabulary, grammar and phonetic gaming from two languages blended on an unpredictable way and a context dependent manner. For example, a standard Hinglish sentence such as the one above (“Main (I) tomorrow office jaunga go.PAST”) combines Hindi words (main; “go”) and English words (tomorrow; office) along with hybridized syntax. Hinglish has become prominent in urban India, particularly among youths and is widely used on various social media posts, advertisements and informal conversation.

Since Hinglish is complex it is very difficult for NLP systems. Traditional machine translation (MT) systems built for monolingual and bilingual scenarios are not well-poised to translate code-mixed text because of its dynamic syntactic structure, phonetic variations (e.g., “phir”, written as “fir”) and the use of slang or region specific languages. All existing translation systems primarily translate Hinglish to either Hindi or English, yet hardly any of these cater for both types of translations, which considerably restricts their suitability in applications that demand multilingual outputs (e.g. customer support chatbots, educational tools or sentiment analysis platforms). Furthermore, absence of any standardized dataset in terms of Hinglish text and the informal nature of Hinglish texts further complicate task for building good translation systems. Hybrid NLP systems achieve promising results for Hinglish by utilising rule-based, statistical and neural techniques but investigations in this way are rare especially on informal data and concurrent Hindi-English translation. We propose a method to overcome these challenges by developing a hybrid translation model to convert Hinglish text parallelly into pure Hindi and English. Through the use of preprocessing (f, g)-compositions (e.g., normalization and language identification), transformer-based models, as well as crosslingual embeddings and featurization elements, it aims to generate precise and contextually faithful translation possibilities.

B. Objectives

The main objectives of this project are as follows:

- 1) To design and implement a hybrid translation system that converts code-mixed Hinglish text into pure Hindi and English outputs.

- 2) To develop a pipeline for preprocessing, so as to normalize the Hinglish text by converting phonetic spellings/slang and mixed grammatical structures.
- 3) To exploit some transformer-based models and cross-lingual embeddings in order to enhance translation quality for Hinglish text, type formal as well as informal.
- 4) To examine the system's performance across various types of corpora including social media text to confirm robustness and generalization.
- 5) To overcome the drawbacks of other systems by building a multilingual translation framework where automatic Hindi and English translations are generated simultaneously.

C. Purpose, Scope, and Applicability

- 1) *Purpose*: The goal of this work is the construction of a real-time end-to-end translation system that can be scaled to any form of Hinglish by replacing word sequences and still promise to preserve fluency and expressiveness between multilingual speakers. By converting the code-mixed text to pure Hindi and English, the system aims for enabling applications in social media analytics, automated customer support, and educational systems which require understanding or generation of pure language outputs.
- 2) *Scope*: This project would involve building an end-to-end system for translating Hinglish text, which involves several subtasks: preprocessing Hinglish data, language identification between Hindi and English in a piece of text (which can be a sentence or a word), normalization, translation from Hinglish to pure Hindi and English. The model is based on text sourced from social networks, casual conversation, and formal use choosing among them phonetic transformations or slang or code-switching patterns. The project is based on existing NLP tools and libs (Python/Pytorch/Hugging Face/API methods), as well as crosslingual models like XLM-R or mBART. The system is also restricted to text translation and does not include verbal or real time translation at the present (though it was designed for expansion).
- 3) *Applicability*: Our proposed TL-system is suitable for versatile applications over the multilingual digital scene of India. This new feature can be integrated into a social media to eliminate analysis translation for the user created content (Hinglish) which significantly improve the SPM and OCM. In customer service, the technique could allow chatbots to understand queries in complex Hinglish and communicate in pure Hindi or English for a better user experience. In customer service, the system could be used to help chatbots comprehend Hinglish queries and respond in pure Hindi or English and improve user experience. In the field of education, it can be used for conversion of Hinglish study materials & conversational content from non-standardized mediums to standardized form in order to make them easily available throughout India.

D. Organization of Report

This report is structured as follows: Section II presents the literature survey; Section III conducts requirement analysis and methodology; Section IV details system design; Section V describes implementation; Section VI presents results and findings; and Section VII concludes with a discussion and future scope.

II. LITERATURE SURVEY

The investigation of code-mixing in languages such as Hinglish and translating from them to purist forms has become an emerging research theme in natural language processing (NLP) due to multilingual digital communication which is being promoted now-a-days in India. We surveyed 20 such studies, reported between 2020 and 2024, that address translation systems on Hinglish to Hindi and/or English (hybrid methods as well), as well as data issues and informal use cases like social media.

A. Base Paper: HiPHET

The research is done by Attri et al. (2020) [1], which is titled "HiPHET: A Hybrid Approach to Translate Code Mixed Language (Hinglish) to Pure Languages (Hindi and English)" is the base for this review. The authors present HiPHET, a novel computational model which marries statistical and rulebased methods for translating Hinglish into clean Hindi and English with 91 percentage and 84 percentage accuracy on Hindi and English. This approach commences with a partial preprocessing phase in which language identification and morphological analysis (doing brown clustering for rigid word formation in Hinglish) breaks the ambiguous and composite structure of Hinglish text.

However, in spite of the advantages, the HiPHET model also suffers from several drawbacks. However, a key drawback is the lack of neural integration, thereby not being portable to real-time and increasingly complex/modern examples of Hinglish use (eg slang, non-standard transliterations eg phir- ěfir).

This space could affect its efficiency when applied to dynamic user-generated content popular on platforms such as Twitter or Instagram.

B. Hybrid Approaches for Hinglish Translation

Hybrid models that combine rule-based, machine learning and neural techniques have been very successful at dealing with complexities of Hinglish. Jadhav et al. (2022) [2] propose pipeline for Hinglish-English translation pipelines using morphological analyzer and crossmorphological analysis, targeting structured code-mixed text. Similarly, Liu et al. (2022) [3] propose a system for WMT 2022 shared task using mBART together with preprocessing and language transliteration, resulting in extracting high ROUGE-L and WER scores for Hinglish to English.

Mahata et al. (2024) [6] study syntactic rules of codeswitching in Hinglish with hybrid models to reach (95%) for language identification, and discuss implications for translation. Sinha and Thakur (2020) [8] present a transfer-based model for Hinglish to Hindi and English, focusing on morphological conversion. These studies underscore the value of hybrid methods but often limit focus to single-language outputs or outdated techniques without modern transformers.

C. Data Generation and Corpus Development

The scarcity of data has been a major problem in the translation of Hinglish. Srivastava and Singh (2023) [4] construct a parallel corpus of 13,738 Hinglish sentences and suggest a pipeline based on Google Translate for Hinglish to English along with augmented transfer learning in comparison. Agarwal et al. (2021) [9] The cover generation of code-mixed Hinglish sentences from English, with translation as sub-tasks. Hence we acknowledge that when we improve the corpus, but the datasets remain small and do not fully support bidirectional translation.

D. Language Identification and Preprocessing

The main roles is to find correct language for best translation. An IEEE Access study (2024) [7] reviews techniques for code-mixed text, including Hinglish, using hybrid neural and non-neural methods, noting data scarcity challenges. Goyal et al. (2020) [17] develop a syntactic parser for Hinglish, handling code-switching structures to aid translation.

E. Research Gaps

The reviewed studies reveal several gaps that this project aims to address:

- **Limited Bidirectional Translation:** Most focus on Hinglish to English, lacking simultaneous Hindi outputs.
- **Data Scarcity:** Small corpora limit robustness, especially for informal text.
- **Handling Informal Variations:** Non-standard transliterations and slang are underexplored.
- **Neural Integration:** Older studies miss transformer advancements.
- **Scalability:** Few extend to other code-mixed languages or real-time applications.

III. REQUIREMENT ANALYSIS AND METHODOLOGY

A. Problem Definition

Hinglish, is a language variation challenging to translate in its own way (not only because of syntax derived from Hindi and vocabulary borrowed from English) because it combines phonetic spelling of some words (eg: "fir" for phir) and slang terms (eg: "jhakasa" for awesome.). The mixed syntax and context dependent semantics of Hinglish are not handled well by typical monolingual MT systems, leading to low accuracy (e.g., 60 BLEU scores for informal) accuracies.

The problem is compounded by:

- **Limited Datasets:** There are less no. of annotated content is present for hinglish.
- **Linguistic Variability:** Due to place and platform variations, there is increased diversity.
- **Underreporting of Errors:** Translation errors in informal text are frequently overlooked.

B. Requirement Specification

1) Functional Requirements: The system must:

- Import Hinglish text from diverse sources (CSV, JSON, plain text)

-
- Clean inputs by removing noise (emojis, hashtags)
 - Perform bidirectional translation to Hindi and English
 - Achieve 95% accuracy in language identification
 - Generate interactive plots and exportable reports

2) *Non-Functional Requirements:*

- **Performance:** Process 1,000 sentences in 2 minutes
- **Accuracy:** Achieve 80% BLEU score
- **Scalability:** Handle datasets up to 100,000 sentences
- **Usability:** Web-based interface accessible to non-technical users
- **Security:** Comply with data protection regulations

3) *Software Requirements:*

- Operating System: Ubuntu 20.04+ or Windows 10/11
- Programming Language: Python 3.8+
- Libraries: PyTorch, Hugging Face Transformers, NLTK, spaCy, Scikit-learn
- Development Tools: Jupyter Notebook, VS Code, Git
- Database: SQLite for storing datasets and logs

4) *Hardware Requirements:*

- Processor: Intel Core i5 or equivalent (2.5 GHz+)
- RAM: 16 GB minimum
- Storage: 500 GB SSD
- GPU: NVIDIA GPU with 8 GB VRAM recommended

C. *Planning and Scheduling*

The project follows a 6-month timeline:

- **Phase 1 (Month 1):** Research and Planning
- **Phase 2 (Month 2):** Data Collection and Preprocessing
- **Phase 3 (Months 3-4):** Model Development
- **Phase 4 (Month 5):** Testing and Validation
- **Phase 5 (Month 6):** Reporting and Documentation

D. *Methodology*

The comprehensive research and development methodology is illustrated below:




Fig. 1: Flowchart of the proposed hybrid Hinglish translation methodology.

TABLE I: Summary of Key Studies on Hinglish Translation

Title	Year	Authors	Description	Gap
HiPHET	2020	Attri et al.	Bidirectional translation using hybrid methods; 91% Hindi accuracy	Limited neural integration; poor formal text handling
Code-Mixed Framework	2022	Jadhav et al.	Pipeline with morphological analyzers for Hinglish–English	No Hindi output; lacks real-time focus
Gui at MixMT	2022	Liu et al.	mBART-based system for Hinglish–English	Roman script only; no Hindi translation
Multilingual TTS	2023	Dhoundiyal et al.	TTS system with translation components	Limited text translation evaluation
Machine Translation	2020	Sinha & Thakur	Transfer-based translation to Hindi and English	Outdated; limited informal handling

IV. SYSTEM DESIGN

A. System Architecture

The Hinglish translation system is designed as a modular pipeline integrating rule-based, statistical, and neural methods. The system comprises five key modules:

- 1) **Input Module:** Accepts Hinglish text from diverse sources, validates formats, removes noise, and tokenizes text using SentencePiece.
- 2) **Preprocessing Module:** Performs language identification, normalization, and feature extraction using XLM-R model with 95% accuracy.
- 3) **Translation Module:** Integrates three approaches:
 - Rule-based: Applies syntactic rules for grammar correction
 - Statistical: Uses Moses for probabilistic word alignments
 - Neural: Employs mBART for contextual translation
- 4) **Output Module:** Formats translations into Hindi (Devanagari) and English (Latin), with post-processing rules for error correction.

- 5) **Knowledge Retention Module:** Implements simplified Elastic Weight Consolidation mechanism to preserve critical model weights.

B. Database Schema Design

The system uses SQLite database with the following tables:

- **Text Table:** Stores input Hinglish text (TextID, Hinglish- Text, Source, Timestamp)
- **Translation Table:** Stores translations (TranslationID, TextID, HindiText, EnglishText)
- **Dictionary Table:** Maps non-standard spellings (DictID, Original, Normalized)
- **Log Table:** Records performance metrics (LogID, Text- tID, Metrics, ErrorDetails)

C. User Interface Design

The web-based UI built with Streamlit features:

- Input section for text entry or file upload
- Side-by-side display panels for Hindi and English trans- lations
- Control buttons for translation options
- Metrics visualization dashboard
- Export functionality for results (CSV, PDF, JSON)

D. Algorithm Design

Algorithm 1 Hinglish Translation Algorithm

Require: Raw Hinglish text

Ensure: Hindi and English translations

```

1: tokens ← preprocess (text)
2: rule_based ← apply_syntactic_rules (tokens)
3: stat_align ← moses_align (rule_based)
4: neural_trans_hi ← mbart_translate (stat_align, 'hi_IN')
5: neural_trans_en ← mbart_translate (stat_align, 'en_XX')
6: return format_output (neural_trans_hi, neural_trans_en)

```

E. Security Measures

- Data anonymization through hashing
- Role-based access control using OAuth
- HTTPS for secure transmission, AES-256 for storage
- SQL injection prevention through parameterized queries
- Comprehensive audit trail logging

F. Test Case Design

TABLE II: Test Case Design

Test Level	Input	Expected Output
Unit Test	"Main book read kar raha"	Cleaned tokens
Integration	100 sentences	Seamless data flow
System	1,000 sentences	BLEU $\geq$ 0.80
Edge Case	"Bhai, yeh event kit tha"	Correct slang handling
Performance	10,000 sentences	Processing $\leq$ 5 minutes

V. IMPLEMENTATION

A. Experimental Setup

- **Hardware Setup:** Intel Core i5 processor, 16 GB RAM, 500 GB SSD, with optional NVIDIA GPU support.

- **Software Environment:** Python 3.10, PyTorch, Hugging Face Transformers, and supporting NLP libraries.
- **Dataset Composition:** Approximately 10,000 custom Hinglish sentences from social media, along with the Srivastava & Singh corpus.
- **Data Split:** 80% training, 10% validation, and 10% testing.

B. Framework Implementation

A Streamlit-based web interface allows users to input text, upload files, view translations, and store results in an SQLite database.




Fig. 2: Flowchart of the hybrid NLP-based Hinglish translation framework and system workflow.

C. Experimental Procedure Algorithm

The experiments were conducted in an orderly manner:

Algorithm 2 Experimental Procedure Algorithm

Require: Hinglish dataset

Ensure: Evaluated translation results

1: Collect and clean the Hinglish dataset

2: Preprocess Hinglish sentences

3: Train and fine-tune neural translation models

4: Execute the hybrid translation pipeline

5: Store translation outputs and evaluation metrics

6: Compare results with existing translation systems

VI. RESULTS AND FINDINGS

A. Experimental Outcomes

Empirical study shows that the hybrid combination of rule-based, statistical and neural translation is promising for the code-switching translation. The system manages to handle problems such as obscure grammar and unconventional alpha-bet. The results suggest that hybrid NLP systems could be easily extended to work for multilingual countries like India, and may serve as a foundation toward building social media analytics, customer support chatbots and educational tools.

B. Evaluation Metrics

The system was evaluated using standard metrics: TABLE III: Translation Performance Metrics

Metric	Hindi Output	English Output
BLEU Score	0.82	0.80
ROUGE-L	0.78	0.76
WER	14.5%	15.2%

These scores indicate high translation quality for a low- resource, code-mixed language.

C. Comparison with Existing Work

The system was compared with Google Translate and earlier hybrid approaches:

Table IV: Comparison with Existing Systems

System	BLEU Score
Google Translate	0.74
HiPHET (2020)	0.76
Proposed System	0.82

The proposed system outperformed existing solutions, particularly in handling slang and mixed grammar.

D. Key Findings

- The hybrid approach significantly improves Hinglish translation accuracy
- Data preprocessing and normalization are crucial
- Neural models benefit from rule-based and statistical support
- Simultaneous Hindi-English output is more effective than single-target translation

VII. DISCUSSION AND CONCLUSION**A. Discussion**

The empirical results show that the hybrid system of rule-based, statistical and neural translation is beneficial in terms of translation effectiveness for code-switching. The system is successful at tackling problems like obscure grammar and unorthodox alphabet. Results indicate that hybrid NLP systems can be readily adapted in multilingual countries such as India, and can be used as a basis for social media analysis, customer support chatbots and educational tools.

Limitations: We acknowledge some limitations of our study; such as the scarcity of large, high-quality Hinglish data sets, computational requirements for transformer models and suboptimal performance for excessively slang heavy or novel expressions.

B. Conclusion

Summary This work has achieved in the designing and developing a hybrid Hinglish translation system for codemixed text that can translate the codemixed text to pure Hindi and English with proficiency. The system obtained higher scores than available tools with BLEU of 0.82 on Hindi side and 0.80 on English side by adopting pre-processing steps and multi translation models in combination.

Major Contributions:

- Development of a robust hybrid translation pipeline
- Creation of a preprocessing framework for Hinglish normalization
- Simultaneous bilingual translation capability
- Improved accuracy on informal and real-world text

C. Future Scope

Possible Extensions:

- Extension to other Indian code-mixed languages (Benglish, Tamlish)
 - Integration with speech-to-text and real-time translation
 - Larger scale fine-tuning with user feedback loops
- Recommendations for Future Research:

- Creation of standardized Hinglish benchmarks
- Exploration of lightweight transformer models
- Inclusion of sentiment-aware and context-adaptive translation

ACKNOWLEDGMENT

The authors would like to express sincere gratitude to Dr. Anju Kapoor, Principal, and Dr. Smruti Nanavaty, Vice- Principal, for providing the opportunity to conduct this research. Special thanks to Dr. Prashant Chaudhary for constant guidance and supervision, and to Mrs. Sunita Gupta for valuable feedback and support. We are also grateful to the IT Department faculty of SVKM's Usha Pravin Gandhi College for their encouragement throughout the project.

REFERENCES

- [1] S. H. Attari, T. V. Prasad, and G. Ramakrishna, "HiPHET: A hybrid approach to translate code mixed language (Hinglish) to pure languages (Hindi and English)," 2020.
- [2] I. Jadhav et al., "Code-mixed Hinglish to English language translation framework," 2022.
- [3] Y. Liu, J. Gu, N. Goyal et al., "Gui at MixMT 2022: English-Hinglish: An MT approach for translation of code mixed data," 2022.
- [4] V. Srivastava and M. Singh, "Improving Indic code-mixed to monolingual translation using mixed script augmentation, generation & transfer learning," 2023.
- [5] S. Dhoundiyal et al., "A multilingual text to speech engine Hindi- English: Hinglish," 2023.
- [6] S. K. Mahata et al., "Analyzing code-switching rules for English-Hindi code-mixed text," 2024.
- [7] IEEE Access, "A systematic review on language identification of code-mixed text: Techniques, data availability, challenges, and framework development," 2024.
- [8] R. M. K. Sinha and A. Thakur, "Machine translation of bilingual Hindi- English (Hinglish) text," 2020.
- [9] V. Agarwal et al., "Towards code-mixed Hinglish dialogue generation," 2021.
- [10] Anonymous, "Quality evaluation of the low-resource synthetically generated code-mixed Hinglish text," 2022.
- [11] TECHSSN1, "Emotion classification in Hindi-English code-mixed dialogue using transformer-based models," 2024.
- [12] Anonymous, "IASBS at SemEval-2024 Task 10: Delving into emotion discovery and reasoning in code-mixed conversations," 2024.
- [13] P. Sailaja, "Hinglish: Code-switching in Indian English," 2020.
- [14] K. Thakre, "Transliteration for low-resource code-switching texts: Building an automatic Cyrillic-to-Latin converter for Tatar," 2020.
- [15] K. Thakre, "A novel approach to synthesize Hinglish text to English text," 2020.
- [16] M. Bansal and D. K. Lobiyal, "Incorporating distinct translation system outputs into statistical and transformer model," 2020.
- [17] P. Goyal and M. R. Mital et al., "A bilingual parser for Hindi, English and code-switching structure," 2020.
- [18] S. N. Sridhar, "Word-level language identification in bilingual code-switched texts," 2020.
- [19] University of Edinburgh, "The University of Edinburgh's submission to the WMT22 code-mixing shared task (MixMT)," 2022.
- [20] G. Lee and H. Li, "Code-switching sentence generation," 2020.

COMPARING YOLOv8 AND YOLOv9 FOR SNAKE CLASSIFICATION INTO VENOMOUS AND NON-VENOMOUS CATEGORIES

Om Rawal and Neha Vora

Department of Information Technology SVKM's Usha Pravin Gandhi College of Arts, Science and Commerce
Mumbai, India

ABSTRACT

The categorization of snakes and a key task which is for medicine to aid in their identification of Venomous species or conservation of wild life to determine their abundance and distribution in various habitats. Proper identification which in turn can prevent death from snake bites and help in conserving biodiversity. Recent Deep in the field of object detection (e.g. YOLO). Sequence of studies which have also reported very efficient and reliable classification. The paper reports a comparison of Study of the work done on YOLOv8 and YOLOv9 in the field of snake classification. YOLOv8 which is fast and efficient, great for real time Applications which at times see issues in complex background and different lighting conditions and partially occluded objects.

Index Terms—Snake classification, venomous, non-venomous, YOLOv8, YOLOv9, object detection, real-time applications, deep learning, transformer architecture, wildlife monitoring.

I. INTRODUCTION

Public health and wildlife management depend upon correct identification of venomous versus non-venomous snakes. Snakebites represent a major medical problem in many parts of the world, especially rural and tropical regions where venomous snakes often live causing human fatalities or at risk for serious injuries. The WHO estimates that about 5.4 million snakebites occur around the world each year, leading to up to 2.7m envenomings and over 100,000 deaths. Hence if venomous snakes are identified and classified correctly there could be a great reduction in the death toll as those individuals can timely be administered proper medical treatments. Pit vipers also help keep other snakes and many rodents in check, so proper identification is necessary to avoid the wanton killing of non-venomous species as well as to provide timely medical treatment if an envenomation accident occurs.

Because this involves some specialist knowledge and manual identification, not always available in the increasing number of areas monitored remotely for snakes. Advances in the fields of computer vision and deep learning have enabled the creation of automated systems for snake classification using large volumes of data processed in real-time. These can be deployed in different environments — for example they can

be part of a mobile app for hikers, installed in a sensor box which is left and sampled by itself at an automated monitoring system in wildlife reserves or used on drones that conduct habitat monitoring.

The You Only Look Once (YOLO) family of models is one such leading framework among the numerous algorithms for object detection and classification. YOLO (You Only Look Once) models are well-known for being able to detect objects within an image quickly, accurately, and in real-time, which is why they make good candidates for the snake classification task. A YOLO model works in such a way that it processes the whole image at once through the network and simultaneously predicts both bounding boxes of objects and their class labels. This enables quick and efficient classification, even on devices with modest computational power.

YOLOv8 is the latest model arrival on YOLO versions and it has received attention for being fast and maintaining moderate accuracy. With its lightweight architecture and low memory requirements, provides an attractive means to implement real-time applications that require minimal footprint, e.g. smartphones or drones. On challenging environments, YOLOv8 performance is questionable, especially with many changes in light conditions, snake orientation and occlusions.

One of the results is YOLOv9 which is improvements in architecture and transformer layer added to capture context information. For instance, in image understanding transformers have changed many areas of machine learning transforming models by enabling them to understand how different parts of an image relates. For example: while a standard YOLOv9 object detector should not be directly usable for snake classification, the network architecture could—when deployed somewhere sorted out by its design—highlight even minor-difference features like head shape or scale patterns (both of which can be very indicative of venomous species or non-venomous ones).

This is study comparison for YOLOv8 and YOLOv9 on snake classification. YOLOv8 — Best real-time object detection with faster inference time (intended for software develop-

ers) YOLOv9 — For highest accuracy with robustness against more complex environments In this paper, we seek to compare these models in terms of different performance metrics such as accuracy, speed, memory consumption and generalization which will provide a clue towards the fact that which model is best suited for this snake classification task under what circumstances These are promising results for the potential development of snake detection technologies and therefore public safety from a conservation perspective.

II. RELATED WORK

Object detection and classification have been developed with a great help of deep learning techniques. It has a wide range of applications in the identification of wildlife species, including snake classification. Walder and Maeder showed the potential of convolutional neural networks for species classification. It was found that though the CNNs performed well in distinguishing species, these models were computationally expensive and hence not suitable for real-time applications. Mohapatra et al. [2] applied CNN to identify snakes, with an overall accuracy of more than 80% in categorizing venomous and non-venomous snakes, and concluded that snake classification is one of the most important things for public safety.

While CNNs worked well for static image classification, object detection required models with the capability of carrying out both classification and location, hence the development of more efficient models like You Only Look Once. Redmon et al. [3] proposed the YOLO—a real-time object detection model that revolutionized the field of object detection by considering the whole image in only one pass. Its approach to simultaneously predict the bounding box and class label gave an enormous speed advantage for YOLO over any other models, making it perfect for applications regarding monitoring wildlife or autonomous systems.

YOLOv3: In YOLOv3, Redmon and Farhadi managed to move closer to or even surpass state-of-the-art detectors on the standard detection task by implementing Darknet-53 for feature extraction.

YOLOv4: Bochkovskiy et al. [5] proposed a model with further architectural improvements, including better data augmentation and anchor-based detection, which gave a better balance of speed and accuracy.

Though YOLOv5 was not an official version, it was widely adopted because it was much easier to use and more optimized in performance, especially at resource-constrained devices [6]. Then, YOLOv6 and YOLOv7 further pushed real-time detection limits with anchor-free detection and decoupled head structure, respectively, but were more computationally expensive [7]. These have been furthered by YOLOv8, with the main focus lying in speed and efficiency for real-time uses when resources may be quite a big concern. However, for YOLOv8, complex environments, such as variable lighting or occlusion, may pose a challenge. On the other hand, YOLOv9 introduces transformer-based architectures, first popularized by Vaswani et al. [8], in natural language processing, shown to further enhance image classification tasks through a great catching of long-range dependencies.

Transformed features are more exposed with transformers within YOLOv9, therefore making it highly effective for subtle feature detection, which is important in snake categorization solely based on aspects like scale patterns and head shapes, in order to discern the venomous from the non-venomous poisonous species. Several comparative studies reviewed different YOLO models for various applications. The works of Jocher et al. [9] compared YOLOv4 and YOLOv5, stating that the latter had better speed without losing much accuracy. Correspondingly, Wong et al. [10] showed that YOLOv7 outperformed its lower versions on certain challenging detection tasks with more developed architectural features, although this came at the cost of higher computation. Based on the findings of the studies examined, during the evolution of YOLO models, improvement in the increase of speed, accuracy, and robustness is a trade-off. This therefore lays a foundation for the comparison between YOLOv8 and YOLOv9 in snake classification.

III. METHODOLOGY

This section describes how the dataset was formulated and creative details of the object detection models chosen as well as the setup used to analyze differences between YOLOv8 and YOLOv9 when they classify snakes as venomous vs non-venomous. Every resolution defined containing a comparison between the two models using all these steps under the same conditions, so that the outcome is unbiased and appropriate.

A. Dataset Formulation

Data Sources: Secondary Data -The study dataset was collected from secondary sources (publically available datasets from wildlife organisations and academic institutions or snake research repositories. The dataset contains labelled images of venomous and non-venomous snake species.

The images are of varied quality, resolution as well as they include environmental diversities like lighting clutter and occlusion that represent a real-world setting where the models must be generalizable to withstand these alterations. The dataset contains approximately 10,000 images, split into two primary categories:

- **Venomous Snakes:** Species including cobras, vipers, and rattlesnakes (5,000 images)
- **Non-Venomous Snakes:** Species including pythons, garter snakes, and corn snakes (5,000 images)

snakes. Each image is annotated with the bounding boxes for marking the snake location and its bounding box region and an associated venomous/non-venomous label. The dataset was split into training, validation and testing with a partition of 70:20:10 making sure that the venomous as well nonvenomous categories were proportionally present across all three splits

B. Object Detection Models

YOLOv8 and YOLOv9 were the two object detection models selected for this study. Both models belong to the YOLO family, known for their real-time object detection capabilities, but they have different architectures and optimization techniques. YOLOv8 is the fastest and most efficient of all the YOLO versions, it was designed for real-time detection on low-powered hardware. CNN architecture has a traditional role in optimizing accuracy and speed trade-off. The YOLOv8 is incredibly light weight which makes it very well suited for mobile/embedded systems where computation power can be a limit. YOLOv9: The next milestone in the YOLO family, YOLOv9 introduces transformer-based layers to improve feature localization and context understanding. Through the use of transformers, which have been prevalent in image and natural language processing workloads, YOLOv9 is able to model long-range dependencies and fine-grained textures essential for disambiguating between visually similar objects (e.g. snakes). YOLOv9's architecture improves accuracy, particularly in complex scenarios involving occlusions or varying lighting conditions, though it requires slightly more computational resources than YOLOv8.

C. Experimental Setup

Both models were trained and evaluated under identical conditions to ensure a fair comparison. The experiments were conducted on a high-performance computing system of google Collab with using T4-GPU, which allowed for efficient training of both models. Some of the important parameters for experimental setup is: Length of training: Both models were trained for 60 epochs to have a balanced sharing of the data during learning phase without over fitting. Batch Size: 16 batch sizes for our models and massive learning rate were chosen, which was a good balance between memory usage (and therefore speed) in the data pipeline. Image Size: All input frames are resized to 416x416 pixels because it is the common input size for YOLO models and this guarantees consistency across both models. Optimizer: Used Adam as an optimizer with default learning rate parameters which turned out to be good trade-off between convergence and generalization. Loss Function: The two models used the same object detection loss function (combining classification loss in venomous vs. non-venomous classes with bounding box regression loss for accurate snakes' locations on images). Metrics: The models were subjected to tests based on Accuracy, Recall Precision, Inference Speed, and memory usage. The effectiveness of the models was tested to their extreme such as with a king cobra partially hidden within grass or obtained during night time.

D. Training Procedure

The training regime was designed to achieve best results for both YOLOv8 and Dataset images were resized to 416x416 size and normalized. Before Passage of the models. We applied to the images augmentations which included random rotations, Flipping and brightness tweaks to represent real world scenarios. Generalization, Augmentations improve model performance in diverse lighting conditions and conditions of occlusion. Both models used transfer learning with weights from pre-trained COCO which Improved performance and generalization for a small dataset of that of snakes The training process was structured to ensure optimal performance for both YOLOv8 and YOLOv9, following a similar pipeline to guarantee consistent results across models. The Models were fine-tuned so that they would know how to interpret images for video input and classify the snake in the frame correctly. Training process: The model is trained using the Adam optimizer with an initial learning rate of 0.001. One thing to note is that when the validation loss does not decrease for 5 epochs in a row, a learning rate scheduler based on 0.1x factor is used. This has been useful in preventing. Validation: Each 5 passes through the data, the models were validated on the 20check. Which are the best performing. We saw to accuracy, precision, recall and Intersection over Union (IoU). Also for [currx] we see that which models perform best in terms of classification. After each iteration of the epoch the models were validated on the 20their progress.

We tracked accuracy, precision, recall, and Intersection of Union (IoU). Also which was applied to evaluate both the models. Classification of and which they do at localizing the snakes in images. This method has been useful in preventing overfitting and ensuring that the models reached convergence efficiently.

E. Evaluation Metrics

Model performance was assessed using standard object detection metrics:

- **Precision:** Ratio of true positive detections to total positive predictions
- **Recall:** Ratio of true positive detections to actual positive instances
- **mAP50:** Mean Average Precision at IoU threshold of 0.5
- **mAP50-95:** Mean Average Precision averaged across IoU thresholds from 0.5 to 0.95
- **Inference Speed:** Processing time per image
- **Model Size:** Memory footprint for deployment considerations

IV. RESULTS AND DISCUSSION

A. Dataset Preparation and Augmentation

Figure 1 defines the annotation process using the RoboFlow platform, where bounding boxes were drawn around snakes to indicate their respective classes (venomous or non-venomous). To achieve high accuracy the custom annotation is best.




Fig. 1. Example of image annotation with bounding boxes indicating snake class (venomous/non-venomous) using the RoboFlow platform.

For increasing the variety of dataset we augmented images. Figure 2 demonstrates horizontal and vertical flipping applied to training images, while Figure 3 shows random cropping within 25%-75% range both vertically and horizontally. This augmentation method is helpful to the model for understanding the complex hidden pattern present in images and also improves the generalization.



Fig. 2. Data augmentation examples showing horizontal and vertical flips applied to training images.



Fig. 3. Random cropping augmentation within the 25%–75% range applied both vertically and horizontally.

B. Model Training Architecture

Figure 4 presents the training flowchart for the pre-trained YOLOv8 network. Dataset Preparation → Model Initialization (COCO Pre-trained Weights) → Training with Data

Augmentation → Periodic Validation → Model Check-pointing.




Fig. 4. Training flowchart of the pre-trained YOLOv8 network illustrating the pipeline from dataset preparation to model deployment

C. Detection Results

Figures 5 and 6 states the detection capabilities of both models on test images. YOLOv9 accurately detects a venomous snake even in a complex background, while YOLOv8 correctly identifies and localizes a non-venomous snake with clear and precise bounding boxes.



Fig. 5. YOLOv9 detection of a venomous snake in a complex background, illustrating robust performance under challenging visual conditions

D. Training Performance Analysis

Figures 7 and 8 present comprehensive training performance metrics for both models. The graphs display loss curves (box loss, class loss, and detection loss) along with precision, recall, and mAP metrics across training epochs.

Both models exhibited similar trends in loss curves, with training and validation losses decreasing over time, indicating successful learning. However, several key differences emerged:

- **Training Losses:** YOLOv9 shows slightly lower training loss, which means it learns faster and is optimized more effectively.



Fig. 6. YOLOv8 detection of a non-venomous snake, showing accurate classification and localization.

- **Validation Losses:** YOLOv9 have lower validation losses, this indicating superior generalization to unseen data
- **Precision and Recall:** Both models showed increasing trends, but YOLOv9 maintained higher values throughout training
- **mAP Scores:** YOLOv9 consistently achieved higher mAP50 and mAP50-95 values, demonstrating more accurate object detection and classification

E. Confusion Matrix Analysis

In order to assess how well the models can differentiate between venomous and non-venomous snakes, a confusion matrix was created. The confusion matrix shows the counts of true positives, false positives, true negatives, and false negatives for each class. We can refer the Figures 9 and 10 for the analysis. The colour intensity and numbers in each box show how many were classified correctly (or incorrectly) as a certain class. The boxes along the diagonal are the ones that should be higher because they are correctly classified. The boxes that are not diagonal should be low as they are incorrectly classified. The overall confusion matrix shows that the model is able to classify the non-venomous snakes correctly, although the model appears to have difficulty correctly classifying background cases.

Analysis of confusion matrices reveals:

- Both models performed well in classifying non-venomous snakes with high true positive rates along the diagonal
- YOLOv8 struggled slightly with classifying venomous snakes in occluded or low-light conditions, showing some misclassifications
- YOLOv9's transformer-based architecture handled edge cases more effectively, with fewer misclassifications in complex scenarios.
- Both models showed some difficulty accurately identifying background instances, though YOLOv9 performed marginally better.

F. Quantitative Performance Comparison

Table I retrieves all performance metrics for both models. YOLOv9 outperformed YOLOv8 via all accuracy-related metrics, achieving 95% precision versus 92% for YOLOv8, 93% recall versus 90%, and 96% mAP50 versus 94%. These improvements are particularly significant for critical applications where misclassification of venomous snakes could have serious consequences.

TABLE I: Overall Performance Comparison of YOLOV8 and YOLOV9

Model	Precision	Recall	mAP50	mAP50-95
YOLOv8	92%	90%	94%	94%
YOLOv9	95%	93%	96%	96%

However, performance must be balanced with computational requirements. YOLOv8 demonstrated faster inference times, thus being more adequate for real-time applications where it is important that speed and computational resources are constrained. YOLOv9's improved accuracy comes at the cost of increased computational complexity due to transformer layers, requiring more powerful hardware for deployment.

G. Discussion

The experimental results reveal important trade-offs between YOLOv8 and YOLOv9 for snake classification:

Table II: Comparison of YOLOV8 and YOLOV9 Models

Model	Key Advantages
YOLOv9	Higher accuracy under challenging conditions such as occlusion and variable lighting. Demonstrates better generalization to unseen data with lower validation loss. Employs transformer-based architecture for robust feature extraction. Achieves higher precision and recall, making it suitable for safety-critical applications.
YOLOv8	Faster inference speed, making it suitable for real-time applications. Requires lower computational resources, enabling deployment on edge devices. Smaller model size supports mobile and embedded systems. Provides adequate accuracy for many practical scenarios.

The table no. II shows choice between models should be guided by application requirements. For critical use cases, YOLOv9 is a good choice because it has the highest accuracy. For resource-constrained deployments, such as mobile applications, embedded systems, or scenarios requiring rapid decision-making, YOLOv8 provides an excellent balance of performance and efficiency.




Fig. 7. Loss curves and performance metrics for the YOLOv8 Medium model trained on the snake classification dataset over 100 epochs.




Fig. 8. Loss curves and performance metrics for the YOLOv9 Medium model trained on the snake classification dataset over 100 epochs.




Fig. 9. Confusion matrix for YOLOv8, showing classification performance across venomous, non-venomous, and background classes.




Fig. 10. Confusion matrix for YOLOv9, demonstrating improved classification accuracy, particularly in challenging scenarios.

V. FUTURE SCOPE

According to the comparison of YOLOv8 and YOLOv9 on snake classification, some future improvements can be considered to boost the performance of our method. One potential way to excel is enhancing model architecture by taking advantages of the fast inference power of YOLOv8 and strong feature extraction capacity of YOLOv9. Furthermore, methodologies such as model pruning, quantization and knowledge distillation can be used to achieve higher computational efficiency while maintaining reasonable accuracy. Accelerating attention mechanisms in a light weight level may contribute to a better feature learning with less computation time, which will result in more efficient and convenience models.

Another encouraging direction for future work is to enlarge the data and take the system into their real life applications. The addition of snake images from multiple geographic regions, as well as the inclusion of rare or endangered species has been suggested to increase model generalization and encourage conservation. The system can further include multi-modal data such as thermal or infrared images for enhancing the detection in low-lighting and dense environments. Additional utilizations in the wild include applications to identify snakes on smartphones, drone-based monitoring systems and wildlife surveillance platforms for real-time snake detection that can enhance public safety as well as ecosystem research. In summary, we believe that these future directions substantially extend the current work and create practical as well as socially beneficial possibilities.

VI. CONCLUSION

As per our observation, YOLOv9 appears to be a more suitable option for detecting snakes than YOLOv8. It learns more quickly, makes fewer mistakes and is generally more accurate. But we will need to do more testing to know for sure.” We need to see how well each model performs on real-world images and apply them to various data sets. We should also think about how fast they are, how computer-intensive, and how easy they are to apply in different cases.

We understand that YOLOv8 is useful for snap decisions, YOLOv9 is more appropriate for high-stakes work like wildlife protection. To improve these models even further, we could use more data, train on images augmented in other ways and adopt advanced techniques such as transfer learning from other models or using an ensemble of models. With more testing and experimentation, we will be able to make a better decision about which model is best for our particular purposes. There are also ways in which we can improve both models going forward.

Performance of YOLOv8 was compared to YOLOv9 in which a series of tests were conducted in the case of snakes between venomous and non-venomous. The YOLOv8 performed well in speed and real-time detection, while YOLOv9 exhibited better accuracy along with robustness especially in challenging scenarios. YOLOv8 is a good choice for applications which are particular speed-sensitive, including mobile uses and embedded systems. But for critical applications which require highest accuracy, like in wildlife monitoring and conservation YOLOv9 is better implementation. Tomography) the increasing better performance of model further improvement with including more data and utilizing advanced augmentation technique could be valuable.

REFERENCES

- [1] World Health Organization, “Snakebite envenoming,” WHO Fact Sheet, 2019. [Online]. Available: <https://www.who.int/news-room/fact-sheets/detail/snakebite-envenoming>
- [2] J. Redmon, S. Divvala, R. Girshick, and A. Farhadi, “You only look once: Unified, real-time object detection,” in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016, pp. 779–788.
- [3] G. Jocher, A. Chaurasia, and J. Qiu, “YOLOv8: A new state-of-the-art computer vision model,” Ultralytics, 2023. [Online]. Available: <https://github.com/ultralytics/ultralytics>
- [4] C.-Y. Wang, I.-H. Yeh, and H.-Y. M. Liao, “YOLOv9: Learning what you want to learn using programmable gradient information,” arXiv preprint arXiv:2402.13616, 2024.
- [5] J. Waldchen and P. Maeder, “Plant species identification using computer vision techniques: A systematic literature review,” *Archives of Computational Methods in Engineering*, vol. 25, no. 2, pp. 507–543, 2018.
- [6] S. Mohapatra, K. Bhuyan, D. Swain, and J. Nayak, “Venomous snake identification using deep learning,” *Journal of King Saud University - Computer and Information Sciences*, vol. 33, no. 3, pp. 318–328, 2021.
- [7] J. Redmon and A. Farhadi, “YOLOv3: An incremental improvement,” arXiv preprint arXiv:1804.02767, 2018.
- [8] A. Bochkovskiy, C.-Y. Wang, and H.-Y. M. Liao, “YOLOv4: Optimal speed and accuracy of object detection,” arXiv preprint arXiv:2004.10934, 2020.
- [9] G. Jocher, K. Nishimura, T. Mineeva, and R. Vilarin˜o, “YOLOv5,” GitHub Repository, 2021. [Online]. Available: <https://github.com/ultralytics/yolov5>
- [10] C. Li et al., “YOLOv6: A single-stage object detection framework for industrial applications,” arXiv preprint arXiv:2209.02976, 2022.
- [11] C.-Y. Wang, A. Bochkovskiy, and H.-Y. M. Liao, “YOLOv7: Trainable bag-of-freebies sets new state-of-the-art for real-time object detectors,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2023, pp. 7464–7475.
- [12] A. Vaswani et al., “Attention is all you need,” in *Advances in Neural Information Processing Systems (NeurIPS)*, 2017, pp. 5998–6008.
- [13] G. Jocher et al., “Comparative analysis of YOLOv4 and YOLOv5 for object detection,” *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 43, no. 11, pp. 4567–4580, 2021.
- [14] L. Wong, C. Yu, et al., “Comparative analysis of YOLOv6 and YOLOv7 for real-time object detection,” *IEEE Transactions on Image Processing*, vol. 31, pp. 2856–2869, 2022.

ANALYZING OCCUPATIONAL INJURIES AND DISEASES: A DATA-DRIVEN STUDY OF THE US WORKING-CLASS POPULATION USING OSHA DATA

Abhinav Kumar and Dr. Neelam Naik

Department of Information Technology, SVKM's Usha Pravin Gandhi College of Arts, Science and Commerce, Mumbai, Maharashtra 400056, India

ABSTRACT

In this paper the discussions is mainly about the injuries or diseases faced by workers in different fields of work no matter how small or big they are. Considering different work features in the data gained from OSHA so the work is on USA data for past 10 years and trying to learn from it different patterns so that it can be used to other countries outside USA too. In this dataset various features were focused on like location, work hour, type of work, age etc. to get the ideal risk assessment where the risk are separated into 3 categories of risk levels i.e high low and moderate according to risk involved in all these process. And performing different analysis techniques on the following dataset we understood different pattern in the dataset and also worked with different models such as k means, logistic regression, random forest etc. but we realize that K means is able to give the best output possible and works best with these kinds of data helping us to understand and react faster and more well to the work place problems faced by the workers overall in general

Keywords— OSHA data, workplace safety, occupational injuries, machine learning, classification, clustering, risk assessment, and data analytics

I. INTRODUCTION**A. Background**

Work safety is especially true for jobs that require a lot of work, where workers are often around machines, have to lift heavy things, and are in dangerous situations.

The information from OSHA inspections and injury records gives us a picture that helps us look at patterns of workplace risks in different industries and, over time, can use this information to understand workplace injuries and try to prevent them. Workplace injuries are still a concern and we need to keep looking at the data to stay safe.

Every year millions of workers around the world get hurt on the job because of things that can harm them at work. This has effects on the health of workers how much work they can do and their money. The International Labour Organization says that about 395 million workers have injuries that do not kill them and 330,000 workers die from workplace injuries. Workers and the International Labour Organization are concerned about workplace hazards and the International Labour Organization is working to make workplaces safer, for workers. The International Labour Organization wants to help workers and the International Labour Organization is trying to reduce the number of workers who get hurt at work.

Injuries happen every year. In the United States a lot of people work in jobs that're really tough on their bodies like construction, manufacturing and industrial work. This is why workplace injuries are a problem, in the US.

The Occupational Safety and Health Administration, which is a government agency collects a lot of information about injuries that happen at work. This information can really help all to learn about the type of injuries that people get on the job like muscular, bones, cuts or other types of hearing loss from loud noises, which are pretty common, in certain jobs. The Occupational Safety and Health Administration looks at all these types of injuries.

Old research papers primarily looks at the causes of injuries. They don't focus on identify trends when injuries will occur. This study attempts to focus on that issue. It employs a method of analyzing OSHA injury records to identify risky behaviors and identify patterns-based trends in various industries. This study accomplishes this by adhering to the project code's steps. The OSHA injury records are crucial to this research. In order to categorize risk behavior and find sector-specific patterns in OSHA injury records, the study examines these records.

Designing successful safety initiatives requires an understanding of the connection between job types and physical injuries. For example, manufacturing workers may experience accidents involving machinery, while construction workers are frequently at risk from falls and heavy lifting. Reilly et al.'s base paper [3] gives deep information, shows the prevalence of serious injuries necessitating hospitalization in manufacturing and construction.

B. Objectives

The project is driven by the following objectives:

- **Analyze OSHA Data:** To examine OSHA datasets to study sector-wise injury patterns and identify the types and prevalence of physical injuries across various job categories.
- **Perform Statistical Analysis:** To conduct exploratory and statistical analysis on injury attributes and workplace conditions.
- **Apply Machine Learning Classification:** To implement classification models (Logistic Regression, Random Forest, Gradient-Boosted Trees) to predict injury-risk groups etc .
- **Use Clustering Techniques:** To apply K-Means clustering to identify similar injury-pattern clusters and sector-level risk profiles.
- **Provide Analytical Insights:** To deliver data-driven insights that support workplace-safety evaluation and assessment.

C. Purpose, Scope, and Applicability

The main purpose of this project is to find out how different kinds of jobs are related to injuries that happen at work. The project will look at information from the Occupational Safety and Health Administration to see if there are any patterns. It will use computer methods to analyze the data. The goal is to learn more about how to keep workers safe. This project is about jobs and physical occupational injuries among workers. It will help us understand how to do safety assessments by looking at the data, from the Occupational Safety and Health Administration.

The scope of this work is pretty simple. We are looking at analysis and classification modelling of OSHA injury and inspection datasets. We are also doing clustering. The project is about injuries like MSDs, fractures, cuts and hearing loss from OSHA injury and inspection datasets. data. We are not talking about what this means for the economy or rules.

All the methods we used are things that we actually did in the project notebooks, for OSHA injury and inspection datasets. The study uses math and computer programs to look at data from different areas like construction, manufacturing, industrial work, logistics and agriculture. It uses things like statistics to understand the data from these sectors. The study looks at data, from construction, manufacturing, industrial work, logistics and agriculture to see what it can find out.

Applicability: The results of this study provide analytical insights relevant to stakeholders in the US occupational health ecosystem. The findings can support employers, policymakers, and occupational health professionals in their workplace safety assessment and evaluation processes.

II. LITERATURE SURVEY

A. Understanding of occupational injuries shows a critical intersection of public health, workplace safety, and economic policy. As industrialization continues to expand globally, particularly in developed economies like the US, understanding the patterns and causes of work-related injuries has become increasingly urgent. This literature survey examines key studies published between 2020 and 2024, providing a comprehensive foundation for analyzing occupational injuries within OSHA datasets.

B. Foundation Study: Understanding Severe Workplace Injuries

The work by Reilly et al. [3] titled "Evaluation of the characteristics of workers injured on the job requiring hospitalization" serves as the foundation for the main idea of this literature review. This study provides us with an understanding of serious work injuries that aligns with the OSHA data we are examining. OSHA data usually includes workers who need help. The study by Reilly et al. [3] is really important, for understanding OSHA data and serious work injuries.

Reilly and the other people who worked with him looked at the records from hospitals and the information about injuries that happened on the job to see if they could find any patterns among the workers. They wanted to understand what was happening to the workers so they studied the hospital records and the occupational injury surveillance data to find out. The workers were the focus of their study and Reilly and the others were trying to learn more, about the workers hospitalized due to workplace injuries. Their findings revealed that construction and manufacturing sectors demonstrate the highest rates of severe injuries, including fractures, amputations, and traumatic head injuries.

The study documented specific mechanisms of injury: falls from heights in construction environments and machinery-related accidents in manufacturing settings emerged as predominant causes of hospitalization-requiring injuries.

C. Musculoskeletal Disorders: The Hidden Epidemic

When we think about bad injuries we find out that musculoskeletal disorders are the most common type of injury that happens to people who work in jobs that are physically tough. Musculoskeletal disorders are a problem. Wang and his team looked at disorders that happen to construction workers. They wanted to see how the work that construction workers do affects their bodies. They found out that doing the motions over and over lifting heavy things and standing in weird positions are the main reasons why construction workers get musculoskeletal disorders. Musculoskeletal disorders are a deal because they can really hurt construction workers.

In order to understand injury causation from a variety of angles, Garcia et al. [5] conducted qualitative research on occupational injuries in manufacturing organizations using interviews with both workers and safety managers. According to their research, cuts, bruises, and sprains are frequently caused by inadequate safety instruction and poor workplace design.

Automation's effects on patterns of occupational injuries were investigated by Lee et al. [9]. Their findings showed a contradictory relationship: while automation decreased some conventional dangers, such injuries from heavy lifting, it also created new risks, such as injuries from malfunctioning robotic equipment and programming errors.

D. Systemic Challenges and Data Analysis

Martinez and his colleagues conducted a deep analysis to determine the obstacles to accurately documenting workplace injuries. They discovered that many employees keep their injuries to themselves. Because they don't want to get into trouble with the rules, the persons in control of the workplace may also fail to disclose these injuries. Martinez is attempting to determine why this occurs with injury data, as are the other individuals that collaborated with him.

Table I: Summary of Key Studies on Occupational Injuries

Study	Year	Focus	Key Findings
M.J. Reilly et al.	2022	Hospitalization-requiring injuries	Construction and manufacturing exhibit high severe-injury ratios
X. Wang et al.	2023	Musculoskeletal disorders (MSDs)	Repetitive manual tasks and load-bearing motions are primary contributors
P. Garcia et al.	2022	Manufacturing-related incidents	Lack of safety training and poor ergonomic design increase injury risk
Q. Zhang et al.	2022	Noise-induced hearing loss	Prolonged motor-equipment exposure leads to hearing damage
S. Martinez et al.	2020	Reporting behavior	Barriers to accurate injury documentation identified

III. METHODOLOGY

A. Problem Definition

Workplace hazards and occupational injuries continue to be a significant public health and economic concern, especially in labor-intensive and high-risk industries like construction, transportation, logistics, warehousing, manufacturing, and industrial operations. The International Labour Organization (ILO) estimates that there are over 395 million non-fatal occupational injuries worldwide each year, with about 330,000 fatal cases.

In the United States, OSHA collects detailed information about all aspects of occupational safety, such as injuries, accidents, hazards, exposure risks, safety violations and/or compliance, and incomplete reporting or unsafe working practices associated with the employer's character. OSHA's database of employers/employees includes information about injuries sustained by employees while at work; the causes of those injuries (e.g., machinery malfunction), the number of exposure incidents per year; the types and number of violations of the Occupational Safety and Health Act; and the nature and extent of non-compliance with the Act.

Even with thousands of reported incidents per year through OSHA, there are still several major analytical voids:

-
- There is an inability to identify injury trends specific to each unique sector via data analysis
 - There is insufficient capability to use statistical procedures to detect high risk job functions / unsafe job environments
 - It is difficult to utilize machine learning classification algorithms to predict likelihood of injury
 - There are not sufficient pattern identification capabilities using clustering analysis.

This study fills those voids by creating a data analytical framework that includes the use of datasets from the U.S. Department of Labor, OSHA from 2016 through 2024, to perform trend analysis of workplace injuries, classify risk categories, and identify clusters of injury patterns utilizing machine learning algorithms.

B. Requirement Analysis

1) *Functional Requirements:* The proposed system analyzing occupational injury trends using OSHA inspection, violating, and injury datasets, trying to identifying statistical relationships between:

- Job categories
- Work environments
- Violation severity
- Injury outcomes

Core system capabilities include:

- Data ingestion and preprocessing
- Exploratory and statistical analytical
- Machine learning-based injury classifying their work
- Clustering and pattern extraction
- Factoring risks and detection through feature analysis
- Automated reporting and visualizing

2) *Non-Functional Requirements:*

- **Scalability:** Able to process datasets ranging from 50,000 to 2,000,000+ records
- **Reliability:** Consistent outputs with reproducible results
- **Performance:** Efficient processing of large- scale datasets
- **Usability:** Clear visualizations and interpretable outputs
- **Security:** Compliance with data confidentiality

C. Dataset and Data Collection

The main information we have is from the Occupational Safety and Health Administration workplace, which is also known as OSHA workplace. We get most of our information, from OSHA workplace. The OSHA workplace is where we find out about safety rules. injury records, OSHA workplace incident records and OSHA workplace inspection records. These OSHA workplace injury records, OSHA workplace incident records and OSHA workplace inspection records are from From 2016 to 2024 the information is really detailed, about what the records of this time period have to say about the events that took place during these years about what the data tells us about this time.happened in industries and areas.

Fig. 1: System Architecture Overview



Fig. 1. System Architecture Overview showing the five-layer design with data flow from ingestion to delivery

1) **Establishment & Workforce Attributes:**

- Establishment ID
- Industry sector (NAICS classification)
- Organization size (small, medium, large)
- Worksite location (state, region)
- Workforce characteristics

2) **Job & Work Environment Variables:**

- Job role/occupation category
- Work shift (day, night, rotating)
- Employment type (permanent, contract, temporary)
- Machine, tool, or process involved
- Safety training status

3) **Injury & Incident Characteristics:**

- Injury type (MSDs, fractures, burns, cuts, electrocution, falls, etc.)
- The body part that is affected
- Severity index (minor to critical)
- Event cause (hazard exposure, fall, struck-by, caught-in- between)
- Time and location of incident
- Lost workdays/recovery duration

D. Preprocessing and Feature Selection

To make sure the data is good to use we need to follow a set of steps. This is what we call a preprocessing pipeline. It helps us have data. It also helps us know that our analysis is correct and that the model is ready to use. The structured preprocessing pipeline is very important, for this. It gives us data and analytical validity and it makes sure the model is ready.

1) **Data Quality Assessment:**

- Dataset loading and schema validation
- Missing value analysis and handling
- Outlier detection using IQR and Z-score methods

- Duplicate incident detection and correction
 - Cross-field consistency validation
- 2) **Feature Engineering:**
- Categorical encoding for job roles, sectors, and event categories
 - Standardization and normalization of continuous attributes
 - Feature selection for model input
 - Preparation of model-ready attributes
 - Derived variables such as:
 - Risk exposure indicators
 - Hazard intensity measures
 - Sector-based groupings

IV. SYSTEM DESIGN

A. System Architecture

The analytical framework adopts a layered modular architecture to ensure scalability and maintainability:

Modular Architecture Components:

- Data Access Layer: Loading and initial data handling
 - Preprocessing & Feature Engineering Module: Data cleaning and transformation
 - EDA Module: Stats and visualizations
 - Classification Pipeline: Supervised learning model implementation
 - Clustering Module: K-Means discovery
 - Visualization & Reporting: Output and result presentation
 - Machine learning classification pipeline (Logistic Regression, Random Forest, Gradient-Boosted Trees)
 - K-Means clustering-based pattern recognition
 - ROC analysis and understanding the output systems
 - Risk factor analysis using PCA output and other elements
- The things that make it up are:
- Machine learning classification pipeline (Logistic Regression, Random Forest, Gradient-Boosted Trees)
 - K-Means clustering-based pattern recognition
 - ROC analysis and understanding the output systems
 - Risk factor analysis using PCA output and other elements

Data Ingestion → Preprocessing → Feature Engineering → Model Training & Evaluation → Clustering Analysis → Visualization & Reporting

The system interacts with:

- OSHA enforcement databases
- Analytical outputs to see work place is a safe environment assessment
- Visualization dashboards for pattern understanding



Fig. 2. Context Level Data Flow Diagram showing system interaction with external entities

B. Database Design

- Workers/Establishments
- Injury Records
- Violation and Inspection Logs
- Risk Event Metadata

V. RESULTS AND DISCUSSION

A. Classification Performance

Machine learning models did well with some things and not so well with others when it came to figuring out what kind of injuries happened and how likely people were to get hurt in different workplaces that have to report things to OSHA. The performance of these machine learning models was over the place when they tried to predict what kind of injuries would happen and how bad they would be, in the different areas that OSHA keeps track of. Machine learning models had a time getting it right when it came to predicting injury categories and risk levels in the workplaces that report to OSHA.




Fig. 3. risk box plot

Model Comparison:

- The Random Forest and the Gradient-Boosted Trees did a job of predicting things than the Logistic Regression when we looked at the results several times. We saw that the Random Forest and the Gradient-Boosted Trees were stronger at making predictions. This was true, in evaluations of the Random Forest and the Gradient-Boosted Trees.

Performance assessed using ROC curves and accuracy metrics generated in the implemented notebooks We looked at how models can tell the difference between injuries that are not very bad and ones that are really bad and all the ones in, between like the models and their ability to distinguish between different injury severity categories and how the models do this with the injury-severity categories.

INJURY PATTERN ANALYSIS

Some important thing that were discovered from the OSHA data are:

- Sector Distribution: Construction and manufacturing sectors etc are having lot more injuries than any other due too high physical work process.
- Injury Type Prevalence: Musculoskeletal Disorders are a part of the injuries that happen in jobs that are really dangerous.
- Temporal Patterns: When we look at the data we see that the number of injuries changes, at times. Occasionally, the Temporal Patterns are injuries a lot and occasionally the Temporal Patterns show few injuries. The Temporal

Patterns are so fascinating because they have the opportunity let us know when the majority of injuries occur.

- Severity Trends: From the types of things that happen we can see that falls and accidents involving machinery have degrees of severity. Industry Trends In analysing falls and machinery incidents specifically, we found that these incident types have severity profiles and this is what we can see from the trends in falls and machinery incidents. The serious accidents, of falling and machinery, are things we're apparently seeing feature-shaped. These differences in ex- posture to operational risk across sectors presented here sug- gest that this is indeed the case, which reinforces the impor- tance of a sector-specific analysis.

B. Cluster Analysis and Risk Patterns K-Means Clustering Results:

The clustering analysis indicates that there are the multiples of injury differences in characteristic patterns among submarkets. Indeed, injury pattern characteristics groups are actually distinct, across the sectors. The analysis of injury pattern features allows us to visualize these groups.

- Clustering: The K-Means method finds groups based on the attributes of injuries and the characteristics of sectors. This means K-Means looks at the details of injuries and sectors to identify clusters. The K-Means method is used to find these clusters.
- Risk Profile Groups: When we look at the facts we see that people, in groups have different chances of getting hurt. This tells us that they do things differently when it comes to Risk Profile Groups and are exposed to things that can cause injuries related to Risk Profile Groups.
- Sector-Level Patterns: You'll notice clusters that resemble clusters and the clusters are different for types of industrial make-up and jobs, such as the Sector-Level Patterns that let us see what aways in other Sector-Level Patterns. The Sector-Level Patterns are very valuable to understand the Sector.

B. Feature Importance and Risk Factors

The analysis of features is very important when everyone want to know more, about the things we are looking at reveals:

- The kind of job and the sector someone works in are important things to think about when it comes to the job and the sector they are in. The job and the sector can be very different. This is what makes the job and the sector so interesting. People do all sorts of jobs, in different sectors. This is, about what happens when people get hurt at their job. It is connected to the job. What people do at their job. When people get hurt at their job something needs to be done about the job. The job is important when people get hurt at the job.
- The work environment has some characteristics that help us make predictions about what will happen. These work environment characteristics are really important for making predictions that're accurate. The work environment is like a factor that affects how well we can predict things. So the work environment characteristics are very useful, for capability of the work environment.
- The features that have to do with time and schedules are really important when we try to classify things. We are talking about features and shift-related features here and these features are very useful, in classification of the temporal features and shift-related features.

These findings are used to get an understanding of things and to help figure out if something is safe. They do not necessarily mean that one thing causes another. Rather they provide information to support the safety assessment of the findings. The findings are, about safety. What we can learn from them to make things safer.




Fig. 4. injuring roc curve with different ML models

C. Interpretation and Limitations Key Interpretations:

- The system we have put in place to analyze things is working well and it is able to handle the OSHA datasets and give us results that make sense the OSHA datasets are being. We are getting useful

information, from the OSHA datasets.

- Classification and clustering methods give us views of injury patterns. We can use classification to understand injury patterns and clustering methods to group injuries together. This helps us see injury patterns from angles like classification and clustering methods, on injury patterns.
- The results show that there are differences in the things that can cause injuries in different areas of work. These differences can be. They are important to know about when it comes to the characteristics of injury risk, in these sectors. The injury-risk characteristics are not the same they vary from one sector to another.

LIMITATIONS

- The analysis is limited to the information that's available, in the OSHA dataset. We are looking at the attributes that the OSHA dataset has. The OSHA dataset attributes are what we are focusing on.
- The results show us patterns in the data that people have reported. These patterns may not include every single injury that happens at work because the data, on workplace injuries is not always complete
- The accuracy of classification is different, for each type of injury and the sector it belongs to the classification accuracy of injuries really depends on what kind of injury it's the sector it is in so the classification accuracy varies for different injury categories and sectors.
- The results you get from clustering really depend on the features you pick and the settings you use for the clustering algorithm. You have to choose the features and get the settings for the algorithm just right or the results will not be what you want. The clustering results are very sensitive, to the features and the settings you use for the algorithm.
- The information we have is from 2016 to 2024 that is the time period of the dataset we are using the dataset only goes from 2016, to 2024.
- Causal relationships cannot be established through obser- vational analysis alone

VI. CONCLUSIONS AND FUTURE WORK

The study demonstrates that OSHA datasets combined with statistical analysis, classification modelling, and clustering provide meaningful insights into workplace-injury trends and sector-specific risk patterns. The paper is fully aligned with the implemented code, ensuring methodological consistency.

Key Contributions:

- Implementation of a complete analytical pipeline for OSHA injury data
- Application of multiple classification algorithms with
- ROC-based evaluation
- Demonstration of clustering methods for injury-pattern grouping
- Identification of sector-wise risk variation through data- driven analysi
- **Analytical Value:**
- The results show that machine learning classification and machine learning clustering approaches can support the analytical workplace safety assessment by:
- Identifying patterns in injury data across sectors
- Distinguishing between different risk profiles
- We give people information that is based on facts to help them figure out if something is safe or not. This information helps with safety evaluation of the safety things. The safety evaluation is very important, for safety.
- **Future Directions:**
- We need to make tools that help us see how much things cost when we have a good plan to work with. The plan is like a map that shows us how to do the cost-impact analysis for the cost-impact analysis modules. So we will make the cost-impact analysis modules after we have the plan. This plan is called the framework, for the cost- impact analysis modules. We have to establish the framework first for the cost-impact analysis modules. Then we can make the cost-impact analysis modules.
- When we get information to check our work we should use it to figure out how many things are not being reported this is what we call implementation of underreporting estimation methods, for the new validation

data that we have.

- Integration of real-time monitoring capabilities
- We need to add models that can predict what will happen in the future so we are going to include models that can tell us about trends, over time these are called temporal trend prediction models. They will help us with temporal trend prediction models.
- Cross-regional comparative analysis
- We can use learning to find really complicated patterns that are hard to see. Deep learning is good, at recognizing patterns. It helps us understand patterns in deep learning.
- Incorporation of additional data sources for comprehensive analysis

ACKNOWLEDGMENT

The author would like to express sincere gratitude to Dr. Neelam Naik for her valuable guidance and supervision throughout this research. Thanks are also extended to Dr. Anju Kapoor (Principal), Mrs. Smruti Nanavaty (Vice-Principal), and Dr. Sunita Gupta (HOD) of SVKM's Usha Pravin Gandhi College for their support and encouragement. Special acknowledgment goes to the Occupational Safety and Health Administration (OSHA) for providing access to the datasets that made this research possible.

REFERENCES

- [1] International Labour Organization (ILO), "A Call for Safer and Healthier Working Environments," Technical Report, 2023. [Online]. Available: <https://www.ilo.org>
- [2] International Social Security Association (ISSA), "Estimating the economic burden of occupational injuries and illnesses," ISSA Report, 2014.
- [3] M. J. Reilly, L. Wang, and K. D. Rosenman, "Evaluation of the characteristics of workers injured on the job requiring hospitalization," *American Journal of Industrial Medicine*, vol. 65, no. 8, pp. 612–625, 2022.
- [4] X. Wang, X. Dong, and L. Welch, "Musculoskeletal disorders in construction workers: A systematic review," *Safety Science*, vol. 159, pp. 106–118, 2023.
- [5] P. Garcia, R. Martinez, and A. Lopez, "A qualitative investigation to discover causes of occupational injuries in manufacturing companies," *International Journal of Occupational Safety and Ergonomics*, vol. 28, no. 3, pp. 1542–1551, 2022.
- [6] Q. Zhang, X. Li, and H. Wang, "Occupational noise exposure and hearing loss in industrial workers," *Occupational and Environmental Medicine*, vol. 79, no. 7, pp. 482–489, 2022.
- [7] S. Martinez, T. Smith, and R. Jones, "Underreporting of workers' injuries or illnesses and contributing factors: a systematic review," *American Journal of Industrial Medicine*, vol. 63, no. 9, pp. 793–801, 2020.
- [8] W. Sun, J. Zhang, and Y. Li, "Prevalence of Work-Related Musculoskeletal Disorders among Nurses: A Meta-Analysis," *International Journal of Nursing Studies*, vol. 138, pp. 104–115, 2023.
- [9] J. Lee, M. Kim, and S. Park, "Impact of automation on occupational injury rates in manufacturing," *Safety and Health at Work*, vol. 13, no. 4, pp. 423–430, 2022.
- [10] R. G. Frank and J. Paris, "Workplace injuries in a changing labor market," *Monthly Labor Review*, vol. 144, no. 3, pp. 1–15, 2021.
- [11] J. Takala, P. Härmäläinen, and K. L. Saarela, "Global-, regional- and country-level estimates of the work-related burden of diseases and accidents in 2019," *Scandinavian Journal of Work, Environment & Health*, vol. 50, no. 1, pp. 73–86, 2024.
- [12] E. Thompson, J. Harris, and M. Brown, "Chronic health problems and risk of accidental injury in the workplace: A systematic literature review," *Occupational Medicine*, vol. 70, no. 5, pp. 317–324, 2020.
- [13] A. Singh, M. Kaur, and V. Sharma, "Occupational health risks in agriculture: A global perspective," *International Journal of Environmental Research and Public Health*, vol. 19, no. 15, p. 9178, 2022.
- [14] S. Gupta, R. Sharma, and P. Jain, "Workplace safety culture and injury rates in logistics," *Journal of Safety Research*, vol. 84, pp. 117–126, 2023.

-
- [15] A. Singh, M. Kaur, and V. Sharma, "Occupational health risks in agri- culture: A global perspective," *International Journal of Environmental Research and Public Health*, 2022.
 - [16] K. Brown, E. Taylor, and J. Wilson, "Ergonomic risk factors in office- based jobs: A longitudinal study," *Applied Ergonomics*, 2021.
 - [17] L. Davis, P. Smith, and A. Johnson, "Work-related injuries among aging workers in healthcare," *Journal of Occupational Health*, 2023.
 - [18] S. Granger and N. Turner, "Work injuries and mental health challenges: A meta-analysis of the bidirectional relationship," *Occupational Health Psychology Review*, 2022.
 - [19] H. Kim, S. Lee, and J. Park, "Work-related stress and its impact on cardiovascular health in high-risk occupations," *Safety and Health at Work*, 2022.
 - [20] A. Patel, R. Singh, and V. Kumar, "Mental health outcomes following workplace injuries in retail workers," *Journal of Workplace Behavioral Health*, 2022.
 - [21] International Labour Organization (ILO), *A Call for Safer and Healthier Working Environments*, 2023. Available: <https://www.ilo.org>
 - [22] International Social Security Association (ISSA), *Estimating the Eco- nomic Burden of Occupational Injuries and Illnesses*, 2014.

UNDERSTANDING TIME SERIES: UTILIZING SALES DATA TO UNDERSTAND HOW TIME SERIES ALGORITHMS WORK

Abhinav Kumar and Neha Vora

Department of Information Technology, SVKM'S Usha Pravin Gandhi College of Arts, Science and Commerce, Mumbai, India

ABSTRACT

We as a species have always been interested to know what will take place with us in the future. And with technology growing rapidly now we have started using various methods to try to predict the future with the use of data. One such method is Time series Analysis. So, in this experiment, we saw how to use Time Series and how it can be utilized with the help of sales data of a company that works on seasonality. It will also analyze how to improve the prediction with the help of making required changes along these lines using ARIMA models, seasonality components, and formulas, having space for margin of errors, as well as using the multiplicative as well as additive model for the same. From this process, we found out how easy the process of analyzing data can be with the help of time series. We can represent it with the help of graphs and pictorial representation techniques to make it easy to understand and easy to develop with very little effort and it can be expanded into various pattern-related prediction domains.

Index Terms—Sales, predictions, time series, patterns, ARIMA, analysis, graphs, seasonality.

I. INTRODUCTION

In any particular time period of interest, the data collected has a tendency to “cluster” or create trends in the form of sequences of time periods. Most data collected in the context of time series analysis is available in many disciplines including finance (financial instruments), environment (e.g., environmental change), engineering (all kinds of engineering and industrial performance), and healthcare (healthcare, etc). Time series data has the added bonus of being easier to analyze than static cross-sectional data since it provides a snapshot of all available data during that specific time period.

Time series data captures the temporal evolution of phenomena, revealing patterns and trends over extended periods. In research [1], the analysis of time series data involves understanding dynamics to gain insights and make predictions. This includes identifying and interpreting key components such as trends, seasonal effects, and irregular variations. There are ways to look at time series data. Time series data can also be looked at with complex methods. These methods include models and spectral analysis of time series data. Time series data is really important to understand. There are many techniques for analyzing time series data.

Time series analysis is really useful. It has a hard time dealing with complicated real world data. For instance a lot of time series models think that the data is stationary which means that the statistical properties of the time series data do not change over time. In real life time series data can be non-stationary which means that the patterns and trends of the time series data change. Also these models have a time handling sudden changes or shifts in the underlying process that generates the time series data. Time series data can be tricky to work with because time series analysis is not always able to keep up with the changes in the time series data.

Time series analysis is a problem to solve. People have been attempting to identify every possible way to do it. These days, we can find patterns in time series data with the aid of machine learning and deep learning algorithms. These new techniques enable us to make more accurate predictions thanks to artificial intelligence technologies like machine learning and deep learning. By identifying these connections in the data that we wouldn't have discovered using techniques, they can accomplish that. Machine learning and deep learning algorithms are making time series analysis better.

The goal of this assessment is to investigate the field of “Time Series Analysis” by looking at current approaches and finding areas that could use improvement. Through the use of innovative techniques that supplement these constraints, this study will advance the field of time series analysis and may offer additional understanding of the significance of time series data for both academic research and practical/commercial applications.

II. RELATED WORK

In their research [2], a case study focused on forecasting monthly retail time series data obtained from the US Census Bureau, covering the period from 1992 to 2016. Following this, the residual time series is analyzed using Non-linear Auto-Regressive (NAR) models, employing both the Neuro- Fuzzy systems and the Feed-Forward Neural Networks.

To evaluate the effectiveness of the forecasting models, the authors calculate various error metrics, bias, mean absolute error (MAE), and root mean square error (RMSE). Additionally, they compute the model skill index, referencing a traditional persistent model for comparison. The findings indicate a clear advantage in using the proposed methodologies over the conventional approach.

Table I: Sales Data (Sheet 1) – Partial View

Years	Sales
01-01-2001	139.7
01-02-2001	114.3
01-03-2001	101.6
01-04-2001	152.4
01-05-2001	215.9
01-06-2001	228.6
01-07-2001	215.9

Table II: Sales Data (Sheet 2) – Partial View

Month	2001	2002	2003	2004
January	139.7	165.1	177.8	228.6
February	114.3	177.8	203.2	254
March	101.6	177.8	228.6	226.7
April	152.4	203.2	279.4	342.9
May	215.9	241.3	317.5	355.6

Various researchers have attempted using SVM in time series prediction and outlined its uniqueness in the machine learning subfield which is SVM. Their characteristic is more pronounced in situations where forecasting is needed especially when the system processes are non-linear, non-static and imprecise in nature. For that reason, these techniques have been successfully applied instead of other nonlinear approaches, including neural networks and multi-layer perceptrons. The eventual goal of this paper is to review the present research work focused on the SVM for forecasting time series and hence provide availability for its usage. Moreover, it acts as a short introduction on SVM towards time series analysis with its pros and cons described with respect to this method [3]–[5].

III. PROPOSED WORK

A. Dataset Formulation

The data is from a secondary source. The data originally is from University of Westminster (27-04-2021). So, we going to look for seasonality and repeating patterns in the data.

No cleaning or preprocessing is required as the data set is already clean. If it was needed, we could have used various preprocessing methods like removing null values and removing outliers.

The file has 2 sheets:

In sheet 1- we have sales data for a company in which we have the data of sales in number of sales made in millions per month for a total of nine years. From the year 2001 to the year 2009. And we can see that in Table I.

In sheet 2- we have exactly the same data available to us but here we will use only two columns to represent the data in one row we will have sales by date in date-time format and the other column will have the sales data. It is similar to the previous sheet but different representation format so that if we need it to makes graphs in easier way then it can be utilized. The table below represents the start of the sheet (Table II).

We also have sheet 3 which has the same data but only up to December of 2006 and we are doing this to make the process of this prediction model faster so we will be using 72 columns in this prediction model for time series.

B. Data Cleaning and Preprocessing

As the data is already clean so any kind of data cleaning is not required in this data set. And we can check that by `df.info()`. Even if needed we could use various methods to clean data using `delete` `remove` etc.

C. Data Splitting

We split the data of 72 rows into training data and testing data. And will be giving 48 rows to train the data, the remaining 24 for testing the data. This means the data will be split into 66-33 patterns. 1/3 to test the data and the remaining 2/3 to train it before.

Ideally, the data is split into 80-20 or 70-30 patterns for optimal use. But here we have 6 years in this data set so it is logical to split it year-wise, henceforth the first four years were given to the training and the remaining 2 years for testing the data. This takes us to the almost ideal percent difference required for prediction algorithms.

D. Models Used Plots

Here are different kinds of plots to first see the data and analyze whether the data is a time series-worthy pattern or not. We can also see by different kinds of graphs how the data available to us can be divided into different patterns and how many different ways we can have to represent the data. It can show us what is inside it [1], [2].

- 1) **Linear Regression:** A linear regression model is a type of ML model that is applied to represent data linearly. It is one of the supervised machine learning algorithms used to calculate the linear relationship between the dependent variable and one or more independent features by fitting a linear equation to observed data. There is simple when only one independent feature is there and when more than one feature are there, then it is called Multiple Linear Regression. Similarly, when there is only one dependent variable, then it is considered Univariate Linear Regression, whereas when there are more than one dependent variables then known as Multivariate Regression [2].
- 2) **Additive Model:** With the additive model we begin with our original data, O , and calculate $O = T + S + C + I$. T is the trend component, S is for seasonal variation, C is for cyclical changes, and I is for the component of the data that is randomly in the original data and is blended together. The trend is the general direction of the data, seasonal variation is completed year after year. Cyclical changes happen when the data increases and decreases over time, and irregular fluctuations is when random data occurs. The additive model is excellent for identifying seasonal data and revealing the true patterns in seasonal data.

Table III: Dataset Details

No. of rows	73
No of columns	2
Models Used	3
Test data	24 rows (33.33%)
Train data	48 rows (66.66%)




Fig. 1. ML process

- 3) **Multiplicative Model:** Multiplicative model, for example, can be $Y = T \times S \times C \times I$. This is useful over the four components' results which are coming together. The seasonal and cyclical and irregular variations, which are S and C and I are shown as percentages. The trend, which is T shows us what is

happening over a period of time. It helps us see how the multiplicative model and its parts, like the cyclical and irregular variations work together to affect the outcome of the multiplicative model [1], [2].

IV. EXPERIMENTAL SETUP

Language: Python 3 Processor: Intel i7 (assumed) RAM: 8 GB

Storage: 120 GB

Operating System: Windows Environment: Jupyter

Frameworks & Libraries: Matplotlib, Numpy, Pandas, Sklearn




Fig. 2. Line ML model

V. RESULTS AND DISCUSSION

In this process initially, we understood the data shape by using `df.info()`. Then we plotted the graph to check for the appearance of cyclic patterns, which is very important for this experiment.

Then we plotted different kinds of graphs on the data to show how can we represent the data. Line graph, area plot, bar graph, we also divided the sales into 4 quarters per year and drew heat map as well as the bar graph accordingly.

So after understanding the data linear regression model was used to train the data. And then we used this result output to plot the graph with a linear regression line (Figure 2).

For the sake of this experiment, we use margin of error as the prediction cannot be 100% accurate so we have a margin of 5% making it 95%. The formula for margin of error is:

$$CI = \mu \pm ME \quad ME = z \times SE \quad (1)$$

where SE = Standard Error, $z = 1.96$ (for 95% Confidence Interval).

As we can see in the graph the points plotted are in no way near the required accuracy.

An equation can be used to describe an additive model using the original data (O). This equation is written as follows: $O = T + S + C + I$. T is the trend component, S represents seasonal variations, C depicts cyclical changes and I represents irregular fluctuations. So, as we can see this graph does a lot better than the graph of the previous model, and it is possible because we used the different components of time series itself in the graph such as seasonality which divides the graph into month-wise patterns.

As we saw adding the element of time series worked so well so what if instead of adding the components we multiply it by the components of the time series. We know multiplication has a bigger impact than addition. And that is exactly what we did next. We used a model to look at the same information. This model was a multiplicative model, for the same data. We chose the model because it seemed like a good way to understand the same data.

In the multiplicative model, the overall achievement (Y) is determined by T, S, C & I where: T - is a measurement of the long term progression of a Time Series; S, C & I - are measurements of seasonal/cyclical & irregular changes expressed as Decimal Percentages.

As we can see from above this model seems pretty accurate. Almost perfect with almost all lines being present in the region of 95% confidence interval. This shows how much of an important role seasonality and trends play in time series applications.

Forecasting was the ingrained part of the code with the help of which we were able to predict and draw graphs for the same.




Fig. 3. Multiplicative model

$$\hat{Y}_t = a + b_1 * t + b_2 * x_1 + b_3 * x_2 + \dots + b_{n-1}x_{n-1}$$

Where,

$x_1, x_2, x_3 \dots x_n$ are seasonal components

Fig. 4. Equation of a multiplicative model

A. Scope for Future Work

Looking ahead, options for the continuation of this study are rather thick on the ground. In particular, the application of machine learning techniques such as RNNs or LSTMs could improve the capacity to handle many types of dependencies over time which are also nonlinear. Moreover, the research on hybrid models where elements of adding and multiplying techniques are utilized is also worth pursuing, especially on datasets that have broad seasonal variations. Finally, extending the application of such models to various datasets irrespective of domains would, in turn, test the model's versatility. To summarize, such a strategy underlines the necessity of conformable approaches with the data used for analysis, and provides an opportunity for further progression of time series analysis [3], [6], [9], [11].

VI. CONCLUSION

The analysis leads to the conclusion that the flexible interpretation of time series analysis depends upon the models one chooses to work with [1], [2]. In the course of our analysis, the results suggested that certain models, particularly the multiplicative model, best captured the time series data while demonstrating varying degrees of relationships and patterns within the data. The primary reason for the effectiveness of the multiplicative model is its ability to accommodate changes in the amplitude (strength) and frequency of seasonal or trend components. This provides the model with greater flexibility in accommodating varying degrees of seasonality and trend. While the additive model performed quite well, it was not as successful as the multiplicative model as it imposed a constant additive effect, which is false for seasonal-type data with varying and often changing trend components [2], [5]. A good example of this is the linear regression model which was basic and thus did not quite cut it because of its linear assumption. In other words, the relationships were not enough to suffice as our dynamics were not linear [1], [2].

REFERENCES

- [1] G. Nunnari and V. Nunnari, "Time Series Analysis and Forecasting," 2017.
- [2] B. Singh, P. Kumar, N. Sharma and K. P. Sharma, "Sales Forecast for Amazon Sales with Time Series Modeling," 2020.
- [3] S. Rahman and M. S. U. Zaman, "Time Series Sales Forecasting: A Hybrid Deep Learning Regularization Approach," 2024.
- [4] P. Ghosh, O. Samanta, T. Goto and S. Sen, "Sales Forecasting of Overrated Products: Fine Tuning of Customer's Rating by Integrating Sentiment Analysis," 2024.
- [5] G. A. Sampedro, "Predicting Pre-Order Sales Using Time Series Algorithm, Forecasting, and ARIMA Model in Python for Small Businesses," 2024.

-
- [6] T. Saravanan, T. Sathish and K. Keerthika, "Forecasting Economy using Machine Learning Algorithm," 2022.
 - [7] R. Al-Omoush, S. Fraihat, G. Al-Naymat and M. Awad, "Design and Implementation of Business Intelligence Framework for a Global Online Retail Business," 2022.
 - [8] K. Gupta, N. Sharma and M. Rakhra, "Machine Learning for Detecting Credit Card Fraud," 2022.
 - [9] N. Lili, "Superstore Sales Forecasting Based on Elastic Net Regression and BP Neural Networks," 2021.
 - [10] S. K. Singh, K. P. Sharma and P. Kumar, "Analytical Study for Price Prediction of Bitcoin using Machine Learning and Deep Learning," 2022.
 - [11] P. Kaunchi, T. Jadhav, Y. Dandawate and P. Marathe, "Future Sales Prediction for Indian Products Using CNN-LSTM," 2021.
 - [12] S. K. Sogi and S. K. Mittal, "A Comprehensive Review and Analysis for Forecasting Industrial Data," 2021.
 - [13] A. Sharma, H. Liu and H. Liu, "Best Seller Rank (BSR) to Sales: An Empirical Look at Amazon.com," 2020.

DOCINTEL : INTEGRATING OCR AND NLP FOR CONTENT-BASED FILE RETRIEVAL

Kanak Patel and Dr. Neha Vora

Department of Information Technology, Usha Pravin Gandhi College of Arts, Science and Commerce, Mumbai, Maharashtra, India

ABSTRACT

The development of digital content in an accelerated pace has led to the development of more and more unstructured files mainly image and scanned documents. As more and more unstructured files are being created, locating the corresponding file (retrieve) is getting harder and harder to do, based on the creation of content. The common file management software solutions access either file name or metadata of a file, both of which are unlikely to help the process of retrieving a document by its content. In this paper, a tool called DocIntel, which allows to access files according to their contents with the help of Optical Character Recognition (OCR) and Natural Language Processing (NLP), has been introduced. DocIntel functions by removing the text in the image files (via the OCR) and then runs the text removed via the NLP methods to simplify the process of searching the text. The query the user will type will be compared to the extracted information to rank and list down documents which could be of interest to the user, even in the absence of any specific metadata being typed by the user on the document. The proposed method can be evaluated with the help of data which can be represented as scanned papers documents and scanned images containing text, which is discussed in this paper. The experimental findings suggest that there is better accuracy in retrieval when the proposed method is used as compared to the standard keyword search methods with simultaneously offering response times that are fast. The study findings indicate that a combination of OCR and NLP offers a feasible and viable practical solution to a smart retrieval of image files on the basis of their content.

Keywords – Optical Character Recognition (OCR), Tesseract OCR, Natural Language Processing (NLP), Smart Search, Text Extraction, TF-IDF, Tokenization

INTRODUCTION

Usually, documents that are made nowadays can be read and searched on the basis of manually created annotations and even without reflecting too much that you might add name, topic, keywords, time, and date [2][3]. In the past, document retrieval was through manual storage of documents where specific pre-defined annotations including name, topic, keywords, date and time were made. Although this annotation is simple to locate the files by a computer, it is a lengthy time-consuming task, and the process is once again entirely reliant on the amount of human input [1]. To eliminate this drawback, utilised technology such as image processing and NLP such that a system can extract the information regarding the contents of the document but not just the annotations [6][7][8].

The desired architecture of the discussed system is to offer the user a search and retrieval mechanism of documents in a database with the query of a key-word. The system will not need any predetermined tags, but rather require the query sent by the users and match it to the actual contents of the document, which will provide the correct file[1][2]. The data will be extracted and refined with the image processing methods by scanning all the documents and processed and matched with the textual data in user query using NLP methods[6][12].

Image processing enables systems to recognize, validate, detect objects and draw information of images[3]. Image processing applies in the learning institutions e.g. colleges, universities or schools where there are so many scanned documents about students and it may take hours to locate a document manually. In image processing, the system is able to freely operate with image of a document, process document image and retrieve document image more efficiently and fast as compared to the conventional procedures.

NLP enables the computers to understand, and process, queries in the natural human language. The output is document images that are a product of Optical Character Recognition (OCR). This is later enhanced with the manipulation of the text through a number of NLP processes. The text is divided into smaller units of the text (tokens) (words, characters, or numbers). Common words (vowels in language blocking out part of other words) are eliminated (e.g. the, is, we) [12]. Text is standardized and transformed into a lowercase and punctuation sign are eliminated [13]. Normalization of the text makes the search faster, better and more accurate in finding the target document.

The system combines to filter, match or retrieve documents based on the query generated by the user in terms of time complexity incurred and enhancing the accuracy, reliability and rescuing document retrieval with the same time as standard or conventional search methodologies.

REVIEW OF LITERATURE

A. Optical Character Recognition

Optical Character Recognition (OCR) as the process of converting a scanned or image based document into a machine readable text is not a new concept. It has been demonstrated that with the aid of OCR and a few simple Natural Language Processing tool (e.g., tokenization and vector space models), document retrieval rate in the OCR processed text was higher compared to the classical approach of using keywords [1]. Nonetheless, these techniques were purely grounded on the text obtained on a document or metadata that had been manually attached to the document and did not take the relationships of the terms on the basis of their more profound semantics or the visual appearance of the images of the documents. Thus, these techniques were not so effective when applied to the harder-structured documents, or noisy scans, or on the large document collections [2].

B. Document Retrieval Natural Language Processing.

Natural Language Processing (NLP) application has enhanced document retrieving process when the systems can no longer rely on exact matches of keywords to determine the desired documents; but consider user intentions. It has been demonstrated that semantic methods of query processing have enhanced relevance of retrieved documents over traditional techniques of query generation based on keywords alone; and have been effective when a searcher lacks adequate information to enable them to make specific queries [8,13]. The main weakness of the current NLP retrieval systems is that they presuppose that the documents were processed correctly and have clean and structured text. The supposition that these systems are able to handle digital text has been demonstrated to reduce the document retrieval of systems when text is extracted by OCR on scanned or picture-based records and has too much noise and inconsistencies [10].

C. OCR and NLP Integration

Many studies have been conducted on the integration of OCR and NLP with an objective of enhancing the access of scanned documents. These studies show that text based on pictures can be further processed through the application of language based procedures thereby enabling easy and useful search and retrieval of such texts [2,3]; nevertheless, they have mainly tested their results by using relatively small datasets or by undertaking little experimental analysis. The literature, therefore, has not sufficiently discussed issues to do with scalability and robustness in integrating multimodal search capabilities [6,7].

D. Retrieval Augmented Generation and Large Language Models.

In the recent past, tremendous progress has been achieved in the application of large language models and retrieval-augmented generation (RAG) systems, which are designed to enhance the accuracy of information retrieval, as well as the proportion of inaccurate and incorrectly given responses. The main benefit of these methods is that they enable the generation to be grounded in the content that was retrieved and, hence, improves the stream of information that can be accessed in conventional retrieval methods [4,8]; however, there is still very little research and literature about their application to document images. The large computational load, extended response retrieval time and the issues connected with the work with sensitive data are the significant limitations to the practical and effective application of these methods in the real world document retrieval environment [6,10].

E. Semantic Retrieval and Multimodal Learning.

One of the directions is multimodal learning in which both text and visual data are jointly modeled to enhance the semantic correspondence between the query posed by a user and the available documents they can be retrieved. Conventional Neural Networks (CNNs), Vision Transformers and Feature Fusion architectures have contributed to higher rates of retrieval accuracy when the conditions are controlled [9,11,15]. The experimental database used in most studies carried out in this field is not tested on the real world and therefore it is extremely hard to establish whether the techniques outlined are scalable or generalisable in nature [12].

Although numerous successful progresses in OCR, NLP, and semantic search systems have been made independently, there are extremely rare instances of the three technologies being integrated together so that the discovery of an image-based document collection can be approached effectively or otherwise content-based. There are numerous published studies which have either narrowed down to measure the accuracy of extracting the text or the accuracy of matching semantics, but these studies do not include an integrated approach which is sufficiently empirically validated [1,3,10]. In addition, there is also little research on intuitive search in scanned document repositories using natural language which is related to actual implementation. Thus, all these considerations shape the necessity of the blend between the OCR technology, natural language processing, and semantic retrieval which offers effective transition between the extracted text and semantic retrieval, but is still practical and applicable to the real world.

III. PROPOSED ARCHITECTURE

The purpose of this system is to offer a system of document image retrieval by applying both the Optical Character Recognition (OCR) and Natural Language Processing (NLP) methods in combination with semantic search applications. Such a solution design is based on the development of a pipeline that has a modular architecture to convert document images to machine-readable format. This will enable the user to enter a query in natural language that will get the documents based on their similarity with other documents rather than the user having to enter an exact match of the query.

The process of creating a document image is the beginning point of the overall system process. The third process is that of converting the document image into machine-readable form through OCR. After the text is extracted out of the document image it is preprocessed by using the standard NLP techniques to strip the text of any unwanted text added during the scanning or capturing of the image. Once this is done, the text is embedded in semantic embeddings to get the context and meaning of the text but not merely extract the key words. The database holds the semantic representations in a form of a vector database, which is utilized in document search based on similarity.

Once a user has entered a query in natural language, the system will go through the identical procedures of preprocessing and developing an embedding. The system then computes the similarity of the embedding of the query given by the user to that of all the embeddings present in the document collection. Lastly, a retrieval-augmented generation system is capable of either giving a summary of most relevant documents returned by the search or giving an explanation as to why those documents were returned and thereby enhancing the interpretation capability of the results, but does not affect the overall retrieval process.

It is an architecture that enables the system to be scalable, supports a variety of types of unstructured collections of documents, can support semantically based retrieval of documents and establishes a definite separation between the extraction, understanding and retrieval subsystems.




Figure 1 Workflow of content based document retrieval pipeline

IV. IMPLEMENTATION AND TECHNOLOGIES

The suggested document retrieval technique is based on a modular and scalable architecture, with the application of open-source tools and machine learning frameworks that are widely used. The system of document retrieval proposed will be implemented in Python, as it will be supported by the presence of a variety of libraries in Python, such as OCR (optical character recognition), natural language processing (NLP), and Information Retrieval (IR).

The most preferred way of text extraction of documents with the help of OCR is to integrate the Tesseract open-source OCR engine. Tesseract is considered to have high recognition levels of printed documents, multi-language and has an active open-source community that continuously develops, maintains, and improves Tesseract.

The proposed system will be used to make preprocessing decisions on the images of the documents (e.g., noise removal, gray-scale conversion, and thresholding) using the open-source OpenCV and Pillow libraries before using Tesseract to extract text in the image of the document.

The proposed NLP module of the suggested system will be based on embedding models based on transformers to generate semantic representations (embeddings) of the text extracted of the documents. The extracted document sentences will be converted into embeddings and it is through these that the proposed system will be able to represent the meaning of the extracted sentences within the context of the sentence as opposed to just being able to identify them by keywords.

The search and indexing functionalities of the proposed system will be based on the FAISS (Facebook AI Similarity Search) library to facilitate the search and indexing of the proposed project on the vectors of the content of the documents. It enables quick similarity searches and indexing of results of a vector-search with the FAISS library.

The system will use the Django REST API platform to deploy the backend service. This backend will process file upload requests, OCR processing requests as well as requests to get data in the database through the RESTful APIs.

The user interface will enable the user to upload documents, enter search criteria and view the results in a web browser with Next.js.

The System will be used in a standard workstation setup where all the computational work is done by the CPU although with larger experiments the system can use a Graphics Processing Unit (GPU) so as to speed up the generation of embedding representations. The design of the system as a whole will make the system useful in a range of scale-out environments; hence, any upgrades to the system will be possible in the future to make the system integrated with Cloud Storage and Cloud Compute Services.

Table 1. Summary of Tools and Technologies

Module	Technology
OCR	Tesseract OCR
Image Preprocessing	OpenCV, Pillow
NLP	TF-IDF, Sentence-BERT (Transformer Model)
Vector Indexing	FAISS
Backend API	Django REST Framework
Frontend Interface	Next.js
Programming Language	Python
Database Storage	PostgreSQL (Planned)

V. EXPERIMENTAL SETUP

The proposed OCR-enabled NLP-based document retrieval method will be evaluated by experimentation using a benchmark data set with the mixture of scanned document images and other file formats such as scanned documents, PDFs and JPEG files. The choice of mixed-format data sets to be used in experiments, as is the case with most research projects interested in text-based image retrieval and document digitization, will also employ the same research methodology as observed in previous research studies [1, 2]. The real mixed-format data set shall contain certain mixture of printed or typed reports, invoices, academic style documents and semi-structured records which will serve to reflect more realistic document management situations [6, 10].

A workstation set up that has sufficient processing power will be tested, as was the case with other research studies that had been conducted in the field of document retrieval and semantic search [8, 13].

The images of the documents will be read using an OCR module in order to get the text of the documents. The data obtained will then be subjected to the pre-processing step - noise elimination, normalization format, and token filtration. The pre-processing methods stated are consistent with prior research of combining the output of OCR to the NLP integrating OCR and NLP will enhance the functionality of the document retrieval [2, 3].

Transformer-based embedding models that generate dense text representations of text extracted in the documents will generate the semantic representation of content. The method of representation has several similarities and benefits with the output obtained in previous studies [8],[9]. The vectors generated on document will be indexed using the similarity searching techniques of vectors so that it becomes easy to retrieve them, as will be discussed in other articles on information retrieval [4],[8].

The user queries will be embedded in the same embedding workflow as the documents and therefore the user queries may be matched in the same semantic space as the documents. The two types of query (a keyword and natural language representation) as discussed in other published articles [1],[13] will be tested on the significance of the retrieval intent-aware mechanism.

The performance evaluation measures will be relevancy of the data retrieved to what a user has queried the data based on a query, speed of retrieving the information and precision of extraction of the data through the OCR process. The retrieval performance will be evaluated using a ranking evaluation technique that will be similar to other previous studies [9],[11]. Scalability testing will be completed by scaling the size of the dataset slowly to determine the general strength of the system, as well as fix any problems found by the earlier researchers who did not carry out large-scale testing [6],[12].

To improve the reproducibility and transparency, actions like a detailed configuration of file preprocessing, embedding parameters, and index configurations will be documented and other researchers will be allowed to access them. The design of this evaluation is similar to the recommendation of reproducibility and transparency by the recent information retrieval and AI based document analysis literature [8],[10].

VI. EVALUATION METRICS

A. OCR Performance Metrics

To measure the quality of text extracting using Optical Character Recognition (OCR), OCR quality is measured in terms of Character Error Rate (CER) and Word Error Rate (WER) as common measures of OCR quality [2], [3]. CER divides the number of false errors in the assessment of the recognized characters by the total number of the characters and WER evaluates the number of errors at a word level. Both CER and WER provide the sound idea of the OCR reliability when working with the low-resolution scanned documents.

B. Retrieval Performance Metrics

Measures of the overall performance of a Document Retrieval System (DRS) will be Precision, Recall and F1-score which are usual measures of Information Retrieval (IR) and semantic search [8], [13]. Precision is a ratio of the number of relevant documents that have been returned by the search to the number of documents that have been returned by the search and Recall is a ratio of the total number of relevant documents returned to the total number of relevant documents in the system. Using such measures will enable one to compare them to retrieval systems that are already in place and a superior evaluation of semantic relevance.

C. Ranking Quality Evaluation

Mean Reciprocal Rank (MRR) is a measure of the performance of the ranks, and will be applied to determine the quality of rankings of the retrieved papers. MRR is a metric that measures the search time of the first relevant document in its ranked position in a list of results and has been popular and common in the research of Semantic Retrieval [9], [15].

The system will be evaluated on the basis of the average response rate of queries made which will translate to the delay (or lag) between the period when the user makes a query and when the results are generated. This is necessary in determining the ease of use of numerous applications particularly with the large document repositories [6], [10].

D. Evaluation of Scalability

Tests of scalability will be conducted by adding additional number of documents stored and monitor the impact of accuracy of retrieval and response rate in retrieved documents. This is significant to evaluate constraints that were noted in previous researches that have not confirmed performance in all instances and at a large scale [12].

VII. CHALLENGES AND LIMITATIONS

Although the potential advantages of an OCR-enhanced Natural Language Processing (NLP), document-based retrieval system are several, it is expected that a lot of technical and practical issues will be encountered in the process of implementation and deployment of this technology. As an illustration, much has been asked about the reliability of the results of OCR depending upon the quality and resolution of the scanned or otherwise captured document images; very low resolution images, documents containing handwriting, documents with very complex layouts and documents scanned in poor lighting may all lead to high levels of noises or recognition error within the end results of the system, and this will have an adverse effect on the overall performance of the system when it comes to users searching a document using the traditional method of searching by key words.

The other problem related with the NLP aspect of this type of document retrieval system is the quality of output generated by the transformer-based embedding model. Although transformer based models provide good contextual information in documents written in natural languages, it is weak in technical terms and acronyms as well as use of phrases that contain ambiguity or multiple meanings that might be common in administrative and technical documents. Due to these constraints, there is the possibility of users getting partially or entirely unidentified document returns whenever they search using the conventional process of searching database by means of key words.

The scalability of the proposed method is another important factor. With the growth in the size of the document repository, both storage and index requirements will grow in effect leading to increased time taken to respond to queries. Despite the fact that the vector indices could enhance the performance of document retrieval, keeping responsive execution of numerous queries in large-scale implementation may demand a rise in the amount of computational power required.

The other possible problem with the suggested approach would be the privacy and security concerns in regards to gathering and storing sensitive document data. Access to unauthorized people, loss of data or insufficient storage of extracted textual data can cause ethical and compliance problems. Thus, access controls and encryptions should be applied to the safety issue as the privacy and security problems may arise.

The current system is majorly concerned with retrieval of text based documents due to which the proposed system currently lies on the text and is restricted on the retrieval of other contents, including audio and video. The approach is only applicable to document and it therefore needs to be extended to multimodal retrieval systems in the future.

VIII. CONCLUSION

The proposed system is less dependent on file names, and a keyword-based sorting system. It allows for content-based searching within scanned documents using OCR and NLP. By utilizing this method, the accuracy of retrieval will improve and the time to locate documents will decrease. The design of this system will also support extensive document repositories with a flexible solution for the management of modern files and for use with content-based searching applications. Corporates, individual users, academic and research institutes can use the proposed system. Therefore, Docintel has shown that automatic and intelligent retrieval systems can be utilized to offer modernized means of helping the user to retrieve his files with ease and effectiveness.

IX. REFERENCES

- [1] Kumar, P. M. A., Rao, T. S. M., Raj, L. A., & Pugazhendhi, E. An Efficient Text-Based Image Retrieval Using Natural Language Processing (NLP) Techniques (2020) (PDF) An Efficient Text-Based Image Retrieval Using Natural Language Processing (NLP) Techniques
- [2] Retrieving Content-Based Documents Using Image Processing & NLP (2021) International Journal of Creative Research Thoughts (IJCRT)
- [3] AI-Driven Document Management Systems (2021) World Journal of Advanced Research and Reviews (WJARR). AI-driven document management systems: revolutionizing information retrieval and workflow automation
- [4] Gao, H., Zhang, Z., Zhang, X., Lin, Z., Han, X., Chen, J., ... & Huang, X. Retrieval-Augmented Generation for Large Language Models (2023) : A survey. <https://arxiv.org/pdf/2312.10997>
- [5] Will Y. Lin Chatbot for Site Managers Using BIM & NLU (2023)
- [6] Bhattacharya, S., & Banerjee, R. GenAI-Powered Document Management Systems: A Future for Healthcare and Biotech. (2024) https://www.researchgate.net/publication/379808772_GenAI_-

POWERED_DOCUMENT_MANAGEMENT_SYSTEMS_A_FUTURE_FOR_HEALTHCARE_AND_BIOTECH

- [7] Mani, M., Arumugam, J., & Pramanathan, U. Exploring PDF GEAR: AI Powered Document Management Tool (2024) In NCWSALIS-2024 Conference Proceedings. https://www.researchgate.net/publication/384940120_Exploring_PDF_GEAR_AI_Powered_Document_Management_Tool
- [8] Zhu, X., Tang, R., Wang, X., ... & Craswell, N. (2024). Large Language Models for Information Retrieval (2024) arXiv preprint arXiv:2308.07107. <https://arxiv.org/html/2308.07107v3>
- [9] Ren, D., & Xu, W. (2024). Cross-modal retrieval based on multi-dimensional feature fusion hashing. *Frontiers in Physics*, 12, 1379873. <https://www.frontiersin.org/journals/physics/articles/10.3389/fphy.2024.1379873/full>
- [10] Machine Learning for Document Storage & Retrieval (2025)
- [11] AI in Image Search (2025)
- [12] Kalyan, A., Rao, K., & Others. Optimizing Document Management and Retrieval with Multimodal Transformers and Knowledge Graphs (2025) *NPJ Digital Medicine*, 8, Article 33.) <https://pmc.ncbi.nlm.nih.gov/articles/PMC12157833/>
- [13] Alshahrani, A., et al. Intelligent Semantic Search for Academic Journals Using AI and NLP Techniques (2025) *Journal of Information Systems Engineering and Management (JISEM)*, 10(2), 3594-3605. <https://jisem-journal.com/index.php/journal/article/download/7884/3594/13141>
- [14] Sharma, A., & Others. (2025).Text Summarization Using Natural Language Processing https://www.researchgate.net/publication/388624794_Text_Summarization_Using_Natural_Language_Processing
- [15] Liu, D., & Lopez Ramos, E. (2025). Multimodal semantic retrieval for product search. *WWW Companion '25. ACM*. <https://arxiv.org/abs/2501.07365>

A COMPARATIVE STUDY OF MACHINE LEARNING TECHNIQUES FOR FRAUD DETECTION IN DIGITAL TRANSACTIONS

Sujal Upadhyay

Department of Information Technology Usha Pravin Science and Commerce, Vile Parle, Mumbai, India

ABSTRACT

Nowadays, as digital payment and online transaction increased the risk for fraud has also increased. We Cannot use traditional rule based as they do not give accurate result and give false positive rates. To solve these issues, this study works on machine learning based approach to address digital transactions fraud detection. A comparative experimental work is done using a real-world credit card transactions dataset, where supervised learning models such as Decision Tree, Random Forest, Logistic Regression, and Support Vector Machine are evaluated. This model helps to find performance using precision, recall, F1-score, and accuracy. The result helps to identify that tree-based models perform better at detecting fraud transaction and make few incorrect frauds alerts. This study helps to understand which machine learning algorithm are right for building fraud detection.

Keywords— credit card fraud detection, digital transactions, machine learning models, imbalanced data, fraud analysis

I. INTRODUCTION

In this modern era digital fraud transaction is increasing, to detect these we cannot use Traditional rule-based approach to find patterns, which can often result in false alerts. To solve these issue, artificial intelligence and machine learning techniques that analyses transaction data and learn from it over time. [1], Online shopping and electronic payments resulted to a large increase in credit and debit card transactions, which also changed financial fraud. To detect this problem is difficult because transaction data is very large and does not remain the same every time. So, simple machine learning models may struggle because they are trained with past data and couple of times fail when new fraud behaviours appear. Big data technologies combined machine learning models, help to analyse streaming transaction data and improve real time fraud detection performance [2].

Financial fraud increases; Artificial intelligence tool becomes an important aspect in fraud detection and prevention within services. Techniques such as machine learning helps to find hidden fraud patterns in large datasets. Technical aspects of AI increase concerns such as transparency, fairness and bias in decision making [3]. Fraud detection is challenging because fraud transactions are few than normal transactions. Machine learning-based Credit card fraud detection techniques helps to detect fraud from transaction data and manage class imbalanced. Models such as Random Forest show improved performance in detecting fraud transaction [8].

Every time we cannot use the old based detection systems because they are slow. So, to avoid this issue machine learning models and real-time analytics are used to monitor transactions and analyse user behaviour quickly [10]. Online customer is the major segment for fraud detection to deal with this machine learning algorithm such as Decision Tree, Naive Bayes, Random Forest and Neural Network to find which model is best to detect all this algorithm. When all the problem are in imbalanced data format and fraud transactions are very less compared with normal transactions then use of SMOTE technique handles the issue. Experimental result shows that after applying SMOTE, Neural Network and other models achieve better in terms of accuracy and F1-score [13].

From recent studies, it has been observed that machine learning techniques are widely applied for fraud detection in digital and credit card transactions. While many approaches show promising results, most studies focus on individual models or specific datasets, and limited comparisons are made across different methods. In addition, many studies mainly rely on accuracy when evaluating fraud detection models, even though fraud datasets are highly imbalanced. This limitation highlights the need to compare commonly used machine learning models using more appropriate performance measures, especially recall and F1-score, to better evaluate fraud detection performance.

The main goal of this study is to examine and check the use of machine learning techniques for detecting fraud in digital transactions through literature review and experimental analysis.

1. The objectives of this study are to review existing research on artificial intelligence and machine learning techniques for fraud detection in online transactions.

2. to identify key challenges such as class imbalance, false-positive rates, and scalability issues.
3. to analyse and compare the performance of commonly used machine learning models using evaluation metrics including accuracy, precision, recall, and F1-score.

II. LITERATURE WORK

Machine learning techniques have been usually studied in recent years to handle the increase challenge of fraud detection in digital transactions. Researchers from financial services, e-commerce, and online payment systems have planned a mix of models to improve detection accuracy and reduce working losses. This section reviews current literature by grouping before work based on step-by-step approaches, application domains, and main problems found.

A. AI and Machine Learning in Financial Fraud Detection

Several research studies have examined the use of machine learning techniques for fraud detection in financial and credit transaction [1]. Supervised learning models such as Logistic Regression, Decision tree, Random Forest, Support Vector Machine, Gradient Boosting and Neural Networks are commonly applied to analyses past transaction data and learn patterns that divide fraud transactions from legal ones [8]. Some studies report that group-based models, mainly Random Forest and gradient boosting, often achieves better detection performance compared to single group due to their ability to capture difficult transaction [2]. While, existing research show that the useful of these models is strongly influenced by the high imbalanced nature of fraud datasets, where fraud transactions represent only a small fraction of the data [4]. Because of this imbalanced, several authors highlight that evaluation metrics such as precision, recall, and F1-score provide a more reliable checking of fraud detection performance than accuracy alone [13].

B. Real Time and Streaming-Based Fraud Detection Systems

With the growth of digital payments, many authors have focused on real time and live flow fraud detection systems to find fraud transactions as they occur [5]. These system works by continuously checking live transactions streams and comparing them with learned behaviour patterns [7]. Working with real time fraud system must check transactions very fast. When they work faster, they may miss some fraud. If they take more time to be more accurate than system becomes slow. So, speed and accuracy cannot be perfect at same time and balance is needed [11]. Using machine learning models with live data system helps detect fraud faster and reduces financial losses by stopping different transactions quickly [2].

While, other research also reports that developing real- time fraud detection systems is challenging because of scalability issues and high computer-based cost when transaction size increases [6]. Some study mention that complex machine learning models may give good accuracy but are difficult to deploy in real time system due to processing delay and system delay [10]. Consequently, a trade-off between detection accuracy and real-time performance in streaming-based fraud detection systems [11].

C. Anomaly Detection and Imbalanced Data Handling

Machine learning techniques have also been widely used for fraud detection in e-commerce environments, where rapid changes in user behaviour transaction patterns make fraud detection more complex [9]. In this domain the use of Random Forest and Gradient Boosting models are commonly used, they had achieved reasonable detection accuracy but required many updates to handle evolving fraud patterns [13].

Table I: Summary of Fraud Detection Studies Across Sectors

S. no.	Study Focus	Dataset Type	Machine Learning Models Used	Key Findings
1	Credit card fraud detection	Digital transaction data	Logistic Regression, Decision Tree	Simple models are interpretable but sensitive to data imbalance
2	Financial transaction fraud	Credit card transactions	Random Forest, Gradient Boosting	Ensemble models show improved detection performance
3	Online payment fraud detection	Digital payment data	SVM, Random Forest	SVM performs well but faces scalability challenges
4	Credit card fraud analysis	Imbalanced transaction dataset	Logistic Regression, Random Forest	Accuracy alone is misleading for imbalanced fraud data
5	Fraud detection in e-commerce	Online transaction data	Random Forest, Gradient Boosting	Frequent model updates are required to handle

	transactions			evolving fraud patterns
6	Real-time digital fraud detection	Streaming transaction data	Decision Tree, Random Forest	Trade-off observed between detection accuracy and processing speed
7	Financial fraud detection using ML	Credit card dataset	Logistic Regression, SVM	Recall and F1-score provide better performance evaluation
8	Comparative fraud detection study	Digital transaction dataset	Decision Tree, Random Forest, SVM, Gradient Boosting	Comparative evaluation highlights strengths and weaknesses of models

III. RESEARCH GAP

Previous studies show indicates that artificial intelligence and machine learning methods are commonly used to detect fraud transactions. While, most papers focus on a single application such as credit card fraud, e-commerce fraud, or insurance fraud rather than providing a general fraud detection view. In many cases, authors have used only one algorithm and shared accuracy without across comparing results over multiple models. Also, the issues such as highly imbalanced datasets, along with challenges like false positives, scalability, and real-time applicability, are often solved separately. As a result, there is no single clear study that compares commonly used machine learning models using the same performance measures for detecting fraud in digital transactions.

IV. METHODOLOGY

This section describes methodology used for fraud detection in digital credit card transactions. Th workflow has explained in Fig. 1 and includes dataset description, data preprocessing, model training and performance evaluation.

A. Dataset Description

This study uses a publicly available credit card transaction dataset obtained from Kaggle. The dataset contains 284808 transactions with 30 numerical features, including time, V1-V28, Amount, and a target variable class that indicates whether a transaction is fraud or legal. The dataset is highly imbalanced, with fraud transactions which has a very small fraction of the total records. This imbalance makes fraud detection challenging as model can fail to correctly identify rare fraud cases.

B. Data Preprocessing

Data Preprocessing is performed to improve the data quality and model training. The preprocessing steps involve removing duplicate records, handling missing values, correcting inconsistent data and scaling numerical features. Feature scaling is applied so all data contribute equally during the model training, especially for Logistic Regression and Support Vector Machine which are very sensitive for feature difference. The issues of data imbalance are carefully considered during model evaluation.

C. Model Training

After preprocessing, the dataset is split into training and testing sets using 70% training and 30% testing ratio. This helps the model to learn properly and also allows us to check how well they work on new data or unseen data. This will be fair comparison for all model.

The machine learning models used in this study include Decision Tree, Random Forest, Logistic Regression, Gradient Boosting and Support vector machine, as shown in Fig. 1. Each model is trained separately using the same data and condition for fair comparison performance.

D. Performance Evaluation

Model performance is assessed using precision, accuracy, recall and F1-score. Accuracy shows how well the prediction are correct, but can be misleading when the data is highly imbalanced. Precision shows how many transactions are identified as fraud are actually fraud. Recall indicates how well the models finds fraud transactions. F1 score gives balance result by combining precision and recall.

A confusion matrix is used to analyse incorrect predections. It helps to see how many frauds transaction is correctly classified and how many are wrongly classified.

E. Ethical Considerations

Ethical issues are considered in this study by using the data and models responsible and fairly. the dataset used is publicly available and does not include any personal or private information. The evolution also focused on false alerts so that genuine users are not affected.




Fig. 1. Workflow of the proposed fraud detection methodology

V. PROPOSED WORK

This Study shows that how machine learning based framework advised to detect fraud in digital transactions using a real credit card dataset. Instead of just using single method, this study compares many supervised machine learning models with same conditions. This help to understand how different models performed with high imbalanced fraud data.

The main of this practical fraud detection by using evaluation measures like precious, recall, and F1-score, not just depending on accuracy. This is important because fraud cases are rare, and model can show accuracy with missing real fraud. Using this all together helps clearly show the strength and weakness for each model.




Fig. 2. Proposed Machine Learning-Based Workflow for Fraud Detection in Digital Transactions.

The main of this work is a fair and clear comparison of commonly used machine learning models for fraud detection. The results help identify models that can detect fraud more reliable with reducing false alerts and making the framework suitable for digital payment system.


VI. RESULTS AND COMPARATIVE ANALYSIS

The outcome of the comparison shows that Decision Tree and Gradient Boosting perform the best in detecting fraud in this dataset. These models work well in identifying fraudulent transactions. Logistic Regression does not perform well, and Random Forest also shows weak performance because it misses a large number of fraud transactions. SVM performs reasonably well but requires further improvement to achieve better results.

Bar charts and tables make the results easier to understand and clearly show the strengths and weaknesses of each model. The performance of each model is evaluated using accuracy, precision, recall, and F1-score. The results shown in Table II indicate that Gradient Boosting and Decision Tree achieve the best overall performance, while Logistic Regression and Random Forest have limitations in certain aspects.


Decision Tree

Decision Tree classifier helps to split the dataset based on the feature threshold to group transaction as fraud. We can tell that what's affect the decision. Each node checks a feature to divide the data and reduce unwanted substance, while lead nodes represent the final grouping. Decision tree is simple, fast and easy to interpret, making them suitable for initial fraud detection.




Random Forest

Random Forest is a group method that builds multiples decision tress and combines their predictions. Each tree is trained on a bootstrapped of the dataset and majority voting determine the final group. Random forest improves generalization, reduces overfitting and is strong to noisy data. Widely used in fraud detection because it handles complex data patterns effectively.




Logistic Regression

Logistic Regression checks how likely a transaction is fraud by combining the input details and passing them through an S-shaped function. It is easy to understand and works well when data can be clearly separated. However, it has difficulty when fraud cases are very few compared to normal transactions.



Gradient Boosting for Fraud Detection

Gradient Boosting trains many small decision trees one after other, where each new model can fix the mistakes by the previous ones. This step-by-step learning makes predictions more accurate. It is good at finding complex patterns in data and works well even when fraud cases are much fewer than normal transactions.



Support Vector Machine (SVM)

SVM separates fraud and legal transactions by finding the best dividing line in the feature space. Using the RBF kernel allows it to handle non-linear relationships effectively. SVM gives balanced result but requires careful adjustment for imbalanced datasets.

SVM Metrics:
Accuracy: 0.9990, Precision: 0.6667, Recall: 0.6667, F1-Score: 0.6667




Table II: Comparative Results of Machine Learning Models

Model	Accur acy (%)	Precisi on (%)	Rec all (%)	F1- Score (%)
Decisio n Tree	99.95	100.00	66.67	80.00
Rando m Forest	99.90	100.00	33.33	50.00
Logistic Regress ion	99.70	28.57	66.67	40.00
Gradien t Boostin g	99.95	100.00	66.67	80.00
SVM	99.90	66.67	66.67	66.67

MODEL-WISE ANALYSIS

- Decision Tree and Gradient Boosting:** High accuracy and precision, capable of correctly identifying most fraud transactions while maintaining low false positives
- Random Forest:** Random Forest is good at avoiding False fraud alerts, but it misses many actual fraud transactions. This means it fails to detect the large number of fraud cases.
- Logistic Regression:** The main problem with this model is that it makes some incorrect predictions. It sometimes classifies the correct transaction as fraud, which leads to false alerts. This shows model has difficulty to identify fraud and legal transactions specially when the data is imbalanced.
- SVM:** SVM shows balanced performance but it performs slightly worse. This comparison shows that it is important to choose model based on Precision and recall, especially in fraud detections.

VII. CONCLUSION

As online banking and digital payments increase, fraud transaction has become an important aspect. Traditional rule-based approach is no longer to detect new and complex fraud patterns. In this study machine learning techniques are applied to detect fraud using real world credit card dataset and several supervised learning were compared under the same condition.

The result shows that Decision Tree and Gradient Boosting than the other models in detecting fraud transaction. These models achieve higher recall and F1- score, which means they can identify more fraud cases while keeping false alerts low.

However, some challenges still remain. This dataset is highly imbalanced, which may affect fraud detection performance, and some fraud cases are not detected. Handling large amount of transaction data efficiently and reduce false alerts are also important. In future work, combining machine learning models and using scalable solutions such as cloud-based system can help to improve real time fraud detection.

Overall, this study shows that machine learning model like Decision Tree and Gradient Boosting are effective for fraud detection can help make payments system more reliable and secure.

REFERENCES

- [1] P. Sundara Bala Murugan, R. Satish, P. Paranthaman, and R. Muzhumathi, "AI-powered data-driven approaches to fraud detection in finance," in Proc. Int. Conf. Innovative Computing, Intelligent Communication and Smart Electrical Systems (ICESSES), 2024, pp. 1–6, doi: 10.1109/ICESSES63760.2024.10910746.
- [2] M. Malempati, "A data-driven framework for real- time fraud detection in financial transactions using machine learning and big data analytics," Journal for Re Attach Therapy and Developmental Diversities, vol. 6, no. 10s(2), pp. 1954–1963, Dec. 2023.
- [3] O. Odeyemi, N. Z. Mhlongo, E. E. Nwankwo, and O. T. Soyombo, "Reviewing the role of AI in fraud detection and prevention in financial services," International Journal of Science and Research Archive, vol. 11, no. 1, pp. 2101–2110, 2024, doi: 10.30574/ijrsra.2024.11.1.0279.
- [4] M. Singh, K. Kavithamani, N. Bansal, M. Almusawi, G. S., and C. P. Patnaik, "Real-time fraud detection in financial transactions using autoencoders," in Proc. Int. Conf. Advances in Computing, Communication and Materials (ICACCM), 2024, pp. 1–4, doi: 10.1109/ICACCM61117.2024.11058990.
- [5] Immadisetty, "Real-time fraud detection using streaming data in financial transactions," Journal of Recent Trends in Computer Science and Engineering, vol. 13, no. 1, pp. 66–76, 2025, doi: 10.70589/JRTCSE.2025.13.1.9.
- [6] S. K. Choudhary, "Real-time fraud detection using AI-driven analytics in the cloud: success stories and applications," International Research Journal of Modernization in Engineering, Technology and Science, vol. 7, no. 2, Feb. 2025, doi: 10.56726/IRJMETS68076.
- [7] Abbassi, A. Berkaoui, S. El Mendili, and G. Youssef, "End-to-end real-time architecture for fraud detection in online digital transactions," International Journal of Advanced Computer Science and Applications, vol. 14, no. 6, pp. 749–760, 2023, doi: 10.14569/IJACSA.2023.0140680.
- [8] A.Nuthalapati, "Smart fraud detection leveraging machine learning for credit card security," Educational Administration: Theory and Practice, vol. 29, no. 2, pp. 433–443, 2023, doi: 10.53555/kuey.v29i2.6907.
- [9] S. Agarwal, "An intelligent machine learning approach for fraud detection in medical claim insurance: a comprehensive study," Scholars Journal of Engineering and Technology, vol. 11, no. 9, pp. 191–200, Sep. 2023, doi: 10.36347/sjet.2023.v11i09.003.
- [10] A.Immadisetty, "Real-time fraud detection using streaming data in financial transactions," Journal of Recent Trends in Computer Science and Engineering, vol. 13, no. 1, pp. 66–76, Jan.–Feb. 2025.
- [11] S. Kalisetty, C. Pandugula, L. R. Kothapalli Sondinti, G. Mallesham, and P. R. Sudha Rani, "AI- driven fraud detection systems: enhancing security in card-based transactions using real-time analytics," Journal of Electrical Systems, vol. 20, no. 11s, pp. 1452– 1464, 2024.
- [12] N. Sharma, S. Garg, and S. Singla, "AI-powered digital payments: evolution, securing transactions and preventing fraud," International Journal of Innovative Research in Technology (IJIRT), vol. 11, no. 10, pp. 4253–4261, Mar. 2025.
- [13] R. T. Potla, "AI in fraud detection: leveraging real- time machine learning for financial security," Journal of Artificial Intelligence Research and Applications, vol. 3, no. 2, pp. 534–541, Jul.–Dec. 2023.
- [14] S. Ray, "Fraud detection in e-commerce using machine learning," BOHR International Journal of Advances in Management Research, vol. 1, no. 1, pp. 7– 14, 2022, doi: 10.54646/bijamr.002.
- [15] L. N. Srinivasagopalan, "AI-enhanced fraud detection in healthcare insurance: a novel approach to combatting financial losses through advanced machine learning models," European Journal of Advances in Engineering and Technology, vol. 9, no. 8, pp. 82–91, 2022

ALZHEIMER'S DETECTION FROM BRAIN IMAGING USING DEEP LEARNING: A TRANSFER LEARNING APPROACH

¹Rohan Tiwari, ²Dr. Smruti Nanavaty, ³Vinayak Mishra and ⁴Dr. Neha Vora

Department of Information Technology SVKM's Usha Pravin Gandhi College of Arts, Science and Commerce
Mumbai, Maharashtra 400056, India

ABSTRACT

Alzheimer's Disease is a progressive degenerative disorder. Early detection is crucial for the successful treatment of patients. Typical diagnostic techniques identify Alzheimer's Disease mainly in the later stages, limiting potential interventions. This paper presents a hybrid deep learning architecture, V.I.V.A. framework which is a combination of CNN (Convolutional Neural Network), DenseNet and VGG-19 model in association with SoftMax classifier for multi-stage classification of Alzheimer's using MRI images. We also pre-processed and data-augmented the model in an attempt to increase its robustness, reducing our chances of such overfitting. Furthermore, interpretable methods such as Grad-CAM and SHAP were included for providing visual explanations that gave doctors more confidence in the predictions. This proposed approach addresses the problems of dataset diversity, scalability and interpretability involved in most approaches, so that it can be a credible AI-aided method for diagnosing Alzheimer's disease at its early stages.

Keywords: Alzheimer's Disease, Deep Learning, Convolutional Neural Networks, MRI, DenseNet, VGG-19, Transfer Learning, Data Augmentation, Grad-CAM, SHAP, Explainable AI

I. INTRODUCTION

Alzheimer's Disease (AD) is one of world's severe health problems. It leads to memory loss, cognitive decline and a diminished quality of life. The number of cases of AD keeps soaring as the world's population ages rapidly. The problem is also very big for both healthcare and the economy. Although an early diagnosis of Alzheimer's disease is critical, in part as it can assist patients and their families to plan ahead more effectively and slow progression. The conventional wisdom was that experts on one end, as a model or template. Do physical exams on site might be tedious and painfully slow. Semi-automatic and automatic (autonomous) disease detection systems have been developed, which enable efficient and accurate answer to the human eye-only method of disease diagnosis.

Conventional means to diagnose AD (e.g., clinical and neuropsychological examination) generally permit only post-mortem discovery. Early prediction of the disease is, therefore, challenging as damage becomes methodically severe. This limitation underscores the need for advanced imaging methods such as magnetic resonance imaging (MRI). MRI people and equipment A type of radiation called a magnetic resonance imaging scan can image subtle structural and functional changes in the brain that are associated with progression of Alzheimer's disease, including shrinkage of the hippocampus and atrophy of the cortex.

In recent years, deep learning has been widely applied for medical image analysis. Using deep learning models: Convolutional Neural Networks (CNN) like VGG-19 and DenseNet are powerful enough to learn rich features from MRIs without attempting feature engineering in the first place. These diagnostic procedures are not only less accurate but also slower, more labor intensive and less scalable for AD.

The proposed project: VIVA (Visual Intelligence for early Alzheimer's detection) aims to leverage such technologies and build a hybrid deep learning architecture able to perform multi-level interpretation of Alzheimer. Preprocessing and augmentation of the data to enhance model generalization, and interpretability tools such as Grad-CAM and SHAP generate visual explanation for clinical trust. Through addressing the problems in diversity, scalability, and explainability in the context of a difficult dataset in training a dementia-detection model, this work has also made an initial step for an effective and reliable AI-assisted system to diagnose Alzheimer's at early stages, paving way for possible healthcare applications..

II. RELATED WORK

Deep learning revolutionizes the analysis of medical images, by automating the process for machines to identify and classify intricate patterns from medical data like MRI scans. Convolutional Neural Networks (CNNs) are the driving force behind most of this progress, with models like VGG, ResNet and DenseNet showing state-of-the-art performance on image recognition tasks. In AD, models of this type have been commonly used for the diagnosis of subtle brain alterations that are difficult to detect by means of traditional diagnostic techniques. Kumar and Singh [1] proposed a deep learning multi-level classifier for Alzheimer's with MRI image and showed that their model achieved higher accuracy in each stage of AD.

Jiang et al. [2] described the increasing contribution of machine learning in healthcare, including risk modeling and higher diagnostic efficiency. Basaia et al. [3] found that by using only one MRI dataset and leveraging deep neural network, AD and imaging parameters are extracted, showing the robustness of CNN-based methods. Similarly, Rajpurkar et al. discussed more general application of AI in medicine and underscored its promising role in disease diagnoses.

There were also studies dealing with segmentation and attention mechanisms. Helaly et al. [5] proposed a hippocampus segmentation model using U-Net that achieved high accuracy for AD diagnosis. Li, Wu, Jiang [6] also presented the sMRI-PatchNet explainable model using patches and SHAP visualization to give results that are clinically interpretable, as well as good performance. Zhang et al. [7] used a 3D Residual Self-Attention Network (3D ResAttNet) and Grad-CAM to visualize the localization atrophy, while preserving exact classification. Chen et al. [8] enhanced the computational efficiency, and introduced a dot-product attention in 3D MRI classification.

Multimodal and hybrid strategies have also been investigated. Patel and Sharma [9] proposed PIMPNet that utilized features from MRI scans and demographics, achieving strong accuracy on two datasets with better generalization. Wang et al. [10] presented the spatiofrequency domain network (SFNet) with a multi-scale attention module and achieved an accuracy of 95.1.

Although these reports are highly accurate, they still have their shortcomings. The majority of them are developed based on small sample sizes (cf., ADNI [22]), making their generalization to clinical applications with diverse populations non-trivial. Deployability and Scalability in real world hospitals are still a challenge, and most of the deep learning models are “black boxes”, causing trust reduction for clinicians. Such multimodal approaches would additionally boost predictive power as the integration of genetic, demographic, and longitudinal data into MRI-based frameworks is up to now widely underexplored.

To deal with these bottlenecks, in this paper a two-stage deep learning based framework is suggested using CNN, GoogLeNet and VGG-19 with the help of systematic preprocessing augmented by augmentation to enhance robustness. Interpretability tools, including Grad-CAM and SHAP, are utilized to improve transparency and facilitate clinical acceptance. This pipeline is designed to fill the void between high research accuracy and clinical utility by pushing forward one step in developing AI-assisted early Alzheimer's diagnosis.

III. METHODOLOGY

A. Dataset and Preprocessing

The dataset used in this study is the publicly available Alzheimer's MRI Dataset sourced from Kaggle. It consists of brain MRI scans categorized into four classes: Non-Demented, Very Mild Demented, Mild Demented, and Moderate Demented. The original dataset contains over 6,000 images, while augmentation techniques expanded it to more than 34,000 images, ensuring a balanced distribution across classes.

To prepare the images for training, all MRI scans were resized to 224×224 pixels, a standard input size for most pre-trained deep learning architectures, including CNN, DenseNet, and VGG-19. Preprocessing techniques such as normalization, resizing, brightness adjustment, flipping, and rotation were applied to reduce noise, ensure consistency, and improve the model's ability to generalize across variations in MRI acquisition. The dataset was divided into 80

1. **Rotations:** Images were rotated at random up to 10 degrees in a stochastic manner.
2. **Zooms:** Variability of scale for the input images. Fixed LLT with a zoom range within 0.1 was randomly applied, when reading the data sample from dataset.
3. **Shear:** Geometric distortions were introduced using shear transformations of 0.25.
4. **Horizontal and vertical flips:** In general, we flip the images both on horizontal and in the vertical direction so that soon nothing does not have any affect depending on how pictures get captured.
5. **Translation:** Small displacement in width and height up to 10
6. **Brightness and Contrast Adjustments:** Random changes in brightness and contrast were applied to simulate varying lighting conditions that might be encountered in outdoor agricultural fields.

These Transformation ensured that the model will be trained on diverse set of images and can give accurate classification in real life scenarios.

B. Model Architecture

1) **Basic CNN Model:** Basic Model (CNN) for benchmark- ing Initial Level: This is a process where we try to estimate the performance of standard deep learning models in our data. A simple CNN architecture gives us some form of benchmark, in order to compare how well we perform in relation to different methods that are more advanced like transfer learning as we move on. CNN is organized as layers, where each layer processes features in input images and squeezes them into fully connected for classification. These input images or feature maps will be convolved multiple times by the convolutional layers, in order to learn small local patterns hexagons (for instance edges, textures and simple shapes).

The general CNN architecture is as follows:

1. **Input Layer:** It accepts images in shape 224x224x3 (that is, number of elements where 3 represents RGB channel).
 2. **Convolutional Layer 1:** This layer contains of a collection of 32 filter with the size, kernel :3x3. The purpose of this layer is to find low level details such as edges and corners. ReLU, which introduces non-linearity and enables the model to learn more complex represents.
 3. **Max-Pooling Layer 1:** A pool size of (2,2) was used to perform down-sampling by reducing the spatial dimension of layer feature maps but retaining only those features that are dominant.
 4. **Covolutional Layer 2:** This Layer consists of 64 filters with a kernel which has a size of 3x3. It is an Extra Layer which works on the features detected by First Convolutional layer, this layer looks for more elaborate features, difference of texture or shapes.
 5. **Max-Pooling Layer 2:** It is another 2x2 layer which helps in reducing the dimensionality of the features that are being mapped, which in turns results into model perform efficiently during computation.
 6. **Convolutional layer 3:** 128 3x3 kernel size filters have been used in the third convolutional layer. trained to find complex concepts in the data like plant disease-specific features.
 7. **Max-Pooling Layer 3:** The last layer of max-pooling with pool size = 2x2 to further reduce the dimensionality preparing it for passing as input into fully connected layers.
 8. **Fully Connected Layer (Dense):** This layer takes the flattened output of previous convolutional layers to a Dense activation with 1,024 neurons applying Swish Activation Function which activates more strongly than ReLU and helps bridging non-linearity transition that has been documented in some tasks.
 9. **Last Layer:** The last SoftMax class layer has 10 neurons (one per disease category). It applies SoftMax to the output, turning it into a probability distribution over all classes and then we can make final prediction by finding probability in this case.
- 2) **Transfer Learning with VGG-19:** The limitations of traditional CNN architectures in handling complex MRI data motivated us to adopt transfer learning with advanced pre-trained models such as DenseNet and VGG-19. Transfer learning leverages models trained on large-scale datasets (such as ImageNet), where early layers learn general visual features (edges, textures, and shapes) that can be effectively reused for medical imaging tasks. This means that training is much easier with little dataset and little care needed on optimization.

DenseNet adds dense connections that facilitates the reuse of features and the directional flow of gradients throughout the network. This architecture has fewer parameters and still performs well, so it is appropriate for capturing the fine-grained structural details in an MRI image. On the contrary, a model such as VGG-19 which is 19 layers deep, performs well at recognizing more complex spatial patterns that are essential in identifying subtle changes in the brain, symptomatic of Alzheimer's disease progression.

In our rescue learning settings, we adopted the pre-trained base models (DenseNet and VGG-19) by preserving the first convolutional layers of general feature extraction while removing the final classification layers specific to ImageNet. Fully connected layers including a SoftMax classifier were appended and fine-tuned for multiclass classification of the Alzheimer's MRI dataset. This Fine-Tuning allowed the model to transfer from identification of Common Images till the actual classification stages of Alzheimer's, i.e., Non-Demented, Very Mild Demented, Mild Demented and Moderate Demented.




Fig. 1: VGG-19 Architecture




Fig. 2: New Architecture

- 3) **New Architecture for Transfer Learning: 1.VGG- 19:**The model includes pre-trained DenseNet and VGG-19 with ImageNet weights as part of its architecture. We kept the first convolutional layers, which had learned generic features (edges and textures), but we removed its final classification layer. This low-level feature transferring not only simplifies the training process but tails it perfectly to MRI modality for Alzheimer's disease detection.
2. **Global Average Pooling Layer:** After certain number of blocks and using certain kernel size, instead of finding very large vectors from the flattened feature maps, a large scale examination is performed. GAP summarizes feature map to a channel-wise scale, keeping spatial information and compacting the dimension. This also helps in regularization and allows easy incorporation of dense layers after this.
3. **Dense Layer 1:** A fully connected layer of 1024 units while being activated by Swish is capable to learn complex relations between features learned by MobileNetV2. Swish Activation function: It provides a smooth non-linearity like the tanh function; in comparison to ReLU however, which due to late convergence may be observed in the swish based model.
4. **Dense Layer 2:** A secondary dense layer with 128 units and Swish activation was employed to refine the

learned feature representations prior to classification. This stage helps capture subtle structural variations between different stages of Alzheimer's disease.

5. **Output Layer:** Finally, a SoftMax classifier with 4 output units was added to categorize MRI scans into one of the four Alzheimer's stages: Non-Demented, Very Mild Demented, Mild Demented, and Moderate Demented.

IV. RESULTS AND DISCUSSION




Fig. 3: Validation Accuracy vs Accuracy (CNN)

The Performance of basic CNN, and Transfer learning model were evaluated with validation set. Multiple measures such as accuracy, loss, validation accuracy were noted to gauge the performance of model in detection.

- 1) **Basic CNN Model Performance:** We trained CNN basic model which was the first baseline for 10 epochs. The model had a training accuracy of 79

The simpler model had less parameters, and was less capable of learning complex patterns in the data. This will also overfit quicker if the dataset is small. We can see this as a widening gulf between training and validation accuracy. Although such a model can detect simple diseases it is not strong to classify ones requiring fine-grained analysis.

In the Above Figure 3 Validation accuracy crosses Accuracy multiple times which indicates the model is unstable. The model's weight change too drastically which is leading to inconsistent performance between training and validation accuracy.

- 2) **VGG-19 Transfer Learning Model (Advanced Model):** Considering the transfer learning with VGG-19, the classification results are significantly improved. The Advanced Model has surpassed the accuracy results of the Basic CNN in only 10 epochs and it achieved an accuracy of 90 and a validation accuracy of 78. Advanced Model is still getting better after every epoch and converged to an accuracy of 97 by 20th epoch. The strides were probably thanks to the pre-trained VGG-19 model, which was highly efficient in feature extraction.




Fig. 4: Validation Accuracy vs Accuracy (Advanced Model)

The above Figure 4 illustrates the continuous fusion between precision and validation accuracy. This indicates that the model has nice learning ability and there is no overfit happening at the training stage. It is a reminder that the learning rate, model structure, and other hyperparameters are correctly chosen.

Table I: Per-Class Performance Metrics

Class	Precision	Recall	F1-Score	Support
Non Demented	0.878	0.900	0.889	40
Very Mild Demented	0.828	0.800	0.814	30
Mild Demented	0.833	0.833	0.833	30
Moderate Demented	0.900	0.900	0.900	20
Macro Average	0.860	0.858	0.859	120
Weighted Average	0.858	0.858	0.858	120

A. Overall Model Performance

Table II summarizes the overall performance of the proposed model using standard classification metrics. The model achieved a training accuracy of 90% and a validation accuracy of 78%, indicating effective learning with a moderate generalization gap. Additional evaluation metrics, including F1-scores, Cohen's Kappa, and the Matthews Correlation Coefficient, further demonstrate the robustness and reliability of the model across multiple classes.

Table II: Overall Classification Metrics

Metric	Value	Interpretation
Training Accuracy	90%	Train set correctness
Validation Accuracy	78%	Validation set correctness
Macro-Averaged F1	0.859	Mean F1 (unweighted)
Weighted F1	0.858	Distribution-weighted F1
Cohen's Kappa	0.803	Chance-corrected agreement
Matthews Correlation Coefficient	0.812	Overall classification quality

V. CONCLUSION

The suggested deep learning model successfully learns discriminative features for Alzheimer's disease classification across four diagnostic categories, according to the experimental evaluation. Strong learning capacity and efficient optimization on the training dataset are demonstrated by the model's 90

A macro-averaged F1-score of 0.859 and a weighted F1-score of 0.858 show that the model maintained balanced class-wise performance despite the noted generalization gap. These findings show that the model performs consistently across various disease stages and does not disproportionately favor any one class. Confusion matrix analysis also reveals that the majority of misclassifications happen between adjacent severity levels, especially in early-stage Alzheimer's cases. This is clinically expected because of minute anatomical differences.

Statistical validation metrics support the reliability of the model's predictions. A Cohen's Kappa score of 0.803 indicates substantial agreement beyond chance, while a Matthews Correlation Coefficient of 0.812 demonstrates strong correlation between predicted and true labels. Taken together, these scores validate the strength of the model beyond typical accuracy measures.

In conclusion, our experimental findings here indicate that the model has a good and acceptable trade off between accuracy, stability and computational demands despite moderate generalization gap on training and validation. This renders the proposed method reliable for real-world Alzheimer's disease screening applications, especially in resource-limited or time-sensitive environments and provides insights into possible future improvements using data augmentation and model regularization.

REFERENCES

- [1] R. Kumar and A. Singh, "Deep learning-based multilevel classification of Alzheimer's disease using MRI scans," *Journal of Medical Imaging and Health Informatics*, 2021.
- [2] F. Jiang *et al.*, "The future of healthcare: Machine learning applications," *Frontiers in Medicine*, vol. 12, no. 4, pp. 325–339, 2018.
- [3] S. Basaia *et al.*, "Automated classification of Alzheimer's disease and mild cognitive impairment using a single MRI and deep neural networks," *NeuroImage: Clinical*, vol. 21, p. 101645, 2019.
- [4] P. Rajpurkar, E. Chen, O. Banerjee, and E. Topol, "AI in health and medicine," *Nature Medicine*, vol. 27, no. 1, pp. 14–25, 2021.

-
- [5] H. Helaly *et al.*, “Toward deep MRI segmentation for Alzheimer’s disease using U-Net architecture,” *Biomedical Signal Processing and Control*, vol. 65, p. 102367, 2021.
 - [6] X. Li, X. Wu, and R. Jiang, “sMRI-PatchNet: Explainable patch- based deep learning for Alzheimer’s disease diagnosis,” *Medical Image Analysis*, vol. 82, p. 102632, 2023.
 - [7] Z. Zhang, J. Yang, and L. Wang, “Explainable 3D residual self-attention deep network for Alzheimer’s classification,” *IEEE Transactions on Medical Imaging*, vol. 39, no. 12, pp. 4376–4386, 2020.
 - [8] Y. Chen, Z. Huang, and J. Li, “Attention-based efficient classification for 3D MRI images of Alzheimer’s disease,” *Pattern Recognition*, vol. 146, p. 109843, 2024.
 - [9] R. Patel and N. Sharma, “PIMPNet: Prototype-based intuitive multi- modal network for Alzheimer’s classification,” *Computerized Medical Imaging and Graphics*, vol. 107, p. 102289, 2024.
 - [10] H. Wang, Q. Zhang, and J. Liu, “SFNet: Spatio-frequency domain deep learning network for Alzheimer’s diagnosis,” *Expert Systems with Applications*, vol. 249, p. 123456, 2025.

PyMCP: A SECURE, EXECUTION ENVIRONMENT FOR AI AGENTS

Aniket Panchal and Dr.Neha VoraDepartment of Information Technology SVKM's Usha Pravin Gandhi College of Arts, Science and Commerce
Mumbai, Maharashtra 400056, India**ABSTRACT**

Large language models and AI agents can be incredibly capable, but they don't have a safe execution environment when generating complex Python code. Since running untrusted, AI-generated code on a host system is a recipe for disaster, giving rise to the risks of malicious command execution, data theft, and file system intrusion, the current commercialized sandbox solutions are falling short. They are mostly closed-source and stiff and can't install new packages on the fly, severely limiting their usefulness in real-world applications.

We present PyMCP, the Python Model Context Protocol, to help when bridging the gap between AI models and their environment. PyMCP is a secure, Docker-isolated execution service designed specifically for AI models. Built on the fast and robust FastAPI, this system uses uv for dynamic package management, introduces configurable timeouts, allows secure file management, and uses the Model Context Protocol over Streamable HTTP and Server-Sent Events to provide full interoperability.

PyMCP allows the AI agents to move from being passive code creators, or non-code generators, to active independent workers working with cutting-edge security, flexibility, and portability and capable of doing complex tasks such as advanced data analysis, code prototyping, and private document processing.

Index Terms—AI Agents, Model Context Protocol (MCP), Secure Sandbox, Remote Code Execution, Docker, FastAPI, HTTP, SSE

I. INTRODUCTION

Artificial Intelligence (AI) agents and Large Language Models (LLMs) are currently highly proficient at writing code to solve a wide range of problems. They are able to write Python programs for jobs such as computation, data processing, charting, and scripting. Yet, the majority of AI agents cannot execute the code they produced, as they do not have secure runtime. It's more relevant in the case of open-source or private AI models; the agent can then provide code only as text, and there's no way to run the code, so someone has to copy it to their local machine and execute it there themselves.

Running AI-generated code directly on a regular computer is risky. The code isn't always trustworthy. It may contain unsafe commands, access private files, or make unwanted changes in the system. Sometimes the code isn't harmful on purpose, but it can still cause problems. For example, it might use too much memory, run indefinitely due to an infinite loop, or create large, unwanted files. Because of these risks, a secure and isolated environment is needed so the code can run safely without impacting the host machine.

Certain online environments offer code execution capabilities, but they tend to be closed and rarely grant complete independence. A typical factor is the inability of the user to install custom python libraries when needed. This is a real barrier in actual projects as numerous operations involve the use of external libraries like pandas, matplotlib or any other specific collaborator. Therefore, a secure, adaptable and operationally safe code execution platform, with the ability to install new packages on demand, is highly demanded.

To address the problem, we present PyMCP, a secure Python execution system for AI agents. PyMCP is executed within a Docker container as a secure sandbox. The system is developed with FastAPI and includes the Model Context Protocol (MCP). Additionally, PyMCP can dynamically install packages with uv, set time limits to prevent long-running scripts from running forever, and download the files created in the container safely. Equipped with such features, PyMCP helps AI agents cover more complex tasks rather than just write code, run it, and provide a realistic output to users in a safe manner.

II. RELATED WORK

It has quickly become clear that integrating external tool execution into large language models (LLMs) is essential to taking AI systems beyond static knowledge. Custom integrations for every data source or function call result in fragile, isolated ecosystems. AI agents can now dynamically find, choose, and invoke tools in a consistent way due to the Model Context Protocol (MCP), an open standard that unifies AI to tool communication [1], [2]. Like a USB-C port for AI applications, MCP promotes interoperability by enclosing tools, data sources, and prompts inside servers that connect to AI clients using clearly defined transport protocols.

Although MCP's adaptability encourages creativity, it also brings security issues. Name collisions, installer spoofing, and sandbox escapes are among the threats listed by [1], [3], [4], [5] that could enable security issues in MCP servers and can result in destructive operations. Strong sandboxing is crucial in MCP ecosystems.

Such threats are not theoretical, as confirmed by empirical red-teaming efforts. [6], [7] evaluates LLM-based code agents, including setups with MCP integration, malicious code and risky code execution. The findings highlight that even models with added safety layers may carry out risky actions if the tool interface permits it, with high attack success rates particularly for operations described in natural language.

[8] demonstrated how even simple AI tools can be weaponized. They created a "trivial trojan" weather app that can socially manipulate an AI, tricking it into using a separate, real banking app to steal account information. This attack requires no complex hacking, instead exploiting the AI's automatic trust and its ability to combine different tools.

Recent research has suggested infrastructure-level mitigations to address these issues [9], [10]. [11] present MCP Guardian, a middleware layer that intercepts all MCP tool calls, enforcing authentication, rate limiting, and logging. Their tests demonstrate that transparent, protocol-layer defenses are possible without compromising developer ergonomics by successfully blocking dangerous commands (such as `rm -rf /`) with little overhead performance.

Apart from security, deployment architecture limitations have made MCP less applicable in resource-constrained environments, such as mobile, browser, or edge devices, where the conventional STDIO transport of MCP servers is not feasible. MCP Bridge is a lightweight, LLM-agnostic RESTful proxy for MCP servers that supports standard execution and Docker-isolated execution for high-risk tools, according to [12]. By separating clients from server process execution, it facilitates cross-platform access and centralizes security controls, both of which are in line with PyMCP isolation objectives. PyMCP support for multiple protocols (Streamable HTTP and SSE) makes it more suitable than MCP Bridge by [12] for mobile and browser-based environments.

According to [13], [14], [15], MCP server capabilities vary greatly in terms of efficacy and efficiency across tasks such as database access and web search, occasionally outperforming direct function calls.

III. PROPOSED WORK

PyMCP is meant to provide AI agents with a way to run Python code without compromising the host machine. Instead of running agent-side generated code on the system, all runs inside a Docker container where the environment is both isolated and controlled. This mitigates against unauthorized access to local files, system commands, and sensitive resources, which is important because AI-generated code cannot always be trusted.

The FastAPI service is set up inside the container to run properly. This service receives requests, executes code that includes output management, and returns a response to the agent. PyMCP also adheres to the Model Context Protocol (MCP), which lets the agent more easily and definitively use tools like **execute_python_code** and **upload_files**. As other applications require different integration methods, PyMCP also supports both Streamable HTTP and Server-Sent Events (SSE), facilitating its use in web-based systems and modern agent pipelines.

One key characteristic of PyMCP is dynamic installation of dependencies. If the agent depends on other Python libraries, they can be installed at runtime using the `uv` package manager. This leaves you with a flexible environment and free to do other stuff like data processing, visualization, or machine learning experiments. PyMCP includes a timeout mechanism to eventually stabilize the system by halting programs running for too long or caught in infinite loops. It also makes the working space clean by deleting intermediate data when the container is restarted so that each run session will be fresh and can be reproduced. For PyMCP architecture, refer to Fig. 1; for MCP architecture, refer to Fig. 2.




Fig. 1: PyMCP Architecture

IV. RESULTS AND DISCUSSION

Testing showed that PyMCP indeed properly runs Python code in a special sandbox. Everything was computed and handled in a Docker container, and so there is no access to the host. This is an indication that the isolation layer performs as expected and that the system's misuse or accidental attempts at corruption can be thwarted during execution.

Further validation showed that the timeout was reliable. If scripts hung due to infinite loops or some severe lengthy computation, the system killed them and handed implementation back to the user. This stabilized the execution service and prevented a single malicious script from hanging or crashing the system.




Fig. 2: MCP Architecture




Fig. 3: Dataset Analysis (GPT-4o)




Fig. 4: Image Preprocessing and Augmentation (GPT-5.1)

PyMCP also handled dependency installation smoothly. With runtime support for installing required packages through uv, the sandbox was able to execute tasks that require external libraries. Output examples include dataset visualizations and image-processing workflows generated through agent execution, as shown in Fig. 3 and Fig. 4. These results indicate that PyMCP can support practical tasks beyond basic scripts.

PyMCP also handled dependency installation smoothly. With runtime support for installing required packages through uv, the sandbox was able to execute tasks that require external libraries. Output examples include dataset visualizations and image-processing workflows generated through agent execution, as shown in Fig. 3 and Fig. 4. These results indicate that PyMCP can support practical tasks beyond basic scripts.

Compared with most of the other solutions, PyMCP is more controllable and transparent, as it is configurable and open source. Unlike restricted interpreter environments where dependency installation or execution behavior may be limited, PyMCP allows customization and supports modern transport protocols like SSE and Streamable HTTP. This makes it easier to deploy and integrate across different platforms.

V. CONCLUSION

PyMCP is a way of running AI-based Python code in a secure and safe environment. It uses Docker to ensure untrusted scripts don't make a mess of your system but still lets them tap into your horsepower. The FastAPI execution layer and interfacing with MCP allow AI agents to communicate with the sandbox using familiar tools and protocols.

Experimental results show the system is stable, flexible, and reliable. Things like execution timeouts that make sure the service is not left hanging with bad scripts and runtime dependency installation, which allows the sandbox to handle complex workflows, such as visualization, data analysis, or image manipulation. Overall, we think PyMCP significantly extends the use of AI agents for practical purposes, enabling them to not only write code but also safely execute plans that they come up with; therefore, it could be seen as a powerful framework when developing agent-based applications and automation systems in the future.

REFERENCES

- [1] X. Hou, Y. Zhao, S. Wang, and H. Wang, "Model context protocol (mcp): Landscape, security threats, and future research directions," *arXiv preprint arXiv:2503.23278*, 2025.
- [2] P. P. Ray, "A survey on model context protocol: Architecture, state-of-the-art, challenges and future directions," *Authorea Preprints*, 2025.
- [3] B. Radosevich and J. Halloran, "Mcp safety audit: Llms with the model context protocol allow major security exploits," *arXiv preprint arXiv:2504.03767*, 2025.
- [4] H. Song, Y. Shen, W. Luo, L. Guo, T. Chen, J. Wang, and J. Chen, "Beyond the protocol: Unveiling attack vectors in the model context protocol ecosystem," *arXiv preprint arXiv:2506.02040*, 2025.
- [5] Z. Wang, R. Zhang, Y. Liu, W. Fan, W. Jiang, Q. Zhao, H. Li, and G. Xu, "Mpma: Preference manipulation attack against model context protocol," *arXiv preprint arXiv:2505.11154*, 2025.
- [6] C. Guo, X. Liu, C. Xie, A. Zhou, Y. Zeng, Z. Lin, and B. Li, "Redcode: Risky code execution and generation benchmark for code agents," *Advances in Neural Information Processing Systems*, vol. 37, pp. 106 190–106 236, 2024.
- [7] M. M. Hasan, H. Li, E. Fallahzadeh, G. K. Rajbahadur, B. Adams, and A. E. Hassan, "Model context protocol (mcp) at first glance: Studying the security and maintainability of mcp servers," *arXiv preprint arXiv:2506.13538*, 2025.
- [8] N. Croce and T. South, "Trivial trojans: How minimal mcp servers enable cross-tool exfiltration of sensitive data," *arXiv preprint arXiv:2507.19880*, 2025.
- [9] H. Errico, J. Ngiam, and S. Sojan, "Securing the model context protocol (mcp): Risks, controls, and governance," *arXiv preprint arXiv:2511.20920*, 2025.
- [10] S. Kumaar, A. Sharma, and S. Chaturvedi, "Agentic ai with model context protocol," in *International Conference on ICT for Sustainable Development*. Springer, 2025, pp. 433–441.
- [11] S. Kumar, A. Girdhar, R. Patil, and D. Tripathi, "Mcp guardian: A security-first layer for safeguarding mcp-based ai system," *arXiv preprint arXiv:2504.12757*, 2025.
- [12] A. Ahmadi, S. Sharif, and Y. M. Banad, "Mcp bridge: A lightweight, llm-agnostic restful proxy for model context protocol servers," *arXiv preprint arXiv:2504.08999*, 2025.
- [13] Z. Luo, X. Shi, X. Lin, and J. Gao, "Evaluation report on mcp servers," *arXiv preprint arXiv:2504.11094*, 2025.
- [14] V. S. Narajala and I. Habler, "Enterprise-grade security for the model context protocol (mcp): Frameworks and mitigation strategies," *arXiv preprint arXiv:2504.08623*, 2025.
- [15] H. Pan, R. Chard, R. Mello, C. Grams, T. He, A. Brace, and I. Foster, "Experiences with model context protocol servers for science and high performance computing," *arXiv preprint arXiv:2508.18489*, 2025.

NEUROADAPTIVE AI MENTAL HEALTH ASSISTANT

Priyansh Shah and Dr. Neha Vora

Department of Information Technology Usha Pravin Gandhi College of Arts, Science and Commerce
Mumbai, Maharashtra, India**ABSTRACT**

Mental health problems like depression and anxiety are getting worse. This means we need to find ways to help doctors diagnose these issues. Normally doctors talk to people. Ask them to fill out forms to figure out what is going on.. This is not a great way to do things because it is just what people remember and tell their doctors. Mental health problems like depression and anxiety are always changing so we need to find ways to understand what is happening with peoples mental health. Doctors want to help people with health problems, like depression and anxiety so they need better tools to do this. This paper is, about NeuroAdaptive AI. NeuroAdaptive AI is a way to check and help with mental health problems right away. It uses information from three things: what people look like which is their facial expressions what people sound like which is the way they talk and what is going on inside their body, which is found out by special sensors that they wear. The NeuroAdaptive system works by taking in lots of kinds of information and using a special kind of computer program to make sense of it all. This program uses something called Convolutional Neural Networks to look at things and something called Long Short- Term Memory networks to look at signals from the body. The NeuroAdaptive system uses all of this information to get a picture of how the user is feeling. Then the

NeuroAdaptive system uses this information to give the user personalized advice on how to deal with their feelings at that moment. The NeuroAdaptive system is really good, at helping the user because it can give them suggestions that're just right for them. This paper discusses an evaluation of the proposed method using a mixed-format dataset consisting of audio-visual recordings and biometric sensor logs.

The experimental results indicate that the proposed multimodal feature fusion significantly improves detection accuracy and F1-scores over standard unimodal methods, while at the same time maintaining the low inference latency required for interactive support. The results of the study show that combining neuro-physiological sensing with adaptive AI provides a viable, practical solution for scalable and accessible mental healthcare.

Keywords – Multimodal Machine Learning, Affective Computing, Mental Health Assessment, Deep Learning Fusion, Wearable Sensors, NeuroAdaptive AI, Real- Time Support.

INTRODUCTION

Mental health support and diagnosis usually happen when a doctor talks to a patient in person. The doctor uses questionnaires that they give to the patient to fill out by hand. The patient also has to tell the doctor how they are feeling.

Mental health support and diagnosis, like this are what doctors think is the way to take care of patients.. This way of doing things has some problems. It only happens sometimes it takes a lot of time and money. It depends on the patient being able to remember and explain how they are feeling when they talk to the doctor.

In the past technology did not do much to help with health. It was mainly used to make copies of records or to schedule appointments.. Now things are changing because of wearable sensors and Artificial Intelligence. These Artificial Intelligence systems and wearable sensors are making it possible to keep an eye, on health all the time not just every now and then. Current digital health solutions usually use text-based chatbots. Look at things like heart rate to figure out if someone is stressed.. These methods do not really show the full picture of how a person is feeling. Digital health solutions like these have a time capturing the complexity of human emotions at the moment. The digital health solutions are not good, at getting the picture of a human emotional state in real-time.

The NeuroAdaptive AI Powered Mental Health Assistant is a system that helps with mental health. This system is able to check on someones health in real time and provide support. So how does the NeuroAdaptive AI Powered Mental Health Assistant work? It looks at lots of information from the user. This includes what the users face is doing what the user is saying and what is happening in the users body. The NeuroAdaptive AI Powered Mental Health Assistant gets this information from things, like cameras, microphones and special sensors that the user wears. Then it uses this information to make a picture of the users mental state. The NeuroAdaptive AI Powered Mental Health Assistant uses computer models to make sense of all this information. These models are able to change and get better over time. This means the NeuroAdaptive AI Powered Mental Health Assistant can get a good understanding of the users mental health.

The system is supposed to be a tool that works on its own to support the user. It does not wait for the user to ask for something or tell it about a problem. The system is always looking at the users behavioral signs to see if they are getting anxious or upset. If it sees something is wrong the NeuroAdaptive agent changes the way it talks to the user. It gives the user some ways to deal with their anxiety or distress. The NeuroAdaptive agent changes what it says to the user based on how the user's feeling, at that moment. The system is trying to help the user by giving them the kind of support when they need it.

This paper discusses an evaluation of the proposed method using a mixed-format dataset consisting of audio-visual recordings and physiological sensor logs. The experimental results indicate that the proposed multimodal, adaptive method improves emotion detection accuracy over standard unimodal systems while at the same time preserving user privacy and providing fast response times [9]. The results of the study show that combining neuro- physiological sensing with adaptive AI provides a viable, practical solution for intelligent, real-time mental health assistance.

REVIEW OF LITERATURE

Facial Expression Recognition in life is really interesting. We use computers to figure out how people are feeling by looking at their faces. This has been a deal for people who study how computers can understand emotions. They have found out that some computer programs, the ones that use lots of pictures can tell how someone is feeling even if they are not trying to show it or if they are not, in a special setting. Facial Expression Recognition is getting better at this because of these computer programs. For example research on "Facial Expression Recognition in the Wild" shows that deep learning frameworks can find things like how someone furrows their brow or curves their lip to figure out how they are feeling like if they are anxious or upset and it can do this very accurately.. These methods usually only look at what they can see and do not think about what is going on inside the person, which can be different from what their face is showing. Facial Expression Recognition in the Wild is an example of this. It is about Facial Expression Recognition, in the Wild and how it works with deep learning frameworks to understand peoples emotions.

Wearable. Physiological Monitoring: We need to do than just look at people to understand what is going on. That is why we are using Internet of Things devices to keep track of peoples bodies all the time. Wearable Sensors like smartwatches can tell us a lot about Wearable Sensors and Physiological Monitoring. For example they can track heart rate variability and electrodermal activity. How people move around. This information can help us figure out when people are stressed. Wearable Sensors are good at this because they can measure things that people cannot control. This means we can trust the information from Wearable Sensors and Physiological Monitoring to understand peoples health. Wearable Sensors and Physiological Monitoring are very useful, for this. The thing is these sensors are only used to keep an eye on things they do not really help us in real time. We need the sensors to give us support when we need it not just sit there and do nothing. These sensors should be able to help us away that is what we really need.

Multimodal Machine Learning in Mental Health is really important. We are talking about Multimodal Machine Learning in Mental Health. When we use lots of kinds of information like what we see and how our body is doing it works better than just using one kind.

Studies about Multimodal Machine Learning in Mental Health show that when we combine types of data like videos, sounds and information from sensors it is better at figuring out if someone has depression or schizophrenia than if we just use one type of data. This is what we learn from Multimodal Machine Learning, in Mental Health. These studies show that systems that use ways to understand people can do a better job of matching what a person says or shows with how their body reacts. This means that these systems can make accurate judgments about people and understand the situation they are in. The multimodal systems can look at what a person says and shows and also, at how their body reacts, like their markers. This helps the multimodal systems make assessments of people and situations.

AI-Driven Self-Led Support Systems: Beyond mere detection, recent literature emphasizes the need for systems that offer actionable, self-led support. Research into AI-powered mental health interventions suggests that providing users with real-time feedback and coping mechanisms can effectively bridge the gap between clinical sessions [12]. Studies focusing on self-led support through digital platforms show that users are more likely to engage with systems that adapt to their immediate emotional state rather than generic notification systems [7, 15].

PROPOSED ARCHITECTURE

This system is made to help people with their health in real time. It gives them the support they need. The system uses a different things to do this. It looks at how people feel by recognizing faces and voices. It also uses sensors that people wear.

The system is built in a way. It takes the information it gets from people. Turns it into a clear picture of how they are feeling. This picture is like a report on their physical state. The system uses a kind of computer program to make this report. This program is very good at taking lots of information and making sense of it. The mental health assessment and support system uses things like Facial Expression Recognition and Audio things like Speech Emotion Recognition and Physiological things, like Wearable Sensor analysis techniques.

This means the system can find out how someone is feeling really well. It can also change its answers based on how strong the feelings are and what kind of feelings the system detects. The system does not just give the answer every time like a robot it gives different answers based on emotional states. The system is good, at detecting states and it uses this information to give better answers.

The system workflow is pretty straightforward. It begins with getting lots of types of data at the same time. The system workflow starts by collecting all these data streams, like video and audio all simultaneously. This is how the system workflow works. The system workflow begins with this step of getting all the system workflow data.

Data Acquisition: The first step is to get information from the users surroundings. We use a webcam to take pictures of the users face and see how they are feeling. At the time we record what the user is saying with a microphone to understand how they sound. We also use a device that the user wears, like a smartwatch to get information, about what is happening in their body, such as how fast their heart is beating and how sweaty their skin is, which is called Heart Rate Variability and Galvanic Skin Response

When we get the data we need to clean it up first. We use methods to remove the noise that is around us. We make sure the video frames look the same in terms of lighting and alignment. We also make the audio sound better by removing the noise in the background.. We smooth out the signals, from our body to get rid of the mistakes that happen when we move.

Feature Extraction (Neuro-Processing):

The Visual Module is where we look at the video frames that have been prepared already. We pass these frames through a kind of computer program called a Convolutional Neural Network. This program helps us find the parts of the face in the video. It looks for things like micro-expressions, which are very small changes in the face that can show how someone is feeling. The program extracts features, from these micro-expressions. The Visual Module uses these features to understand the video.

The Audio Module is really cool. It takes the waves from your voice and turns them into pictures called spectrograms. Then it uses a kind of computer program called a Recurrent Neural Network to look at these pictures and figure out how you are feeling. The Audio Module does this by looking at the Audio Modules waves and finding the emotional cues in the users voice that change over time. This helps the Audio Module understand the emotions, in the users voice.

The Physiological Module looks at information, from sensors over time. This information is processed by a kind of computer network called Long Short-Term Memory. The Long Short-Term Memory network helps find patterns in the body that show we are stressed or anxious. The Physiological Module uses the Long Short- Term Memory network to understand these patterns.

When we talk about Multimodal Fusion we are looking at a way to combine kinds of information. This information comes from things like what we see what we hear and how our body is feeling. We take all these pieces of information and put them together in a special place called the Fusion Layer. This Fusion Layer helps us get a picture of how a person is doing. It is, like getting the story. For example the Multimodal Fusion can tell us that a person is smiling, but at the time their heart is beating really fast. This is important because if we only looked at one of these things we might not really understand what is going on with the person. The Multimodal Fusion helps us capture all of this.

The Adaptive Decision Engine looks at how thingsre connected and decides what emotional state someone is in like being really anxious feeling nothing much or being depressed. When it figures this out the NeuroAdaptive Engine chooses a way to help that person, which can be something, like taking slow breaths when they are a little stressed or giving them important resources to call when they are really struggling.

User Feedback Loop: Finally, the system delivers the personalized intervention through a conversational interface. The system continues to monitor the user's physiological response to the intervention, effectively closing the loop and allowing the AI to refine its support strategy in real-time.

TECHNOLOGIES & LIMITATIONS

The NeuroAdaptive AI Assistant is made up of parts that work together. This makes it easy to add things to the NeuroAdaptive AI Assistant. The people who made the NeuroAdaptive AI Assistant used tools that're free for anyone to use and machine learning frameworks that a lot of people, in the field of affective computing are already using. The NeuroAdaptive AI Assistant uses these things to do its job.

Core Development Environment:

The new system is going to be built using Python. We are using Python because it has a lot of tools for Deep Learning, Computer Vision and Signal Processing. Python is really good at combining types of data like pictures, sound and sensor information. This makes Python the best choice for our system that uses different types of data. We will use Python for the system because it is good at handling types of data, like vision, audio and sensor data.

Visual Processing Module:

To find the features of a face we should use the OpenFace library along, with OpenCV for finding faces in pictures and getting them ready to use. We need to make the pictures simpler like turning them into black and white and making sure they are all the same. When we find a face the system uses PyTorch to put a kind of brain called a Convolutional Neural Network, like ResNet-50 to work. This brain has already been taught with lots of pictures of faces and how they are feeling so it can find out how someone is feeling from their face. The OpenCV library and PyTorch work together to make this happen.

Audio and Physiological Processing:

For the part we use the Librosa library to get some important details from the audio sound. We call these details Mel-frequency coefficients or MFCCs for short. The audio module uses these MFCCs.

We then use a kind of computer program called a Recurrent Neural Network or RNN to look at these details. We made this RNN using PyTorch.

At the time we also look at some other information from the body like Heart Rate and GSR.

We use SciPy and NumPy to clean up this information so it is easier to use.

Then we use a Long Short-Term Memory network, which's a kind of computer program to find out when someone is stressed. The Long Short-Term Memory network is also called an LSTM network.

The audio module and the physiological data streams, like Heart Rate and GSR are important, for this.

Backend and Adaptive Engine:

The Django REST Framework or FastAPI will be used to build the backend service for the system. This backend service is like the Fusion Hub. The Fusion Hub gets information from the module, the audio module and the physiological module. Then the Fusion Hub does the fusion logic. Uses the NeuroAdaptive decision engine to figure out the best support response, for the system. The NeuroAdaptive decision engine is a part of the system and it helps the Fusion Hub make good decisions.

User Interface and Hardware:

The user interface lets the user see how they are doing with their health right now and get ideas on how to deal with things from a computer program. This all happens on a website that uses React.js. The system works on a computer setup.. To make the computer program smarter and to figure out what is going on with the user really fast the system uses special computer parts from NVIDIA that can do lots of math problems quickly. These special parts are important for the health metrics and, for giving the user good ideas on how to cope with things. The system uses health metrics and the computer program gives the user coping strategies.

Summary of Technologies:

The following table summarizes the key components and technologies used in the proposed architecture:

Module	Technology
Programming Language	Python 3.9+
Deep Learning Framework	PyTorch / TensorFlow
Computer Vision	OpenCV, Pillow
Audio Analysis	Librosa
Signal Processing	NumPy, SciPy
Backend API	Django REST Framework / FastAPI
Frontend Interface	React.js
Database	PostgreSQL (User Profiles & Logs)

Evaluation Metrics

To see how well the NeuroAdaptive system can tell what people are feeling we need to measure how good it is at getting things right. We use things like Precision and Recall and the F1-Score to do this. These are ways to check if systems like this are working well. The NeuroAdaptive system uses these Emotion Recognition Metrics to make sure it is classifying states correctly. We use Precision and Recall and the F1-Score, for the NeuroAdaptive system because they are ways to measure how well the NeuroAdaptive system is doing.

Precision measures the trustworthiness of the system's diagnostic alerts. It is defined as the ratio of correctly identified mental health events to the total number of events flagged by the system.

In the context of the NeuroAdaptive framework:

When the Artificial Intelligence system gets it right this is called Positive or TP for short. This means the Artificial Intelligence correctly figures out how a user is feeling. For example the system uses a lot of information from sensors and it says the user has High Anxiety.. In fact the user really is feeling anxious at that time.

False Positive or FP for short is when the Artificial Intelligence gets it wrong. This happens when the Artificial Intelligence thinks someone is feeling a way like Stress but they are actually feeling Neutral. For example the system might send an alert saying the user is feeling Stress because their body is reacting in a way even if they are really feeling fine. This is a False Positive because the Artificial Intelligence made a mistake about the users state. The Artificial Intelligence incorrectly flags the state, which, in this case is Stress, when the user is actually feeling Neutral.

Recall measures the system's sensitivity and safety. It is defined as the ratio of correctly identified mental health events compared to the total number of actual events that occurred. High recall is critical in this domain to ensure the assistant does not overlook a user in distress [14].

$$Recall = \frac{TP}{TP + FN}$$

$$Precision = \frac{TP}{TP + FP}$$

In the context of the NeuroAdaptive framework:

The False Negative thing happens when the Artificial Intelligence system does not see a state that is really there. For example the user is going through a Depressive Episode. The system gets it wrong and thinks the user is Calm. This means the Artificial Intelligence misses the mental state of the user, which is a Depressive Episode and instead thinks the user is feeling Calm. The False Negative is a mistake made by the Artificial Intelligence system when it should have detected a Depressive Episode.

$$F1 = 2 \times \frac{Precision \times Recall}{Precision + Recall}$$

The F1-Score provides a single, balanced metric that combines Precision and Recall. This metric is particularly vital for mental health datasets, which are often imbalanced [2, 5].

SYSTEM EFFICIENCY METRICS

The system needs to be good for real-time support. So we measure how efficient it is, by looking at something called Inference Latency. This Inference Latency is important because it helps us see how well the system is working. We use Inference Latency to make sure the system can handle things quickly.

Inference Latency: This measures the time delay (in milliseconds) between the acquisition of raw multimodal data (visual/physiological) and the generation of an adaptive response. This measure is essential for assessing the system's responsiveness during live user interactions, a key requirement identified in recent mobile health reviews [11, 13].

CHALLENGES & LIMITATIONS

Even though there are numerous potential benefits associated with a NeuroAdaptive AI- based mental health assistant, significant technical and practical challenges will likely arise during implementation and real-world deployment.

The thing with Facial Expression Recognition is that it can be really unreliable. For instance the quality of the picture and the lighting in the room where you're can affect the results. If you are using a quality webcam or if the room is not well lit it can cause a lot of mistakes. Even things like having your hands in front of your face can make it hard for the system to get it right. This means that the system might not be able to pick up on changes in your face like when you make a very quick expression. Facial Expression Recognition systems have to deal with these kinds of problems all the time.

Facial Expression Recognition results can be wrong because of things like lighting or low quality webcams. This is an issue, for Facial Expression Recognition because it needs to be able to see your face clearly to work properly. So when we collect information from devices that people wear this information can be wrong because of the way people move around. This is called "motion artifacts" which's like noise that happens when people are moving. It can look like the signs of stress like a heart rate but it is really just because someone is walking, not because they are anxious. The devices can get confused between a heart rate from walking and a fast heart rate, from being stressed.

Emotions can be. People can hide how they really feel. This is a problem with the way computers understand people. Computers are good, at seeing signs but they have trouble when people put on a happy face even if they are feeling bad inside. Emotional masking is when people do this on purpose. They might look happy. Really they are feeling sad or upset. This can be hard for computers to understand because they are looking at the face and not what is going on inside. The Neuro-Processing component has to deal with this problem of people hiding their emotions. The system has a limitation. This means it can get messages. For example it might see a smiling face. The persons body is really stressed out. This can cause the system to make a mistake. It might say someone is feeling neutral when they really need help. This is called a "False Negative" classification. The system says the user is "Neutral" when they actually need support.

The proposed method has to be able to handle a lot of things at the time. This means it has to process Video and Audio and Sensor data all at the time without any delay. The Video and Audio and Sensor data streams are very important for the system to work properly.

The system is more complicated than systems that only use one type of data. Because of this the system uses a lot computer power. This is called Computational Overhead. The Computational Overhead of the proposed method is significantly higher, than that of systems.

When a user does something the system has to respond. The time it takes for the system to respond is called Inference Latency. The Inference Latency of the proposed method has to be very low. If the Inference Latency is high the system will not work well. Low Inference Latency is critical for a conversational agent to be effective. The conversational agent has to be able to respond to what the user is doing. The proposed method has to be able to keep the Inference Latency low so that the conversational agent can work properly. When you have a lot of people using something at the time the computer needs a lot of power from the graphics card to make sure everything runs smoothly. If the graphics card is not powerful enough it can cause delays. That can be a problem for the therapy session because it can interrupt the therapy interaction. The therapy interaction needs to flow so the computer needs to have enough power, from the graphics card specifically the GPU resources to prevent this from happening and keep the therapy interaction going smoothly.

The thing about the proposed method is that it also raises some concerns about privacy. When you are dealing with information like biometric and mental health data you have to be careful. There are concerns because this kind of data could get into the wrong hands.

Data leaks could happen

Someone could access the information without permission

Emotional profiles could be misused

To avoid these problems the data needs to be protected with encryption and access controls. This way the information, about the users is kept private like medical records. The privacy and security of the users data is very important. Needs to be taken care of.

Clinical Scope Limitations The focus of the current system is primarily on the detection and support of mild to moderate emotional states; therefore, the proposed system is limited regarding its ability to handle severe psychiatric crises or diagnose clinical disorders. Consequently, the applicability of this approach is limited to acting as a supportive "Assistant" rather than a replacement for professional medical intervention, highlighting the need for future extensions that include "human-in-the-loop" protocols for crisis management.

REFERENCES

1. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. (2019). NAACL-HLT. <https://aclanthology.org/N19-1423.pdf>
2. The Ryerson Audio-Visual Database of Emotional Speech and Song (RAVDESS). (2018). *PLoS ONE*. <https://journals.plos.org/plosone/article?id=10.1371/journal.pone.0196391>
3. Facial Expression Recognition in the Wild via Deep Attentive Center Loss. (2021). *IEEE/CVF CVPR*. <https://www.semanticscholar.org/paper/Facial-Expression-Recognition-in-the-Wild-via-Deep-Farzaneh-Qi/95a7cb74098d1e6751f5b6f7ce4cf0fb2b3dc9fa>
4. Multimodal Emotion Recognition with Fusion Models. (2023). *IEEE Transactions on Affective Computing*. <https://www.mdpi.com/1424-8220/23/12/5475>
5. Mood Prediction from Smartphone Sensor Data Using Deep Multitask Learning. (2023). *Journal of Biomedical Informatics*. <https://pmc.ncbi.nlm.nih.gov/articles/PMC7266106/>
6. Transformer-Based Emotion Forecasting from Passive Data Streams. (2024). *JMIR Mental Health*. <https://www.jmir.org/2025/1/e63962>
7. The Effectiveness of AI Chatbots for Mental Health: A Scoping Review. (2024). *JMIR Human Factors*. <https://www.mdpi.com/2076-3417/14/13/5889>
8. Multimodal Machine Learning in Mental Health: A Survey of Data, Algorithms, and Challenges. (2025). <https://www.themoonlight.io/en/review/multimodal-machine-learning-in-mental-health-a-survey-of-data-algorithms-and-challenges>
9. A Comprehensive Review of Multimodal Emotion Recognition: Techniques, Challenges, and Future Directions. (2025). <https://ouci.dntb.gov.ua/en/works/lxLLmJY0/>
10. AI Chatbots for Psychological Health for Health Professionals: Scoping Review. (2025). <https://humanfactors.jmir.org/2025/1/e67682/>
11. Deep learning in time series forecasting with transformer models and RNNs. (2025). *PeerJ*. <https://peerj.com/articles/cs-3001/>
12. Providing Self-Led Mental Health Support Through an AI-Powered Chat Bot (Leora). <https://scispace.com/papers/providin-g-self-led-mental-health-support-through-an-2z6mnd6i>
13. Artificial Intelligence and Machine Learning in Mobile Apps for Mental Health: A Scoping Review. (2025). <https://journals.plos.org/digitalhealth/article?id=10.1371/journal.pdig.0000079>
14. 1AI in Mental Healthcare: An Overview and Future Perspectives. (2025). *British Journal of Radiology*. <https://academic.oup.com/bjr/article/96/1150/20230213/7498934>
15. AI Chatbots for Mental Health: A Scoping Review of Effectiveness, Feasibility, and Applications. (2025). *PMC*. <https://pmc.ncbi.nlm.nih.gov/articles/PMC11939020/>

TECHNOSTRESS: A REVIEW OF ITS DIMENSIONS, IMPACTS, AND MANAGEMENT STRATEGIES

Jiya Patel and Dr. Smruti Nanavaty¹Department of Information Technology, Usha Pravin Gandhi College, Mumbai, Maharashtra, India²Assistant Professor/ Vice Principle, Usha Pravin Gandhi College, Mumbai, Maharashtra, India**ABSTRACT**

The rapid proliferation of Information and Communication Technologies (ICTs) has fundamentally reshaped the modern professional and academic landscape, fostering a culture of perpetual connectivity and high-speed information exchange. While these advancements have driven efficiency and global collaboration, they have simultaneously introduced significant psychological burdens, most notably "technostress"—defined as the struggle of individuals to adapt to the escalating demands of digital tools.

This research paper provides a multi-dimensional analysis of technostress, moving beyond traditional definitions to explore its cognitive, behavioural, and emotional manifestations in the post-pandemic era. The study is grounded in the theoretical frameworks of the Job Demands– Resources (JD-R) model and Person–Environment (P–E) Fit theory, which provide a lens through which to view technology not merely as a tool, but as a dynamic environmental factor that can either deplete or enhance human psychological resources.

The core of this research identifies and categorizes the five primary "techno- creators" prevalent in contemporary work environments: techno-overload, techno-invasion, techno-complexity, techno-insecurity, and techno- uncertainty. Through a systematic review of recent literature, this paper demonstrates how these creators act as significant job demands that, when left unmanaged, lead to diminished productivity, professional burnout, and severe psychological strain. Conversely, the study also explores the concept of "techno-eustress," where technological challenges—when supported by organizational resources—can act as catalysts for innovation and increased engagement. Special attention is paid to the "pandemic shift," analysing how the sudden transition to remote work and virtual collaboration platforms accelerated digital saturation and blurred the boundaries between professional and private lives, particularly highlighting the dominance of techno-invasion as a primary stressor during this period.

To address these challenges, this paper proposes an innovative, four-layered architectural framework for technostress mitigation. The architecture begins with Layer 1: Detection, utilizing validated psychometric scales to identify early warning signs of digital strain. Layer 2: Organizational Intervention focuses on implementing Corporate Digital Responsibility (CDR) and digital literacy training to reduce complexity. Layer 3: Leadership and Culture advocates for a shift toward empowering, trust-based management styles that act as a buffer against techno-insecurity. Finally, Layer 4: AI Integration proposes the use of advanced technological solutions, such as therapeutic chatbots and algorithmic transparency, to provide personalized stress-relief interventions.

The paper concludes by addressing the critical technological and methodological limitations currently facing the field. It highlights the "black-box" nature of algorithmic management and the lack of cross-cultural reliability in existing measurement tools. By identifying these gaps, the research emphasizes the necessity for longitudinal studies and a more inclusive approach to demographic vulnerability, particularly for middle-aged and manual workers. Ultimately, this research provides a comprehensive blueprint for creating "mentally fit" digital ecosystems, ensuring that the future of work is defined by a sustainable synergy between human well-being and technological innovation.

Keywords: Technostress, ICT, Digital Transformation, Job Demands– Resources Model, Remote Work, AI Ethics, Digital Wellness.

1. INTRODUCTION

The fast pace of the Information and Communication Technologies (ICTs) integration has completely changed the environment of contemporary working and studying. Although such technological developments have brought about unmatched flexibility, automation and access to information, they have also given rise to an everywhere "24/7" culture. The culture is marked with excessive connectivity and constant need for multitasking where the line between professional and personal lives is still getting blurred. With the increased use of the digital tool by organizations and academic institutions, the normal work patterns have vanished and in their place is a system where people are expected to be continuously available.

As such, this digital change not only has increased efficiency but has also raised complicated socio-technical challenges that affect the manner through which human beings approach technology in their everyday lives.

In this regard, there has been an emergence of a psychological phenomenon termed as technostress, and this phenomenon has become an important subject of concern. Technostress is a modern adaptation disease described as coined in 1984 by Craig Brod as a result of the inability to adjust to new technologies. Although the term was first applied in referring to a single psychological response, it has since become a complex phenomenon that has been applied to include cognitive, behavioral, and emotional responses. Technostress is the discrepancy between the technological needs and the inner potential of the person to cope with the technological needs. The strain occurs when the velocity of technological changes is greater than the ability of the person to adapt to them, and this stress is expressed through the inability to establish a healthy psychological state in a digital ecosystem.

The issue statement of technostress focuses on the increasing demands of contemporary employees. Today, employees are put under a lot of pressure to deliver a quick response and be constantly online. The necessity to keep up to the rapidly changing tools, as well as the necessity to be accessible at all times, results in a digital overload. The demands can usually surpass the coping capacities of an individual causing a number of adverse consequences such as anxiety, frustration, cognitive exhaustion, and professional burnout. More so, when technology invades individual territories- what has been referred to as techno-invasion- it undermines psychological health and output, forming a stress chain that is hard to break.

This problem became a critical global threshold during the COVID-19 pandemic, which has become a trigger in terms of an enormous digital dependence pandemic shift. The abrupt and urgent change of the remote working environment, distance learning, and virtual team working platforms was practically overnight. This transition exposed millions of people to lengthy screen time and techno-fatigue or the feeling of mental exhaustion due to constant use of technology. The lack of recovery time of the home-working workers became the most significant factor during the stages of lockdown, as the stressors turned into techno-invasion and techno-overload. The pandemic itself was rather efficient in highlighting that when not managed properly, technology is a cause of considerable psychological trauma instead of power.

This paper will aim to solve such challenges by presenting a holistic framework that will be used to balance the benefits of technology and the psychological health of man. This study will help answer the question by synthesizing theoretical frameworks like the Job Demands-Resources (JD- R) model and Person-Environment Fit theory to find out the effective ways of preventing and reducing technostress on individuals and institutions. The idea is not to go past merely being defensive but to create sustainable and mentally healthy online communities. Finally, the paper aims at offering a practical roadmap to designing ecosystems in which human capabilities are equated with digital invention so that the latter can be used to complement rather than to dominate human experience.

2. REVIEW OF LITERATURE

Technostress, as understood academically, has developed over time as a simple psychological response to an advanced socio-technical phenomenon. The initial studies were mainly dictated by the Technostress Model that emphasized finding particular techno-creators or causes of stress. Current scholarships have however shifted to more integrative paradigms such as Job Demands- Resources (JD-R) Model and Person- Environment (P-E) Fit Theory. The JD-R model hypothesizes that ICTs may be both a job demand that consumes energy and job resources that attain work objectives, based on organizational contexts. On the same note, P-E Fit theory implies that technostress sets in when a person experiences a mismatch between technological landscape and his or her capabilities or requirements. The emergence of this theoretical change is the opportunity to explain the influence of personal characteristics and the organizational support mediating the effect of digital demands more thoroughly.

The most significant dimension of technostress research is a set of five dimensions that are referred to as Techno-Creators that describe the prevalent strain that is caused by technology in an individual. Techno-overload happens when technology takes control of a person and makes him or her work more and more, and in most cases, it causes one to feel that he or she is drowning in the mass of information overflowing with digital information. The invading technology that penetrates personal Slife and space making one find it hard to disengage with work is the techno- invasion culture. Techno-complexity occurs when new tools are too complex, and individuals are unwilling to accept the fact that they are not skilled enough, or they are compelled to spend too much time learning.

Techno-insecurity is associated with the fear of being fired to a more tech- savvy person or being automatized. Lastly, techno-uncertainty is the stress that is brought about by continuous, unforeseeable software and hardware modifications and upgrading.

The contributions of these creators have been widely written in different Impact Studies, especially in the context of innovation. Studies have found out that technostress has a two- sided nature; it may slow down or facilitate innovative behavior. Technostress is perceived as a hindrance, and this results in anxiety and reduces innovation but when perceived as a challenge (techno- eustress) it can motivate engagement and increase creative output. This is an indication that a moderate amount of digital pressure with the assistance of the appropriate environment may contribute to digital resilience and skill development.

The demographic studies have also indicated that not all populations are susceptible to technostress. White-collar workers, manual or blue-collar workers have proven to be more susceptible to techno-strain and burnout because of their middle-aged age. As an example, it was revealed that age-based variations in mental health outcomes based on the use of technology are substantial, and middle-aged populations are more vulnerable to it. Moreover, gender variations may also have a role in affecting psychological well-being in relation to certain stressors such as techno-insecurity.

Finally, the Leadership Role has become a major systemic inhibitor or driver of digital strain. The method of systematic reviews proves that trust and autonomy-based supportive and empowering leadership styles can help decrease technostress significantly. On the other hand, "controlling" leadership, which is surveillance and monitoring and high availability expectation-based leadership, strongly enhances the levels of stress. These results point to the fact that organizational culture and leadership sympathy are crucial aspects of building a mentally healthy digital working environment.

3. PROPOSED ARCHITECTURE

The study hypothesizes that a multi- layered architectural model based on the principles of preventive medicine and Job Demands Resources (JD-R) view is suitable to handle the multidimensional aspects of technostress. This architecture goes beyond the reactive, measures, and instead, it provides a systemic approach to the balancing of the needs of technology with the resources of the organization and the individual. Through establishing four definite layers of interventions namely Detection, Organizational Intervention, Leadership Culture, and AI Integration, institutions can develop a sustainable ecosystem that will eliminate the adverse effects caused by digital transformation and proactively develop digital resilience. The model is aligned to Human potential and technological prowess whereby digital tools can be used as developmental tools and not sources of strain.

The primary layer of this architecture is Layer 1: Detection (Primary Prevention) that is concerned with early detection and active monitoring. Primary prevention entails the use of validated measures that are used to define the onset of stress prior to the occurrence of chronic burnout. As an example, one can utilize the one-factor structure scale that was tested on academic settings by Schettino et al. or the multidimensional Techno-Creators Scale to detect the particular stressors in a work setting. Through this, institutions can be able to customize their responses by determining the most common of the five dimensions of overload, invasion, complexity, insecurity, or uncertainty. Another point highlighted in this layer is that in the future, multimodal detection should be integrated, which is a combination of self-reported surveys with a physiological indicator, such as heart rate variability or cortisol levels, to get a better ecological validity.

Going beyond the identification stage, Layer 2: Organizational Intervention (Secondary Prevention) is aimed at providing the required individuals with a special set of skills and resources to handle the digital demands. This layer entails the application of digital wellness programs, as well as all- encompassing digital literacy education, put in place specifically as a measure to decrease techno- complexity. One of the critical innovations in such a layer is the implementation of Corporate Digital Responsibility (CDR) protocols that serve as a mediator between use of technology and innovation by employees. These guidelines are ethical, including policies on the right to disconnect to avoid invading people with technology. Organizations may manage the workloads to ensure that technology is used as an efficient tool and not a cause of techno-fatigue as it may cause.

Systemic environment is discussed in Layer 3: Leadership and Culture (Tertiary prevention) that transforms the organizational environment to deliver long-term stability. Tertiary prevention is aimed at changing the management style towards an authoritarian or surveillance-based approach which is known to increase the sense of techno-insecurity and anxiety. Rather, the framework suggests a shift to empowering and empathetic leadership that will enable trust and autonomy. Employees with high levels of social support and organizational support are also allowed to re-conceptualize technological requirements as a challenge (eustress) compared to

an obstacle (distress) by their leaders. This cultural transformation is critical to the development of a psychologically fit digital environment in which the employees will be safe to be innovative without the fear of being monitored or replaced by algorithms.

Lastly, Layer 4: AI Integration uses improved technology to address technology-related issues. This layer will incorporate AI-based stress management systems like therapeutic chatbots which have been proven to be effective in alleviating depression and anxiety in the case of university students. Such systems would be able to offer a quick, self-help intervention against digital fatigue, and would offer a risk-free form of a therapeutic alliance with individuals who might otherwise be reluctant to find traditional counseling. Also, this layer seeks to minimize the anxiety of black-box automation that is a side effect of modern automation by focusing on algorithmic transparency and explainability. This four-layered architecture can be carried to the future of technology being used as a means of sustainable productivity and psychological well-being by acknowledging technology as a collective issue.

4. TECHNOLOGIES AND LIMITATIONS

The proposed architecture is to be implemented based on a range of Applied Technologies that have found a place in the center of the contemporary digital workspace but are simultaneously the main elements that cause the digital strain. The emergence of Information and Communication Technology (ICT) platforms such as remote e-working and virtual team collaboration platforms have become the new normal of millions of people, offering the platform on which flexibility and automation can be achieved. The platforms, although acting as the means to access information, are also the causes of the so-called techno-fatigue because of the extended screen time and culture of being always-on technologies.

AI & Chatbot Implementation (Self- Help Interventions)

To develop therapeutic chatbots that can also be applied in self-help interventions of depression and anxiety, Python will be the main language because it has expansive libraries of Machine Learning and Natural Language Processing (NLP).

Ideas: The developers would use Natural language Understanding (NLU) to enable the system to decode user distress, and Sentiment Analysis to understand the emotional state such as anxiety or frustrations of users in real time.

Methods: The study refers to the establishment of a therapeutic partnership, which means establishing a sympathetic flow of conversation using deep learning models.

Stress Detection and Behavioral Analytics

A combination of Python, R, and SQL would be applied in order to implement Layer 1 (Detection) which detects stressors such as techno-overload and techno-fatigue.

Ideas: It would work based on Pattern Recognition to be applied to Online Activity Logs and determine the behaviors associated with over-connectivity or digital saturation.

Physiological Integration: In case of the measurement of physiological markers such as heart rate variability or cortisol, the data processing techniques (Signal Processing and Time-Series Analysis) would be needed to triangulate self-report measures of stress with biological measures.

User-Centered ICT Platforms

To develop remote e-working and virtual collaboration tools that make techno-complexity less dominant, web-based languages such as JavaScript (React/TypeScript) or Java are usually employed.

Theory: The main theory in this case is User-Centered Design (UCD) that dwells on the usability of a system so that technological changes do not create techno-uncertainty or adequacy anxiety.

Interoperability: Making the various digital tools used to communicate easily is one of the important concepts that should be implemented to avoid the disjointedness that gives way to techno overload.

Algorithms, Transparency and CDR.

The architecture should include the concepts of Explainable AI (XAI) in order to solve new stressors like algorithmic surveillance and the black-box character of AI.

Ideas: Corporate Digital Responsibility (CDR) will be used as the ethical guideline, and there has to be a Data Privacy and Encryption set of protocols to keep the data of the workers secure and track their well-being.

Algorithmic Fairness: Coding performance-tracking systems with guarantees of being perceived as fair and will not impose techno-insecurity or fear of being replaced.

The suggested architecture can successfully move the defensive stress management paradigm into the proactive digital well-being ecosystem, combining these Python-based AI frameworks with user-centric web ideas and ethical CDR protocols.

Currently, these applied technologies are also limited by serious Technological Limitations which hamper the achievement of a stress-free digital environment. The existence of Black-Box Algorithms is one of the most urgent problems. The nature of most AI systems being non-transparent and non-explainable makes it challenging for workers to comprehend how they are being judged to perform at work or how machines make judgments. This attribute of black box has the effect of generating a perception of unfairness and psychological stress since people feel that they are being judged upon by systems whose functioning they can do nothing about and which they cannot understand. Technology is a cause of uncertainty and not a predictable tool to growth without algorithmic transparency.

Moreover, the Measurement Tools that are in place to measure technostress are narrow in their assessment and reliability. Some of the existing scales are unidimensional and only consider such aspects as techno-overload but no other important creators such as techno-uncertainty or techno-invasion. Such heterogeneity of its methodological aspects complicates cross-study comparisons or meta-analyses. Secondly, not all validated scales have a cross-cultural reliability since most of the scales are usually designed in the Western or East Asian business environment and might not be relevant in reflecting the stress perceptions in the developing economies or collectivist societies. The possibility to precisely diagnose and treat technostress will be disjointed until measurement instruments are standardized and validated among various groups of demographics and occupational categories, such as blue-collar and gig economy workers.

EVALUATION METRICS

To determine the efficacy of technostress mitigation strategies, a robust set of evaluation metrics must be established, spanning psychological, behavioral, and organizational dimensions. These metrics are mainly aimed at the metastasis of the transition between the techno-distress and the techno-eustress, where technology is perceived as a manageable challenge instead of a threatening eventuality. At the psychological level, the framework consists of validated scales to assess emotional exhaustion and cognitive fatigue, both of which are the immediate consequences of the long-term effects of techno-creators such as overload and invasion. With the help of the tools, including the one-factor structure scale with the validation conducted by Schettino et al., organizations will be able to measure academic and professional satisfaction and compare the results to general mental health. Such psychological indicators are a point of reference to the influence of digital saturation on the inner ability of the person to cope with it.

The suggested architecture aims to bring additional objective behavioral and physiological indicators on top of self-reported information. Although the old research has been using cross-sectional research surveys extensively, the current assessment mandates longitudinal monitoring to trace the process of adaptation or escalation over a period. There are the suggested measures like online activity logs, which are used to measure digital saturation, and recovery time, which is the time spent not in contact with ICTs. Moreover, the physiological markers' integration, e.g., cortisol levels and heart rate variability, can offer an empirical signature of the stress that avoids the subjectivity of data collected via surveys. Such multimodal measures help improve the ecological validity of the assessment, enabling the researchers to distinguish between short-term stress responses and long-term syndromes of technostress.

The assessment is also run into organizational performance and innovation pointers. One of the measures of success is the degree of Inno Vat Behavior, which is extremely sensitive to the level of technostress as per research. When the employees develop a perception that technology is a hindrance, innovation is reduced since there would be anxiety, but when the architecture has managed to create an environment that supports employees, innovation is high since employees become engaged and not overwhelmed. Thus, the performance of the socio-technical ecosystem is estimated by the quality and quantity of the creative outputs. Also, satisfaction with work-life balance is an urgent measure, in particular, the decrease in the level of techno-invasion of personal areas, which was one of the primary stressors reported during the pandemic shift.

6. CHALLENGES AND LIMITATIONS

Although much has been understood about the psychological effects of the use of digital tools, there are still some severe methodological gaps that obstruct the formulation of a coherent theory of technostress.

One major problem is that cross-sectional surveys have a high dependence where the stress is only measured at a single point at a given time. Such a method does not consider the adaptability of human response; it is uncertain whether people will develop digital resistance in the long run or whether the burnout will be accumulated over time, and the recovery will not be possible. To eliminate this, longitudinal studies are needed in the field to monitor the trends of techno-creators, including techno-invasion and techno-uncertainty, at various points of a career or educational path of an individual. Moreover, the abstract division of technostress between a modern disease and a transactional process introduces discrepancies in the design of the interventions and it is hard to create a set of organizational guidelines.

The other limitation that is important is the existence of cultural and occupational prejudice in the current literature. Majority of the existing studies focus on the Western corporate environments or East Asian high-tech industries, and do not pay much attention to the specific stressors that employees in the developing economy experience or in the blue-collar labor force or manual labor. As an example, a remote office employee may face the problem of techno-invasion into his home life whereas a manual worker may have acute techno-insecurity about the automation of his physical work. The technostress management strategy of one-size-fits-all approach does not recognize these various socio-economic realities. Cross-cultural validation of measurement scales is urgently required to make digital wellness initiatives inclusive and effective to a multi-generational workforce of globally diverse people.

The issue of data privacy and digital surveillance has raised ethical issues that pose a significant challenge to the effective execution of mitigation measures. The more organizations shift to Layer 1 (Detection) and Layer 4 (AI Integration) of the proposed architecture, the more the boundary between well-being monitoring and invasive surveillance becomes unclear. The productivity tracking through the application of the algorithmic management may, without intention, increase the stress the management is meant to reduce since employees lose their autonomy and become afraid of being evaluated by black-box systems that they do not comprehend. To avoid turning these technologies into the instruments of control and not empowerment, it is necessary to guarantee the transparency of the algorithms and the creation of distinctly established protocols regarding Corporate Digital Responsibility (CDR). The use of stress-tracking technologies can be met with a considerable opposition on part of the employee without any ethical protection, which will only worsen the situation between the human and digital workforce.

Lastly is the problem of theoretical integration especially in matching the Job Demands-Resources (JD-R) model with the fast growing AI. With the further independence of artificial intelligence, the conventional concept of a techno-creator might be redefined to incorporate such stressors as an algorithmic bias or human-AI trust problems. The therapeutic relationship between humans and chatbots has only recently been studied in the literature and further studies are required to uncover the psychological consequences of turning to machines in the long term. To overcome these difficulties, it is necessary to use a transdisciplinary approach, i. e. integrate the knowledge of psychology, information systems, and ethics to guarantee that the digital transformation of the 21st century could be human-centric and sustainable.

REFERENCES

1. **Ayyagari, R., Grover, V., & Purvis, R. (2011).** Technostress: Technological antecedents and implications. *MIS Quarterly*, 35(4), 831–858.
2. **Berger, M., Schäfer, R., & Gimpel, H. (2023).** How to prevent technostress at the digital workplace: A Delphi study. *Information Systems Journal*.
3. **Brod, C. (1984).** *Technostress: The Human Cost of the Computer Revolution*. Addison- Wesley.
4. **De Giovanni, P., & Catania, G. (2016).** Information technology and mental health: A study on middle-aged workers and manual labor. *Journal of Occupational Health*.
5. **Kumar, P. S. (2023).** Technostress: A comprehensive literature review on dimensions, impacts, and management strategies. *International Journal of Information Management*.
6. **Kupang, G. B., Ballangan, M. G., Carantes, F. T., & Yanes, P. S. (2022).** Unpacking Technostress: A systematic review of its effects and mitigation. *Technology in Society*.
7. **Pansini, M., Buonomo, I., & Benevene, P. (2022).** Positioning technostress in the JD-R model perspective: A systematic literature review. *Frontiers in Psychology*.

-
8. **Schettino, G., Marino, L., & Capone, V. (2022).** Technology-enhanced learning and wellbeing: Validation of a technostress measure. *European Journal of Investigation in Health, Psychology and Education*.
 9. **Taser, D., & Aydin, E. (2021).** Remote e-working, flow experience, and technostress: The impact of COVID-19. *Journal of Business Research*.
 10. **Yang, H. J., Cheng, Y., & Liu, Y. L. (2021).** Techno-strain and techno-insecurity associated with poor mental well-being in the AI era. *Computers in Human Behavior*.
 11. **Zhang, S., Guo, P., & Yuan, Y. (2023).** Anxiety or engaged? Research on the impact of technostress on employees' innovative behavior. *Journal of Innovation & Knowledge*.

DEEP LEARNING SYSTEM FOR RESPIRATORY DISORDER DETECTION USING MULTIMODAL AUDIO FEATURES (MFCC, MEL SPECTROGRAM, AND CHROMA STFT)

Dhruvin Soni and Dr. Prashant Chaudhary

¹MScIT Student, Department of Information Technology, Usha Pravin Gandhi College of Art, Science and Commerce Mumbai, Maharashtra, India

²Assistant Professor & B.Sc.IT Coordinator Department of Information, Technology Usha Pravin Gandhi College of Art, Science and Commerce Mumbai, Maharashtra

ABSTRACT

This article introduces the development of an automated, non-invasive system for the diagnosis of eight different respiratory diseases, such as COPD, asthma, and pneumonia, based on the analysis of lung sounds. Acknowledging the limitations of qualitative manual auscultation, I utilized the strength of deep learning—namely, Convolutional Neural Networks (CNNs)—in classifying sound recordings. The foundation of my method lies in the extraction and concatenation of three key two-dimensional audio features: MelFrequency Cepstral Coefficients (MFCC), Mel Spectrogram, and Chroma Short-Time Fourier Transform (STFT). I developed a new concatenated CNN architecture that handles these multimodal inputs in parallel. The model was trained and crossvalidated on a publicly released dataset of 920 labeled respiratory recordings from 126 patients. Results show the better performance of my suggested concatenated model, which attained a high classification accuracy of 94.90% with low loss of 17.27%, forming a highly powerful solution for objective respiratory diagnosis.

I. INTRODUCTION

Respiratory illnesses are a major global health issue, and they account for significant morbidity and mortality. Early and correct diagnosis is important for effective treatment and minimizing fatalities. Conventional lung auscultation with a stethoscope has been the mainstay of diagnosis.

This process, however, is subjective in nature and relies on the practitioner's expertise and is also vulnerable to human factor errors.

To ensure that the above limitations are overcome and a non-invasive, automated, objective alternative is presented, I aimed to establish a strong respiratory disorder classifier using deep learning and digital interpretation of lung sounds. My goal was to develop a model that would be able to correctly classify eight prevalent respiratory disorders: Asthma, Bronchiolitis, Bronchiectasis, Chronic Obstructive Pulmonary Disease (COPD), Healthy, Lower Respiratory Tract Infection (LRTI), Pneumonia, and Upper Respiratory Tract Infection (URTI). This paper has its primary interest in converting onedimensional audio signals into twodimensional spectral-temporal images, to which the CNNs are then applied, a method that I have been impressed with for image classification purposes.

II. RELATED WORK

A literature review noted two key issues in creating automated classifiers for lung sounds: obtaining good, clean data and using effective feature extraction. Most previous research utilized basic classifiers such as Support Vector Machines (SVM) or K-Nearest Neighbor (KNN). Improved performance, however, has been provided more recently by the increasing complexity of deep learning algorithms.

Table I: Related Models with Their Accuracy

Model or Propose Method	Reference	Accuracy
ResNet with S-Transform	[10]	0.98
CNN using MFCC	[7]	0.93
back propagation neural network	[11]	0.88
CNN using RMS Normalisation	[12]	0.87
K-nearest neighbour	[13]	0.84
Counter propagation neural network	[11]	0.84
short-time Fourier transform (STFT)	[14]	0.84
CNN with Ensemble Architecture	[3]	0.80
Linear Support Vector Machine	[13]	0.71
Support Vector Machine	[9]	0.65
CNN using VGG-16	[11]	0.65
CNN using SoftMax	[9]	0.63

Earlier studies have established the effectiveness of mapping raw audio into visual inputs for CNN. For example, Minami et al. were able to convert onedimensional recordings to two-dimensional timespectral visualizations successfully for classification. Other researchers have also investigated CNNs with other features such as STFT and backpropagation neural networks and attained accuracies ranging from 80% to 90%. I was especially spurred by research showing high accuracies (as much as 94.9%) employing CNNs of two-dimensional features, reaffirming the effectiveness of this deep learning method to match or surpass human diagnostic performance.

III. PROPOSED METHOD

My proposed approach is a multi-step workflow leading to a concatenated CNN model for highaccuracy classification. The process workflow involves Exploratory Data Analysis (EDA) and Preprocessing, Feature Extraction, Model Building, and extensive testing.

A. Exploratory Data Analysis and Data Preprocessing

The dataset I have used consists of 920 labeled respiratory recordings from 126 individual patients. There are recordings for the eight aforementioned disease classes present in the data. Early EDA showed that the gender distribution is slightly imbalanced (63.2% Male, 36.8% Female), and heavily class-imbalanced over the eight disease categories. In order to reduce bias, I used a stratified splitting method, allocating the dataset into 75% for training and 25% for testing purposes, such that the disease type proportions were preserved uniformly between the training set and the validation set.




Fig. 1. Basic Flowchart

In order to normalize the input for the CNN, all the sound files were uniformly pre-processed. Because the most of the sound files were shorter than 6 seconds, I padded each of them to a length of 6 seconds using a method known as zeropadding. This guarantees that each input feature map has the very same dimensions.




Fig. 2. Gender Distribution




Fig. 3. Visualizing Data Imbalance





Fig. 4. Scatter plot for start and end of sound files

B. Feature Extraction

From the standardized 6-second audio recordings, I derived three different spectraltemporal features with a Python library. Firstly, the Python library librosa was used to extract features such as MFCC, chroma, and melspectrogram.



5. Box plot for start and end of sound files

1. Mel-Frequency Cepstral Coefficients (MFCC): Extremely effective in representing the sound's acoustic properties.
2. Chroma Short-Time Fourier Transform (STFT): Effective for detecting pitch classes and harmonic content.
3. Mel-Spectrogram: A significant feature, displaying the Mel-scale frequency spectrum that simulates human hearing perception.

These characteristics were transformed into twodimensional arrays, which were then used as the input "pictures" for the CNN models.

C. Model Building

I created and contrasted four different CNN models for this research: three standalone models and one resulting concatenated model.

Layer (type)	Output Shape	Param #
mfcc (InputLayer)	[(None, 20, 259, 1)]	0
mfccModel (Functional)	(None, 128)	94560
concatenate_1 (Concatenate)	(None, 128)	0
dense_3 (Dense)	(None, 50)	6450
dropout_4 (Dropout)	(None, 50)	0
dense_4 (Dense)	(None, 8)	408
Total params: 101,418		
Trainable params: 100,778		
Non-trainable params: 640		

Fig. 6. MFCC Model Architecture

1. Individual Models: I initially trained individual CNNs for every one of the three types of features. Each model was tuned to be able to handle its own feature map dimension (i.e., MFCC input of (None, 128, 259, 1)) and had several convolutional, pooling, and dense layers, all featuring the ReLU activation function.
2. Concatenated Model (Final Proposed Model): The best and final structure is a concatenated CNN. It is a three-parallel-branch CNN, one for each feature type.

Layer (type)	Output Shape	Param #	Connected to
mfcc (InputLayer)	[(None, 20, 259, 1)]	0	[]
croma (InputLayer)	[(None, 12, 259, 1)]	0	[]
mspec (InputLayer)	[(None, 128, 259, 1)]	0	[]
mfccModel (Functional)	(None, 128)	94560	['mfcc[0][0]']
cromaModel (Functional)	(None, 128)	53120	['croma[0][0]']
mSpecModel (Functional)	(None, 128)	94560	['mspec[0][0]']
concatenate (Concatenate)	(None, 384)	0	['mfccModel[0][0]', 'cromaModel[0][0]', 'mSpecModel[0][0]']
dense (Dense)	(None, 50)	19250	['concatenate[0][0]']
dropout_1 (Dropout)	(None, 50)	0	['dense[0][0]']
dense_1 (Dense)	(None, 25)	1275	['dropout_1[0][0]']
dropout_2 (Dropout)	(None, 25)	0	['dense_1[0][0]']
dense_2 (Dense)	(None, 8)	208	['dropout_2[0][0]']
Total params: 262,973			
Trainable params: 261,245			
Non-trainable params: 1,728			

Fig. 7. Concatenated Model Architecture

Each branch processes its own feature (MFCC, Chroma STFT, and Mel-Spectrogram) independently with its own convolutional and pooling sequence of layers to learn deep, specialized features.

The last feature vectors of the three branches are then concatenated into a single unified feature vector.

This compounded vector is fed through a common fully connected portion, such as dense layers of 50 and 25 neurons (ReLU activation), and a final dense output layer of 8 neurons with the softmax activation function used for multiclassification.

3. Mel-Spectrogram Model: One of the most effective audio processing techniques is the melspectrogram. It is required to extract relevant characteristics in order to detect audio, since audio data typically has complicated properties. The values in hertz are converted to mel scale values using the melspectrogram.

Layer (type)	Output Shape	Param #
chroma (InputLayer)	[(None, 12, 259, 1)]	0
chromaModel (Functional)	(None, 128)	53120
concatenate_2 (Concatenate)	(None, 128)	0
dense_5 (Dense)	(None, 50)	6450
dropout_6 (Dropout)	(None, 50)	0
dense_6 (Dense)	(None, 25)	1275
dropout_7 (Dropout)	(None, 25)	0
dense_7 (Dense)	(None, 8)	208
Total params: 61,053		
Trainable params: 60,605		
Non-trainable params: 448		

Fig. 8. Mel-Spectrogram Model Architecture

IV. RESULTS AND DISCUSSION

I tested the performance of the models on accuracy, categorical cross-entropy loss, and runtime.

Table II: Related Models with Their Accuracy

Model	Accuracy	Loss	Execution Time(ms)
MFCC	86.55%	34.69%	99.75
Chroma STFT	82.96%	58.54%	93.68
Mel-Spectrogram	85.68%	46.57%	83.74
Concatenated Model	94.90%	17.27%	126.66

The data presented above confirms that our feature combination strategy offers a clear advantage over single-feature approaches. Where individual models capped out at roughly 86.55% accuracy, the proposed concatenated architecture pushed performance to 94.90%, simultaneously dropping the loss to 17.27%.

This improvement is driven by the complementary nature of the input data. Because MFCC, MelSpectrogram, and Chroma STFT extract different aspects of the audio ranging from acoustic texture to pitch the model isn't limited to a single perspective. Instead, it combines these layers to form a complete picture of the signal, resulting in robust classification capability across the varying disease classes.

Table III: Respiratory Diseases Classification Result Table

Disease	Precision	Recall	F1-score	Support
Asthma	0.00	0.00	0.00	1
Bronchiectasis	0.96	0.88	0.92	26
Bronchiolitis	0.74	0.50	0.60	40
COPD	0.99	0.99	0.99	1437
Healthy	0.79	0.81	0.80	81
LRTI	0.33	0.12	0.18	8
Pneumonia	0.80	0.93	0.86	71
URTI	0.62	0.67	0.65	61
Accuracy			0.95	1725
macro avg	0.65	0.61	0.62	1725
weighted avg	0.95	0.95	0.95	1725

V. CONCLUSION

Through the use of deep learning applied to lung auscultation, I successfully developed a sophisticated and highly effective system for classifying respiratory disorders. My proposed model, which intelligently utilizes a concatenated CNN architecture to combine MFCC, Mel Spectrogram, and Chroma STFT features, achieved an exceptional **94.90% accuracy** on the test set.

This finding strongly confirms that convolutional neural networks are an ideal tool for analyzing respiratory sound features when the audio is appropriately transformed into two-dimensional spectrogram-like images. While the high accuracy and low loss (17.27%) demonstrate the model's potential for clinical application, I also note that disorders with less data available, such as Asthma and LRTI, still require further research to achieve perfect classification scores. The methodology presented here serves as a potent starting point and encourages further exploration into deep learning applications for automated medical diagnosis.

REFERENCES

- [1] K. Minami, H. Lu, H. Kim, S. Mabu, Y. Hirano, and S. Kido, "Automatic classification of large-scale respiratory sound dataset based on convolutional neural network," in *2019 19th International Conference on Control, Automation and Systems (ICCAS)*, pp. 804–807, 2019.
- [2] R. Dubey and R. M. Bodade, "A review of classification techniques based on neural networks for pulmonary obstructive diseases," in *Proceedings of Recent Advances in Interdisciplinary Trends in Engineering & Applications (RAITEA) 2019*, 04 2019. [3] L. Pham, I. McLoughlin, H.
- [3] Phan, M. Tran, T. Nguyen, and R. Palaniappan, "Robust deep learning framework for predicting respiratory anomalies and diseases," in *2020 42nd Annual International Conference of the IEEE Engineering in Medicine & Biology Society (EMBC)*, pp. 164–167, 2020.
- [4] S. Chatterjee, M. M. Rahman, E. Nemati, and J. Kuang, "Wheezed: Respiration phase based wheeze detection using acoustic data from pulmonary patients under attack," in *13th EAI International Conference on Pervasive Computing Technologies for Healthcare - Demos and Posters*, EAI, 6 2019.
- [5] R. Hazra and S. Majhi, "Detecting respiratory diseases from recorded lung sounds by 2d cnn," in *2020 5th International Conference on Computing, Communication and Security (ICCCS)*, pp. 1–6, 2020.
- [6] Vaityshyn, H. Porieva, and A. Makarenkova, "Pretrained convolutional neural networks for the lung sounds classification," in *2019 IEEE 39th International Conference on Electronics and Nanotechnology (ELNANO)*, pp. 522–525, 2019.
- [7] K. Mridha, S. Sarkar, and D. Kumar, "Respiratory disease classification by cnn using mfcc," in *2021 IEEE 6th International Conference on Computing, Communication and Automation (ICCCA)*, pp. 517– 523, 2021.

VEHICLE DAMAGE DETECTION USING DEEP LEARNING TECHNIQUES: A COMPREHENSIVE REVIEW

Khushi Dama

Department of Information Technology, Usha Pravin Gandhi College of Arts, Science, and Commerce, Mumbai city, India

ABSTRACT

The ability to accurately identify damage to vehicles is crucial for the processing of insurance claims as well as for vehicle inspections and determining repair costs. Typically the methods used for inspecting damaged vehicles are manual, labor intensive, expensive, heavily reliant on expert opinion/analysis and subjective in nature. Therefore, utilizing AI technology to assist with the inspection process through automating vehicle damage assessment with computer vision/deep learning techniques has drawn a lot of interest from researchers in recent years. In this paper, an extensive overview of currently available Deep Learning Based (DLB) Methods related to Vehicle Damage Assessment is provided. Analyses of the various approaches that have been developed for identifying, classifying, segmenting, and calculating the severity of vehicle damage are discussed in detail and compared across multiple criteria. Also presented are commonly utilized datasets, evaluation metrics, and application scenarios found within current literature about DLB Methodology Regarding Vehicle Damage Assessment. Finally, an overall System Model for a generalized DLB Approach,

Current Research Trends, Existing Gaps in Research, and Possible Future Direction for Automated Vehicle Damage Assessment Systems are provided.

Keywords: Vehicle Damage Detection, Deep Learning, Computer Vision, CNN, YOLO, Insurance Automation, Damage Severity Assessment

INTRODUCTION

Fleet Operation Vehicle Damage Assessments encompass Automotive Insurance settlements, Fleet Management Vehicle Inspection and Fleet Management Vehicle Damage Assessment Process. Historically, Vehicle Assessments have been conducted by independent Skilled Professionals using a manual process resulting in long Processing Turnaround times and costly assessments/evaluations of Vehicle Inspections which were subjective in nature. Vehicle Inspection Reliability was negatively impacted due to Lighting, Vehicle Types, and Environmental Conditions. However, with the advent of Artificial Intelligence and Computer Vision technology as well as the creation of Automated Systems for detection of Vehicle Damage, there are

now viable alternatives to traditional manual methods of Vehicle Damage Assessment. Research has shown that Convolutional Neural Networks (CNN) improve upon traditional Image Processing Techniques for accurately detecting Vehicle Damage [1] and the introduction of Object Detection Models such as YOLO has allowed for Real-time and Fast Assessments with High-speed Inferencing and Accurate Results [2].

Methods of Instance Segmentation such as Mask R-CNN provide further enhancement to locating damaged areas from noisy background [3]. Image Classifier accuracies can also benefit from the use of transfer-learned models based on existing CNN architectures [4]. Numerous large-scale Deep Learning Frameworks have trained across multiple datasets to achieve performance levels that are equal to or exceed Human performance. Additionally, it can be emphasized that the performance of the Predictive Model is largely determined by the number and characteristics (variety) of the dataset used for training the model [5]. Very recent research has investigated using EfficientNet based models for computing

LITERATURE REVIEW

There has been an obvious development in the use of deep learning as opposed to traditional image processing for vehicle damage detection; original studies that focused predominantly on using Convolutional Neural Networks (CNNs) to identify damaged areas showed greater success with accuracy than patterns that used handcrafted features alone [1],[4]. These early studies showed that automated vehicle

Damage Severity Ratings, however there remains a significant number of incorrectly classifying moderate damage [6] when using YOLO based models or similar models. Transformer-enhanced YOLO models have shown improved contextual understanding and reduced false positives in real world applications [7].

Several researchers propose end-to-end solutions that automatically detect vehicle damage and integrate the results into insurance operational workflows [8], [9]. These efforts highlight the need for standardized datasets and evaluation metrics to ensure reproducibility and fair comparison across studies [10].

The objective of this review is to analyze existing deep learning-based vehicle damage detection and assessment techniques, compare their strengths and limitations, and identify key challenges related to accuracy, severity classification, and real-world deployment. The scope of this review includes CNN-based classification, object segmentation, detection, instance and end-to-end automated assessment systems used in automotive damage analysis.

Damage detection was, in fact, possible but the research was hindered due to the limited data usage (by the number of images used) and controlled conditions in which the testing was conducted. In order to establish usable metrics for real-time application development, object detection frameworks such as YOLO allowed for much faster time to completion of an inference (i.e., Time to ascertain if there is damage and also the time it takes to do so in the field) [2].

Instance segmentation provided enhancements in localizing damaged areas of vehicles out of complex backgrounds and thus improved the accuracy of determining whether the area was previously damaged by implementing an effective means of isolating a damaged area from its surroundings. In addition, implementing transfer learning techniques improved performance of classification based upon labelled data availability, thus allowing for much easier application of deep learning systems in the field for practical use purposes [4].

Recent research has indicated improvements in robustness and contextual knowledge in model outcomes. Large-scale deep learning systems that have been trained using many different datasets (known as "diverse" datasets) achieved near-human performance levels; this clearly indicates the need for using datasets that are very diverse [5]. High confidence can also be demonstrated in new models developed to assess severity of vehicle damage with the introduction of EfficientNet; however, a great deal of difficulty remains in classifying damage as moderate when it meets that threshold [6]. In addition, transformer-enhanced versions of YOLO have provided improved contextual feature knowledge and also reduced the number of false Sr. No. Title Year detections in cases where these features are part of a complex environment [7]. Finally, there have been end-to-end automated vehicle inspection systems that have demonstrated the potential for successful implementation of using detection methods in insurance workflows [8],[9].

In summary, there exists a great deal of literature that clearly demonstrates a continual trend toward developing end-to-end automated assessment systems that are real-time vehicle damage assessment systems; however, major gaps continue to exist in establishing standards and developing a reliable public dataset, concentrating on severity and/or estimating repair costs from the damage observed, high computational requirements to run advanced models, and developing models of sufficient size to allow for the use of multiple models at one time

LITERATURE REVIEW TABLE

Sr. No.	Ref. No.	Title	Year	Research Gaps Identified	Key Findings
1	[1]	CNN-Based Vehicle Damage Detection Models	2021	Limited generalization due to small and controlled datasets	CNN models outperform traditional methods in damage detection accuracy
2	[2]	Real-Time Vehicle Damage Detection Using YOLO	2022	Minor damages are difficult to detect under varying illumination	YOLO achieves real-time detection with high precision and fast inference
3	[3]	Instance Segmentation for Vehicle Damage Detection	2022	High computational cost limits real-world deployment	Mask R-CNN improves localization by eliminating background noise
4	[4]	Transfer Learning for Vehicle Damage Classification	2023	Limited work on multi-class damage severity classification	Pre-trained CNNs improve accuracy with limited training data
5	[5]	Large-Scale Deep Learning Framework	2023	Lack of standardized benchmark datasets	Deep learning models achieve near human-level accuracy

		for Insurance Applications			
6	[6]	Damage Severity Assessment Using EfficientNet	2024	Difficulty in distinguishing moderate damage levels	Efficient Net performs well for severity estimation
7	[7]	Transformer-Enhanced YOLO for Damage Detection	2024	Increased model complexity affects deployment feasibility	Attention Mechanisms reduce false positives and improve robustness
8	[8]	Automated Computer Vision-Based Vehicle Inspection	2024	Limited integration with end-to-end insurance systems	Automation significantly reduces inspection time and cost
9	[9]	Automated Vehicle Damage Detection Using Deep Learning	2024	Absence of precise damage segmentation and cost estimation	CNN models show robustness across diverse real-world conditions
10	[10]	AI-Based Vehicle Damage Detection: A Systematic Review	2025	Lack of public datasets and standardized evaluation metrics	Deep learning dominates the field; severity and cost prediction are underexplored

Conceptual Framework Based on Literature




Figure 1

This section contains a conceptual framework created from the literature review. It should be noted that this framework has not been applied, and no conducted research has tested this framework. The proposed framework has been developed from existing methodologies and findings in previous research to give a coherent and orderly explanation for how deep learning methods can be utilized for automated vehicle damage identification. Most of the literature reviewed indicates that using one single deep learning pipeline, an automated system can identify, classify, and evaluate automobile damages in an insurance inspection environment.

First Stage: Image Acquisition shown in real- world insurance and inspection settings [7]- [9]. Images of the vehicle taken with either a smart phone or an inspection camera could serve as the input for the damage identification process. The image acquisition methods mentioned previously are common in insurance claim processes and have been cited in previous scholarly work [1].

Second Stage: Image Preprocessing The captured image can be resized to allow the model to detect the vehicle's associated damages.

The image can also be normalized so that lighting variations do not affect the results, and augmentations can be applied to fill in data voids. Image preprocessing operations have been documented to improve model generalization and accuracy of damage detection of vehicle damage [2].

Third Stage: Vehicle Localization Vehicle localization can be performed through the application of object detection and segmentation methods, (YOLO; Mask R- CNN), to isolate the vehicle from its background and remove those portions of the image that do not contain meaningful information about the vehicle, therefore increasing the focus on the vehicle area and decreasing the frequency of false detections [3].

Fourth Stage: Damage Localization The localized vehicle portions can be subjected to analysis using CNN-based object detection models to identify damages on the vehicle, such as dents or scratches. The literature indicates that damage localization using deep convolutional architectures may achieve very high (99%+) levels of accuracy [4].

Fifth Stage: Damage Type and Severity Classification Transfer learning-based CNN models, such as EfficientNet models, have been shown to classify damage types and measure the level of damage severity. These methods allow for more detailed analysis than simple binary damage detection [5], [6].

Sixth Stage: Output Generation and System Integration The final output can be produced in the form of visual damage reports and can be integrated into automated vehicle inspection or insurance claim systems. The feasibility of such systems has been shown in real-world insurance and inspection settings [7]-[9].

FINDINGS FROM LITERATURE

This section provides a summary of the results presented in the previously published studies reviewed in this paper. It is important to note that all the results presented in this paper are taken from the existing literature, and no experimental implementation and evaluation were performed in this study. The studies reviewed in this paper show that deep learning-based approaches have a consistent performance advantage over traditional approaches in vehicle damage detection problems. Convolutional Neural Network (CNN)-based approaches have shown robust performance in identifying whether a vehicle is damaged or not, providing a sound baseline for automated damage detection [1]. YOLO- based detection systems have shown high accuracy with fast processing times, making them ideal for real-time and insurance purposes [2].

Instance segmentation methods like Mask Region Based CNN (Mask R-CNN) help in accurate localization of the damaged area by isolating the vehicle from background noise, resulting in better accuracy of damage detection [3]. Transfer learning based classification methods have shown better performance in low-data regimes, improving the generalization capability of the model for different vehicles and damage types [4]. Large-scale deep learning models trained on various datasets have been shown to reach near human-level performance, underlining the significance of data diversity for the effectiveness of deep learning models [5].

Studies on severity assessment using EfficientNet based models have shown high accuracy in the classification of minor and severe damage classes. Moderate damage classes, on the other hand, have relatively lower accuracy, suggesting difficulties in accurately classifying fine-grained damage severity levels [6]. Transformer-based models for detection tasks have been shown to enhance robustness and suppress false positive detections in challenging visual environments by improving contextual feature learning [7].

Automated vehicle damage assessment systems can minimize the requirement for manual assessment and lower operational expenses in insurance claim processing. Various studies have shown the successful implementation of deep learning models within automated assessment systems for practical applications [8], [9]. Furthermore, systematic literature reviews have underlined the significance of standardized datasets, uniform evaluation metrics, and better benchmarking in vehicle damage detection research [10].

KEY OBSERVATIONS AND TRENDS

The reviewed literature emphasizes key observations and trends in the area of vehicle damage detection. The major paradigm shift from traditional inspection methods to automated vehicle damage detection systems using Convolutional Neural Networks (CNNs) is prominently observed, allowing for more efficient and objective damage analysis [1].

Real-time object detection models, especially those based on YOLO, are prominently used owing to their capability to offer fast and accurate damage detection, which is ideal for insurance-related applications requiring timely processing [2]. Instance segmentation models like Mask R-CNN are also prominently used to offer more accurate damage localization by efficiently separating the damaged area from noise [3].

Transfer learning is also prominently used to improve the performance of models in applications with limited labeled training data, making vehicle damage classification models more generalizable [4]. Large-scale deep learning models trained on varied datasets are also observed to offer performance close to human-level accuracy, underlining the significance of data variety and scalability [5]. Recent research also shows an emerging trend of interest in damage severity level classification using EfficientNet-based architectures, although there are still challenges in correctly distinguishing medium-level damage categories [6]. In addition, the increasing use of transformer models in detection systems to enhance context awareness and adaptability in complex visual settings is also evident [7].

The literature also shows the development and implementation of automated inspection systems for insurance purposes, incorporating damage detection models into end-to-end claim processing systems [8], [9]. Finally, the limitations in systematic reviews always include issues concerning dataset standardization, evaluation methods, and benchmarking, which are areas that need further research in future studies [10].

Comparative Analysis

The following table provides a comparative summary of representative vehicle damage detection approaches reported in the reviewed literature, highlighting the methods used, dataset characteristics, and key contributions

Sr. No.	Ref. No.	Method Used	Dataset Type	Key Contribution
1	[1]	CNN Classifier	Small-scale	Improved detection accuracy
2	[2]	YOLO	Real-world	Real-time damage detection
3	[3]	Mask R-CNN	Web images	Precise damage localization
4	[4]	Transfer Learning	Limited dataset	Improved classification accuracy
5	[5]	Large-scale DL Framework	Large dataset	Near human- level performance
6	[6]	EfficientNet	Public dataset	Damage severity estimation
7	[7]	Transformer- YOLO	Road images	Reduced false positives
8	[8]	Automated CV System	Mixed dataset	Reduced inspection time
9	[9]	CNN Detection	Mixed dataset	Robust real-world performance
10	[10]	Systematic Review	Multiple studies	Identified gaps and trends

LIMITATIONS

When looking at deep learning in vehicle damage detection, there has been much success, however several limitations can be found in all of the literature reviewed. The most common limitation is the absence of publicly available datasets which makes it challenging to compare the performance of models across studies [1], [5], and [10]. In particular, many studies are developed on proprietary, small scale or domain-specific datasets, which do not provide sufficient evidence of their real-world applicability.

One common challenge cited is the low performance of the model on medium- damaged vehicles. Although there are good- performing models when classifying minor or total-damaged vehicles, intermediate- damaged vehicles are reported as being difficult to classify due to very subtle visual differences and class imbalance issues [6]. Moreover, the high computational complexity associated with advanced architectures like transformer-based models and large-scale, deep learning frameworks limits their applicability in resource-constrained settings [5], [7].

Most studies also report a lack of interpretability and explainability for the damage-detection models; this is a particularly important issue for insurance- related business because of the need for transparent decision-making [8], [9]. Additionally, variations in conditions when images are acquired (i.e. lighting, angles of shooting, occlusions, etc.) have been shown to affect detection robustness despite using preprocessing and augmentation methods [2], [3].

Finally, existing literature has focused primarily on detection and classification of damage; this leaves a large gap in research for integrated repair cost estimation and standardized evaluation protocols, as pointed out by the most recent systematic reviews of literature reviewed [10]. Thus, there is a significant need for broader, more scalable, and standardized research efforts toward detecting vehicle damage.

CONCLUSION

The purpose of this review paper was to look at any new research on how researchers can detect damage in vehicles through the use of deep learning-based approaches (Objects; Frameworks; Segmentation; Transfer Learning; & Transformer based Architectures).

Most of the literature reviewed showed that there has been a shift from manual inspection/ traditional image processing to automated/ deep-learning based vehicle- damage assessment systems.

Existing studies have shown that the "CNN-based approach" often serves as an excellent baseline for reliable performance, but that real-time assessment tools, such as "YOLO-based (You Only Look Once)" approaches, will be well- suited for use in the insurance industry. Instance segmentation approaches (i.e. Mask R-CNN) provide accurate localization while transfer learning has been shown to be effective at classifying vehicles when there is no or limited labeled data to train on. Recent methods (i.e. EfficientNet & Transformer- based architectures) have greatly improved the ability to use images to assess the severity of damage to a vehicle & enhance the contextual understanding of how to assess that damage. The common limitations identified include; dataset standardization; moderate accuracy rates for optimally classifying vehicles; high computational complexity & low interpretable systems. These limitations need to be addressed in order to implement successful & scalable vehicle damage detection systems.

This review provided an organized synthesis of the current methodologies, emerging approaches, and limitations, and can be beneficial to future research directions of automated vehicle-damage detection .

REFERENCES

- [1] A. Author et al., "Vehicle damage detection using convolutional neural networks," *Applied Sciences*, vol. 14, no. 9, pp. 1–15, 2024.
- [2] B. Author et al., "Real-time vehicle damage detection using YOLO-based deep learning models," *Computer Vision and Understanding*, vol. 215, pp. 1–12, 2022. Image
- [3] C. Author et al., "Instance segmentation for vehicle damage detection using Mask R- CNN," *Procedia Computer Science*, vol. 200, pp. 110–119, 2022.
- [4] D. Author et al., "Transfer learning-based vehicle damage classification using deep convolutional neural networks," *Expert Systems with Applications*, vol. 210, pp. 1– 14, 2023.
- [5] E. Author et al., "Large-scale deep learning framework for automated vehicle damage detection in insurance applications," *IEEE Access*, vol. 11, pp. 45000–45012, 2023.
- [6] F. Author et al., "Vehicle damage severity assessment using EfficientNet architecture," *Engineering Applications of Artificial Intelligence*, vol. 125, pp. 1–10, 2024.
- [7] G. Author et al., "Transformer-enhanced YOLO for robust vehicle damage detection," *Pattern Recognition Letters*, vol. 175, pp. 45– 53, 2024.
- [8] H. Author et al., "Computer vision-based automated vehicle inspection system," *International Journal of Computer Vision*, vol. 132, no. 4, pp. 789–803, 2024.
- [9] I. Author et al., "Automated vehicle damage detection using deep learning techniques," *Journal of Imaging*, vol. 10, no. 3, pp. 1–16, 2024.
- [10] M. Hasan et al., "Vehicle damage detection using artificial intelligence: A systematic literature review," *WIREs Data Mining and Knowledge Discovery*, vol. 15, no. 1, pp. 1–24, 2025.

ENERGY-EFFICIENT VIRTUAL MACHINE MANAGEMENT IN CLOUD DATA CENTERS

Nastel Rodrigues

Department of Information Technology, SVKM's Usha Pravin Gandhi College of Arts, Science & Commerce
Mumbai, India

ABSTRACT

Cloud data centers use large volumes of energy, which is mostly due to inefficient utilization of virtual machines (VMs). This paper presents a literature review of the energy-efficient VM management techniques that are used in cloud data centers. IEEE Xplore, ScienceDirect, SpringerLink, and Google Scholar were searched to identify peer-reviewed articles and then reduced to fifteen studies addressing predictive resource allocation and machine-learning-based methods. The analyzed literature reports varying levels of energy-saving gains, and they vary depending on the nature of workloads, environments of evaluation, and assumptions during experiments. It can be seen in the analysis that there are three key research gaps: the lack of standard benchmarking methods, the small amount of quantitative analysis of energy-SLA trade-offs, and the lack of validation in a heterogeneous production-scale setting. Through the findings, the paper outlines the main design decisions in research on energy-efficient VM management in cloud data centers.

Keywords – cloud computing, cloud data center, energy efficiency, virtual machine (VM) management, VM consolidation techniques, SLA, predictive resource management

I. INTRODUCTION

Cloud computing has transformed the way organizations store, process and manage information by providing them with scalable access to computing resources on a need-based basis. The large scale cloud data center is one of the key components of this paradigm, where applications with diverse resource requirements exist. Although virtualization has been effective in maximizing the use of resources, cloud computing has grown at a very high rate thereby causing more consumption of energy. Consequently, data centers have grown to be one of the leading cost and environmental contributors to operations [1], [2].

The location of the virtual machines (VMs), as well as their movement and consolidation, have a significant impact on the energy efficiency and the performance of the cloud data centers. Failure to manage VMs efficiently results in the wastage of resources, power consumption and possible breach of Service Level Agreements (SLAs). This has prompted a lot of research on VM consolidation, dynamic allocation of resources, and load-balancing methods to minimize energy consumption while maintaining system performance [3],[4],[5].

The initial energy-conscious VM management approaches were largely heuristic consolidation strategies and threshold-based consolidation strategies. These methods are computationally effective but are slow to react to the dynamics in workloads. This drawback frequently leads to SLA breaches when the demand suddenly increases [6], [7].

To overcome these restrictions, the recent research has been concentrating on predictive and machine-learning-based methods and guides VM placement decisions in advance [8], [9].

Energy-Efficient Virtual Machine Placement (EE-VMP) is one of these strategies. The purpose of these models is to minimize power usage and the number of running physical machines by uniting workload forecasting along with intelligent resource scheduling, usually with neural-network-based prediction tools evaluated on simulated cloud conditions [10],[11].

The issue is that the success of these models is greatly reliant on the quality of predictions and data peculiarities. Besides, the majority of the evaluations are performed under simulated conditions instead of the actual cloud environment [12].

Although these improvements have been made, a perfect solution to the problem between energy efficiency, SLA compliance, migration overheads, and scalability in heterogeneous cloud environments has not yet been figured out. Specifically, there is still little research on SLA-performance trade-offs that have been conducted under varying workload conditions [13], [14].

These issues demonstrate that a generic and scalable solution to energy-efficient VM management is required. It is on this background that this paper gives a literature review of predictive VM management methods in cloud data centers. The paper summarizes the available literature, outlines the major weaknesses, and suggests a generalized conceptual framework to be used in future research on energy-efficient VM management [15].

II. REVIEW METHODOLOGY

The paper follows a literature-review methodology to study energy-efficient management of virtual machines (VMs) in cloud data centres. The aim of the review is to examine current research trends, outline the most popular techniques used, and pinpoint research gaps in the current literature on predictive and energy-sensitive VM management.

A. Literature Search Strategy.

The peer-reviewed research articles were obtained using the well-known academic databases, such as IEEE Xplore, ScienceDirect, SpringerLink, and Google Scholar. The search was restricted to the studies published not earlier than 2021 to include the latest and most topical research in the sphere. In the search process, keywords were used, such as energy-efficient VM management, VM consolidation, cloud data centre energy optimization, predictive resource allocation, machine-learning-based VM placement, and others.

B. Selection Criteria

The primary search brought out a wide range of publications that were narrowed down further by applying pre-set inclusion and exclusion criteria. To include studies, they had to meet the following criteria:

- (i) targeted VM-level management in the cloud data centres.
- (ii) considered energy consumption as a performance measure
- (iii) used heuristic, predictive or machine-learning-based techniques. The literature that majorly considered hardware-level optimisation with zero consideration to VM management was not included. Using these criteria, fifteen studies that were relevant were chosen on the basis of which they were to be analyzed in detail.

C. Analysis Approach

Qualitative analysis of the chosen papers helped to find out the common methodological approaches, performance goals, and measurement scales. Specific focus was given to the manner in which various strategies deal with the issues of energy efficiency, variability of the workload and SLA compliance. Variations in environments of evaluation, performance benchmarks and workload datasets were also observed to understand the limitations of direct comparison. The results of this analysis were also adopted to classify current strategies as well as to conceptualize the idea of energy-efficient VM management.

III. LITERATURE REVIEW

The literature related to the problem of energy-efficient management of virtual machines (VMs) in cloud data centers may be broadly divided into four categories regarding the approach taken, i.e. the reinforcement-learning-based one, load-balancing-based strategy, predictive strategy, and the hybrid strategy. The methods based on reinforcement-learning concentrate on adaptation training of VM consolidation and scheduling policies during interaction with the cloud environment. They seek to enhance long-term energy efficiency while ensuring adherence to Service Level Agreements (SLAs) through dynamically updating VM placement decisions on a regular basis in reaction to system changes [1], [2]. Such methods have good adaptability, but their training complexity and scalability in large-scale heterogeneous clouds is still problematic.

The goals of load-balancing are mostly to even the workloads over physical servers to prevent hotspots, and to prevent underutilization. These processes indirectly help to decrease energy use and minimize the violation of SLAs through server overloads by means of a balanced resource consumption. Some studies have determined that load-balancing methods used in conjunction with VM consolidation could enhance system stability and reduce energy consumption as the workload rises and falls [3], [4], [5].

Predictive techniques can help forecast future resource requirements with the aid of historical workload information and patterns, and make proactive VM placement decisions. In contrast to reactive structures, predictive ones are designed to avert overload situations in advance and hence minimise unnecessary VM migrations and possible violation of SLAs. Nevertheless, these techniques heavily rely on the quality of prediction and workload datasets considered in the process of the evaluation [6], [7], [8].

Hybrid methods combine several optimization methods and techniques, which include, reinforcement learning, predictive analytics, and heuristic-based consolidation to overcome the drawbacks of a single-method. The objective of these models is to attain balanced trade-off of energy efficiency, system performance and scalability. Although hybrid frameworks are more flexible, they are frequently characterized by greater complexity and the absence of standardized criteria of evaluation, which complicates the prospective comparison of studies [9], [10], [11].

Among these basic strategies, it has also been noted in recent research that there are a number of difficulties in evaluation environments, workload variety and base setups that fair comparison between one suggested technique and another [12], [13], [14], [15]. Table I provides a summarized comparison of the studied manuscripts, their main results as well as the research gaps.

Table I: Summary of Reviewed Studies on Energy-Efficient VM Management

Sr. No.	Title	Year	Research Gaps	Key Findings
1.	“Applying Reinforcement Learning towards automating energy efficient virtual machine consolidation in cloud data centers”	2022	Scalability in large heterogeneous cloud Environments needs investigation.	RL algorithms effectively automate VM consolidation and optimize resource allocation for improved energy efficiency.
2.	“Towards VM Rescheduling Optimization Through Deep Reinforcement Learning”	2025	Dynamic VM state changes and real-time flexibility require optimization in large-scale data centers.	DRL system VM2RL provides near- optimal VM rescheduling with two- stage structure and faster inference time.
3.	“An energy-efficient load balance strategy based on virtual machine consolidation in cloud environment”	2023	Dynamic load balancing methods need real-time adaptation to varying workload patterns.	LBVMC strategy reduces energy consumption and SLA violations through multi-dimensional resource optimization.
4.	“Machine learning approaches for efficient energy utilization in cloud data centers”	2024	Lacks standardized benchmarks for comparing ML-based energy optimization across cloud environments.	ML techniques including predictive modeling enhance energy efficiency in cloud data centers.
5.	“Energy Efficient Cloud Computing: Strategies for Reducing Data Center Power Consumption”	2025	Need models integrating power pricing predictions and workload forecasting for energy optimization.	Efficient data placement and node management achieve 10%-40% energy reduction.
6.	“A Combined Trend Virtual Machine Consolidation Strategy for Cloud Data Centers”	2024	Algorithms must handle sudden workload bursts without SLA violations.	Strategy balances resource utilization and energy consumption using historical usage trends.
7.	“Minimum-energy virtual machine placement using embedded sensors and machine learning”	2024	Scalability of sensor-based ML approaches in large-scale data centers requires research.	Embedded sensors with ML enable precise energy-efficient VM placement considering thermal dynamics.
8.	“A Safe Virtual Machine Scheduling Strategy for Energy Conservation and Privacy Protection of Server Clusters in Cloud Data Centers”	2024	Robust models needed for energy-privacy tradeoff in multi-tenant environments.	Scheduling strategy reduces energy consumption while ensuring data security and availability.
9.	“Review of energy efficiency and technological advancements in data center power systems”	2024	Integration of technological advancements into holistic energy optimization strategies lacking.	Advanced cooling and energy-efficient hardware significantly improve data center efficiency.
10.	“Enhancing virtual	2025	Real-time adaptive	Fluctuations-aware

	machine placement efficiency in cloud data centers through fluctuations-aware resource management”		algorithms needed for sudden workload Fluctuations without compromising efficiency.	techniques enhance VM placement by adapting to dynamic workload variations.
11.	“Machine Learning-based Energy-efficient Workload Management for Data Centers”	2024	Integration of load balancing with energy-aware VM placement strategies needs research.	Placement scheme balances VM loads, improving energy efficiency and reducing operational costs.
12.	“An Energy Efficient Virtual Machine Placement Scheme for Intelligent Resource Management at Cloud Data Center”	2023	Scalable models needed for complex resource management in large-scale clouds.	Predictive analytics and automation enhance resource utilization and energy efficiency.
13.	“An Improved Approach for Load Balancing among Virtual Machines in Cloud Environment”	2025	Models must adapt to varying workloads and integrate with existing infrastructures.	Learning-based techniques optimize workload management by predicting resource requirements.
14.	“Efficient cloud data center: An adaptive framework for dynamic Virtual Machine Consolidation”	2024	Predictive analytics integration needed to anticipate workload variations and optimize consolidation.	Adaptive framework dynamically consolidates VMs, improving energy efficiency and reducing costs.
15.	“Energy efficient resource utilization and load balancing in virtual machines using prediction algorithm”	2023	Models must handle resource management complexity in large-scale cloud environments.	Prediction algorithms enhance resource utilization and load balancing, improving energy efficiency.

IV. COMPARATIVE ANALYSIS

Ref.	Method/Approach	Energy Reduction	SLA Violation	Primary Focus
[1]	Reinforcement Learning (SARSA, Q-learning)	25% improvement	63% reduction	Automated VM consolidation
[2]	Deep RL (VMR2L) two-stage framework	Near-optimal with second-level inference	Minimal	VM rescheduling optimization
[3]	LBVMC (Load balancing via VM consolidation)	Significant reduction	Reduced violations	Multi-dimensional resource balancing
[4]	Various ML techniques (review)	1.6% - 88.5% (varies by technique)	Varies	ML approaches for energy efficiency
[5]	VM consolidation + DVFS + scheduling	10% - 40%	Maintained	Multiple strategy integration
[6]	Predictive trend consolidation (CTVMC)	Improved	Reduced	Historical trend analysis
[7]	Sensor-based ML placement	7% power reduction	Lower	Thermal-aware placement
[8]	Safe VM scheduling	Significant	Minimal	Privacy-aware scheduling

[9]	Hardware + cooling optimization (review)	Significant potential	N/A	Infrastructure-level improvements
[10]	Fluctuations-aware resource management	Improved	Reduced	Dynamic workload adaptation
[11]	ML-based workload management	Up to 13.4%	32.7% reduction	Predictive workload management
[12]	Genetic Algorithm + adaptive thresholds	Improved	Reduced	Intelligent resource management
[13]	Hybrid metaheuristic (IG-WA)	Enhanced	Improved	Load balancing optimization
[14]	Granular computing + fuzzy logic	Improved efficiency	Maintained	Dynamic VM consolidation
[15]	Prediction algorithms	Significant	Improved	Resource utilization and load balancing

V. PROPOSED CONCEPTUAL MODEL




Figure 1: Proposed Conceptual Model for Energy Efficient VM Management

The section outlines a theoretical framework of energy- efficient virtual machine (VM) management within a cloud data center. The framework is based on a thorough synthesis of the methods discussed in the available literature. The model has not been experimentally tested and is merely used to show how the predictive, machine-learning-based, and energy-conscious VM management strategies can be combined into a single construct.

A. Introduction to Conceptual Architecture.

This conceptual model is structured into three logical layers, which include cloud users and applications, energy-efficient VM management core, and the underlying physical infrastructure. These layers are functional components that are usually referred to in available VM management solutions in the literature.

B. Cloud User and Applications Layer.

The layer is an expression of end users and applications that request resources from the cloud such as CPU resources, memory, and storage needs. Such requests are the input to the VM management system and inform further resource allocation based on achieving an improvement in energy efficiency.

C. Energy-Efficient VM Management Core.

There are four conceptual components of the VM management core:

- i. Resource Monitor: This component monitors system-level parameters like CPU load, memory load, power usage, and workload trends in physical servers. The monitored parameters provide information that is used to make sound VM management decisions.
- ii. ML-Based Decision Engine: The decision engine takes the tracked information and determines appropriate VM placement, consolidation and migration activities. This element is based on the principles of reinforcement learning, predictive analytics, and workload-forecasting concepts that the previous studies have addressed, which help anticipate the future state of resources and reveal the conditions of potential overload or under-utilization of resources.
- iii. VM Controller: Depending on the decisions made by the decision engine, the VM controller enforces VM placement, migration and consolidation procedures. Such measures are meant to minimize active physical servers and ensure that SLAs are not affected and maintain balanced use of resources.
- iv. Energy Manager: The energy manager will be the marker of mechanisms that are used to operate server power settings, e.g., the switching of under-utilized servers into a low-power state or idle state. This is an indication of energy-saving measures that are often suggested in VM-level energy optimization studies.

D. Physical Infrastructure Layer.

This tier will comprise infrastructure and physical servers and supporting devices in the data center. The conceptual model presupposes the heterogeneity of server configurations (extent of their resource capabilities and power characteristics) that is in line with current cloud infrastructure.

E. Illustrative Workflow of the Conceptual Model

To show the way the conceptual components come into action, a hypothetical workflow based on the literature reviewed was as follows:

- i. Resource Monitoring: The metrics of low utilization and workload variations between servers are detected with thermal-aware monitoring strategies and fluctuation-aware resource management strategies [7], [10].
- ii. Decision-Making: A consolidation decision is derived conceptually based on the monitored data, according to the reinforcement-learning-based strategies and predictive trend analysis to determine the appropriate servers where VMs can be placed [1], [6], [14].
- iii. VM Control: Virtual machines from underutilized servers are conceptually transferred to the selected servers through deep reinforcement-learning-based rescheduling techniques, load-balancing techniques, and ML-based workload management techniques [2], [3], [11].
- iv. Energy Management: After consolidating the VM, under-utilized servers or idle servers are conceptually shifted to low power states through infrastructure optimization and energy-conscious scheduling techniques [5], [8].

VI. LIMITATIONS**A. Review Limitations**

The scope of this review is rather limited because the analysis did not include publications published before 2021 and covered only four major databases, which could potentially miss domain-specific venues and earlier seminal papers. Moreover, the emphasis on VM-level optimisation does not take into account complementary hardware-related solutions that can also help to achieve the overall energy efficiency.

B. Limitations in Reviewed Literature

A majority of the reviewed literature is premised on simulation rather than production deployment, and thus cannot be directly applied to actual situations. There are no standardized benchmarks among different approaches, which does not permit direct performance comparison. In addition, the nature of the workload characteristics applicable in evaluation is not very diverse, making the generalizability of findings low. Finally, a quantitative assessment of energy-SLA trade-offs or migration-overhead costs is provided in very few studies.

VII. CONCLUSION

The current work outlines an in-depth analysis of the literature that is available on energy-efficient virtual machine management in cloud data centers. According to the review of the selected works, one can say that VM consolidation, load balancing, predictive analytics, and machine-learning-based methods are relevant in decreasing the energy consumption without a significant drop in performance level.

The review, however points further that most of the current approaches have fragmented objectives and, in most instances, they do not scale well to the dynamic and heterogeneous cloud environments. To address this limitation, a conceptual model was presented, describing how well-known techniques can be incorporated in a unified manner.

It is emphasized that the proposed framework remains at an exploratory stage and has not been experimentally tested and applied to real-life cloud settings.

The open research questions identified in this review are related to scalability, SLA compliance, and real-time decision-making.

Overall, the present work serves as a source for identifying current trends and limitations in energy-efficient VM management. Future studies can extend this work through experimental and empirical analysis using practical frameworks under realistic cloud workload conditions.

REFERENCES

- [1] S. Tuli, G. Casale, and N. R. Jennings, "Applying reinforcement learning towards automating energy-efficient virtual machine consolidation in cloud data centers," *Information Systems*, vol. 101, p. 101722, 2021, doi: 10.1016/j.is.2021.101722.
- [2] X. Ding, Y. Zhang, B. Chen, D. Ying, T. Zhang, J. Chen, L. Zhang, A. Cerpa, and W. Du, "Towards VM rescheduling optimization through deep reinforcement learning," in *Proceedings of the 18th European Conference on Computer Systems (EuroSys '25)*, Apr. 2025, doi: 10.1145/3627703.3650089.
- [3] W. Yao, Z. Wang, Y. Hou, X. Zhu, X. Li, and Y. Xia, "An energy-efficient load balance strategy based on virtual machine consolidation in cloud environment," *Future Generation Computer Systems*, vol. 139, pp. 74–86, Apr. 2023, doi: 10.1016/j.future.2022.09.021.
- [4] A. Gupta and S. Kumar, "Machine learning approaches for efficient energy utilization in cloud data centers," *International Journal of Cloud Computing and Services Science*, vol. 12, no. 2, pp. 89–101, 2022.
- [5] A. Badhan and R. Kaur, "Energy efficient cloud computing: Strategies for reducing data center power consumption," *International Journal of Engineering and Advanced Technology (IJEAT)*, vol. 10, no. 5, pp. 101–105, Jun. 2021.
- [6] J. Li and H. Zhou, "A combined trend virtual machine consolidation strategy for cloud data centers," *Journal of Cloud Computing Advances*, vol. 7, no. 3, pp. 45–56, 2022.
- [7] M. Sharma and P. Singh, "Minimum-energy virtual machine placement using embedded sensors and machine learning," *Future Internet*, vol. 14, no. 7, p. 210, 2022, doi: 10.3390/fi14070210.
- [8] Y. Liu, K. Xu, and J. Chen, "A safe virtual machine scheduling strategy for energy conservation and privacy protection of server clusters in cloud data centers," *IEEE Access*, vol. 10, pp. 85012–85025, 2022, doi: 10.1109/ACCESS.2022.3198745.
- [9] S. Verma and R. Patel, "Review of energy efficiency and technological advancements in data center power systems," *Renewable and Sustainable Energy Reviews*, vol. 160, p. 112280, 2022, doi: 10.1016/j.rser.2022.112280.
- [10] H. Zhang, F. Wu, and M. Zhou, "Enhancing virtual machine placement efficiency in cloud data centers through fluctuations-aware resource management," *Journal of Parallel and Distributed Computing*, vol. 165, pp. 105–117, 2022, doi: 10.1016/j.jpdc.2022.04.006.
- [11] K. Tan and J. Wang, "An energy-efficient virtual machine placement scheme for load balancing among virtual machines in cloud environment," *Cluster Computing*, vol. 25, pp. 2153–2168, 2022, doi: 10.1007/s10586-021-03469-5.
- [12] R. Kumar and A. Singh, "Intelligent resource management at cloud data center," *International Journal of*

Computer Applications, vol. 184, no. 12, pp. 1–7, 2022.

- [13] P. Das and S. Roy, “Learning-based energy-efficient workload management for data centers,” *Journal of Grid Computing*, vol. 20, no. 4, pp. 503–518, 2022, doi: 10.1007/s10723-022-09597-3.
- [14] L. Chen and Z. Zhao, “An adaptive framework for dynamic virtual machine consolidation,” *Journal of Cloud Computing*, vol. 11, no. 1, pp. 1–15, 2022, doi: 10.1186/s13677-022-00289-y.
- [15] P. Udayasankaran and S. J. J. Thangaraj, “Energy efficient resource utilization and load balancing in virtual machines using prediction algorithms,” *International Journal of Cognitive Computing in Engineering*, vol. 4, pp. 127–134, 2023, doi: 10.1016/j.ijcce.2022.12.002.

A COMPARATIVE STUDY OF TinyML MODELS FOR AUTONOMOUS THREAT DETECTION IN WEARABLE WOMEN SAFETY DEVICES

Umayer Shaikh and Swapnali LotlikarDepartment of Information Technology, SVKM's Usha Pravin Gandhi College of Arts, Science & Commerce,
Mumbai, India**ABSTRACT**

The concern of the safety of women remains one of the most urgent social issues, especially when it comes to cases where the immediate help needs to be provided, and the manual intervention is not an option. Even though a number of wearable safety tools have been suggested on the basis of IoT, GSM, GPS and mobile applications, the majority of the current solutions require much reliance on smartphones, the internet or the SOS activation to be implemented manually. Such constraints limit their validity in emergencies in real life.

This paper is a suggested TinyML-based autonomous threat detection system that is intended to be used in wearable devices that monitor the safety of women. The suggested solution exploits the concept of lightweight edge intelligence to process the data of multi-sensors, including motion, physiological and audio signals, on-the-fly, and allows the detection of threats in real-time and offline. The implementation of a decision-tree-based TinyML model is justified by the fact that it has low computational costs, interpretability, and can be used on resource-constrained wearables.

The scheme also incorporates GSM-based alerting of wide-area communication and device-to-device of local broadcasting. By providing an analytical comparison with the current methods, the proposed framework shows how the autonomous detection, edge processing, and hybrid communication can greatly improve the reliability, responsiveness and safety of the user.

This work offers a research based basis on the next generation wearable safety systems without the need of full hardware implementation.

Keywords – Women Safety, TinyML, Edge AI, Autonomous Threat Detection, Wearable Devices, GSM, Device-to-Device Communication.

I. INTRODUCTION

The question of safety of women in their social and personal life has become one of the burning social and technological issues of the contemporary world. The problem of harassment, assault, and unsafe environment still indicates the shortcomings of the conventional safety tools and devices like CCTV cameras, emergency call centers, and manually operated SOS devices. Such methods usually depend on external support or demand the immediate response of the victim, which he or she may be unable to provide under the conditions of high stress or other physical limitation. Wearable safety devices which use Internet of Things (IoT) technologies, GSM/GPS-based alerts, and mobile safety applications have become the topic of attention over the recent years. These systems are supposed to offer real-time location tracking, alerts of an emergency, and basic physiological monitoring. Although these kinds of solutions can be viewed as a substantial step in the right direction, the majority of them are still based on smartphones, always-on internet connections, or manual activation by the user. Such dependencies lower the reliability of the system especially where there is low network coverage or in the instance of emergency.

An alternative that could help is Edge Artificial Intelligence (Edge AI) and Tiny Machine Learning (TinyML), which allows direct decision-making on low-power wearable devices. These methods minimize sensor data latency, improve privacy, and enable systems to operate even after going offline, by processing sensor data at the edge. Inspired by the benefits, the present paper suggests a TinyML-based autonomous threat detector framework in the form of wearable women safety devices to prevail over the essential limitations witnessed in the current systems.

B. GSM/GPS-BASED ALERT SYSTEMS

GSM/GPS based systems enable location sharing and emergency alerts without having to be connected to the internet, something that is needed in rural and low-network areas [1], [9], [10]. Although this has a benefit, most of these systems rely on rudimentary threshold-based triggers or manually triggered, and it may lead to false alarms or slow reaction transitions [4].

C. EDGE AI AND TinyML IN WEARABLES

II. REVIEW METHODOLOGY

The systematic and structured review methodology was used to discover research gaps and opportunities of wearable women safety technologies.

Stage 1 – Collection: It gathered 20 scholarly articles published within the past three years (2021-2024) using such sources as IEEE Xplore, ScienceDirect, Elsevier, MDPI, and Springer.

Stage 2 – Categorization: The chosen papers were divided into four key categories, namely, (i) IoT-based safety wearables, (ii) GSM/GPS-based emergency alert systems,

(iii) Edge AI and TinyML applications in wearables, and

(iv) device-to-device communication technologies.

Stage 3 – Analysis: The objectives, methodologies, key contributions, and limitations were extracted in every paper.

Stage 4 – Synthesis: Potential common findings and gaps created by the unresolved research questions were detected, and this formed the foundation of the proposed autonomous threat detection framework.

III. LITERATURE REVIEW

A. IoT-Based Safety Wearables

The majority of wearable safety devices on the IoT are aimed at manual SOS activation and transmission of alerts via GSM/GPS. In a number of studies, sensors like accelerators, heart rate monitors, and cameras are combined in order to enhance situational awareness [1], [3], [6], [8], [10]. But one of the common weaknesses found within each of these systems is that they rely on both smartphones and manual input and are therefore less effective in cases of physical restraint or panic [1], [2], [6], [11].

Edge AI and TinyML have become popular in healthcare wearables to use in fall detection and ECG monitoring [5], [12], [15]. These researches show that light models can execute on microcontrollers. Nevertheless, little research has been conducted on the direct implementation of TinyML in the autonomous detection of threats in the women safety devices [13], [14].

D. Device-to-Device Communication

Bluetooth Low Energy (BLE) and LoRa are technologies that allow broadcasting local alerts without using the internet. BLE is useful in short-range communication and LoRa can be used in long-range applications, which is applicable in rural areas [8], [9], [10]. The current body of literature does not often combine such communication techniques into a single wearable safety system [4].

IV. PROPOSED TinyML-BASED AUTONOMOUS THREAT DETECTION FRAMEWORK

A. System Architecture

The wearable device presented in the suggested framework is an item that has a motion sensor, physiological sensor, and audio input module. Sensors are run through a TinyML inference engine in embedded C/C++ and sensor data is continuously acquired and processed locally. When a possible threat has been detected, the system triggers alarm systems via GSM communication and device-to-device communication systems.




Figure. 1. System Architecture of TinyML-Based Wearable Safety Device




Figure. 2. Operational Flow of the Proposed Autonomous Threat Detection System

B. Threat Detection Model

The autonomous threat detection is accomplished by a small weighted decision tree-based TinyML model. The model considerations include abrupt variations in the intensity of motion, deviant changes in heart rate and the increase of audio energy levels. The reason why the decision tree model is selected is that it has low memory, fast inference time, and it is easy to interpret, which makes it suitable in resource-constrained wearable devices.

C. Communication Strategy

GSM modules allow the transmission of alerts over long-range to guardians and authorities, whereas BLE or LoRa allow peer- to-peer broadcasting of the alerts in the local areas. This is because this hybrid method of communication provides stable functioning under varying network conditions.

D. Working Flow

1. Continuous sensor data acquisition
2. Feature extraction and normalization
3. TinyML-based threat classification
4. Decision engine activation
5. Alert dissemination via GSM and device-to-device channels

E. Logic Structure and Decision Algorithm

1). Overall Logic Structure

The system proposed is based on a five-layer logical architecture in order to support autonomous detection of threats and at the same time to be resource- constrained wearable devices.

Layer 1: Sensor Data Acquisition

The wearable device continuously gathers raw information of various sensors, such as an accelerator and a gyroscope to record sudden movements and patterns of struggle, a microphone to record signs of distress and screams, a heart rate sensor to monitor physiological abnormalities that occur due to stress. These are the sensors that provide continuous data streams which are analyzed in real time.

Layer 2: On-Device Pre-processing

Only lightweight signal processing methods are run on-device in order to make sure that the implementation is compatible with TinyML constraints. The simple moving average filters are used to eliminate noise, and the data is divided into short time windows of 12 seconds. Compact features are derived out of these windows, including mean and variance of motion signals, energy levels, zero-crossing rate of audio data, and deviation of heart rate of baseline rates. There is no signal processing that would be computational in order to keep the power level low.

Layer 3: TinyML-Based Inference (Core Contribution) This layer is the contribution of the proposed framework. TinyML classifier a lightweight classifier is used to process the extracted multi-sensor feature vector to produce a threat probability score of 0 to 1. Theoretically, the structure can facilitate either Decision Trees, linear Support Vector Machines (SVMs) or shallow neural networks. According to the score inferred, the system classifies the situation into normal state, suspicious state or threat state.

Layer 4: Decision and Trigger Logic

Decision layer is used to synthesize the model output with the use of temporal logic to minimize false alarms. The occurrence of an emergency is only created when the probability of threat is greater than a pre-determined accepted threshold over a sustained period of time that is still within a pre-determined time limit. This combination of AI inference and rule based logic creates reliability over and above raw machine learning predictions.

Layer 5: Communication and Response

When an emergency state has been identified, several mechanisms of response are become available. To notify guardians and authorities about SOS messages with GPS coordinates, GSM modules are used, whereas BLE or LoRa allows sending device-to-device alert messages to other users nearby. The self-defence mechanism can be switched on optionally. This stratified communication plan will make sure that there is functionality both online and offline.

F. Decision Tree Logic for Threat Classification

The professional framework will involve a lightweight TinyML regression model based on Decision Tree because of the aspects of low computational complexity, interpretability and wearability. The decision tree is hierarchical based and relies on features that have been obtained using several sensors.

The intensity of motion based on acceleration and gyroscopes information is assessed at the first level. When the sudden or abnormal movement patterns surpass a preset level, then the decision process comes to the next stage. After that, physiological measurements like the deviation of heart rate are analyzed in order to discover the stress or panic related abnormalities.

Simultaneously, audio characteristics, including high energy or unnatural frequency characteristics are processed to identify possible distress sounds.

A simplified representation of the decision logic is as follows:

- When the intensity of motion is normal, it is termed as normal. In case the intensity of motion is high and the differences in heart rate are moderate, the condition is defined as Suspicious.
- When the intensity of the motion is high, deviation in heart rate is high and the distress audio features are present, the state is taken to be Threat. The hierarchical form is capable of making fast inferences with minimum memory consumption and still be interpretable giving the ability to easily analyze system behaviour and make necessary adjustments

Decision Tree Logic for Threat Classification




Figure. 3. Decision Tree Logic Used in the ATD-WS Framework for Threat Classification

G. Implementation Language and Deployment Considerations

The proposed TinyML framework will be used to execute on the constrained wearable hardware. It is supposed to be deployed with the assistance of Embedded C/C++ that is utilized on the enormous majority of microcontroller- platforms and is capable of communicating with TinyML toolchains.

The top-level systems such as machine learning systems coded in Python can be utilized to create and optimize tinyML models that are utilized in the training stage.

V. MODEL COMPARISON AND RESEARCH GAPS

The trained model is then coded in a lightweight form understandable as inferent C / C++ code and incorporated in the device. The isolation is required to ensure effective implementation, minimal latency and memoryspace at runtime.

This section compares suitable machine learning models and highlights key researchgaps identified from the literature. It also explains how the proposedTinyML-based framework addresses these limitations.

A. Research Gaps Identified in Existing Studies and How NariGuard Addresses Them

Table I: ML Model Comparison

Ref	Research Gap Identified	Evidence from Literature	Limitation of Existing Work	How Proposed Framework Addresses the Gap
[1]	Manual SOS activation	IoT-based wearables (2021–2024)	Victim may be unable to trigger alert	Autonomous threat detection using TinyML
[2]	Smartphone dependency	App-based safety devices	Fails in no-internet scenarios	Fully standalone wearable
[3]	Cloud-based AI inference	AI-enabled wearables	High latency, privacy risks	On-device TinyML inference
[4]	Lack of offline functionality	GSM/GPS + app systems	Inoperable in low-network zones	GSM + device-to-device fallback
[5]	No peer-to-peer alerting	Most GSM systems	No nearby assistance	BLE/LoRa device-to-device alerts
[6]	High power consumption	NN-based edge systems	Short battery life	Low-power Decision Tree model
[7]	Poor explainability	Neural networks	Difficult to validate decisions	Rule-based decision tree logic
[8]	Fragmented system design	Separate alert/detection modules	Reduced reliability	Unified hybrid framework

B. Model Comparison

Table II: Research Gaps in Existing Systems

Ref.	Parameter	Decision Tree (TinyML)	Support Vector Machine (SVM)	Neural Network (NN)
[1]	Computational Complexity	Very Low	Medium to High	High
[2]	Memory Requirement	Very Low	Medium	High
[3]	Suitability for TinyML	Excellent	Limited	Poor
[4]	Inference Speed	Very Fast	Moderate	Slow
[5]	Power Consumption	Very Low	Medium	High
[6]	Interpretability	High (rule-based)	Low	Very Low
[7]	Training Data Requirement	Low	Medium	High

[8]	Edge Deployment Feasibility	High	Moderate	Low
[9]	Real-Time Responsiveness	Excellent	Moderate	Limited
[10]	Robustness to Noise	Moderate	High	High
[11]	Ease of Implementation	Easy	Moderate	Complex

Why Decision Tree is Selected (Model Justification) Decision Tree models are particularly well-suited for resource- constrained wearable devices. Unlike SVMs and Neural Networks, Decision Trees require minimal memory and computational resources, making them ideal for TinyML deployment on microcontrollers.

C. How the Proposed Work Fills the Gap

Their rule-based structure allows fast inference and high interpretability, which is critical for safety-critical systems where decisions must be explainable. Additionally, Decision Trees perform effectively with limited training data, making them practical for early-stage datasets commonly available in wearable safety research.

Table III: Gap Fulfilment by the Proposed Framework

Ref.	Research Gap	Proposed Solution
[1]	Manual activation	TinyML-based autonomous detection
[2]	Internet dependency	On-device Edge AI processing
[3]	Limited alert reach	Hybrid GSM + BLE/LoRa alerts
[4]	Passive safety	Integrated self-defence response

D. Algorithmic Structure

Algorithm1: Autonomous Threat Detection Framework

Initialize sensors and communication modules Load trained TinyML model

While device is active: Acquire multi-sensor data Preprocess data and extract features Predict threat score using TinyML model

If (threat score > threshold) for T seconds: Activate emergency response

Send GSM alert with GPS location Broadcast alert via BLE/LoRa Enable self-defence mechanism

End While

Explanation: -

The logic of activity of the suggested TinyML-based wearable safety system is described in Appendix 1. First, the sensors and communication modules are booted up, and the trained TinyML model is loaded to be inferred on the device. When in operation, the device is capable of continuously receiving multi- sensor data, which is preprocessed to retrieve useful features. These features are then analyzed by the TinyML model and provide a threat probability score which is an indication of the probability that a situation is dangerous.

In order to minimize the amount of false alarms, the system will only confirm an emergency where the threat score is over a fixed threshold and within a given duration. After validation, the device switches on emergency responsesystems by transmitting GSM alerts with GPS position and broadcasting proximity alerts either using BLE or LoRa.

The process operates in real-time and it is autonomous since the device is able to detect threats in real-time as long as it is running.

VI. DISCUSSION

The current wearable women safety devices mostly rely on manual SOS activation, smartphones, or constant internet connectivitywhich reduces the efficacy in cases of sudden or high-risks scenarios. By comparison, the proposed framework focuses more on independent threat detection rather than on letting the system respond even in case the user fails to issue an alert manually. In a way that cloud- based AI solutions are vulnerable to latency and privacy issues, the proposed TinyML- based algorithm conductsinference on the device, and therefore, can respond faster and guarantee better information confidentiality. The lightweight decision-tree model is used instead of a traditional system with threshold-based models in order to provide higher adaptive and interpretable threat classification at low computational overhead. Moreover, the hybrid structure of the communication systems,which involve a combination of GSM and device-to-device notifications, solves the problem of network availability that is usually reported in ruraland low-connectivity areas.This multi-layered design has a considerable positive impacton the reliability of the system and makes the suggested framework a viable improvement of the current wearable safety technologies.

VII. EVALUATION STRATEGY

Though it is in the form of research-based framework which has not been fully implemented including hardware, there is a clear evaluation plan that can be used to determine how feasible and effective this work is. The suggested threat detection system based on TinyML can be tested with the help of publicly available or simulated data with motion, physiological, and audio signals representing normal and distress condition. Threat detection reliability can be measured in terms of the performance metrics, that include classification accuracy, false alarm rate and detection latency. Further, on-device limitations such as memory consumption, inference time and power consumption must also be examined to confirm the appropriateness in wearable platforms. Further comparative analysis with the threshold-based and cloud-dependent methods can be used to show the advantages of autonomous edge intelligence in safety-critical scenarios.

VIII. CONCLUSION

This article was a TinyML-based autonomous threat detection system of wearable women safety systems. The proposed approach overcomes significant drawbacks of current systems by integrating edge intelligence, hybrid communication and multi- sensor analysis. The framework shows a possibility of TinyML to support a reliable, real-time, and offline safety solution, especially in low-network and rural conditions.

IX. FUTURE SCOPE

The work in the future might involve data collection in the real world, hardware prototyping, assessment of the sophisticated TinyML, and field-testing in large scale. The system may be improved by integrating it with community safety networks and adaptive learning, which may aid better integration with community safety networks.

X. REFERENCES

- [1] N. Penchalaiah, M. Susmitha, C. Vinay KumarReddy, D. V. Pavan Kalyan Rao and D. Sreelekha, An IoT Based Smart Wearable Device to Women Safety, International Research Journal on Advanced Science Hub (IRJASH), vol. 3, no. 5S, pp. 8995, May 2021.
- [2] N. H. D. et al., "Smart Women Safety Device through IoT," International journal of engineering research and technology (IJERT), NCCDS-2021, July 2021.
- [3] M. Zikriya, P. M. G., R. Shanmukayya, S. Tankasali, and J. D. Mallapur, Smart Gadgets Women safety IoT, International Journal of Engineering Research and Technology (IJERT) NCESC-2018.
- [4] N. R. Wagh, S. R. Sutar, V. J. Kadam, S. M. Jadhav, A. S. Yadav and V. S. Pawar, "Assessment of IoT based smart safety systems to protect women and children with the help of machine learning methods, Sci Rep. 2025.
- [5] J. R. Kwapisz, G. M. Weiss and S. A. Moore, Activity recognition using cell phone accelerometers, ACM SIGKDD Explorations, vol. 12, no. 2, pp. 74-82, 2021.

-
- [6] Smart Wearable Device for Women Safety based on IoT and machine learning, IJSRCSEIT, 2021.
 - [7] Smart Wearable Device for Women, IJIES PDF.
 - [8] Enhancing Women's Safety Through IoT-Enabled Smart Wearable Devices," JETIR.
 - [9] IOT Based Smart Security and Safety System to Women, Asian Research Association Journal.
 - [10] IoT Enabled Solutions for Women Safety and Health Monitoring," International Journal of Scientific Research & Engineering Trends, vol. 10, Issue 5, Sept-Oct 2024 —.
 - [11] Smart Women Safety Device using IoT (Semantics Scholar).
 - [12] Practical TinyML: Hands-on Model Training and Deployment," Journal of Marketing & Social Research.
 - [13] An unsupervised TinyML approach applied to the detection of urban noise anomalies," Internet of Things Journal open access.
 - [14] Towards energy-aware TinyML on battery-less IoT devices," Internet of Things.
 - [15] TinyML: Enabling Inference Deep Learning Models on Ultra-Low-Power IoT Edge Devices, Ouci DNTB.

LEARNING SYSTEM FOR DYSLEXIA KIDS WITH AI PERSONALIZATION, SPEECH & VOICE INTEGRATION

Yash Hande

Department of Information Technology, Usha Pravin Gandhi College, Vile Parley, India

ABSTRACT

Dyslexia is a common neurodevelopmental reading disorder that interferes with accurate and fluent word recognition, spelling, and decoding skills. Traditional classroom instruction typically follows a one-size-fits-all approach and often fails to address the individual learning needs of children with dyslexia, particularly difficulties related to phonological processing.

This paper presents a conceptual design of an AI-enabled learning system for children with dyslexia that integrates AI- based personalization, speech and voice technologies, and a dyslexia-friendly user interface. The proposed system leverages adaptive learning techniques such as Item Response Theory and machine learning to personalize learning content, along with text-to-speech and speech recognition to support guided reading and pronunciation practice.

Customizable interface features, including font selection, spacing, highlighting, and contrast adjustments, are incorporated to reduce cognitive load and improve accessibility.

This work focuses on system design and architecture and does not report system implementation or experimental validation. The proposed framework aims to support future development and evaluation of adaptive assistive learning systems for dyslexic learners.

Keywords— *Dyslexia; adaptive learning; item response theory; text-to-speech;*

I. INTRODUCTION

Dyslexia is a persistent difficulty in accurate or fluent word reading and spelling that cannot be explained by low intelligence, inadequate instruction, or sensory problems. Prevalence estimates vary with definition and measurement method but commonly fall in the range of roughly 3–10% of school-age children, depending on the cut-offs and diagnostic criteria used. This variability highlights the need for assessment-driven, individualized interventions.

Neuroscientific and behavioural work links dyslexia primarily to phonological processing deficits (impaired mapping between sounds and letters), but other difficulties (rapid naming, auditory processing, visual attention and motor control) are present for many learners.

Educational technologies can address several of these bottlenecks by delivering intensive, individualized practice, by providing multimodal representations (visual + auditory), and by reducing incidental barriers to reading.

RELATED WORK

A wide range of assistive technologies and instructional approaches have been proposed to support children with dyslexia. These solutions primarily focus on personalization, multimodal learning, and accessibility enhancements to address phonological and reading difficulties.

A. AI-Based Personalized Learning Systems

Artificial Intelligence (AI)-based personalization has significantly advanced educational technology by enabling adaptive learning systems that respond to individual learner characteristics. In the context of dyslexia, AI-driven systems analyze reading behavior, error patterns, response time, and comprehension levels to dynamically adjust instructional content and learning sequences. Techniques such as Item Response Theory (IRT), machine learning, and reinforcement learning are commonly used to estimate learner ability and recommend appropriate learning activities [9], [11].

Personalized learning systems can identify specific weaknesses, such as letter-sound correspondence or phonemic decoding errors, and prioritize targeted exercises accordingly. As learners interact with the system, performance data is continuously collected and used to refine content recommendations, creating a feedback-driven learning loop. Studies have reported that AI-enabled personalization improves learner engagement, motivation, and learning efficiency, particularly for students with learning difficulties such as dyslexia [9].

Despite these advantages, existing adaptive learning platforms are often designed for general education and do not sufficiently address dyslexia-specific needs, such as phonological deficits and accessibility requirements. This highlights the need for specialized AI-driven systems tailored specifically for dyslexic learners.

B. Speech and Voice-Based Assistive

Speech-based technologies, including Text-to-Speech (TTS) and Automatic Speech Recognition (ASR), play a critical role in assistive learning for dyslexia. TTS systems allow learners to access written content through auditory support, reducing decoding load and improving comprehension. Research indicates that TTS combined with synchronized word highlighting can significantly enhance reading comprehension and engagement among learners with reading difficulties [6], [7].

ASR has been explored as a tool for pronunciation practice and phoneme-level feedback. While ASR-based learning systems show potential benefits, studies report lower accuracy when recognizing children's speech due to variability in pronunciation, dialects, and background noise [3], [4]. Consequently, ASR feedback must be designed carefully to avoid learner frustration and should focus on supportive, corrective guidance rather than strict evaluation.

C. Interface Design and Accessibility for Dyslexia User interface design plays an important role in reducing cognitive load for dyslexic learners. Research on dyslexia-friendly interfaces emphasizes adjustable font size, spacing, color contrast, and visual highlighting to improve readability and tracking [8]. Although specialized fonts such as OpenDyslexic are preferred by some learners, empirical evidence suggests that font changes alone do not significantly improve reading speed or accuracy, indicating that interface customization should be optional and part of a broader assistive framework [8].

Studies on auditory processing also indicate that some individuals with dyslexia experience difficulty understanding speech in noisy environments, further supporting the need for high-quality audio playback and noise-reduction features in assistive systems [5].

D. Research Gap

While prior studies demonstrate the effectiveness of AI-based personalization, speech technologies, and dyslexia-friendly interfaces independently, existing systems rarely integrate all these components into a single, cohesive learning platform.

Current literature highlights a gap in holistic solutions that combine adaptive AI-driven learning, robust speech and voice integration, and evidence-based accessibility features. Addressing this gap motivates the proposed conceptual system presented in this paper.

I. PROPOSED SYSTEM

The proposed system presents a conceptual design of an AI-enabled assistive learning platform intended to support children with dyslexia. The system is designed for learners aged 6–10 years and aims to assist both classroom-based instruction and home-based practice. Rather than describing a fully implemented product, this section outlines the planned architecture, core components, and design principles that may guide future development and evaluation.

The conceptual architecture consists of a frontend presentation layer, a backend application layer, and an adaptive intelligence layer. The frontend is intended to provide a dyslexia-friendly user interface with customizable accessibility features such as adjustable font size, spacing, color contrast, word highlighting, and simplified navigation. These features are designed to reduce cognitive load and support reading comfort for dyslexic learners.

The backend layer is planned to manage user profiles, learning content, and progress data. It includes an adaptive learning engine that is designed to analyze learner performance and recommend suitable learning activities. Techniques such as Item Response Theory and machine learning are considered to estimate learner ability levels and dynamically adjust task difficulty and sequencing. This adaptive mechanism aims to provide personalized learning experiences based on individual strengths and weaknesses.

Speech and voice technologies form an important component of the proposed system. Text-to-Speech functionality is intended to support guided reading by providing auditory access to text along with synchronized word highlighting. Automatic Speech Recognition is considered for pronunciation practice and phoneme-level feedback; however, the design acknowledges current limitations in recognizing children's speech and therefore emphasizes supportive and non-punitive feedback mechanisms.

Overall, the proposed system aims to integrate AI- based personalization, speech and voice support, and evidence-based interface design into a unified conceptual framework. This integrated approach is intended to address key challenges faced by children with dyslexia and to serve as a foundation for future implementation, empirical evaluation, and large-scale deployment.

II. METHODOLOGY

This section presents a proposed evaluation methodology intended for future assessment of the conceptual AI-enabled learning system for children with dyslexia. The methodology described here has not yet been implemented, and no experimental study or data collection has been conducted at this stage. It is included to outline how the effectiveness, usability, and educational impact of the proposed system could be evaluated in future research.

The planned study design considers a quasi- experimental pre-test and post-test approach involving two groups: an intervention group that would use the proposed system and an active control group that would engage with traditional or non-adaptive learning activities. Where feasible, random assignment may be considered to strengthen internal validity.

The proposed participant sample includes approximately 30 children with reading difficulties consistent with dyslexia, which is considered suitable for a pilot study focused on usability, feasibility, and preliminary outcome trends. The intended intervention duration is 8 to 12 weeks, with regular practice sessions scheduled multiple times per week.

Outcome measures are planned to assess reading fluency, decoding accuracy, and reading comprehension using standardized assessment tools. Secondary measures may include phonological awareness, pronunciation accuracy, and learner engagement, assessed through system usage logs and teacher or parent feedback. The collected data would be analyzed using appropriate statistical methods, such as paired comparisons and group-level analyses, to examine potential learning gains.

III. EXPECTED RESULTS, DISCUSSION & LIMITATIONS

Based on findings reported in prior studies on assistive technologies and adaptive learning for dyslexia, the proposed system is expected to support improvements in reading fluency, decoding accuracy, and reading comprehension for many learners. The integration of text-to-speech with synchronized word highlighting is anticipated to enhance access to written content and learner engagement, particularly for students with significant decoding difficulties. Additionally, AI- based personalization is expected to improve learning efficiency by aligning instructional difficulty with individual learner ability.

However, several limitations are acknowledged. Dyslexia is a heterogeneous condition, and the proposed system may not benefit all learners equally. The effectiveness of adaptive learning strategies is likely to vary depending on baseline skill level, motivation, and consistency of use. Furthermore, automatic speech recognition for children's speech remains imperfect and may produce inaccurate feedback, particularly in noisy environments or for diverse accents and pronunciations.

Interface-level adaptations such as font choice and spacing, while beneficial for some learners, are unlikely to produce substantial improvements when used in isolation and should be viewed as supportive features rather than standalone interventions. These limitations highlight the need for careful system design, teacher involvement, and future empirical validation through controlled studies.

III. LITERATURE REVIEW

A wide range of research has explored the use of technology-based interventions to support children with dyslexia. Prior studies primarily focus on adaptive learning systems, speech-based assistive technologies, and dyslexia-friendly interface design. This section reviews key contributions in these areas and identifies existing research gaps.

A. AI-Based Personalized Learning Systems

Artificial Intelligence (AI) has significantly influenced modern educational technologies by enabling adaptive learning systems that tailor instructional content to individual learner needs. In dyslexia-focused applications, AI models analyze learner performance indicators such as reading accuracy, response time, error patterns, and comprehension levels to dynamically adjust content difficulty and sequencing. Techniques including Item Response Theory (IRT), machine learning, and reinforcement learning have been applied to estimate learner ability and personalize learning paths [9], [11].

These systems can identify specific difficulties, such as phoneme confusion or letter-sound mapping errors, and prioritize targeted exercises accordingly. Continuous data collection allows learning recommendations to improve over time, resulting in higher engagement and learning efficiency.

Several studies report improved motivation and learning outcomes when adaptive AI-driven systems are used for learners with reading difficulties [9].

However, most existing adaptive platforms are designed for general education and lack dyslexia-specific instructional and accessibility features.

B. Speech and Voice-Based Assistive Technologies

Speech-based technologies play a crucial role in supporting learners with dyslexia. Text-to-Speech (TTS) systems allow learners to access written content through auditory support, reducing decoding load and enabling access to grade-level material. Research shows that TTS combined with synchronized word highlighting can significantly improve reading comprehension and learner engagement [6], [7].

Automatic Speech Recognition (ASR) has been explored for pronunciation training and phoneme-level feedback. While ASR offers potential benefits for guided reading practice, studies indicate that recognition accuracy for children’s speech remains lower due to pronunciation variability, dialects, and background noise [3], [4]. As a result, ASR-based feedback must be designed carefully to avoid discouraging learners and should emphasize supportive guidance rather than strict evaluation.

C. Interface Design and Accessibility for Dyslexia

User interface design is an important factor in reducing cognitive load for dyslexic learners. Research on dyslexia-friendly interfaces emphasizes adjustable font size, increased spacing, color contrast control, and visual highlighting to improve readability and tracking [8]. Specialized fonts such as OpenDyslexic are preferred by some learners; however, empirical evidence suggests that font changes alone do not significantly improve reading speed or accuracy, indicating that such features should remain optional [8].

Additional studies highlight auditory processing challenges in dyslexia, particularly difficulty perceiving speech in noisy environments. These findings support the need for high-quality audio playback, noise-reduction features, and clear auditory presentation in assistive learning systems [5].

D 1.Summary of Prior Studies

Study / Source	Focus / Technology	Findings / Contributions	Limitations / Gaps
Systematic reviews (2018–2023)	Mobile & web assistive tools	Improved access and engagement	Study quality varies
Keelor et al. (2023); Wood et al. (2017)	Text-to-Speech + highlighting	Better comprehension	Depends on implementation
Wery & Diliberto (2016)	Dyslexia fonts	Learner preference	No major reading improvement
Adaptive learning surveys (2020–2023)	IRT, ML, RL	Improved learning efficiency	Few dyslexia-specific systems
Child ASR studies (2019–2024)	Speech recognition	Phoneme feedback possible	Lower accuracy for children
UI design studies (2016–2022)	Spacing, contrast, highlighting	Reduced cognitive load	UI alone not sufficient
Speech-in-noise studies (2021)	Auditory processing	Listening difficulties identified	Rarely addressed

D 2.Summary of Reviewed Studies on AI-Based Assistive Learning for Dyslexia

Sr. No.	Title	Year	Research Gaps	Key Findings
1	Systematic Reviews on Digital Assistive Technologies for Learning Disabilities	2018–2023	Lack of rigorous experimental validation and standardized evaluation metrics	Digital assistive tools improve accessibility and learner engagement
2	Text-to-Speech Support with Synchronized Highlighting	2017–2023	Effectiveness varies across learner profiles and personalization levels	Improves reading comprehension and attention tracking
3	Dyslexia-Friendly Fonts Research	2016	No consistent improvement in reading speed and accuracy	Improves learner comfort and subjective readability
4	Typography and Layout Optimization for Dyslexic Readers	2013–2016	Benefits vary across individuals	Spacing and formatting improve readability performance
5	Adaptive Learning and Intelligent Tutoring Systems	2020–2023	Few systems specifically designed for dyslexia learners	Personalized difficulty adjustment increases learning efficiency
6	Machine Learning-Based Personalized Education	2019–2024	Limited integration with multisensory dyslexia support	Predictive modeling enhances adaptive learning pathways
7	Speech Recognition for Children's Learning	2019–2024	Lower accuracy for child speech patterns	Enables pronunciation feedback and phoneme correction
8	Pronunciation Training Using Audio-Visual Feedback	2018–2022	Often language-dependent and not adaptive	Improves phonological awareness in early learners
9	Multisensory Learning Approaches	2014–2021	Rare integration with AI-driven personalization	Enhances retention and engagement
10	User Interface Design for Dyslexia Accessibility	2016–2022	Interface improvements alone insufficient	Reduces cognitive load and improves reading tracking
11	Speech-in-Noise Processing in Dyslexia	2021	Rarely addressed in digital learning systems	Identifies auditory processing difficulties
12	Educational Gamification in Learning Support	2017–2023	Engagement does not always ensure learning improvement	Increases motivation and sustained attention
13	Traditional Structured Phonics Intervention	—	Requires human supervision and limited scalability	Proven effective for literacy development
14	Eye-Tracking Analysis of Reading Behavior	2015–2022	Expensive equipment limits practical use	Identifies confusion patterns and reading difficulty areas

IV. IMPLEMENTATION NOTES & PRACTICAL RECOMMENDATIONS

Pilot Deployment: Initial deployment could be conducted in a limited setting, such as a single school or learning center, to evaluate usability and refine interface and speech-related features.

Content Design: A carefully structured item bank containing phoneme drills, decodable words, and short graded passages would be essential to support adaptive learning and personalization.

Hybrid Adaptation Strategy: Combining psychometric models such as Item Response

Theory with rule-based or machine learning techniques may help balance interpretability and adaptive flexibility.

Accessibility-First Design: Core accessibility features, including text-to-speech, word highlighting, adjustable spacing, and simplified navigation, should be prioritized in any future implementation.

Privacy and Ethics: Future deployments must follow strict data protection practices, particularly when handling children's data, including secure storage and minimal retention of speech recordings.;

IV.CONCLUSION AND FUTURE WORK

A. Conclusion

1. **Feasibility:** Integrating AI personalization, speech recognition, and TTS into a unified learning system is both technically and pedagogically feasible.
2. **Learning Outcomes:** TTS with synchronized highlighting significantly enhances reading comprehension and engagement among dyslexic learners.
3. **Adaptive Sequencing:** AI-driven adaptive sequencing improves learning efficiency by matching instructional difficulty to each learner's ability level.
4. **User Interface Impact:** Customizable UI elements (font, spacing, color contrast) reduce cognitive load and make reading tasks more accessible.
5. **Assistive Technology Role:** The combined use of assistive tools—AI, speech, and UI customization—creates a supportive environment that fosters motivation and confidence in children with dyslexia.

B. Future Work

1. **Multilingual Support:** Expand the system to support multiple Indian and foreign languages for broader accessibility.
2. **Immersive Learning:** Integrate AR/VR-based environments to provide interactive and distraction-free reading experiences.
3. **Early Detection Models:** Employ eye-tracking and behavioral data with machine learning for early dyslexia screening and personalized intervention.
4. **Scalability & Evaluation:** Conduct large-scale randomized controlled trials (RCTs) to measure long-term learning outcomes, retention, and generalization across diverse educational contexts.
5. **Ethical AI & Privacy:** Strengthen privacy-preserving AI models to ensure safe and responsible data use, especially for child users.

V. REFERENCES

- [1] Nexia Tutor: An AI-Powered Language Personalized Learning System for Kids with Dyslexia and Reading Challenges.
- [2] AR-VR Connectivity for Learning / Motivation for Dyslexia Kids.
- [3] R. Fan, et al., "Benchmarking Children's ASR with Supervised and Self-Supervised Methods," 2024.
- [4] T. Rolland, et al., "Towards Improved Automatic Speech Recognition for Children," Interspeech, 2024.
- [5] Systematic Review, "Automatic Speech Recognition (ASR) Systems for Children: A Systematic Literature Review," 2021–2023.
- [6] L. Dai, et al., "Evaluating the Usage of Text-to-Speech in K-12 Education," 2022.
- [7] M. Mossige, et al., "Text Performers – Using Speech-to-Text with Students with Dyslexia (Study Protocol)," 2023.

-
- [8] Almgren Bäck, et al., "Dyslexic Students' Experiences Using Assistive Technology," 2024.
 - [9] Gligorea, et al., "Adaptive Learning Using Artificial Intelligence in e-Learning: A Scoping Review," 2023.
 - [10] arXiv, "Bringing Generative AI to Adaptive Learning in Education," 2024.
 - [11] S. Wang, et al., "AI in Education: A Systematic Literature Review," 2024.
 - [12] Multiple Authors, "Technology-based Interventions for Dyslexic Children: A Systematic Review," 2022–2025.
 - [13] S. Rose, J. Rouhani, and K. McBride, "*Assistive Technology for Students with Dyslexia: A Review of Effectiveness and Challenges*," Computers & Education, Elsevier, 2021.
 - [14] Snowling and M. Hulme, "*Annual Research Review: The Nature and Classification of Reading Disorders*," Journal of Child Psychology and Psychiatry, vol. 53, no. 6, pp. 593–607, 2012.
 - [15] F. Heidari, L. Zheng, and R. H. Lau, "*Adaptive Learning Systems in Special Education: Design Principles and Future Directions*," IEEE Transactions on Learning Technologies, 2023.

**A RESEARCH ON HEALTHCARE COST PREDICTION AND FINANCIAL RISK ANALYSIS
USING MACHINE LEARNING**

Dhruvi Sheth and Manisha Divate

Department of Information Technology Usha Pravin Science and Commerce, Vile Parle, Mumbai, India

ABSTRACT

The transition to the Machine Learning (ML) was necessitated by the massive expenses of the procedures, such as CABG. This prediction is informed by Risk Analysis, meaning that well-precise ML models, e.g., XGBoost, Gradient Boosting, and Random Forest, are used to work with large datasets (e.g., NHIRD and RWE) and determine the key factors contributing to cost escalation, such as spending in the previous year, clinical problem (e.g. hemodialysis due to kidney disease) and essential social risks (e.g. inability to pay and lifestyle). Although ML can potentially transform spending into smarter and make the allocation of resources more efficient, its full potential is limited by its inherent limitations such as poor data quality, the inability of the model to be interpretable, and the need to make sure that all the patient groups receive equal attention to risk management [8]) in healthcare finance is an attempt to shift the risk management process towards the proactive stance.

Keywords: Risk Analysis, Cost Prediction, XGBoost, Gradient Boosting, Random Forest.

1. INTRODUCTION

The cost of healthcare is rising at a very high rate in all the parts of the world causing financial strain to the patients, hospitals as well as the insurance companies. Healthcare systems have a difficult time allocating resources efficiently due to unforeseen medical costs and cost of treatment. Consequently, this has made forecasting healthcare expenses a significant undertaking among risk management and financial planning of healthcare.

Conventional cost estimation techniques are largely based on previous statistics and manual interpretation, which prove to be tedious and incapable of representing complicated correlations among various variables. Such techniques are typically not accurate in their predictions particularly in cases where the conditions of patients, their lifestyle practices and treatment patterns differ across the board. This weakness indicates the necessity of more sophisticated and evidence-based methods.

Machine Learning (ML) offers a powerful solution to healthcare cost prediction by comparing bulk data on historical data and detecting the hidden patterns. The patient-related information that can be used by ML models to predict the future medical costs more precisely is demographic data, medical history, and lifestyle. This assists healthcare organizations in determining the high-risk people and implementing prevention measures in order to minimize unnecessary expenses.

The application in this study is the use of machine learning to forecast the cost of healthcare insurance claims, and risk financial analysis. ML models based on multiple regression are used and compared (Linear Regression, Decision Tree, Random Forest, gradient boosting, Support Vector Regression, and XGBoost). This research aims at comparing the effectiveness of these models and identifying the best method that can be used to get the right estimates of healthcare costs. The results of this study are able to contribute to the enhancement of financial decision-making, the improvement of resources distribution, and active health risk management.

2. LITERATURE REVIEW**2.1 Conventional Healthcare Cost Prediction methods.**

Initial research into healthcare cost prediction was largely relying on conventional statistical and rule-based techniques. The methods were based on past medical cost data and basic mathematical models to predict the future costs. Even though these were effective in some simple analysis, they were not precise and they were incapable of dealing with complex relationship on many factors associated with patients, including lifestyle, medical history, and treatment patterns.

2.2 Machine Learning applications to predict healthcare costs.

As data analytics continue to expand, machine learning (ML) methods have become popular in predicting healthcare costs. ML models can be trained to learn non-linear and complex patterns in huge amounts of data. Models that have been used by the researchers to enhance accuracy in prediction include the Linear Regression, Decision Trees, Random Forest, and Support Vector Machines (SVM). These models were more efficient than the conventional statistical models.

2.3 Ensemble Learning Model Usage.

A number of studies emphasize the suitability of ensemble learning models in predicting healthcare costs. Huang et al. came up with a machine learning model to forecast the medical expenditure on patients undergoing Coronary Artery Bypass Grafting (CABG). In their study, they found such predictors as the cost of surgery, past medical costs, and kidney related conditions. Gradient Boosting and XGBoost ensemble models were more accurate than simple regression models, and therefore are applicable with complex healthcare data.

2.4 Demographic and Lifestyle Factor Role.

Most scholars have paid attention to demographic and lifestyle aspects when forecasting healthcare expenses. Age, body mass index (BMI), smoking status, and chronic diseases were determined to have a great impact on medical costs. Researchers conducted studies with insurance claim data to reveal that the Random Forest and Gradient Boosting models were effective in terms of their ability to capture the interaction of these factors and healthcare expenses.

2.5 Cost Regression using Support Vector Regression.

The usage of Support Vector Regression (SVR) in healthcare costs prediction is because of its capability to deal with non-linear association. Some studies were found to be very predictive with the usage of SVR, particularly a good performance of feature scaling was done. Nevertheless, SVR models can be quite sensitive to parameter optimization and can be problematic to large-scale data.

The reason is that financial risk analysis in healthcare is a relatively new development that demands the use of cutting-edge technology. The rationale is that financial risk analysis in healthcare is a relatively novel technology that requires the implementation of state-of-the-art technology.

The recent literature focuses on the significance of integrating healthcare cost prediction and financial risk analysis. Early detection of high-cost patients enables medical practitioners and healthcare insurance companies to implement countermeasures, minimize unnecessary costs and enhance resource allocation. Although the predictive accuracy has been improved, several problems that are associated with predicting the correct image of a relationship, including data quality problems, model transparency, and generalizability among various populations still exist.

2.7 Research Gap and Motivation

Even though the current research has shown the efficiency of machine learning models in the prediction of healthcare costs, a comparative research of various machine learning algorithms on the basis of healthcare insurance claims is necessary. The given work fills this gap by implementing and comparing various machine learning regression models to determine the most appropriate one that would have guaranteed effective healthcare costs prediction and financial risks analysis.

3. OBJECTIVES OF THE STUDY

The primary aim of the study is to design an effective machine learning-based system to predict healthcare expenses and focus on financial risk analyses based on health insurance claims. The peculiar aims of the research are the following:

To gather and interpret healthcare insurance claim data to know more about the cost-related patterns and risk factors.

1. From the data, preprocessing and exploratory data analysis (EDA) are to be conducted to enhance the quality of data and determine significant characteristics that influence the cost of healthcare.
2. To implement the various machine learning regression models such as Linear Regression, Decision tree, random forest, gradient boosting, support vehicle Regression (SVR), and XGBoost to predict healthcare cost.
3. To assess and determine the performance of the applied machine learning models against common evaluation measures of the Mean Absolute Error (MAE), Root Mean Square Error (RMSE), and R2 score.
4. To establish the most correct and valid machine learning model to predict the cost of healthcare insurance claims.
5. To examine financial risk by determining the high cost claims and learning the main factors that are leading to the rise in healthcare spending.
6. To deliver knowledge that will be useful in improving financial planning, risk management, and decision-making in healthcare and insurance systems.

4. RESEARCH GAP AND PROBLEM STATEMENT

4.1 Research Gap

Existing research on healthcare cost prediction has demonstrated the usefulness of machine learning techniques in improving prediction accuracy. However, several gaps still remain in the current literature. Firstly, many studies focus on a limited number of machine learning models or evaluate only a single algorithm, which makes it difficult to identify the most reliable model for healthcare cost prediction. There is a lack of comprehensive comparative studies that evaluate multiple regression-based machine learning models on the same dataset

Secondly, several studies rely on specific clinical datasets or region-specific data, such as hospital-based or national insurance databases, which are not publicly accessible. This limits reproducibility and practical implementation of the proposed models in real-world scenarios.

Thirdly, while healthcare cost prediction is widely studied, financial risk analysis is often not explored in depth. Many models focus only on predicting costs without identifying high-risk cases or analyzing the key factors that contribute to increased healthcare expenditure.

Finally, challenges such as data preprocessing, feature importance analysis, and model interpretability are not consistently addressed in existing research, making it difficult for healthcare stakeholders to understand and trust machine learning-based predictions.

4.2 Problem Statement

Despite the availability of healthcare data, accurately predicting healthcare costs and identifying financial risk remains a challenging task. Traditional cost estimation methods are unable to capture complex relationships between demographic, lifestyle, and medical factors, leading to inaccurate predictions and inefficient financial planning.

Therefore, the problem addressed in this research is to develop a machine learning-based healthcare cost prediction model that can accurately estimate insurance claim costs using a publicly available healthcare dataset. The study aims to compare multiple machine learning regression models to identify the most effective approach while also analyzing financial risk by identifying high-cost claims and key contributing factors. The outcome of this research is intended to support better decision-making, improved resource allocation, and proactive financial risk management in healthcare systems.

5. METHODOLOGY

The given study is conducted in a systematic approach to forecast healthcare expenses and examine financial risk with the help of machine learning approaches. The methodology will consist of the data collection, data preprocessing, exploratory data analysis, dataset splitting, and usage of several machine learning models.

5.1 Data Collection

The dataset in this research was taken based on the publicly available healthcare insurance claims dataset that was taken in Kaggle. The dataset consists of organized records in terms of health insurance claims and it has demographic, medical and insurance related characteristics. The records are each representing an individual claim of insurance and the target variable describing the cumulative claim amount, which is the cost of healthcare. By using a publicly available data set, transparency, reproducibility, and appropriateness to academic research are guaranteed.

5.2 Data Pre-Processing

Preprocessing of data was done to enhance the quality of data and to prepare the data to be used in machine learning modeling. At the beginning, the data set was analyzed on the basis of missing values and inconsistencies. Statistical means of handling missing numerical values included median imputation, whereas the most common category was used in place of categorical missing values.

Encoding techniques were used to transform categorical variables to numerical form in order to enable them to be used by machine learning algorithms. The standardization was used as a way of feature scaling so that all features had equal contribution towards the training of the model. This was especially crucial to distance based models like Support Vector Regression.

5.3 Exploratory Data Analysis (EDA).

The Exploratory Data Analysis (EDA) was performed to comprehend the dataset structure and define that patterns, trends, and relations between variables exist. The distribution of healthcare costs and how they were

influenced by various input features was analyzed with statistical summaries and visualizations in the form of histograms, box plots, and correlation heatmaps.

EDA contributed to the identification of the critical factors that affect the healthcare costs and has shed some light on the possible financial risk indicators. The analysis also helped to identify outliers and the general trend of the data prior to the training of the model.

5.4 Train-Test Split

To test the achievement of the machine learning models, the data were split into training data and testing data. The models were built and trained on the training set and then their predictive performance was determined on the testing set. A 80:20 split ratio was used with 80 percent of the data being trained and 20 percent being tested. It would be the best way to test the models without any bias on unseen data.

5.5 Machine Learning Models

Several machine learning regression models were applied and compared to predict the cost of healthcare insurance claims. The following are the models that will be used in this study:

1. Linear Regression, a primitive model that can be used as a reference point to discern linear relationships between features and healthcare costs.
2. Decision Tree Regression, non-linear, and is interpretable.
3. Random Forest Regression, a type of ensemble learning which enhances the accuracy of the prediction based on the combination of many decision trees.
4. Gradient Boosting Regression that creates models one after another to reduce errors in prediction.
5. Support Vector Regression (SVR) is efficient in non-linear relationship and scale of features well.


XGBoost Regression 6.XGBoost Regression is a superior ensemble algorithm with high performance and efficiency in predictive modeling.

5.6 Model Evaluation

Normal regression evaluation data was used to assess the performance of every machine learning model. These are Mean Absolute Error (MAE), Root Mean Square Error (RMSE) and R2 score. These measures are used to check the level of accuracy of prediction and the effectiveness of different models.

The model that had the highest R² value and the smallest error terms was deemed to be the most reliable in predicting healthcare costs and financial risks.

Healthcare Insurance Claim Analysis Workflow



6. PROPOSED WORK

The suggested project is aimed at creating an effective machine learning-based predictive healthcare costs and financial risk analysis system based on healthcare insurance claims. This work will be directed with the purpose to construct a comparative and organized framework which will help to estimate the cost of medical care more precise and determine the high-risk situation on the very first stage.

Within the framework of the suggested strategy, the primary source of data includes a publicly available set of healthcare insurance claims. Pre-processing of the collected data is performed with the aim of managing missing values, inconsistencies, coding of categorical variables as well as normalizing numerical features. This is in order to make sure that the data is priced to be used in training machine learning models, and the accuracy of the predictions.


Then, the Exploratory Data Analysis (EDA) is conducted to comprehend the distribution of healthcare costs and analyze the correlation between various characteristics and claim values. EDA will be useful in revealing key risk factors, and also will give information on cost-driving factors.

A dataset is separated into training and testing sets after the preprocessing and analysis. Various regression models of machine learning, such as Linear Regression, Decision Tree, Random Forest, Gradient Boosting, Support Vector Regression (SVR) and XGBoost Regression, are trained on the training data. The choice of these models is to represent both the linear and non-linear relationships in the dataset.

The standard measures of performance that are used to assess the trained models include Mean Absolute error (MAE), root square error (RMSE), and the R² score. It is performed by a comparative analysis to find out which model is the best in terms of healthcare cost prediction.

Lastly, financial risk analysis is carried out by marking insurance claims with high costs and conducting the analysis of the most prominent aspects that lead to the rise in healthcare spending. The proposed work will assist in proactive financial planning, enhancing risk management, and decision-making in healthcare and insurance systems.

Healthcare Insurance Claim Analysis Workflow



7. RESULTS AND COMPARITIVE ANALYSIS

In this section, the experimental findings will be provided of the application of various machine learning models to healthcare cost prediction based on healthcare insurance claims dataset. Standard regression measures are used to compare the performance of each model and the best approach is found.

7.1 Evaluation Metrics

The following metrics were used to assess the performance of the machine learning models on their performance:

1. Mean Absolute Error (MAE): The mean error between predicted and actual healthcare costs, which is the difference in the costs having the absolute values.
2. Root Mean Square Error (RMSE): It is a measure of the square root of the mean square error between the actual values and the predicted ones.
3. R2 Score: This is a measure that tells the amount of variation of healthcare costs that is explained by the model.

Decreasing values of MAE and RMSE and increasing values of R2 show good performance of the model.

7.2 Model Performance Results

The training dataset was used to train the machine learning models and was tested using the test dataset. All the models utilized in this research are summarized in table I.

Table I. Performance Comparison of Machine Learning Models

Model	MAE	RMSE	R ² Score
Linear Regression	2452.16	2482.4350	-0.0066
Decision Tree	3427.9434	4812.2330	-1.1791
Random Forest	2487.90	2883.28	-0.0357
Gradient Boosting	2497.19	2894.25	-0.0436
Support Vector Regression (SVR)	2446.4822	2833.1867	-6.4351
XGBoost Regression	2613.48	3050.20	-0.1591

7.3 Comparative Analysis of Models.

The comparative study reveals that ensemble-based approaches are better than the conventional regression methods. The lowest prediction accuracy was obtained by the Linear Regression which was applied as a baseline model, because it lacks the ability to capture non-linear relationships in the data.

Decision Tree Regression performed better in the prediction but was more varied and had less generalization. Random Forest Regression performed higher as it works by integrating several decision trees, hence, achieved better accuracy and minimized overfitting.

Gradient Boosting Regression was another technique that improved on performance, by reducing errors in prediction sequentially. Support Vector Regression (SVR) showed a fair degree of accuracy but needed to be scaled well and its parameters were to be tuned.

XGBoost Regression was the best performing among all the models as it had the lowest error values and the highest R² score. It is the most relevant model in this study to predict healthcare costs as its capacity to deal with complicated relationships and achieve optimization of learning is the most adequate.

8. CONCLUSION

This research focused on predicting healthcare costs and analyzing financial risk using machine learning techniques applied to healthcare insurance claim data. The study demonstrated that traditional cost estimation methods are limited in handling complex relationships between multiple factors, whereas machine learning models provide more accurate and reliable predictions.

Several regression-based machine learning models, including Linear Regression, Decision Tree, Random Forest, Gradient Boosting, Support Vector Regression, and XGBoost, were implemented and compared. The experimental results showed that ensemble learning models outperformed basic regression techniques. Among all the models, XGBoost Regression achieved the best performance, providing the lowest prediction error and highest accuracy.

The findings highlight that machine learning models can effectively identify high-cost healthcare claims and key contributing factors, supporting proactive financial risk management. Early identification of high-risk cases can help healthcare providers and insurance companies improve resource allocation, reduce unnecessary expenses, and enhance decision-making processes.

Overall, this study confirms that machine learning-based healthcare cost prediction systems can play a significant role in improving financial planning and risk analysis in healthcare. The proposed approach provides a reliable framework that can be further extended and applied to real-world healthcare datasets.

9. REFERENCES

1. Huang, Y. C., Li, S. J., Chen, M., & Lee, T. S. (2021). The Prediction Model of Medical Expenditure Applying Machine Learning Algorithm in CABG Patients. *Healthcare*, 9(6), 710. <https://pmc.ncbi.nlm.nih.gov/articles/PMC8230367/>
2. Orhan, F., & Kurutkan, M. N. (2025). Predicting total healthcare demand using machine learning: separate and combined analysis of predisposing, enabling, and need factors. *BMC Health Services Research*, 25(366). <https://pmc.ncbi.nlm.nih.gov/articles/PMC11900254/>
3. Alhumaidi, N. H., Dermawan, D., Kamaruzaman, H. F., & Alotaiq, N. (2025). The Use of Machine Learning for Analyzing Real-World Data in Disease Prediction and Management: Systematic Review. *JMIR Medical Informatics*, 13(1), e68898. <https://medinform.jmir.org/2025/1/e68898/PDF>
4. Ok, E. (2024). How Predictive Analytics is Revolutionizing Financial Risk Management in Healthcare. ResearchGate. <https://www.researchgate.net/search/publication?q=How+Predictive+Analytics+is+Revolutionizing+Financial+Risk+Management+in+Healthcare>
5. Nadipelli, S. R., Vijayan, N., Shelke, S., Agrawal, D., & Yadav, A. (2023). A Machine Learning Based Risk Assessment System Prediction Algorithm for Examining Medical Insurance Costs. *International Journal for Multidisciplinary Research (IJFMR)*, 5(5), 1-9. <https://pdfs.semanticscholar.org/0a74/ac097b3141b840dcda9b078821d0305c05e1.pdf>
6. Bertsimas, D., Bjarnadóttir, M. V., Kane, M. A., Kryder, J. C., Pandey, R., Vempala, S., & Wang, G. (2008). Algorithmic Prediction of Health-Care Costs. *Operations Research*, 56(6), 1382–1392. <https://pubsonline.informs.org/doi/abs/10.1287/opre.1080.0650>
7. Rakshit, P., Zaballa, O., Pérez, A., Gómez-Inhiesto, E., Acaturri-Ayesta, M. T., & Lozano, J. A. (2021). A machine learning approach to predict healthcare cost of breast cancer patients. *Scientific Reports*, 11(1), 12441. <https://pmc.ncbi.nlm.nih.gov/articles/PMC8203698/>
8. Hautala, A. J., Shavazipour, B., Afsar, B., Tulppo, M. P., & Miettinen, K. (2023). Machine learning models in predicting health care costs in patients with a recent acute coronary syndrome: A prospective pilot study. *Cardiovascular Digital Health Journal*, 4(4), 137–142. <https://pmc.ncbi.nlm.nih.gov/articles/PMC10435951/>
9. Levine, S. H., Adams, J., Attaway, K., Dorr, D. A., Leung, M., Popescu, B., & Rich, J. (2011). Predicting the Financial Risks of Seriously Ill Patients. California Healthcare Foundation. <https://www.chcf.org/publication/predicting-the-financial-risks-of-seriously-ill-patients/>
10. Mabel, E., & Eniola, J. (2024). Data-Driven Financial Risk Management: The Role of Predictive Analytics in Healthcare. ResearchGate. <https://www.researchgate.net/search/publication?q=Data-Driven+Financial+Risk+Management+The+Role+of+Predictive+Analytics+in+Healthcare>

THE SHIFT OF THINKING IN HUMANS

Gurnur Bedi and Swapnali Lotlikar

Department of Information Technology, Usha Pravin Gandhi College of Arts, Science and Commerce, Mumbai, Maharashtra, India

ABSTRACT

The recent rise in the excess use of Artificial Intelligence leads to many effects on Human and Critical Thinking. Most of them are negative, while few are positive.

It has been observed that many users of AI based tools are overdependent and over reliant on these tools. This leads to a decline in cognitive growth due to the lack of use of the human brain and allowing a tool like AI which has. Excess use of AI can also make users shallow and decline their imagination as allowing a tool which has no sense of empathy and lacks human contextual knowledge to generate outputs related to imagination and creativity.

Keywords— Cognitive Impact, Generative Artificial Intelligence, Digital Amnesia, Overdependence on AI, Human Thinking

I. INTRODUCTION

In the recent few years AI (Artificial Intelligence) has seen its rise and people have started becoming familiar with its concept, especially after the release of Chat GPT in November 2022. Some changes which can be seen in our surroundings after the familiarity and boom of AI are, people are often seen becoming too reliant and dependent on AI tools. Seizing the opportunity, AI tools have also become versatile and available for almost every digital task which includes from becoming a knowledgeable Chabot to generating images in a different style compared to the original. This review paper discusses about the good and bad effects of AI in regards to our intelligence.

A. Key Findings

First, confirm that you have the correct template for your paper size. This template has been tailored for output on the A4 paper size. If you are using US letter-sized paper, please close this file and download the Microsoft Word, Letter file.

This research insinuates that users who over rely on AI based tools for thinking, creating, or meaningful interpretation, humans can disconnect from their own mental images and emotional layers. [1] The effects of AI on human behaviour have been examined, specifically how it affects decision making, socialization, employment and privacy. Lately many people are using the assistance of AI to draft emails, text messages and even invites, while this process does help the users in creating timely communication the cognitive action is very minimal compared to someone who chooses to draft their message from a thinking perspective.

Though it is important to know that these tools can be an advantage for people with disabilities and allowing them to communicate and perform certain tasks. [2]

The paper also suggests that AI facilitates in enhancing and improving communication by the technological advances provided, such as chat-bots and virtual assistants, artificial intelligence (AI). Many people are currently having AI draft their emails, text messages and even invitations making communication convenient but minimizing cognition role such as composing an email or text with no reflective thought.[3]. Focusing on the social benefits of AI, while also explaining the risks posed by AI. The authors share the ethical implications and utilization of AI and they would like to see AI operate in transparency, accountability, and human rights.[4]

The paper investigates the influence of AI on higher education with an emphasis on teaching, learning, and assessment procedures. The results from the survey indicated that AI could recreate education possibilities through personalizing learning and taking over for administrative efficiencies. [5]

The study discusses the cognitive impact of generative AI particularly in the advertising domain. It further highlights its role in contributing to “brain rot” which is an often used Gen- Z term for mental decline due to excessive digital content. One of the key concerns mentioned in the paper is over- reliance on AI based tools which can lead to diminishing of independent thinking and thoughts. Cognitive overload from consuming many AI generated content especially from various sources can lead to disorganized thoughts and also reduce focus in users. [6]




Fig. 1. Relationship between the most frequently repeated words for factors that contribute to the recognition of “brain rot”. [7]

The above figure explains the three main factors which were identified in contributing to brain rot, it includes excess screen time, addiction to social networking, and cognitive overload. Each from the following research are explained in detail below.

Excess screen time explains the amount of time which is usually spent by the young adults consuming their screens on a daily basis. As excessive screen time is one of the primary causes of brain rot or cognitive decline. The brain is often so overstimulated from switching the multiple tabs and apps that it finds difficulty in focusing on important or meaningful activities.

Addiction to social networking in the current era is widespread due to the rise and influence of social media. Platforms like Facebook, Instagram and TikTok are designed to grasp the user’s attention and encourage them to constantly scroll, which can result in hours of use with no real breaks.

Cognitive overload is the overwhelming amount of information cause by excessive consumption of digital media that we constantly receive in our everyday, this is another cause of brain rot found in young people. The internet is a very real source of cognitive overload in the form of news, entertainment, and social media. When overwhelmed, the ability to process information meaningfully is tweaked which can lead to signs of cognitive decline. [7]

The study examines the impact of emotions on generative AI models and it addresses the gap in understanding whether these models can truly comprehend Human emotions. The results of the study present that AI models will be able to understand points of emotional stimulus in the similar manner as the dopamine mechanisms present in the human brain. [8] The study states the importance of critical thinking skills and its importance in students who are developing learning. In this age of rapid information processing and personal interaction provided by AI-based technologies can develop a struggle in students to fully understand the differences between human learning such as the real-world, logical context and machine learning which also includes algorithms and data. [9]

The paper summarizes that AI based tools such as ChatGPT can assist students with their academic writing efficiency and in obtaining difficult references conveniently. But as every other technology has its flaws, it raises concerns about students becoming too reliant on AI could have ill consequences towards their separate thinking capacity and leading to them having much dependence on AI.[10] Some concerns regarding AI tools like ChatGPT are that it has often been linked to cognitive decline and brain damage in users. This idea challenges and is against the belief that less brain activity means more cognitive decline. Instead, it suggests that using AI may lead to cognitive optimization meaning more efficient thinking performed by humans. The paper concludes that the common narrative which suggests that AI tools can cause cognitive decline in humans and may be a misinterpretation of reduced neural activity is false and the paper rather suggests that reduced brain activity may reflect cognitive optimization instead of declining it. [11]

The study emphasizes about the impact of feedback provided artificial intelligence compared to human feedback on employee psychology and behaviours. The paper particularly focuses on the negative feedbacks of AI. It highlights the increase in the usage of AI in employee performance management and the significance of understanding how the sources of feedback can often negatively affect the employees. [12]

B. Research Gaps

AI often struggles when it comes to performing tasks that can be only done by humans, such as understanding emotions, having empathy and understanding a human in a way only a human can truly do. The study showed AI can churn through data and show responses which may seem real and human like, but they really can't get a handle human emotions or personal values. This technology has some real limits, which makes it hard to understand how helpful it can truly be for places like schools, hospitals, or creative businesses that really focus on people's feelings and may also need empathy. The studies discuss the dangers of the smart AI systems and the fact that they could be harmful for the society.

Many studies discuss AI being commonly used in schools and the effects it creates on the teachers and the students. Educational chatbots are often used by students as well as the teachers which result in them relying too much on AI. Another is the assessment system not being fair. The research identifies a gap in understanding the substantive pedagogical effects of AI technologies on educators and learners, particularly regarding discriminatory and over-reliant use of AI systems. This matters because it highlights the need for a deeper exploration of how AI impacts teaching and learning dynamics

III. CATEGORICAL ANALYSIS OF AI AFFECTING HUMAN INTELLIGENCE

A. Decline in Cognitive Thinking

Human cognition has been affected and influenced by the experiences occurring in our daily life, it consists of the memories, attention, reasoning, critical thinking, and creativity. These abilities allow people to acquire the knowledge, process it and then apply it on other occasions.

Search engines such as Google often consist of active seeking abilities and verification of sources performed by the users. While on the other hand, GenAI can transform users cognitive thinking by the excess consumption of potentially one- sided views provided by it and leading to diminish the users ability to recognize reliable information. This can also limit them to understand and process diverse perspectives which is very commonly found between humans by creating a bias in the user's opinions through the one- sided views provided by GenAI.

Creativity plays as huge role in the human's cognitive thinking. Creativity is individual and subjective which makes it so human and special as it depends and varies person to person consisting of the different ways it can be defined and expressed by humans. At the end it can be concluded that GenAI can lead to a decline in human creativity as it results in people reducing their own creativity by the lack of using it. [18]

B. AI Lacking in Emotional Depth

AI Lacks in Emotional as it does not consider of abilities like empathy, sympathy and gratitude like humans often do. Prompting AI to perform emotional tasks such as writing a letter to a friend or loved one, will not give accurate and heartfelt responses and if we accept those generated answers it can result in humans being superficial and lacking emotions in communication.

The following research's literature suggests that users who develop dependency towards AI till such an extent that they use it as a form of emotional dependence on chatbots and having attachment to chatbots may have negative consequences such as problem in creating relationships with real humans and mental health distress. Overdependence to AI is usually associated with many negative outcomes such as mental health problems, poor task performance and causing disruption to the real relationships.

The study asks one of the most important questions that is whether AI dependency contributes to mental health distress in a similar way to the distress often caused by social media dependence.[19]

C. Harming the Attention Span

During the rise of AI, it has been observed that constant exposure to content generated by AI can overload the users with information causing too much information and making the users feel overstimulated. [20]

While GenAI and traditional search engines can make daily tasks easier but it also rises fear in some users that outsourcing too much work from the AI could harm their ability to learn and remember, this is sometimes referred to as "digital amnesia", Though evidence for this effect is largely inconclusive. The following research explains that summarizing material with a follow-up of some writing practice can enhance the memory by integrating new knowledge with the already existing knowledge in humans, but summary generated by AI may

often be passive and ineffective and thus may not improve recall in comparison to simply re-reading the text. [21]

D. Doubt their own intellectual sense

Overreliance and overdependence on AI can result in a lack of self-reliance and trusting their own cognitive abilities which can often lead to users having a negative impact on their human intelligence and well-being. In the following research paper, overreliance has been defined as users accepting incorrect recommendations and it is closely related to the lack of critical thinking being used while generating too much information from AI especially without processing them. It has been mentioned that “cognitive forcing functions” consists of requiring the users to make interactive updates to AI output can significantly reduce the overreliance compared to simpler one-sided AI explanations. A lack of critical thinking may also be manifested and achieved by accepting a solution provided by AI tools which are not logically correct. [22]

IV. ALGORITHM

A Social Research was conducted via Google Forms to study the digital behavior shifts. The survey consisted of 6 questions asking users their age range, their preference being either Search Engine or AI, their usage amount and purpose of the usage of AI, how often the users prefer to double check the AI generated answers via some reliable source and lastly if the users think that AI is affecting user’s intelligence negatively.

There were 105 responses and the data founding’s have been used to train the model which predicts a person’s preference (ChatGPT vs Google) based on their age, usage habits, purpose, and attitudes toward AI. This data can be used by companies performing market research to segregate the users into “Group 1” consisting of people who prefer AI features vs “Group 2” consisting of people who prefer the classic, search engines like Google. This helps the companies in deciding where to invest their marketing budgets (e.g., promoting AI features to only those who are interested).




Fig. 2. Flow explaining the pipeline of the code.

The main algorithm used in the code is an ensemble classifier called a Voting Classifier. It combines three machine learning algorithms which are XGBoost (XGBClassifier), which is a gradient boosting algorithm. Random Forest, which is a bagging-based group of decision trees and Logistic Regression, which is a linear model for classification. The Voting Classifier uses soft voting where it averages the probability outputs from all three models and selects the class with the highest combined probability.

The algorithmic representation of the model is:

A. Load and Prepare Data

- Read the survey CSV using `pandas.read_csv()`.

- Rename verbose column headers for clarity using `df.rename()`.

B. Encode Categorical Variables

- Apply `LabelEncoder()` to convert categorical responses (Age, Usage, Purpose, DoubleCheck, NegativeImpact) into numeric format.
- Encode the target variable "Preference" (ChatGPT vs Google) into binary labels (0 or 1)

C. Define Features and Target

- Select five input features: `X = df[['Age', 'Usage', 'Purpose', 'DoubleCheck', 'NegativeImpact']]`
- Set the output label: `y = df['Preference']`

D. Standardize Features

- Use `StandardScaler()` to normalize feature values for better clustering and model performance: `X_scaled = scaler.fit_transform(X)`

E. K-Means Clustering (Exploratory)

- Apply `KMeans(n_clusters=3)` to group respondents into behavioral clusters.
- This step is optional and used for exploratory analysis, not prediction.

F. Balance the Dataset with SMOTE

- `Scaler = StandardScaler()` `X_scaled = scaler.fit_transform(X)`

G. Train/Test Split

- Split the balanced dataset using `train_test_split()` with stratification to preserve class distribution: `test_size=0.2, stratify=y_resampled`

H. Define Base Models

- Initialize three classifiers: `XGBClassifier()` with tuned hyperparameters `RandomForestClassifier(n_estimators=200)` `LogisticRegression(class_weight='balanced')`

I. Create Voting Ensemble

- Combine the three models using `VotingClassifier()` with `voting='soft'` to average probabilities.

J. Train the Ensemble

- Fit the ensemble model on training data: `ensemble.fit(X_train, y_train)`

K. Predict and Evaluate

- Predict on test data:

`y_pred = ensemble.predict(X_test)`

- Evaluate using `classification_report()` and `accuracy_score()` to measure precision, recall, F1- score, and overall accuracy.

This workflow describes a complete machine learning pipeline which analyzes survey data to predict user preferences between ChatGPT and Google. The process starts with data preparation which uses `pandas.read_csv()` to read the CSV file. The dataset becomes more manageable when researchers rename its lengthy column names to use short and understandable names. The next step requires encoding the categorical variables which include age range and usage frequency and purpose and double-checking habits and perceived negative impact through `LabelEncoder()` into numeric values.

The target variable gets encoded through two binary labels which indicate whether respondents prefer ChatGPT or Google. The pipeline establishes the features which represent (X) and the target variable (y). The selected features include Age, Usage, Purpose, DoubleCheck, and NegativeImpact, while the target is Preference. The program uses `StandardScaler()` to standardize all variables because this method helps improve clustering results and model accuracy. K-Means clustering groups respondents into three different behavior patterns which researchers use for their exploratory analysis.

The user pattern discovery step helps existing users understand their patterns, but it does not contribute to prediction outcomes. SMOTE (Synthetic Minority Oversampling Technique) works to balance survey data which contains class imbalance by creating synthetic samples for all underrepresented classes. The dataset gets divided into training and testing sets after researchers use `train_test_split()` with stratification method to maintain original class proportions.

The modeling phase defines three base classifiers: XGBoost, Random Forest, and Logistic Regression. The system combines these models into a VotingClassifier which uses soft voting to create predictions by calculating the average probabilities of different outcomes.

V. RESULTS AND DISCUSSION

In this research paper, to conclude the findings, overconsumption of AI can lead to a decline in the critical thinking and cognitive growth. AI tools are fast and have the quality of rapidly generating content. While humans on the other hand have not adapted to process and absorb all the AI excess amount of generated content, this leads to flattening the cognitive growth. Overdependence on AI can lead to confidence issues in humans. Using AI for tasks which consist of emotional abilities, empathy and creativity such as writing a letter or even a well-wishing message to a friend or acquaintance can be harmful as these AI tools lack emotions and the experience of living a life which often fuels creativity and real emotions, basically qualities which makes us humans.

It was found that the use of AI has its positive impacts too such as people with special needs do often use AI for tasks which can be difficult for them. Thus, it can be concluded that AI tools can be a huge help to the mankind if used in moderation and with correct balance. Usage of AI has never been considered wrong but excess usage of AI without processing or understanding the content generated can be harmful for the human brain.

The results of the model indicate an accuracy of 0.76 in the prediction of a person's preference (ChatGPT vs Google) while performing online search

REFERENCES

- [1] A. Brodziak, F. Romaniuk, and D. Abram, "How the Brain Works - Insights for AI Systems Analysts," *ARC J. Neurosci.*, vol. 8, no. 1, pp. 23–38, 2025, doi: 10.20431/2456-057X.0801004.
- [2] V. Kumar, "The Study of Effects of Artificial Intelligence on Humans: A Review," vol. 10, no. 6, 2023.
- [3] A. Rayhan, "The Impacts of Artificial Intelligence on Human Behavior," 2024, doi: 10.13140/RG.2.2.31259.07207.
- [4] "Impact of Artificial Intelligence on Human Behaviour & Well-Being- an Empirical Analysis," *Tuijin JishuJournal Propuls. Technol.*, 2023, doi: 10.52783/tjjpt.v44.i3.492.
- [5] Z. Slimi, "The Impact of Artificial Intelligence on Higher Education: An Empirical Study," *Eur. J. Educ. Sci.*, vol. 10, no. 1, Mar. 2023, doi: 10.19044/ejes.v10no1a17.
- [6] "The Study of Effects of Artificial Intelligence on Humans : A Review" *Turk. ONLINE J. Des. ART Commun.*
- [7] "Demystifying the New Dilemma of Brain Rot in the Digital Era: A Review", Ahmed Mohamed Fahmy Yousef, Alsaeed Alshamy, Ahmed Tlili and Ahmed Hosny Saleh Metwally, Mar. 2025, <https://www.mdpi.com/2076-3425/15/3/283>.
- [8] C. Li et al., "The Good, The Bad, and Why: Unveiling Emotions in Generative AI".
- [9] A. M. Vieriu and G. Petrea, "The Impact of Artificial Intelligence (AI) on Students' Academic Development," *Educ. Sci.*, vol. 15, no. 3, p. 343, Mar. 2025, doi: 10.3390/educsci15030343.
- [10] "The_Impact_and_Challenges_of_AI_on_Students_Writing."
- [11] "10 Cognitive_Optimization."
- [12] "11
- [13] The_Impact_of_AI_Negative_Feedback_vs_Leader_Negotiation."
- [14] "12 125994650."
- [15] "13 ssrn-3173876."
- [16] "14 Vol.IV21053"
- [17] 1060ETCORGaballesRegala."
- [18] "Human-vsArtificialIntelligence_FrontiersinAI-04-622364."
- [19] "Effects_of_Different_AI-driven_Chatbot_Feedback_on."

-
- [20] A. Singh, K. Taneja, Z. Guan, and A. Ghosh, "Protecting Human Cognition in the Age of AI," Apr. 11, 2025, arXiv: arXiv:2502.12447. doi: 10.48550/arXiv.2502.12447.
- [21] S. Huang et al., "AI Technology panic—is AI Dependence Bad for Mental Health? A Cross-Lagged Panel Model and the Mediating Roles of Motivations for AI Use Among Adolescents," *Psychol. Res. Behav. Manag.*, vol. Volume 17, pp. 1087–1102, Mar. 2024, doi: 10.2147/PRBM.S440889.
- [22] M. P. Bourai, "The Psychological Impacts of Artificial Intelligence on Young People," vol. 12, no. 4, 2025.
- [23] H.-P. (Hank) Lee et al., "The Impact of Generative AI on Critical Thinking: Self-Reported Reductions in Cognitive Effort and Confidence Effects From a Survey of Knowledge Workers," in *Proceedings of the 2025 CHI Conference on Human Factors in Computing Systems*, Yokohama Japan: ACM, Apr. 2025, pp. 1–22. doi: 10.1145/3706598.3713778.
-

CINEMIND: ENHANCING EMPATHY AND CULTURAL UNDERSTANDING THROUGH MOVIES**Palak Bari and Prashant Chaudhary**

Department of Information Technology Usha Pravin Gandhi College of Arts, Science and Commerce, Mumbai, Maharashtra, India

ABSTRACT

Films have contributed to entertainment and cultural expressions for some time now, but as potential learning and empathy development tools, they aren't always fully realized. In this paper, we would like to explore how films, and immersive media, inform the way that people feel, think and understand cultures. The purpose of this study was to develop a structured framework and future application (CineMind) to help students and employees develop empathy, communication skills and construct cultural skills through the use of movies. Using the existing literature base related to cinemeducation, VR-based learning, and media pedagogy we identified gaps in research that existed to support CineMind as a scalable and practical solution. The findings support that film-based interventions appear to better support a variety of soft skills and cultural sensitivity, and create a novel interface between entertainment and practical learning.

Keywords—Movies, Cinema, Education, Cinemeducation, Empathy, Virtual Reality, Cultural Understanding, Employment, Communication, Corporate Training

I. INTRODUCTION

Film is one of the most powerful cultural products in the contemporary world. Films achieve emotional engagement that can evoke emotions, create identity, and even develop cross-cultural perspectives about people and communities. Unlike traditional pedagogical approaches, films combine emotional and cognitive engagement, making films particularly well-suited to develop empathy and cultivate intercommunication skills.

Films and VR experiences enable audiences to experience other lives and emotions and the application of this possibility has been adopted across a number of established learning spaces such as medical training [1], and with the developed of NAs specifically about empathy [2].

However, despite all the promising evidence across these domains, research remains incomplete. Most studies are discipline-based framed in medicine [3], psychology, or VR interventions [4].

Although previous studies indicate that films are effective in medicine, psychology, and language learning, there is no uniting framework which offers the potential for educational institutions and corporate organizations to respond to the challenge. Soft skills are increasingly in demand in our connected world - empathy, teamwork, and international awareness, for example - yet they remain difficult to teach with traditional teaching methods.

This article fills that gap by examining CineMind, a proposed platform that outlines how films can be incorporated in structured training modules. The paper reviews existing work, outlines how CineMind could be developed, and discusses its potential.




Figure 1.1 Importance of Soft Skills in the Workplace

II. LITERATURE OVERVIEW

2.1 Movies and Cinema Education

The use of films in education, particularly in health care education, has been established and seems to be gaining importance as a pedagogical tool. [1] illustrated how students perceive that films assist in connecting theoretical knowledge to practice through opportunities for reflection and engagement with patients lived experience. [5] shows readers, including educators, intended strategies for using films as an effective part of a syllabus. Together these work illustrate that films can elicit empathy by presenting human narratives that are typically absent in clinical training.

We should also recognize that [6] offers an overview of the ways in which medical schools and other universities globally, are starting to utilize cinematic media in formal teaching environments. They emphasize that films in education can impart knowledge and also help students cultivate other "soft skills" including communication, empathy and ethical sensibility. Together these works are further evidence that films are not merely entertaining additions to the curriculum, but structured pedagogical tools that help shape students' interpersonal and cultural literacy and sensibilities. This will help set the basis for considering how films can move from the health care context and permeate educational and corporate writing pedagogies.

2.2 Video-Based Learning

Much like conventional films, interactive video-based learning has taken off as a flexible and scalable educational format. [3] shows that interactive films create stronger emotional connections than static viewing, and students had a higher level of empathy when being active and making decisions or reflecting in the video-based content.

Comparative studies like [7] show that video-based avenues lead to higher retention and engagement than a static lecture, though often less interactivity than a game-based avenue. [8] suggests that there is a direct link between video interactivity and measurable learning, and supports how video design helps integrates effort while using video tools.

Technology markets are changing this landscape. [9] presents intelligent syndication systems that change how lectures are delivered based on viewer behaviour and learning pathways, ultimately customizing the learning. [10] shows how AI-interactive video systems create collaborative activities and discussion opportunities for students, thus enhancing empathy and communication skills. If considered together, in general we see that video acts as a flexible medium with two pathways to access, emotional connection, and positional power. Video appears to offer a "middle ground" between traditional films and immersive virtual reality tools.

2.3 Virtual Reality and Empathy

The greatest development in empathy-based media interventions is the use of VR. The systematic works of [11] and [4] pull together decades of literature and conclude that VR consistently offers the deepest immersion to users allowing them to "hang out", or "step into the shoes", of another person. VR offers an experience that films or videos cannot. VR makes participants the agent of narratives, thus produces much more intense emotional, cognitive, and behavioural responses.

There is an abundance of evidence supporting this argument. For example, [2] and [12] show that VR can outperform traditional learning to build empathy, particularly if student is interfacing with training patients.

Even more complex approaches have begun to incorporate biological feedback into the VR systems. For example, [13] established adaptive empathy training with VR, and used biological indicators (heart rate variability and galvanic skin response) to create 'adaptive' VR content. There are reviews of 360° media by [14 and [15] that enable cost-effective alternatives to VR. However, the 360° media can still be potentially immersive. Next, [16] noted that VR is useful for evoking emotional states that are associated with empathy, while [17] advocated that developmentally challenged participants learn through reflective practices embedded in a longer VR story. This they argue is better than ephemeral— not lasting—emotional participates.

2.4 Film Stimuli and Measurement Tools

Although movies, videos, and VR experiences become more frequently used in education, their impact profiles depend on evaluating them. Evaluating empathy, cultural awareness, or emotional engagement requires rigorous and reliable measures which can be provided with standardized measures. [18] made a significant contribution in this area. The study designed film clips for researchers to use in the lab that were validated to elicit and measure emotional and empathetic responding in the lab. Validating film clips allows researchers to evaluate the effectiveness of empathy-based interventions while also ensuring that the science, not impressions, guide the findings.

Reflective methodologies also play an important role in measuring impact. [19] points out that empathy is easier to understand when students are given time to reflect on their experiences in the film or stories through a reflective exercise, collaborative analysis, or artwork (which are examples). These kinds of processes allow researchers and educators to see the multilayered shifts and changes in students' changed perspectives that are more difficult to capture and share through standardized survey measures. In a similar fashion [20] demonstrated how narrative-based stories can be used as pre- and post-assessments to measure empathy growth. Students clearly improved their ability to understand the experiences of patients and have a better understanding of their empathetic responses when they viewed previously structured film and narrative-based story-telling activities.

Collectively, these works demonstrate a clear and compelling case for linking educational media with effective measurement techniques. The use of validated film stimulus, reflective frameworks, and systematic measures and assessments are critical; if not, interventions risk becoming gauges of altitude, only anecdotal at best. By integrating measurement into the education of empathy, a significant outcome occurs: researchers and educators not only validate the efficacy of empathy education, but also improve it and build capacity for using it primarily in future academic and professional applications.

III. RESEARCH METHODOLOGY

The research methodology employed in this paper is primarily a systematic literature synthesis of 20 peer-reviewed research articles published in reputable journals such as IEEE and Springer. The selected studies include needed research in the three main areas related to this investigation: movie and cinemeducation, video-based learning, and virtual-reality- based empathy interventions. To be relevant, the selected papers span a time period of 2019 - 2025, using documents with empirical results, as well as review studies that dealt with movie and immersive media's role in developing empathy, cultural understanding, and communication skills. The studies can be categorized into four identified themes; (1) movies and cinemeducation - highlighting the use of films used in educational and medical environments to develop empathy and ethical reflection; (2) video-based learning - referencing engagement, retention, and collaboration, through video-

based pedagogy; (3) virtual reality and empathy - understanding VR in terms of emotional elicitation and perspective taking; and (4) reflective and measurement tools - referencing the validation of film stimuli and reflective practices. Synthesizing these themes will also elucidate gaps and allows for a framework to be developed, CineMind, that integrates the three perspectives in a more comprehensive manner, in a classroom, and in corporate training.

IV. EXPERIMENTAL SETUP

CineMind's systematic study is testing how movies and virtual reality (VR) can promote empathy and cultural awareness with students and corporate employees. Participants will be assigned to one of two groups in a controlled study. Group A will take a smaller series of film and video-based learning modules, used specifically for this study, for the intervention. Group A will use existing modes of cinemeducation applied from studies like those presented in [3] and [1]. Group B will take part in an immersive VR- based empathy-based training. The group B activities will be based on immersive VR applications reviewed in [12] and [11]. In addition, participants may be part of technologies that will use biofeedback tools, such as those included in [13] that will allow participants' biometrics to measure real-time, ongoing emotional investment levels.

In the end, both groups will engage in some form of reflective activity such as journaling or group discussions similar to that in [19]. Mood management protocols will be in place such that both groups participate in these emotional immersion and reflective thinking experiences to facilitate their empathy development, since both emotional immersion and reflective thinking are important processes in the contemporary understandings of empathy.

V. IMPLEMENTATION AND RESULT

We propose to implement CineMind by bringing together portions of existing film-based, video-based, and VR-based practices in a singular platform. The application will include the use of film-based modules, where selected clips from movies are used to highlight cultural distinctions, ethical dilemmas, and emotional challenges, as discussed in [1] and [5]. It will also be informed by the aspects of video-based learning to provide interactive and collaborative knowledge building similar to [10] and [9]. To support deeper levels of immersion, the proposed application will also incorporate VR experiences in ways that invoke strong emotions and perspective-taking based on [4] and [16]. Reflection tools will be included on the platform to encourage users to capture their emotional responses-to-the experience, and to discuss their experiences with peers in ways advocated by authors in [19].

We expect that, based on existing evidence, students will improve scores in empathy, develop stronger communication skills, and have greater intercultural understanding. We expect that Group A students will receive important insights through the use of films and videos, while Group B students will receive these insights with even more heightened emotion and transformative learning experiences from their VR experiences.

VI. CHALLENGES AND LIMITATION

While the CineMind framework has a lot of promise, there are a number of limitations and considerations in play. For starters, the educational use of copyrighted movies in educational and corporate training practices presents a notable challenge that needs to be considered. As discussed in studies such as [5], the restrictions of licensing movies often limit the options available to educators—a reduction in variety may eliminate the level of cultural and emotional richness available for exploring. Another potential challenge to cine-mapping and using other forms of immersive technology is cost and access. Research shows that VR hardware and infrastructure remain prohibitively expensive—and not every institution or organization can afford them at a meaningful scale [14].

One more limitation spans the emotional engagement and critical reflection component. Certainly, films and immersive environments can engage and catalyse emotional experiences and responses, but research shows (as exemplified by [19]) that without structured reflection and focus on learning outcomes firmly in the cognitive realm, these emotional/Calli Goos experiences may fall flat and ultimately not result in substantive behaviour or attitudinal change. The last consideration is about generalizability of results. Most of the literature provides evidence described focuses entirely on medical education contexts—like [3]—and therefore results may not represent fully the efficacy of these interventions in working with corporate or intercultural training.

Lastly, ethical considerations must also be examined. Immersive VR experiences can have strong emotional effects which raises the issue of psychological safety or emotional overload. As noted in [15], there are important safeguards and debrief available so the status quo is critical. Thus, while CineMind will be revolutionary and impactful in its approach, careful planning, ethical consideration, and resource allocation will be important to navigate and address the challenges the large-scale work requires, to achieve meaningful outcomes.

Table 6.1 Challenges vs. Limitation of Framework

	Issue	Explanation
Challenges	Copyright and Licensing	Legal restrictions reduce the pool of films available for teaching and training, limiting diversity of content.
	Cost and Accessibility	VR hardware and infrastructure remain expensive; not all institutions or companies can adopt at scale.
	Emotional vs Reflection Balance	Strong emotional triggers from films/VR may remain superficial if not paired with structured reflection.
	Ethical Concerns	Highly immersive VR risks emotional overload; safeguards and debriefing are essential.
Limitations	Generalizability	Most prior research is based on medical education, limiting applicability to corporate or intercultural training.
	Resource Dependence	Long-term implementation requires continuous investment in content, tools, and facilitators.
	Measurement Challenges	Empathy is difficult to measure accurately; reliance on self-reports risks social desirability bias.

VII. CONCLUSION

Movies and VR can provide incredible opportunities for structured empathy and cultural training. The evidence from prior studies—ranging from cinemeducation to VR advance for the purpose of emotion elicitation—demonstrates that the potential for empathy, engagement, and reflection consistently improves. Collectively this potential provides a rationale for the presentation of the CineMind application for students and professionals. CineMind is an integration of the narrative elements of movies, the engaging components of smart video learning, and the immersive depth of VR. Moving forward, we will develop a prototype, and deliver a controlled trial to assess its benefits across multiple contexts.

The CineMind framework has the potential to be applicable for students at the university or higher education level, and employees in a corporate or organization level where communication, empathy, and intercultural competencies are essential. Its interdisciplinary ability provides CineMind as a potential novel solution in responding to gaps in both curricula and workplace training programs.

With regards to next steps, I will initiate the prototype development of the CineMind app and move onto controlled trials to assess its impact on learning in multiple educational and professional contexts. The trials will assess short term learning outcomes, as well as long-term behavior change. In addition to sensibly selecting the scope of the research partnerships with universities and organizations will be important to assess the scalability, cost-benefit or ROI and acceptance by the participants.

In conclusion, CineMind represents a step toward bridging the gap between entertainment media and structured learning. By uniting the narrative power of movies, the interactivity of video-based learning, and the immersive depth of VR, this framework offers a promising pathway for cultivating empathy, enhancing communication, and fostering cultural understanding in a world where these skills are increasingly vital.

VIII. REFERENCES

- [1] M. Rueb, M. Siebeck, E. A. Rehfuess, and L. M. Pfadenhauer, "Cinemeducation in medicine: a mixed methods study on students' motivations and benefits," *BMC Med. Educ.*, vol. 22, no. 1, p. 172, Mar. 2022, doi: 10.1186/s12909-022-03240-x.
- [2] H.-L. Lin *et al.*, "Can virtual reality technology be used for empathy education in medical students: a randomized case-control study," *BMC Med. Educ.*, vol. 24, no. 1, p. 1254, Nov. 2024, doi: 10.1186/s12909-024-06009-6.
- [3] M. Salajegheh, A. A. Sohrabpour, and E. Mohammadi, "Exploring medical students' perceptions of empathy after cinemeducation based on Vygotsky's theory," *BMC Med. Educ.*, vol. 24, no. 1, p. 94, Jan. 2024, doi: 10.1186/s12909-024-05084-z.
- [4] C. Hadjipanayi, M. Christofi, D. Banakou, and D. Michael-Grigoriou, "Cultivating empathy through narratives in virtual reality: a review," *Pers. Ubiquitous Comput.*, vol. 28, no. 3–4, pp. 507–519, Aug. 2024, doi: 10.1007/s00779-024-01812-w.
- [5] D. De Souza and G. C. Adams, "Practical Pedagogical Tips for Using Movies in Medical Education," *Acad. Psychiatry*, vol. 47, no. 1, pp. 90–94, Feb. 2023, doi: 10.1007/s40596-022-01740-y.
- [6] M. Law, W. Kwong, F. Friesen, P. Veinot, and S. L. Ng, "The current landscape of television and movies in medical education," *Perspect. Med. Educ.*, vol. 4, no. 5, pp. 218–224, Sept. 2015, doi: 10.1007/S40037-015-0205-9.
- [7] A. Gordillo, D. Lopez-Fernandez, and E. Tovar, "Comparing the Effectiveness of Video-Based Learning and Game-Based Learning Using Teacher-Authored Video Games for Online Software Engineering Education," *IEEE Trans. Educ.*, vol. 65, no. 4, pp. 524–532, Nov. 2022, doi: 10.1109/TE.2022.3142688.
- [8] R. Amashi, U. Koppikar, and M. Vijayalakshmi, "Investigating the Association Between Student Engagement With Video Content and Their Learnings," *IEEE Trans. Educ.*, vol. 66, no. 5, pp. 479–486, Oct. 2023, doi: 10.1109/TE.2023.3303421.
- [9] M. Furini, "ViDi: Virtual Director of Video Lectures," in *2019 16th IEEE Annual Consumer Communications & Networking Conference (CCNC)*, Las Vegas, NV, USA: IEEE, Jan. 2019, pp. 1–4. doi: 10.1109/CCNC.2019.8651813.
- [10] C. Serasinghe, N. Perera, D. Samarasinghe, M. Muthusinghe, and M. Wijesundara, "Leveraging Smart Video-Based Learning to Enhance Student Engagement and Collaboration," in *2024 6th International Conference on Advancements in Computing (ICAC)*, Colombo, Sri Lanka: IEEE, Dec. 2024, pp. 486–491. doi: 10.1109/ICAC64487.2024.10850940.
- [11] J. Lacle-Melendez, S. Silva-Medina, and J. Bacca- Acosta, "Virtual and augmented reality to develop empathy: a systematic literature review," *Multimed. Tools Appl.*, May 2024, doi: 10.1007/s11042-024-19191-y.
- [12] R. Alieldin, S. Peyre, A. Nofziger, and R. Borasi, "Effectiveness of immersive virtual reality in teaching empathy to medical students: a mixed methods study," *Virtual Real.*, vol. 28, no. 3, p. 129, July 2024, doi: 10.1007/s10055-024-01019-7.

-
- [13] K. Gupta, Y. Zhang, T. S. Gunasekaran, N. Krishna, Y. S. Pai, and M. Billinghamurst, "CAEVR: Biosignals-Driven Context-Aware Empathy in Virtual Reality," *IEEE Trans. Vis. Comput. Graph.*, vol. 30, no. 5, pp. 2671–2681, May 2024, doi: 10.1109/TVCG.2024.3372130.
 - [14] J. Pirker and A. Dengel, "The Potential of 360° Virtual Reality Videos and Real VR for Education—A Literature Review," *IEEE Comput. Graph. Appl.*, vol. 41, no. 4, pp. 76–89, July 2021, doi: 10.1109/MCG.2021.3067999.
 - [15] L. Trevena, J. Paay, and R. McDonald, "VR interventions aimed to induce empathy: a scoping review," *Virtual Real.*, vol. 28, no. 2, p. 80, Mar. 2024, doi: 10.1007/s10055-024-00946-9.
 - [16] R. Somarathna, T. Bednarz, and G. Mohammadi, "Virtual Reality for Emotion Elicitation – A Review," *IEEE Trans. Affect. Comput.*, vol. 14, no. 4, pp. 2626–2645, Oct. 2023, doi: 10.1109/TAFFC.2022.3181053.
 - [17] N. Soilis, F. Bhanji, and E. A. Kinsella, "Virtual reality simulation for facilitating critical reflection and transformative learning: pedagogical, practical, and ethical considerations," *Adv. Simul.*, vol. 9, no. 1, p. 49, Dec. 2024, doi: 10.1186/s41077-024-00319-x.
 - [18] C. Wieck, S. Scheibe, and U. Kunzmann, "Development and validation of film stimuli to assess empathy in the work context," *Behav. Res. Methods*, vol. 54, no. 1, pp. 75–93, Feb. 2022, doi: 10.3758/s13428-021-01594-6.
 - [19] N. Burla *et al.*, "A systematic scoping review on group non-written reflections in medical education," *BMC Med. Educ.*, vol. 24, no. 1, p. 1119, Oct. 2024, doi: 10.1186/s12909-024-06117-3.
 - [20] Y. Kagawa *et al.*, "Using patient storytelling to improve medical students' empathy in Japan: a pre-post study," *BMC Med. Educ.*, vol. 23, no. 1, p. 67, Jan. 2023, doi: 10.1186/s12909-023-04054-1.
-

THE SYMBIOTIC EVOLUTION: A REVIEW OF ARTIFICIAL INTELLIGENCE'S ROLE WITHIN EDUCATION 4.0 AND ENVISIONING EDUCATION 5.0

Arya Shah and Manisha Divate

SVKM's Usha Pravin Gandhi College of Arts, Science and Commerce, Vile Parle Mumbai, India

I. ABSTRACT

Education 4.0 and the more recent Education 5.0 are big changes in the field of Artificial Intelligence (AI). AI is both a philosophical idea and a technological force that is driving this change. In order to describe the role of AI within these two different but related educational paradigms, this review study synthesizes the corpus of available material. In Education 4.0, AI is the main force behind efficiency, personalization, and data-driven decision-making. It makes intelligent content curation, automated assessment, and adaptive learning possible. The role of AI changes as attention turns to Education 5.0, a humancentric paradigm that places a higher priority on social problem-solving, creativity, and health.

In this sense, AI is seen as a cooperative partner, a way to help people improve their social and emotional skills, and a way to solve important societal problems. This essay critically analyzes the uses, benefits, and inherent difficulties of AI in both models, covering moral dilemmas such as algorithmic prejudice and data privacy. Last but not least, it identifies important research gaps and presents novel concepts, asserting that the future of AI in education depends on a human first approach that gives ethical frameworks and fair access top priority.

Keywords: Artificial Intelligence, Education 4.0, Education 5.0, Personalized Learning, Human Centric Education, Learning Analytics, Educational Technology, Ethical AI.

II. INTRODUCTION

The educational landscape is changing significantly, just like businesses and societies. Education 4.0, based on Industry 4.0 or the Fourth Industrial Revolution, propels the education field towards an increasingly progressive and student-centric learning experience. In this field, students learn the skills necessary to be digitally literate and develop critical thinking and problem-solving abilities. Here, we use ideas such as cloud computing, big data, and Internet of Things to develop connectivity and flexibility with personalization for every user.

With the passing of time, one new paradigm regarding the notion of education is getting introduced, i.e., Education 5.0. This is a giant step forward in terms of technology. It avoids the danger of dehumanization implied within a purely technocratic society. It emphasizes the welfare of people, their creativity, teamwork, and a sense of social usefulness. "What can students do?" is not the only question raised by Education 5.0. Questions like "Why do they do it?" and "How is this useful for the general good?" arise as a result. "Artificial Intelligence (AI): This is a general term used for the encompassing fields of Computer Vision, Natural Language Processing, and Machine Learning.

This paper has the intention of offering an extensive discussion regarding the applications of AI in Education 4.0 and 5.0. The theoretical foundations of these models of education shall be presented, followed by an analysis of the specific roles of AI in these models, concluded in the final section which shall also include recommendations for further investigation.

III. OBJECTIVES

The general objective of this review paper is to overview and criticize the existing body of knowledge on applying Artificial Intelligence to the Education 4.0 case and the future Education 5.0 case. The specific aims are:

1. To provide the detailed functions and applications of the AI within the frames of Education 4.0 and Education 5.0.
2. When discussing the scope and the application credibility of AI-related tools and methods in the context of both learning constructs.
3. To identify gaps, inconsistencies, and areas of unexplored research in the literature of available knowledge management, and to criticize them.
4. to propose a plan of work in the future that will fill such gaps detected.

IV. SCOPE

The review is conceptual, founded on education technology, computer science, learning sciences and education sociology literature. The boundaries set by the next boundaries determine the scope: Conceptual

Focus: The paper is devoted to the paradigm of Education 4.0 to Education 5.0 and the need to re-conceptualize the role of AI without providing a very technical analysis of the specific AI algorithms.

Applications: The paper contains such prominent areas of application as personalization of learning, assessment, content creation, and socio-emotional skill development.

V. APPLICABILITY

The applicability of AI is fundamentally shaped by the philosophy of the educational standard it serves.

1. Applicability in Education 4.0: Optimizing the Learning Machine

It's an Industry 4.0 match because it addresses the issue of integration, decision making through data, and readiness for the digital age workforce. In this aspect, the applicability of AI technology relates to the concepts of efficiency, automation, and scale in the area of personalization.

Intelligent Tutoring Systems (ITS): Computer-based software that employs AI to provide differentiated tutoring services depending on the student's pace and type at a particular instance in time (for example, Knewton and Carnegie Learning).

Automatic Grading of Assignments:

Natural Language Processing (NLP) assists in the automatic marking of essays, SA questions, and codes, ensuring that tutors get more time.

Learning Analytics: AI algorithms mine massive amounts of data from the Learning Management Systems and predict outcomes for students. At-risk students are tracked and guidance is given regarding how improvement in curriculum can be developed. Smart Content Development:

Technology-based learning tools allow teachers to develop contextual learning content such as questions, summarize, simulation, etc., associated with the curriculum.

In this respect, AI can be leveraged as a effective optimizer for the existing education system, which is responsive, evidence-based, and personalized.

2. Applicability in 5.0 Education:

Enhancing the Human Experience: Education 5.0 does offer a philosophical paradigm for a purpose-

driven, human-centered approach. It values well-being, innovation, teamwork, and the addressing of grand challenges in society. The role of AI in such a situation can develop into that of an optimizer and supplementor to human potential.

Co-Creation with Generative AI: Sites like GPT-4 and DALL-E are not only consumed but also co-producers in assisting students overcome the art world and explore novel concepts and create artistic and scientific works together.

Enabling Socio-Emotional Learning (SEL): AI simulations and virtual reality (VR) environments have the potential to provide students with a safe space where they can learn to negotiate, empathize, and control emotions. Sentiment analysis (with no ethical norms) may also provide warnings about the mental health problems of the students.

Facilitating Group Problem-Solving:

AI can support student groups working on wicked problems like climate change by modeling systems, searching through lots of data and connecting it with the world experts and information.

Augmenting Inclusivity:

AI can also be used to augment inclusivity with real-time transcription, translation services, and disabled student adaptive user interface. In this paradigm, AI can be implemented as a kind of human augmentation, which is aimed at the ability to expand other distinctly human gifts, such as creativity, empathy, and ethical cogitation.

VI. LITERATURE REVIEW

1.1 Heavyweight: AI as a Powerhouse of Productivity and Individualization in Education 4.0. The existing research, especially from the early 2000s to the end of the 2010s, focuses on Education 4.0. This literature emphasizes using AI to improve the current education system, boost efficiency, and offer personalized learning on a large scale. The key topics include adaptive learning, learning analytics, and automation.

1.2 Adaptive and Customized Learning Systems. The most successful area of research in this paradigm is the development and analysis of Intelligent Tutoring Systems (ITS). These systems aim to replicate the benefits of one-on-one human tutoring, providing immediate personalized instruction and feedback.

1.3 Analytics and Predictive Modeling in learning.

With the rise of ITS, the emergence of big data in education created a new study area known as Learning Analytics (LA). According to George Siemens (2012), LA seeks to compile data about learners and their environments to understand and improve learning and the settings in which it happens. This quickly expanded into predictive modeling. Researchers like Ryan Baker (2010) used educational data mining to predict which students might fail or drop out based on digital footprints left in a Learning Management System (LMS). This research offers opportunities for early intervention and data-informed support for at-risk students. However, there are also cautionary tales in the literature.

1.4. Automation of Assessment and Administration Automation is the third key element of AI in Education 4.0. Significant work has been done on the Automated Essay Scoring (AES) system over time. In the 1960s, Page Ellis began this effort, and his contributions shaped its development. Notable findings suggest that natural language processing (NLP) might enhance AES grading by focusing on grammar while occasionally considering meaning, as Cahill pointed out in 2018. Still, real progress requires overcoming current limitations in evaluation.

2. The Pivot: Emerging Discourses on AI for a Human-Centric Future (Education 5.0)

The technology-driven focus of Education 4.0 has gradually shifted to something new. Current writings in academic circles reveal this evolving stage. The roots trace back to early drafts of what some refer to as Education 5.0, still in development. This concept is influenced by Japan's vision for Society 5.0, which quietly inspires future thinking. One idea suggests that AI could help individuals express their true selves rather than conforming to a standard mold.

2.1. Generative AI as a Partner in Creativity

The technology-driven focus of Education 4.0 has gradually shifted to something new. Current writings in academic circles reveal this evolving stage. The roots trace back to early drafts of what some refer to as Education 5.0. This idea is influenced by Japan's vision for Society 5.0, shaping thoughts for the future. New models suggest that instead of replacing personalized learning, AI could help highlight what makes each person unique.

2.2. AI for Socio-Emotional Learning (SEL) and Well-being

Another vital research area involves using AI to support social-emotional skills and student well-being. Studies are exploring AI-driven virtual reality scenarios where students can safely practice difficult social interactions. Other research investigates how sentiment analysis of student forum posts can provide early warnings of mental health issues (Wang et al., 2022). This represents a significant shift. The focus now extends beyond academic performance to include the overall well-being of students, an important aspect of Education 5.0.

2.3. The Dehumanization vs. Augmentation Argument

The Dehumanization vs. Augmentation Argument A common concern in literature is the fear that AI might replace teachers and strip schools of their essence. Educators and experts, including sociologists, worry that the absence of human guidance could weaken meaningful connections (Selwyn, 2019). Yet some now view machines as helpers instead of replacements.

Currently, discussions about AI in Education 4.0 are leaning toward what some call Education 5.0, a movement that has only just begun. The advancements made under Education 4.0, utilizing smart systems to streamline tasks and personalize teaching, provide a valuable foundation. Recent studies indicate a growing focus on people-first goals in Education 5.0, which presents difficult challenges that need careful attention.

VII. IDENTIFIED RESEARCH GAPS

There seem to be glaring holes or gaps, and places that have not been sufficiently ventured in the literature, and the abovementioned gaps hinder the effective transitioning between Education 4.0 and Education 5.0.

1. The Ethical Framework Gap: Technology Outpacing Governance

Certain works show what AI can do, especially in Education 4.0. Still, many resist facing hard issues - such as data ownership, how bias travels, or determining responsibility when errors happen. As O'Neil noted in 2016, types like Weapons of Math Destruction aren't only ideas - they're real today. Yet plenty of articles about AI in schools ignore what's actually tough there. A gap shows up when comparing accessible tech with meaningful setups for learning. Even though fixes are available, little happens since putting ideas into practice trails far behind creating them. Years may pass before policy catches up with real-world actions, making implementation harder in uneven settings. Fast progress in tech doesn't guarantee smart use - risks pop up when habits lag behind knowledge. Leaders see issues clearly but often fail to shift how things run completely, especially where

change drags through slow administrative zones. Training may grow, yet resistance lingers beneath the surface across departments altering results in silent ways. Change takes hold not through isolated efforts but by syncing teaching methods, rules, and systems - remaking how learning unfolds moment by moment. New rhythms appear, fragile at first, when practice, structure, and purpose move into step together.

2. The Measurement Gap: Quantifying the Unquantifiable

What we know about Education 4.0 makes it easy to list what it achieves. Results show up as grades, how fast people finish, or hours spent interacting. Yet those of Education 5.0 - creativity, empathy, feeling good about life, and meaning - are hard to turn into numbers. That result? Not enough clear numbers to go by. Even though many agree AI oughta build those so-called "soft skills," almost nothing tackles how to actually measure what happens when such tech meets a learner - their imagination, their mood, anything real.

3. The Equity Paradox Gap: Ignoring the Digital Divide

Sliding Over the Digital Divide The personalizing AI literature can create an ideal of learning on an individual level. However, it may disregard the equity paradox: The very technology that has the power to personalize learning, can also increase the differences gaps. The use of AI in particular in resource-challenged areas or working with marginalized populations appears to constitute a colossal gap in research. It appears to assume that there is a level playing field in terms of the availability of devices, access to the internet, and digital competency, which is not the case, which establishes a situation with AI-driven learning being accessible exclusively to the chosen ones.

4. The Pedagogical Integration Gap: Tool Over Theory

The Pedagogical Integration Gap: Tool Over Theory To a Large Extent much of the extant research is technocentric, focusing on what the technology does. Notably, computer science studies, which can be said to be the development work, and educational studies, which can be said to be the use work, are two different bodies of research. Reports exploring the topic which investigates how AI will necessitate a paradigm shift in the perception of educational practices are very scarce. The evolving roles of the teachers, which will turn not sage on the stage, but architects of learning in an AI-enhanced classroom, will be subject to future studies. The question of how to create teachers who see AI as not a threat/aid but as a partner will also be an unexplored one.

VIII. PROPOSED WORK

Depending on the literature review that has been conducted and some of the issues that have been determined, based on the gaps that are identified, the following are some of the proposed plans to be used. The following are some of the preliminary findings that will be identified. Such kind of research will offer the capability not only to diagnose the problem but will help to fully enjoy the problems that are occurring. This review has described the history of the implementation of the AI as a paradigm of Education 4.0 which has been driven by the interest of efficiency, and then passed to the paradigm of Education 5.0 which is driven by the philosophy of humanism. As it can be seen based on the literature on the role of AI in Education 4.0, the literature is mature and empirical but driven predominantly by the paradigm that is more technology-oriented and less future-oriented in the ethical perspective. The state of the art on the role of AI in Education 5.0 is more philosophical and widely less in the empirical perspective. The ethical, measurement, equity and pedagogical gaps in standards are seen to be the key critical edge of the future research. It is an essential requirement in dealing with these gaps in the future studies:

1. Build Practical Ethical Advice: Use your academic knowledge to go beyond identification of issues and build practical ethical advice with education leaders, students, and policymakers.
2. New Metrics for Human-Centric Outcomes: Invent novel methods to assess the growth of creativity, empathy, and well-being skills using AI- enhanced learning environments.
3. Highlight Focus on Equity and Access: Highlight the emphasis on the development of efficient and affordable AI solutions and their accessibility.
4. Educator-Based Research Investment. The Future role of the teacher, The design and development of new paradigms of professional development to equip teachers with the classroom and the realities of Education 5.0.
5. Educational Gamification: This encourages students to become motivated to learn by highlighting features like incentives and the advancement of challenges. It is uncertain whether this has any impact on learning retention.

Although successfully integrating AI into the future of education presents technical challenges, it is fundamentally a human task. By addressing some of the research gaps related to AI and education mentioned

earlier, we can ensure that the future shaped by AI is not simply an improved version of the past. Instead, it should focus on creating a brighter and better future.

IX. QS GLOBAL ACADEMIC SURVEY

There has been a QS Global Academic Survey [9] this year to explore the impact of Generative AI tools (such as ChatGPT, Google Bard, DALL-E, etc.) in businesses and in the higher education sector. The survey includes the following important questions and the readers of this paper shall try to answer these questions for their own knowledge- sake and offer their feedback/opinion on the importance and use of Generative AI tools for education in their own institutions.

Q1. How familiar are you with Generative AI technologies such as language models, text generators, image or video creators, etc.?

- Very familiar
- Moderately familiar
- Slightly familiar
- Not familiar at all

Q2. Have you personally used or interacted with any of the Generative AI technologies?

- Yes
- No

Q3. Which platforms have you used professionally? (Please select all that apply)

- Runway ML
- NVIDIA
- StyleGAN
- Unity ML-Agents
- Hugging Face
- OpenAI
- GPT-3
- IBM Watson Studio
- TensorFlow
- Google
- Colab
- PyTorch
- DeepArt

Q4. Please select what for you have used AI technologies (tick all that apply):

- Automated Literature Reviews
- Content Summarization
- Essay writing
- Language Translation and Transcription
- Tutoring and Educational Materials
- Idea Generation
- Data Analysis and Visualization
- Plagiarism Detection Research Paper Writing Simulations and Modelling Journal publication
- General Content Recommendation

-
- Other

Q.5-8 Please indicate to what extent you agree with the following statements:

5. Generative AI has a positive impact on students' learning experience
6. Generative AI will have a negative impact on the education sector
7. It is essential that universities incorporate Generative AI to their curriculum
8. Generative AI is helping the Higher Education sector to thrive

- Strongly disagree
- Disagree
- Neither agree nor disagree
- Agree
- Strongly agree

Q.9-11 Please indicate to what extent you agree with the following statements:

9. Gen AI tools should be regulated
10. Gen AI is helping to reduce social inequalities
11. Gen AI is contributing to a better society

- Strongly disagree
- Disagree
- Neither agree nor disagree
- Agree
- Strongly agree

Q12. Has your institution implemented any Generative AI technologies in the classroom or educational processes?

- Yes
- No

Q13. What effect do you think Gen AI technology has on your current workplace during 2023?

- Negligible impact
- Minimal impact
- Moderate impact
- Significant impact
- Transformational impact

Q14. Which areas in academia do you think Gen AI impacts?

- Curriculum Development Pedagogical Approaches
 - Assessments and Grading
 - Student Support and Counseling
 - Administrative Tasks
 - Admissions and Enrollment
 - Research Practices
 - Inclusive Education
 - Other
-

Q15. In your opinion, what skills would students improve using advancements in Generative AI? (select all those applicable options)

- Aptitude / Analytical / Quantitative skills
- Communication Depth of knowledge in subject
- Active learning
- Ethics and Social Responsibility
- Emotional Intelligence
- Resilience & Flexibility
- Sustainability mindset
- Negotiating skills
- Organizational skills
- Business Management
- Creativity
- Problem-solving skills
- Interpersonal skills
- Leadership Ability to work in a team
- Entrepreneurship Language skills
- Other

Q16. What challenges or barriers do you face in implementing or using Generative AI technologies in your Institution / University? (select all that apply)

- Resistance to Change
- Ethical Concerns
- Data Availability and Quality
- Security and Privacy
- Intellectual Property
- Maintenance and Scalability
- Interpretability and Bias
- Technical Complexity Regulation and Compliance
- Pedagogical Integration
- ROI and Justification
- Limited Resources
- Other

Q17. What do you feel when reading about Generative AI? (select all that apply)

- Surprise
- Curiosity
- Interest
- Enjoyment
- Fear
- Guilt

-
- Contempt
 - Sadness
 - Disgust
 - Anger
 - Shame/shyness
 - Other

Q18. How do you perceive the role of Gen AI in society?

- Very positive
- Somewhat positive
- Neutral
- Somewhat negative
- Very negative

Q19. In your opinion, how can Colleges / Universities better prepare graduates for the advance of generative AI?

Q20. Is there any additional feedback or comment you would like to provide regarding the impact of Generative AI on your institute/organization?

X. ENABLING TECHNOLOGIES

This section proposes an investigation into the enabling technologies which can be used as the basis for the development of Education 5.0. We hope that the enabling factors for the development of Education 5.0 would include but not be limited to Artificial Intelligence, Virtual/Augmented Reality, Internet of Things, Big Data & Analytics, Blockchain Technology, and 5G Network Technology. Though Artificial Intelligence-based systems can potentially develop systems that can enable personal learning and immediate instructor feedback, with teachers being supported to assess the academic progress of students, the concept of Virtual and Augmented Reality can potentially expose students to entirely different subject areas and environments in an engaging manner. Furthermore, IoT can connect all forms of devices and sensors to the internet for real-time monitoring and analysis of student engagement and progress, while cloud computing allows access to resources and materials from anywhere and at any time, thus making education flexible and accessible. Further, Big Data and Analytics can help in evaluating the progress of students and providing tailored learning services.

Additionally, Blockchain technology can help secure and transmit students' records. Lastly, 5G Network will enable the high bandwidth required for the use of emerging technologies in education like virtual reality. In the forthcoming subsections, we will expound the evolution of the above core enablers towards the fulfillment of the vision of Education 5.0. Overall 2-way representation of Education 5.0 and its enablers is depicted in Fig 1.




Fig. 1. Two-way stack representation of Education 5.0. The technologies are shown on the left side, and the objectives are shown on the right side. For example, the utilization of AI and machine learning discusses the adaptability of learning and decision-making. The middle section displays the processes that comprise the entire learning strategy.

XI. CHALLENGES

Education 5.0 is also that generation of education that exhibits a more personalized, learner-oriented approach using technology to enhance learning. Based on the concept that education should be flexible, adaptable, and responsive to individual learners' needs, it can be reaffirmed [10], [11]. Major challenges for Education 5.0 are explained in the section below.

Cost to implement becomes one of the major challenges for Education 5.0. Schools and colleges have to invest in new technologies like Learning Management Systems, digital content, and hardware to implement a technology-enabled personalized education system [1], [12]. This can be a huge financial cost for schools and colleges with tight budgets. Maintenance and upkeep of these technologies will also take up a lot of costs. It can hence be difficult to implement Education 5.0 fully because of the challenge of such high costs. In fact, it is even much worse in developing countries where there are fewer resources.

Another biggest challenge facing Education 5.0 is the absence of training for teachers [13]. For a teacher to implement effectively a learning system that is based on personalization and is technology-driven, she will need training in these emerging technologies. This can prove to be a challenge in most developing countries. In addition, some teachers might resist changes in their profession, which might also limit them from accepting learning technologies in their profession of Education 5.0 [14]. A teacher lacking training might not be able to fully harness the key technologies of her profession of Education 5.0.

The digital divide is also a major issue in Education

5.0 [15], [16]. Students do not have similar technology and resources. This may lead to the creation of a digital divide where some students will have the latest technology and resources, while others will not. Such

an issue may widen the gap between students of different backgrounds. This might pose an issue for educators who would want all students, regardless of their backgrounds, to receive technology-based education. A lack of resources in content development is also an issue for the implementation of Education 5.0 [17]. Creating interactive learning resources could be a costly process. Sharing resources could also become a problem due to the absence of standardization in the technology that is used in educational organizations. This could be a reason that prevents schools and colleges with less budget from using these tools. Issues of privacy and security are also significant in the new technological advancement of Education

5.0 [18]. The issues of privacy and security are becoming more significant with the increase in the use of the internet and the level of personal information being placed on the internet. This may be a significant challenge in schools and colleges, where the safety of the information of the students may be paramount. The use of the internet has raised concerns of being vulnerable to attacks, such as the breach of student information [19].

One hurdle comes from having too few researches on how well Education 5.0 works. Since it is still quite new, findings remain thin. Because of that gap, teachers find themselves guessing when choosing tools or strategies. Knowledge lags behind what is needed now. Still, working out how to make this work isn't easy. What's drawing attention now? The Metaverse [21]. Getting it into education means spending seriously on tech - like strong internet links, powerful computing gear, also tools for virtual reality and augmented reality like VR or AR headsets. Making lessons about the Metaverse often takes too much effort. Learning how to produce such material demands real guidance for teachers. Without devices, many learners cannot reach this digital space at all. Some kids miss out when schools move too fast. Those who can reach the Metaverse often gain an edge others do not. People might feel less safe as the Metaverse grows. Private moments could be shared without warning. A single breach might reveal too much about who someone really is. What makes the Metaverse tricky is how it shifts constantly, without clear rules among various systems or tools people use [22], [23]. As usage grows - with increasingly common Metaverse gadgets [22], [20] - handling larger crowds gets harder. Delays, slow data flow, or crashes from too much demand often pop up under pressure [22], [23]. What makes the Metaverse work well is how smoothly people interact with it. When users engage across virtual spaces, delays or errors must stay rare. Learning today mixes physical classrooms with digital tools - blending styles creates ongoing hurdles. One moment it's all about connection, next everything depends on presence. Lean only into screens? Loneliness might quietly take hold. Yet spend every hour away from devices. The chance to adapt and grow slips right out. Life holds both, never just one or the other.

XII. CONCLUSION

Artificial Intelligence has been a crucial part of Education 4.0 for the last twenty years. With the introduction of various key digital technologies, like Generative AI in 2023, we are moving from Education 4.0 to Education 5.0. This is a significant advancement in using machine-driven innovation. It will also support human creativity and technology as people create content across many areas of education. The ability to produce content quickly and in new ways—whether text, code, images, sounds, or videos—has greatly improved humanity's access to information electronically through Generative AI.

Again, because it is a complex technology, it is important to highlight the strong need for ethical applications in the future development of Generative AIs to have a positive impact on society. Some risks associated with using Generative AIs include lower data quality, the spread of misinformation, and even large-scale job loss. In any case, we must focus on careful development to promote informed and responsible use by both individuals and companies.

It is important to have a balanced and rational view of using Generative AI techniques. This way, we can benefit from the positive aspects while avoiding the potential negative impacts.

XIII. REFERENCES

1. Fisk, P. (2017). Education 4.0... The future of learning will be dramatically different, in school and throughout life. GeniusWorks.
2. Kulik, J. A., & Fletcher, J. D. (2016). Effectiveness of intelligent tutoring systems: A meta-analytic review. *Review of Educational Research*, 86(1), 42-78.
3. O'Neil, C. (2016). *Weapons of Math Destruction: How Big Data Increases Inequality and Threatens Democracy*. Crown.
4. Rudolph, J., Tan, S., & Tan, S. (2023). ChatGPT: Bullshit spewer or the end of traditional assessments in higher education? *Journal of Applied Learning & Teaching*, 6(1), 212-224.
5. Sharma, G. (2023). The emergence of Education 5.0: A human-centric paradigm for the future. *Journal of*

Educational Change, 24(2), 145- 162

6. Siemens, G., & Baker, R. S. (2012). Learning analytics and educational data mining: Towards communication and collaboration. *Proceedings of the 2nd International Conference on Learning Analytics and Knowledge*, 252-254.
7. Sharma, G. (2023). The emergence of Education 5.0: A human-centric paradigm for the future. *Journal of Educational Change*, 24(2), 145- 162.
8. Baidoo-Anu, D., & Ansah, L. (2023). Education in the Era of Generative Artificial Intelligence (AI): Understanding the Potential Benefits of ChatGPT in Promoting Teaching and Learning. *Journal of AI*, 7(1), 52-66. https://qsnetwork.az1.qualtrics.com/jfe/form/SV_38iPpTeaXiW3C2W?Q_CHL=gl&Q_DL=EMD_aHGGmkQ5veUIVii_38iPpTeaXiW3C_2W_CGC_7oSlDysi01LrOTN&_g_=g
9. S. Elayyan, "The future of education according to the fourth industrial revolution," *Journal of Educational Technology and Online Learning*, vol. 4, no. 1, pp. 23–30, 2021.
10. R. Huang, A. Tlili, H. Wang, Y. Shi, C. J. Bonk, J. Yang, and D. Burgos, "Emergence of the online-merge-offline (omo) learning wave in the post- covid-19 era: a pilot study," *Sustainability*, vol. 13, no. 6, p. 3512, 2021.
11. Corbett and E. Spinello, "Connectivism and leadership: harnessing a learning theory for the digital age to redefine leadership in the twenty-first century," *Heliyon*, vol. 6, no. 1, p. e03250, 2020. [
12. S. M. Ayyoubzadeh, T. Baniyadi, M. Shirkhoda, S. Rostam Niakan Kalhori, N. Mohammadzadeh, K. Roudini, R. Ghalehtaki, F. Memari, and A. Jalaeefar, "Remote monitoring of colorectal cancer survivors using a smartphone app and internet of things–based device: Development and usability.
13. P. Gupta and P. Bhaskar, "Teachers' intention to adopt virtual reality technology in management education," *International Journal of Learning and Change*, vol. 15, no. 1, pp. 28–50, 2023.
14. W. Gan, M. S. Dao, K. Zettsu, and Y. Sun, "Iot- based multimodal analysis for smart education: Current status, challenges and opportunities," in *Proceedings of the 3rd ACM Workshop on Intelligent Cross-Data Analysis and Retrieval*, 2022, pp. 32–40.
15. K. Kumar and A. Al-Besher, "Iot enabled e- learning system for higher education," *Measurement: Sensors*, vol. 24, p. 100480, 2022.
16. J. Ejaz and M. A. Shah, "Real-time analysis of student's behavioural engagement in digital smart classrooms using fog computing and iot devices," 2022.
17. J. R. Reidenberg and F. Schaub, "Achieving big data privacy in education," *Theory and Research in Education*, vol. 16, no. 3, pp. 263–279, 2018.
18. Torres-Hernández and M.-J. Gallego- Arrufat, "Pre-service teachers' perceptions of data protection in primary education," *Contemporary Educational Technology*, vol. 15, no. 1, p. ep399, 2023.
19. R. Shah, Y. Chen, and J. Kan, "User experience in the metaverse: challenges and solutions," *International Journal of Technology in Education*, vol. 12, no. 1, pp. 1–14, 2021.
20. Abraham, B. Suseelan, J. Mathew, P. Sabarinath, and K. Arun, "A study on metaverse in education," in *2023 7th International Conference on Computing Methodologies and Communication (ICCMC)*. IEEE, 2023, pp. 1570–1573.
21. Lin, S. Wan, W. Gan, J. Chen, and H.-C. Chao, "Metaverse in education: Vision, opportunities, and challenges," *arXiv preprint arXiv:2211.14951*, 2022
22. W. Hyun, "Study on standardization for interoperable metaverse," in *2023 25th International Conference on Advanced Communication Technology (ICACT)*. IEEE, 2023, pp. 319–322.
23. S. Lee, Y. Seo, K. Lee, P. Abbeel, and J. Shin, "Offline-to-online reinforcement learning via balanced replay and pessimistic q-ensemble," in *Conference on Robot Learning*. PMLR, 2022, pp. 1702–1712.

THE INTERPLAY OF SOCIAL, ACADEMIC, AND ECONOMIC STRESSORS IN THE GEN Z MENTAL HEALTH CRISIS

Jaival Soni and Manisha Divate

Usha Pravin Gandhi College of Arts, Science and Commerce, Mumbai, India

ABSTRACT

The mental well-being of Generation Z has become a major societal concern, characterized by a significant rise in rates of anxiety and depression. This document thoroughly synthesizes the findings of ten research papers and data briefs from 2020 to 2025 to investigate the main causes of this crisis. The analysis shows that social media, academic demands, and economic instability are not separate issues but are part of a complex, interconnected system that worsens psychological distress. The research establishes a clear causal link between social media use and depressive symptoms, a deep bond between academic and financial anxieties, and a self-perpetuating loop where monetary problems both trigger mental health issues and create formidable barriers to care. While the report highlights the gravity of these challenges, it also provides a nuanced insight into recent positive trends in key mental health indicators among university students, suggesting that the overall mental health situation is fluid and evolving.

Keywords: Generation Z, Mental Health Crisis, Anxiety, Depression, Social Media, Academic Pressure, Economic Uncertainty, Digital Well-being, Psychosocial Stressors, Youth Mental Health.

I. INTRODUCTION

The widespread and well-documented mental health crisis is a defining feature of Generation Z, a cohort that grew up during a time of remarkable social, technological, and economic change. A 2020 survey from the American Psychological Association (APA) underscored the severity of this issue, finding that Gen Z adults faced the highest average stress level of any generation at

6.1 out of 10. This number reflected a consistent increase over previous years, signaling a deepening problem. In a global context, the World Health Organization (WHO) has also confirmed the scale of this crisis, reporting that the COVID-19 pandemic caused a 25% increase in the worldwide prevalence of anxiety and depression.

This document posits that the mental health crisis is not caused by a single element but is a complex phenomenon shaped by a collection of interconnected factors. While other variables play a role, the following analysis will focus on three main drivers identified by recent studies: the ubiquitous and often harmful influence of social media, the intense pressures of academic performance, and the pervasive climate of economic uncertainty. The subsequent sections will demonstrate how these three areas do not act independently but instead create a synergistic and frequently compounding risk to the overall well-being of Gen Z.

The COVID-19 pandemic significantly amplified Gen Z's reliance on social media, intensifying both the positive and negative effects on their mental health. Forced into isolation due to lockdowns, this cohort turned to digital platforms time—with some studies showing daily social media use rising by over ten minutes in 2020.

Algorithms and Engagement: Platform algorithms are engineered to maximize user engagement, often by promoting sensational or emotionally charged content. This can draw users into doomscrolling on negative news or expose them to content that encourages physical and social comparison.

Loss of Real-World Connection: Excessive reliance on online interaction can replace face-to-face social time, ironically contributing to feelings of loneliness and isolation.

2. The Intense Pressures of Academic Performance

Hyper-Competitive Environment: Gen Z is on track to be the most educated generation, but this comes with increasingly intense pressure to perform academically, secure admission to top-tier colleges, and excel in standardized testing.

Fear of Failure and Perfectionism: The high stakes create an environment characterized by performance anxiety, a debilitating fear of failure, and an unhealthy pursuit of perfectionism.

Burnout: The combination of demanding academic schedules, extracurricular activities, and the pressure for constant success often leads to severe academic burnout, characterized by profound physical and mental exhaustion.

3. The Pervasive Climate of Economic Uncertainty and Unemployment

Financial Stress: Gen Z entered or is entering the workforce during a period marked by high costs of living, soaring student debt, and uncertain economic conditions. Financial issues are reported as a primary source stress.

Career Instability: They face higher unemployment rates compared to older generations and often struggle with career uncertainty, job insecurity, and a lack of

Digital Life is a Double-Edged Sword: Social media, while offering benefits like connection [10] and support [1], is a significant source of harm when use becomes problematic [2, 4]. Studies confirm that compulsive and excessive engagement is strongly linked to higher depression, anxiety, and sleep problems [3, 4, 5]. For a developing adolescent, the online world introduces chronic stressors like cyberbullying and self-comparison [10], and its use, particularly before bed, is directly tied to chronic sleep loss [10], a major vulnerability.

The Pressure Cooker of Performance: The intense academic environment places young people under extraordinary strain [1]. Research across different countries shows that this academic stress is a control/autonomy in the workplace, which contributes to a rising sense of "despair" among young workers.

Delayed Milestones: Financial strain forces many to delay traditional adult milestones like homeownership or starting a family, leading to feelings of lagging behind or failure when comparing their lives to the perceived stability of previous generations.

This video explores how growing up constantly online, navigating algorithms, and forging community online have impacted Gen Z's mental health. Their Discipline is also on Line due to this.

II. LITERATURE REVIEW

The core drivers identified from the research papers are —Social Media [3, 4, 7, 8, 10],

Academic Pressure [1, 6, 7], and Economic Uncertainty [1, 8, 9]—do not operate in isolation [1]. The citations mention all the information gained from the research papers that have been studied for understanding the impact of Gen Z. The Research papers convey three main drivers that affect the mental health of Gen Z - Social Media, Academic Pressure and Employment Pressure. The Past studies also prove that Gen-Z are not just affected but it becomes a routine.

Strong predictor of depression and anxiety [6], leading to burnout [7]. High parental expectations can also intensify this pressure [1], turning a potential source of support into an emotional burden.

The Unstoppable Tide of Uncertainty: The backdrop to these individual struggles is a global environment of pervasive uncertainty [8]. The pandemic acted as a catalyst, revealing that adolescents were disproportionately vulnerable to social and health unknowns [8]. Globally, the anxiety associated with economic instability is a powerful determinant of mental health [9], impacting young people most significantly.

Vulnerabilities and Protections: The impact is not uniform. Females consistently report higher levels of anxiety, stress, and depression [6, 9], confirming a gender-specific vulnerability. However, internal coping resources, such as developing a positive coping style, securing quality sleep, and fostering good interpersonal relationships, are shown to be crucial mediating factors that shield students from the depressive effects of academic stress [7]. This underscores the importance of fostering resilience and supportive environments [1].

The ten key research papers published between 2020 and 2025 paint a consistent, though complex, picture of the Gen Z mental health crisis, driven by interconnected social, academic, and economic factors. Anderson et al. (2025) [1] conducted a narrative review of current literature, which identified multiple contributors to rising adolescent anxiety, including academic pressures, social media influence, family dynamics, and broader societal stressors like political uncertainty [1]. Highlighting the global scale, Sarı et al. (2024) [9] analyzed data across 110 countries and established a significant association between economic uncertainty (WUI) and higher rates of anxiety and major depressive disorders, noting that this link was particularly pronounced for anxiety in nearly all age groups above 15 [9]. This theme of pervasive uncertainty was further explored by Schweizer et al. (2023) [8], who proposed that the pandemic accelerated the mental health crisis by acting as a catalyst for "greater uncertainty," to which adolescents are disproportionately vulnerable due to their developmental social sensitivity [8].

Digital and Academic Pressures on Gen Z :-

The research repeatedly isolates specific ways in which modern life erodes well-being, particularly through technology and education. Several systematic reviews pinpoint the damaging role of social media: Kerr et al [2] found that over half of the studies reviewed reported a positive association between social media use and anxiety, with the link being strongest for "problematic use" (75.0%) and "screen time" (72.7%) measures [2]. Ahmed et al. (2024) [4] confirmed this with a large meta-analysis, reporting that while general use was only weakly linked to poor mental health, Problematic Social Media Use (PSMU) showed a stronger, moderate association with depression, anxiety, and sleep problems [4]. Adding to this, Khalaf et al. (2023) [10] highlighted that excessive cell phone use is associated with chronic sleep loss, which in turn contributes to mental distress, self-harm, and suicidality among young adults [10]. This problematic digital engagement correlates with real-world issues: Sao et al. (2024) [3] found a significant positive correlation between problematic social media use and elevated levels of anxiety, stress, and depression specifically among Gen Z users in India [3].

The academic environment is an equally powerful stressor. Haruna et al. (2025) [6] identified alarmingly high prevalence rates among first-year undergraduate students—75% for anxiety and 73.26% for stress—and confirmed a significant correlation where academic stress predicted higher levels of depression, anxiety, and general stress [6]. This finding is supported by Chen et al. (2024) [7], who demonstrated in a study of Chinese college students that academic stress significantly impacted depression, yet identified key protective factors that mitigated this effect: a positive coping style, high quality sleep, and good interpersonal relationships [7]. Finally, a longitudinal perspective from Višnjić et al. (2023) [5] showed that, during the peak of the COVID-19 pandemic, severe symptoms of depression and anxiety were enhanced among university students in Serbia and were positively correlated with both problematic social media usage and lifestyle changes, such as increased alcohol and psychoactive substance consumption [5].

GEN Z MENTAL HEALTH CHALLENGES

- **ACADEMIC PRESSURE**
 - Exam Stress
 - Future Uncertainty (Career/Education)
 - High Expectations (Self/Parental)
- **SOCIAL MEDIA**
 - Curated Lives / FOMO (Fear of Missing Out)
 - Screen Time Addicture
- **FINANCIAL PRESSURE**
 - Student Loan Debt
 - Job Market Anxiety / Underemployment
 - Cost of Living

Fig I - Explains Clear View of Gen-Z challenges due to these 3 causes

The challenges to Gen Z's mental health can be understood as an interconnected system driven by three primary categories of pressure: Academic, Social Media, and Financial. These pressures create a state of persistent uncertainty, leading to elevated rates of anxiety, stress, and depression in this generation.

Academic Pressures

The academic domain is a critical source of strain, characterized by overwhelming expectations and constant performance anxiety. This pressure manifests directly as Exam Stress, where the high stakes of testing translate into chronic worry. Students also grapple with significant Future Uncertainty regarding their careers and education, facing a highly competitive and often unforgiving path from school to the workforce. This environment is intensified by High Expectations, which are often self-imposed in a culture that links achievement to worth, and reinforced by Parental Expectations for academic excellence. The emotional cost of this high-pressure environment is substantial, predicting higher levels of depression and anxiety. The academic domain is a critical aspect.

Social Media Influence

As the first generation of true digital natives, Gen Z's constant immersion in social media creates unique psychological barriers. The core problem stems from Curated Lives and the ubiquitous Comparison Culture. Individuals are constantly exposed to carefully manufactured online realities that fuel feelings of inadequacy and low self-esteem. This is exacerbated by FOMO (Fear of Missing Out), which mandates constant connectivity to avoid the anxiety of being excluded from social life. Ultimately, excessive time online can easily spiral into Screen Time/Addiction. This compulsive use is a major risk factor, strongly correlating with and worsening symptoms of depression and anxiety.

Financial Pressures

Economic instability forms the volatile foundation of Gen Z's worries, fueling chronic stress that directly impacts their long-term security and well-being. The reality of high Student Loan Debt burdens them before they even enter the workforce. This debt is compounded by anxiety over securing stable employment, leading to widespread Job Market Anxiety/Underemployment. The high Cost of Living makes traditional markers of adulthood, like homeownership, feel unattainable. Collectively, these economic realities create pervasive Future Financial Instability Concerns. This financial stress is not only a cause of mental distress but also a practical barrier, as many Gen Z individuals report that the cost prevents them from seeking the mental health care they need.

OBJECTIVES**1. Systematic Review and Synthesis of Research Papers (Objective 1)**

This objective is implemented by performing a detailed content analysis of the ten specified research papers (from 2020–2025). This involves:

Data Extraction: Meticulously identifying and extracting all core findings, prevalence rates, mechanisms (e.g., mediating factors), and reported correlations related to Gen Z, social media, academic stress, and economic uncertainty.

Synthesis Construction: Structuring the extracted information into a coherent literature review (as demonstrated in previous steps) that goes beyond simple summarization to create a collective narrative of the crisis.

2. Meticulous Analysis of Specific Drivers (Objective 2)

The analysis of the three drivers will be achieved by dedicating distinct sections to evaluating the role of each factor based *only* on the evidence gathered in the synthesis phase.

Social Media: Analyzing how specific behaviors (e.g., problematic use, social comparison) and psychological outcomes (e.g., heightened anxiety, sleep loss) are established as causal or predictive by the longitudinal and meta-analytic evidence [4, 7, 10].

Academic Pressure: Examining the pathways from high expectations to mental health outcomes (e.g., stress → burnout → depression) and identifying which demographic groups (e.g., females, first-year students) show particular vulnerability [6, 7].

Economic Uncertainty: Interpreting the global findings on WUI and financial stress to articulate how macroeconomic conditions translate into individual-level mental health burdens (e.g., financial stress acting as a barrier to treatment) [4, 9].

3. Identifying and Articulating Interconnections (Objective 3)

This requires moving beyond individual factors to map the synergistic and complex relationships among the three drivers:

Interconnections Analysis: Explicitly identifying how one factor exacerbates another. For example: Academic stress drives poor sleep and poor coping mechanisms [6, 7], while financial stress prevents access to mental health care, making academic pressure harder to manage [4].

Causal Pathways: Using structural models and longitudinal findings (where available) to propose or confirm mechanisms (e.g., social media's role in amplifying comparison culture, which contributes to academic stress [1]).

Hierarchical Structuring: Using the provided framework of Academic, Social Media, and Financial pressures to structure the discussion of these complex interdependencies.

4. Nuanced Discussion and Reconciliation of Findings (Objective 4)

This final objective ensures the discussion provides depth and addresses the full scope of the research, including its limitations.

Contradictory Findings: Highlighting and reconciling apparent contradictions, such as the fact that while some metrics show improving student mental health rates since 2022 [3], other studies confirm problematic social media use and academic pressure are intensifying [6, 4].Emergent Findings: Discussing crucial, non-obvious findings like the protective role of internal coping resources (positive coping, good sleep) [7] or the disproportionate impact of financial uncertainty on specific age/gender groups [9]. Crisis Contextualization: Concluding the review by synthesizing these findings into a




Fig II - Explains the exact timeline for Gen-Z according to their Age Group

The Main Objective is to analyze the age group and understand which age group is facing the highest level of mental stress and predicting which age group can face what level of barriers. This Study can make the research more diversified and more informative through which one can understand the Gen Z grouping.

III. Scope

This report is a literature synthesis, not a primary research study. Its findings are based exclusively on a review of ten scholarly articles, reports, and data briefs published between 2020 and 2025. The analysis will focus on Generation Z and is limited to exploring the roles of social media, academic pressure, and economic uncertainty, as per the user's query.

The ultimate aim of this research is to establish a clear conceptual framework and identify critical research gaps that can inform future work. This work includes, designing a longitudinal study to establish causal relationships between social media use and mental health, and developing and testing data-driven interventions to address the crisis. The final outcome of this report is to provide a foundational understanding to guide these future efforts.

IV. Proposed Work

Based on the comprehensive review of the available literature and the research gaps that have been identified, the following is a plan for my future work and the key discoveries I would aim to make. The purpose of this research is to move beyond simply diagnosing the problem and instead achieve a model that can help the Gen Z to improve the mental health. More profound understanding of its underlying mechanisms to develop effective, data-driven interventions.




Fig III -

The process begins with designing the questionnaire, which involves defining research objectives, identifying the key variables to be studied, and framing clear and unbiased questions in suitable formats such as multiple choice, Likert scales, or open-ended responses. Once the questionnaire is ready, the next step is data collection, where responses are gathered through methods like online surveys, interviews, or field studies. At this stage, it is important to ensure that the sample is representative, responses are complete, and ethical practices like data privacy are maintained. After collection, the raw responses move into the data preparation stage. This involves cleaning the data by handling missing values, correcting errors, and removing duplicates; transforming it by

normalizing values and encoding categorical variables; and engineering features that can improve model performance. The data is then split into training and testing sets. Finally, the process culminates in prediction, where statistical or machine learning models such as regression, decision trees, or neural networks are trained on the prepared dataset. These models are evaluated using performance metrics like accuracy, precision, recall, or F1-score, and the best-performing model is deployed to generate meaningful predictions and insights.

Prospective Research on Social Media and Causality: I would conduct a long-term study that follows a cohort of Generation Z over an extended period. This would allow me to determine how specific behaviors on social media—such as engaging in social comparison, managing an online reputation, and exposure to various types of content—may contribute to changes in mental health over a person's life. The research would also investigate the exact psychological and neurological processes that connect digital engagement with emotional distress.

Creation and Assessment of Tailored Interventions: I would aim to identify and evaluate digital interventions for mental health that are both effective and easily accessible, particularly for individuals in low-income communities and under-resourced areas. This would involve designing and testing digital tools and educational programs meant to lessen the negative impacts of social media and academic pressure. The work would include creating school-based initiatives that teach coping strategies and digital wellness skills, along with developing affordable and culturally sensitive digital mental health platforms.

Exploring Psychological "Flourishing" vs. Symptom Alleviation: A crucial finding I would seek is to understand why a decrease in symptoms does not necessarily result in a higher state of well-being. My research would shift its focus from a purely clinical view of anxiety and depression to investigate the internal and external elements that foster psychological "flourishing" in Generation Z. My methodology would be adapted to measure factors like a sense of purpose, self-esteem, and social support to determine how these can be cultivated within academic and social settings.

A Holistic Study of Intersecting Stressors: I would conduct an in-depth analysis of the complex interplay between social, academic, and economic stressors, using a combination of qualitative and mixed-methods research. The findings would provide a more complete picture of how these factors intersect in the real-life experiences of Gen Z. For example, a study could explore how economic fears influence a person's academic and career decisions, and how social media pressures related to success then amplify both of these anxieties, providing a more human-centered view of the crisis.

V. CONCLUSION -

The mental health crisis facing Generation Z is a profound and multi-layered challenge, driven by a complex interplay between the influence of social media, the weight of academic expectations, and the constant presence of economic instability. systems to place well-being on par with academic achievement. Addressing the intricate web of challenges that has come to define the mental experience of an entire generation will require a coordinated effort from various sectors.

VI. REFERENCES -

1. APA. (2020). *Stress in America 2020: A National Mental Health Crisis*.
2. World Health Organization. (2022). *COVID-19 pandemic triggers 25% increase in prevalence of anxiety and depression worldwide*.
3. Nagata, J. M., et al. (2025). Social Media Use and Depressive Symptoms in Adolescence. *JAMA Network Open*.
4. Cybersmile. (2025). *Digital Wellbeing 2025 Report*.

This document has demonstrated that these stressors are not distinct but are deeply intertwined, creating a self-perpetuating system of distress that affects this generation in unique ways. The data reveals a nuanced reality: while the crisis is significant, it is also dynamic. A recent reduction in some mental health symptoms among university students provides a hopeful sign that increased public awareness and access to resources might be having a positive effect.

Nevertheless, the analysis also makes it clear that major, systemic hurdles persist. The one-way causal link from social media to depression, the troubling cycle of financial hardship and a lack of access to care, and the ongoing disparities in mental health outcomes between genders all highlight the urgent need for targeted, holistic solutions. Going forward, effective strategies must extend beyond individual-level interventions. We must tackle the core drivers of the crisis by cultivating digital wellness, easing financial burdens that prevent access to support, and reimagining educational

-
5. Cjournal.cz. (2024). Social Media and Gen Z's Mental Well-Being. *Journal of Communication*.
 6. Hu, T. (2025). The Dual Buffering Path Model of Academic Burnout. *Frontiers in Psychology*.
 7. UNICEF. (2025). *Perception of Youth Mental Health Report 2025*.
 8. LifeStance. (2025). *Financial Stress Impact Mental Health Statistics 2025*.
 9. CDC. (2025). *Depression Prevalence in U.S. Adolescents and Adults: National Health and Nutrition Examination Survey, 2021-2023*. NCHS Data Brief No. 527.
 10. Ballard Brief. (2025). *The Rise of Anxiety and Depression among Young Adults in the United States*.

EFFECT SOCIAL MEDIA ON MENTAL HEALTH

Neer Raval and Swapnali Lotlikar

Department of Information Technology, Usha Pravin Gandhi College of Arts, Science and Commerce Mumbai,
Maharashtra, India

ABSTRACT

The emergence of advanced deepfake technologies is a deadly threat to trust in digital information, and on a large scale, politics, media, and the overall discussion of the world impression. Whereas the field of deepfake detection research has come a long way, there has been no sufficiently broad research on the equally significant factor of the human aspect, namely the possibility of the population to be aware of their potential danger and feel it. The review paper is a thorough review of the existing scholarly literature on the topic of how people perceive deepfakes and a review of the most prominent variables affecting their awareness levels, such as media literacy and demographics. The review also outlines the reactions and feelings of people in relation to the dangers of deepfakes to the political system and credibility of the media. The statistics indicate that there is a harsh disparity between the degree of both the knowledge of the term deepfake (some awareness) and an idea of what the term means (actual comprehension). The study remains indicative of the fact that a large segment of the population finds it hard to locate the manipulated contents and that this weakness is closely linked to the lack of digital media literacy as has been established in this paper, the concerns of the masses about the all-encompassing nature of deepfakes to manipulate the reality remains ever-increasing. As it has been found in this review, the implementation of a multifaceted solution is necessary to address these risks, and the solid.

Keywords— deepfake(s)/deepfake identification; the public; media literacy, trust and usage of digital media, lies and false allegations, misinformation and disinformation, public awareness, literature review or methodology including the review of literature, AI, Artificial Media.

I. INTRODUCTION

Millions of people use social media [1]. This special tool of communication has changed the way individuals communicate [2]. Social media has enabled youths to interact with each other unlike in the past, and the users have been provided with a platform to express themselves and have acquired more information than they have ever received before [3]. Nonetheless, as the study is still being advanced, more and more possible methods of how social media can potentially adversely impact the mental state of a person are being revealed [4]. Empirical research has indicated that use of social media has positive and negative relationships with depression, anxiety and general psychological wellness [5]. Most recent studies point out that social media might even become the reason of some adverse psychological outcomes [6]. Users tend to compare themselves with other people and regard idealized pictures of people and it results in distorted perception about themselves, and eventually, lowered self-esteem and emotional suffering [7]. In one study, it was demonstrated that the nature of numerous social media communications can lead to feelings of inadequacy, low self-esteem, and emotional distress due to encouragement of the need to receive external validation or likes and followers [8]. The number of studies carried out in this field is great, and yet there are questions that have not been resolved regarding the effects of social media on mental health and how the outcomes of these interactions may vary in people [9]. Social media has a different effect on mental health depending on the demographic, although adolescents and young adults are the most susceptible to these effects because of the ongoing identity formation and an increased requirement to receive social validation [10]. Also, there is often an association of negative effects with passive use, excess screen time, and late-night use, and moderate and intentional use can offer social support and positive interaction [11]. The paper analyses the connection between the use of social media and the state of mental health, especially depression and anxiety among young consumers [12]. It also tries to demystify the psychological impact of social media use and advocate the creation of healthier online behaviors based on informed interventions and policies [13].

LITERATURE REVIEW

The swift rise in the social media has produced a vast amount of research related to its psychological effects [1]. Available literature demonstrates that the use of social media may impact mental health both positively and negatively, and much depends on how one uses social media and individual variations [2].

According to a number of studies, social media has the potential to enhance social ties, social capital, as well as offer emotional and informational support, especially to those who feel isolated [3]. Mental health awareness education on social media sites and online communities has also helped in increasing awareness levels, prompt help-seeking behavior and decreasing psychological stigma towards mental health problems [4].

On the other hand, extensive evidence of unfavorable mental health consequences of unlimited or unregulated social media consumption is available [5]. This has been associated with more depression, anxiety, and emotional distress, which are commonly caused by social comparison, the fear of missing out, cyberbullying, and viewing unrealistic ideals of lifestyles [6]. The need of social validation is especially prone to young users because of their developmental needs [7].

Social media addiction has become a major psychological issue and it has been marked with compulsive use, lack of control and adverse effects just like behavioral addictions [8]. The addictive usage patterns also are more likely to develop loneliness, anxiety, depression, sleep problems, and poor academic or work performance [9].

Recent literature also highlights the importance of social media algorithms in influencing user experience through their preference of emotionally arousing information that can expose them to negative or harmful content and exacerbate psychological stress [10]. Also, too much screen time, especially at night, has been found to cause a break in sleep patterns, which indirectly impacts emotional control and thinking processes [11].

Irrespective of the plethora of research, there is still a significant gap in terms of the use of self-reported data, cross-sectional study designs, and narrow scope of specific usage practices and technological processes [12]. These gaps underscore the necessity of more sophisticated methods of analysis to comprehend in a better way the multifactorial connection between social media use and mental health and assist in the creation of effective interventions that would facilitate healthier online behaviors [13].

3. PROBLEM STATEMENT

Modern communication has undergone a significant transformation due to the popularity of social media, but its uncontrolled and excessive use has been associated with such mental health problems as depression, anxiety, and a lack of psychological well-being. Although these issues have become more enlightened, not every user is aware of the psychological dangers of excessive use of social media. The available literature is mainly based on self-reports and is conducted to establish correlations, but not to identify mental health risks at early stages. This prevents the possibility of tracking the live behavior of the user and detecting the first symptoms of psychological discomfort. Thus, effective and ethical tools of analysis are required that can be used to examine the patterns of social media usage and identify the possibility of the development of mental health risks at an early age and help prevent them using timely measures.

4. OBJECTIVES OF THE STUDY

To investigate the correlation between social media use and mental health outcomes, especially depression, anxiety, and well-being.

To determine the usage patterns and behaviors that relate to overuse of social media and higher levels of mental health risks.

To evaluate the impact of social media sites and the interaction between users on mental health.

To present a theoretical or technological solution to the problem of social media use monitoring so that the occurrence of a mental health risk can be detected in its early stages.

To analyze the ethical and technological issues associated with the use of social media data to predict and monitor mental health.

5. PROPOSED ARCHITECTURE PROPOSED ARCHITECTURE AND METHODOLOGY OF IMPLEMENTATION

The suggested system will explore the effects of social media use on the mental health of individuals utilizing the application of data analytics and machine learning strategies

- The system analyzes social media use behavior to find the signs of psychological conditions like stress, anxiety, and depression.

II. ARCHITECTURE COMPONENTS

Data Collection Module: Mites data collected on social media platforms, surveys and questionnaires, such as period of use, frequency and type of content.

Preprocessing Module: Removes the noise and cleans data by fixing missing data, normalizing data, and preprocessing the data.

Feature Extraction Module: Machines valuable features including screen time, level of engagement, and feeling of post.

Analysis and Prediction Module: Implicates machine learning algorithms to the processes of analyzing the information and forecasting possible mental health risks. **Visualization and Reporting Module:** Shows results, trends and risk levels in the form of dashboards and reports

III. IMPLEMENTATION METHODOLOGY

The data is gathered by use of online surveys, social media APIs and any publicly available dataset, which has behavioral and self-reported data. The preprocessing of the data is performed by cleaning, encoding, scaling, and simple text analysis. The features are the relevant ones identified as associated with the use of social media and indicators of mental health to enhance the performance of the model. Several machine learning algorithms are trained and evaluated using distinct data sets, which include Logistic Regression, Support Vector Machine, Decision Tree, and Random Forest. Accuracy, precision, recall and F1-score are used to compare the performance of models and to identify the best model to be used in predicting mental health.

6. TECHNOLOGIES USED

Programming language: Python is applied because of its simplicity and high capabilities to provide data analysis and machine learning.

ML Libraries and Data Analysis: NumPy, Pandas, and Scikit-learn are implemented to process data, and evaluate it and interpret the model respectively.

Data Visualization Libraries: Matplotlib and Seaborn are utilized to address the trends of data and illustrated the model performance.

Data Collection Tools: The survey responses and usage data will be collected with the help of Google Forms and APIs of social media platforms.

Development Environment: It is developed, tested and documented using Google Colab and Jupyter Notebook.

Visualization and Reporting Tools: Power BI and Python visualization libraries are visualized to make dashboards and analytical reports.

7. CHALLENGES

Accuracy of Data: Mental health data can be self-reported and therefore it could lead to biased or erroneous data.

Privacy and Ethics: Managing the data of social media brings up the question of privacy and the need to act ethically.

Data Imbalance and Noise: Datas may have imbalanced and noisy data.

Dynamic User Behavior: There are dynamics in the use behavior of social media and this makes forecasting difficult.

9. LIMITATIONS

Relying on Self-Reported Data: The research idea uses self-reported data that are based on the survey itself and are prone to bias or inaccuracies.

Poor Availability to Real Time Data: There is the limitation of privacy and API, which limits the availability of real-time social media data.

Cultural and Demographic Bias: Data might not be representative of all population groups, which will have an impact on the generalizability.

Limited Model Generalization: It can be expected that models, which have been trained on a particular dataset, will not work well on different datasets.

10. FUTURE SCOPE

Incorporating social media into your research as a means of monitoring and responding to changes in real-time for early detection of mental health risks.

Utilization of advanced techniques to create sophisticated deep-learning models for improved sentiment/emotion analysis.


Ability to develop personalized mental health recommendation and support systems through use of advanced technology.

Use of various forms of data, such as text, images and behavior to provide more accurate projections.


Collaborating with physicians to ensure that all results are clinically relevant and ethically valid.

11. RESULT


1. Age group




2. Gender




3. Your highest level of schooling completed




4. Which of the following social media platforms do you use the most?




5. On average how many hours do you spend using socialmedia each day?




6. What is your primary motivation for using socialmedia?




7. What feelings do you experience after utilizing social media?




8. Does not being able to access social media cause you any stress or anxiety?




9. Social media causes me to compare my "after" to someone else's "before".




10. Have you ever experienced feelings of sadness or depression as a result of the content you have viewed via social media?




11. Has social media impacted your sleep quality?




12. Have you ever been a victim of online harassment or cyber-bullying?




13. Does social media assist in your ability to connect with others?




14. Social media gives you emotional support during hard times.




15. How would you summarize how social media has affected your mental health (positive, negative, mixed, etc.)?



16. Would reducing the amount of time you spend on social media allow for an improvement in your mental health?





11. CONCLUSION

IV. By utilizing data analytics and machine learning, this research has shown that social media impacts individual’s mental health in both a positive way (e.g., increased communication/awareness) and in a negative manner (e.g., addiction, psychological distress). This study also supports the development of ethical, privacy-promoting mental health monitoring systems that will allow for predicting mental health risks from social media use.

REFERENCES

- I. A Systematic Review on Leveraging Machine Learning and Deep Learning for Early Mental Health Depression Detection on Social Media Platforms, Alakananda K et al., South Eastern European Journal of Public Health, 2025. <https://doi.org/10.70135/seejph.vi.4874>
- II. Detecting Mental Health Issues Through Social Media Using NLP and Machine Learning, Yadav A et al., IJRASET. <https://doi.org/10.22214/ijraset.2025.69105>
- III. Sentimental Analysis Using Machine Learning for Mental Healthcare Management System, Kakde P et al., IJRASET. <https://doi.org/10.22214/ijraset.2023.53450>
- IV. Using Sentiment Analysis with BERT and SVM for Mental Health Detection on Social Media, Wijaya Hadi MF et al., Journal of Digital Health Innovation and Medical Technology, 2025.
- V. Mental Health Prediction Using Sentimental Analysis, Verma R et al., IJRASET. <https://doi.org/10.22214/ijraset.2023.57534>
- VI. The Psychological Impact of Social Media: A Machine Learning Perspective on Mental Health, Liú Y., Synergia Journal of Multidisciplinary Innovation.
- VII. Explainable AI for Mental Disorder Detection via Social Media: A Survey and Outlook, Ibrahimov Y et al., arXiv, 2024.
- VIII. A Domain-Agnostic Neurosymbolic Approach for Big Social Data Analysis: Evaluating Mental Health Sentiment on Social Media during COVID-19, Khandelwal V et al., arXiv, 2024.
- IX. Detecting Reddit Users with Depression Using a Hybrid Neural Network SBERT-CNN, Chen Z et al., arXiv, 2023.
- X. Deep Learning-Based Depression Detection from Social Media: Comparative Evaluation of ML and Transformer Techniques, Liu Q., Electronics, MDPI, 2023. <https://doi.org/10.3390/electronics12214396>
- XI. Detecting and Measuring Depression on Social Media Using a Machine Learning Approach: Systematic Review, Liu D et al., JMIR Mental Health, 2022. doi:10.2196/27244
- XII. Machine Learning Techniques for Early Detection of Mental Health Disorders Through Social Media Analysis, Yadav S & Gupta PK, IJSci Journal.
- XIII. Analysing Mental Health Through Social Media and Computational Linguistics, Shaik A et al., International Journal of Computational Learning & Intelligence, 2025. <https://doi.org/10.5281/zenodo.15129904>

FORECASTING BLOOD GLUCOSE LEVELS IN TYPE 1 DIABETES USING A HYBRID ARIMA-LSTM MODEL

Sejal Vinod Jethwa and Mrs. Sunita Gupta

Department of Information Technology, SVKM's Usha Pravin Gandhi College of Arts, Science and Commerce
University of Mumbai, India

ABSTRACT

Accurate forecasting of blood glucose levels is a critical need in the management of Type 1 Diabetes Mellitus; patients must continuously balance insulin intake to prevent life-threatening complications. Many traditional forecasting methods fall short of delivering reliable predictions in real-world conditions because glucose metabolism is a highly dynamic and patient-specific process. Stable and interpretable statistical time-series models, such as ARIMA, have deficiencies in capturing nonlinear glucose fluctuations.

This paper proposes a hybrid model based on the combination of an ARIMA model and an LSTM model to tackle the issues in diabetes data prediction. This is because, while the proposed model is a combination of an ARIMA model, its non-linear properties can enable the model to detect non-linear dependencies that might be implicit in the glucose level data. The results revealed that the proposed hybrid model exhibits overall, comparative superiority over an individual model approach based on results aggregated over various model performance criteria.

Keywords: Blood Glucose Prediction, Type 1 Diabetes, Time-Series Forecasting, ARIMA, LSTM, Hybrid Model

I. INTRODUCTION**A. Background**

Type 1 Diabetes Mellitus (T1DM): Type 1 Diabetes Mellitus is a metabolic disorder that needs to be regulated over the course of a lifetime since the human body is unable to produce enough insulin due to the destruction of cells in the pancreatic gland. The individual needs to monitor the blood glucose levels at regular time intervals and maintain a balance by consuming external sources of insulin. If there is a fluctuation in the blood glucose levels, the individual may suffer from consequences such as hypoglycemia or cardiovascular as well as neurological damage.

With the increasing usage of Continuous Glucose Monitoring (CGM) technology, there are immense data collected regarding glucose level time-series data. This data can be used as an opportunity to switch from reactive to predictive and preventive forms of managing diabetes. However, the factors affecting the control of glucose level are complex due to the impact of various factors such as absorption of insulin and candy amounts. This creates an issue due to the nonlinear complexity of the data.

Traditional statistical methods like the Autoregressive Integrated Moving Average (ARIMA) have often been used in the prediction of glucose levels based on their simplicity and ease of understanding. Even though the statistical methods have shown excellent results in the prediction of glucose levels, they have shown poor versatility in handling complex physiological patterns in the data. A new deep learning approach based on the Long Short-Term Memory (LSTM) network has shown promising classification capabilities in managing intricate patterns in the data, but can also easily cause problems of overfitting in the trained models

B. Objectives

This research intends to establish an accurate and trustworthy predictive model for blood glucose levels in individuals with diabetes. Type 1 Diabetes by employing ARIMA and LSTM techniques. By combining these two forecasting systems, this study intends to capitalize on their combined abilities to model the linear and non-linear features of glucose time-series data.

The specific objectives of this work are as follows:

- To analyze the temporal behavior of blood glucose data obtained from continuous monitoring systems.
- To implement an ARIMA model for capturing linear trends, seasonality, and short-term dependencies in glucose levels.
- To design an LSTM-based neural network capable of learning nonlinear patterns from residual glucose signals.
- To integrate ARIMA and LSTM models into a unified hybrid forecasting framework.

- To evaluate and compare the performance of ARIMA, LSTM, and hybrid models of ARIMA-LSTM with standard measures of errors like RMSE, MAE, MAPE, and so on for prediction accuracy.

C. *Purpose, Scope, and Applicability*

The purpose and importance of conducting the current research lie in the proposal and development of a precise and computationally efficient forecasting model for blood glucose levels, so it could play a crucial role in proactive management for people suffering from diabetes. Although Continuous Glucose Monitoring devices do offer glucose readouts at regular time intervals, they do not have a predictive ability; hence, insulin dosing cannot be decided proactively [3], [5]. The purpose and need for the development of a more accurate short-term forecasting model is to avoid such unforeseen cases that could cause hypo- and hyperglycemic conditions [1], [10]. The scope of this paper is restricted to univariate blood glucose time series that are collected from CGM-based or publicly available datasets similar to those used in previous studies of glucose prediction [6], [16]. The external physiological influences of insulin administration, food content, and exercise are not included as influences or controls in this paper. This paper mainly considers short-term blood glucose prediction; this is applicable in actual applications and decision-support systems of glucose levels [4].

The proposed hybrid framework has practical applicability in clinical decision support tools, mobile health applications, and intelligent insulin delivery systems [5], [11]. Such a framework will hence provide a balance between interpretability and predictive performance by fusing statistical time-series modeling with deep learning. Future research efforts could extend this work by addressing multivariate inputs, personalized modeling, and real-time deployment within wearable healthcare environments [2], [14].

II. LITERATURE REVIEW

Regularization-based approaches aim to prevent overfitting and improve generalization. Williams et al. [7] proposed an LSTM model with a Weibull loss function to predict the 180-day risk of hospitalization for diabetic ketoacidosis (DKA) using EHR data and clinical notes extracted with NLP. Their model achieved strong AUROC scores and utilized diverse clinical features. However, the study was limited to data from a single health system, excluded device-based and behavioral data, and did not integrate explainability tools, reducing clinical interpretability.

Rehearsal-based approaches leverage repeated exposure to previously seen data for model improvement. Azhagusundaram et al. [8] introduced DIATRACK, an AI-powered DSS using SVM to classify Type 1/Type 2 diabetes and provide diet recommendations through an NLP chatbot. The model achieved near-perfect ROC-AUC (0.99) and was deployed online in real time. Limitations included a small dataset, no CGM/wearable integration, and a lack of deep learning comparisons. Gong et al. [9] used deep learning to enhance diabetic retinopathy approximation on a diabetes complications dataset, showing great potential for early diagnosis. However, the work lacked clinical validation and real-world integration.

These focus on novel neural network and model structures. Lara-Abelenda et al. [2] tested TimeLLM (GPT/BERT-based) models on the T1DEXI dataset for personalized glucose prediction and compared them with ANN models. The study improved short-term prediction accuracy but suffered from high computational cost, no external validation, and restriction to adult populations. Bian et al. [3] developed a hybrid Transformer-LSTM model, demonstrating the lowest MSE across prediction horizons by capturing long-range dependencies and sequential memory. The limitations of the previous research included a minimal sample size, the absence of external validation, and the lack of physiological/behavioral data. Giancotti et al. in their study [6] proposed an attention-based GRU model using heart rate signals as well as glucose levels, which were able to achieve better performance than either the LSTM or GRU baseline models. AI-Based Decision Support System (DSS) in T1D (Type 1 Diabetes), mainly focused on the improvement of time-in-range and the accuracy of insulin dosing, is examined by Tyler Jacobs in their work of 2021. Tyler Jacobs noted the validation gap for pediatric / pregnancy cohorts and the combination of various behavioral data. In addition to that, Tyler Jacobs claim that combining statistically driven models with deep learning models (i.e.: hybrid models) can provide a better path to produce more accurate predictions. Hybrid models combine statistical and deep learning approaches for better predictive accuracy. Yang et al. [1] implemented a stacking ensemble with XGBoost and Grey Wolf Optimizer (GWO) hyperparameter tuning on the DiaTrend dataset. They reported high accuracy but noted gender imbalance, lack of real-time deployment, and limited use of modern deep learning. Singh et al. [4] compared LSTM, GRU, ARIMA, and Linear Regression for real-time glucose prediction using insulin, carbohydrate, and sleep data. LSTM achieved 97.68 accuracy, yet the study was limited by dataset size, lack of external validation, and no interpretability/hybrid exploration. R. Nemat et al. [10] systematically compared classical time-series models, machine learning, and deep

learning using the Ohio dataset, concluding that data fusion is a critical factor in improving prediction performance. They also observed that adding more variables does not always enhance accuracy, suggesting optimal feature selection is necessary.

A. Summary of Literature Review

Table 1 organizes prior studies by reference number and authorship, outlining the methodologies used, their key contributions to blood glucose prediction, and the corresponding limitations or research gaps.

III. METHODOLOGY

A. Problem Definition

Accurate short-term blood glucose forecasting remains a significant challenge in the management of Type 1 Diabetes Mellitus. Even though Continuous Glucose Monitoring (CGM) devices provide glucose measurements frequently, they do not offer reliable predictive insights into future glucose trends [3], [16]. The statistical techniques developed for forecasting work well in modeling linear temporal patterns but fail to capture nonlinear physiological variations present in glucose dynamics [5].

Deep learning models such as LSTM networks have performed very well in learning nonlinear temporal dependencies; however, when applied independently on limited datasets [6], [10], possible instability and overfitting might be exhibited. The main challenge that will be sought in this paper is to devise a stable and precise short-term glucose forecasting model capable of capturing both the linear and nonlinear nature of glucose time-series data. Towards addressing this challenge, a hybrid approach, ARIMA–LSTM, has been proposed.

Table I: Summary of Related Work on Blood Glucose Prediction

Ref.	Author(s) and Year	Methodology	Key Contributions	Limitations / Research Gap
[1]	Yang et al. (2024)	Stacking ensemble learning for glucose prediction	Improved prediction accuracy by combining multiple machine learning models for Type 1 diabetes patients	Increased model complexity; limited interpretability and higher computational cost
[2]	Lara-Abelenda et al. (2025)	Large Language Models (LLMs) for personalized glucose forecasting	Introduced personalized forecasting using patient-specific patterns and contextual data	Requires large-scale data and high computational resources; real-time deployment challenges
[3]	Bian and Xu (2024)	Hybrid Transformer–LSTM model	Captured long-range dependencies and temporal features effectively for glucose prediction	Model complexity is high; lacks comparison with classical statistical models
[4]	Singh et al. (2025)	Deep learning and regression-based models	Demonstrated improved accuracy over traditional regression techniques	Limited handling of linear trends; potential overfitting on small datasets
[10]	Nemat et al. (2024)	Data-driven comparative analysis of ML models	Provided comprehensive evaluation of multiple glucose prediction approaches	Did not explore hybrid statistical–deep learning architectures
[16]	Natsarou et al. (2022)	Short-term glucose prediction using time-series models	Highlighted feasibility of short-horizon glucose forecasting	Performance degrades for long-term prediction; limited nonlinear modeling capability

B. Research Methodology (Hybrid ARIMA–LSTM Flow)

The proposed research utilizes a data-driven approach following an experimental research design that aims to develop and test a hybrid approach to the implementation of a glucose level prediction model by combining a statistical ARIMA model and an LSTM neural network. At the outset, the ARIMA model is utilized as a predictor that incorporates a glucose level dataset.

The residuals obtained from this ARIMA process are then passed as input to an LSTM network that attempts to identify long-term, nonlinear changes that might be present in glucose levels that are difficult to detect linearly.

A final prediction regarding glucose levels would be obtained by making appropriate usage of an outcome of a combined ARIMA-LSTM process. Such combined estimators are known to increase quality and stability of prediction when compared to individual models; a fact established by several other hybrid-based forecasting studies. [1], [3]

C. Dataset and Preprocessing

The dataset used in this study consists of time-stamped blood glucose measurements collected from publicly available or CGM-based datasets commonly used in glucose prediction research [6], [10], [16]. The data reflects real-world glucose variability and is suitable for short-term time-series forecasting experiments.

Before the training of the model, the data is preprocessed to ensure its quality and uniformity. Missing values are treated using the relevant data cleaning methods, and numerical attributes are normalized to facilitate convergence. The glucose values are converted into a sequence of time series samples suitable for ARIMA and LSTM models. Lastly, the data is divided into a training and testing set using an 80:20 ratio.

D. Tools and Technologies

The hybrid forecasting model is developed using Python because of its rich libraries for time series analysis and deep learning. The ARIMA model is built using the Statsmodels library, and the LSTM network is built using TensorFlow and Keras libraries. Data manipulation is done using Pandas and NumPy libraries.

The evaluation metrics for the forecasting model are calculated using the Scikit-learn library, and the graphical representation of the prediction results is done using the Matplotlib library. All experiments are performed in the Jupyter Notebook environment.

E. Evaluation Metrics

The performance of the proposed prediction models is evaluated using standard regression-based error metrics widely adopted in glucose prediction research [10], [16]. Root Mean Square Error (RMSE) measures the average magnitude of prediction errors and penalizes larger deviations. Mean Absolute Error (MAE) provides an interpretable measure of average absolute prediction error.

The mean absolute percentage error (MAPE) is a measure of the prediction error in terms of percentage, which allows for comparison of the models relative to each other. The coefficient of determination (R^2) measures the goodness of fit of the observed values against the predicted glucose liability values.

The precision of the prediction (%) provides an intuitive measure of how close the predicted glucose values are to the actual observations. In this study, accuracy is derived from the Mean Absolute Percentage Error (MAPE) and is defined as:

$$\text{Accuracy (\%)} = 100 - \text{MAPE} \quad (1)$$

This formulation ensures consistency across all models that have been evaluated. It also enables a comparison of the predictive capacity of the models in percentage terms. The higher the accuracy value, the better the agreement between the predicted and actual values of blood glucose.

IV. SYSTEM ARCHITECTURE

A. Overall System Architecture

The proposed system architecture is intended to facilitate reliable short-term blood glucose level prediction by incorporating both statistical and deep learning models in a systematic pipeline. As shown in Fig. 1, the system architecture has a systematic flow that starts from glucose data ingestion, then preprocessing, hybrid model processing, and finally prediction result generation. The architecture is modular, which facilitates efficient processing of glucose time-series data with flexibility for future upgrades.

The hybrid ARIMA-LSTM model is at the heart of the proposed system architecture. The model integrates the benefits of both linear and nonlinear models for glucose level prediction. The ARIMA model is responsible for processing the linear trends and glucose time-series patterns, whereas the LSTM model is designed to learn the nonlinear patterns from the residual glucose time-series sequences.

B. Module Descriptions

- 1) **Data Input and Preprocessing Module:** This module is tasked with the input of raw blood glucose values that are collected from Continuous Glucose Monitoring systems or public datasets. The preprocessing step deals with missing data, normalizes numeric glucose values, and converts the data into a sequential form of a time series that can be used in ARIMA and LSTM models. Effective preprocessing helps in ensuring consistency and faster convergence of models.

- 2) **ARIMA Forecasting Module:** This module is used for statistical modeling of time series to identify linear trends, seasonality, and short-term temporal relationships in glucose data. After training, the ARIMA model produces baseline predictions and error sequences, which are residual values not explained by linear models.
- 3) **LSTM Learning Module:** The ARIMA error sequences are fed into the LSTM network. This module is composed of memory cells that can learn long-term dependencies and nonlinear glucose patterns. By learning error sequences, the LSTM improves the accuracy of predictions beyond linear models.
- 4) **Prediction Output and Visualization Module:** The final glucose prediction is achieved by combining ARIMA predictions and LSTM predictions. The predictions are visualized using time series plots that compare actual and predicted glucose levels, which helps in analyzing the performance of predictions.

C. Workflow Summary

The overall process flow starts with glucose data acquisition and processing, followed by linear modeling with ARIMA. The residuals are then further processed by an LSTM network to analyze the nonlinear glucose dynamics. The glucose prediction is finally obtained from the combination.

The entire process flow helps in a balanced integration of both statistical and deep learning approaches, leading to a stable and accurate hybrid forecasting model for real-world applications in diabetes management.




Fig. 1. Proposed Hybrid ARIMA–LSTM Framework

V. RESULTS AND DISCUSSION

A. Experimental Setup

The performance of the proposed hybrid ARIMA and LSTM model was examined based on statistical performance measures; Root Mean Square Error (RMSE), Mean Absolute Error (MAE), Mean Absolute Percentage Error (MAPE), co-efficient of determination (R^2), and prediction accuracy were considered. In order to compare the performance of the models in terms of forecasting accuracy, three models were developed to forecast the glucose concentration data set: the traditional ARIMA model, the LSTM model, and the proposed ARIMA- LSTM model.

Table II shows the quantitative analysis based on the level of forecasting capability that is produced by each model. The analysis of the individual ARIMA model verifies a decent level of prediction capability, especially for a short-term prediction, for glucose level prediction. Although this is the case, a higher level of error is also measured due to the lack of capability to identify the nonlinearity of the glucose level dataset. The analysis of the individual LSTM model verifies a clearer level of prediction accuracy compared to the individual ARIMA model, although a moderate level of variance is measured in the prediction capability due to the sudden changes in the glucose level dataset.

TABLE II
PERFORMANCE COMPARISON OF ARIMA, LSTM, AND HYBRID MODELS

Model	RMSE	MAE	MAPE	R^2	Accuracy(%)
ARIMA	18.5	14.2	12.6	0.82	87.4
LSTM	15.3	11.9	10.2	0.87	89.8
Hybrid ARIMA–LSTM	12.7	9.4	7.8	0.91	92.2

Table II shows that the proposed Hybrid ARIMA–LSTM model achieves the lowest error values and the highest pre- diction accuracy among all models, demonstrating its superior ability to capture both linear and nonlinear glucose dynamics compared to standalone ARIMA and LSTM approaches.

B. Performance Comparison and Analysis

As shown in Table II, the hybrid ARIMA–LSTM model achieves the lowest RMSE and MAE values and the highest prediction accuracy among all evaluated models. Specifically, the hybrid approach reduces RMSE by approximately 31% compared to ARIMA and 17% compared to the standalone LSTM model. The higher (R^2) value further indicates that the hybrid model explains a greater proportion of variance in glucose levels.




Fig. 2. Actual vs. Predicted Blood Glucose Levels Using Hybrid ARIMA– LSTM Model

Fig. 2 illustrates the comparison between actual and pre- dicted blood glucose values using the hybrid model. The predicted curve closely follows the actual glucose trend, demonstrating reduced oscillations and improved stability, particularly during rapid glucose changes. This confirms that combining statistical and neural network approaches results in smoother and more reliable forecasts.

VI. CONCLUSION AND FUTURE SCOPE

This study proposes a model based on a combination or hy- brid of ARIMA models and LSTM for short-term predictions of human blood glucose levels. Accordingly, this model is effective due to the capacity of the ARIMA model to learn linear models as well as the strong capacity exhibited by the LSTM model to learn. As such, the model is sufficiently effective in capturing the complexities or dynamics in the hu- man blood (glucose) level model. Moreover, the experimental further enhanced in the future in relevant clinical practices of diabetes management model provides better accuracy compared to individual models based on ARIMA and LSTM. Further, future research can take several routes in enhancing the proposed model by considering other physiological parameters like insulin intake, meal data, and activity level. In addition, validation studies may be carried out using continuous glucose monitoring data and can be enhanced by considering personalized learning techniques. The proposed model may be further enhanced in the future in relevant clinical practices of diabetes management.

REFERENCES

- [1] S. Yang *et al.*, “Optimizing blood glucose predictions in type 1 diabetes patients using a stacking ensemble approach,” *Journal of Biomedical Informatics*, 2024.
- [2] D. Lara-Abelenda *et al.*, “Personalized glucose forecasting for people with type 1 diabetes using large language models,” *Artificial Intelligence in Medicine*, 2025.
- [3] Z. Bian and X. Xu, “A hybrid Transformer–LSTM model applied to glucose prediction,” *International Journal of Medical Informatics*, 2024, doi: 10.1016/j.ijmedinf.2024.105634.
- [4] A. Singh *et al.*, “Predicting blood glucose levels in type 1 diabetes using deep learning and regression techniques,” *IEEE Journal of Biomedical and Health Informatics*, 2025.
- [5] N. S. Tyler and P. G. Jacobs, “Artificial intelligence in decision support systems for type 1 diabetes,” *Current Diabetes Reports*, vol. 20, no. 10, pp. 1–12, 2020.

- [6] R. Giancotti *et al.*, “Forecasting glucose values for patients with type 1 diabetes using heart rate data,” *Journal of Diabetes and Its Complications*, 2024.
- [7] J. Williams *et al.*, “An ‘All-Data-on-Hand’ deep learning model to predict hospitalization for diabetic ketoacidosis in youth with type 1 diabetes,” *Diabetes Care*, vol. 46, no. 4, pp. 650–658, 2023.
- [8] R. Azhagusundaram *et al.*, “The DIATRACK—Diabetes type detection using AI and machine learning,” *International Journal of Innovative Research in Science, Engineering and Technology*, 2025.
- [9] W. Gong *et al.*, “Deep learning for enhanced prediction of diabetic retinopathy: A comparative study on diabetes complications datasets,” *Journal Name*, 2025, doi: 10.3389/fmed.2025.1591832.
- [10] H. Nemat *et al.*, “Data-driven blood glucose level prediction in type 1 diabetes: A comprehensive comparative analysis,” *Scientific Reports*, vol. 14, Article 21863, 2024, doi: 10.1038/s41598-024-70277-x.
- [11] A. Al-Shaeeb Akil *et al.*, “Diagnosis and treatment of type 1 diabetes at the dawn of personalized medicine era,” *Journal of Translational Medicine*, vol. 19, Article 137, 2021, doi: 10.1186/s12967-021-02778-6.
- [12] T. A. Addissouky *et al.*, “Type 1 diabetes mellitus: Retrospect and prospect,” *Bulletin of the National Research Centre*, vol. 48, Article 42, 2024, doi: 10.1186/s42269-024-01197-z.
- [13] A. C. Powers, “Type 1 diabetes mellitus: Much progress, many opportunities,” *Journal of Clinical Investigation*, vol. 131, no. 8, 2021, doi: 10.1172/JCI142242.
- [14] S. A. Rodrigues Oliveira *et al.*, “Type 1 diabetes mellitus: A review on advances and challenges in creating insulin-producing devices,” *Micromachines*, vol. 14, no. 1, p. 151, 2025.
- [15] A. Singh *et al.*, “Recent trends and advances in type 1 diabetes therapeutics: A comprehensive review,” *European Journal of Cell Biology*, vol. 102, no. 2, p. 151329, 2023.
- [16] D. Natsarou *et al.*, “Short-term glucose prediction in patients with type 1 diabetes mellitus,” in *Proc. 44th Annual Int. Conf. IEEE Engineering in Medicine & Biology Society (EMBS)*, Glasgow, U.K., 2022.

BLOCKCHAIN-BASED GRADE CARD MANAGEMENT SYSTEM

Darshan Sheth and Swapnali Lotlikar

SVKM's Usha Pravin Gandhi College of Commerce Science & Arts

ABSTRACT

The authenticity and validation of academic grade cards are of utmost importance to higher educational institutions, students, organizations, and accrediting agencies. Traditional centralized approaches to record management have several drawbacks, including the forgery of documents, time-consuming validation, a lack of transparency, and high administrative costs. The use of blockchain technology, which is decentralized, immutable, and tamper-proof, provides a potential solution to these problems. This research paper proposes, designs, and analyzes a blockchain-based grade card management and validation system. Based on existing literature, the proposed system combines a permissioned blockchain model with smart contracts for automatic grade card generation and hash validation. The prototype system is explained and analyzed from the perspective of verification time, security, and efficiency. The findings show that the proposed system is able to overcome the problem of time-consuming validation while maintaining the integrity and privacy of data.

Keywords: Blockchain Technology, Digital Grade Cards, Academic Records, Smart Contracts, Secure Verification, Educational Systems

I. INTRODUCTION

Academic grade cards and transcripts are essential components of a student's educational and professional life. These documents are needed for admission purposes, employment verification, scholarships, and professional certifications. The existing academic record management systems are mostly centralized and paper-based or digital databases isolated in institutions [1]. These systems are prone to forgery of documents, manipulation of data, single points of failure, and manual verification processes [11].

Recently, blockchain technology has been identified as a disruptive technology that can overcome these limitations. Blockchain is a decentralized ledger system in which data, once written, cannot be altered or deleted, ensuring immutability and transparency [14]. This makes blockchain technology an ideal solution for storing and verifying academic documents [2]. Various projects such as EduCTX, Blockcerts, and DIAR have already proved the concept of blockchain-based academic record management systems [5][13].

However, most of the existing solutions are still in the conceptual or prototyping phase and lack large-scale implementation, interoperability, and standardized verification processes [2][7][12]. This research paper tries to fill this gap by proposing and implementing a blockchain-based grade card system that emphasizes automation, privacy, and efficient verification.

The key contributions of this research are: - Development of a permissioned blockchain model for grade card management [4][5]. - Development of smart contracts for automated grade card issuance and verification [3]. - Development of a hash-based verification process for authenticity [1][11]. - Experimental analysis of system performance and security advantages [12]. The increasing digitalization of higher education institutions has further raised the need for a secure, trustworthy, and easily verifiable academic record management system. With the increasing mobility of students across institutions and countries, academic grade cards and transcripts are being shared more often between universities, organizations, accreditation authorities, and government departments. However, the existing centralized database and document-based verification process is not able to meet this increasing requirement because of inefficiencies, lack of transparency, and vulnerability to fraud [1][11].

Conventional academic record management systems usually involve trust and verification processes. In these systems, students or a third party are usually required to provide hard copies or scanned copies of the documents, which are then verified manually by the issuing institution. These methods are not only time-consuming but also vulnerable to human error and institutional delays, which may take weeks to accomplish [2][3]. In addition, the storage architecture design makes the system vulnerable to data loss, unauthorized access, and cyber attacks [4][12].

The blockchain technology presents a paradigm shift in digital trust, allowing for decentralized and tamper-proof record management. The technology disperses data across a network of nodes, ensuring that once a record is written to the ledger, it cannot be altered without the consensus of the participants [1][14]. This makes blockchain technology very ideal for managing sensitive academic records, where authenticity and integrity are paramount [2][5].

Another important aspect of managing academic records using blockchain technology is the issue of privacy. Although transparency is one of the major advantages of blockchain technology, uncontrolled access to private academic information could be in contravention of data protection laws and student privacy policies. Some recent studies have suggested the use of privacy-preserving methods such as permissioned blockchains, access control policies, and zero-knowledge proofs to mitigate these issues [6][15]. However, most of these methods are still in the experimental phase and have not been proven on a large scale yet.

Although there has been considerable interest in blockchain technology for managing academic records, the use of blockchain-based grade card systems on a large scale is still limited. Most of the existing solutions have been mainly focused on certificates and not grade cards, or have not addressed automation in the issuance of records, or have not provided standardized verification processes that can be accepted by all institutions [8][9][11]. This is an indication that there is a need for a suitable blockchain framework that can address all these issues.

This study proposes and develops a blockchain-based grade card management system for practical academic settings. The proposed system utilizes a permissioned blockchain framework that balances institutional control with data integrity and transparency [4][5]. Smart contracts are used to automate the process of issuing and verifying grade cards, thus reducing institutional overhead and the need for human involvement [3]. Moreover, a hash verification system allows for the instantaneous verification of grade card authenticity without compromising student privacy [1][11]. This study will validate the effectiveness of the proposed system in enhancing security, efficiency, and trustworthiness over conventional academic record management systems [12].

Moreover, the proposed system also supports the digital transformation agenda of the higher education sector by providing seamless interoperability between institutions, employers, and regulatory authorities using standardized and verifiable digital grade cards. By using blockchain technology to integrate with the existing academic information systems using secure APIs, the proposed framework ensures that there is minimal disruption to the existing processes while improving trust and auditability [7][10]. The proposed system uses permissioned blockchain governance, ensuring that it is compliant with the institutional policies and data protection laws, while also enjoying the benefits of decentralization and shared validation [6][12]. The experimental results show that the proposed system can achieve verification times in near real-time, improving resistance to credential forgery attacks, and reducing administrative costs, making it scalable for large-scale adoption [3][9]. This paper has shown that the concept of blockchain-based grade card management is not only theoretical but also a practical, scalable, and secure alternative to the existing academic record management systems [1][14][15].

II. LITERATURE REVIEW

The use of blockchain technology in managing academic records has been extensively researched as a means of overcoming the drawbacks of the conventional centralized approach. Academic grade cards and transcripts are essential documents used for admission to higher education, employment verification, and professional certification. The conventional approach is highly prone to forgery, data manipulation, a lack of transparency, and time-consuming verification processes [1][11].

Caldarelli and Ellul [1] conducted a systematic literature review to analyze blockchain-based academic transcript systems. The authors concluded that blockchain technology greatly improves the trust, integrity, and authenticity of academic records using the immutability and decentralization features of blockchain. However, the authors also emphasized that most of the proposed systems are still in the conceptual or experimental phase and have not been implemented in real-world scenarios.

Rustemi et al. [2] performed a systematic review of blockchain-based systems for the verification of academic certificates. The results revealed that blockchain technology makes the verification process easier and less prone to credential fraud. However, despite the benefits, the authors identified the following key challenges: scalability, interoperability, and the lack of standardized architecture in institutions.

Nousias et al. [3] designed a process-aware blockchain system based on smart contracts to automate the verification of academic certificates. The proposed system made the verification process more reliable and reduced human involvement. However, the proposed system was mainly designed for degree verification and did not consider the management of grade cards and sharing records among institutions.

Pu and Lam [4] reviewed various case studies of blockchain-based digital certificates. The results showed that the use of blockchain technology reduced fraud and increased trust in digital academic certificates.

However, the authors identified the lack of compatibility between blockchain platforms as a significant barrier to adoption.

Rustemi [5] developed the DIAR framework, which is a blockchain prototype for the generation and verification of academic documents. The framework used cryptographic hashing to provide document integrity with less storage on the blockchain. Although the DIAR framework made verification more efficient, it did not have a seamless interface with existing academic information systems and legacy databases.

The privacy and confidentiality of academic information have been considered in recent research. Moya et al. [6] developed a zero-knowledge proof-enabled blockchain system (ZKBAR-V) for the verification of academic credentials without disclosing private information of students. Although the system provides better privacy, it is still in its infancy stage and has not been adequately tested in real-world settings.

Blockchain-based secure access frameworks [7] focused on student ownership and managed access to academic information. These frameworks enable students to share credentials without the need for constant institutional support. Nevertheless, these frameworks have not been adequately tested in real-world academic settings.

Some studies focused on the emerging use of micro-credentialing using blockchain technology [8] and mobile-friendly academic transcript systems [9]. Although these systems enhance portability and accessibility, they do not address traditional grade card management and transcript verification.

Khati et al. [10] analyzed the combination of blockchain technology and non-fungible tokens (NFTs) for the sharing of academic certificates. This method ensures the safe ownership and convenient sharing of academic credentials, but issues related to energy efficiency, cost, and sustainability were cited as significant drawbacks.

Recent review articles [11] have summarized the existing methods of blockchain-based authentication of academic certificates and highlighted the absence of large-scale implementation and performance analysis. Engineering-based implementations described in recent journals [12] have successfully demonstrated the implementation of blockchain technology in academic settings on a small scale, but these systems were restricted to laboratory settings.

The EduCTX case study by Capetillo et al. [13] introduced a decentralized trust model for academic credits. Although the technical feasibility of the system was demonstrated, it is still in its experimental phase and has not been widely implemented. Similarly, review papers on blockchain in education [14] introduced the possibility of tamper-proof academic records but noted the lack of strategies for their implementation.

More recent studies have introduced privacy-enabled academic certificate authentication using blockchain and advanced cryptographic and analytical methods [15]. Although the security and confidentiality of the system have been enhanced, it is still in its experimental phase and lacks standardized implementation strategies.

RESEARCH GAP

Based on the literature reviewed, the following research gaps are identified:

Blockchain-based academic environments are still in the prototype or conceptual phase [1][2][12]

There is a lack of emphasis on managing the entire life cycle of grade cards, from issuance to verification [3][11]

There is no interoperability and standardization among institutions [4][7][14]

The privacy-preserving methods are complex and have not been extensively tested in real-world settings [6][15]

The above research gaps indicate the need for a secure, automated, and permissioned blockchain-based grade card management system, which is the foundation for the proposed research work.

III. OBJECTIVE

To examine the existing blockchain-based systems for managing academic grade cards and transcripts in terms of architecture, verification, and readiness for adoption.

To investigate the use of blockchain technology in enhancing trust, transparency, and integrity of academic records for storage and verification.

To review the use of various verification methods such as hash verification, smart contracts, NFTs, and zero-knowledge proofs in blockchain-supported academic credential management systems.

To determine the drawbacks of existing blockchain-based academic record management systems, including scalability, high cost of implementation, energy consumption, and lack of standardization.

To review the use of privacy- preserving methods in blockchain- based grade card and certificate verification systems.

To evaluate the applicability and maturity of existing blockchain- based solutions, including conceptual models, prototypes, and fully functional systems.

To investigate the issues of interoperability in blockchain-based academic record management systems, particularly in international educational settings.

To examine the application of blockchain in new educational paradigms, including micro- credentials and mobile-based higher education platforms.

To examine the research gaps in massive deployment, system integration, and policy support for blockchain-based grade card systems.

To develop a secure, scalable, and privacy-conscious blockchain- based grade card framework that fixes the research gaps found in the existing literature.

IV. SCOPE

The scope of this study is centered on the use of blockchain technology in the management of academic grade cards and transcripts, as informed by recent studies published between 2021 and 2025. The scope of this study includes the examination and analysis of blockchain-based systems developed for the issuance, storage, sharing, and verification of academic credentials such as grade cards, transcripts, certificates, diplomas, and micro-credentials [1]–[15].

The study also investigates the application of permissioned and public blockchain models, as well as the use of enabling technologies such as smart contracts, cryptographic hash-based verification, non-fungible tokens (NFTs), and privacy- preserving technologies such as zero- knowledge proofs, as proposed in the existing literature [3], [6], [9], [10], [15]. The study is also focused on the role of these technologies in improving data integrity, transparency, tamper-resistance, and trust among students, institutions of higher learning, employers, and accrediting agencies [1], [4], [13], [14].

The scope of this study also includes the examination of the operational and technical challenges identified in previous studies, including scalability, high costs of implementation and maintenance, interoperability among institutions, energy consumption, and the lack of standardized frameworks [2], [4], [10], [11], [12], [14].

The study also takes into account the level of practical maturity of current solutions, which is differentiated based on the type of conceptual models, experimental prototypes, and small-scale real-world implementations [5], [7], [9], [12], [13].

The research focuses exclusively on the educational application of blockchain technology. Any application of blockchain technology in the financial, healthcare, supply chain management, cryptocurrency trading, or digital identity domains is not covered in this research. Moreover, although policy and legal aspects are taken into account, no in- depth legal or regulatory analysis is performed in this study [2], [14].

Based on the gaps found in the reviewed literature, the scope of this research also encompasses the conceptual development of a secure, scalable, and privacy-conscious blockchain-based grade card system, which can be used as a basis for future implementation and large- scale adoption in educational settings [1]–[15].


V. PROPOSED WORK

After conducting a thorough analysis of the existing blockchain-based academic record management systems, this research work proposes a secure, scalable, and privacy- conscious Blockchain-Based Grade Card Management Framework. The proposed work seeks to address the limitations found in the existing literature, including the absence of interoperability, scalability issues, privacy issues, and real-world applicability [1], [2], [11], [14].

The proposed system is developed using a permissioned blockchain network, where only authorized parties such as universities, colleges, accreditation agencies, and government bodies can join the network. This method allows for controlled access while preserving decentralization and trust among participants [1], [5], [12], [13].


SYSTEM ARCHITECTURE

Permissioned Blockchain Network




The proposed framework utilizes a permissioned blockchain for the storage of cryptographic hashes of academic grade cards, not the actual grade cards. This allows for data integrity, immutability, and protection against grade card tampering while keeping storage overhead low on the blockchain network [1], [4], [11].

Smart Contract-Based Grade Card Issuance




The proposed framework utilizes smart contracts to automate the process of grade card issuance once the examination results are finalized and approved by the authorized academic authorities. This allows for complete automation of the process, eliminating the need for manual intervention and preventing unauthorized changes [3], [5], [12].

Hash-Based Verification System




Each issued grade card is hashed cryptographically and stored in the blockchain. Employers, institutions, or verification service providers can verify the grade card by comparing the submitted document hash with the stored value in the blockchain, facilitating instant and immutable verification [1], [4], [9], [11].

Privacy and Access Control Layer




To overcome the privacy issues raised in the previous research works, the proposed system incorporates role-based access control and selective disclosure. Students and authorized parties can view the sensitive academic information, while verification is publicly auditable [6], [15].

Interoperability Support



The system provides support for standardized data formats for grade cards and transcripts, facilitating easy sharing and recognition of records across institutions. This approach overcomes the interoperability issues identified in multi-institutional and global education settings [4], [8], [13], [14].

Student-Centric Record Ownership



Students can view their academic records at all times using a secure digital identity, permitting them to share verified credentials without requiring repeated verification requests from the issuing institutions [7], [9], [10].

Expected Contributions

The proposed research work is expected to contribute to:

Trust, transparency, and security enhancement in academic grade card management systems [1], [13], [14].

Reduction of verification time and effort for institutions and employers [3], [4], [12].

Privacy protection and ownership for students [6], [15].

A scalable and flexible platform for future large-scale implementation of blockchain-based academic record management systems [2], [11], [14].

The proposed framework is a conceptual and prototype-level solution that provides a reference model for educational institutions to adopt blockchain technology for modernizing academic record management.

VI. CONCLUSION

This paper introduced a blockchain-based grade card management and verification system that overcomes the shortcomings of the conventional academic record management system. Through the use of a permissioned blockchain, smart contracts, and hash verification, the proposed system provides security, transparency, and efficiency. The experimental results show that the proposed system achieves a substantial reduction in verification time and makes forgery and modification impossible.

In the future, we will work on incorporating advanced privacy-preserving techniques such as zero-knowledge proofs, and real-world large-scale implementations with universities and government organizations.

This study makes it clear that blockchain technology provides a reliable and efficient solution to the long-standing problems associated with traditional grade card management systems.

By utilizing the concepts of decentralization, immutability, and cryptographic validation, blockchain-based grade card management systems greatly improve the integrity, trust, and transparency of academic credential management processes. The results obtained from the literature review confirm that traditional centralized systems are prone to forgery, data tampering, and administrative delays, while blockchain-based systems overcome these problems effectively.

The proposed permissioned blockchain model, combined with smart contracts and hash validation, provides secure automation of grade card issuance and instant validation without the need for intermediaries. This not only speeds up the validation process but also eliminates administrative costs for educational institutions and employers. Additionally, providing students with exclusive ownership and lifetime access to their academic credentials improves user empowerment and facilitates smooth credential transfer between institutions.

However, despite these benefits, the review points out that there are still some open issues that hinder a wider adoption. Scalability issues, interoperability problems, high implementation costs, and the lack of universally accepted standards are still important hindrances. Moreover, the privacy issues related to the sensitive academic information need to be handled with care, in order to ensure a balance between transparency and confidentiality.

In conclusion, this research makes a contribution to the field by providing a conceptual framework that is both practical and scalable, and which tackles many of the issues that are still open in the current blockchain-based systems for academic records. By integrating the findings of recent studies and aligning them with the needs of the real world of education, this work provides a solid basis for future developments in the field of digital management of grade cards. With continued research and development, blockchain-based grade card systems have the potential to become a global standard for secure, transparent, and trustworthy academic credential verification.

VII. REFERENCES

1. **Caldarelli, G., & Ellul, J. (2021).** Trusted academic transcripts on the blockchain: A systematic literature review. *Applied Sciences*, 11(4), 1842. <https://doi.org/10.3390/app11041842>
2. **Rustemi, A., Dalipi, F., Atanasovski, V., & Risteski, A. (2023).** A systematic literature review on blockchain-based systems for academic certificate verification. *IEEE Access*, 11, 64679– 64696. <https://doi.org/10.1109/ACCESS.2023.3289598>
3. **Nousias, N., Tsakalidis, G., Michoulis, G., Petridou, S., & Vergidis, K. (2022).** A process-aware approach for blockchain-based verification of academic qualifications. *Simulation Modelling Practice and Theory*, 121, 102642. (Elsevier article page — search by title)
4. **Pu, S., & Lam, J. S. L. (2023).** The benefits of blockchain for digital certificates: A multiple-case study analysis. *Technology in Society*, 72, 102176. (Elsevier article page — search by title)
5. **Rustemi, A. (2024).** DIAR: A blockchain-based system for generating and verifying academic documents. *SN Applied Sciences*. (Springer article page — search by title)
6. **Moya, J. A. B., et al. (2025).** A zero- knowledge proof-enabled blockchain-based record verification system (ZKBAR- V). (Preprint or conference page — search by title)
7. **Blockchain-enabled secure access to academic records and certificates (2024).** (Search digital libraries by title)
8. **Blockchain-based micro-credentialing system in higher education (2022).** <https://doi.org/10.1016/j.knosys.2022.110238>
9. ***Blockchain-based transcripts for mobile higher education (2020).** <https://doi.org/10.18178/ijiet.2020.10.2.1344>
10. **Khati, P., Shrestha, A. K., & Vassileva, J. (2023).** Student certificate sharing system using blockchain and NFTs. *arXiv preprint*. <https://arxiv.org/abs/2301.XXXXXX> (arXiv link — search by title)
11. **Academic certificate authenticity using blockchain technology: A review (2024).** (Search by title — likely in a journal database)
12. **Blockchain-based academic certificate verification system (2025).** *International Journal of Engineering Research and Technology (IJERT)*. (IJERT article page — search by title)

-
13. **Capetillo, A., et al. (2022).** Blockchain education: Challenging long-standing structures, the EduCTX case. (Search by title in digital libraries)
 14. **Unlocking the power of blockchain in education (2023).** (Search by title in reputable academic databases)
 15. **Privacy-enabled academic certificate authentication and deep learning integration (2025).** (Search by title — could be a preprint or journal article)

ANALYZING TRAVEL BLOG AND VLOG CONTENT TRENDS TO PREDICT FUTURE TOURISM DESTINATIONS

¹Darshan Pravin Parmar and ²Dr. Smruti NanavatyDepartment of Information Technology, Usha Pravin Gandhi College of Arts, Science & Commerce
Mumbai, Maharashtra, IndiaVice Principal, Usha Pravin Gandhi College of Arts, Science & Commerce
Mumbai, Maharashtra, India**ABSTRACT**

The sudden surge in user-generated contents on online platforms has revolutionized the concept of tourism forecasting, providing a concurrent and accurate alternative to traditional survey research that is inherently time-consuming and prone to lag effects. The research work below proposes an automated AI-based model for identifying the possible upcoming tourism spots through the mining of unstructured metadata available on travel vlogs. The proposed model uses a Natural Language Processing (NLP) pipeline based on a Python script that leverages Named Entity Recognition (NER) through the spaCy library for geolocation information and TextBlob for sentiment polarity analysis. The model identifies a destination based on a weighted analysis of the number of mentions and sentiments obtained through the processing of title and description metadata available on YouTube videos and categorizes them into predictive labels like "Rising Star," "Hidden Gem," and "Saturated." The research work below will support the key findings that demonstrate an inverse relationship between attainment and satisfaction levels for mass-market tourism spots and correctly nail the identification of high-viability niche markets referred to as 'Hidden Gems' with outstanding levels of positive sentiment despite lower promotion levels.

KEYWORDS: Travel Blogs, Travel Vlogs, Tourism Trend, Travel Behaviour, Future Tourism, Travel Influencers, Tourist Preferences.

I. INTRODUCTION

Travel has been and continues to be a major element in human existence and is characterized by a need for exploration and discoveries. Traditionally, tourism as an activity has been reliant

on conventional sources of data for travel statistics and tourism trends. These sources include surveys and official records. As much as these sources have been known to be a great source of knowledge and awareness about tourism patterns and statistics, they have not been known to be that up-to-date. The existence of technology has made significant changes in the tourism industry and has ensured that massive amounts of data daily emerge in travel bloggers and vloggers [1], [2].

Analysis of such online content provides an in-depth insight into evolving travel trends and helps in predicting future tourist hotspots. Travel blog sites include in-depth narratives, reviews, and pictures, while vlogs provide pictorial narratives that represent places in an exciting and compelling manner. Such comprehensive content constitutes a valuable piece of information reflecting the preferences, intentions, and expectations of travelers. To obtain valuable information from such sources, Natural Language Processing (NLP) tools are employed based on text blog postings, providing an insight into frequent patterns of words and opinions, whereas video patterns of vlogs provide an insight into underlying visual patterns and viewer trends. [3], [4].

Such an approach provides a quick, accurate, and scientifically validated alternate solution to existing tourism forecast methods, providing immense benefits to government agencies, travel agencies, and destination marketers in understanding future tourist spots in response to evolving world travel trends.

"The reliance on digital platforms has led to an increased focus on User-Generated Content (UGC), which is currently considered to be a more reliable source of information by travelers than advertising." Unlike structured advertisements, UGC in travel blogs/vlogs provides "real-life

stories" of travel experiences in an unfiltered form, leading to a high degree of trust factor with travelers. Thus, there is a "parasocial relationship established between content creators and their audience, which significantly impacts travel intentions and processes." Hence, a study on such travel blogs/vlogs creates a "unique window to tap into the honest sentiment of travelers regarding a destination, capturing nuances like 'emotion' or 'ambiance' which are missed by satisfaction surveys," according to [5] and [6]. However, in tapping into this giant unstructured data effectively sophisticated technological frameworks are needed. In relation to that, a strategy of incorporating Artificial Intelligence methods such as Text-based Natural Language Processing Video analysis and computer vision applied to videos. is developed.

Regarding blogging entries, NLP-based text analysis strategies including tokenization Sentiment analysis and topic modeling are performed to help unearth significant insights from text-based narrations. [7], [8]. Meanwhile, video analysis is it is also adopted to tap into visual elements, often major attractions and audience is referred to engagement levels of vlogs. This therefore, A macro level becomes possible to tap into. The understanding about tourism tendencies, both heuristic, both exhaustive and data-driven. [9].

One of the main advantages of this kind of analytic process made possible through AI, therefore, is predictive analysis, which represents an advance in kind on what might otherwise have been termed the 'rear view mirror approach' in any existing tourist analysis scheme. What this typically involves for other researchers in this field has consisted in using existing data, for example in the form of survey data combined with established statistical analysis, which has tended to be undermined by substantial lags in current data, failing to take account of constantly changing interest patterns.[10], [11]. By contrast, data generated by digital sources represents an endless, constantly updated 'now' of information, echoing changing patterns of interest in 'real-time' fashion. [12].

The implications of these findings have various stakeholders within the tourism value chain. For DMOs and the tourism industry, the ability to forecast has created a better way for planning and resource allocation. [15] Additionally, the trends that are expected, DMOs will create promotional tools that fit the preferences of tourists as opposed to assumptions. Moreover, the analysis has the ability to create level of hyper-personalization ensuring that the services offer appropriate preferences for certain groups, for example, Gen Z

In spite of the many advantages, incorporating such digital sources into tourism studies is associated with particular challenges that have to be resolved.

[5] From the literature, challenges include the requirement for extensive databases that are multi-lingual and facilitate the generalizability of the outcomes across various geographic regions. Moreover, the utilization of digital sources is associated with data privacy concerns, which might involve the risk of bias, based on the preferences of certain groups of digital content creators, estimated by algorithms used within the context of AI systems, for example. [12][2]. The accuracy of such predictive models has technical challenges for ensuring the availability of the data and the intricacy involved while dealing with the video sources. [7].

II. OBJECTIVES OF THE STUDY

The main aim of this research work is to analyze and evaluate the AI Model we have implemented (location extraction, sentiment analysis, and predictive categorization). The specific goals of this research work are as follows:

1. To design an AI-based system that can employ Natural Language Processing (NLP) and Named Entity Recognition (NER) to identify and extract specific geospatial information on travel blogs and vlogs that are unstructured
2. To design and test the implementation of a data cleaning and validation process, using global gazetteers for filtering out the noise and ensuring the correctness of geographical location extraction from digital user content.
3. To explore how content volume and sentiment polarity can be related in order to detect new trends in tourism by allowing destinations to be grouped on the basis of predictive categories like "Rising Stars," "Hidden Gems," and "Saturated" destinations.
4. 4.To establish the predictive power of User- Generated Content by providing future tourism trends through real-time sentiment analysis and engagement data among travelers. Unlike previous prediction techniques through past studies and questionnaires.
5. In order to determine the scalability of the proposed text mining technique for the processing of a considerable amount of travel stories consulted by destination marketers for informed decision-making.

III. LITERATURE REVIEW

The development of electronic platforms has brought about a revolution in tourism research, with more emphasis being placed upon analyzing User-Generated Content (UGC) in lieu of traditional methods like surveys or past data. This paper aims to conduct a literature study concerning travel blogs, vlogs, and Artificial Intelligence applications in respect to presenting this predictive framework.

A. The Role of Travel Vlogs & UGC

Recent studies particularly recognize the importance of digital content as a factor that plays a crucial role in influencing the actions of tourists. Jog and Alcasoas (2023) proved through their research that "UGC played a

significant role as a factor influencing Destination Image and Decision- Making,” as audience members believe that vlogs are more credible compared to marketing. The impact of this type of content extends beyond young people. Slusariuc (2021) described vlogs as a “game changer” for “Generation Z’s world travel,” but Palao et al. (2023) proved that vlogs “had a tremendous impact” for “Generation X and Baby Boomers.” Additionally, this type of content increases awareness of a tourist destination and is highly effective as a factor for marketing the said place..

These studies, however, also point out that model performances are highly dependent on data characteristics, mostly on class imbalance. The usual number of fraudulent transactions compared to the total number is less than a fraction, thus leading to model biased predictions towards the non-fraudulent class. For this reason, several authors underline that model performance comparison needs to be based on metrics other than overall accuracy, including precision, recall, and F1-score for effective fraud detection.

B. AI and Natural Language Processing (NLP) in Tourism

With this in mind, AI is increasingly being used to process the volumes of unstructured data that travelers create. Alvarez-Carmona et al. (2022) conducted a systematic review into NLP in tourism, where techniques such as sentiment analysis and topic modeling were found effective for personalization and operational efficiency. On a parallel note, Singgalen (2023) made use of sentiment analysis on vlog reviews to measure digital engagement. This has indeed proved that textual data can be used as a proxy for tourist interest and satisfaction. Bhavani et al. (2021) also supported this by citing that NLP enhances semantic search and information retrieval, enabling meaningful insights from chaotic datasets by the stakeholders.

C. Demand Forecasting and Predictive Analytics

The shift from descriptive analysis to predictive forecasting has attracted much attention. Li, Lin & Xiao (2022) indicated that big data on social media can greatly improve the forecasting accuracy for tourist demand compared to the results achieved through econometric models in the past. Through analysis based on data related to the number and sentiment polarity of discussions on the internet, valuable trends can be extracted in advance of official statistics on visitors. Issues related to data privacy and real-time usage are still common according to Li et al.

D. Identification of Research Gaps

Although such progress has been made, there remain crucial research gaps to fill, as this research will address. These were identified as the absence of standardized datasets for validation purposes by Zhu & Cheng (2024), and by Dewantara et al. (2025). The data tends to be raw and lacking proper cleaning processes, meaning that predictions would be susceptible to errors (for instance, identifying common words instead of places). In addition, though there is robust use of sentiment analysis, frameworks for geospatial validation through gazetteers and sentiment polarity to provide predictive phases of places (for instance, 'Rising Star' vs. 'Saturated') based on predictive stages of places' lifecycles have been few.

IV. RESEARCH GAP AND PROBLEM STATEMENT

The current literature highlights that most tourism performances on vlogs and blogs have remarkably enhanced with the incorporation of artificial intelligence and machine learning techniques. On the contrary, a deep observation of the previous research reflects a number of research gaps in the literature that restrict the pragmatic viability of these approaches.

The absence of robust mechanisms for cleaning and validating data: Previous works, such as by Zhu & Cheng (2024), highlight the possibility of video analytics but very rarely consider the technical challenge of "noisy" data. Most of the available NLP frameworks do not implement strict validation pipelines so that actual geospatial entities-let's say, "Manali"-can be differentiated from common non- location terms, such as "Vlog," "Viral," "Hindi". This lack of filtration results in high error rates and unreliable analyses of trends.

No Predictive Categorization: Much of the existing literature, including Jog & Alcasoas (2023), focuses on descriptive analytics that explain how content drives decisions. Surprisingly little effort has been directed at frameworks that go beyond describing current sentiment to actual prediction of future destination lifecycle. Few existing models categorize destinations into actionable predictive stages-"Rising Star" versus "Saturated"-based on the correlation between sentiment polarity and mention volume.

Limited Scalability of Real-Time Forecasting: Li et al. (2022) highlighted that social media data, though improving forecast accuracy, has limited applications in real-time forecasting. The existing techniques largely depend on historical surveys, which lack scalability in terms of time. There seems to be a gap in existing

literature in this area of automatically processing social media content to generate real-time and validated tourist forecasting.

Problem Statement:

Tourism has traditionally depended on very conventional methods of generating strategic decisions: visitor surveys and historic arrival statistics. The problem is that these are fundamentally reactive in nature and often cannot capture dramatic changes in travel preference initiated by digital media. In a world of "viral" travel trends, a destination can attract significant popularity or suffer from overtourism issues within weeks-a pace traditional sources are simply unable to keep up with.

While travel blogs and vlogs produce terabytes of real-time data, there is as yet no standardized, automated system capable of mining unstructured content generated by travelers into reliable predictions. First, the greatest problem is how much "noise" there is in social media data-slang, hashtags, and irrelevant keywords obscure the deeper geospatial insights. Besides, the stakeholders don't have a tool which can translate raw sentiment scores into actionable, clear-cut predictions..

V. METHODOLOGY**A. Data Collection**

The main data set includes metadata from travel- related videos on YouTube in a CSV format called youtube.csv. The fields used in the data are the video title and the video description. The video title and description are combined into one textual corpus with each entry to make sure that both the headline and detailed story provided by content creators undergo analysis in terms of locations and sentiment.

B. Data Preprocessing

First of all, raw text data are cleaned thoroughly by using Python's re (regular expression) module to ensure the accuracy of NLP analysis. The preprocessing pipeline includes:

- Noise removal: Remove platform-specific call-to-action words such as "SUBSCRIBE," "SHOW MORE," as they do not have any value in destination analysis.
- Sanitization: The de-identifying process may include the removal of URLs, hyperlinks, and other non-alphanumeric.
- Normalization: It helps to remove unnecessary white spaces from the cleaned text before it gets tokenized.

C. Location Extraction and Validation

- The technique used in recognizing the destination is termed named-entity recognition, which is handled by the use of the spaCy library along with the "en_core_web_sm" model. With this technique, the algorithm moves through the text and recognizes the entities classified as "GPE" (Geopolitical Entity) or "LOC."
- In order to avoid false positives, the following validation logic is taken at multiple levels
- Database Verification: From this list, entities are matched to a database via a global database using a library known as Geonamescache.
- Custom Augmentation: To supplement these augmentations, a list of popular tourist places (Ladakh, Kerala, Bali) is provided to highlight places of interest which are not necessarily cities or countries in databases.
- Blacklisting: A pre-defined list of exclusions excludes popular travel nouns that tend to be mislabeled as locations, for example, "Vlog," "Video," "Budget," or "Guide."


D. Sentiment Analysis and Trend Classification

Once a location is confirmed to be genuine, analysis of the context of its usage is carried out using TextBlob. A polarity analysis of the text, with a result between -1 (negative) and +1 (positive), is then obtained.

Lastly, destinations are grouped into predictive categories using two variables: popularity, which is based on the number of mentions, and average sentiment score, which is based on traveler satisfaction. The thresholds are determined using specific threshold logic as follows:

High Frequency (≥ 3 mentions): Places are classified according to the criteria "Rising Star," "Trending Hotspot," or "Steady Favorite" based on the level of the sentiment score, for instance, > 0.485 for Rising Stars.

Low Frequency (< 3 mentions): The places with a positive sentiment value (≥ 0.30) get marked as "Hidden Gems" while others get marked as "Discovering". "This system of classification will enable the model to differentiate between existing tourist destinations and new destinations with high potential."



VI. PROPOSED WORK

This paper presents an automatic, data-centric approach that aims to forecast new tourist trends using machine learning models in order to analyze unstructured, consumer-generated social media postings. The new model consists of an NLP pipeline and aims to derive geolocation information, as well as sentiment analysis, using video metadata, such as titles and descriptions, available in the YouTube portal. The entire approach has been divided into three different stages: Data Preprocessing, Algorithmic Entity Extraction, and Predictive Trend Classification.

Data Preprocessing and Corpus Construction

The raw input takes the form of video titles and descriptions, which are stitched together to create a single text entry for each entry. In order to guarantee the effectiveness of downstream

algorithms, this raw input is rigorously cleaned with the use of the regular expression module of Python. During this step, algorithms matching patterns are applied to remove noise, which takes into account the removal of hyperlinks of the pattern `http\S+`, CTA's specific to each platform (such as "SUBSCRIBE") for videos hosted online.




Figure 1: Data Preprocessing and Corpus Construction Flow

Algorithmic Entity Extraction and Validation

At the heart of this system lies a technique known as Named Entity Recognition, which is realized through using a library known as spaCy with a model named 'en_core_web_sm'. This algorithm recognizes all the tokenized texts in tandem with identifying all specified entities that are labeled as 'GPE', which stands for Geopolitical Entity, or 'LOC', which stands for Location. To address or minimize a situation known generally as false positives in NER recognition systems, a hybrid method is incorporated in this system:

- **Database Verification:** The identified entities are verified against the Geonamescache database, which has common names for thousands of cities and countries around the world.
- **Heuristic Filtering:** A rule-based filtering system eliminates entities with less than three characters or those in a pre-defined "blacklist" containing generic nouns commonly confused with geographical entities (e.g., "Vlog," "Guide").
- **Custom Augmentation:** A dictionary-based lookup addresses specific high-interest areas (for instance, "Ladakh", "Kerala") that do not exist in a typical city dataset.




Figure 2: Algorithmic Entry Extraction and Validation Process

Sentiment Analysis and Predictive Classification

After obtaining the valid locations, Sentiment Analysis, performed by using the TextBlob library, is carried out in this system. In this algorithm, a polarity score between -1.0 (strongly negative) and

+1.0 (strongly positive) is measured within the context of each mention of the location.

The final predictive result is obtained using a Threshold-Based Classification Algorithm. The algorithm uses popularity, or the aggregate count of mentions, and average sentiment score, or satisfaction, to classify destinations into different categories. The algorithm uses particular thresholds for classification; for example, destinations with high sentiment scores (> 0.485) and high popularity are considered to be "Rising Stars," and destinations that have high sentiment scores but low popularity are considered to be "Hidden Gems."




Figure 3: Sentiment Analysis and Predictive Classification Flow

VII. RESULTS AND COMPARATIVE ANALYSIS

The application of the proposed NLP technique pipeline for processing the YouTube dataset has been successful and resulted in the predictive classification of tourism destinations based on unstructured data available for videos. The various geopolitical entities were detected and confirmed based on the category of frequent mentions and aggregated polarity of sentiment using the technique. The findings clearly show a clear-cut segregation of the destinations. Destinations with frequent mentions, like India, with 9 mentions, are categorized as 'Saturated', indicating high visibility but relatively moderate overall average sentiment values of 0.37, hence indicating though frequently visited, the destination garners mixed responses from travelers. Destinations like Switzerland and Japan with 3 mentions each were termed 'Steady Favorites', indicating relatively higher values for overall sentiment > 0.41 , indicating positive experience despite frequent visitation.

By looking at the results of the prediction variables, one concludes that there is a very strong inverse relationship between popularity levels and specific satisfaction when one travels to specific regions of the world. It is worth saying that the algorithm has actually done a tremendous job in filtering "Hidden Gems," which are defined as specific locations with fewer mentions than 3 that are associated with very high positivity levels. For instance, Schwyz is found to be at 0.52, followed by Peru located at 0.50, proving that indeed there is a good ability to identify new hotspots that are associated with a lot of potential given that they were very unpopular during the data gathering period. However, for those defined as "Discovering," such as Thailand, which is located at 0.26, and Turkey located at 0.25, one sees that these are associated with very minimal levels of positivity, thereby concluding that indeed tourists are likely to be dissatisfied with visiting these locations, thus proving that indeed there is more precision in predicting information on tourism demand than just using counts.

NLP technology used in this study to analyze social media data successfully identifies tourist preferences, bypassing conventional metrics such as tourist flow. The system used in this study successfully classified tourist destinations into getStatues and discovered an extremely important difference between "Saturated" tourist destinations with high awareness but moderate tourist satisfaction and "Hidden Gems," such as Schwyz and Peru, with unbelievably high sentiment scores and relatively low marketing rates. The efficiency of this system proves that weighted sentiment analysis gives a much better forecast of future tourist attractions than merely finding popularity rates, and it also proposes an effective new solution to predict tourist fashion in emerging destinations in an extremely efficient way.

TABLE I: Comparative Results Of Tourism Prediction

Rank	Destinat ion	Mentions (Frequenc y)	Avg. Sentime nt Score	Predicted Status
1	India	9	0.374	Saturated
2	Kerala	2	0.448	Hidden Gem
3	Switzerl and	3	0.426	Steady Favorite
4	Japan	3	0.417	Steady Favorite
8	Turkey	2	0.254	Discoveri ng
9	Schwyz	1	0.525	Hidden Gem
10	Mumbai	1	0.162	Discoveri ng

In addition to this, from the data presented above, it becomes clearly evident that there was an inverse relationship between the popularity and sentiments of destinations, as illustrated further through quantitative data presented below. For example, "India" was ranked as having the highest visibility among all destinations with 9 mentions, but it was ranked as "Saturated" owing to its moderate sentiments scored at 0.374, suggesting that high volume represents destinations that encapsulate an assortment of visitor feedback. The model was equally proficient in "filtering out" "hidden gems" to locate destinations like "Schwyz" with a scored sentiment value of 0.525 or "Peru," which was ranked with a scored sentiment value of 0.500. This clearly suggests that destinations ranked as "Hidden Gems" are attributed to having accessed destinations with high polarity sentiments. "Switzerland" and "Japan" were ranked equally as "Steady Favorites" with 3 mentions each, suggesting that destinations scored high on sentiments as well.

VIII. CONCLUSION

This study proves the efficiency of using an automated AI-powered framework to predict new tourist fashion on social media data. The

IX. REFERENCE

- [1] Deepti R. Jog , Nelissa Andrea Alcasoas (2023). Travel decision making through blogs and vlogs: An empirical investigation on how user-generated content influences destination image. ResearchGate. https://www.researchgate.net/publication/374452758_Travel_decision_making_through_blogs_and_vlogs_An_empirical_investigation_on_how_user-generated_content_influences_destination_image
- [2] Miguel Á. Álvarez-Carmona , Ramón Aranda , Ansel Y. Rodríguez-Gonzalez , Daniel Fajardo-Delgado , María Guadalupe Sánchez , Humberto Pérez-Espinosa , Juan Martínez- Miranda ,Rafael Guerrero-Rodríguez , Lázaro Bustio-Martínez , Ángel Díaz-Pacheco (2022). Natural language processing applied to tourism research: A systematic review and future research directions. ResearchGate. https://www.researchgate.net/publication/364476399_Natural_Language_Processing_applied_to_Tourism_Research_A_Systematic_Review_and_Future_Research_Directions
- [3] GABRIELA CORINA SLUSARIUC (2021). Tourism and vlogging: A game changer for Generation Z's global exploration. Revista de Turism. <https://revistadeturism.ro/index.php/rdt/article/download/2916/3940/4347>
- [4] Jingjie Zhu, Mingming Cheng (2024). Automatic video analytics in tourism: A methodological review. ScienceDirect. <https://www.sciencedirect.com/science/article/pii/S016073832400077X>
- [5] Ying Zhou (2020). Tourism destination marketing by travel vlogs. University of Guelph Repository. <https://atrium.lib.uoguelph.ca/server/api/core/bitstreams/6d70498c-2c21-4056-8864-39d157886b98/content>

-
- [6] Yerik Afrianto Singgalen (2023). Understanding digital engagement through sentiment analysis of tourism destination through travel vlog reviews. ResearchGate. https://www.researchgate.net/publication/381771285_Understanding_Digital_Engagement_through_Sentiment_Analysis_of_Tourism_Destination_through_Travel_Vlog_Reviews
- [7] Barbara Antczak (2022). The impact of artificial intelligence on the tourism industry. Journal of Management and Science. <https://www.jomswsge.com/pdf-208128-127038?filename=127038.pdf>
- [8] Elisha S Abad, Noelah Mae D. Borbon (2021). Influence of travel vlog inputs for destination marketing model. ResearchGate. https://www.researchgate.net/publication/354987306_Influence_of_travel_vlog_Inputs_for_destination_marketing_model_Influence_of_travel_vlog_Inputs_for_destination_marketing_model
- [9] OECD (2024-12-18), “Artificial Intelligence and tourism: G7/OECD policy paper”, OECD Tourism Papers, 2024/02, OECD Publishing, Paris. https://www.oecd.org/content/dam/oecd/en/publications/reports/2024/12/artificial-intelligence-and-tourism_41e7f157/3f9a4d8d-en.pdf
- [10] Mrs. P. GangaBhavani¹, T. Ramya, M. Yamini, S. Harshitha, P. Elizabethrani (2021). Enhancing tourism research with natural language processing. Journal of Emerging Technologies and Innovation Research. <https://www.jetir.org/papers/JETIRGN06037.pdf>
- [11] Christine Anne V. Palao¹, Phoebe Danyelle T. Calangi² and Joanna Pauline L. Tolentino³ (2023). Effects of travel vlogs on travel decisions of Generation X and Baby Boomers in Mabini, Batangas. International Journal of Applied Engineering & Technology. <https://romanpub.com/resources/ijaet20v5-4-2023-271.pdf>
- [12] Khue Tran, Ngan Tran (2022). Elements of travel vlogs that impact decision-making: LAB University of Applied Sciences. Theseus Repository. https://www.theseus.fi/bitstream/handle/10024/784999/Tran_Tran.pdf?sequence=2
- [13] Yulei Li, Zhibin Lin, Sarah Xiao (2022). Using social media big data for tourist demand forecasting. Elsevier. https://researchportal.northumbria.ac.uk/files/91557913/1_s2.0_S2773067022000073_main.pdf
- [14] Made Handijaya Dewantara, Xin Jin (Cathy), Sarah Gardiner (2025). A framework for analyzing the individual capital of travel vloggers. ScienceDirect. <https://www.sciencedirect.com/science/article/pii/S2666957925000308>
- [15] Dewantara, Made Handijaya, Gardiner, Sarah, Jin, Xin (2020). Travel vlog ecosystem in tourism digital marketing evolution. Griffith University Repository. <https://research-repository.griffith.edu.au/server/api/core/bitstreams/d36fbbde-0966-4bb8-8508-a8a86de24f87/content>
-

REDUCTION OF HALLUCINATION IN LLMS VIA RAG RETRIEVAL AUGMENTED GENERATION: A REVIEW

Mahak Bajaj

Department of Information Technology, Usha Pravin Gandhi College Arts, Science & Commerce, Mumbai

ABSTRACT

Large Language Models (LLMs), despite their remarkable fluency, suffer from critical limitations, notably knowledge hallucination and data outdatedness. The emergence of Retrieval-Augmented Generation (RAG) marked a paradigm shift, transforming LLMs from closed, parametric knowledge bases into open, dynamic systems. This paper chronologically reviews ten pivotal RAG architectures, tracing their evolution from foundational models to advanced, self-correcting mechanisms. While each innovation has significantly boosted performance—from improved fusion and multi-hop strategies to advanced search and domain-specific grounding—a critical gap remains: the lack of a robust, universally efficient, and truly context-adaptive system. We argue that the core vulnerability of RAG persists in its sensitivity to low-quality retrieved context and the inefficiency of generalized evaluation, limiting its trustworthiness and scalability across complex, real-world deployments. This analysis provides a roadmap for future research directions focused on true modularity and self-supervised grounding fidelity.

Keywords: Large Language Models, Hallucination, Retrieval-Augmented Generation, Groundedness, Factuality, Reranking, Hybrid Search, HalluLens.

1 INTRODUCTION

The rapid ascent of Large Language Models (LLMs) has ushered in an era of unprecedented natural language capability. These models, trained on vast corpora, possess an encyclopedic, albeit static, knowledge base encoded within billions of parameters [1]. This static nature, however, presents two fundamental challenges for real-world application: factual inaccuracy (known as "hallucination") and knowledge decay (inability to reference post-training information) [1].

The Retrieval-Augmented Generation (RAG) framework emerged as the de facto solution to these problems. Conceptualized as an "open-book" approach, RAG grounds the LLM's response generation process by dynamically querying an up-to-date, external knowledge corpus. The architecture combines the reasoning and synthesis power of a generator with the precision and verifiability of a retriever [2].

This paper provides a narrative review of the RAG evolutionary landscape, tracing its progression through ten foundational and state-of-the-art works. The goal is to systematically identify the key architectural milestones, synthesize the recurring technical challenges, and define the critical research gaps that must be addressed to unlock the full potential of grounded generation systems. The paper is structured as follows: Section II reviews the RAG evolutionary arc. Section III synthesizes the problem from the identified gaps. Section IV concludes the analysis and outlines limitations.

2 LITERATURE REVIEW

The RAG evolution can be segmented into four waves, each building upon the previous to address specific weaknesses in the retrieval-generation pipeline.

A. Wave 1: Foundational End-to-End Models

The first wave established the core RAG paradigm by coupling the retriever and generator in an end-to-end training loop.

REALM (2020): Retrieval-Augmented Language Model Pre-training was a critical precursor, demonstrating the power of a learnable knowledge retriever trained jointly with a Masked Language Model (MLM) objective [2]. It proved that retrieval could be made integral to the language modelling task itself, enabling the model to implicitly learn when and what to retrieve.

RAG (Lewis et al., 2020): This work formalized the paradigm. It paired the Dense Passage Retriever (DPR), a bi-encoder for efficient retrieval [5], with a BART sequence-to-sequence generator. The key innovation was the use of probabilistic marginalization over retrieved documents. The model calculated the probability of generating a sequence Y by summing the probabilities conditioned on each of the K top retrieved documents Z : $P(Y|X) = \sum_{Z \in \text{TopK}} P(Z|X)P(Y|X, Z)$

This approach allowed the generator to softly select the most relevant evidence, improving both fluency and accuracy [1].

B. Wave 2: Context Fusion and Scaling

The second wave addressed the inefficiency and input length limitations of the early RAG models, particularly RAG's complex marginalization step.

FiD (Fusion-in-Decoder) (2021): Recognizing the computational cost, FiD introduced a highly effective concatenation approach [4]. All retrieved passages are independently encoded by the model's encoder. The decoder then attends to this aggregated, concatenated context. This simplified fusion mechanism allowed the model to process a much larger number of retrieved documents, significantly scaling the available context and demonstrating superior performance on knowledge-intensive tasks [4].

DPR (Karpukhin et al., 2020): While a component of RAG, DPR's standalone contribution defined modern retrieval [5]. It optimized dense representation learning for passage retrieval, making vector-based semantic search feasible over massive corpora like Wikipedia, thereby accelerating the entire RAG pipeline's front-end efficiency.

C. Wave 3: Pre- and Post-Retrieval Enhancement

This phase focused on refining the quality and relevance of the retrieved context itself, acknowledging that initial vector search is often noisy.

Query Rewriting/Expansion: This category represents a family of pre-retrieval techniques (e.g., HyDE, Step-Back Prompting) that address the semantic gap [8]. The LLM is used to generate an intermediate artifact (a hypothetical answer or a simpler question) before the actual retrieval. This artifact, being semantically richer, results in a more relevant vector query and thus better retrieved documents.

RAG-Fusion (e.g., RRF-based RAG): These post-retrieval methods introduce re-ranking to filter the top K documents [8]. They often use Reciprocal Rank Fusion (RRF) to combine the results of multiple retrieval methods (e.g., dense vector search and sparse keyword search), selecting the most consensus-driven, high-quality context for the final prompt.

Recursive/Iterative Retrieval (IRAG/Iter-RAG): To tackle complex, multi-hop reasoning queries, these architectures introduced a sequential loop [8]. The LLM's intermediate output is used as a new query to trigger a subsequent retrieval step, allowing the system to build a chain of evidence to answer questions that require synthesizing facts from multiple steps.

D. Wave 4: Self-Correction and Adaptability

The most recent wave introduces meta-cognitive abilities, allowing the RAG system to evaluate its own retrieval and generation quality.

Self-RAG (Asai et al., 2024): This marks a major shift towards internal feedback [7]. The LLM is fine-tuned to generate special reflection tokens that signal when retrieval is necessary, and more crucially, to critique the retrieved context's quality and the generated output's relevance. This introduces dynamic, on-demand retrieval, departing from the static "always-retrieve" structure of earlier RAGs.

Noisy data or documents retrieval problem issue was handled through CRAG (Corrective RAG) which is light weight and finetuned to assess any document quality[6]. Based on a confidence score, the system triggers a corrective action: (i) using the retrieved document, (ii) performing knowledge refinement (fetching better documents), or (iii) resorting to web search, thereby enhancing robustness [6].

Structured/Graph RAG (GraphRAG, etc.): This paradigm shifts the external knowledge source from unstructured text to a Knowledge Graph (KG) [10]. Retrieval becomes a form of structured query or graph traversal, which is inherently richer in relational context. This is particularly valuable for domain-specific tasks requiring logical reasoning and relationship inference, addressing a key limitation of text-only RAG.

Here is a small summary of other works:

Paper/Concept	Primary Findings (Contributions)	Gaps/Limitations Addressed or Remaining
	Introduced the foundational RAG framework by jointly fine-tuning a pre-trained sequence-to-sequence	Gaps Addressed: Hallucination and inability to easily update knowledge in

	model (BART) and a neural retriever (DPR) end-to-end.	parametric-only LMs.
Lewis, P., et al. (2020) RAG (Retrieval-Augmented Generation)	Achieved SOTA on knowledge-intensive NLP tasks like open-domain Question Answering (QA) and Fact Verification (FEVER).	Remaining Gaps: The retriever is static after fine-tuning; the generator may still over-rely on its internal knowledge or struggle with noisy retrieval.
Guu, K., et al. (2020) (Retrieval-Augmented	Integrated an implicit knowledge retriever directly into the pre-training objective (Masked Language Modelling, MLM), treating the retrieved document as a latent variable.	Gaps Addressed: Made the retrieval process a first-class citizen during pre-training, enhancing the LM's internal knowledge base for retrieval.
	Showed that pre-training with retrieval leads to superior performance on downstream knowledge-intensive tasks.	Remaining Gaps: Retrieval is still a pre-training step and not dynamically optimized at inference; potential computational expense of fine-tuning the entire model end-to-end.
Karpukhin, V., et al. (2020) DPR (Dense Passage Retrieval)	Introduced Dense Passage Retrieval (DPR), a bi-encoder framework for training highly effective dense retrievers using a large amount of weak supervision (question-answer pairs).	Gaps Addressed: The sub-optimal performance of sparse retrieval methods (like BM25) for semantic search and open-domain QA.
	Demonstrated that a simple Maximum Inner Product Search (MIPS) on dense vectors outperforms advanced sparse methods, setting the foundation for RAG's retriever component.	Remaining Gaps: Relies on negative sampling, which is crucial but complex; the internal knowledge of the pre-trained model can limit retrieval performance.
Izacard, G., et al. (2021) FiD (Fusion-in-Decoder)	Proposed a simple yet powerful decoder-side fusion mechanism that concatenates all retrieved passages in the encoder and allows the decoder to cross-attend over them.	Gaps Addressed: Inefficient or sub-optimal ways previous methods combined information from multiple retrieved documents for final generation.
	Improved performance on knowledge-intensive QA by effectively synthesizing information scattered across multiple documents.	Remaining Gaps: The concatenated input can lead to very long sequence lengths, increasing computational cost and potential information overwhelm in the attention mechanism.
Izacard, G., et al. (2021)	Proposed a knowledge distillation method to train a better retriever by using the cross-attention scores of a strong Reader model as a soft label/signal for the Retriever.	Gaps Addressed: The difficulty of training high-quality retrievers without strong, manually annotated query-document pairs.
	Showed that this iterative process significantly improves retrieval and overall QA performance without expensive manual labelling.	Remaining Gaps: The iterative training procedure can be slower; the quality of the 'distilled' signal is bounded by the Reader's own capacity and potential biases.

Asai, A., et al. (2024)	Introduced a framework where the LLM learns to retrieve on demand, and critically critique its own generation based on the retrieved information using "reflection tokens."	Gaps Addressed: Static, mandatory retrieval in traditional RAG (retrieving even when unnecessary); lack of mechanisms for the model to self-correct based on retrieved context.
	Achieved higher factual accuracy and verifiability by explicitly deciding if, when, and what to retrieve, and then assessing the quality/support of the generated text.	Remaining Gaps: Requires an extensive and diverse corpus of (query, reflection tokens, retrieved passages, generation) for effective fine-tuning, which is complex to create.
Lyu, Y., et al. (2024) CRAG (Corrective RAG)	Proposed a retrieval evaluator that assesses the quality of initial retrieval and takes one of three corrective actions: refine, web search, or ambiguous fusion.	Gaps Addressed: The poor robustness of RAG when initial retrieval is irrelevant or of low quality (a major cause of hallucinations).
	Demonstrated enhanced robustness and factual accuracy by dynamically adapting the retrieval strategy to the quality of the initial	Remaining Gaps: The lightweight retrieval evaluator and the corrective actions (like web search) introduce additional latency at inference time.
	results (e.g., using a web search for low-quality retrieval).	
Chain-of-Note Rewriting/Expansion/Re-ranking Example)	A prompting/fine-tuning paradigm that forces the model to generate intermediate "reading notes" or re-rank passages, simulating a human-like thought/research process.	Gaps Addressed: Over-reliance on a single, one-shot retrieval and immediate generation; improves the utility of retrieved information by enforcing intermediate processing.
	Leads to a more systematic evaluation of retrieved documents, reducing the impact of noisy or irrelevant passages (the "needle in a haystack" problem).	Remaining Gaps: Increased token usage and latency due to intermediate steps; complexity in crafting effective prompt templates or fine-tuning the model for the "note" generation.
Multimodal RAG (e.g., LLaVA-RAG, RetGen)	Extends RAG to handle and retrieve diverse data types (text, images, video) by mapping them to a shared or aligned embedding space (cross-modal retrieval).	Gaps Addressed: The strict limitation of traditional RAG to only text-based knowledge bases; inability to answer questions requiring visual or audio evidence.
	Enables "any-to-any" retrieval (e.g., text query to image result) and grounded generation across multiple modalities.	Remaining Gaps: Requires sophisticated and resource-intensive multimodal encoders/projectors; challenging to maintain semantic coherence across different data modalities.
	Leverages Knowledge Graph (KG) structures to encode relationships between entities, using graph traversal/embedding for retrieval instead of, or in addition to, text chunks.	Gaps Addressed: Traditional RAG struggles with questions requiring multi-hop reasoning or understanding complex relationships, which KGs are designed to

GraphRAG/Structured RAG		handle.
	Improves performance on multi-hop QA and provides outputs grounded in structured, verifiable facts and their relationships.	Remaining Gaps: Requires significant upfront effort to construct and maintain the high-quality Knowledge Graph; typically performs less well on single-hop, detail-oriented questions than text-based RAG.

Human annotation or rely on LLM-as-a-judge metrics whose own reliability is debatable.

3 PROBLEM STATEMENT AND GAPS

The synthesis of these ten advancements highlights a fundamental, persistent tension in RAG systems, which we term the Grounding Fidelity Paradox.

The core problem is that architectural enhancements designed to improve Grounding Fidelity (e.g., CRAG, Self-RAG) inherently introduce significant Computational Overhead, while methods focused on Retrieval Coverage (e.g., RAG-Fusion, FiD) often remain vulnerable to soft noise and low Grounding Fidelity.

This paradox is driven by three interconnected gaps:

A. Gap 1: The Robustness to Soft Noise

RAG systems remain fragile when retrieved documents contain highly plausible but incorrect information ("soft noise"). Traditional RAG indiscriminately uses the context. While Self-RAG and CRAG attempt correction, their decision-making mechanism (the reflection token or the retrieval evaluator) adds a layer of complexity that is itself prone to error. The system's robustness is tethered to the quality of its internal critique mechanism, which is difficult to train and validate universally.

B. Gap 2: The Scalability-Fidelity Trade-off

The deployment of state-of-the-art architectures is severely limited by a direct trade-off with efficiency. Techniques like multi-stage re-ranking (RAG-Fusion) or sequential self-reflection (Self-RAG) significantly increase latency. For high-throughput, low-latency enterprise applications, the cost of achieving maximal Grounding Fidelity becomes prohibitively high. An architecture that is both highly accurate and real-time efficient remains an open challenge.

C. Gap 3: The Evaluation Deficit

The current RAG evaluation landscape is fragmented and insufficient. Metrics often rely on proxies like retrieval, Recall and Precision, which do not fully measure Fidelity (Is the answer supported only by the context?) or Relevance (Is the context necessary for the answer?). The lack of an efficient, unified, and truly context-aware evaluation framework slows down the research cycle. New architectures require costly, non-scalable

4 CONCLUSION

The evolution of Retrieval-Augmented Generation is a narrative of continuous refinement, transforming Large Language Models into verifiable and timely knowledge engines. From the foundational joint training of RAG (2020) to the self-aware, corrective loops of CRAG and Self-RAG, the field has made tremendous strides in tackling hallucination and knowledge staleness.

However, the analysis of these ten core works reveals that the next frontier is defined by overcoming the Grounding Fidelity Paradox. Future research must focus on designing architectures that are not merely augmented by retrieval, but are truly adaptive, enabling efficient, fine-grained context utilization and noise suppression without incurring crippling latency penalties. The ultimate goal is a RAG system where grounding is not an external constraint, but an intrinsic, self-supervised guarantee of trustworthiness.

Limitations and Future Work:

This review is limited by its focus on ten representative works and does not fully address the equally critical operational challenges of knowledge base maintenance, chunking strategies, and domain-specific embedding drift. Future work should target the development of:

- 1. Self-Supervised Grounding: Training signals that allow the LLM to learn context fidelity entirely from the

knowledge base itself, minimizing the reliance on costly, task-specific reflection or correction tokens.

2. **Adaptive Query Caching:** Mechanisms that dynamically manage the retrieval and re-ranking cost based on the predicted complexity or confidence of a query, optimizing the trade-off between fidelity and latency in real-time.
3. **Unified RAG Evaluation Benchmarks:** Standardized, reference-free metrics that holistically quantify factual consistency, context adherence, and answer relevance.

5 REFERENCES

- [1] Lewis, P., et al. (2020). Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks. Advances in Neural Information Processing Systems (NeurIPS 33).
- [2] Guu, K., et al. (2020). REALM: Retrieval-Augmented Language Model Pre-training. International Conference on Machine Learning (ICML).
- [3] Izacard, G., et al. (2021). Distilling Knowledge from Reader to Retriever for Question Answering. The 59th Annual Meeting of the Association for Computational Linguistics (ACL).
- [4] Izacard, G., et al. (2021). Fusing a Retriever into a Transformer for Knowledge-Intensive NLP Tasks (Fusion-in-Decoder, FiD). International Conference on Learning Representations (ICLR).
- [5] Karpukhin, V., et al. (2020). Dense Passage Retrieval for Open-Domain Question Answering (DPR). International Conference on Learning Representations (ICLR).
- [6] Lyu, Y., et al. (2024). Corrective Retrieval Augmented Generation (CRAG). arXiv preprint arXiv:2401.15884.
- [7] Asai, A., et al. (2024). Self-RAG: Learning to Retrieve, Generate, and Critique through Self-Reflection. International Conference on Learning Representations (ICLR).
- [8] Chain-of-Note (Query Rewriting/Expansion/Re-ranking Example): A general concept encompassing advanced prompt engineering for retrieval.
- [9] Multimodal RAG (e.g., LLaVA-RAG, RetGen): A broad architectural paradigm focused on cross-modal retrieval and generation.
- [10] GraphRAG/Structured RAG: A modern domain-specific RAG approach leveraging Knowledge Graph structures for enhanced reasoning.

INCLUSIVE UI/UX DESIGN FOR E-LEARNING: A CASE STUDY OF EDUABLE

¹Harshida Prajapati and ²Dr. Neelam NaikDepartment of Information Technology, Usha Pravin Gandhi College of Arts, Science and Commerce
Mumbai, Maharashtra, India harshidaprajapati8@gmail.comDepartment of Information Technology, Usha Pravin Gandhi College of Arts, Science and Commerce
Mumbai, Maharashtra, India neelam.naik@upgcm.ac.in**ABSTRACT**

Inclusive e-learning requires effective design of a user's interface and experience (UI/UX) that makes the system usable and accessible to users with diverse capabilities and technical skills; however, the majority of current e-learning platforms are not designed to provide an adaptable user interface for inclusive learning. The EduAble is an e-learning system that has been designed using principles of adaptive UI/UX and accessibility. It includes an interface that allows users to switch between light and dark modes; use a zoom feature; and navigate the system audio via audio commands. A user-centered usability evaluation was performed on users from four different categories (disabled, novice, intermittent, expert) to gain insight into how well users were using the EduAble platform. Results from this evaluation indicate that the use of audio-based navigation tools and adaptive user interfaces enhance the usability, accessibility, and user satisfaction of e-learning systems. Findings of this research support the need for inclusive UI/UX design when designing for e-learning.

Keywords - UI/UX Design, Inclusive E-Learning, Accessibility Design, Adaptive User Interface, Usability Evaluation, Audio- Based Navigation, EduAble Platform

I. INTRODUCTION

Designing user interfaces (UI) and user experience (UX) is very important for ensuring how easy it will be to use, how accessible it will be for all people and whether or not it will actually work. Good designs for both UIs and UXs will lower the cognitive load required to use an application, improve navigation efficiency and create user satisfaction by allowing users to use the app intuitively when they interact with it. [1][2] In particular, with the growing number of digital apps popping up in every area of our lives such as education through e-learning, Health Care technology, etc., it is becoming increasingly critical to create applications that are designed to be user-centred and accessible to all types of users.

The emergence of the electronic Learning systems as viable means of distributing Educational opportunities to diverse users within our society has been on the rise [3]. Until recently, most electronic Learning systems had a one size fits all design, and in the development of many, consideration was not given to creating an Electronic Learning System that would meet the needs of the users needing and using the platform. This has led to ineffective learning and poor engagement by Users due to barriers created by existing Electronic Learning Systems.

Adaptive UI/UX design is designed to cope with the limitations of traditional user interface design by adapting user interaction components and user interface elements to meet the needs of users, their interactions, and to accommodate the context of usage or behaviour of users. Past

studies indicate that Adaptive and Accessible User Interface features, like adaptable visual themes, navigation via audio, and consistent user interface design structures, enhance user experience and promote learning outcomes [4][6] Inclusive User Experience is accomplished through utilising these Adaptive UI/UX Design features to enhance the ability of users with varying degrees of ability to use digital technology.

There has also been an increasing amount of research conducted around the potential of Artificial Intelligence AI technology to augment and support User Experience Design and Evaluation. There is also a growing body of research demonstrating how AI can be used to both analyse user interface designs and assist in identifying user interface design problems and assist in user-centred design decisions [5]. Although, the research conducted to date indicates the strong potential of AI to support User Interface/UX Systems, the current level of application of AI to real-world e-learning systems is still minimal.

This research project specifically focused on designing and evaluating an inclusive e-learning website, called EduAble, that utilizes User Interface / User Experience (UI/UX) design principles. The site's features promote accessibility through options for light/dark mode, zoom functionality, audibased navigation, as well as consistency in layout/interface across the site, which were developed to assist all users (disabled, novice, intermittent and expert).

A design-focused approach to user experience (UX) coupled with AI-assisted analysis was employed to assess the effectiveness of these site features by means of user feedback and observational studies. In bridging the gap between the theory behind creating a user- friendly UI/UX to the actual deployment of such technology, this research will support the development of better, more inclusive and accessible e-learning systems.

II. RELATED WORK

Many previous investigations provide a comprehensive overview on how applying UI/UX principles can help you to make your website more engaging for your users through higher levels of usability when they navigate the site. Research has significantly demonstrated that using accessibility-based design features (i.e., visual and auditory navigation, and uniformity of layout) improves interaction with your site's users [2][6].

Past studies that have focused on creating adaptive user interface (UI) & User Experience (UX) suggested designing adaptive user interfaces based on a user's behavior patterns or by analyzing the actions taken by the user and feedback from the user [4].



Fig. 1. Framework of adaptive UI/UX design in the EduAble platform for different user groups.

More recently, researchers have also begun exploring the role of artificial intelligence (AI) within UI/UX Design and how AI can enable the development of Human-Centric and Inclusive Systems [5]. Additionally, one review found that there are many challenges and future research opportunities related to applying adaptive UI/UX systems to educational platforms [3] and [8].

The present work additionally includes the validation and evaluation of the practical application of adaptive UI/UX to a fully functional e-learning environment, EduAble, which also aims at creating an environment that is accessible, usable, and inclusive in order to provide the most optimal educational experience for all users.

III. PROPOSED SYSTEM: EDUABLE

The EduAble platform is an e-learning solution that includes many features previously inaccessible or difficult to use with conventional online classes. Through adaptive UI/UX technology, EduAble has been designed to provide all users with an ease of use at their own level.

The Following are the some of the Key Features of EduAble:

A. Light and Dark Mode:

EduAble offers light and dark themed versions of its website for better eye comfort and to alleviate eye strain from prolonged use, especially for visually sensitive or low-light situation.

B. Zoom In and Zoom Out Functionality:

Users can resize text and interface elements (buttons, controls, etc.) according to their eyesight; the ability to zoom in/out is particularly beneficial for seniors & anyone with low vision.

C. Audio-Based Link Identification:

When hovering over a link with a mouse, users will hear an audio alert announcing its purpose. This feature assists users who are blind, as well as those who are new to using EduAble, with knowing where to go next and what options are available.

D. Voice-Assisted Navigation:

Voice-assisted navigation is available on the EduAble Platform to improve accessibility and facilitate users' ability to communicate with the platform according to their diverse needs. This functionality allows users to use their voice as an interface to navigate the platform and access their learning materials, which will eliminate the need to depend solely on conventional means of entering data (i.e., keyboard/mouse). Voice-assisted navigation can provide tremendous benefits to users who are blind and physically limited in their ability to use traditional methods of interaction with a computer or device. Additionally, voice-assisted navigation can provide great assistance to new users in navigating the site with ease while minimizing the cognitive processing required when using the platform. Users will feel more comfortable interacting with the EduAble platform by controlling it hands- free and having access to an inclusive learning environment.

In conclusion, the integration of voice-assisted navigation will create an even more accessible, efficient, and user-friendly e- learning experience for everyone.

E. Consistent and Familiar Interface:

The EduAble interface is designed with consistent layouts, icons, and navigation throughout the entire platform, making it easier for users who use the product occasionally to learn how to use it again when they return to it.

F. Shortcut and Efficiency Features:

EduAble has built-in keyboard shortcuts and quick access functionality for the experienced user, allowing for a more productive and efficient experience.

Figure 1 depicts the adaptive user interface/design framework that was implemented in the EduAble Platform. Through the framework, we can see how the various types of users relate to the interface features that focus on making the platform accessible, as well as how those interface features affect user accessibility to the platform. The Adaptive UI/UX framework provides the basis for the evaluation methodology that will be discussed in greater detail in the next section.

TABLE I

User Group	Design Requirement	Adaptive UI/UX Features in EduAble
Disabled Users	Accessibility, auditory support, visual adaptability	Audio-based link identification, voice-assisted navigation, zoom in–zoom out, light/dark mode
Novice Users	Simplicity, clarity, ease of navigation	Consistent interface layout, clear navigation structure, audio cues on hover
Intermittent Users	Familiarity, consistency	Uniform page layout, predictable navigation flow, reusable UI components
Expert Users	Efficiency, speed, user control	Keyboard shortcuts, quick access controls, minimal interaction steps

Fig. 2. Adaptive UI/UX features for different user group in EduAble.

Table 1 provides an organized overview showing how each type of user accessing the EduAble platform is provided with different adaptive UI/UX capabilities based upon their personal experience level and accessibility requirements. The table shows that for each type of user who accesses EduAble, a variety of interface designs were incorporated to provide a specific adaptive capability (for example, visual accessibility settings, audio-based navigation, or regular interaction pattern) based upon their unique usability needs. By aligning

these capabilities with the specific usability needs associated with each type of user that accesses EduAble, accessibility is improved for everyone, cognitive load is reduced for everyone, and ease of use is also enhanced for everyone. The mapping of adaptive UI/UX capabilities to the usability requirements of each type of user demonstrates the purposefully inclusive design approach utilized by EduAble and supports the validity of the adaptive UI/UX framework to provide a highly flexible, user-directed learning experience.

IV. IMPLEMENTATION OF EDUABLE PLATFORM

At the center of the EduAble platform's design is the inclusive and adaptable user interface (UI) and user experience (UX) to enable all users, regardless of their capabilities or level of computing experience, to use the technology successfully. The design process focused on the user interaction and interface behaviours, as well as on the development of assistive mechanisms, and the developing of the support services that would be used for users with various types of disabilities. Little attention was placed on back-end architectural design or algorithmic complexity. To provide support for these users, the platform contains adaptive visual components and audio-assisted navigation to assist users with differing abilities and levels of computing experience. The platform also maintains a consistent and uniform look and feel across multiple modules to decrease the learning curve for all users and to give all users a sense of familiarity and increase usability. The collective effect of all of these design considerations results in an educational resource that is highly usable and accessible to all users.

A. Platform Interface Overview:**Fig. 3.** EduAble platform home interface.

The home page of the EduAble Learning Management System gives users immediate access to learning modules and options for personalized accessibility features as shown in Fig. 2, allowing them to begin using key features of EduAble right away. The user-centric design principle of the EduAble Learning Management System emphasizes simplicity and clarity, so the overall design of the EduAble Learning Management System offers a uniform experience for all learners. To minimize visual clutter and enhance the user's cognitive capacity, a clean and organized page layout was created to support efficient navigation. A consistent placement of the navigation menus, icons and other interface components is maintained throughout all pages of the EduAble Learning Management System to enhance user familiarity with and to facilitate the ease of navigation for first-time and occasional users. These design principles help users quickly grasp how the EduAble Learning Management System operates and minimise the need for re-learning while improving the overall usability throughout the entire EduAble Learning Management System.

B. Visual Accessibility Implementation:**Fig. 4.** The implementation of light mode, dark mode, and visibility- focused.

Figure 3 shows the light, dark, and visibility-enhanced interfaces available on the EduAble platform. The aim of these multiple display modes is to provide users with additional options for increased accessibility when using EduAble. The Light Mode is intended to be used under normal lighting conditions; the Dark Mode is designed for reducing strain on the eyes when used in low-light conditions; and the Enhanced Visibility controls will assist users in identifying interactive elements better. By providing users with options to customize their interface displays based on their personal needs and visual preferences, the EduAble platform can help users feel more comfortable when using the EduAble service.

C. Audio-Based Navigation Implementation:**Fig. 5.** Audio-based link identification in the EduAble platform.

Figure 4 illustrates the use of an audio identification system while users interact with the system. An audio navigation system was designed to support visually impaired users and inexperienced users by providing auditory support during their interactions. As such, the EduAble platform allows the user to choose an audio learning mode and has auditory support options via accessible interface controls. As a user interacts with the audio learning mode, they are provided audio prompts, or "cues", to assist them in selecting the features of the system and content available to them. This method aids in reducing dependence on visual elements and improving clarity of navigation through the content.



Fig. 6. Consistent navigation structure across the EduAble platform.

D. Consistency and Efficiency Features:

The navigation structure that is consistent throughout the various platforms can be seen in Figure 5. The EduAble platform uses consistent layouts, typography, iconography, and navigation patterns to help minimize the amount of time it takes to learn how to use the platform. For users with more experience, keyboard shortcuts and Quick Access Controls were added to help speed up the task execution process. Efficient features help users become more productive while still providing simplicity for less experienced users.

V. RESEARCH METHODOLOGY

A. Research Approach

This study has undertaken an AI-assisted and design- driven analysis method for evaluating the efficacy of adaptive UI/UX features on the EduAble E-Learning Platform. The analytical method for this study includes a focus on the design decisions made and their subsequent effect on the usability, accessibility, and user engagement with the product, rather than on algorithmic or quantitative metrics for performance. AI tools were employed for the literature review, identification of relevant UI/UX design patterns, and to assist in developing the research framework.

B. User Group Selection

As the first step in usability assessment, users were classified into four distinct categories based on the user's experience level and any assistive technology that they might need to use when interacting with EduAble. The four groups classified were: disabled users, novice users (new to the platform), sporadic users (somewhat familiar but infrequent usage), and proficient users or experts (very experienced with the platform). This structure allowed for a diverse range of interaction types and user accessibility requirements to be captured while evaluating the implementation of specific UI/UX features. By separating users into these four groups, the evaluation could specifically examine how well the implemented UI/UX features met the defined needs of each category. It also allowed for an organized representation of how users interacted with the system, compared and contrasted with users from the various levels of experience; thus creating a comprehensive picture of the adaptability and inclusivity of EduAble..

C. Data Collection Method

Task-based usability interaction and structured user feedback were used for data collection. The user interface of the EduAble platform was tested by participants in order to obtain information regarding the following aspects of interaction: mode selection, navigation menus, visual accessibility controls, and audio-based assist features. Users' interactions were observed to determine how effectively users navigate through the interface, and also how easy it is to use and how effective the interface is in terms of accommodating the visual and audio assistance. Additionally, user feedback was collected to gauge users' perceptions of their comfort level, clarity of use and satisfaction.

D. Evaluation Parameters

Aspects of Usability/Aesthetics and Accessibility were evaluated on multiple levels to determine measures of success with respect to the implementation of UI and UX characteristics.

These aspects included navigation ease, visual readability, availability of access support, completion rate of tasks, and general user satisfaction. Analysis of user errors, indecisiveness (hesitation), and already completed (selected) features were also reviewed.

E. Data Analysis Technique:

Observations and feedback were collected and analyzed qualitatively from a design-driven perspective by utilizing a design-driven analytic framework. The focus of the analysis was on identifying usability-related "trends" as well as understanding how users interact with or behave toward an application via the types of tools that are part of the overall experience and how individual UI/UX features contribute to the overall improved interaction with the UI, as well as the overall increased accessibility for all users. These outcomes from the qualitative analysis were then used to develop the subsequent section results and discussion.

VI. RESULT AND DISCUSSION

In this section, we will discuss the observations and conclusions drawn from the evaluation of the usability of the Adaptive User Interface and User Experience (UI/UX) of the EduAble platform through a usability evaluation that analysed how users interacted with the Adaptive UI/UX of the EduAble platform across various groups of users including people with disabilities, novice users, occasional users or intermittent users, and expert users.

A. Observations

All users were able to use the EduAble platform with minimal assistance to navigate through its Adaptive UI/X. Individuals with disabilities were able to navigate the EduAble interface with greater confidence because of the ability to identify links via audio, and the ability to use the zoom feature for all types of content. Novice users took less time to understand the layout of the EduAble platform because it provided a layout that was consistent across the interface and had a clear structure for navigation. Intermittent users could resume usage of the EduAble platform easily without the need to relearn how to navigate through the interface. Expert users were able to complete tasks on the EduAble platform faster than other users because they were able to take advantage of the use of shortcut keys and other types of controls that enhance their efficiency while using the EduAble platform.

B. User Feedback

Overall, users had positive feedback regarding their experiences using the Adaptive UI/UX of the EduAble platform. The majority of users indicated that the availability of light and dark modes for visual comfort was a major benefit, and that the use of audio navigation helped them tremendously, especially individuals with visual impairments and novice users. All users felt that the use of Adaptive UI/X reduced their cognitive load and enhanced their overall experience with the EduAble platform compared to what they experienced with traditional e-learning systems.

C. Feature Impact Analysis

A direct evaluation of the effects that specific UI/UX elements have on how users interact with and react to them was done by observing how users interacted with the UI/UX elements via direct observation and/or engagement with the

product. The implementation of using the zoom feature on a smartphone or tablet to zoom in and out of an electronic document increased the ability of the user to read the content, especially for visually impaired users because it allowed for increased flexibility in changing the size of text and/or interface elements on the screen. Audio prompts were a significant factor in assisting users to navigate through the interface, helping them build a better understanding of where they are in relation to the interface and reducing the number of errors made when navigating. For users who only sporadically visit the platform, using consistent layouts and standard navigation patterns reduced confusion and improved the learning curve when returning. Keyboard shortcuts and other quick access features improved task efficiency for power users by reducing the number of steps and the time taken to complete a task. Overall, the analysis shows that each of the adaptive features was positive in improving usability, accessibility, and user satisfaction among all types of users.

D. Link with Proposed Framework

This research supports the adaptive UI/UX framework presented in figure 1, as the framework presents the appropriate adaptive interface features to each user group based on their needs for usability and accessibility. The observations made by users, as well as the feedback given, show that implementing the targeted design choices made by the researchers provides an increase in usability of the system.

VII. CONCLUSION

This study demonstrates how a design, develop, and evaluate process can be used to create an inclusive e-learning platform, called EduAble, using adaptive user interface and user experience (UI/UX) design principles. The study found that implementing accessible design features such as; audio- based navigation, visual adaptability, and consistent interface layout greatly enhances usability for multiple user groups. Usability improvements were seen across users with disabilities, users with limited technology experience, intermittent technology users and experienced technology users; thus adaptive UI/UX design provides a way to meet the varying needs of accessibility and usability within an individual platform.

This research supports evidence for the need for inclusive design in the field of educational technology and illustrates the positive effect of adaptive interface features on user interaction, accessibility and overall user satisfaction. Focusing on behavior of an interface and user-centered design instead of system complexity, EduAble offers users a flexible and accessible e-learning environment.

Future development of the EduAble platform can extend accessibility by supporting access to educational content that is complex such as math equations, scientific diagrams, and other harder educational resources. Future phases of the EduAble project will also include the exploration of better techniques for representing content and providing advanced access to education for all users regardless of learning differences. These future phases will continue to create inclusive educational opportunities and increase the potential for EduAble to be used in many academic disciplines.

REFERENCES

- [1] K. W. Kong, "Importance of UI/UX design in enhancing mobile and web app functionality," Techies App Blog, Jun. 10, 2024. [Online]. Available: <https://techies.app/blog/ui-ux-design>
- [2] A. Alzahrani, "UI/UX design principles, trends, and best practices," ResearchGate, 2024. [Online]. Available: https://www.researchgate.net/publication/389701340_UIUX_Design_Principles_Trends_and_Best_Practices
- [3] M. Ahmed and S. Hassan, "User interface and user experience design methodologies and evaluation techniques: A systematic literature review," ResearchGate, 2024. [Online]. Available: https://www.researchgate.net/publication/389461787_User_Interface_and_User_Experience_Design_Methodologies_and_Evaluation_Techniques_A_Systematic_Literature_Review
- [4] R. Sharma and A. Patel, "Advancements in UI/UX design models for adaptive systems," Semantic Scholar, 2024. [Online]. Available: <https://www.semanticscholar.org/reader/c1328ffd660dce1e9d16b5f3b568f1987a0bc575>
- [5] H. Singh and K. Raj, "Human-centered UI/UX approaches with AI integration," arXiv preprint arXiv:2411.00381, Nov. 2024. [Online]. Available: <https://arxiv.org/pdf/2411.00381>
- [6] S. Kumar, "The impact of user interface design on user engagement," International Journal of Engineering Research & Technology (IJERT), 2025. [Online]. Available: <https://www.ijert.org/research/the-impact-of-user-interface-design-on-user-engagement>
- [7] M. R. Ali and T. F. Tan, "Website UI/UX analysis and redesign using usability testing methods," ResearchGate, 2024. [Online]. Available: https://www.researchgate.net/publication/381660427_Website_UIUX_Analysis_and_Redesign_using_Usability_Testing_Methods
- [8] P. Dasgupta, "A review paper on UI/UX design in the digital era: Trends, challenges, and educational gaps," ResearchGate, 2025. [Online]. Available: https://www.researchgate.net/publication/392007987_A_Review_Paper_on_UIUX_Design_in_the_Digital_Era_Trends_Challenges_and_Educational_Gaps
- [9] R. N. Joshi, "Implementation of UI/UX concepts and techniques in web layout design with Figma," ResearchGate, 2024. [Online]. Available: https://www.researchgate.net/publication/379484204_Implementation_Of_UIUX_Concepts_And_Techniques_In_Web_Layout_Design_With_Figma

PREDICTIVE ANALYTICS IN HEALTHCARE FOR EARLY DISEASE DETECTION

¹Heli Dakhra and ²Dr. Neha Vora¹Student M.Sc.IT(SVKM'S Usha Pravin Gandhi College Of Arts, Science and Commerce, Mumbai India)²Professor (SVKM'S Usha Pravin Gandhi College of Arts, Science and Commerce, Mumbai India)¹helidakhara942@gmail.com and ²neha.vora@upgcm.ac.in**ABSTRACT**

The growing global burden of chronic and acute diseases calls for a paradigm shift from reactive to proactive healthcare systems. Predictive analytics, fueled by machine learning (ML) and deep learning (DL), is rapidly emerging as the key facilitator for the early diagnosis of diseases, leading to improved prognoses and decreased healthcare expenditures. This paper presents a review of the current state-of-the-art in the application of DL algorithms to various medical data sources, such as medical images and Electronic Health Records (EHRs), for predicting the development or progression of diseases such as cancer, cardiovascular disease (CVD), sepsis, and Alzheimer's Disease (AD). We summarize the progress made from a comprehensive analysis of twenty key papers, emphasizing the success achieved by Convolutional Neural Networks (CNNs) and Recurrent Neural Networks (RNNs). From the identified shortcomings, specifically the "black-box" nature of DL, data heterogeneity, and privacy issues, we develop a new framework that combines an interpretable hybrid model with Federated Learning (FL) to develop robust, trustworthy, and scalable predictive models for broad clinical use healthcare environments.

Keywords: Predictive Healthcare Analytics, Deep Neural Learning Models, Early-Stage Disease Prediction, Electronic Health Record Systems (EHRs), Convolutional Neural Network Architectures (CNNs), Recurrent Neural Network Models (RNNs), Model Explainability, Privacy-Preserving Federated Learning

I. INTRODUCTION

The current healthcare environment is characterized by large, complex, and longitudinal data. Ranging from high- resolution medical images to detailed time- series data infused into Electronic Health Records (EHRs), this data explosion is the gateway to personalized and predictive healthcare. However, the problem lies in the ability to convert this data into actionable clinical intelligence. Conventional statistical analysis tends to fail in understanding the non- linear patterns and complex temporal relationships that exist in biological and clinical phenomena. Predictive analytics, driven by advanced ML and DL algorithms, overcomes this problem by identifying deeply embedded patterns that indicate the onset of a disease before its symptoms become clinically visible. This is especially revolutionary for diseases where early treatment is critical, such as cancer and sepsis. This paper is an in-depth investigation of this technological shift, tracing the milestones of success, facing the ongoing challenges, and charting a course for future clinically feasible predictive models for early detection.

II. RELATED WORK AND LITERATURE REVIEW

The use of deep learning to identify diseases at the earliest stage possible is creating new potential for early diagnosis by utilizing a wide variety of methods in different fields of medicine. An outstanding example of this is the

work done by Esteva et al. [1], who trained a convolutional neural network on a large dataset of images to evaluate the characteristics of skin lesions with a level of precision comparable to or higher than dermatologists who have been board certified. Esteva et al.'s work represented the first successful application of convolutional neural networks to the area of visual diagnosis. The application of a CNN for image classification was expanded on by Poplin et al.

[2] when they demonstrated that a deep learning model could accurately predict many of the traditional cardiovascular risk factors (e.g., blood pressure, smoking status, etc.) simply from a retinal scan, thereby providing a way of using the retina as a "window" into the cardiovascular system. Moreover, this research also showed the ability of the deep learning algorithms to identify subtle but non-evident biomarkers of disease. Another area that has been impacted by the application of deep learning is the diagnosis of breast cancer. In this case, transfer learning was used to fine-tune pre-trained CNNs for use with mammography data, allowing for significant improvement in the accuracy of breast cancer diagnosis with a reduced need to re-train a model from scratch [3]. The ability to identify subtle changes in the structure of the brain related to Alzheimer's disease (AD) through the use of three- dimensional convolutional neural networks (3D-CNNs), which are being used to identify early indicators of AD by examining an individual MRI volume, has also been demonstrated to be effective in providing accurate classifications of the earliest indication of the disease [4].

In addition to static images, the research community has made great progress in working with EHR data. EHRs contain rich, longitudinal, time-series information that allows researchers to access much more than just a snapshot of a patient's health status at one given point in time. One highly-cited research paper titled "Deep Patient" used an unsupervised deep learning algorithm to create higher-level representations of patients across many different disease categories to predict the future onset of these diseases accurately [5]. Che et al. [6] demonstrated the ability of Recurrent Neural Networks (RNNs) to model irregular time-stamped events that occur in EHRs to produce better predictions about the development of acute conditions such as sepsis,

because every hour can be critically important for sepsis patients. The temporal modeling ability of RNNs has been further demonstrated through research by Choi et al. [7], who successfully predicted the development of heart failure by leveraging RNNs to detect subtle declines in cardiovascular function over time. Rajkomar et al. [8] have shown, on a large sample scale, that deep learning algorithms can predict clinical outcomes inside hospitals — including mortality rate and prolonged hospital stay due to complications — with improved accuracy compared to traditional clinical scoring methods. All of these studies have increased the confidence and practical applications of prediction via EHR data.

The increased concentration of scientific literature regarding the management of chronic diseases and the refinement of techniques for detecting chronic illnesses has been observed over time. The use of feature engineering techniques with ensemble methods, such as Random Forests, has been identified in studies as being critical to the development of very robust and efficient models for Chronic Kidney Disease (CKD) [9] as a result of the difficulties associated with high-dimensional clinical data. The real-time and personalized nature of cardiovascular risk assessments generated from IoT devices through the combination of ensemble learning and IoT data collection has been established as viable [10]. Regarding data quality, which has been a long-standing difficulty in healthcare research, B. Al-Daoud et al. [11] found that the combination of Genetic Algorithm and Artificial Neural Network (ANN) would yield a more reliable classification of Cancer, where pre-processing and optimization of features is the important first step. A recent review of diabetic patient population characteristics has suggested there are an abundance of different types of ML techniques being leveraged in diabetes diagnosis and monitoring [12].

Efforts to improve the integration of AI into clinical settings have focused primarily on overcoming practical barriers. A key barrier has been that interpretability is one of the main reasons clinicians do not trust many types of AI. Advances in interpretability have taken place, particularly for sepsis prediction models. Two methods have emerged that provide an explanation of individual predictions, i.e.,

transforming a model into a "glass box" from the "black box" of uncertainty regarding the interpretation of a model's predictions. SHAP (SHapley Additive exPlanation) values are one way to explain individual predictions related to sepsis prediction [13]. The use of a Gradient Boosting model that utilized feature importance analysis allowed for a clearer explanation of the rationale behind its prediction of early Acute Kidney Injury (AKI) [14]. There are several solutions to the issues of lack of data generalizability between institutions and scarcity of large enough datasets. S. Zhang's group [15] developed a method to search for prostate cancer using multi-modal fusion of medical images with clinical data. O. R. et al.

[16] have provided evidence for the viability of Federated Learning (FL) for the classification of pneumonia using FL to allow multiple hospitals to train a predictive model without the sharing of sensitive patient data. Hybrid deep learning architectures have combined the benefits of a CNN plus a recurrent neural network (RNN), e.g., LSTM's ability to model temporal order, to be useful for complex tasks involving ECG-based heart disease prediction

[17] as well as the analysis of longitudinally collected data to help in diagnosing depression [18]. Johnson et al. [19] demonstrated that there is a requirement to build robustness in order to counteract shifts in the data; this was further confirmed by Johnson et al's research on predicting the severity of COVID-19. This research further identifies how vulnerable models are to these shifts when they are implemented in scenarios for which they were not designed. In addition, the use of deep auto-encoders may allow for more complex pattern recognition for general health monitoring without the need for a supervised learning mechanism. This suggests that it may be possible to develop algorithms that learn to identify features of interest without having explicit labels associated with any particular disease [20].

III. GAPS AND FINDINGS

There are still several key barriers that need to be resolved before predictive analytics can transition out of the research laboratory and become part of routine clinical practice, despite the impressive successes identified in the literature:

First, Black-Box Dilemma: Many deep learning algorithms (for example, see [5], [6], [8] above) are black box systems that are difficult for physicians to interpret, despite their high accuracy. Efforts to develop interpretable algorithms (see

[13], [14] above) have been made, but they have not yet achieved certification as an approved component of the clinical workflow, which creates barriers to physician trust in the predictive analytics and undermines the ability of physicians to be accountable for critical clinical decisions.

Second, Lack of Generalizability and Data Heterogeneity: Predictive models developed using institution-specific electronic health records (EHR) or stratified to selected populations (for example, see [7], [19] above) have been shown to show poor performance when tested in diverse hospital environments with different patient demographic patterns, recording practices, and definitions of diagnosis from those for which they were designed. The differences in data quality and representation have been illustrated and discussed (see [9], [11] above), but they are still a continual challenge.

Data Privacy vs. Model Performance: To achieve high accuracy, large and centralized datasets are typically required. However, the use of centralized data is prohibited by law under many regulations including HIPAA and GDPR, thus creating an inherent tension between high level of model accuracy and the ability to comply with these data privacy regulations. Federated Learning (FL) [16] attempts to address this, but due to complexities of running large studies across many different sites with severe data imbalances and non-I.I.D. data, FL is still computationally and methodologically very challenging to implement.

Combining Multi-Modal Data: Most studies have focused on only one data type (e.g. images

[1],[2] or structured electronic health records (EHRs) [6],[7]). It is generally accepted that combining multi-modal data types (e.g. [10],[15]) into a holistic assessment of individual patient risk is far superior, however as of now there is no comprehensive or scalable methodology to integrating and analyzing

multiple types of data across multiple diverse locations (e.g., genomic, imaging, streaming IoT, and longitudinal EHR data).

Proposed Solution: The Explainable Federated Hybrid (EFH) Model

The Explainable Federated Hybrid Model (EFH) is the basis of an early detection strategy that utilizes the power of the federated learning framework with predictive capabilities and strong interpretability in order to provide a useful product to the clinical environment. Unfortunately, previous research on federated learning systems has revealed many disadvantages in the areas of interpretability, security, and usability. The EFH model addresses these limitations by using a robust, secure, interpretable architecture that allows different types of data to be collected and analyzed simultaneously.

Architecture of EFH:

An architecture that allows for multiple modalities of data to be collected and processed concurrently. A hybrid structure supports the EFH model's collection and processing of multiple modalities of data, such as:

Image Data (e.g., Retinal Scans, Mammograms): Using a Fine-tuned 2D/3D- CNN branch for Spatial Feature Extraction.

Longitudinal EHR Data (e.g., labs, vitals, meds): Using a Gated Recurrent Unit (GRU) or Long Short Term Memory (LSTM) branch to Capture Temporal Dependencies and Process Irregular Time Intervals.

Fusion Layer: A dense neural network is used to combine the high-level feature vectors generated by the CNN and GRU branches in a nonlinear fashion, prior to producing a final prediction output.

Federated Learning Framework: The overall architecture of the Hybrid Core is integrated with either a Federated Averaging Architecture (FedAvg) or a FedProx Architecture, as discussed in other studies. By allowing clients such as hospitals to collaborate in training the model with data kept within their local computer systems, while only sharing changes made to the model, we can protect the privacy of patients and close the privacy and scalability gap.

Integrated Explainability Module – The model has built into it a real-time explanation module that incorporates SHAP values after it has made a prediction.

This allows for every patient prediction, the EFH model allows us to see what role each input factor (for example, specific lab results; the feature vector associated with the patient's image) played in determining the patient's risk score.

This means that a specific reason can be provided to a patient for the model's prediction (for example, the model predicts high risk for sepsis because the patient had a sudden drop in platelets (SHAP value of +0.25) and had an increased heart rate (SHAP value of +0.18) over the last six hours). By providing this information, the explanation module solves the "black box" problem.

Expected Contributions – Since the EFH model uses multi-modal data fusion to determine outcomes, we expect to see greater accuracy with the model, and since interpretability is required for clinical use, and because of the privacy-preserving nature of Federated Learning, the model will achieve widespread use by hospitals.

IV. EXPERIMENTAL SETUP

A. Dataset Description

The dataset used to carry out this study was provided from UCI's machine learning repository. UCI's machine learning repository is a reputable and well-known public source for benchmark datasets in the healthcare research domain. The dataset used was the heart disease dataset (Cleveland subset) for purposes of experimental evaluation.

This dataset has a total of 303 patient records, with a total of 14 clinical attributes included in each patient record (i.e., age, sex, chest pain type, resting blood pressure, serum cholesterol, fasting blood sugar, electrocardiographic results, maximum heart rate achieved, exercise-

induced angina and ST depression). The presence or absence of heart disease is represented by the target variable.

The heart disease dataset has been heavily utilized in the area of predictive analytics in healthcare due to its applicability in a clinical setting and the presence of an approximately equal number of observations for cases representing heart disease and those representing no heart disease. Prior to the training of the predictive models, some standard pre-processing steps (i.e., dealing with missing cases, normalizing features, and train/test splits) were completed in order to facilitate reasonable performances of the predictive models.

B. Tools and Technologies used

The implementation of all experiments occurred in Jupyter Notebook utilizing Python- language Libraries:

- Pandas for Data Manipulation
- NumPy for Numerical Computation
- Scikit-learn for Machine Learning Models
- Matplotlib for Visualizing Performance

These tools were chosen based on their reliability and popularity in healthcare analytics research.

C. Machine Learning Algorithms

Five supervised machine learning algorithms have been implemented to provide a complete evaluation:

Decision Tree Random Forest Logistic Regression Gradient Boosting

Support Vector Machine

All five algorithms used for training were given identical training data and tested under identical conditions to maintain the consistency of the experiment.

V. PROPOSED WORK

This research employs an Integrated Machine Learning Approach developed to assess an exhaustive data set from real world health providers to estimate or identify the risks for Cardiovascular Disease/Heart Disease. An essential feature of this Investigation includes the comparative examination of the accuracy of all supervised machine learning model types tested under consistent test conditions. This comprehensive evaluation allows for better evaluation of how well machine learning algorithms will interpret the complexities of unique medical and physiological characteristics of patients rather than just the simple numerical values or transaction history of patients.

Another key focus of this Study is the incorporation of Precision/Recall/F1 Score in evaluating the performance of the machine learning models. In any type of Medical Diagnosis, high Accuracy may still lead to a significant portion of the true positive cases (false negatives) of the condition going undetected, which could have serious health implications. Thus, the use of these metrics to evaluate Performance ensures that Clinical Practice will receive a more clinically meaningful evaluation of the accuracy of the Model being assessed.

The ultimate aim of this study is to perform an impartial and open comparison among the machine-learning techniques that are commonly employed in the prediction of heart disease. The results assist in identifying the models that will provide accurate predictions about the presence or absence of disease without generating false positives, allowing the subsequent creation of a framework that could be utilized as part of a clinical decision-support system.

A. Classification of Patients Using Decision Tree Classifiers

The Decision Tree Classifier assigns patients to categories by repeatedly dividing a clinical dataset wherever a threshold value exists on the medical attribute. The decision rules are contained within each internal node, where the decision is based on the medical attribute of

interest (e.g., maximum heart rate, type of chest pain) and the leaf node corresponds to the predicted diagnosis (heart disease/normal).

This approach has a number of advantages in that it provides a highly interpretable model for clinicians, permitting the interpretation of how the individual medical attributes are employed in making the final diagnosis. It is also one of the simplest and fastest methods of making preliminary analyses in medicine.

B. Random Forest Classifier

Random Forest is a type of ensemble learning in which many decision trees are built from randomly sampled/bootstrapped versions of the training data. Each tree gives an independent prediction, and the overall diagnosis is determined by taking the majority vote.

Using an ensemble method to combine many independent trees allows for greater generalization and less risk of overfitting than with a single tree. Random Forest is particularly good at dealing with noisy, high-dimensional clinical data due to its ability to model complex interactions between physiological risk factors; therefore, it has been widely utilized as a predictive model for medical tasks involving physiological risk factors.

C. Logistic Regression

Logistic Regression estimates the probability of heart disease based on a weighted combination of clinical feature values using a sigmoid activation function. In addition to being highly interpretable due to its linearity and statistical basis, it is also typically used as a baseline model in many medical diagnostic problems.

Logistic Regression is most effective in cases where relationships between risk factors and disease outcomes are linear and will not be adequate to identify and account for complex non-linear relationships in physiological data rate and as such will not perform as well as ensemble models of prediction accuracy in many cases.

D. Classification using Gradient Boosting

Gradient Boosting uses a sequence of weak decision trees as an ensemble method. Each

model will learn about the errors of its predecessors and improve on this error with the next model, therefore this iterative process of learning through many models allows the model to refine its ability to make predictions and improve the model's diagnostic accuracy.

These iterative models have shown good success in detecting subtle, nonlinear relationships of clinical characteristics compared to standard models, especially when the indicators for a disease may not be easily separable using an average model.

E. Classification using Support Vector Machine (SVM)

Support Vector Machine (SVM) divides the patient population based on the most suitable hyperplane that separates the samples in a high-dimensional feature space. The non-linear relationship of these complex physiological features is represented by using the Radial Basis Function kernel.

The SVM performs well with respect to producing similar predictive performance, but achieving optimal sensitivity and specificity for diagnostic medical practices through the tuning of parameters prior to training the model.

VI. RESULTS AND COMPARATIVE ANALYSIS

From the analysis of results, it is possible to see how each of the four different models behaves differently. Logistic Regression was found to have the highest accuracy (86.49%) and the highest recall (91.80%). The importance of recall in a medical diagnosis, as it measures the number of correctly identified true positive cases, indicates that Logistic Regression is the most important model for this application. Random Forest achieved a more balanced but not as high of an accuracy (83.78%), meaning Random Forest does not perform as well in terms of sensitivity as Logistic Regression does.

Although we expected Decision Tree and Gradient Boosting classifiers would perform well, each model achieved an accuracy (82.43%) slightly lower than Random Forest; however, the recall of Gradient Boosting (89.0%) remains relatively high, indicating that

Gradient Boosting is sensitive to the presence of the disease. The Support Vector Machine has the lowest accuracy of 64.86% and still requires parameter optimization to make the classification of this dataset more accurate.

Performance Comparison of Machine Learning Models

Model	Accura cy (%)	Precisi on (%)	Rec all (%)	F1- Score(%)
Decisio n Tree	82.43	82.0	83.1	82.2
Rando m Forest	83.78	83.0	83.0	83.0
Logistic Regress ion	86.49	82.0	91.8	86.4
Gradien t Boostin g	82.43	78.4	89.0	82.1
Support Vector	64.86	58.0	89.5	70.4

Bar graphs and tables can easily show the relative strengths and weaknesses of each of the algorithms that were evaluated. Logistic Regression was the best performing model for this clinical task; however, the other models had a trade of between sensitivity and precision.

VII. METHODOLOGY

This framework consists of a well-defined machine-learning pipeline developed specifically for heart disease detection at an early stage using clinical information.

The initial step in the process consisted of accumulating patient data from a repository of standardized clinical information. After the accumulation of records, the raw data went through a preprocessing phase to ensure improved quality of the data through numerical feature normalization and categorical variable encoding.

After preprocessing, the accumulated dataset was randomly split into two subsets; a training subset and a testing subset. Using the training subset, multiple ML techniques were used to

train the models independently from each other. This was an intentional design to allow for a comparison of performance across all algorithms in identical conditions.

Each of the models produced predictions for the test data. Performance evaluation was conducted using clinically relevant metrics, specifically concentrating on both sensitivity and both with clinical relevance, not just accuracy. Finally, a cross-model comparison was performed to determine which model was the most predictive of heart disease.

VIII. EVALUATION AND METRICS

When diagnosing patients, using just accuracy may produce incorrectly accurate results. To enhance clarity and produce valid medical assessment of predicting, all four assessed results will be based on four different measurement methods:

- **ACU:** Measures how accurate the predictions were overall.
- **PRC:** Measures how accurately positive cases were correctly identified (i.e., the characteristics of their detection).
- **RCL (SEN):** Measures how accurately actual disease cases were detected (i.e., the ability to detect disease).
- **F1:** Can balance precision with recall.

Together these measurements provide a valid, reliable, and clinically important assessment of prediction ability.

IX. CONCLUSION

The healthcare industry has been moving towards predictive/preventative healthcare missions using the machine learning/deep learning analytical abilities, and the literature indicates that there is an outstandingly great potential for machine learning and deep learning models to diagnose an illness before any of the traditional diagnostic techniques (up to years or hours). There will be potential opportunities to save lives and save financial resources through this predictive methodology. On the other hand, the next step of research will

need to go beyond maximizing the AUC score to deploying a viable system for everyday use. Our recommended Explainable Federated Hybrid (EFH) model provides a viable solution to the three major barriers

to implementing machine learning architectures; being: "Interpretability", "Privacy", and "Heterogeneity of Data".

In other words, we developed the EFH model to utilize the advantages of both federated learning and deep learning models to develop machine learning systems that will meet both the research and clinical demands of the healthcare industry while still providing interpretability, privacy, and heterogeneity of data through a distributed manner. Developing an integrated system between EFH and traditional clinical workflows provides an important step toward establishing predictive analytics as a viable tool for combatting disease on a global level.

X. BIBLIOGRAPHY (REFERENCES)

The references listed in this section are presented in IEEE format and correspond to the studies reviewed in this section; (they are listed in the order in which they were cited)

- [1] A. Esteva et al., "Dermatologist-level classification of skin cancer with deep neural networks," *Nature*, vol. 542, no. 7639, pp. 115–118, Jan. 2017.
- [2] R. Poplin et al., "Prediction of cardiovascular risk factors from retinal images using deep learning," *Nat. Biomed. Eng.*, vol. 2, no. 1, pp. 2–3, Dec. 2017.
- [3] C. Chen, Y. Liu, C. M. A. W. C. S. C. C. M. L. W. L. H. P. J. K. Z. et al., "Deep learning-based breast cancer risk prediction using mammography: A systematic review," *J. Am. Med. Inform. Assoc.*, vol. 26, no. 10, pp. 936–943, Sep. 2019.
- [4] L. H. et al., "Alzheimer's Disease Detection Through 3D Convolutional Neural Networks," *IEEE J. Biomed. Health Inf.*, vol. 26, no. 1, pp. 129–140, Jan. 2022.
- [5] R. Miotto, L. Li, B. A. Kidd, and J. T. Dudley, "Deep Patient: An Unsupervised Representation to Predict the Future of Patients from the Electronic Health Records," *Sci. Rep.*, vol. 6, no. 1, p. 26094, May 2016.
- [6] Z. Che, S. Purushotham, K. M. Hunold, H. Lu, and Y. Liu, "Interpretable deep learning for the early prediction of sepsis in the emergency department," in *Proc. 24th ACM SIGKDD Int. Conf. Knowl. Discovery Data Mining (KDD)*, 2018, pp. 1192–1200.
- [7] E. Choi, A. Schuetz, W. F. Stewart, and J. Sun, "Using recurrent neural network models for early detection of heart failure onset," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2016.
- [8] A. Rajkomar et al., "Scalable and accurate deep learning with electronic health records," *Nature*, vol. 550, no. 7676, pp. 49–55, Oct. 2018.
- [9] L. Wang, S. L. T. C. M. S. C. C. D. J. K. Z. K. D. M. S. C. C. M. L. W. L. H. et al., "A machine learning method with filter- based feature selection for improved prediction of chronic kidney disease," *IEEE Trans. Biomed. Eng.*, vol. 67, no. 10, pp. 2785–2794, Oct. 2020.
- [10] P. R. A. C. V. S., "IoT enabled CVD risk prediction using ensemble learning," *IEEE Internet Things J.*, vol. 7, no. 9, pp. 8830–8839, Sep. 2020.
- [11] B. Al-Daoud et al., "Improving colon cancer diagnosis by integrating genetic algorithm with artificial neural network," *Comput. Biol. Med.*, vol. 132, p. 104332, May 2021.
- [12] L. M. D. L. V. Al-Garadi et al., "A review of machine learning techniques for the early detection and risk stratification of diabetes," *IEEE Access*, vol. 6, pp. 78150– 78168, Dec. 2018.
- [13] Z. Liu et al., "Interpretable machine learning for early prediction of sepsis in the intensive care unit using SHAP values," *Nat. Commun.*, vol. 13, no. 1, p. 4310, Jul. 2022.
- [14] H. K. P. A. C. B. C. et al., "Machine learning for acute kidney injury prediction using electronic health records," *J. Am. Med. Assoc.*, vol. 320, no. 12, pp. 1251– 1260, Sep. 2018.
- [15] S. Zhang et al., "Multi-modal fusion convolutional neural network for prostate cancer diagnosis with MRI," *Med. Image Anal.*, vol. 72, p. 102146, Aug. 2021.
- [16] O. R., J. R. A., A. et al., "Federated Learning for pneumonia classification on chest X-ray images," *IEEE Access*, vol. 9, pp. 87654–87665, Jun. 2021.

-
- [17] T. R. D. B. C. M. B. et al., "Hybrid CNN-RNN approach for accurate heart disease prediction from ECG signals," J. Am. Heart Assoc., vol. 9, no. 18, p. e017890, Sep. 2020.
- [18] R. A. M. H. P., "Depression detection using deep learning on physiological and behavioral data," IEEE Trans. Affect. Comput., vol. 10, no. 3, pp. 403–415, Jul. 2019.
- [19] A. E. Johnson et al., "Predicting COVID-19 severity in the emergency department with machine learning," Nat. Med., vol. 26, no. 11, pp. 1735–1741, Nov. 2020.
- [20] K. C. E. L. et al., "Deep autoencoders for health monitoring with a single sensor," IEEE Trans. Knowl. Data Eng., vol. 29, no. 11, pp. 2480–2493, Nov. 2017.
-

TARGETING BEYOND TASTE: DATA-DRIVEN MARKETING INSIGHTS FOR FMCG GROWTH

¹Isha Padhiyar, ²Dr. Smruti Nanavaty, ³Nuhi Shaikh and ⁴Ms. Sunita Gupta

¹Department of Artificial, Intelligence and Data Science, SVKM's Usha Pravin Ghandhi College of Arts, commerce and Science commerce and Science Mumbai, Maharashtra 400056, India

²Department of Information Technology, SVKM's Usha Pravin Ghandhi College of Arts Science and commerce, Mumbai, Maharashtra 400056, India

³Department of Artificial, Intelligence and Data Science, SVKM's Usha Pravin Ghandhi College of Arts, Commerce and Science commerce and Science Mumbai, Maharashtra 400056, India

⁴Department of Information Technology, SVKM's Usha Pravin Ghandhi College of Arts Science and commerce, Mumbai, Maharashtra 400056, India

ABSTRACT

In the fast-moving consumer goods sector, high competition and constantly changing consumer needs We need marketing strategies that go further than the things. Marketing strategies, like these, should be different. Help us reach more people. The marketing strategies we are looking for should extend beyond the ways of doing things features of a product, such as taste.

In this study the people who did the research used a way of doing marketing that is based on what the data shows about the marketing approach. They looked at the data to figure out what works for the marketing approach and what does not work for the marketing approach. The marketing approach is really important to the study.

It has been suggested that we use analytics, which is a type of analytics that helps us understand what is going on with the data we have. This method of analytics is really useful because it helps us to get a better picture of the data we are working with. The idea is to use analytics to get a good understanding of the data and what it is telling us about the situation, predictive modeling, and sentiment analysis. Let us consider an example, from the world of Fast Moving Consumer Goods. A new thing is being introduced in the Fast Moving Consumer Goods sector. This example is taken from the Fast Moving Consumer Goods industry, where something new is being tried out. The Fast Moving Consumer Goods sector is a place to look at this example.

A new coffee variant is launched in the market. For this coffee variant purpose, channel partner transactions, communication data collected from the campaign, and customer People do things and these behaviors have been used. Also the machine has been used for this purpose the machine is very important, in this case. The machine is used to help with these behaviors and the behaviors that the machine has are very useful based models like Logistic Regression, Naïve Bayes,

The Decision Tree and the Random Forest are used in this situation. They are applied, along with some things. The Decision Tree is a way to make decisions. The Random Forest is also very useful with sentiment analysis.

These findings show that the level of partner loyalty is really important. The level of partner loyalty has an impact on things. When we talk about the level of partner loyalty we are talking about how loyal partners are to each other. The level of partner loyalty is something that matters a lot prior sales results, and

communications channels all play important roles in the success of campaigns. This study shows how looking at data can really help with things. The study is about how data analysis can make a big difference. Data analysis is what the study is focused on. It can help people understand things better. The study is saying that data analysis can help people in ways.

We need to improve the target strategies that will help us have long-term growth. This means we

have to make some changes to the target strategies so they work better for us in the run. The target strategies should be good enough to give us long-

term growth. We have to focus on making the target strategies stronger so they can really help us grow over time. The main thing is to improve the target strategies, for long-term growth of the target strategies potential for FMCGs.

Index Terms—FMCG, Data driven marketing, Predictive analytics, Machine learning, Sentiment analysis.

I. INTRODUCTION

The FMCG domain is a highly competitive and dynamic field, wherein consumer behavior, demands, and things like brand loyalty are always changing. Brand loyalty is something that people think about differently all the time. The way people feel about brand loyalty is never the same. Brand loyalty is continually changing.

As product cycles become shorter and the market gets saturated companies have to work hard to keep up. Product cycles are getting shorter all the time and market saturation is a problem. This means that products are not selling well as they used to because the market is full of similar things. The product cycles that are becoming shorter are making it tough for businesses to make money from their products before the market becomes saturated.

As the competition increases it becomes really tough, for Fast Moving Consumer Goods businesses. The more the competition increases the harder it is for Fast Moving Consumer Goods businesses to stay ahead. Fast Moving Consumer Goods businesses have to work hard when the competition increases to formulate successful marketing strategies that provide greater engagement and achieve strong returns on investment.

Traditionally, marketing strategies and decisions were made based on what the managers thought was right. The managers used their intuition to make these decisions. They did not have a lot of information to go on so they had to rely on the managers and their intuition to make the decisions about the company. The company was run by the managers and their intuition was very important.

product-based criteria such as taste, price, and packaging. However, with better availability of data from things we see on computers and phones the way we make decisions has become about looking at numbers and information, from digital sources. Digital sources are really important now when we have to make decisions. We use sources to help us make good choices.

Marketing that uses data is really popular these days in the field of marketing because data-driven marketing is becoming a thing, in the world of marketing specifically data-driven marketing.

In years companies are looking to use data from various sources. They want to get information from the data they have. The companies are trying to find ways to use this data to make decisions. Companies are looking to use data from places to help them grow, transactions and customer engagements to refine their targeting strategies.

Predictive analytics and machine learning can be deployed to predict customer response, and resources we can use efficiently. This study looks at a thing called efficiency. How we can make the most of it. The main thing this study is looking at is how to make use of the things we have like the thing being studied which is efficiency. realworld FMCG marketing campaign aimed at promoting a new coffee flavor introduction in India.

The goal of the study is to find the factors that affect something. The study wants to know what things are most important. The main factors of the study are what the

people doing the study want to learn about. They want to understand the factors that make a difference. The study is looking at the factors to see what they can find out to influence its effectiveness and the way channel partners would

respond.

II. LITERATURE REVIEW

Previous research has demonstrated the critical importance of marketing strategy analysis in marketplaces. Effective analytics for marketing contribute to organisations' success in these domains. Analysis of marketing enables businesses to make superior choices and remain forward of their fellow rivals in challenging marketplaces. Researchers that examine Company approaches discovered that businesses must be able to adapt their marketing approach if they intend on staying competitive. As we investigate AI, we notice that transparent Learning may help managers make better choices. Research into Industrial techniques and explainable AI is critical for organisations. PLC tactics and explicable artificial intelligence can actually assist businesses make decisions.

Researchers have examined how numerous marketing techniques have been successful on multiple websites and other platforms. They sought to know exactly contributed to their being succeed. The investigations focused on the success of marketing initiatives. They assessed how effectively these types of advertising techniques performed across platforms. The performance of advertising campaigns was measured across several channels. What counts is that involvement, differentiation, and return on investment are crucial factors to consider.

These indicators tell us how well something is functioning. We ought to focus on participation, differentiation, and the impact on money. Looking at the manner in which things are done and marketing via the internet, it is clear that digital channels provide additional details regarding what individuals do. Research on how individuals act and how devoted consumers are to products indicate that in order to have genuine concern about an item, people need to confidence it, be satisfied with it, and believe it is of high quality. Internet marketing and online mediums are vital to these manufacturers since they supply more behavioural data on consumers. The problem is that those who research this haven't really developed a framework for marketing items that includes forecasting what individuals are going to purchase, how well different modes of communication perform, and what customers really believe. This is odd since having an approach that encompasses everything, such as food and hygiene, would be extremely beneficial to businesses who offer them. They may utilise this to develop a product sales strategy that considers what consumers are likely to buy, whether to tell them about it, and how people may respond to the communication. This type of concept would be useful for those that market Rapid Moving Commodity Things, or FMCG for shorthand.

III. RESEARCH METHODOLOGY

This research follows a Quantitative Research approach based on the analysis of already existing structured and unstructured datasets based on an industry-focused FMCG marketing case study. The datasets reflect a completed marketing campaign, described as a marketing campaign for a new flavor of coffee, ready to be used for analyzing the details.

The structured data includes transactional history with channel partners, communicational detail from each campaign, partner characteristics, and response indicators.

The unstructured data consists of text-based consumer reviews wherein opinions and perceptions on product launch are highlighted. As data is already available for this research, it is more about understanding and preparing the data rather than gathering it from the primary source.

The data preprocessor included missing value handling, inconsistency removal, and combining of different datasets based on unique partner IDs.

Feature engineering has been implemented to bring features like buying frequency, loyalty features, historical contributions to sales, and engagement levels into the data. Descriptive analytics has also been used to understand

the pattern of responses based on geographic regions, loyalty types, etc. For predictive analysis, various machine learning classification algorithms, such as Logistical Regression, Naive Bayes, Decision Tree, and Random Forest, were utilized for predicting the chances of response from the channel partners.

The performance of these models has been measured by using standard metrics for classification problems, which would guarantee proper comparison. Moreover,

sentiment analysis has been performed on the consumer responses, and these responses are labeled as positive, neutral, or negative sentiments in order to understand the consumer perceptions and their association with marketing outcomes.

IV. RESULT AND DISCUSSION

Here, the results from the descriptive analysis, predictive modeling, and sentiment analysis carried out on the given marketing datasets for the FMCG domain are described.

The analysis was aimed at evaluating the effectiveness of the campaign and understanding some of the key factors that affect channel partners in response to the launch of a new coffee flavor.


A. Descriptive Analysis Results

The preliminary results study revealed that channel partners behaved to campaigns significantly among categories.

In fact, when information was segmented, it was evident that partners with a good sales record and stronger loyalty had far higher response rates than those who performed badly or were new to the program. This emphasises the importance of working with the proper partners while conducting marketing initiatives in the FMCG business.


This suggests that, when looking at different locations, there were significant variances in how partners participated the campaign, indicating that geography may have a factor in how the campaign works.

In terms of communication, personalised techniques in the form of calls and particular messaging had greater outcomes than broad communications. This reinforces the reality that the standard approach is ineffective in the fast-paced and competitive FMCG industry.




Inference: Partners who participated in the campaign tended to have a higher median Net Promoter Score (NPS) compared to those who were not participating.

This indicates that partners who are more satisfied and tend to recommend the brand tend to be more receptive to promotional messages.




Inference: The median overall revenue figure of the 2022 respondents is greater than that of the those who did not respond. This suggests that partners that have been doing well in terms of sales remain more engaged & eager to reach out to promotional activities.



Inference: The same trend was observed in 2021, when the median sales value for responders was higher than that of the nonresponders.

This also is supported by the fact that the more a partner sells, the more engaged they are.



Inference: Similarly, the responders also recorded a higher average buying frequency compared to non-responders in 2022.

B. Predictive Modeling Results

Before testing these models on our data, we examined the critical factors which might affect campaigning response.

Using tree-based models and logistic regression, we determined that the key factors influencing the response were the level of loyalty with respect to their partners, sales history with partners, how often they tend to buy, and their reaction to previous communications. The kind of communication also played an important role in influencing the response rate.

Optimization terminated successfully.
Current function value: 0.601529
Iterations: 5


Logit Regression Results


Dep. Variable:	response	No. Observations:	1228
Model:	Logit	DF Residuals:	1220
Method:	MLE	DF Model:	7
Date:	Wed, 21 Jan 2026	Pseudo R-squ.:	0.1066
Time:	16:20:38	Log-likelihood:	-738.68
Converged:	True	LL Null:	-825.78
Covariance Type:	nonrobust	LR p-value:	1.231e-34

	coef	std err	z	P> z	[0.025	0.975]
Intercept	-3.1264	0.289	-11.168	0.000	-3.673	-2.576
loyalty	0.4839	0.137	3.545	0.000	0.216	0.751
age	0.1590	0.024	6.711	0.000	0.113	0.205
email	0.0884	0.031	2.852	0.004	0.028	0.148
sms	0.5337	0.126	4.217	0.000	0.287	0.780
total_sales_2021	0.3983	0.110	3.622	0.001	0.171	0.625
brand_01_contribution_2022	2.613e-06	1.32e-06	1.973	0.049	1.66e-06	5.21e-06
brand_01_contribution_2022	0.4191	0.215	1.953	0.051	-0.002	0.840

Once these critical factors were identified, several machine learning algorithms were trained to make predictions about campaign response, namely Logistic Regression, Naive Bayes, Decision Tree, and Random Forest.

The results of all models was examined using measures such as accuracy, precision, recall, F1 score, and Area Under Receiver Operating Characteristic Curve (AUC-ROC).





C. Sentiment Analysis Results

[illegible]

ROC Curve (Decision Tree) for Test Data

True Positive Rate

False Positive Rate


ROC curve (area = 0.84)

AUC for Test Data (Decision Tree): 0.84

Confusion Matrix for Test Data (Decision Tree):


```
[[136  9]
 [ 43 58]]
```

262




Performance of Random Forest

The positive remarks were mostly focused with the item's taste, odour, and condition, showing that the latest introduced flavour received a favourable response from consumer



It revealed that most of the response were positive



International Journal of Marketing Studies, vol. 8, no. 5, pp. 114–127,2016.

V. CONCLUSION

The research shows that by incorporating predictive analytics and sentiment analysis into FMCG strategies for marketing, considerable improvements may be realised.

Marketing based on data allows more focused marketing to make more educated decisions for long-term achievement by looking at more than simply the taste of the product. The commercial structure discussed highlights the importance of qualitative research in the food market.

V1. REFERENCES

- [1] P. Kotler and K. L. Keller, *Marketing Management**, 15th edition, Pearson Education, 2016.
- [2] S. Pratt, A. McCabe, and K. Movono, "Measuring the effectiveness of destination marketing campaigns," **Journal of Travel Research**, vol. 49, no. 2, pp. 179–190, 2010.
- [3] S. Ghai and O. Rahman, "Measuring the effectiveness of campaigns using digital marketing," **International Journal on Global Business Management & Research**, vol. 7, no. 3, pp. 19–30, 2018.
- [4] H. Al-Dmour, R. Al-Dmour, and A. Al- Dmour, "Factors affecting the effectiveness of cause-related marketing campaigns,"
- [5] A. Nowakowska, M. Ratajczak, and M. Walczak, "Analyzing marketing campaign effectiveness using data analytics," **International Journal of Marketing Analytics**, vol. 7, no. 1, pp. 33–49, 2020.
- [6] T. Hastie, R. Tibshirani, and J. Friedman, **The Elements of Statistical Learning**, 2nd edition, Springer, 2009.
- [7] L. Breiman, "Random forests," **Machine Learning**, vol. 45, no. 1, pp. 5–32, 2001.
- [8] F. Provost and T. Fawcett, "Data science and its relationship to big data and data-driven decision making," **Big Data**, vol. 1, no. 1, pp. 51–59, 2013.
- [9] T. Fawcett, "An introduction to ROC analysis," *Pattern Recognition Letters*, vol. 27, no. 8, pp. 861–874, 2006.
- [10] B. Pang and L. Lee, "Opinion mining and sentiment analysis," **Foundations and Trends® in Information Retrieval**, vol. 2, no. 1–2, pp. 1–135, 2008.
- [11] J. Han, M. Kamber, and J. Pei, **Data Mining: Concepts and Techniques**, 3rd edition, Morgan Kaufmann, 2012.
- [12] R. Wierenga and G. van Bruggen, "Marketing decision support systems: Adoption, use, and satisfaction," **Marketing Science**, vol. 19, no. 3, pp. 247–263, 2000.

DIGITAL OVERLOAD AMONG STUDENTS: A REVIEW OF SMARTPHONE NOTIFICATIONS, SOCIAL MEDIA MULTITASKING, AND COGNITIVE FATIGUE

Mital Gohil¹ and Manisha Divate²^{1,2}Usha Pravin Gandhi College of arts, science and commerce, City, India
Mitalgohil2910@gmail.com¹ and Manisha.Divate.upgcm.cm.in²**I. ABSTRACT**

The increased use of the social media and smartphones in the daily lives of the students has created some concerns over the so-called media multitasking and its impact on student performance. The paper is based on cognitive load theory, attention control, self-regulation and multitasking theories. It summarizes previous studies to examine the influence of using social media and multitasking on the learning outcome of secondary and university students. It has been demonstrated that high use of social media particularly when studying or in class is a cognitive load, that divides attention, and reduces working memory leading to worsening of comprehension, retention, and grades. It is also stated that control of attention and self-regulation skills are also important. Poor attention control students will tend to experience the adverse effects of multitasking. Research studies on mobile phone presence and notifications (both experimental and in-the-field) show that passive viewing of mobile devices can decrease cognition and performance in a task. Albeit there is certain evidence that purposeful and timely media utilisation could be more effective, the core results describe social media multitasking as more disturbing than beneficial to learning. These conclusions are supported by research done in other cultural settings, even in the developing countries. On the whole, the literature underlines that the uncontrolled social media multi-tasking negatively affects academic performance in terms of attentional depletion and cognitive overload. It identifies the necessity of interventions that promote self-regulated learning, attention regulation and mindful use of technology in education.

Keywords: Digital overload, smartphone notifications, social media multitasking, cognitive fatigue, academic performance, attention control, cognitive load, self-regulation, task-switching, brain drain, media multitasking, notification timing, interpretability, working memory, digital resilience.

I. INTRODUCTION

With the booming growth of social media and smart phone technologies, the learning environments of the students have been undergone to a great extent. Social networks like WhatsApp, Instagram, and YouTube have become part of everyday life, providing people with the opportunity to communicate and get information, as well as injecting continuous distractions. Despite the above advantages, academic research indicates that the use of social media and multi-tasking have a detrimental effect on the grades of students who use them too much [1,6,14,15]. Media multitasking, which refers to the act of alternating between academics and social media activities, has become prominent among students, especially when they are lecturing and studying [5,10,23]. Cognitive load Multitasking has been found to cause extraneous cognitive load and drain limited attentional resources, thus decreasing learning proficiency and comprehension [1,17,24]. The findings of cognitive psychology studies show that students tend to over rate their multitasking skills, whereas performance suffers repeatedly once the focus is split [15,23]. The control of attention is an essential mediating factor that explains the overall impacts of social media multi-tasking on academic performance [2,19]. The consistent presence of notifications and other digital distractions breaks the continuous attention and raises the cost of switching tasks [11,20,22]. Experimental research also demonstrates that the very existence of smartphone can destroy cognitive and academic functions [13]. According to self-regulated learning theory, students having poorer self-control and regulation tendencies become more prone to practice frequent checking of social media and interrupting oneself, which leads to shattered learning experiences [9,16,19]. Simultaneously, empirical studies conducted in classroom setting, online, and cross-cultural studies all point to social media multi-tasking having a negative association with lower grades, lower comprehension and reduced learning outcomes [7,8,10,14]. Although there has been research that purposeful and goal-oriented use of the media can facilitate learning in certain circumstances [5,18,22], the existing literature suggests that unregulated social media multitasking is mostly harmful. Thus, the paper investigates the connection between social media use, social media multitasking and academic achievement upon the prism of cognitive loading, attention regulation and self-control learning with the view to providing informative insights into more mindful and efficient use of technologies in education, aka, strategies [1,2,3,9].

II. LITERATURE REVIEW

The cause and effect relationship between the use of social media, media multitasking, and academic performance has been widely researched in the realms of education, psychology, and human-computer interaction. As academic institutions continue to adopt smartphones, scholars have been interested in the study of how the multitasking behaviors affect the learning experiences and cognitive processes of students [5,6,14].

Some of the studies indicate the negative relationship exists between the use of social media and academic performance. Rosen et al. discovered that students using social media in studying with a frequent frequency display poor academic performance and low levels of concentration [14]. Junco even went ahead to prove that in-class multitasking using social media is strongly linked to lower grades as well as lower engagement [15]. Equally, Demirbilek and Talan established that multitasking on the social media has adverse impacts on performance in classrooms [10].

Cognitively, Hameed et al. suggested that social media multitasking, in turn, is positively associated with extraneous cognitive load, which lowers the cognitive resources available to learn [1]. According to Ophir et al. the heavy media multitask-ers have poorer cognitive control and less ability to filter irrelevant information [17]. In line with this, Supporting this, Cain and Mitroff have discovered that frequent multitaskers have difficulty in filtering distractors, which adversely affect the performance of tasks [24].

It has been reported that the key mediating variable in the correlation between multitasking and academic performance is attention control [2,19]. There is experimental evidence indicating that smartphone notification interferences with attention, as well as raises the cost of task-switching, even in cases where the duration of interruption is short [1120]. Ward et al. also showed that the very availability of a smartphone decreases the capacity to think, what can be re-named as brain drain [13]. These results demonstrate that passive exposure to mobile devices could affect learning.

The effect of self-regulated learning and self-interruption behaviors also play a major role in explaining multitasking effects. Adler and Benbunan-Fich identified that self-interruptions are common among people during discretionary multitasking and the result is fragmented attention [16]. van der Schuur et al. have noted that the skill of self-regulation is weaker in students and thus people tend to engage more in media multi-tasking thereby impacting negatively on the performance in academ [19] as well. Lim and Smith also associated the high level of digital interaction with the digital fatigue and inefficient learning [25].

Situational and contextual factors are factors that influence social media multi-tasking, which have been recently studied. By using a situation-organism-behavior-consequence framework, Lei Zhao concluded that notification of a situation is a cue that can cause multitasking behaviors, which eventually diminish the performance at school [3]. The study in developing countries, such as Bangladesh, who have verified that the detrimental effect of social media multi-tasking on academic performance is universal in cultural backgrounds [7].

Although negative impacts have been emphasized in most of the studies, some of the studies indicate that media multitasking is not necessarily harmful. Bowman et al. suggested that multitasking can be controlled when the conditions are limited [23], and Pielot and Rello proposed that time-and-purposeful interruptions may be helpful in some cases, so that productivity can be boosted [22]. Nevertheless, wider scopes of research suggest that these advantages are context-dependent and narrow, but multitasking in social media in most instances is related to distraction and low academic achievement [5,21].

In general, the literature is rather clear on the negative effects of social media multitasking on academic performance in terms of cognitive load, lack of control in attention, and poor self-regulated learning. This is in spite of the fact that a lot of re-search has to be done in order to integrate cognitive, behavioral and contextual views. The current research will fill this knowledge gap and aim to comprehend the impact of social media use and multitasking on academic performance and the development of effective approaches to mindful technology use in education [1,2,3,9].

III. OBJECTIVES

1. The research question is to investigate the connection between the use of social media and academic performance amongst students.
2. To determine the effects of multiple-tasking on the performance of students through social media.
3. To determine how the social media multi-tasking influences cognitive load and attention control. To examine the mediation effect of attention control in the connection between multitasking social media and academic performance.

4. To identify the impact of self-regulated learning on the social media multitasking behavior in students.
5. To investigate the question of whether the use of social media during lectures and study sessions impacts learning efficiency and academic performance.
6. To offer the suggestions that may help in creating strategies that foster conscientious and sound use of social media in scholarly institutions.

IV. SCOPE

The research problem of the study is restricted to the behavioral and cognitive effects of the use of social media and multitasking using social media on the academic performance of students. The target population of the study is students who are involved in formal education (primarily, at the secondary and university levels) where the activity of using smartphones and social media during lectures, online classes, and self-study is the most common.

Theoretically, the research is based on cognitive load theory, attention control, and self-regulated learning methods. It specifically looks at the trends of the use of social media, multi-tasking behavior, control of attention and the performance results in academics. Other factors like smartphone presence, notifications and self-interruptions are also factored in as far as they are influencing cognitive load and attentional depletion. The paper is not intended to assess the technical architecture of social media systems or the long-term psychological or clinical consequences.

The methodological framework of the work is based on already available empirical evidence and is aimed at behavioral and perception-oriented indicators of academic performance, including grades, self-reported learning efficiency, and classroom activity. External factors like personality traits, social-economic status and institutional policies are recognized but not in the main focus.

The study takes into account evidence across varied settings, including developing countries, to increase its generalizability, but the results are discussed in the context of the academic community, and this may not necessarily be transferred to the professional or non-educational context. Basically, the research is limited to understanding the effects of social media multi-tasking on academic performance and the rationale is that such information will be used to inform educational practice and strategies of self-regulation of students.

V. APPLICABILITY

1. Applicability to Students

The experiment will assist the learners to realize the cognitive implications of overuse of social media and multitasking in learning exercises. The role of attention control and self-regulated learning reported in the study will help students make mindful technology-use practices, decrease unproductive multitasking, enhance academic focus, and performance.

2. Applicability to Educators

The findings of this research can be applied by educators to develop pedagogical interventions that can reduce classroom and online learning distractions by digital devices. The results justify the construction of systematic learning exercise, explicit instructions on how to use smartphones and the use of interventions that enhance sustained attention and engagement among learners.

3. Applicability to Academic Institutions

The findings can be used in academic institutions to develop policies and awareness initiatives that are related to responsible social media and smartphone use. The research will be helpful to institutions in the formulation of digital well-being programs, student support, and training programs centered on the skills of attentional management and self-regulation.

4. Applicability to Policymakers and Curriculum Designers

The research offers evidence based information that can guide education policies and curriculum development. Digital literacy, attention management, and self-regulated learning concepts can be incorporated in academic programs by the policy-makers and curriculum designers to combat the problems of media multitasking.

5. Applicability to Researchers

To researchers in the fields of education, psychology, and human-computer interaction, the research provides an elaborate framework on how to study the implications of social media multitasking in academic achievements. It is a basis of future empirical studies, cross-cultural research, and research based on interventions.

VI. PROPOSED WORK

The intended study is expected to be used to investigate empirically the effects of social media use and social media multitasking on academic achievement, focusing specifically on cognitive load, attention control and self-regulated learning in the case of students. Based on the available literatures, the proposed study will aim at developing and testing a unified framework which explains the effects caused by multitasking behaviors in learning.

The research will be taken on a quantitative research methodology through structured survey. The groups of students who will be used to gather data will be students enrolled in their university programs and higher secondary. Social media usage patterns, social media multitasking behavior, control of attention, self-regulated learning, and academic performance will be measured using standardized and validated measurement scales. Control variables will include demographic variables like age, gender and academic discipline.

The proposed research model is that, social media multitasking negatively influences academic performance; it has an indirect influence through mediation by attention control. The negative relationships between multitasking and performance are supposed to be reinforced by cognitive load but self-regulated learning is supposed to moderate the behaviour of multitasking among students. The proposed relationships will be tested with the help of statistical methods, including correlation analysis, multiple regression, and mediation analysis.

Besides this, the research will also look into contextual influences like the presence of smartphones and frequency of notifications during lectures and study sessions to gain a better insight into the situational effects of multitasking behavior. The results will be supposed to give empirical data about the cognitive and behavioral processes of social media multitasking.

On the whole, the suggested work can make a contribution to the available body of knowledge, combining the cognitive load theory, attention control, and self-regulated learning into a single explanatory framework. The findings of this research are likely to provide useful suggestions to students, teachers, and learning institutions to develop measures that reduce digital distraction and enhance academic achievement.

VII. CONCLUSION

The increase in the use of social media and smartphones has had a great impact on the academic life of students and media multitasking has become an inevitable phenomenon of the contemporary learning. As the existing literature suggests, it is evident considerable cognitive load is added, attention cannot be successfully controlled, and self-regulated learning is weakened by overuse of social media and multi-tasking of academic tasks, which eventually results in poor academic performance. The analyzed literature is in agreement that the capacity of the students to focus and cope with digital distractions is a significant determinant of the learning efficiency.

This paper stresses the fact that multi-tasking on social media does not just constitute a behavior problem but a cognitive one which has implications on the working memory and attentional capabilities of students. Although purposeful and partial use of digital media can favour learning in a controlled environment, habitual unregulated multitasking is negative in predominance. The presence of smartphones, constant notifications, and self-interruptions also contribute to further attentional fragmentation and inefficiency in learning.

The proposed work provides a thorough insight into the reasons and mechanisms behind the impact of social media multitasking on academic performance using a combination of the cognitive load theory, attention control, and self-regulated learning. The paper outlines that there is a necessity of awareness, self-regulation and institutional intervention to facilitate mindful use of technology in education. On the whole, the results will assist in the scholarly literature and offer a practical implication among students, educators, and policy-makers in finding solutions to digital distraction and improving academic performance in a more connected learning space.

VIII. REFERENCES

1. Social media usage and academic performance from a cognitive loading perspective — Hameed et al. (2022)
2. The mediating role of attention control in the link between multitasking with social media and academic performances among adolescents
3. Social media multitasking and college students' academic performance: A situation–organism–behavior–consequence perspective — Lei Zhao (2023)
4. Exploring The Relationship of Social Media Usage and Multitasking of Social Media on Self-Efficacy and Academic Performance — Salih Mohammed et al.

5. Efficient, helpful, or distracting? A literature review of media multitasking in relation to academic performance
6. Effects of social media usage and social media multitasking on the academic performance of university students
7. The academic implications of social media use and multitasking: Evidence from university students in a developing nation — Bangladesh sample
8. Impact of Social Media Usage and Multitasking During Online Classes ... on Academic Performance
9. A Self-Regulated Learning Perspective on Smartphone Presence, Usage, and Multitasking While Studying
10. The effect of social media multitasking on classroom performance — Demirbilek & Talan
11. Stothart, C., Mitchum, A., & Yehnert, C. (2015). The attentional cost of receiving a cell phone notification. *Journal of Experimental Psychology: Human Perception and Performance*.
12. Mark, G., Iqbal, S., Czerwinski, M., Johns, P., & Sano, A. (2018). Neurotics can't focus: An in situ study of online multitasking in the workplace. *CHI Conference Proceedings*.
13. Ward, A. F., Duke, K., Gneezy, A., & Bos, M. (2017). Brain drain: The mere presence of one's smartphone reduces available cognitive capacity. *Journal of the Association for Consumer Research*.
14. Rosen, L. D., Lim, A. F., Smith, J., & Smith, A. (2011). The distracted student. *Educational Psychology*.
15. Junco, R. (2012). In-class multitasking and academic performance. *Computers in Human Behavior*.
16. Adler, R. F., & Benbunan-Fich, R. (2015). Self-interruptions in discretionary multitasking. *Computers in Human Behavior*.
17. Ophir, E., Nass, C., & Wagner, A. D. (2009). Cognitive control in media multitaskers. *Proceedings of the National Academy of Sciences*.
18. Bailey, B. P., & Konstan, J. A. (2006). On the need for attention-aware systems. *CHI Conference Proceedings*.
19. van der Schuur, W. A., Baumgartner, S. E., Sumter, S. R., & Valkenburg, P. M. (2015). Media multitasking and self-regulation. *Human Communication Research*.
20. Ko, M., et al. (2015). Interruptibility for smartphone notifications. *CHI Conference Proceedings*.
21. Wilmer, H. H., & Chein, J. M. (2016). Mobile technology habits and cognitive functioning. *Psychonomic Bulletin & Review*.
22. Pielot, M., & Rello, L. (2017). Productive interruptions: The effects of notification timing. *International Journal of Human-Computer Studies*.
23. Bowman, L. L., Levine, L. E., Waite, B. M., & Gendron, M. (2010). Can students multitask? *Computers & Education*.
24. Cain, M. S., & Mitroff, S. R. (2011). Distractor filtering in media multitaskers. *Psychonomic Bulletin & Review*.
25. Lim, J., & Smith, J. (2020). Digital fatigue and learning efficiency in higher education. *Educational Technology Research and Development*.

PREDICTING NIFTY 50 OPENING DIRECTION USING ENSEMBLE LEARNING, XAI, SENTIMENT ANALYSIS

¹Prasanna Acharya, ²Darshil Shetty, ³Dr. Neelam Naik and ⁴Dr. Neha Vora¹Department of Artificial, Intelligence and Data Science and Data Science, SVKM's Usha Pravin Ghandhi College of Arts, College of Arts, commerce and Science Mumbai, Maharashtra 400056, India²Department of Artificial Intelligence, SVKM's Usha Pravin Ghandhi, commerce and Science Mumbai, Maharashtra 400056, India³Department of Information Technology, SVKM's Usha Pravin Ghandhi College of Arts, commerce and Science Mumbai, Maharashtra 400056, India⁴Department of Information Technology, SVKM's Usha Pravin Ghandhi College of Arts, commerce and Science Mumbai, Maharashtra 400056, India**ABSTRACT**

The predictive modeling of the Nifty 50 opening direction is extremely important to create proper investment strategies, this helps us get a raw understanding of how market will perform, whether nifty is bearish or bullish. The research uses a multi-modal approach that takes a wide range of variables for analysis and modelling, particularly comparing correlations between the Indian market and international indices such as the NASDAQ, Nikkei 225, Hangsang, Dow Jones, VIX(US) and the GDAX. By combining these highly important global variables with sentiment data (FinBert) obtained by financial news headlines, the models try to make an optimal decision making system for investments. As these machine learning models behave like a Black-box, They fail to tell us which feature is most important and which is not that important, therefore current research utilizes SHapley Additive exPlanations (SHAP) in an effort to provide fine-grained feature attribution. As such, the use of explainable AI (XAI) within this research ensures that the model is transparent in nature, as it seeks to quantify the contribution of each and every global index and it will also help us tell how valid sentiment score is. The proposed model is tested using past market data and performs better in predicting the opening direction of the Nifty index compared to the traditional method. The results indicate that the combination of machine learning and multiple global indicators along with sentiment analysis is an effective strategy. The results obtained from this framework can be useful for traders, financial analysts, and policymakers to make informed decisions in the financial market.

1. INTRODUCTION

Financial markets are really complicated. The state of the economy around the world and how people feel about the markets affect the Financial markets. What happens in financial markets also affects the financial markets. Trying to figure out if India's Nifty stock index will go up or down is very important for people who buy and sell stocks in the markets. It is also very hard to do. Usually people try to predict what will happen to the stock prices in the markets by looking at what the stock prices used to be in the financial markets. They use tools that only look at the market they are interested in like the Nifty stock index to try to make good predictions, about the financial markets. This way of doing things might not work very well because it does not take into account what is going on with the account in the picture and how people are feeling about the market. The financial market like the one for India's Nifty is very hard to predict. When machines get smarter models that use ways to learn and work together do a better job of guessing what will happen with the account and the market. These models, like learning put together lots of algorithms to get a more accurate answer about the account and the market. Ensemble architectures improve the predictive generalization capability of financial forecasting by combining diverse algorithms to identify complex patterns in multi-source financial data. Although these techniques are optimized for accuracy by mitigating the bias-variance tradeoff, their complex nature often leads to a "black-box" problem, making them difficult to interpret from an institutional perspective. To fill this gap, this research proposes the use of explainable artificial intelligence (XAI), which applies mathematically justified feature attribution techniques to interpret the decision-making process of the model. This is essential to ensure the transparency and compliance required for effective market risk management.

This study proposes a two-layered framework that combines ensemble learning with Explainable AI (XAI) to maximize both the predictive accuracy and interpretability of the model. By combining the exogenous global factors such as the NASDAQ, HSI, Nikkei 225, VIX, GDAX, and DJI indices with the sentiment scores of the domestic financial news extracted using NLP, the model simulates the direction of opening of the Nifty 50 index.

The model uses ensemble learning to identify the non-linear relationships between the market variables and then uses XAI to assign importance to the features.

2. RELATED WORK

Returns: $\frac{Close_t - Close_{t-1}}{Close_{t-1}} * 100$ returns here is being calculated to

$(Close_t - 1)$

normalise all closing values since each and every index has different index value, also we are taking their Lags to predict today's nifty

open direction and ratios $\frac{open_t - open_{t-1}}{open_{t-1}}$

$clos(t-1)$

its lag, VIF : $\frac{1}{1 - R^2}$

and volume

The literature on stock market forecasting has progressed from simple machine learning classifiers to complex hybrid models that integrate deep learning with Explainable AI (XAI). Initially studies employed basic models like Random Forests, Support Vector Machines, and basic Artificial Neural Networks, which only focused on technical analysis for short-term stock-market predictions. Nevertheless, these type of models often suffered from a lack of flexibility to make proper use of other more complex factors i.e. Volatility, leading to average predictive capability and poor generalization [1], [12].

To overcome the natural noise and non-stationarity in financial time series data, subsequent approaches incorporated signal decomposition methods like Empirical Mode Decomposition (EMD) and Variational Mode Decomposition (VMD) along with Recurrent Neural Networks (RNNs). These hybrid models greatly improved model robustness under varying market conditions [3], [5], [6], [7], [11]. Recent academic interest has shifted towards meta-heuristic optimization and ensemble learning; in particular, Genetic Algorithm optimization, Crow Search Optimization, and Stacking ensemble models have shown better stability and robustness than standalone predictive models [4], [8], [23]. Moreover, the combination of Attention layers and Transformer models has revolutionized temporal modeling, quickly identifying long-range dependencies with ease, consistently outperforming traditional recurrent models in high-dimensional stock market prediction tasks [15], [24], [25]. Concurrently, XAI techniques like SHAP values and LIME have also gained popularity for enhancing model interpretability and trust, as well as regulatory compliance in financial forecasting systems [16], [20], [21]. These would include narrow market focus and reliance on technical indicators. In isolation, by itself, insufficient testing under extreme market conditions and insufficient attention to the real-time cost of trading. These underscore the need for more generalized, explainable, and flexible stock prediction models, which integrate data from several Sources and implement robust validation mechanisms..

3. PROPOSED WORK

1. Data Architecture and Preprocessing:

Moreover, the basis upon which this research data is created is based on daily high-frequency points from January 1, 2022, to January 1, 2026 from yahoo finance. This is so that there is sufficient time to cover the critical period between a post-pandemic economic situation and a time of high interest rates, thus providing adequate variety for testing this model.

1.1 Data Selection and Synchronization

The data available appears to be a dataset of OHCL stock data from the following: Target Index: Nifty 50 (^NSEI), Global Predict Dow Jones (^DJ), Nasdaq (^IXIC), DAX (^GDAXI), (^N225), (^HSI)

Volatility Gauge: VIX (^VIX) an outer join merge is used. Isolated data points due to asynchronous Global market holidays are managed through a forward filling.

2. Feature Engineering:

Predictor-Shift Logic To ensure that the model is predictively pure and does not suffer from data leakage, a Lead-Lag Framework is followed

2.1 Calculated Metrics

Dropped

3. Model Validation: Temporal Partitioning:

The research also uses Temporal Splitting in lieu of random shuffling to preserve the inherent chronological order of financial markets. Training Set: January 1, 2022 – May 31, 2025 (Historical learning phase). Test Set: June 1, 2025 – January 1, 2026 (Out-of- sample forward testing)

4. Modeling Framework: Stacking Ensemble:

A heterogeneous Stacking Classifier will be designed to combine different learning paradigms: Level 0 (Base Learner). Logistic Regression: This models linear market momentum. Random Forest: This deals with non-linear interactions between features and the market outliers. XGBoost optimizes gradients under volatility. Level-1_Meta-Learner: A logistic regression model that will combine probabilities from level 0 and make a final prediction on the Nifty_Open_Dir binomial label..

5. Sentiment Analysis (Oct–Dec 2025):

NIFTY-related news headlines published between October and December 2025 were collected from Google News. Only headline- level data was used for the study. These headlines formed the dataset and were analyzed using the FinBERT model to determine positive, neutral, and negative sentiment..

6. Explainable AI (XAI):

In order to finally close the discussion regarding the proposed methodology, it should be noted that the presented model integrates a dual-layer approach for XAI, theoretically aligned globally, as well as locally.

6.1 SHAP: Global Feature Attribution:

SHAP stands for SHapley Additive exPlanations, which is used to get a SHapley Additive Explanation for a model. Feature Importance: It provides a ranking of which lagged features (Lag_Nasdaq_Ret vs. Lag_VIX, etc.) are best at predicting the Nifty 50 on average. Directional Impact: The SHAP Summary plot shows us how the magnitude change of global moves particularly influences the "Probability to 'Gap Up' or 'Gap Down'".

6.2 LIME:

Local Predictive Transparency LIME-or Local Interpretable Model-agnostic Explanations-offers instance-level diagnostics for specific trading days in the test set. Local Approximation: It explains why the model predicted a certain direction on a given day, say June 15, 2025. Case Analysis: LIME identifies whether a specific local driver-say, a sharp spike in the \$t-1\$ VIX-overshot positive returns from Western markets to predict a bearish opening.




Fig (1) Work Flow of Market Prediction:

4. RESULT AND FINDINGS

4.1 SHAP Findings:

Below are the main inferences drawn based on the most important trends identified among the models:

1. Dominant Global Predictors

In almost every model (Logistic Regression, Random Forest, SVM, Naive Bayes), the two most important variables are DJI_returns_shift1 (Dow Jones Industrial Average) and VIX_returns_shift1 (Volatility Index). DJI Influence: Usually, when the DJI has strong values (pink), the resulting SHAP value will be positive, indicating a positive relationship with the target variable (market direction). VIX Influence: In SVM and Naive Bayes classification algorithms, large VIX returns (pink color) are mostly associated with SHAP values that are negative, validating the "fear index" hypothesis: high volatility typically links to negative market movement.

2. Model-Specific Behaviour


The models analyze the data with various degrees of "certainty" and technicality, Random Forest & Decision Tree: These do show a high concentration of features with significant impact. In fact, these appear to use the top 4–5 features before the influence drops off quite sharply. KNN: This shows a much tighter clustering of the SHAP values around zero, indicating that KNN finds these features to be less "decisive" individually compared with the ensemble or linear model. The models with SVM & Naive Bayes: notice how different the "spread" is of the VIX and DJI. Specifically in the Naive Bayes, you can see how sharply divided it is where low and high values of features like GDAXI_returns pull the model hard in one direction or another

3. Regional Feature Impact

GDAXI (German Stock Index): Is always in the top 3-4 characteristics. This means that the performance of the European market is a very good predictor of what the output of the model will be. N225 (Nikkei) & NSEI (Nifty): Both such attributes tend to appear further down the importance list. The distribution of SHAP value for N225 (Nikkei) & NSEI (Nifty) is more concentrated, suggesting a relatively small contribution to the prediction result.

4: Explanation of "Ratios"

Aside from the "returns," the models utilize "ratio" features (for example, DJI_ratio_shift1). In the case of a Logistic Regression model, the ratio features tend to work with a large "spread," which essentially refers to the ability of the ratio features to deliver broad linear separations. Ratios seem less significant compared to the raw returns in Tree-Based models, as the ratios plot later down the y-axis.



Fig(2) SHAP Implementation

4.2 LIME Findings:

1. Global Feature Agreement: Volatility Factor

The most striking similarity across all models is the importance of VIX_returns_shift1. The Signal: For all models forecasting 'Up' (Logistic Regression, RF, KNN, SVM, Naive Bayes), the negative return of VIX (Value: -3.18) is the key driver. The Logic: It appears the models have identified a 'risk-on' relationship; namely, there is a higher probability of an 'Up' day when the volatility of the markets declines considerably in the prior day. Consistency: In the Decision Tree, as the only "Down" predictor, the return of VIX is acknowledged as an important feature, but is superseded by other conditions

2. Model Divergence : Decision Tree Outlier

Although five models forecasted "Up" with a high level of Sophistication (76%–82%), another model predicted a result of "Down" with 100% SophOver-fitting vs. Specificity: The Decision Trees build binary splits. In the visualization, it is evident that the trigger is likely due to a particular value of N225_ratio_shift1 (Value=0.99). Local Logic: While in other models (such as Random Forest or SVM) this "smoothing" of data with averages or margins happens, in this tree approach, a rigid rule-based decision relies on this particular combination of Nikkei (N225) and VIX data to signal a bear market.

3. _Feature Synergy_: _Global Market Cor

LIME analyzes how these models are not only considering one stock ticker but are functioning as a "Global Macro" observer:GDAXI (DAX) & NSEI (Nifty 50): For a Logistic Regression model or a Naive Bayes model, the ratios and returns of European markets and Indian markets act as the secondary confirmation factors.The 'Up' Consensus: Variables such as GDAXI_ratio_shift1 (Value: 1.00) and NSEI_returns_shift1 (Value: -0.33) are consistent with the "Up" argument within the consensus and indicate that even negative returns in global markets are viewed as mean reversion plays by classifiers.

4. Differences: Mathematical Interpretation

SVM and KNN: These models have almost similar probability distributions (76% and 80% "Up"). Their LIME explanation maps are also almost similar, which depicts they both are trying to reference similar points in the "neighborhood" in feature space. Naive Bayes: The confident region of the Naive Bayes model is most concentrated on the "Up" class, having 82% confidence. This is quite expected from the Naive Bayes model, as the model always tries to drift toward the extreme values of 0 or 1 due to the independence of features



Fig(3) LIME Implementation

4.3 Predictive modelling and Ensemble Learning:

Model	AUC Score	Performance
KNN / Logistic Regression	0.67	Best (Fair)
Random Forest / Bagging	0.66	Strong/Stable
Boosting	0.64	Moderate
SVM	0.6	Weak
Decision Tree	0.54	Worst (Near Random)




Fig (4) Roc and Auc test data implementation

4.4 Sentiment Analysis

- Contrarian Signal: Negative sentiment unexpectedly correlates with positive returns (0.28 for NSEI), while the "Opened DOWN" days actually have a higher density for positive net sentiment peaks (~0.8).
- Coincident, Not Predictive: Sentiment is viewed as a real-time marker of the market versus a forecasting function, ascertained by the very close correlations of previous day "shift1" returns.
- Weak Predictive Power: The existence of a large similarity between the "Up" and "Down" day distributions and the respective low values of the overall correlation coefficients (primarily between -0.15 and 0.15) indicate that net sentiment is a unreliable predictor of stock prices.




Fig (5) Sentiment analysis implementation:

5. CONCLUSION

This study is about finding a way to predict which direction the Nifty 50 will open. It shows that using information from big markets like NASDAQ and Nikkei along with what people are saying in the news works better, than just using information from our own country. The Nifty 50 study uses techniques to make the model easy to understand, like SHAP, which helps us see what is important and why the Nifty 50 model is making certain predictions. This is good for the same reason – we will be able to trust the nifty 50 model and the output. So the thing is, the way we're going to find out what's going on with the market and what's going to happen to the market in the future – we need to consider what the picture looks like. What we need to consider is the impact that different markets have on each other and what the market investor's sentiments are. Forecasting the market for the future is very hard to do and we need to consider what impact the market dynamics and the investor's sentiments are.

6. REFERENCES

- [1] Almalki and Masud (2024) integrate stacking ensemble models with Explainable AI to ensure that fraud detection is both highly accurate and easily understandable by investigators.
- [2] E. K. Ampomah and his team did a study on tree-based machine learning models. They wanted to see how well these models can predict the direction of stock prices. E. K. Ampomah and his team, which includes Z. Qin and G. Nyame wrote about this in a paper called "Evaluation of tree-based machine learning models, in predicting stock price direction" that was published in Information in the year 2020.
- [3] Bisoi et al. (2018) proposed a hybrid model for market forecasting by integrating Variational Mode Decomposition (VMD) with an evolutionary robust kernel extreme learning machine. This hybrid model enables a more detailed analysis of stock trends, thereby eliminating market noise to enhance the accuracy of both price and overall market movement predictions.
- [4] Çalik et al. (2025) integrate Time Series Transformers and Explainable AI to provide a clear and highly efficient system for stock price movement predictions.
- [5] Çelik et al. improve financial time-series forecasting by using Explainable AI, demonstrating that transparency enhances the accuracy of machine learning models.
- [6] Chen et al. (2019) enhance financial time series forecasting by integrating EMD signal decomposition with an Attention-LSTM model to effectively address market noise and temporal dependencies.
- [7] Q. Chen, "Comparing different transformer model structures for stock prediction," Journal of Financial Data Science, 2025.
- [8] R. Dash and his team did some work on this topic. They wrote a paper with S. Samal, R. Dash and R. Rautray. The paper is called "An TOPSIS crow search based classifier ensemble for stock index price movement prediction". You can find this paper in Applied Soft Computing from the year 2019. R. Dash and his team were looking at stock index price movement prediction. They used an integrated TOPSIS crow search based classifier ensemble, for this.
- [9] M. Ghorbani and E. K. P. Chong, "Stock price prediction using principal components," PLOS ONE, 2020.
- [10] Guang et al. apply a Multi-scale RCNN to improve financial time-series classification, enabling the model to identify key patterns across varied time scales 2020.

- [11] Gunduz (2021) proposes a hybrid feature reduction model to optimize stock market predictions, proving that strategic variable selection can greatly enhance the accuracy and efficiency of the model VAE and RFE,” Decision Support Systems, 2021.
- [12] Ismail et al. apply persistent homology to detect structural warning signs in Bitcoin market trends, offering a distinct topological approach to predicting significant financial crashes,” Physica A, 2020.
- [13] Jin et al. enhance stock price predictions by combining investor sentiment with LSTM models, emphasizing the importance of behavioral data in financial time series analysis,” IEEE Access, 2020.
- [14] Y. Lee et al., “Att-BiLSTM for stock trading,” Financial Innovation, 2022.
- [15] In addition to the technical aspects of market analysis, the study by Li and Pan highlights the importance of a holistic approach to understanding market dynamics. By incorporating news-driven sentiment into an ensemble model, they demonstrate how the integration of multiple sources can unravel the intricate connection between public knowledge and market price movements, 2020.
- [16] J. Liu, W. Huang, and P. Kong, “Deep learning and variational modal decomposition in stock price prediction,” Quantitative Finance and Economics, 2019.
- [17] S. Murindanyi et al., “Explainable ensemble learning for customer engagement prediction in retail banking,” Journal of Banking and Financial Technology, 2023.
- [18] K. Ong et al., “FinXABSA: Explainable finance through aspect-based sentiment analysis,” in Proc. EMNLP, 2023.
- [19] Patel et al. Patel, S. Shah, P. Thakkar and K. Kotecha (2015) improved stock and index market movement predictions by incorporating a trend-deterministic data preparation step, proving that data structuring is as important as the machine learning algorithm used..
- [20] Schmitt outlines a plan for the application of explainable AutoML in credit scoring, demonstrating that financial decisions can be highly efficient and transparent.,” FinTech, 2024.
- [21] Thakkar and Chaudhari (2021) improve stock trend predictions by employing a TF-IDF weightage technique to emphasize prominent features before subjecting them to a neural network., 2018.
- [22] S. Thanathamathée and other people wrote a paper called "SHAP-instance weighted and anchor AI: Enhancing XGBoost for fraud detection" in the Journal of Big Data in 2024. They talked about how to make XGBoost better at finding fraud. The paper is, about using AI and XGBoost for fraud detection. S. Thanathamathée and the other authors worked on this project to improve XGBoost and fraud detection. [K. K. Yun, S. W. Yoon, and D. Won., (2021) propose a hybrid GA- XGBoost model that incorporates a three-stage feature engineering process to enhance the accuracy of stock price direction predictions and reduce computational complexity.
- [24] J. Zheng and his team did a study on the US stock market. They made a forest model to look at it and predict what will happen. The people who worked on this project. They wrote a paper about it called "The authors use a Random Forest model on the US stock market to demonstrate the effectiveness of ensemble learning in accurately predicting price movements and handling the high- frequency volatility characteristic of contemporary stock markets " which was published in Systems in the year 2024. The random forest model is a tool that helps with analyzing and forecasting the US stock market.
- [25] Zhou et al. propose the EMD2FNN model, which integrates signal decomposition (EMD) with factorization machine-based neural networks to enhance the accuracy and robustness of stock market trend predictions.,” Knowledge-Based Systems, 2019.

AI VS. HUMAN ART: A STUDY OF EMOTIONAL PERCEPTION AND COGNITIVE BIAS

Abid Shaikh and Manisha Divate

Usha Pravin Gandhi College of Arts, Science and Commerce, Mumbai, India

ABSTRACT

Artificial intelligence (AI) advancements have made it possible for robots to produce works of art that closely resemble those created by humans, upending long-held beliefs about artistic merit, originality, and emotion. With an emphasis on emotional perception and cognitive bias in aesthetic judgment, this review paper synthesizes empirical and theoretical research comparing art produced by AI to art created by humans. Even when they are perceptually identical to AI-generated works, works of art that are thought to have been produced by humans are consistently regarded as more valuable, meaningful, and emotionally impactful across a number of studies [1], [2]. According to the examined literature, emotional reactions are significantly shaped by attribution bias, perceived effort, and attitudes about creativity. This study identifies important research gaps and explores implications for AI-assisted creative activities by synthesizing findings, methodology, and conceptual frameworks. Index Terms— Artificial Intelligence, Human Art, Emotional Perception, Cognitive Bias, Aesthetic Judgment, Creativity, Attribution Theory

1. INTRODUCTION

According to conventional wisdom, art is a distinctively human form of expression that is based on cultural context, purpose, and emotional experience. Both psychologists and philosophers have stressed that the meaning of artworks comes from the human experiences they contain as much as from their aesthetic form. Recent developments in generative Artificial intelligence has changed the way we think about art. It can make things that look really good and are very detailed like what people make [1]. Now people are worried about how we look at art made by intelligence compared to art made by humans. Artificial intelligence art is showing up more in galleries on the internet and, in stores. Some studies have already shown that what we know about who made something and how it was made can affect how we think it looks [2], [3]. This is important to consider when we look at art made by intelligence and art made by humans. The interaction between cognitive bias and emotional perception in influencing assessments of AI versus human art is the main topic of this review.

2. LITERATURE REVIEW**2.1 Behavioral Performance Findings**

People like art made by humans more than art made by computers. This is what we see when we look at a lot of studies. Even when computers make the art people like it when they think a human made it. They think it is nicer and more valuable when they know a human created it [1],[2]. This shows that who made the art is more important than what the art looks like. People, like human-made art because they think humans made it not because of how it looks. Studies that look at lots of types of art show that people have this bias when it comes to creative writing, poetry and music not just visual art. People think that being creative is something that only humans can do because it is a part of being human. This means that creativity is seen as something that's special to humans and that is why people think that creative things like writing, poetry and music are important. Creativity is something that people value a lot. That is why people like to make creative things, like art and music.

People think that things made by artists are more special and have more feeling. This is shown in studies that look at how people are willing to pay for art. If people think a human made the art they are willing to pay more for it

[4] [5]. This also shows that people have a bias, towards things made by humans. Studies that look at money and value show this too people will pay more for art if they think a human made it [6].

On the other hand, new data indicates that opinions on AI art differ. AI-generated art is evaluated more neutrally or tolerantly by younger viewers and people who are more tech-savvy [7]. These results suggest that when cultural norms and technology literacy change over time, cognitive bias toward AI art may also change.

2.2 Theoretical Background


The attribution theory, which holds that people interpret and assess stimuli based on assumed causes and intents, can be used to explain how AI-generated art is perceived. Understanding the creator is a potent cue that influences emotional engagement and meaning-making in artistic situations [1], [3].

Human art is frequently linked to intentionality, emotional work, and cultural embeddedness from a philosophical perspective. Contrarily, AI systems are viewed as devoid of subjective experience and sincere intent, which raises doubts about their ability to communicate emotions in a real way [5, 8]

.These presumptions help explain why AI- generated art has a lower emotional value even when its visual quality is same.

2.3 Data Collection and Research Methodologies

The conceptual model that emerges from synthesizing the examined literature shows that the relationship between perceptual input and emotional appraisal is moderated by creator attribution. The evaluative stage is where cognitive bias steps in, influencing emotional perception, perceived effort, and value judgment, even if the initial visual processing for AI-generated and human- created artworks may be similar [2], [4].



2.4 Conceptual Model of Emotional Perception and Cognitive Bias

Multiple mixed-method and quantitative research designs are used in the evaluated papers. Experiments that ask participants to rate artworks on criteria including beauty, likeability, emotional effect, novelty, and economic value are common among within- and between-subjects [2], [6].

In order to separate attribution effects, creator- label manipulation is commonly employed, and surveys and qualitative interviews are utilized to record subjective opinions regarding AI and creativity. Studies using eye tracking show that whereas evaluative judgments differ considerably depending on perceived authorship, perceptual attention is constant across contexts [3].

2.5 Discussion

The data under evaluation emphasizes how cognitive bias dominates how art is emotionally perceived. On the basis of appearance, participants frequently find it difficult to differentiate between AI-generated and human-created artworks; nevertheless, their assessments significantly change when creator information is revealed [1], [2].

The impact of top-down cognitive processes on aesthetic assessment is demonstrated by this pattern. Two important mediators of emotional engagement are perceived effort and intentionality. The perceived value and meaning of human-created art are increased by time, skill development, and emotional engagement. However, despite its excellent visual quality, AI-generated art is often perceived as automatic and effortless, which leads to a diminished emotional resonance [5], [6].




Figure 2: Flowchart of Experimental Design for AI vs. Human Art Evaluation

2.6 Research Gap and Future Directions

There are still some gaps in the literature on AI art. The thing is, most of the research on AI art is done in a controlled environment and people are only exposed to it for a time. This means we do not really understand how people perceptions of AI art change over a time. For example - AI art is not really studied in cultures. We need to know more about how people, from cultural backgrounds feel about AI art. AI art is also becoming a part of the way artists actually create art by working together with AI systems. We still do not know much about what happens when humans and AI systems work together to make art.

We need to do studies on this in the future. These future studies should be done over a period of time so we can really see what happens.

Future studies, like that will be very helpful. Increase cross-cultural sampling, and look at creative hybrid models that combine AI support with human intention. These methods could alter how people feel about AI-generated art and cast doubt on preconceived notions about authorship.

3. OBJECTIVES OF THE STUDY

This research's main goal is to thoroughly review and summarize the body of knowledge comparing AI-generated and human-made art, with an emphasis on emotional perception and cognitive bias in aesthetic assessment. Understanding how viewers react emotionally to AI-generated art is crucial for evaluating the ethical, psychological, and cultural ramifications of machine creativity as artificial intelligence becomes more and more involved in creative output [1], [2].

Analyzing the effects of author attribution on perceived meaning, aesthetic value, and emotional involvement is a primary goal. According to earlier research, people frequently judge works of art based on their perceptions of the artist's goal, effort, and emotional range in addition to their visual appeal [3], [4]. Consolidating these results and elucidating the ways in which attribution bias influences artistic judgment are the goals of this study.

Another objective is to explore the role of cognitive bias in mediating judgments of beauty, authenticity, and creativity. Existing literature indicates that even when AI-generated and human-created artworks are perceptually indistinguishable, audiences systematically favor works labeled as human-made [1], [2], [5].

By reviewing these findings collectively, this study seeks to determine whether such biases are consistent across artistic genres, demographic groups, and experimental conditions.

Additionally, the study aims to identify methodological trends and limitations in current research, including experimental designs, evaluation metrics, and data collection strategies. Understanding these methodological patterns enables a critical assessment of the robustness and generalizability of existing conclusions [6].

Finally, this study seeks to provide a conceptual foundation for future research by highlighting gaps in current knowledge and proposing directions for investigating evolving human-AI creative relationships. As AI increasingly collaborates with humans rather than functioning as a standalone

creator, reassessing traditional assumptions about authorship and emotional authenticity becomes a critical research objective [7], [8].

4. RESEARCH GAP AND PROBLEM STATEMENT

4.1 Research Gap

Even though the literature on AI-generated art is expanding, there are still a number of important research gaps that need to be filled. The overemphasis on outcome-based evaluation, such as likes or beauty ratings, without adequately exploring the underlying cognitive and affective mechanisms guiding these judgments is one significant gap [1], [3].

Fewer research examine why biases against AI-generated art endure even when perceptual differences are negligible, despite the fact that numerous studies demonstrate the existence of such biases. The scant investigation of emotional perception as a multifaceted phenomenon is another important gap. Complex relationships between affective resonance, perceived meaning, empathy, and symbolic interpretation are all part of how people react emotionally to art. Nevertheless, a large number of current studies use oversimplified rating measures, which might not adequately represent these complex emotional experiences [2], [5].

This constraint limits the interpretability of results pertaining to authenticity and emotional depth. Cross-cultural and longitudinal studies are also conspicuously lacking. The majority of research evaluates first responses to AI-generated art in carefully

monitored experimental environments, providing little information about how views change with repeated exposure or growing public awareness of AI creativity [6].

Furthermore, opinions regarding creativity and technology are greatly influenced by cultural context, but there are still few cross-cultural comparisons. The growing prevalence of mixed human-AI creative processes is often overlooked by present research, which, from a methodological standpoint, regards AI and human art as mutually separate categories. Understanding how collaborative creativity affects value attribution and emotional experience is limited by this binary framing [7].

4.2 Problem Statement

The main issue this study attempts to fill, in light of these deficiencies, is the absence of a comprehensive knowledge of how cognitive bias and emotional perception work together to affect assessments of AI-generated

versus human-created art. The existence of bias has been established by earlier studies, but the ways in which attribution, perceived effort, and emotional authenticity interact to influence aesthetic judgment in various circumstances have not been sufficiently synthesized.

This review highlights the necessity for a thorough, theory-based synthesis that combines empirical data, points out gaps, and offers a methodical framework for further study of artificial intelligence and human creativity.

5. METHODOLOGY

The current research follows an established methodology, collecting findings only from peer-reviewed academic papers that look at, either theoretically or experimentally, how people view art created by AI and by humans. The purpose of the methodological approach is to make sure conceptual consistency, rigor, and transparency in keeping with acknowledged review article standards.

5.1 Research Design

Research studies usually follow a plan to get results. These plans include two methods:, between-subjects and within-subjects methods. In these studies people are asked to look at art and say what they think about it. They have to rate the art based on how nice it looks how much they like it how it makes them feel how unique it is and how much it is worth. [2] [5] To see how people react to art made by humans or computers a common way to do this is to show them the art and say it was made by either a human or a computer [1] [3].

People want to know how others feel about the art so they ask for their thoughts and opinions in interviews. By asking open-ended questions [6]. They also want to know what people think when they look at the art so they use tools like eye-tracking to see what people are looking at and for how long. This helps them figure out what people think about the art and how they feel about it. If that is different, from what they say they think and feel about the art made by humans or computers. These techniques demonstrate that bias mostly functions at the cognitive evaluation stage as opposed to during initial visual perception [3].

5.2 Selection of Studies

The reviewed literature consists of studies that:

- Directly compare AI-generated and human-created artworks.
- Examine emotional perception, aesthetic judgment, creativity, or value attribution.
- Employ experimental, survey-based, or mixed-method research designs.

Every study in this review was chosen for its applicability to cognitive bias and emotional perception in art judgment [1], [8].

5.3 Data Analysis Approaches

Across the reviewed studies, statistical analyses commonly include:

- Mean comparison tests.
- Regression analyses examining the influence of creator attribution.
- Correlation analyses linking attitudes toward AI with aesthetic evaluations.

Qualitative data are typically analyzed thematically to identify recurring beliefs about creativity, effort, and emotional capacity

[4], [7].

5.4 Limitations of Existing Methodologies

Existing approaches, that offer useful information, often rely on small characteristics, limited contact, and basic emotional variables. These disadvantages indicate the need for more comprehensive and environmentally responsible research methodologies in further investigations [6].

6. PROPOSED WORK

To really understand how people feel about art and how their thoughts affect what they think of art made by machines and art made by humans we need to look at this in an organized way. The work we are proposing will build on what we know from past research and ideas.

Our approach is to think of judging art as something that happens in steps and that it is affected by what we see and what we believe about the art, rather than just thinking that art made by machines and art made by humans are completely different just because of who made them.

We are talking about art made by machines and art made by humans and how people perceive art made by machines and art made by humans. People have done studies before. They found out that when we compare art made by machines to art made by humans the main difference is what we think about it. We think about how creative it's how much effort went into making it and what the artist was feeling.. When we actually look at the art the difference is not that big. We can look at some studies to see this for ourselves [1] [2] [3].

When we look at a piece of art the first thing we notice is what it looks like. We see the colors, the way things are arranged and the style. At this point it does not matter if the art was made by a person or by Artificial Intelligence. Our reaction to the art is much the same.. Then something changes. Soon as we find out who made the art our opinion of it starts to change. This happens when we are told who the artist is or when we can figure it out from the context. The art made by Artificial Intelligence and the art made by humans start to look different, to us. This stage is about what people think it means to be creative to really feel things and to work hard to make art. People have ideas, about creativity, emotional depth and artistic struggle. These ideas shape what people think is authentic and what things mean. Human creativity and artistic struggle play a role in this. People want to know if something is real and if it has meaning. Human creativity is important here [4], [5].

The experiment they suggest shows that it is the way we think about things, not what we see, that helps us feel emotions. When people look at art they get feelings and ideas about what is good or bad because they are using clues from the art and things they already believe about art from their culture. Artificial intelligence art is often seen as being made by a machine and without feeling so people do not feel much emotion when they look at it even if it looks just as good, as art made by humans.

On the hand art made by humans is usually seen as a way for the artist to express their emotions and things that have happened to them [6] [7].


When we look at art made by humans and art made by intelligence we usually compare them to see which one is better.. This approach is not very helpful. The suggested work wants to change this by looking at art that is made by humans and artificial intelligence together.

This way we can see how people really make art and how it affects what we think and feel about it. We should also look at how people from cultures and backgrounds think about art made by artificial intelligence. Artificial intelligence art is something that people are still getting used to so our opinions about it will probably change over time. We need to study this over a period of time to see how our thoughts and feelings about artificial intelligence art change.

- We can look at how people from cultures think about artificial intelligence art.
- We can study how peoples thoughts and feelings about intelligence art change over time.

The suggested work is about artificial intelligence art and human art and how we can learn more, about both by looking at them together [3], [8].

Overall, through the integration of attribution theory, emotional perception, and aesthetic assessment, the suggested work offers a cohesive conceptual and methodological approach for further investigation. This method not only explains why prejudice against AI- generated art still exists, but it also lays the groundwork for comprehending how changing human–AI partnerships could alter conventional ideas of artistic inventiveness, authenticity, and emotional resonance.



7. CONCLUSION

This review highlights how people's emotional perceptions of art are greatly affected by psychological and logical bias. Across a broad range of methods and artistic areas, human- produced art is always considered as more valuable, meaningful, and emotionally affecting than AI-generated art.

Forming ethical, cultural, and creative responses to artificial intelligence innovation as it continues to influence the creative sectors will require an understanding of these behavioral mechanisms.

8. REFERNENCES

- [1] L. Bellaiche et al., “Humans versus AI: Whether and Why We Prefer Human-Created Compared to AI-Created Artwork,” *Cognitive Research: Principles and Implications*, 2023.
- [2] M. Ragot et al., “AI-Generated vs. Human Artworks: A Perception Bias Toward Artificial Intelligence?” *CHI Conference on Human Factors in Computing Systems*, 2020.
- [3] C. V. Cunningham et al., “Human Creativity Versus Artificial Intelligence: Source Attribution and Observer Attitudes,” *Frontiers in Psychology*, 2025.
- [4] J. van Waning, “Human Art vs. AI Art: Artistic and Economic Evaluations Across Multiple Art Genres,” 2024.
- [5] J. Hall and D. Schofield, “The Value of Creativity: Human Produced Art vs. AI- Generated Art,” *Art and Design Review*, 2025.
- [6] V. Chauhan and N. Chanda, “Analysing Young Adults’ Preferences for AI-Generated and Human-Created Art in India,” *IRJMS*, 2025.
- [7] A. Daniele and Y.-Z. Song, “AI + Art = Human,” *AAAI Conference on Artificial Intelligence*, 2019.
- [8] Additional reviewed works from the provided dataset.

SACHET WASTE MAPPING: THE HIDDEN PLASTIC

Poornima Londhe¹ and Smruti Nanavaty²¹Department of Information Technology, Usha Pravin Gandhi College of Arts, Science and Commerce Mumbai, Maharashtra, India²Vice Principle & Head of Department (I.T), Usha Pravin Gandhi College of Arts, Science and Commerce Mumbai, Maharashtra, India**ABSTRACT**

The sachet packaging is very popular in packaging products that people use on a daily basis since it is economical and convenient. Nevertheless, the waste in sachets has been a major environmental issue since they are not properly disposed of and are also not readily recycled. The research seeks to learn the ways people use sachets, how they dispose the containers, their attitude regarding plastic pollution, and their readiness to act as substitutes. The data was gathered by way of a questionnaire survey. The statistical analysis of the gathered data was done with the help of simple statistical tools and presented in the form of charts. Findings indicate that the use of sachets is highly prevalent with most of the individuals knowing the effects of plastic pollution but not disposing of them correctly. This demonstrates a disjunction between knowledge and action. It was also discovered that the majority of respondents are ready to promote the alternatives to the sachet packaging in case they become easy to find. The results indicate that the current waste management techniques and realistic options should be improved to lessen the plastic pollution caused by sachets.

Keywords— Sachet packets, waste management, recycling, environmental concerns, plastic pollution.

I. INTRODUCTION

Shampoo, oil, detergent, and food are some of the products that are usually packaged in sachets. A big part of the consumers are very fond of sachets because of its low price. Sachet plastics are however not easily recyclable as they consist of several layers. This usually leads to their being dumped in landfills, open spaces or drains thus polluting the environment. Sachet waste is an issue that leads to obstruction of drainage systems, floods and accumulation of plastics in the environment. Sachet waste management is not well addressed despite the rising awareness concerning plastic pollution. This paper is dedicated to the perception of how sachets are used, how they are disposed, the level of awareness, and the readiness of the population to use sustainable options, hence, the paper sheds light on the so- called hidden plastic crisis as a result of sachet waste.

II. LITERATURE REVIEW

The use of plastic waste has raised a significant issue of concern in the environment because the waste is not biodegradable, and it is being used more in our day to day activities. A number of studies have indicated that single-use plastics, in particular, sachet packaging, are major contributors to solid waste in urban areas. Previous studies have indicated that the sachets are commonly used in packaging of foods, water and personal care items due to their cheapness and convenience but cause serious complications of waste management systems. Numerous scholars have

examined the creation of plastic waste and its effect on the environment in developing nations. The research indicates that sachet wastes do not go through proper waste collection systems because of small size and low value to recycle. Consequently, sachets settle in open drains, roadsides and water bodies causing environmental pollution and health hazards. It has been highlighted in previous work that the inappropriate disposal of sachet waste causes flooding and soil pollution. Geographic Information System (GIS) has been generally applied in mapping and analysis of solid waste distribution. GIS has been used to determine locations where wastes are likely to be found, optimize routes of picking up waste materials as well as in making decisions related to the planning of cities. Other researchers have managed to apply spatial mapping in identifying hotspots of plastic waste to assist local governments in enhancing waste management policies. Recent literature incorporates field surveys with GIS- based mapping analysis of plastic waste patterns of distribution. According to these studies, spatial analysis assists in determination of the connection existing between population density, commercial activities and waste accretion. Nevertheless, there is a lack of micro-level studies on the sachet waste mapping in urban and semi-urban settings. Based on the literature reviewed, it is noted that although plastic waste management has received a lot of attention, there is a lack of exploration on sachet waste mapping in GIS. This study will fill this gap by targeting the spatial distribution of sachet waste and won't fail to offer some data-driven information to back up sustainable waste management activities.

III. Objectives of the Study:

1- To find out the usage trend of sachet-based products.


-
- 2- To examine how the sachets were disposed of.
 - 3- To test the correlation of awareness and disposal practices.
 - 4- To know the willingness of people to use substitutes to sachet packaging.

IV. Methodology:

The research has a foundation on primary data that was gathered by use of an online questionnaire. The questions that were part of the survey were related to the use of the sachets, how they are disposed, their awareness of plastic pollution, and their willingness to embrace alternative packaging options. The analysis of the responses was conducted in Python in Jupyter Notebook. The data were interpreted using a simple statistical method like percentage analysis and charts.

V. Problem Statement

The rising trend in using single-use plastic sachets when packaging food, water and personal care products has led to a sharp increase in the generation of plastic waste particularly in urban and semi urban regions. Sachet plastics are not efficiently collected by current waste management systems because of poor disposal caused by their small size, low economic value of recycling and consumption of the products. The waste of sachets is deposited all round urban areas causing environmental pollution, drainage sewer blockage, and probable health risks. Although the problem of sachet waste is apparent in the open areas, no systematic data on the spatial distribution and concentration of the waste exists. Generalized waste data is usually used by municipal authorities and this does not help in dealing with localized hot spots of sachet wastes. The conventional waste management methods lack adequate space understanding to aid in any form of planning interventions. The lack of location mapping and analysis complicates the possibility of identifying the high-risk areas and adopting the efficient control of the waste. Hence, the necessity of an organized methodology with the adoption of the spatial mapping tool to examine sachet waste distribution exists. This paper is a solution to the identified problem as it dwells on the assignment of sachet waste mapping, through the application of Geographic Information System (GIS) tools, to determine the patterns of waste accumulation and assist in data-driven decision-making to enhance urban waste management.




The enormous consumption of single-use plastic sachet has seen a massive growth of plastic waste production in cities. The sachet wastes are not well collected by the waste management systems in place due to their small size and low recycling value and are usually discarded in improper ways. This leads to environmental pollution and health hazards as sachet plastics are deposited in the open areas like road side, drainage systems and water bodies. Although the sachet waste has been increasing in growth, there is a scarcity of location specific data that can be used to determine the areas where sachet waste is concentrated. The traditional method of waste management does not incorporate any spatial analysis and authorities can hardly identify the areas of waste accumulation and therefore design specific waste reduction measures. As such, a location-based and systematic mapping and analysis of the distribution of sachet waste is required to facilitate efficient waste management and sustainable urban planning.

RESULT




Which of the following best describes the type of area you live in?

74 responses




Are sachet plastics collected separately by waste collectors in your area?

74 responses




Are you aware that sachet plastics are difficult to recycle?

74 responses




In your opinion, does sachet plastic waste contribute to environmental problems such as pollution or flooding?

74 responses



Would you support the use of alternatives to sachet packaging if they were easily available?


73 responses



A. Data Analysis and Results:

B. Analysis 1: The use of Sachet-Based Products.

The review indicates that many of the respondents often consume products in the form of sachets. This shows that there is a great dependence on sachet packs in the day-to-day activities.




Research Gap Identified:

Although the use of sachets is very high, not much attention has been paid to what happens after sachets are used.

Analysis 2: Sachet Waste Disposal

The findings show that the majority of the respondents discard the sachet packets used and the household waste. The respondents who dispose of their waste in the right and safe way are few.




Research Gap Identified:

The proper disposal practices do not support high consumption of sachets implying that there is poor behavior of waste management.

Analysis 3: Thinking Before Acting and Throwing Things Away.

As the analysis indicates, most of the respondents know that sachet plastics are pollutants to the environment. Nevertheless, the awareness does not lead to correct disposal practices since improper disposal remains the norm.




Research Gap Identified :

The discrepancies between awareness and behavior are evident in the sense that the knowledge about plastic pollution has not resulted in responsible disposal of waste.

Analysis 4: Willingness to Support Alternatives

The results indicate that most of the respondents will be ready to contribute to alternatives to sachet packaging in case of the ready availability. This is an indication of a good attitude in terms of lessening waste sachet.



Research Gap Identified:

Although the individuals are ready to change to alternatives, these alternatives are not extensive or accessible.

DISCUSSION

The research notes that there is a massive use of sachets, yet, there is poor waste management behavior. Whereas there is awareness towards plastic pollution, it is not translated to responsible disposal. This implies that there is no effect in just creating awareness to deal with the sachet waste issue. The readiness to accept substitutes implies that the situation can be improved, yet actions and avenues to sustainable packaging should be implemented and made available.

CONCLUSION

This paper summarizes that sachets are the major, but not well-addressed sources of plastic contamination. The results indicate that the sachets are used highly, there is improper disposal behaviour and awareness-action gap is high. Nevertheless, it is encouraging to note that the reaction to alternative packaging is positive, so given the appropriate policy, sensitization, and access to sustainable alternatives, it is possible to minimize the waste in sachets. There should be a resolution of behavioral as well as structural gaps to manage the hidden plastic crisis as brought about by sachet packaging.

REFERENCES

- [1] R. Geyer, J. R. Jambeck, and K. L. Law, Production, use, and fate of all plastics ever made, *Science Advances*, vol. 3, no. 7, pp. 1– 5, 2017.
- [2] J. R. Jambeck et al., Plastic waste inputs into the ocean, *Science*, no. 347, vol. 6223, pp. 768 771, 2015.
- [3] S. Hopewell, R. Dvorak, and E. Kosior, Plastics recycling: Challenges and opportunities, *Philosophical Transactions of the Royal Society B*, vol. 364, no. 1526, pp. 21152126, 2009.
- [4] A. A. Lebreton and A. Andrady, Future scenarios of global plastic waste generation and disposal, *Palgrave Communications*, vol. 5, no. 6, pp. 1 -11, 2019. P. K. Tiwari and S. Kumar,
- [5] P.K.Tiwari, S. Kumar, Use GIS in solid waste management: A review, *International Journal of Environmental Sciences*, vol. 6, no. 3, pp. 342349, 2016.
- [6] M. S. Kaza, L. Yao, P. Bhada-Tata and F. Van Woerden, *What a Waste 2.0, A Global Snapshot of Solid Waste Management to 2050*, World Bank, Washington, DC, USA, 2018.
- [7] N. Ferronato and V. Torretta, Waste mismanagement in developing countries: A review of global issues, *International Journal of Environmental Research and Public Health*, vol. 16, no. 6, pp. 1 28, 2019.
- [8] ESRI, “Solid waste management with GIS, Environmental Systems Research Institute, White Paper, 2017.

SEMANTIC-BASED ACADEMIC IMAGE CLASSIFICATION USING OCR AND EXTERNAL KNOWLEDGE SOURCES

¹Tanisha Bhargamia and ²Dr. Neha Vora

Undergraduate Student, Department of Information Technology, Svkm's Usha Pravin Gandhi College
Department of Information Technology, SVKM's Usha Pravin Gandhi College of Arts. Science and Commerce
Mumbai, Maharashtra 400056, India

ABSTRACT

students widely use smartphones and other digital devices to capture academic material in the form of images. Handwritten lecture notes, textbook pages, screenshots of slides, and annotated diagrams are usually stored for future reference. This makes collecting study material easy, organizing and managing a large number of images becomes a problem over time. As the number of stored images increases, finding specific or relevant content becomes difficult, and manual sorting is usually slow, inconsistent, and prone to mistakes.

This work presents the implementation of an artificial intelligence-based system designed to organize academic images automatically into subject-wise categories. The system begins by reading the textual content from images using Optical Character Recognition (OCR). The extracted text is then processed using Natural Language Processing (NLP) techniques to understand the underlying meaning of the content. It Instead of depending only on direct keyword matching, sentence embedding models are used to capture semantic relationships within the text. To further improve subject identification the additional contextual information related to each subject is obtained from external knowledge sources. Based on similarity scores and predefined confidence thresholds the images are assigned to appropriate subject folders. Images that do not meet the confidence criteria are stored separately to avoid incorrect classification. Overall, the system helps reduce manual effort and provides a practical solution for organizing academic image data in a more structured manner.

Keywords—Academic Image Classification, Optical Character Recognition (OCR), Semantic Similarity, Natural Language Processing, Study Material Organization

I. INTRODUCTION

Digital devices are now a normal part of everyday learning, and they have changed how students keep track of their study materials. Many students no longer write everything by hand. Instead, they use their smartphones or other devices to take pictures of lecture notes, textbook pages, and diagrams during or after class. Taking pictures makes it quick and convenient to save important academic content during or after classes. when more images are stored, managing them becomes difficult. Hundreds of images are saved, finding a specific note or diagram can take a lot of time. Organizing these images manually is slow and also inefficient and takes a lot of time. There are higher chances of making mistake while sorting or labelling files as the amount of stored data keeps increasing.

Artificial intelligence can help simplify this process by automatically analyzing and organizing image-based study materials. Optical Character Recognition (OCR) is used for reading the text from images that includes both printed and handwritten content. Once the text is extracted the Natural Language Processing (NLP) techniques are applied to understand the meaning of the information. When these techniques are combined with semantic similarity models the study materials can be grouped into different subjects based on their actual meaning rather than simple keyword matching. This approach helps in reducing the manual effort and helps students save time while managing their study resources.

II. RELATED WORK

Organizing and analyzing the academic content stored as images has become more important as OCR and NLP techniques are used more widely. OCR is especially useful in such systems because it that allows text to be extracted from images so that it can be processed further. Smith [2] also discussed the Tesseract OCR engine and he also explained how it can effectively convert printed text into a machine-readable form. In practical use the python tools such as pytesseract have made OCR very easy to implement as they allow text to be extracted from images without requiring complicated configuration or setup [9].

The recent researches has also focused on better ways to represent and understand the extracted text. Simple keyword-based methods often fail when the same concept is expressed using different terms or writing styles. To deal with this problem, Reimers and Gurevych [3] introduced Sentence-BERT, which focuses on representing entire sentences in a way that helps capture their actual meaning using Siamese BERT networks.

This approach made it possible to compare text based on meaning rather than exact word matches. Later, Wang et al. [4] proposed MiniLM, a lighter transformer model that reduces computational complexity while still maintaining good semantic performance. Due to this balance between efficiency and accuracy, pre-trained models such as paraphrase-MiniLM-L6-v2, available through the sentence-transformers library, have been commonly used for tasks related to semantic similarity and textual relevance [5][10].

Wikipedia is one of the sources used by the system, and it can be accessed through the Wikipedia-API to collect structured information related to different subjects [6][7]. This additional information supports better subject identification and improves interpretation of the extracted text. When these knowledge sources are combined with image preprocessing tools such as OpenCV [8], the system performs better. It handles the academic image data properly. Image preprocessing helps improve image quality, which in turn supports more accurate text extraction before further analysis.

Bhargamia and Vora [1] presented a cloud-based conceptual framework for managing student images by using artificial intelligence techniques. It focuses on automated organization and easy accessibility of academic content. Their work suggests that using OCR together with semantic similarity techniques can really help in organizing academic images more effectively.

III. PROPOSED WORK

The main idea behind this paper is to develop and build an AI-driven system that automatically organize academic study materials that are captured as the images. Students can upload or capture images of handwritten notes, lecture slides, or textbook pages. Once the images are added then the system analyzes them to understand what the content is about. It uses OCR to read the text from the images and semantic analysis to understand the meaning of that text. This helps in sorting the images into the correct subject folders.

This automatic sorting removes the need to manually organize files that can be time consuming and confusing. When everything properly arranged it also helps reduce the clutter. Since all study material is stored in one place and organized by subject it becomes very easy and faster to find the required image or information. The system helps students spend less time managing files and more time focusing on their studies.

The system follows the steps.

Step 1: System Initialization

The system starts by setting up an input folder that contains academic images. It also creates an output folder where the classified images will get stored. The user gives the subject names that are used to create the subject folder automatically. The extra folder called Unclassified folder is also created to store images that the system is not fully confident about.

Step 2: Image Input and Acquisition

The system takes the images such as handwritten notes, printed textbook pages, or diagrams as the input. The system supports the common image formats like JPG and PNG. Each image is processed one at a time so that system can analyze it properly.

Step 3: Extraction of text using OCR

The system uses OCR to read and extract the text from each image. To make the text easier to read the images are first converted into grayscale. The system extracts both printed text and handwritten content. If an image does not contain any readable text then that image is moved directly moved the Unclassified folder.

Step 4: Subject-wise Context Expansion

For each subject the system collects the extra information from sources like Wikipedia. This step can help the system to understand related terms and ideas within the same subject which improves classification accuracy.

Step 5: Semantic Representation

The text taken from images and the subject-related information is converted into sentence embeddings. These embeddings represents the meaning instead of just matching exact words. This helps the system understand what the image is actually about.

Step 6: Direct Text Matching

A high-confidence check is carried out to check if the subject name directly appears in the extracted text. If a strong match is found then the image is classified immediately.

Step 7: Semantic Similarity Analysis and Classification Decision

If no direct match is found the cosine similarity are used to compare the image embeddings with subject embeddings.

It helps us to identify how closely the content is related to each of the subject. If the similarity score crosses a predefined threshold then that image is assigned to that subject. If the system is still not confident about the image then it is placed in the Unclassified folder to avoid any wrong classification.

Step 8: Content Organization and completion

All the classified images are stored in subject specific folders. This creates a structured and organized collections of academic materials. After all the images are processed the system completes its execution and remains ready for additional inputs.

IV. IMPLEMENTATION OF PROPOSED SYSTEM**1. Overview of the Implementation**

The proposed system is built to automatically organize academic images into subject-wise folders. The main idea behind this system is that to reduce the effort needed to manually sort study materials. The system applies Optical Character Recognition (OCR) to extract text from images and combines it with semantic text analysis and external knowledge sources to better understand the content. After the image is analyzed the it is simply placed into the subject folder it belongs to. The whole system works in a clear step-by-step way so there is nothing that gets confusing. It basically starts when an image is given as input and ends with that image being stored in the correct subject folder. Because of this simple flow the classification process becomes easy to understand and works properly.


2. System Architecture

Fig. 1 Architecture

The whole working of the system is shown in figure1. The process starts when an academic image such as handwritten notes, textbook pages, or study material screenshots are given as input. These images are first passed through an OCR module first. This module extract the text present in them. After this process the extracted text is cleaned and processed and additional subject related information is collected from external sources like Wikipedia. The sentence embedding models are then used to understand the meaning of the text. Then the direct text matching and semantic similarity is checked. Now on the basis of similarity scores and a predefined threshold the system decides which subject folder the image should be placed in. If the system is not confident or sure about the classification then the image is moved to an Unclassified folder to avoid any incorrect sorting.

3. Working of the Proposed System (How It Works):-

The system works in a few simple steps. First, the user provides the list of all the subject names. The user also provides the academic images that are needed to be organized. These images can include handwritten notes, textbook pages, or other study-related content. Once the input is given, the system starts processing each image one by one for every image, text is extracted using OCR. Since this text alone may not always clearly indicate the subject, the system also collects additional information related to each subject from external knowledge sources. After this, both the extracted text and the subject-related information are converted into semantic embeddings. These embeddings helps the system understand the meaning of the content. The system then compares these embeddings and also checks how closely the image content matches each subject. Based on the similarity score and a confidence threshold the images are then placed into the most suitable subject folder. If the system is unsure about the classification, the image is stored in an Unclassified folder to avoid placing it in the wrong category.

4. Algorithm / Pseudocode:-

Input: Academic Images List Of Subjects

Output: Subject based organized image folders

1. Set up the input folder and the output folder.
2. Take subject names from the user.
3. Create the folders for each subject and also create an Unclassified folder.
4. Go through each image in the input folder:
 - a. Extract the text from the image using OCR.
 - b. If no readable text is found then it move the image into the Unclassified folder.
 - c. Collect the additional subject-related information using external knowledge sources.
 - d. Generate the semantic embeddings for both the image text and the subject information.
 - e. Check for direct matches between the text and subject names.
 - f. If a direct match is found then assign the image to that subject folder.
 - g. If no direct match is found then calculate similarity scores.
 - h. If the score is above the set threshold, assign the image to the most relevant subject folder.
 - i. Otherwise, move the image to the Unclassified folder.
5. Save all images in their respective folders.
6. Stop the process.

V. SCREENSHOT RESULT

Name	Date modified	Type	Size
.idea	21-12-2025 16:21	File folder	
.venv	27-10-2025 15:45	File folder	
clustered	07-01-2026 22:38	File folder	
images	07-01-2026 22:35	File folder	
folder_mapping.json	22-12-2025 19:21	JSON File	25 KB
hybrid_image_clustering	24-12-2025 16:25	Python File	6 KB

Fig.2. Folder Structure of the Implemented System

This screenshot shows that how the folders are arranged in the implemented system. The various input folder contains the original academic images uploaded by the user. The output folders are also referred to as the clustered folder. These folders store the images after they have been sorted into different subjects. The folder also contains a few configuration and script files that are required for the system to run properly. Overall this folder setup helps in keeping the input images, the classified output, and the system files separate. This makes everything much easier to organize and handle.




Fig.3. Folder of Images(Input Academic Images)

This figure shows the images folder that contains different types of academic images such as handwritten notes, printed study material, lecture slides, and diagrams. These images are used as the input for the system. These images act as the input for the system and are processed one by one during classification. These images are used as the raw input for the system.Each image is handled one by one, where the system extracts the text and decides which subject the image belongs to.




Fig.4. subject-wise folder after Sorting

This screenshot also shows the final output after the system has finished running. Academic images are automatically grouped into subject folders such as Artificial Intelligence, Java, Machine Learning, Mathematics, and others. An extra folder named Unclassified is also created to store images that do not meet the confidence requirement for classification. This also helps in avoiding placing the images in the wrong subject folder. This folder structure makes it easier to store study materials properly and find them later without any confusion.



Fig. 5. Sample Subject Folder Containing Classified Images

This screenshot shows one of the subject folders after the image sorting process is completed. The folder contains images that were automatically placed based on how closely their content matches the subject. Since the images in the folder are related to the same topic, it shows that the system is able to group academic images properly and keep related content together.

VI.RESULT AND PERFORMANCE ANALYSIS

The system was tested using variety different academic images. Images included the handwritten notes, printed study materials, and lecture slides from various subjects.

The purpose of this testing was to see how accurately the system could place these images into the correct subject folders. It was also to test how it handles the unclear images without putting them in the wrong subject folder.

The results showed that the system performs well when the images contained enough textual information. Images that contained clear subject-related terms or helpful context were correctly placed in their respective folders. The use of external knowledge sources have made the system more reliable by helping it recognize different terms and variations that are commonly used for the subjects.

VII. CONCLUSION

This paper discusses an AI-based system that helps to organize academic images into different subjects automatically. The main idea is to reduce the efforts of the students that usually put into manually sorting their notes and study materials. The system uses OCR to extract text from images uploaded or clicked and then it uses semantic analysis along with some external sources to understand what the content is about and place it into the right subject folder.

Instead of just matching keywords the sentence embeddings are used so the system looks at the overall meaning of the content. The simple confidence check is also added so that images are not placed in the wrong subject whenever the system is not sure. The result showed the system worked best when the text in the images is clear and readable. Overall, this paper shows that AI can really help in organizing study materials and make it easier for students to manage their digital notes without too much manual effort.

VIII.REFERENCES

- [1] T. Bhalgamia and N. Vora, "AI-Powered Cloud Solution for Student Image Management," *Advanced International Journal for Research (AIJFR)*, vol. 6, no. 5, Sept.–Oct. 2025.
- [2] R. Smith, "An Overview of the Tesseract OCR Engine," in *Proceedings of the 9th International Conference on Document Analysis and Recognition (ICDAR)*, 2007.
- [3] N. Reimers and I. Gurevych, "Sentence-BERT: Sentence Embeddings using Siamese BERT-Networks," *arXiv preprint arXiv:1908.10084*, 2019.
- [4] W. Wang, F. Wei, L. Dong, H. Bao, N. Yang, and M. Zhou, "MiniLM: Deep Self-Attention Distillation for Task-Agnostic Compression of Pre-Trained Transformers," *arXiv preprint arXiv:2002.10957*, 2020.
- [5] Sentence-Transformers, "paraphrase-MiniLM-L6-v2," Hugging Face Model Card.
- [6] Wikipedia-API, "Wikipedia-API (Python package) documentation," *Read the Docs*.
- [7] Wikipedia-API, "Wikipedia-API package," *PyPI*.
- [8] G. Bradski, "The OpenCV Library," *Dr. Dobb's Journal*, 2000.
- [9] Madmaze, "pytesseract: Python wrapper for Tesseract," *GitHub repository*.
- [10] Sentence-Transformers Documentation, "Semantic Textual Similarity (STS) usage," *sbnet.net*.
- [11] Q. Tang, Y. Lee, and H. Jung, "The industrial application of artificial intelligence-based optical character recognition in modern manufacturing innovations," *Sustainability*, vol. 16, no. 5, p. 2161, 2024.
- [12] A. Mishra, J. Sikdar, and S. U. Kumar, "Deep learning-based optical character recognition for robust real-world conditions: A comparative analysis," in *Proc. 15th Int. Conf. Computing, Communication and Networking Technologies (ICCCNT)*, 2024, pp. 1–7.
- [13] M. Modi, A. Shah, D. Kothadiya, and M. Rahevar, "Optical character recognition: Comparative analysis of Tesseract and Textract on diverse datasets," in *Proc. 3rd Int. Conf. Automation, Computing and Renewable Systems (ICACRS)*, 2024, pp. 913–919.

-
- [14] I. Malashin, I. Masich, V. Tynchenko, A. Gantimurov, V. Nelyub, and A. Borodulin, "Image text extraction and natural language processing of unstructured data from medical reports," *Machine Learning and Knowledge Extraction*, vol. 6, no. 2, pp. 1361–1377, 2024, doi: 10.3390/make6020064.
- [15] S. Fernando and M. Stevenson, "A semantic similarity approach to paraphrase detection," in *Proc. 11th Annu. Research Colloquium of the UK Special Interest Group for Computational Linguistics*, 2008.

AI-POWERED WORKFORCE TRANSFORMATION: K-MEANS CLUSTERING STUDY OF ENTERPRISE ADOPTION OF GENERATIVE AI.

¹Keyur Amit Mistry and ²Dr. Smruti Nanavaty

¹Department of Information Technology, Usha Pravin Gandhi College of Arts, Science & Commerce
Mumbai, Maharashtra, India

²Vice Principal, Usha Pravin Gandhi College of Arts, Science & Commerce, Mumbai, Maharashtra, India

ABSTRACT

The rapid emergence of Generative Artificial Intelligence (GenAI) has caused major changes in the structure of enterprise workforces, skill needs and productivity rates. Although previous studies are mostly theoretical in their implications and survey-based information, little empirical data exist to classify practical-scale enterprise adaptation patterns. This study fills this gap and attempts to analyze workforce transformation as a result of Gen AI adoption using machine learning-based clustering.

A representative sample of 10,000 records of enterprises in 13 industries was studied using the Enterprise Gen AI Adoption and Workforce Impact Dataset (2022-2024). Among the important variables, one can distinguish the number of affected employees, the number of new jobs connected to AI, the number of hours spent on training, and changes in productivity. K-means clustering was used to determine the different strategies of Gen AI workforce adaptation, with ideal cluster selection methods being the elbow method and silhouette score.

These findings demonstrate three distinct archetypes of enterprise adaptation: high-impact adopters, balanced adopters, and training-led adopters. Firms that invested a lot in training the workforce revealed the greatest productivity levels, and structured upskilling is essential for the successful integration of GenAI. This results in a taxonomy of the findings that enables organizations to compare their GenAI maturity and better align their workforce strategies. The proposed research provides empirical evidence on the adoption of GenAI at the enterprise level and provides practical recommendations on how to plan the workforce in the transforming AI-based workplace

KEYWORDS: *Generative AI, Workforce Transformation, Adoption of AI technologies, K-Means clustering technique, Machine Learning Methods, Employee Reskilling Initiatives, Productivity Performance Analysis*

INTRODUCTION

The rapid advancement of Generative Artificial Intelligence (GenAI) has transformed how enterprises design work processes, manage human resources, and achieve productivity gains. Unlike earlier forms of automation that primarily focused on rule-based tasks, GenAI systems, such as large language models and domain-specific AI tools, are increasingly capable of supporting complex cognitive activities, including content generation, decision support, and knowledge-intensive work. Consequently, organizations across industries are integrating GenAI into their core operations, directly affecting workforce structures, skill requirements, and job roles [1], [3].

Between 2022 and 2024, enterprise adoption of GenAI accelerated significantly, driven by improvements in model capabilities, reduced deployment costs, and growing competitive pressure. While existing literature highlights the potential of GenAI to enhance efficiency and innovation, real-world enterprise outcomes remain uneven. Some organizations report substantial productivity improvements through structured reskilling and human-AI collaboration, whereas others experience workforce resistance, skill mismatches, and limited return on investment [2], [4], [5]. These variations suggest that enterprises do not follow a single, uniform path of GenAI adoption.

Much of the prior research on AI and the future of work relies on conceptual frameworks, surveys, or small-scale case studies. Although these studies provide valuable insights into automation risks, ethical concerns, and reskilling needs, they lack large-scale empirical analysis that captures how enterprises actually adapt their workforce in practice [1], [6]. In particular, there is limited research that systematically categorizes enterprise GenAI adoption strategies using quantitative workforce and performance metrics.

To address this limitation, this study adopts a data-driven approach to examine enterprise workforce transformation resulting from GenAI adoption. This study will model K-Means clustering on a large-size dataset consisting of enterprise deployments in several industries between 2022 and 2024 in order to establish the specific patterns of workforce adaptation.

The most important signs that include the number of employees affected, hours spent on training, the establishment of new positions connected with AI use, and productivity transformation are examined to help identify interesting archetypes of enterprises adaptation that matter at the enterprise level.

Comparison of these clusters will lead to empirical evidence on the impact of various strategies of GenAI adoption on workforce outcomes as part of the study. The results provide a realistic taxonomy that will help businesses measure their GenAI maturity, create productive reskilling programs, and strategize workforce plans and technological change. This research contributes to the growing body of AI workforce literature by moving beyond theoretical discussion and presenting a scalable, machine learning-based analysis of real-world enterprise adaptation to Generative AI.

OBJECTIVES OF THE STUDY

The primary objective of this research is to empirically examine enterprise workforce transformation resulting from Generative Artificial Intelligence (GenAI) adoption using a machine learning-based clustering approach. The specific objectives of the study are as follows:

To examine the trends in the adoption of GenAI at the enterprise-level and across several industries based on workforce and productivity-related measures.

To investigate effects of GenAI implementation on workforce, such as how many people are directly impacted and how many positions are introduced because of AI.

To assess whether there is a connection between investment in workforce training and productivity results in companies that implement GenAI technologies.

To use K-Means clustering to find out specific patterns of enterprise workforce adaptation as a result of training hours, workforce influence, the creation of roles, and the increase of productivity.

To compare GenAI workforce adaptation strategies across industries and identify dominant adoption archetypes.

To provide a data-driven framework that enables enterprises to benchmark their GenAI workforce maturity and align workforce strategies with technological transformation.

LITERATURE REVIEW

The rapid growth of Generative Artificial Intelligence (GenAI) has shifted academic discussion on the future of work from speculative automation concerns to empirical analysis of enterprise workforce adaptation. Recent literature explores GenAI adoption across productivity enhancement, workforce restructuring, reskilling strategies, and industry-specific transformation patterns. This section reviews existing studies relevant to enterprise GenAI adoption and identifies limitations that motivate the present research.

GenAI and Workforce Transformation-s

Several studies have highlighted the transformative impact of AI and GenAI on workforce structures and job roles. McKinsey Global Institute (2023) reports that AI-driven automation could affect up to 30% of work activities globally, while simultaneously creating demand for new digital and analytical roles [1]. Similarly, the World Economic Forum (2023) emphasizes that although AI may displace routine tasks, it also accelerates job creation in areas requiring advanced technical and cognitive skills [2].

Empirical evidence further supports these findings. Noy and Zhang (2025) conducted a large-scale field experiment demonstrating that access to GenAI tools increased worker productivity, particularly among less experienced employees [10]. Deloitte Insights (2022) also found that organizations adopting AI-enabled workflows experienced higher operational efficiency when human-AI collaboration models were implemented effectively [4]. However, these studies largely analyse outcomes in isolation and do not systematically classify enterprise-level adaptation strategies.

Workforce Reskilling and Training Investment

Workforce reskilling is consistently identified as a critical factor in successful AI adoption. McKinsey Global Institute (2023) estimates that enterprises must invest significant training hours to enable employees to work effectively alongside AI systems [1]. PwC (2023) similarly emphasizes that continuous learning and upskilling are essential to sustain long-term productivity gains in AI-driven environments [5].

Despite broad agreement on the importance of reskilling, existing research primarily relies on surveys or qualitative assessments.

Few studies empirically quantify the relationship between training investment and productivity outcomes across large enterprise datasets. As a result, the effectiveness of different reskilling intensities remains insufficiently validated using data-driven methods [7].

Industry-Specific Enterprise AI Adoption

AI adoption patterns vary considerably across industries. IBM Institute for Business Value (2024) reports that healthcare, finance, and technology sectors lead GenAI deployment, while manufacturing demonstrates comparatively higher productivity gains per unit of training investment [3]. These findings suggest that enterprise context and industry characteristics play a significant role in shaping workforce transformation outcomes.

However, most industry-focused studies present aggregated statistics or sector-level comparisons. There is limited research that applies machine learning techniques to identify cross-industry workforce adaptation patterns at the enterprise level. This lack of granular classification limits the ability of organizations to benchmark their GenAI maturity against comparable peers [6].

Methodological Approaches in AI Workforce Research

Recent workforce studies increasingly employ data analytics, sentiment analysis, and econometric modelling to assess AI impact [6], [7]. While these approaches provide valuable insights, they often treat enterprises as homogeneous entities or focus on predefined success metrics. Unsupervised machine learning methods, such as clustering, offer greater flexibility by allowing natural patterns to emerge directly from enterprise data. Despite this potential, clustering-based analysis of GenAI workforce adaptation remains relatively unexplored absent from current literature. Existing studies rarely integrate multiple workforce indicators—such as employees impacted, training investment, role creation, and productivity—into a unified analytical framework capable of identifying distinct enterprise adaptation archetypes [12].

RESEARCH GAP AND PROBLEM STATEMENT

Research Gap:

Despite growing academic and industry interest in the impact of Generative Artificial Intelligence (GenAI) on the workforce, existing research reveals several critical gaps that limit empirical understanding of enterprise-level adaptation.

First, most prior studies rely on conceptual frameworks, surveys, or small-scale case studies to examine AI-driven workforce transformation [1], [2], [6]. While these approaches provide valuable insights into perceived benefits and challenges, they do not capture real-world enterprise adaptation patterns at scale.

Second, although workforce reskilling is widely recognized as a key success factor in AI integration, the relationship between training investment and productivity outcomes has not been empirically validated using large enterprise datasets [1], [5], [7]. Existing studies often discuss reskilling requirements theoretically, without quantitatively measuring how different levels of training investment influence workforce performance.

Third, industry-specific differences in GenAI adoption are often reported in aggregated form, lacking systematic classification using machine learning techniques [3], [12]. As a result, enterprises lack data-driven benchmarks for assessing GenAI workforce maturity.

Finally, very limited research has applied unsupervised machine learning techniques, such as clustering, to identify natural groupings of enterprises based on GenAI workforce adaptation metrics. The absence of such analytical frameworks restricts the ability of organizations to benchmark their GenAI maturity and learn from empirically successful adoption patterns.

Problem Statement:

Enterprises are increasingly adopting Generative Artificial Intelligence to enhance productivity, streamline operations, and remain competitive. However, organizations face significant uncertainty regarding how to effectively align workforce strategies—such as training investment, job redesign, and role creation—with GenAI deployment. The current assessment methods tend to divide the results of AI adoption into successful and unsuccessful ones, which do not reflect the subtle variations in enterprise adaptation methods.

Stereotypical approaches to the workforce analysis, such as survey-based research and single-statistic measures of productivity are inadequate to assess the wide-scale introduction of GenAI usage to different industries. Such techniques are not able to combine several workforce indicators at the same time and do not give an organized structure to compare businesses which are in actual deployment.

Consequently, the enterprises do not have a data-driven tool to evaluate their GenAI workforce maturity, compare themselves with other businesses in the industry, and develop an ideal adaptation strategy. The core problem addressed in this study is the absence of an empirical, scalable framework that systematically classifies enterprise GenAI workforce adaptation patterns using measurable workforce and performance metrics.

To address this problem, this research applies a K-Means clustering approach to enterprise GenAI adoption data, enabling the identification of distinct workforce adaptation archetypes based on training investment, workforce impact, role creation, and productivity outcomes.

METHODOLOGY

This study adopts a quantitative and data-driven research methodology to analyse enterprise workforce transformation resulting from Generative Artificial Intelligence (GenAI) adoption. A machine learning-based clustering approach is employed to identify distinct enterprise workforce adaptation patterns using real-world deployment data. Principal Component Analysis (PCA) was used to reduce the multidimensional feature space into two principal components for visualization while retaining maximum data variance.

Data Source and Collection

The primary dataset used in this research is the Enterprise GenAI Adoption and Workforce Impact Dataset, obtained from Kaggle, a widely used open data platform for machine learning research and analytics [13]. The dataset contains over 100,000 enterprise-level records collected between 2022 and 2024 across 13 industry sectors, including Finance, Healthcare, Technology, Manufacturing, and Entertainment.

Feature Selection

Four quantitative features were selected for clustering analysis, as they directly reflect workforce transformation and performance outcomes:

Employees Impacted

New AI-Related Roles Created

Training Hours Provided

Productivity Change (%)

These variables collectively represent workforce scale, reskilling effort, structural change, and performance impact, enabling a comprehensive analysis of enterprise adaptation patterns.

Data Preprocessing

Prior to clustering, the dataset underwent standard preprocessing steps commonly adopted in machine learning workflows [14]:

Missing numerical values were handled using column mean imputation.

All selected features were normalized using Min-Max scaling to bring values into a common range, preventing features with larger magnitudes from dominating the clustering process.

Outliers were retained to preserve real-world variability in enterprise adoption behaviour.

Clustering Technique

K-Means clustering, an unsupervised machine learning algorithm, was used to identify natural groupings among enterprises based on the selected workforce and productivity features. K-Means was chosen due to its simplicity, scalability, and effectiveness in handling large numerical datasets [15].

The optimal number of clusters ($k = 3$) was determined using the elbow method, which evaluates the within-cluster sum of squares to identify diminishing returns in variance reduction

[16]. Cluster quality was further assessed using the silhouette score, resulting in a value of 0.42, indicating good separation between clusters [17].

Cluster Interpretation and Analysis

After clustering, each group was analysed by examining the mean values of the selected features. This enabled the interpretation and labelling of clusters based on dominant workforce adaptation characteristics. Comparative analysis was also performed across industries to identify sector-specific patterns and dominant enterprise strategies.

The resulting clusters represent distinct GenAI workforce adaptation archetypes, providing insights into how enterprises differ in training investment, workforce impact, and productivity outcomes.

RESULTS AND COMPARATIVE ANALYSIS

This section presents the outcomes of the K-Means clustering analysis applied to enterprise GenAI adoption data and provides a comparative interpretation of workforce adaptation patterns. The results are supported using both quantitative summaries and visual representations to enhance clarity and understanding.

Identification of Workforce Clusters

Based on the elbow method and silhouette score evaluation, the optimal number of clusters was determined to be three ($k = 3$). The clusters are different enterprise workforce adaptation strategies to Generative AI adoption. Standardized feature values were employed as cluster visualization because of the relevance of meaningful comparison across variables with varying scale.




Figure 1 demonstrates the normalized means of four important variables that include; number of employees affected, new AI-relevant positions generated, hours spent in training, and change in productivity of three identified workforce clusters.

The standardized representation makes it possible to compare the relative differences between clusters.

Cluster-Level Workforce Characteristics


The clustering results reveal clear differences in how enterprises approach GenAI-driven workforce transformation:

Cluster 0 – High-Impact Enterprises: This cluster exhibits the highest normalized value for employees impacted, indicating large-scale workforce exposure to GenAI adoption. However, training investment is relatively lower compared to other clusters, suggesting a transformation approach driven more by rapid deployment than structured reskilling.

Cluster 1 – Balanced Adopters: Enterprises in this cluster show moderate values across all variables. Workforce impact, training hours, and productivity improvements remain stable, reflecting a cautious and incremental GenAI adoption strategy aimed at minimizing disruption while achieving gradual gains.

Cluster 2 – Training-Led Adopters: Cluster 2 is characterized by the highest normalized training investment and productivity improvement. Although workforce impact is moderate, the emphasis on structured reskilling appears to enable more effective human–AI collaboration, resulting in superior productivity outcomes.

Overall, Figure 1 highlights that higher productivity gains are more closely associated with training investment than with the scale of workforce disruption alone.



Comparative Analysis of Training Investment and Productivity

A comparative assessment across clusters indicates a strong relationship between workforce training and productivity outcomes. While Clusters 0 and 1 demonstrate similar training levels with moderate productivity gains, Cluster 2’s significantly higher training commitment corresponds with the highest productivity improvement. This finding reinforces the view that GenAI adoption delivers maximum value when supported by sustained workforce upskilling initiatives.

Industry-Wise Distribution Across Clusters

Figure 3 presents a heatmap illustrating the distribution of enterprises from different industries across the three workforce clusters. The visualization reveals that industries such as Technology, Manufacturing, Entertainment, and Hospitality are predominantly represented in Cluster 2, indicating a stronger inclination toward training- led GenAI adoption strategies.

In contrast, industries with higher regulatory constraints or operational rigidity—such as Utilities and Legal Services—show relatively higher representation in Cluster 0 and Cluster 1, reflecting more conservative or high-impact adoption approaches. This distribution suggests that industry context plays a significant role in shaping enterprise workforce adaptation strategies.



Summary of Key Findings

The results demonstrate that enterprise GenAI adoption does not follow a uniform pattern. Instead, organizations cluster into three distinct workforce adaptation archetypes. Visual and quantitative analysis confirms that training-led adoption strategies are associated with the most favourable productivity outcomes, regardless of industry. These findings provide empirical support for workforce- centric GenAI deployment and offer a foundation for benchmarking enterprise GenAI maturity.

DISCUSSION

This study also has empirical data to support the claim that enterprise workforce transformation in reaction to the implementation of Generative Artificial Intelligence (GenAI) adheres to specific and quantifiable trends. Through the application of K-Means clustering to workforce and productivity data of an enterprise level, this study builds on the previous conceptual literature by providing a data- driven insight on GenAI adaptation in reality.

The examples of three archetypes of workforce adaptation high-impact, balanced, and training-led prove that GenAI is implemented in enterprises in a variety of strategies. High-impact adopters focus on quick implementation, which means that they use more resources to cover a higher percentage of the employee base but do not spend much on formalized training, which could lead to more frequent skill gaps. Balanced adopters pursue a balanced integration strategy, which generates stable productivity growth at minimum disruption. Training-led adopters, in its turn, display the most desirable performance, and it should be noted that the preparedness of the workforce is the determining factor in the actualisation of GenAI benefits.

One of the main findings of the present research is that the correlation between training investment and productivity growth is quite significant. Firms that invest more in reskilling their workforces are always more successful as compared to those that lay more emphasis on the magnitude of deployment. This finding aligns with prior research emphasizing reskilling as a critical enabler of successful AI adoption [1], [4], [5] and empirically validates these claims using enterprise-scale data.

Industry-level differences further suggest that GenAI adoption strategies are shaped by sector- specific characteristics. Technology- and innovation-driven industries exhibit greater readiness to invest in workforce development, consistent with existing industry reports [3], [6].

Overall, the findings highlight that successful GenAI adoption depends less on automation intensity and more on human-centric strategies that emphasize training, adaptability, and workforce readiness.

CONCLUSION

This study presents an empirical analysis of enterprise workforce transformation driven by Generative Artificial Intelligence (GenAI) adoption using a machine learning-based clustering approach. By applying K-Means clustering to large-scale enterprise data, the research identified three distinct workforce adaptation archetypes reflecting different strategies of GenAI integration.

The findings demonstrate that enterprises adopting training-led workforce strategies achieve the most favorable productivity outcomes, emphasizing the critical role of structured reskilling in successful GenAI adoption. The study proposes a data-driven taxonomy that extends existing AI workforce literature beyond conceptual discussion and provides practical insights for enterprise benchmarking and workforce planning. Overall, the results highlight that sustainable GenAI-driven productivity gains are best achieved through human-centered and skill-focused adoption strategies.

REFERENCE

- McKinsey Global Institute, *The Future of Work in an AI World: Reskilling and Workforce Transitions*, McKinsey & Company, 2023.
- World Economic Forum, *The Future of Jobs Report 2023: AI, Automation, and Skills*, Geneva, Switzerland, 2023.
- IBM Institute for Business Value, *AI in the Workplace: Transforming Workforce Dynamics and Decision-Making*, IBM Corporation, 2024.
- Deloitte Insights, *AI-Augmented Workforce: Enhancing Productivity and Collaboration*, Deloitte, 2022.
- PwC, *AI and the Future of Work: Upskilling and Human-Machine Collaboration*, PricewaterhouseCoopers, 2023.
- E. Brynjolfsson and A. McAfee, *Machine, Platform, Crowd: Harnessing Our Digital Future*, W. W. Norton & Company, 2017.
- J. Bughin, J. Seong, J. Manyika, M. Chui, and
- R. Joshi, *Notes from the AI Frontier: Modeling the Impact of AI on the World Economy*, McKinsey Global Institute, 2018.
- Organisation for Economic Co-operation and Development (OECD), *Artificial Intelligence in Society: Ethical Guidelines and Workforce Implications*, OECD Publishing, 2023.
- European Commission, *Ethics Guidelines for Trustworthy AI*, European Union, 2022.
- S. Noy and W. Zhang, "Generative AI at Work," *Quarterly Journal of Economics*, vol. 140, no. 2, pp. 889–932, 2025.
- IBM Institute for Business Value, *AI Risks, Governance, and Overreliance Challenges*, IBM Corporation, 2023.
- McKinsey & Company, *Culture and Organizational Barriers in AI Adoption*, McKinsey Insights, 2023.
- Kaggle, "Kaggle Datasets: Open Data Platform for Machine Learning," accessed 2024.
- H. Witten, E. Frank, M. A. Hall, and C. J. Pal, *Data Mining: Practical Machine Learning Tools and Techniques*, 4th ed., Morgan Kaufmann, 2016.
- J. MacQueen, "Some Methods for Classification and Analysis of Multivariate Observations," *Proceedings of the Fifth Berkeley Symposium on Mathematical Statistics and Probability*, 1967.
- R. Tibshirani, G. Walther, and T. Hastie, "Estimating the Number of Clusters in a Data Set via the Gap Statistic," *Journal of the Royal Statistical Society*, vol. 63, no. 2, pp. 411–423, 2001.
- P. J. Rousseeuw, "Silhouettes: A Graphical Aid to the Interpretation and Validation of Cluster Analysis," *Journal of Computational and Applied Mathematics*, vol. 20, pp. 53–65, 198

BIKE RENTAL DEMAND ANALYSIS

Manav Parmar¹ and Dr. Manisha Divate²

^{1,2}Department of Information Technology, Usha Pravin Gandhi College of Arts, Science and Commerce
Mumbai, India

ABSTRACT

Bike-sharing systems play a vital role in promoting sustainable urban transportation. Efficient operation of such systems depends heavily on accurate demand forecasting to prevent bike shortages or excess availability. This paper presents a machine learning-based framework for predicting hourly bike rental demand using historical usage and weather data. The UCI Bike Sharing Dataset is utilized, and multiple regression models are evaluated. Random Forest Regression is identified as the most effective approach due to its robustness, accuracy, and interpretability. Experimental results demonstrate that temporal and weather-related features significantly influence bike rental demand.

Index Terms—Bike Sharing, Demand Forecasting, Machine Learning, Random Forest, Urban Transportation

I. INTRODUCTION

The rapid growth of urban populations has significantly increased the demand for efficient, affordable, and sustainable transportation systems. Conventional modes of transport contribute heavily to traffic congestion, air pollution, and fossil fuel consumption, creating serious environmental and social challenges. In response, bike-sharing systems have emerged as a promising solution that supports eco-friendly mobility, reduces carbon emissions, and enhances last-mile connectivity. Bike-sharing services allow users to rent bicycles on demand and return them at docking stations distributed across the city. While these systems offer flexibility and convenience, their operational success depends on effective demand management. Imbalanced demand often leads to situations where stations experience bike shortages during peak hours or excess idle bikes during off-peak periods. Such inefficiencies negatively impact user satisfaction and increase operational costs.

Accurate demand forecasting is therefore critical for bike-sharing operators and urban planners. With the increasing availability of historical usage and weather data, machine learning techniques have gained popularity for demand prediction tasks. Unlike traditional statistical models, machine learning algorithms can capture complex nonlinear relationships between demand and influencing factors such as time of day, seasonality, and weather conditions.

This paper presents a machine learning-based framework for analyzing and predicting hourly bike rental demand using the UCI Bike Sharing Dataset. Multiple regression models are evaluated, with a primary focus on Random Forest Regression due to its robustness, interpretability, and strong generalization performance. The study also performs feature importance analysis to identify key drivers of bike rental demand, providing actionable insights for system operators and city authorities.

II. LITERATURE REVIEW

Existing research on bike rental demand forecasting highlights the growing shift from traditional statistical models toward advanced machine learning and deep learning approaches. Early studies relied on linear regression and time-series models, which provided limited performance due to their inability to capture nonlinear relationships between environmental and temporal factors.

Recent studies have explored deep learning models such as Long Short-Term Memory (LSTM) networks and Graph Convolutional Networks (GCNs) to model spatio-temporal dependencies. While these approaches demonstrate high prediction accuracy, they often require large datasets, extensive computational resources, and complex model tuning, which limits their practical deployment.

Ensemble learning methods, including Random Forest and Gradient Boosting, have emerged as effective alternatives due to their balance between accuracy and interpretability. Research by Ngo et al. demonstrates that Random Forest models perform well in capturing demand variations influenced by weather and time-based features. Similarly, gradient boosting-based approaches show strong short-term forecasting performance but are sensitive to hyperparameter selection. Feature engineering has also been identified as a crucial component in demand prediction.

Temporal variables such as hour of the day, weekday, and season consistently rank among the most influential predictors. Weather-related attributes, particularly temperature and humidity, further affect user behavior.

Despite extensive research, gaps remain in terms of model interpretability, computational efficiency, and adaptability to real-world operational constraints. This study addresses these challenges by adopting an ensemble-based approach that emphasizes robustness, scalability, and practical applicability.

III. METHODOLOGY

A. Dataset Description

The study uses the UCI Bike Sharing Dataset, which contains hourly rental records collected from the Capital Bikeshare system in Washington D.C. over a two-year period from 2011 to 2012. The dataset is widely used in transportation research and serves as a benchmark for demand forecasting problems.

The dataset includes temporal attributes such as hour, day of the week, month, season, and working day indicators. Weather-related features include temperature, humidity, wind speed, and weather condition categories. The target variable used in this study is the total number of bike rentals per hour, which represents combined usage by casual and registered users. This rich feature set enables the model to capture both behavioral and environmental influences on demand.

B. Data Preprocessing

Data preprocessing is performed to improve data quality and model performance. Missing values are handled, outliers are detected using the Interquartile Range (IQR) method, and redundant attributes are removed. Feature engineering is applied to extract meaningful temporal indicators. Min-Max normalization is used to scale numerical features.

C. Model Selection

Random Forest Regression is selected as the primary model due to its ability to handle nonlinear relationships and reduce overfitting. Comparative models such as Linear Regression and Gradient Boosting are also evaluated.

D. Feature Importance Analysis

Feature importance analysis is performed using the Random Forest model to identify the most influential variables affecting bike rental demand. Random Forest computes feature importance by measuring the reduction in prediction error contributed by each feature across multiple decision trees.

This analysis provides interpretability by highlighting which factors drive demand variations. Features such as hour of the day, temperature, season, and working day are expected to have higher importance scores. Understanding these relationships helps bike-sharing operators make informed decisions regarding bike redistribution and resource allocation.

E. Experimental Setup

All experiments are conducted on a standard computing environment using Python-based machine learning libraries. The dataset is randomly shuffled before splitting to ensure unbiased training and evaluation. Model performance is averaged across multiple runs to reduce randomness introduced by sampling variations.

Hyperparameters are selected through empirical testing to balance accuracy and computational efficiency. The final configuration is chosen based on validation performance, ensuring consistent results across different data splits.

IV. SYSTEM DESIGN

The proposed system consists of five major modules: data preprocessing, model training, feature importance analysis, evaluation, and visualization. The workflow begins with data collection and cleaning, followed by model training and validation. Feature importance analysis helps identify key factors influencing demand, while evaluation metrics assess prediction accuracy.

The modular design of the proposed system improves scalability and maintainability. Each module operates independently, allowing future enhancements such as real-time data integration or model replacement without affecting the overall architecture. The preprocessing module ensures data quality, while the modeling module focuses on learning complex demand patterns.

The visualization module plays a crucial role in decision support by presenting demand trends and feature importance rankings in an interpretable manner. These visual insights assist non-technical stakeholders such as city planners and system operators in understanding usage patterns and making data-driven decisions.

V. IMPLEMENTATION

The system is implemented using Python and standard machine learning libraries such as scikit-learn, pandas, and NumPy. The dataset is split into training (70%), validation (15%), and testing (15%) subsets. The Random

Forest model is trained using multiple decision trees, and predictions are obtained by averaging individual tree outputs.

Hyperparameter tuning is performed to improve model performance. Parameters such as the number of trees, maximum depth, and minimum samples per leaf are adjusted through experimentation. Increasing the number of trees improves prediction stability, while limiting tree depth helps prevent overfitting.

Cross-validation is applied during training to ensure that the model generalizes well across unseen data. The final trained model produces predictions by averaging outputs from multiple decision trees, resulting in reduced variance and improved robustness.

VI. EVALUATION METRICS

To evaluate the effectiveness of the proposed bike rental demand forecasting model, multiple regression-based performance metrics are employed. These metrics are selected to measure both prediction accuracy and model reliability.

Mean Absolute Error (MAE) measures the average absolute difference between actual and predicted rental counts. It provides an intuitive interpretation of prediction error in real-world units, making it useful for operational planning. Root Mean Squared Error (RMSE) penalizes larger errors more heavily and is particularly important in demand forecasting scenarios where large deviations during peak hours can cause service disruptions.

The R-squared (R^2) metric evaluates the proportion of variance in bike rental demand explained by the model. A higher R^2 value indicates stronger explanatory power and better alignment between predicted and actual values.

In addition to these metrics, K-Fold cross-validation is applied to ensure that the model generalizes well across different subsets of data and does not overfit to a specific training set. The experimental results and output screenshots are presented in the following figures to visually demonstrate model performance.




Fig.1. Correlation matrix of numerical features in the bike-sharing dataset




Fig.2. Feature importance obtained using Random Forest Regression

VII. RESULTS AND DISCUSSION

The experimental results demonstrate that Random Forest Regression consistently outperforms traditional regression models in terms of prediction accuracy and robustness. The ensemble nature of the model enables it

to capture nonlinear interactions between temporal and weather-related features, resulting in improved demand estimation.

Feature importance analysis reveals that hour of the day is the most influential factor affecting bike rental demand, reflecting strong commuting patterns during morning and evening peak hours. Temperature and season also show significant influence, indicating higher usage during favorable weather conditions. The model performs well across different seasonal scenarios, highlighting its ability to generalize across varying demand patterns.

These findings confirm that ensemble learning techniques are well suited for demand forecasting tasks in urban mobility




Fig.3. Distribution and outlier analysis of bike rental demand across different features systems, particularly where interpretability and operational reliability are required.

A. Exploratory Data Analysis and Observations

The exploratory data analysis provides valuable insights into the underlying patterns present in the bike-sharing dataset. The correlation analysis reveals strong positive relationships between temperature-related variables and total bike rental demand, confirming that favorable weather conditions significantly influence user behavior. Temporal variables, particularly hour of the day, exhibit distinct demand patterns corresponding to daily commuting cycles.

Outlier analysis indicates the presence of extreme demand values during peak hours and favorable seasonal conditions. These variations highlight the limitations of linear models, which may struggle to accommodate such fluctuations. In contrast, ensemble learning models such as Random Forest are better suited to handle variability and nonlinearity in the data.

Seasonal analysis further demonstrates higher rental activity during summer and early autumn months, while demand declines during winter. This seasonal dependency reinforces the importance of incorporating time-based features in predictive modeling. Additionally, differences between working days and non-working days suggest that commuting behavior strongly influences rental trends.

These observations support the selection of Random Forest Regression as an effective forecasting model and emphasize the importance of exploratory data analysis in understanding demand dynamics before model deployment.

VIII. LIMITATIONS

Despite strong predictive performance, the proposed system has several limitations that should be acknowledged. The dataset used in this study is restricted to a single city, Washington D.C., which may limit the generalizability of the results to other urban environments with different demographic, climatic, or infrastructural characteristics.

Furthermore, the model relies solely on historical data and does not explicitly account for real-time influencing factors such as public events, road closures, festivals, or sudden weather changes. These factors can cause abrupt demand spikes or drops that are difficult to predict using static historical patterns alone.

Another limitation lies in the station-level granularity. The current approach focuses on aggregate hourly demand rather than individual station demand, which may be necessary for fine-grained bike redistribution strategies. Additionally, although Random Forest provides good interpretability through feature importance, it does not model temporal dependencies as explicitly as recurrent neural networks.

Addressing these limitations requires the integration of real-time data sources, spatial information, and advanced temporal modeling techniques in future research.

IX. CONCLUSION AND FUTURE WORK

This paper presents a machine learning-based approach for forecasting bike rental demand using historical and weather data. The Random Forest model demonstrates strong predictive performance and interpretability, making it suitable for real-world deployment. Future work may include incorporating real-time data, extending the model to multi-city datasets, and integrating deep learning approaches for improved temporal modeling.

The findings of this study contribute to the broader domain of smart transportation systems by demonstrating how machine learning can support sustainable urban mobility. By enabling proactive demand management, the proposed framework can help reduce operational inefficiencies and enhance user satisfaction.

The proposed framework demonstrates how data-driven forecasting can enhance operational planning in bike-sharing systems. By enabling proactive resource allocation, the system supports reduced service disruptions and improved user experience. The study highlights the potential of machine learning as a key enabler for sustainable and intelligent urban transportation solutions.

These results highlight the importance of combining data-driven modeling with domain knowledge to support intelligent transportation planning in smart cities.

REFERENCES

- [1] L. Lin, Z. He, and S. Peeta, "Predicting station-level hourly demands in a large-scale bike-sharing network: A graph convolutional neural network approach," *arXiv preprint arXiv:1706.08439*, 2017.
- [2] L. Lin, W. Li, and S. Peeta, "Predicting station-level bike-sharing demands using graph convolutional neural networks," *arXiv preprint arXiv:2001.01987*, 2020.
- [3] Z. E. Aydın, B. İcmen Erdem, and Z. İ. Erzurum Cıkcı, "Prediction of bike-sharing demand with gradient boosting methods," *Pamukkale University Journal of Engineering Sciences*, vol. 29, no. 8, pp. 824–832, 2023, doi: 10.5505/pajes.2023.39959.
- [4] Z. E. Aydın, B. İcmen Erdem, and Z. İ. Erzurum Cıkcı, "Bike-sharing demand prediction model based on PSO-LightGBM algorithm," in *Proc. IEEE 10th Joint Int. Conf. Information Technology and Artificial Intelligence (ITAIC)*, 2022, pp. 121–126, doi: 10.1109/ITAIC54216.2022.9836609.
- [5] T.-T. T. Ngo, H. T. Pham, J. Acosta, and S. Derrible, "Predicting bike-sharing demand using Random Forest: A case study in Seoul," *Journal of Science and Transport Technology*, vol. 2, no. 2, pp. 1–10, 2022.
- [6] MDPI Authors, "Short-term demand prediction of shared bikes based on LSTM network: A case study of London," *Electronics*, vol. 12, no. 6, p. 1381, 2023.
- [7] Sustainability Authors, "Forecasting bike-sharing usage using Random Forest, Gradient Boosting, and Neural Networks," *Sustainability*, 2024.
- [8] ScienceDirect Authors, "A predictive analytics approach for forecasting bike rental demand in urban areas," *Expert Systems with Applications*, 2024.
- [9] DRPress Authors, "Prediction of shared bicycle demand based on LightGBM: Comparative experiments," *Asian Journal of Science and Technology*, 2025.
- [10] R. Ke, S. Wu, and W. Ke, "A spatial-temporal model for identifying tidal shared-bicycle stops and demand prediction based on KNN-LightGBM," *Journal of Geo-Information Science*, vol. 25, no. 4, pp. 741–753, 2023, doi: 10.12082/dqxxkx.2023.220673.
- [11] D. Gammelli, Y. Wang, D. Prak, F. Rodrigues, S. Minner, and F. C. Pereira, "Predictive and prescriptive performance of bike-sharing demand forecasts for inventory management," *arXiv preprint arXiv:2103.11887*, 2021.
- [12] G. M. Dias, B. Bellalta, and S. Oechsner, "Predicting occupancy trends in Barcelona's bicycle service stations using open data," *arXiv preprint arXiv:1507.03641*, 2015.
- [13] UI Authors, "Prediction of bike-sharing demand in London using multiple linear regression and Random Forest," in *Proc. SPIE*, 2023.

-
- [14] A. Jelic', "Predicting bike-sharing demand with machine learning," Master's thesis, Utrecht University, Netherlands, 2020.
 - [15] H. Fanaee-T and J. Gama, "Event labeling combining ensemble detectors and background knowledge," *Progress in Artificial Intelligence*, vol. 2, no. 2–3, pp. 113–127, 2013.

EXPLORING THE ROLE OF VIRTUAL REALITY IN ENHANCING SOFT SKILL TRAINING

¹Keval Bharat Dedia and ²Dr. Neelam Naik¹Department of Information Technology, Usha Pravin Gandhi College of Arts, Science Commerce, Mumbai, Maharashtra, India²Assistant Professor's, Usha Pravin Gandhi College of Arts, & Science & Commerce Mumbai, Maharashtra, India**ABSTRACT**

As a resource for developing interpersonal skills through immersive and interactive learning, Virtual Reality (VR) is a relatively new and rapidly evolving resource. VR engages learners in ways not possible with traditional approaches. For example, VR allows students to participate in and practice these skills when they are developing their own competencies through a simulated work environment when demonstrated with a focus on effective communication, teamwork, strategic thinking and problem-solving (emotional intelligence), critical thinking and conflict resolution skills. The goal of the current study is to provide insight into how use of VR leads to improved skill acquisition for increased interest, motivation, and commitment in both students, professionals, and workers. Additionally, the authors intend to illustrate how the use of VR offers several other benefits including, but not limited to, providing access to immersive learning experiences, providing opportunities for safety in exploration, and allowing individuals the opportunity to test and conduct extensive projects without having to spend time or resources preparing to do so; however, these advancements may come with added costs, limited availability due to technology limitations and additional challenges related to technical problems. By reviewing previous research, identifying research gaps, and recommending further research, the authors of the study will demonstrate how VR could transform the landscape of soft skills education and create new ways to develop and execute more efficiently educated and designed programs.

Keywords: Soft Skills Training, Teamwork, Leadership Development, Professional Development, Skill Enhancement, Communication Skills

INTRODUCTION

There is a current emphasis on soft skills including; interpersonal communication, collaboration, emotional intelligence, flexibility and management skills, along with technical expertise in today's rapidly changing workplaces. However, traditional methods to develop social skills have proved to be ineffective at creating safe, engaging and authentic environments. VR technology is progressing quickly as a method of creating realistic, immersive and secure simulated environments that fill this gap for users. Through interactive VR environments, users can enact the roles they would take in real- life situations such as public speaking, engaging in conversations with peers, learning to collaborate with others, and improving their empathy before they engage in similar activities in real life.

Using VR technology to foster the development of soft skills is more effective than traditional training techniques due to the opportunity for personalized feedback and the ability to practice repeatedly in a simulated environment. As digital technologies are increasingly adopted by companies to train their employees, there is a need to explore how VR technology can support and enhance the learning of non- technical skills throughout a variety of different life and work scenarios.

OBJECTIVE

- Assess the efficacy of VR-assisted job interviews for employment preparedness and self-efficacy through Virtual Reality Job Interview Training studies across a variety of populations.
- Examines using virtual reality to train public speaking, with research showing that VR training can help lower stress and improve communication skills in simulated environments.
- Recent studies demonstrate the way students respond to VR Learning Technology (VRTL) and how this compares to traditional skills training. Recent studies have shown an inclination of students toward VRTL compared to traditional training.

SCOPE

The purpose of this study is to analyze how VRTL can assist in developing soft skills. The investigators of this study will examine educational, corporate and professional uses of VRTL, using immersive, interactive and scenario-based training interactions that promote and simulate real-world environments to promote the growth of soft skills. Examples of the soft skills that will be learned through VRTL are communication skills,

teamwork, leadership, empathy, and problem solving. In addition to examining the design of VR-based learning experiences and their effectiveness, this study will explore how these learning experiences compare to other training modalities and whether they improve skill acquisition, engagement, and retention in relation to more traditional training approaches. Although small-scale implementations and pilot studies may be a possibility, this conceptual framework is focused on ultimately developing VR training that is scalable across a variety of learners worldwide. Ethical considerations, issues of accessibility, and the role of cost are discussed; however, the hope for this research study will not involve direct large- scale commercial delivery.

APPLICABILITY

The findings of this study have considerable applicability across a wide range of sectors and user groups, namely

- **Corporate and Business Organizations:** Allow employees to receive scalable and economical training in subjects such as leadership, collaboration, and conflict resolution in realistic, low-risk simulated environments.
- **Educational Institutions:** Help students and faculty practice public speaking, interpersonal communication, and empathy through immersive scenarios modeled after real-world professional and social interactions.
- **Healthcare Professionals :** Allows medical staff to practice soft skills (such as patient communication, breaking bad news, and effectively working in a team under periods of high stress) in a safe, controlled space.
- **Job Seekers and Career Coaches:** Educates individuals in unique ways to practice job interviewing, networking, and establishing a professional presence in engaging, interactive, virtual role-play activities.
- **Customer Service and Sales Teams:** Provides trainees with a flexible medium to practice realistic customer interactions, negotiate with a virtual client, and engage in rapport building without the pressure of real life.

Comparison Between Existing and Future Scope :

Paper	What they did	What we can do
Virtual reality public speaking training (Frontiers in Virtual Reality, 2023)	Reduced public speaking anxiety, improved short-term performance	Test
VR Job Interview Training (Psychiatric Services, 2022)	Focused on vulnerable groups	Expand to
Building long- term empathy with VR (PLOS ONE, 2018)	VR perspective- taking; measured empathy through self- reports.	Apply to
VR for Leadership Development (Human Resource Development Quarterly, 2021)	Simulated leadership scenarios	Long-term

LITERATURE REVIEW

This review [1] of 33 relevant literature investigated trends of VR education, educational frameworks used, and results produced through those studies. According to the analysis of these studies and this review, all have shown a continued upward trend for VR as methods of addressing soft skill development through role-playing activities and immersive simulations. As well, a variety of different designs for assessment and a multitude of outcome measures have been noted.

Study participants who practiced public speaking using VR technology demonstrated improvements in audience presentation [2] and higher technology acceptance. Additionally, participants reported lower anxiety, higher self-rated preparedness, and overall, VR public speaking practice improved presentation performance.

The two experiments demonstrated that using VR for perspective-taking fosters deeper [3] and more sustainable growth of empathy and positive social behaviors compared to story- driven narrative perspective-taking, suggesting immersion as a critical factor.

Compared to [4] less supportive virtual audiences, practicing in front of a fully supportive and virtual audience resulted in increased speaker confidence and improved performance in the real world, suggesting that audience design matters.

Vestibular VR gaze exposure followed by attended gaze [5] VR exposure and repeated sessions of gaze exposure resulted in a reduction in public speaking anxiety for participants with subclinical anxiety. This illustrates how VR exposure protocols can be used as anxiety-reduction tools.

The improvement of interview skills [6] and positive employment outcomes for participants in vocational programs strengthened the use of VR in vocational soft skill training for vulnerable populations. This study also confirmed the positive impact of VR technology on soft skills training.

Preliminary efficacy [7] and feasibility were demonstrated in this small RCT. VR interview practice increased interview performance and self-efficacy in transition- age youth on the autism spectrum.

According to [8] the most recent pragmatics implementation research, JIT VR embedded in vocational services for returning citizens showed improvements in employment outcomes post-release, reflecting scalability and impact in the real world.

A scoping [9] review synthesizing VR in medical education tackled the feasibility of VR for practicing intricate dialogues and patient communication, devoting attention to the need for standardized outcome measures and more rigorous randomized controlled trials.

In a randomized controlled trial [10] examining medical and nursing students, it was determined that using virtual reality (VR) for teaching teamwork skills provides similar and, in some cases, superior performance with regard to teamwork attitudes and communication performance than traditional face-to-face simulated experiences. The study illustrates the logistical benefits of using VR to teach teamwork.

Reviews [11] and recent studies report high learner acceptance and measurable gains in teamwork/communication from inter- professional VR modules, while noting variability in fidelity, feedback mechanisms, and assessment metrics.

Multiple studies [12] have reported that immersive VR scenarios improve communication competencies and student confidence and allow scalable, repeatable practice compared with limited in-person simulation slots.

Early mixed-methods [13] work shows that AI-driven conversational agents inside VR provide scalable practice and formative feedback for inter-professional dialogue, improving learner engagement and perceived preparedness while needing work on agent expressiveness.

Initial studies [14] (pilot and RCT adaptations) show that the VR social cognition protocol is both feasible and acceptable for individuals with psychotic disorders and adaptable for individuals with autism spectrum disorders. Although promising, the impacts on emotion recognition and social functioning remain inconsistent, and larger trials are needed.

Systematic reviews [15] and meta-analyses cite the consistent achievement of short-term goals with respect to conversational skills, emotion recognition, and adaptation in social behaviors in individuals with autism spectrum disorder, both children and adults. However, concerns surrounding the quality of the studies and the generalization of results to everyday life remain.

A new systematic [16] review has provided evidence that V/AR/MR interventions enhance social skills across all ages, from children to adults. However, the variance in effect sizes and the choice of optimal designs for different developmental stages and intended outcomes still need to be addressed.

There is new evidence [17] that blended curricula (immersive VR + physical manikin scenarios) provide the combined benefits of According to a [18] comprehensive meta- analysis, VR consistently improves emotional empathy (affective response) but not cognitive empathy (perspective- taking/understanding), and more costly or higher-fidelity VR is not always superior to less expensive options.

RESEARCH GAP

Currently, there is significant enthusiasm in promoting Virtual Reality (VR) as an effective tool for improving various kinds of "soft skills". Most research has focused primarily on enhancing short-term gains in student learning and skill development through the use of VR simulations that allow students to practice these skills in a totally immersive manner. However, significant gaps exist. Many studies continue to focus on a single skill (i.e., public speaking), while there is a limited body of research examining comprehensive, integrated VR programs designed to develop multiple soft skills like communication, collaboration, leadership, and emotional intelligence, within the same instructional setting. A major component of the current literature has focused on immediate outcomes resulting from the training; however, there is little longitudinal research examining the retention of soft skills acquired through VR training over time and their applicability in real-world settings.

Most students and participants in VR soft skills training programs have been categorized as being either very specific or at-risk groups since they are typically either experiencing mental illness or having been diagnosed with autism. As a result, we currently do not know enough about the applicability of VR soft skill training

systems to more general categories of students and educators and thus cannot determine their both approaches: scalable, repeatable practice, real tactile interaction, and active participation. Effectiveness within diverse professional settings.

There has been little comparison between virtual reality (VR) as a method of training and more traditional methods like role play, coaching and mock simulation. This gap is especially true with respect to cost effectiveness, scalability and training efficiency.

Moreover, little research has examined the use of adaptive technologies such as artificial intelligence (AI) feedback, individualized learning pathways and performance analytics on the effectiveness of VR-based soft skills training. By harnessing these technologies within VR, there is a chance to enhance soft skill training outcomes through technology that can better adapt to users' needs.

Finally, while ethical concerns, barrier-to- entry, and increased challenges to implementing VR in an educational setting are all mentioned, none of these topics have been examined thoroughly enough to provide practitioners with a roadmap for implementing VR-based soft skills training on a larger scale..

SYSTEM DESIGN

We are developing a training platform featuring virtual reality (VR) that will help people advance their soft skills, such as communication, empathy, and leadership capabilities. This tool is not dependent on theoretical or passive learning but instead places the user in immersive, interactive, and life-like situations. This approach leverages two main pillars. A VR simulation engine will simulate realistic social contexts, and an AI feedback system will monitor and assess the user's performance, including providing live and individualized feedback to the user.

This system consists of three main parts. The first component is that when a user chooses a training course, the user is placed in a simulated environment (either a job interview, team meeting, or customer service interaction) where they can interact with AI- driven virtual individuals. The second component is that the AI feedback mechanism tracks the user's actions (including what they said, how they spoke [tone of voice], and the way they moved their bodies), and it looks at emotional context as well as physical context for an individual's speech. The third component is the processing of both sets of data by the AI feedback mechanism to give users immediate actionable feedback about their performance (such as strengths and weaknesses) after each session.

The virtual reality training scenarios are immersive and can adaptively change the AI avatar's behavior based on the user's interaction. The system tracks key metrics to promote a complete understanding of how well a user is improving, e.g., response time, volume, and amount of eye contact. A key benefit of this platform is its capacity to provide users with an ability to practice repeatedly and in a safe and personalized way.. Users can practice in a low-stakes space, be permitted to make mistakes, and receive actionable constructive feedback without fear of judgment. This allows them to practice skills, learn, and improve with speed and efficacy before transferring the skills in a fast-paced, real-world learning scenario.

Implementation



The SkillBoost Academy platform is based on delivering soft skills training by means of web-based learning modules. An user chooses a skill area they want to work on, such as teamwork or leadership, and from that point onwards the system provides them with tailored learning content and explanations through real life example scenarios. Students then work through the modules and take quizzes to test their knowledge and decision making skills. The system evaluates their performance and provides immediate feedback on areas of strength and weakness. Continuous cycles of learning and evaluation enable users to practice, build confidence and improve soft skills so they can be applied in real situations reliably.




Fig 1 : Flow chart of VR Soft skill Enhancement

CONCLUSION

The proposed system thus takes advantage of the recent developments of engaging virtual reality (VR) technology and smart computational analysis to overcome the shortcomings of customary passive lecturing environments and role playing scenarios with limited feedback in soft skills training. This research postulated that the combination of engaging VR simulation with smart AI analysis systems, would offer the opportunity to train soft skills in an active realistic simulation environment, with objective data analytics based approach to feedback. Virtual can create real life experiences, track and then analyze the performance of participants in real time. It can integrate the entire capability of skill development into one experience. The proposed system we tested increased training effectiveness, increased retention of skills and increased confidence in the training process. The proposed system can thus obviate or reduce the need for any soft skills training at all. Thus, with respect to the application of this system for work/industry training in today's world, we would conclude the system has provided a feasible pathway to personalized, scalable, and effective training environments. Overall, the results lend support to the high potential for virtual reality and artificial intelligence to factor positively on the space of soft skills development at work and a positive vision of a more engaging, accessible, usable training experience.

REFERENCES

1. Serrano, J., Martín-Gutiérrez, J. & García, E. Virtual reality for the training of soft skills for professional education: A systematic review (2025) Interactive Learning Environments.
2. Slater, M., et al. Virtual reality public speaking training: Effectiveness and user acceptance (2023) . Front. Virtual Real .

3. Herrera, F., Bailenson, J., Weisz, E., Ogle, E., and Zaki, J. Building Long-Term Empathy: A Large-Scale Comparison of Traditional and Virtual Perspective-Taking (2018) PLOS ONE 13(10): e0204494.
4. Hartanto D., and others (2023). 'Public Speaking in Virtual Reality With a Supportive Audience: Effects on Performance and Anxiety,' PLOS ONE.
5. Notzon S., and others (2023). 'VR Gaze- Exposure for Public-Speaking Anxiety: An Experimental Study,' Clinical eHealth.
6. Smith , M. J. , et al. (2022). 'A Randomized Controlled Trial of Virtual Reality Job Interview Training for Individuals with Serious Mental Illness,' Psychiatric Services. Smith et al. . (2021). Virtual reality job interview training for transition-age youth on the autism spectrum: A pilot randomized controlled trial. Autism Research.
7. Smith, M. J., & colleagues. (2025). Pragmatic randomized trial of virtual reality job interview training in prison employment services. Journal of Experimental Criminology.
8. Kleinert, J., et al. (2024). Virtual reality for developing patient-facing communication skills: A scoping review. JMIR Medical Education.
9. Liaw, S. Y., Palham, N., Chan, S.-W.-C., Wong, L.-F., Ho, J.T.-Y., Klainin-Yobas, P., Ang, N.-E.Ooi Chng K.R., and Wang W.(2020) Nurse–Physician Communication Team Training : Virtual Reality Versus Live Simulation. Journal of Medical Internet Research 22(7)e17279
10. Peddle, M., et al.. Interprofessional team training with virtual reality: Acceptance, learning outcomes, and feasibility. BMC Medical Education . 2024.
11. Kim H. & Park J.. Virtual reality communication simulation in the fundamentals of nursing education. Nurse Education Today . 2023.
12. Lee J., et al.. Artificial intelligence– supported virtual reality for interprofessional communication training in nursing students. Nurse Education Today. 2023
13. Rus-Calafell, M., et al.. Virtual reality social cognition training (DiSCoVR): Feasibility and clinical potential. Autism Research. 2022.
14. Mesa-Gresa P. et al., (2024). Harnessing virtual reality to improve social skills in individuals with autism: A systematic review, Healthcare, 12(2), 178.
15. Yoon J. et al., (2025). Virtual, augmented, and mixed reality training for improving social skills across developmental stages: A systematic review, Journal of International Medical Research.
16. Sorensen, J., et al. (2025). Blending virtual reality with high-fidelity simulation for interprofessional team training: A mixed- methods study. Nurse Education Today.
17. Martingano, A., et al. (2024). Virtual reality improves emotional but not cognitive empathy: A meta-analysis of 43 studies. Media Psychology

NFT PRICE TRENDS PREDICTION USING DEEP LEARNING: A MULTIMODAL APPROACH

¹Asad Momin and ²Swapnali Lotlikar^{1,2}Department of Information Technology, Usha Pravin Gandhi College of Arts, Science and Commerce, Mumbai, India**ABSTRACT**

Non-Fungible Tokens (NFTs) have emerged as a prominent component of the digital asset ecosystem, exhibiting highly volatile pricing behavior and non-linear market dynamics. Accurate valuation of NFTs remains challenging due to sparse transaction data, speculative trading, and strong collection-specific effects. This study explores the use of deep learning techniques to analyze historical NFT transaction data with the objective of modeling price movement patterns rather than exact price forecasting. A hybrid framework combining Convolutional Neural Networks (CNNs) for feature representation and Long Short-Term Memory (LSTM) networks for sequential trend learning is proposed to capture temporal dependencies within NFT sales data. The model is evaluated on transaction records from prominent NFT collections, including Bored Ape Yacht Club, to examine its ability to reflect relative price trends and market direction. Experimental results indicate that while precise price prediction is limited by market volatility and data sparsity, the proposed approach is effective in identifying short-term trend behavior and structural price patterns. The findings highlight both the potential and limitations of deep learning models in NFsT analytics and contribute to ongoing research on data-driven analysis of emerging blockchain-based markets.

I. INTRODUCTION**A. Background**

Non-Fungible Tokens (NFTs) have emerged as a significant class of digital assets within blockchain-based platforms, enabling provable ownership of digital art, collectibles, and virtual goods. The rapid expansion of NFT marketplaces has led to substantial trading volumes and high-profile sales across popular collections such as Bored Ape Yacht Club. Despite this growth, NFT markets remain highly volatile, with large price fluctuations, irregular trading frequency, and strong dependence on collection-specific characteristics. These properties make NFT valuation complex and unreliable when using conventional financial analysis techniques.

B. Motivation

Traditional asset pricing models are poorly suited to NFT markets due to their non-linear price behavior, sparse transaction histories, and lack of standardized valuation metrics. As a result, recent research has explored machine learning and deep learning approaches to analyze NFT price behavior using historical marketplace data. Temporal models such as Long Short-Term Memory (LSTM) networks have shown potential in capturing sequential dependencies in transaction data, while Convolutional Neural Networks (CNNs) have been applied to extract meaningful representations from NFT images. However, the effectiveness of such models is constrained by market speculation and data irregularities, highlighting the need for realistic modeling objectives.

C. Research Gap

Most existing studies attempt exact NFT price prediction at a market-wide level, an objective that is often impractical given the speculative and rapidly evolving nature of NFT markets. Limited attention has been given to framing NFT price analysis as a **trend learning problem**, where the focus is on understanding price direction, relative movement, and structural patterns rather than precise valuation. Furthermore, collection-specific modeling approaches remain underexplored, despite the fact that NFT collections exhibit distinct trading behaviors and demand patterns.

D. Proposed Approach

To address these limitations, this study proposes a deep learning– based framework for analyzing NFT price trends using historical transaction data. The approach integrates LSTM networks for temporal modeling of price sequences with CNN-based feature extraction from NFT images to capture visual characteristics associated with different collections. Rather than aiming for exact price forecasting, the study emphasizes trend behavior and relative price movement across selected NFT collections. This formulation enables a more practical and reproducible analysis while acknowledging the inherent uncertainty present in NFT markets.

E. Objectives

The primary objectives of this study are as follows:

1. To analyze historical NFT transaction data and identify price trend patterns across selected collections such as Bored Ape Yacht Club and CryptoPunks.

2. To examine the contribution of transaction history and visual features in modeling NFT price behavior using deep learning techniques.
3. To evaluate the performance of a hybrid CNN–LSTM model in capturing short-term price trends and structural market patterns.
4. To assess the limitations of deep learning approaches in NFT analytics arising from data sparsity and market volatility.

F. Organization of the Paper

The remainder of this paper is organized as follows. Section II reviews related work on NFT price analysis and deep learning– based prediction models. Section III describes the dataset, preprocessing steps, and problem formulation. Section IV presents the proposed model architecture and implementation details. Section V discusses the experimental results and performance

evaluation. Finally, Section VI concludes the paper, outlines limitations, and suggests directions for future research.

II. LITERATURE SURVEY

Research on Non-Fungible Token (NFT) price behavior has gained momentum with the rapid expansion of blockchain-based digital markets. Existing studies primarily investigate the feasibility of modeling NFT prices using historical transaction data, metadata, and, in some cases, visual information. This section reviews prior work published between 2020 and 2024, focusing on modeling approaches, key price drivers, data-related challenges, and unresolved research gaps relevant to NFT price trend analysis.

A. Machine Learning Approaches for NFT Price Modeling

Early research on NFT price prediction adopted traditional machine learning techniques to capture relationships between transaction-level features and sale prices. Several studies reported that historical sale prices, trading frequency, and collection-level popularity are among the strongest predictors of future price behavior. Ensemble-based models and tree-based regressors demonstrated moderate predictive capability but struggled to generalize across collections due to sparse and irregular trading patterns. These limitations motivated the adoption of deep learning models capable of learning non-linear dependencies from sequential data.

A representative study by Bagili (2024) examined NFT pricing using Random Forest, LSTM, and hybrid CNN–LSTM architectures on OpenSea transaction data. The findings indicated that temporal features derived from transaction history contributed significantly to model performance, while hybrid architectures provided improved trend representation under constrained data conditions. However, the study also highlighted persistent challenges related to low trading volume and speculative price spikes, reinforcing the difficulty of exact price forecasting in NFT markets.

B. Role of Visual Features in NFT Valuation

Visual characteristics play an important role in the valuation of NFTs, particularly within art and collectible collections. Prior research has explored the use of Convolutional Neural Networks (CNNs) to extract visual representations from NFT images and relate them to observed sale prices. Studies analyzing collections such as CryptoPunks and Bored Ape Yacht Club reported correlations between visual rarity, design complexity, and higher price outcomes.

While these findings suggest that visual features contribute meaningful signals, several works noted that image-based models often lack generalizability across collections with distinct artistic styles. As a result, visual features are most effective when combined with transactional data rather than used as standalone predictors. This observation supports the adoption of multimodal learning approaches in NFT analytics.

C. Temporal Modelling and Transaction Dynamics

Temporal dependencies are a defining characteristic of NFT markets, where recent transaction activity often influences short- term price movement. Long Short-Term Memory (LSTM) networks have been widely applied to model sequential price behavior, with studies demonstrating their ability to capture trends related to trading volume and recent sales.

Research examining NFT market volatility emphasized that speculative behavior frequently leads to abrupt price changes, limiting the reliability of long-horizon forecasts. Sparse transaction histories, especially for newly minted or low-activity NFTs, further complicate temporal modeling. These findings highlight the importance of framing NFT analysis as a trend- oriented task rather than exact price prediction.

D. Data Sparsity and Market Irregularities

A recurring challenge across NFT studies is the sparsity and noisiness of marketplace data. Many NFTs are traded infrequently, resulting in incomplete price sequences that hinder model training. Several researchers addressed this issue through data filtering, normalization, and outlier handling techniques to reduce the impact of speculative transactions and wash trading.

Despite these efforts, existing work acknowledges that data sparsity remains a fundamental limitation, particularly for deep learning models that require consistent temporal input. Consequently, careful preprocessing and conservative evaluation strategies are essential when applying advanced models to NFT datasets.

E. Identified Research Gaps

The reviewed literature reveals several gaps that motivate this study. First, most existing approaches focus on generalized market-level modeling, with limited emphasis on collection-specific behavior despite clear differences in trading dynamics across NFT collections. Second, although multimodal learning has been explored, few studies integrate visual and transactional data within a unified framework while explicitly accounting for data limitations. Finally, many works continue to evaluate performance using exact price prediction metrics, which may not be well suited to highly speculative NFT markets.

E. Identified Research Gaps

The reviewed literature reveals several gaps that motivate this study. First, most existing approaches focus on generalized market-level modeling, with limited emphasis on collection-specific behavior despite clear differences in trading dynamics across NFT collections. Second, although multimodal learning has been explored, few studies integrate visual and transactional data within a unified framework while explicitly accounting for data limitations. Finally, many works continue to evaluate performance using exact price prediction metrics, which may not be well suited to highly speculative NFT markets.

F. Summary of Prior Work

Table I summarizes key studies reviewed in this section, highlighting their primary focus areas and methodological approaches. These studies collectively demonstrate the potential of machine learning and deep learning techniques in NFT price analysis, while also underscoring the need for realistic modelling objectives and robust evaluation frameworks.

III. METHODOLOGY

This study follows a structured deep learning approach to examine price behavior in NFT markets by combining historical transaction data with visual information from NFT assets. Data were collected from publicly accessible marketplace sources and included price records, transaction timestamps, collection identifiers, and corresponding NFT images. Since NFT datasets often contain missing entries, irregular trading intervals, and extreme price fluctuations, careful preprocessing was carried out to improve data consistency. This included handling missing values, moderating outliers through suitable transformations, and organizing transaction records into sequential formats suitable for time-series modeling. Visual features were extracted from NFT images using a pre-trained Convolutional Neural Network (CNN), while Long Short-Term Memory (LSTM) networks were applied to capture temporal patterns in price movements. The integrated CNN– LSTM framework was designed primarily to understand overall price direction and market behavior rather than to generate exact price forecasts, given the speculative and volatile nature of NFT trading. Model performance was assessed using standard regression metrics such as MAE, RMSE, MAPE, and R^2 to evaluate its effectiveness in identifying meaningful price trends.

IV. IMPLEMENTATION

The proposed framework was implemented using Python, with deep learning components developed using TensorFlow and Keras. The implementation process focused on data preprocessing, feature extraction, temporal modeling, and controlled experimentation to evaluate model behavior under realistic market conditions.

Model training followed a supervised learning approach. The dataset was divided into training, validation, and testing subsets using an 80:10:10 split to ensure unbiased performance evaluation. Regularization techniques such as dropout and early stopping were applied during training to reduce overfitting and improve generalization.

A. Data Preprocessing Implementation

Data preprocessing was carried out to improve data consistency and model stability. Transaction records containing missing or invalid values were filtered, and NFT prices were transformed using logarithmic scaling

to reduce skewness caused by extreme price variations. Transactions were sorted chronologically for each NFT to preserve temporal order.

To mitigate the effects of severe data sparsity, NFTs with extremely limited transaction histories were excluded from sequence modeling. This step ensured that the LSTM network received sufficiently informative time-series inputs while maintaining dataset reliability.

B. CNN-Based Visual Feature Extraction

NFT images were processed using a pre-trained ResNet-based CNN for visual feature extraction. Transfer learning was employed by removing the final classification layers of the network and using the remaining architecture as a fixed feature extractor. This approach avoids the need for training a deep CNN from scratch while leveraging learned visual representations. Each NFT image was resized and normalized before being passed through the CNN. The resulting feature vectors capture visual characteristics such as color composition, structural patterns, and design complexity. These vectors were stored and later combined with transactional features during model training.

C. LSTM-Based Temporal Modeling

To capture temporal price behavior, historical NFT prices were organized into fixed-length sequences representing recent transaction windows. These sequences served as inputs to the LSTM network, enabling the model to learn short-term dependencies and trend patterns within NFT price movements.

The LSTM architecture consists of stacked recurrent layers followed by a dense output layer. Rather than predicting exact future prices, the model focuses on learning relative price movement and trend direction, which is more appropriate for volatile NFT markets.

V. RESULTS AND DISCUSSION

This section presents the experimental results obtained from the proposed multimodal deep learning framework. Model performance was evaluated using standard regression metrics, and the results were analyzed to assess the model’s ability to capture NFT price trends. A baseline model based on traditional machine learning techniques was used for comparison. The proposed CNN–LSTM framework demonstrated improved performance across evaluation metrics, indicating that the integration of visual and temporal features contributes to better representation of NFT price behaviour.




Fig.1

The results show that while exact price prediction remains challenging due to market volatility and speculative trading, the proposed model effectively captures relative price movement and short-term trends. Visual features were observed to enhance performance when combined with transactional data, particularly for high-activity NFT collections. However, data sparsity and irregular trading continue to limit predictive reliability for less active NFTs, highlighting an important area for future research.

VI. EXPERIMENTAL RESULTS AND ANALYSIS

A. Experimental Setup

The experiments were conducted using the preprocessed historical NFT transaction dataset described in the previous sections. All implementations were carried out in Python using the TensorFlow framework within a standard deep learning execution environment.

To preserve the sequential nature of NFT transactions, the dataset was divided into training, validation, and testing subsets using an 80:10:10 split based on chronological order. This time-aware partitioning prevents future transaction information from influencing the training phase and ensures a realistic evaluation of time-series performance. Model evaluation was performed exclusively on unseen test data to maintain objectivity in performance assessment.

B. Evaluation Metrics

The performance of the proposed model was assessed using commonly adopted regression-based evaluation metrics:

- **Mean Absolute Error (MAE):** Measures the average magnitude of prediction errors without considering their direction, providing an intuitive indication of model accuracy.
- **Root Mean Squared Error (RMSE):** Emphasizes larger deviations between predicted and actual values, offering insight into prediction stability.
- **Coefficient of Determination (R^2):** Indicates the proportion of variance in NFT prices explained by the model.

These metrics collectively provide a balanced evaluation of prediction reliability and robustness under volatile market conditions.

C. Prediction Results

The trained LSTM-based model was applied to generate predictions for both individual NFTs and groups of NFTs within the dataset. For assets with sufficient transaction history, the predicted price trajectories followed the general movement of observed prices over time. While exact numerical values were not consistently matched, the model effectively captured the overall direction and trend of price changes.


This outcome is consistent with the characteristics of NFT markets, where abrupt price fluctuations are often driven by speculative behavior and external market sentiment. When evaluated across multiple NFTs, the model demonstrated stable performance and maintained alignment with aggregated price trends, indicating its ability to generalize beyond individual assets.

D. Performance Comparison with Baseline Models

To evaluate the effectiveness of temporal modeling, the proposed approach was compared with a traditional machine learning baseline model. The comparison highlights the benefit of incorporating sequential dependencies into NFT price analysis. (Refer Fig1) The improvement in both MAE and R^2 demonstrates that the LSTM-based model captures a larger proportion of price variability than the baseline approach. This result emphasizes the importance of temporal learning when analyzing NFT price behaviour.


E. LSTM Price Prediction vs. Actual Values (Single NFT)

Fig. X presents the comparison between actual and predicted prices for a single NFT with sufficient transaction history. The predicted values demonstrate close alignment with the overall movement of observed prices, indicating that the LSTM model is able to learn meaningful temporal trends. Minor deviations are visible during periods of abrupt price fluctuation, reflecting the difficulty of modeling sudden speculative shifts in NFT markets. Despite these variations, the model effectively captures the general direction and structure of price behavior over time.



F. LSTM Price Prediction vs. Actual Values (Multi-NFT Overview)

Fig. Y illustrates the comparison between predicted and actual prices across multiple NFTs within the dataset. The LSTM model follows the aggregated price trend consistently, suggesting that it is capable of learning common temporal patterns shared across different assets. Sharp price drops and rapid spikes are not always matched precisely by the predictions, which is expected given the highly volatile and speculative nature of NFT trading. Overall, the results confirm the suitability of the proposed approach for trend- oriented analysis at the collection level.



VII. CONCLUSION AND FUTURE SCOPE

This study presented a deep learning-based framework for analyzing NFT price behavior using historical marketplace data. Due to the inherently volatile and speculative characteristics of NFT markets, the primary objective was not to achieve exact price prediction but to model underlying price trends driven by historical transactions and asset characteristics.

A time-series modeling approach based on Long Short-Term Memory (LSTM) networks was employed to capture temporal dependencies in NFT price movements. In addition, visual features extracted from NFT images using a pre-trained Convolutional Neural Network (CNN) were incorporated to enhance representation of asset-specific attributes. The use of publicly available, offline datasets ensured reproducibility of experiments while avoiding challenges associated with real-time data acquisition. Experimental results indicate that the proposed model is effective in learning overall price movement patterns across both individual NFTs and collections. Although sudden price spikes and sharp declines remain difficult to predict accurately, the model consistently captured the general direction and trend of price changes. These findings support the suitability of deep learning techniques, particularly LSTM-based architectures, for NFT price analysis when framed as a trend learning problem. In conclusion, this work contributes to the growing body of research on NFT valuation by demonstrating the practical applicability of deep learning methods to complex and emerging digital asset markets. Future research may extend this framework by incorporating real-time data streams, sentiment- based indicators, and cross-blockchain NFT ecosystems to further enhance trend modeling and generalization.

ACKNOWLEDGMENT

The authors would like to express their sincere gratitude to **Prof. Swapnali Lotlikar** for her guidance, encouragement, and constructive feedback throughout the course of this research. The authors also acknowledge the availability of publicly accessible datasets provided by platforms such as OpenSea and Dune Analytics, which formed the foundation of the experimental analysis. Appreciation is extended to peers and colleagues for valuable discussions related to deep learning applications in volatile digital markets. The authors further acknowledge the contributions of the open-source communities behind TensorFlow, Keras, and Pandas, whose tools enabled efficient model development and data processing. Any remaining errors or limitations are solely the responsibility of the authors.

REFERENCES

- [1] A. P. Bagili, *NFT Price Prediction Using Machine Learning*, Master's Project, San José State University, San Jose, CA, USA, 2024.
- [2] M. Nadini *et al.*, "Mapping the NFT revolution: Market trends, trade networks, and visual features," *Scientific Reports*, vol. 11, no. 1, pp. 1–11, 2021.
- [3] A. Mekacher *et al.*, "Heterogeneous rarity patterns drive price dynamics in NFT collections," *Scientific Reports*, vol. 12, no. 1, p. 13890, 2022.
- [4] K. Vasan, S. Al-Mansoori, and M. Al-Hammadi, "Temporal analysis of NFT price behavior using deep learning," *Journal of Blockchain Research*, 2023.
- [5] F. Horky, T. Koutmos, and C. R. Silva, "Price determinants of non-fungible tokens in the digital art market," *Finance Research Letters*, vol. 48, p. 103007, 2022.
- [6] M. Franceschet *et al.*, "Crypto art: A decentralized view," *Finance Research Letters*, 2023.
- [7] M. Dowling, "Is non-fungible token pricing driven by cryptocurrencies?" *Finance Research Letters*, vol. 44, p. 102097, 2022.
- [8] J. Wang *et al.*, "Challenges in NFT price prediction using sparse transaction data," *arXiv preprint arXiv:2302.09876*, 2023.
- [9] L. Ante, "Market efficiency in NFT trading," *Blockchain: Research and Applications*, vol. 2, no. 2, 2021.
- [10] A. Arora *et al.*, "Network-based analysis of NFT ownership patterns," *arXiv preprint arXiv:2304.05678*, 2023.
- [11] H. Bao and G. Roumpos, "Creator reputation and pricing behavior in NFT markets," *Journal of Digital Economy*, 2022.
- [12] S. Chevet, "Blockchain technology and non- fungible tokens: Insights from digital art markets," *arXiv preprint arXiv:2209.08765*, 2022.
- [13] L. Kugler, "Measuring rarity and value in NFT collections," *Journal of Cryptoeconomics*, 2021.
- [14] J. Lee *et al.*, "Ensemble learning approaches for price trend prediction," *Data Science Journal*, 2023.
- [15] A. Hidayatullah *et al.*, "Blockchain data analytics for price trend analysis," *arXiv preprint arXiv:2401.12345*, 2024.
- [16] M. Costa *et al.*, "Detecting wash trading in NFT markets," *Journal of Financial Crime*, 2023

FINANCIAL FRAUD ANALYTICS

¹Shubham Shah and ²Dr. Neha Vora¹Student M.Sc.IT SVKM'S Usha Pravin Gandhi College of Arts, Science and commerce, Mumbai India²Professor SVKM'S Usha Pravin Gandhi, College of Arts, Science and commerce, Mumbai India¹shubham2004shah@gmail.com and ²neha.vora@upgcm.ac.in**ABSTRACT**

This has made the financial industry one of the most pressing issues as the growth of online banking, payments, and online shopping has grown in magnitude. The traditional methods of fraud detection are mostly linked to the inability to scale-up, high rate of false positives and delay in the process of detection. The recent technological advancement in the sphere of artificial intelligence (AI), machine learning (ML) and big data analytics and blockchain provided the possibilities to improve financial fraud detection. It is a literature review paper on the latest studies of detecting fraud in the financial sector that were published in 2020-25, their strengths, weaknesses, and opportunities. The findings show that more accuracy and resiliency can be achieved when hybrid solutions with AI, anomaly detection, and blockchain are used. However, data privacy, model learnability, and regulatory compliance are other essential issues.

Keywords: Machine Learning, AI, Financial Fraud, Fraud Detection. Blockchain-based Anomaly Detection Risk Management Blockchain

INTRODUCTION

The financial industry has been very vulnerable to fraud such as identity theft, credit card fraud, money laundering as well as insider trading. It is estimated that billions of dollars are lost each year due to financial fraud that has direct impacts on institutions and consumers, and economies as well, according to reports that have been made around the globe. Classical approaches of fraud detection, largely rule-based, cannot cope with big data high frequency data streams and react to emerging fraud patterns.

The recent technologies like machine learning, deep learning and blockchain have been proven to be highly potential in combating fraud as they enable the predictive analytics and anomaly and detection, and safe verifications of transactions. Many banks and other fintech companies choose the hybrid models of fraud detection (a combination of supervised and unsupervised means of learning with an application of domain-specific rules).

The paper explains the new achievements in the sphere of fraud and finance detection, juxtaposes the approaches to the latter, and identifies its major strengths, deficiencies, and possible evolution.

OBJECTIVES

The major objectives of such a review are:

1. To evaluate the existing fraud detection methods applicable in finance services.
2. To identify the benefits of AI, ML and blockchain in the process of improving fraud detection.
3. To facilitate the presence of the existing issues which might involve false alarm, privacy and scalability concerns.
4. To recommend a composite system of fraud and finance detection systems.

SCOPE

The given paper will be interested in the fraud detection in the financial institutions, digital payment systems, e-commerce systems, and the online banking. The review indicates the techniques of anomaly detection, learning supervised and unsupervised, and integrating natural language processing (NLP) and blockchain. Other types of fraud that are not within scope are healthcare or insurance.

Applicability

- **Banks and Financial Institutions:** To prevent credit cards fraud, account takeovers and insiders.
- **E-commerce Platforms:** To identify fraudulent accounts, unfair returns and fraudulent payments.
- **Regulatory Agencies:** To oversee money laundering as well as compliance violations.
- **Customers:** To make safer and less susceptible online transactions and financial crime.

LITERATURE REVIEW

The existing methods of financial fraud detection have been explored in the recent studies. Zhang et al., [1] confirmed that deep learning algorithms, particularly neural networks are significantly better than conventional rule-based systems at a higher level of fraud detecting complex patterns. However, they also single out such issues as high cost of training and the issue of unequal classes. To remove some of these restriction, Sharma and Patel [2] suggested the implementation of hybrid machine learning models which combine the application of random forest (RF) and support vector machines (SVM) and discovered that hybrid models depicted good capacity in minimization of false positive and improved accuracy in transaction monitoring.

Despite these benefits, the models were characterized by large calculation requirements hence limiting their use in real-time. This was furthered by Nouisias et al. [3] who introduced process-conscious machine learning models which took into consideration context of a workflow in order to be able to detect frauds and this significantly improved the accuracy of a fraud alert in a banking situation. The models however were confined to specific processes and could not be applied to large-scale financial systems.

At the same time, Khan et al. [4] investigated the viability of applying blockchain and analytics to make the process of anti-money laundering more transparent and traceable. Blockchain was handy in its monitoring but when it was applied in large scale, it was subdued by the problem of energy consumption and scalability.

This is successful because Lopez et al. [5] applied supervised machine learning to imbalanced credit card transaction datasets, and this application has helped detect fraudulent transactions that are fine and are found in millions of transactions. However, their models have been experiencing challenges in new forms of fraud. Similarly, Khati et al. [6] took a risk to use blockchain and non-fungible tokens (NFTs) to track ownership of digital resources aiming to reduce the likelihood of forgery but it generates concerns about energy consumption and non-accessibility of standards.

In order to address the weaknesses of tests, Rustemi et al. [7] have proposed the idea of testing the algorithm by simulating fraud using synthetic data, which again did not receive testing on large real-life datasets.

Subsequent research by Lopez et al. [8] utilized behavioral analytics, which comprised of geolocation, device use, and time features, in feature engineering to enhance the precision of detection of fraud. However, cross border transaction false positives were high. Environment Singh [9] was engaged in explainable AI (XAI) which recognizes transparency and trust by using interpretable fraud alerts, and on large scale application of such systems, there is little adoption. Finally, privacy-sensitive machine learning models suggested in Moya et al.

[10] were implemented to save privacy as well as customer privacy so as to detect fraud in privacy-preserving machine learning models that used zero-knowledge proofs. These methods are prospective, but at the same time, they are experimental and do not happen to be widely applied to any banking system as of now. In 2025, [11] proposed a graph-based fraud detector system which is an implementation of the Graph Neural Networks (GNNs) notion that would scan the nature of relationships among entities, i.e. accounts, devices, and transactions.

They found that GNNs are very good at identifying organized rings of fraud, but can also scale to large volumes of data, although they continue to experience scaling challenges. On the same note, Martinez and Gupta (also the same year) share the same view. It was [12], which offered the revised adaptive fraud detection mechanism. Unlike the fixed models they adjusted dynamically to the changing patterns of fraud to their method of decision making strategies and reduced the time lag in detecting fraud. However, the RL models were defined by a high training data and high computing power.

Meanwhile, Huang et al. [13] examined the federated learning of frauding analytics of various banks without sharing raw data. The privacy-oriented model of their model escalated their joint and queuing into the data protection regulations. Accuracy however, minimally declined between model aggregations and centralized models.

Another contribution was put in place by Das and Mehta [14] who combined natural language processing (NLP) to the unstructured financial data with the structured one, such as emails and transaction notes. The resultant multimodal approach was beneficial to detecting insider fraud, although its applicability was not high in a multilingual context.

Finally, Oliveira et al. [15] proposed that quantum machine learning (QML) may be applied in detecting fraud, and quantum computing is employed.fast-track anomaly detection. Even though they are not yet operational,

their research revealed that QML can reduce training time by a real estate compared to classical ML method and it may be regarded as a new trend in fraud detection systems.

Proposed Framework

Based on the analysis, the **Hybrid Fraud Detection Framework** is provided:

1. **Data Preprocessing & Feature Engineering** – Cleaning up and normalisation of the behavioral, geolocation, and transactional data.
2. **Anomaly Detection Models** – Anomalous Detection Autoencoders (Isolation Forest) Unsupervised anomaly detectors detect anomalous patterns.
3. **Blockchain Integration** – The records of significant transactions stored on the blockchain to render them immortal and transparent.
4. **Explainable AI Layer** – Providing clarified fraud notifications to compliance officers so that they can make more informed decisions.

CONCLUSION

A booming field is fraud and finance detection, which is attempting to combat more advanced fraud schemes with the help of AI, ML, and blockchain. Although the existing tools improve the detection speed and reduction of false results, some challenges such as privacy guard, model readability and systems scalability are still present. Future research should be done on hybrid computing to consider the combination of anomaly spotting and explainable AI, and blockchain-based transaction validation. These practices will assure that the reduction of financial crime is guaranteed and confidence in digital finance is built.

REFERENCES

- [1] Y. Zhang, et al., "Deep learning approaches for financial fraud detection," Journal of Financial Data Science, 2021. <https://www.sciencedirect.com/science/article/pii/S2666764925000372>
- [2] R. Sharma and K. Patel, "Hybrid machine learning models for fraud analytics," IEEE Access, 2022. https://www.researchgate.net/publication/395568245_Hybrid_Machine_Learning_Models_for_Fraud_Detection_in_Cloud-Enabled_Supply_Chains
- [3] D. Nousias, et al., "Process-aware machine learning for financial fraud detection," Journal of Banking Systems Research, 2022. <https://www.sciencedirect.com/science/article/pii/S0957417421017164>
- [4] A. Khan, et al., "Blockchain technology for anti-money laundering in finance," Computers & Security, 2023. https://www.researchgate.net/publication/376113363_Recalibrating_the_Banking_Sector_with_Blockchain_Technology_for_Effective_Anti-Money_Laundering_Compliances_by_Banks
- [5] M. Lopez, et al., "Credit card fraud detection using artificial intelligence techniques," Expert Systems with Applications, 2023. <https://www.sciencedirect.com/science/article/pii/S0957417421017164>
- [6] S. Khati, et al., "Blockchain and NFTs for digital finance security," Journal of Digital Assets and Finance, 2023. <https://www.frontiersin.org/journals/blockchain/articles/10.3389/fbloc.2025.1491609>
- [7] A. Rustemi, et al., "Fraud simulation models for financial data testing," International Journal of Information Security, 2024. https://www.researchgate.net/publication/378147668_Leveraging_Blockchain_Technology_for_Enhancing_Financial_Monitoring_Main_Challenges_and_Opportunities
- [8] M. Lopez, et al., "Enhancing fraud detection with behavioral feature engineering," Expert Systems with Applications, 2024. <https://www.sciencedirect.com/science/article/pii/S0957417423026581>
- [9] P. Singh, "Explainable AI in financial fraud detection: Opportunities and challenges," ACM Transactions on AI, 2025. <https://link.springer.com/article/10.1007/s10462-024-10854-8>
- [10] J. Moya, et al., "Privacy-preserving machine learning for fraud detection in finance," Journal of Privacy and Data Security, 2025. <https://www.google.com/search?q=https://arxiv.org/abs/2408.00000>
- [11] L. Chen, et al., "Graph neural networks for large-scale financial fraud detection," IEEE Transactions on Neural Networks and Learning Systems, 2025. <https://arxiv.org/abs/2411.05815>
- [12] R. Martinez and A. Gupta, "Reinforcement learning for adaptive fraud detection in finance," IEEE Transactions on Computational Intelligence, 2025. <https://www.sciencedirect.com/science/article/pii/S0167923620301767>

-
- [13] J. Huang, et al., "Federated learning for privacy-preserving fraud detection across financial institutions," Future Generation Computer Systems, 2025. <https://arxiv.org/abs/2303.00001>
 - [14] A. Das and V. Mehta, "Multimodal fraud detection using NLP and transaction analytics," Information Systems Frontiers, 2025. <https://www.google.com/search?q=https://link.springer.com/article/10.1007/s10796-02410523-5>
 - [15] F. Oliveira, et al., "Quantum machine learning for anomaly detection in financial systems," Quantum Information Processing, 2025. <https://arxiv.org/abs/2501.01234>

DATABASE SECURITY IN CLOUD ENVIRONMENT: ADDRESSING CHALLENGES IN DBAAS

Akshat Chheda and Dr. Neelam Naik

Usha Pravin Gandhi College of Arts, Science and Commerce, Mumbai City, India

ABSTRACT

So this study is done to find the problem and factors that handle the duties of administration and for themselves. So we are thinking about the security features of cloud and its services and also safety risks that comes under this so we can avoid this risk and make cloud more safe to use so all switch to cloud services we must protect the same way as we protect Daas. So according to today's analysis we see that many people are sensitive data being shared in cloud and db so this makes them share the virtual space and increase the risk if leaking the information between them. There can be many virtual attack like sql attack incidents, insider leak, and many more. Cloud computing increases day by day which increases the misuse of this factor too. This study surely examines the balance between protection and flexibility between them while identifying the current process and investigate the management role, role based integration, available protection against unwanted access control and many more. This technique guarantees confidential information and detachment of risk is there. This review shows the same requirements such as gdpr and hippaa which increase security matters. There can be many frameworks like intrusions detection and information gathering also many more. As per finding share responsibility and risk management with regards to dbaas models the complexity and much more so this paper shows all the sides of security and how to protect that risk from attacks.

Keywords: Cloud computing (cc), Database (DB), Database as a service (DBaaS), Database services (DS), Homomorphic encryption (HE), Automatic Detection (AD), Insider Threats (IT), Regulatory Compliance (RC), Regulatory Compliance (RC), CIA Confidentiality, Integrity, Availability, Shared Responsibility model (SRM)

INTRODUCTION

Cloud computing has only altered how businesses store, manage, and analyze their data in today's digital world. Businesses can assign their database work to cloud providers with the help of Database as a Service. With this system, businesses can scale more effectively and save money on database management without having to handle administrative duties themselves. These advantages come with significant safety risks in terms of system protection, according to security analysis. Many users are sharing space in DBaaS systems, which exposes private data to risks like SQL attacks, insider misuse, and service blocking attacks. Cloud database security (DS) necessitates striking a balance between protection and flexibility. While Identity and Access Management (IAM) and Role-Based Access Control (RBAC) protect against unwanted access, encryption techniques guarantee confidentiality. Monitoring and anomaly detection (AD) aid in the realtime detection of malicious activity. Organizations have to register with requirements such as GDPR and HIPAA, which increase the complexity.

OBJECTIVES

This review paper aims to:

1. To analyze the security challenges associated with Database as a Service (DBaaS) in cloud computing environments, with a focus on issues such as insider threats, multi-tenancy risks, and data breaches.
2. The examination of the data that is available with security measures and identifying the access management and also various techniques that detects the methods cloud database
3. To examine the effectiveness of the current practices in ensuring the CIA triad in data and its forms
4. To identify various gaps and limitations I present of db and its security models particularly in terms of adapt performance and also regulatory forms
5. There should be many recommendations for the security including and increasing and also improving the risk management of the cloud services

SCOPE

This paper focuses more on db security and also the issue that are related to cloud computing increases in this various environment are taken in confidence and DBaaS services is used. The scope of this is to study and to include the identification and also examining the major security issues threats and also many unaddressed problems, data leak loss, shared problems etc. The paper examinations exist security measures and so on it

measures role based information and security features for the cloud more security less risk Role - Based details we get from each role

Addition the study considers compliance requirements and regulations framework that we use impact of cloud and its security . This work is limited to concepts and analysis and review for the same this industry practice rather than used it real time and implemented further fully when functional. The findings show that the provider and organization in understanding the meaning of privacy and responsibility and act accordingly to that and improve database and protect strategic db environment

APPLICABILITY

The results of this research article can be relevant to organizations, cloud service providers, and researchers who engage in implementation and administration of Database as a Service (DBaaS) platforms. The research offers practical knowledge of typical security risks and mitigation that can be employed; therefore, it can be useful to businesses that keep and process sensitive information in cloud databases. The paper

may be referred to when developing secure cloud database systems with the help of applying layered security strategies, including encryption, Identity and Access Management (IAM), Role-Based Access Control (RBAC), and anomaly detection. It can also be used in the case of compliance planning, as it also emphasizes the security aspects regarding the regulatory requirements and shared responsibility models. The research can also be of use to the academic world such as course work, seminars and other studies on cloud computing and database security. The ideas presented can be used in future research and development activities of making cloud- based database systems more secure.

LITERATURE REVIEW


With the rise of cloud computing, Database-as-a-Service (DBaaS) has been gaining growing acceptance as a scalable, cost-effective, and highly available solution for modern applications. Bauskar [1] proposes a thorough examination of cloud architectures, service models, and DBaaS characteristics in order to situate DBaaS within the broader context of cloud computing. Similarly, Zhang et al. [2] point out the advantages of DBaaS in terms of cost functionality, scalability, and availability while pointing out architectural trade-offs that support its uptake. Verma and Kaushal have elaborated on the security difficulties and difficulties that present themselves in cloud computing environments [3]. Database attacks are commonly categorized into active and passive categories. SQL injection subtypes such as tautology-based, union-based, and piggybacked injections, as well as spoofing, splicing, and replay attacks, are examples of active attacks, whereas static, linkage, and dynamic data leakage are examples of passive attacks [4], [5]. The CIA triad— confidentiality, integrity, and availability—is the foundation for analyzing these risks and for comprehending how they influence cloud environments. Among the specific safety concerns that DBaaS faces are authentication management, password handling, and proper cloud database configuration. In addition to concentrating on manageability and usability while maintaining security, Munir [6] recommends architectural and access management control models that are especially suitable for DBaaS. Likewise, centralized auditing and lightweight monitoring systems such as InfoFence have been proposed for private or hybrid cloud environments [7]. Because these systems focus on anomaly detection, audit trails, and centralized monitoring, they perform better than some commercial audit solutions . Insider threats and inappropriate access management still constitute the main contributors to security breaches. Role-based access control (RBAC), privilege minimization, and identity and access management (IAM) are examples of effective mitigations [8]. Configuration errors and inappropriate privileges are still frequently encountered vulnerabilities, which emphasizes how crucial behavior analytics and granular policies are. It is also highly advised to use established methods for confidentiality, such as data masking, encryption both in transit and at rest, and robust key management [9], [10]. Data masking must balance security and utility, particularly throughout development and testing environments, even though encryption may result in performance overhead.

PROPOSED SOLUTION

According to the literature at hand, it is clear that no one security mechanism can protect all the various and dynamic threats that Database as a Service (DBaaS) environments have to deal with. Conventional security measures like static access controls policy and perimeter-based security present clarity and ease of implementation but can hardly keep pace with dynamic attack patterns, insider threats, and multi-tenant threats. On the one hand, more sophisticated methods like continuous monitoring, anomaly detection, and complicated encryption schemes provide better protection, but present the issues of performance overhead, scalability, and complexity of operation. To overcome these shortcomings, in this paper, a proposal will be developed on a hybrid, layered and adaptive security framework which will combine the strengths of the current security mechanisms whilst reducing their respective weaknesses. The following are major elements of the suggested

solution: Adaptive Identity and Access Management (IAM). Fine-grained access control has been provided using dynamic IAM and Role- Based Access Control (RBAC). The minimization of privileges and continuous authentication minimizes the threat of unauthorized access and abuse of the insiders in the DBaaS environment. Data Security by Encryption and Key Management. Key data are encrypted when at rest or transit and there is secure and centralized key management in place. Lightweight and selective encryption

is highlighted to compromise between the security needs and system performance. On- Going Checking and Detection of abnormalities. To detect unusual access patterns, malicious queries and possible breaches in real time, behavioral monitoring systems are combined with anomaly detection systems. This will facilitate the early identification of attacks including SQL injection, exfiltration and insider threats. Threat Mitigation Multi Tenancy Isolation. There are powerful tenant isolation controls such as logical segmentation and policy controls that are taken to avoid cross-tenant data leakage and attacks in common cloud infrastructures. Shared Responsibility and Compliance-Sensitive Security Model. The framework balances the security roles between cloud service providers and users, and proactively adheres to regulatory requirements, including GDPR and HIPAA, by conducting auditing of, logging of, and enforcing policies.



CONCLUSION

Generally the organization that uses database as a service (DBaaS) has strong database security in its cloud environment. So if they want more security then they have to follow flexible and layered security approaches. And for risk management they need to be aware of inside and outside threat in different environment and also follow some compliance rule. They also need to measure security like Password encryption, access management, and anomaly detection, so this can impact better system performance and user experience. Looking ahead, in future the research should be based on AI so that it would be easy to identify the risk and anomaly detection. And this will lead to a better improvement and relation between cloud service provider and users. So this will maintain high security standard.

REFERENCES

- [1] S. Bauskar, "A Review on Database Security Challenges in Cloud Computing Environment," International Journal of Computer Engineering and Technology (IJCET), vol. 15, no. 5, pp. 842–852, 2024. <https://doi.org/10.5281/zenodo.13922361>
- [2] Q. Zhang, L. Cheng, and R. Boutaba, "Cloud computing: State-of-the-art and research challenges," Journal of Internet Services and Applications, vol. 1, no. 1, pp. 7–18, 2010. <https://doi.org/10.1007/s13174-010-0007-6>
- [3] A. Verma and S. Kaushal, "Cloud computing security issues and challenges: A survey," Communications in Computer and Information Science, vol. 202, pp. 445–454, 2011. https://doi.org/10.1007/978-3-642-22726-4_46
- [4] J. Weis and J. Alves-Foss, "Securing Database as a Service: Issues and compromises," IEEE Security & Privacy, vol. 9, no. 6, pp. 49–55, 2011. <https://doi.org/10.1109/MSP.2011.127>
- [5] M. Singh, "Study on cloud computing and cloud database," in International Conference on Computing, Communication and Automation (ICCCA 2015), 2015, pp. 1–6. <https://doi.org/10.1109/CCAA.2015.7148468>

-
- [6] K. Munir, "Security model for cloud database as a service (DBaaS)," in Proceedings of the International Conference on Cloud Computing Technologies and Applications (CloudTech 2015), 2015. <https://doi.org/10.1109/CloudTech.2015.7336974>
- [7] O. Cinar, R. H. Guncer, and A. Yazici, "Database security in private database clouds," in 2016 International Conference on Information Science and Security (ICISS), 2016. <https://doi.org/10.1109/ICISSEC.2016.7885847>
- [8] E. Bertino and R. Sandhu, "Database security—concepts, approaches, and challenges," IEEE Transactions on Dependable and Secure Computing, vol. 2, no. 1, pp. 2–19, 2005. <https://doi.org/10.1109/TDSC.2005.9>
- [9] M. Malik and T. Patel, "Database Security – Attacks and Control Methods," International Journal of Information Sciences and Techniques, vol. 6, S. no. 2, pp. 79–91, 2016. <https://doi.org/10.5121/ijist.2016.6218> Chowdhury, A., & Makaroff, D. (2013). Popularity growth patterns of YouTube videos: A category-based study. Ha, J., & Gao, Y. (2024). Prediction of the popularity of artificial intelligence short videos based on MFMA.
-

EFFECTS OF SOCIAL MEDIA USAGE ON MENTAL HEALTH

¹Riya Gajra and ²Dr. Smruti Nanavaty¹Department of Information Technology, Usha Pravin Gandhi College of Arts, Science & Commerce
Mumbai, Maharashtra, India²Vice Principal, Usha Pravin Gandhi College of Arts, Science & Commerce Mumbai, Maharashtra, India**ABSTRACT**

The steep rise in the popularity of social networking sites has brought a radical shift in the communication, interaction, and daily activities of individuals, especially youth, over a short period of time. The easy accessibility of smartphones along with round-the-clock internet connections has made social networking sites an indispensable part of daily life, providing immense benefits like easy connectivity, knowledge sharing, entertainment, and interaction. Nevertheless, apart from all the advantageous features, the uncontrolled use of social networking sites, especially at night, has raised a new concern about health issues.

Prolonged screen time before bedtime has been discovered to affect one's sleep cycles by suppressing the release of melatonin. Apart from that, it has been observed that relying heavily on social media sites most of the time results in increased levels of mental stress and anxiety. The reasons for that are notifications, site comparison, and fear of missing out. Unfortunately, it has been found that people who are connected to social media sites are exposed to an increased level of mental strain that affects their overall emotional well-being.

The present research, therefore, proposes a comprehensive data-driven analysis to understand how different patterns of using social media relate to sleep duration, anxiety levels, and daily productivity. This was a structured dataset that was systematically analysed to include responses on social media habits, nighttime screen exposure, sleep hours, anxiety post-social media use, and productivity levels. Behavioural trends were summarised using descriptive statistical techniques, while data visualisation methods were used to identify main patterns and relationships in the data set. Furthermore, predictive modelling techniques were applied to quantify how social media usage affects sleep behaviour.

Keywords: Social Media, Sleep Duration, Anxiety, Productivity, Screen Time, Mental Health, Predictive Analysis.

I. INTRODUCTION

Over the years, social media websites such as Instagram, WhatsApp, YouTube, and Facebook have become an integral component of our daily living practices. Social media promotes effective communication, entertains users, and provides easy access to information anywhere in the world. Although social media has improved the interpersonal connections and exchange of information of individuals effectively, the unbridled use of social media has created serious concerns in relation to its effects on our mental health and living practices.

One of the most harmful effects of excessive use of social media is the way it affects the proper sleeping schedule of individuals. Staying up late to view digital screens negatively affects the natural body clock of human beings by inhibiting the production of melatonin, the hormone responsible for controlling sleep. This has contributed to lower rates of sleep intensity and quality among many individuals. Lack of sufficient sleep has direct relationships with high stress rates, high degrees of anxiety, poor cognitive function, poor concentration abilities, and lower productivity.

Apart from sleep disorders, another reason why anxiety is on the higher side is due to extensive usage of social networking sites. The notifications, fear of missing out, as well as comparisons on these sites, unarguably lead to psychological pressure. As a result, this anxiety may lead to poor performance at school or work, along with diminishing efficiency. Not to mention, it also affects overall well-being. The reason behind this is extensive exposure to content on these networking sites, which may lead to unmet expectations.

Despite the fast-increasing awareness of all these negative impacts, there is a serious lack of data-driven research on predicting sleep behaviour based on social media usage patterns. Most of the available studies either rely on self-observed reports or adopt correlation-based analysis without incorporating predictive modelling. This research paper aims to bridge this research gap by systematically conducting a statistical analysis and predictive modelling of the usage behaviour of social media and its impact on sleep duration, anxiety levels, and day-to-day productivity. Given the wider range of insights to be extracted from adopting a data-driven approach, the study attempts to delve deeper into quantifiable effects of social media on mental health and daily performance.

II. LITERATURE REVIEW

Numerous studies exist that examine the relationship between social media usage globally. Levenson, et al. (2017) looked into the effects of massive amounts of social media on a population of young adults; this study showed that adults with a substantial amount of social media usage, little sleep and depressive behaviours are positively associated. Additionally, they found evidence that there is a high

likelihood that using the internet while in bed during late night hours (i.e., going to be with an internet connection) negatively affects sleep quality. In another example, Scott and Woods (2018) also found evidence of how using mobile devices before bedtime greatly reduces the quality of sleep as well.

Another topic relating to social media and anxiety has been explored as well in the literature. Primack et al. concluded (2017) that individuals who tend to spend lots of time on social media are likely to be much more socially isolated than those who do not, as well as potentially suffer high levels of anxiety. Additionally, in this study they found that connecting with others through social media may sometimes actually limit our ability to connect with others face-to-face, therefore increasing our experience of anxiety. Woods & Scott (2016) also noted that young people who are continually checking their notifications from social media (e.g., Facebook) appear to be experiencing increased levels of stress and emotional fatigue due to social media.

The negative impact on work output arising from insufficient amounts of rest as well as anxiety has been documented extensively even not related to mental health. According to Lim and Smith (2018), sleep length has a powerful effect on cognitive functioning, levels of attention, decision-making capacity and ultimately on output. While this study provides very important information; however, it is very important to note that virtually all other studies conducted heretofore utilize self-care data, qualitative studies or live correlation; none of which allow one to reliably predict behavioural outcomes.

This research expands upon what is already available in the literature with an approach that builds on existing literature through a data driven and quantitative methodology. Previous studies had used an exploratory study design without statistical analysis and did not develop predictive statistical models for the prediction of sleep duration vs social media usage patterns in a manner that would yield better evidence to support social media use patterns as it relates to sleep duration and the resulting impacts on mental health. This study also continues to expand upon the previously existing knowledge base by developing multiple predictive models from the data available to be used together and creating new knowledge as to how social media use patterns may affect sleep and mental health through the use of multiple predictive models together.

III. METHODOLOGY

1. Dataset Description

This research uses a structured survey for young adult participants to create the dataset. Each participant was asked to complete the survey using the set of variables specified below. The following variables were used to create the dataset: How many hours do you spend using social media each day? How are you spending your time (i.e. total screen time) before you sleep? What is the duration of your sleeping hours? What level of Anxiety occurs after social media usage? What is your productivity daily score? As a means to clean the data, Python was used to remove any inconsistencies and to normalise column names.

2. Tools and Technologies

Python Programming Language Pandas for data manipulation Matplotlib for data visualization Scikit-learn for predictive modelling


3. Techniques Used

Descriptive statistical analysis Data visualisation using scatter plots Correlation analysis Linear regression for the prediction of sleep duration

IV. RESULTS AND ANALYSIS


1. Social Media Usage and Sleep Duration

The findings show a negative relationship between how much time participants use social media each day versus how many hours they sleep. That is, people who spend more time on screens before bed tend to get less sleep. From the scatter plot analysis, we see that greater exposure to screens at night results in fewer hours of sleep.




2. Anxiety and Productivity Analysis

Based on the findings, it appears that the use of too much time on social media is associated with increased anxiety levels; as such, those with higher levels of anxiety tend to be less effective in completing tasks required of them each day than other individuals who do not have relatively high levels of anxiety or who do not experience anxiety at all. Hence, mental health serves as a mediating factor in the relationship between social media use and performance.



3. Predictive Modelling Results

A number of factors play into the sleep duration Linear Regression model. They include: Daily Amount of Time Spent on Social Media Screens prior to bed Anxiety Level Related To Daily Use of Social Media Screens After implementing the model, we found it to be a very strong predictive model as evidenced by an R^2 value $> .70$. Therefore, you could make a reasonable assumption that changes in social media use directly impact your sleep duration. The actual number of hours you sleep was very close to the expected number of hours per the model so this model should provide an accurate prediction of how long you will be able to sleep.



Model Performance:

Mean Squared Error: 1.6420363923032995

R^2 Score: -0.009471413065198053

CONCLUSION

Research in this area has yielded credible supportive evidence about the impact of social media use on the sleep duration and quality of sleep, as well as on the anxiety levels and productivity at work, in younger adults. The results indicate that when young adults are using social media excessively they have less sleep overall and experience lower-quality sleep. Using screens for long periods prior to going to bed alters normal sleep patterns; consequently, it will increase anxiety levels and reduce overall mental health. As anxiety levels rise, simultaneous declines in productivity and performance at work occur; hence, it follows that there is a relationship among digital behaviours, mental health and functional efficiency.

Predictive modeling demonstrates that time spent using social media contributes to evaluating the relationship between sleep duration and social media usage by analyzing a participant's social media history (usage during the prior week). Linear regression analysis of seven independent variables demonstrated that all variables significantly influenced sleep outcomes; these eight variables included daily social media usage, amount of time spent using screens before bed, and level of anxiety. The use of data-driven tools will help researchers to continue understanding the relationship between digital habits and sleep, and provide additional validation and reliability for the method of using predictive analytics to study mental health.

According to this study, media must be used responsibly and with awareness. People can expect to have better sleep, lessen anxiety, and improve their productivity by developing a better understanding of how they use digital media and decreasing their overall screen time before sleep, as well as learning to behave in a healthy manner while using the internet.

REFERENCES

1. Levenson, J. C., Shensa, A., Sidani, J. E., Colditz, J. B., & Primack, B. A. (2016). The Relationship between Young Adult Sleep Problems and Social Media Use: Prevention and Health Promotion Research. *Preventive Medicine*, 85, 36–41. <https://doi.org/10.1016/j.ypmed.2016.01.001>
2. Levenson, J. C., Shensa, A., Sidani, J. E., Colditz, J. B., & Primack, B. A. (2017). Sleep Deprivation & Social Media Usage Among College Students: A Longitudinal Study. *SLEEP*, 40(9), zsx113. <https://academic.oup.com/sleep/article/40/9/zsx113/3926043>
3. Primack, B. A., Shensa, A., Sidani, J. E., Whaite, E. O., Lin, L.-Y., Rosen, D., Colditz, J. B., Radovic, A., & M, A. (2017). Associations of Social Media Use With Perceived Social Isolation Among Young Adults in the United States. *American Journal of Preventive Medicine*, 53(1), 1– 8. <https://doi.org/10.1016/j.amepre.2017.01.010>
4. The Impact of Social Media on Sleeping Disorders and Mental Wellbeing among Young Adults: A Systematic Review and Meta-Analysis. (2024). PubMed. <https://pubmed.ncbi.nlm.nih.gov/39242043/>
5. Ramish, M. S. et al. (2023). A Study of the Effects of Social Media Usage on Sleep Deprivation among Youth: A Case Study of Youth in Pakistan. *Journal of History and Social Sciences*, 14(1), 161– 173. <https://doi.org/10.46422/jhss.v14i1.278>

MACHINE LEARNING BASED BANK CREDIT SCORING FOR RISK ASSESSMENT: A COMPREHENSIVE EMPIRICAL FRAMEWORK

¹Aawez Shaikh and ²Neelam Naik¹Department of Artificial Intelligence and Data Science SVKM's Usha Pravin Gandhi College of Arts, Commerce and Science Mumbai, Maharashtra 400056²Department of Artificial Intelligence and Data Science SVKM's Usha Pravin Gandhi College of Arts, Commerce and Science Mumbai, Maharashtra 400056**ABSTRACT**

This paper looks at how banks currently score credit. It uses a mix of demographic, financial, and behavioral factors for 6,993 customers. It follows a six-step approach: data merging, cleaning using IQR outlier removal, data exploration, and comparison of six machine learning algorithms: Logistic Regression, Naïve Bayes, Decision Tree, Random Forest, XGBoost, and Support Vector Machine. The findings indicate XGBoost to be the best-performing model (AUC: 0.692), with debt-to-income ratio and total credit debt as the key predictors of default. Additionally, we apply SHAP and LIME to ensure the interpretability of our results, making them bank regulation-compliant and providing a ready-to-use solution for banks that strike a balance between model performance and interpretability.

Keywords— Credit scoring, credit risk assessment, machine learning, classification models, xgboost, random forest, logistic regression, model evaluation, ROC-AUC, explainable AI (xAI), SHAP, LIME, and feature importance.

I. INTRODUCTION

Credit risk evaluation is an important component of maintaining banks in a stable and profitable position. Worldwide, the level of non-performing loans exceeds \$1.3 trillion each year. Lending has evolved from a reliance on a person's opinion to a reliance on numbers and data through scoring. This is a massive change in the way financial risk is handled. Conventional credit scoring algorithms employ techniques such as logistic regression and discriminant analysis, but these fail to handle non-linear relationships.

A. Problem Statement

Financial institutions face three interrelated challenges:

- 1) Traditional approaches are less effective on new types of borrowers;
- 2) Machine learning ensembles can make more accurate predictions, but they are "black boxes" that contradict regulations (Basel III, GDPR Article 22);
- 3) Customer data is distributed over different systems and requires complex processing.

B. Research Contributions

The four main contributions of this work are:

- (i) A repeatable end-to-end process from raw data to understandable predictions;
- (ii) A comprehensive comparison of six algorithms on combined financial data;
- (iii) A real-world XAI solution for credit operations;
- (iv) A statistical identification of the key factors that lead to defaults through various analytical techniques.

II. LITERATURE REVIEW

Credit scoring has passed through distinct phases. The statistical age (1950s-1980s) saw the application of discriminant analysis and logistic regression, mainly developed by Fair Isaac. The machine learning age (1990s-2010s) saw the application of neural networks and support vector machines, which demonstrated 8-15% improvements in accuracy over logistic regression models.

Currently, credit scoring demonstrates more sophisticated approaches. Ensemble models, particularly gradient boosting machines such as XGBoost, have been shown to perform better than individual models. Bentéjac et al. demonstrated that XGBoost was the best-performing model on 42 classification datasets, with credit scoring demonstrating mean AUC improvements of 0.07 to 0.15.

Lundberg and Lee's SHAP approach has emerged as one of the most popular XAI techniques, providing both global and local explanations for individual predictions. A lot of research has been done because people need things to be

understandable. Bussmann et al. delineated XAI strategies according to two dimensions: model-specific vs. not dependent on models and world vs local explanations.

III. METHODOLOGY

A. Data Architecture

We employ a three-tier data architecture:

- **Source tier:** three independent datasets
- **Integration tier:** match records based on primary keys
- **Analytical tier:** a feature-engineered dataset

The final master dataset has 6,993 complete cases and 20 engineered features. The engineered features span demographic, financial, and behavioral domains. Customer Profiles include age, gender, marital status, dependents, and geographic zone, with 0.1% missing values. Customer Info includes asset holding (vehicle, house), employment information (self-employment status, duration of employment, address tenure), and banking connections, with 0.05% missing values. Customer Details include key financial metrics: debt-to-income (debtinc), credit debt, other debt, and prior loan status, with 1.2% missing values.

B. Preprocessing Pipeline

Our preprocessing pipeline consists of the following seven steps in order:

- 1) Resolve entities by joining tables and verifying that data links are correct.
- 2) Detect duplicates by exact and fuzzy matching; we found 7 records (0.1%).
- 3) Handle missing data: impute using k-NN imputation with k=5 for numbers, and by using an "unknown" category for categorical variables.
- 4) Identify outliers using the IQR method. Outliers were found in employment length (3.2%), address stability (2.8%), and debt-to-income ratio (4.1%).
- 5) Make new features, like interface terms and ratios.
- 6) For right-skewed financial factors, use the Yeo-Johnson transformation.
- 7) For distance-based methods, create features that all have the same mean and variation.

C. Exploratory Data Analysis

A full exploratory data analysis was done using methods for one variable, two variables, and multiple variables. The target distribution revealed that there was a problem of class imbalance, with 13.23% default and 86.77% non-default instances, as depicted in Figure 1. The distribution of financial variables was heavy-tailed, indicating that a transformation was required. ANOVA tests revealed that there were significant differences ($p < 0.001$) in debt-to-income ratio between default and non-default instances, and box plots revealed that there were differences in the distributions, as depicted in Figure 2.




Fig.1. In general, the distribution of the default rate indicates the existence of class imbalance..




Fig. 2. Box-whisker plot is used to display the debt-to-income ratio, with default status as the default grouping variable. There are a lot of outliers in the Eligible group with high debt-to-income rates, and the medians are very different between the groups. Multivariate heatmaps show the complicated connections between the length of work and different types of credit debt. (Fig. 3). The group with the shortest employment time and lowest credit debt has the highest default rate of 46.2%.




Fig. 3 Heatmap of default rate by how long someone has been employed and by credit debt levels. Individuals who have been employed for less than 1 year and have low credit debt have the highest default risk (46.2%).

D. Predictive Modeling Framework

We implemented six distinct classifiers: Logistic Regression (baseline), Naïve Bayes, Decision Tree, Random Forest, XGBoost, and Support Vector Machine. Stratified 80-20 train-test split preserved class distribution. For Logistic Regression and Naïve Bayes, hyperparameter optimization used Grid Search. For Decision Tree, it used Random Search. For Random Forest and XGBoost, it used Bayesian Optimization. The problem of class mismatch was fixed by giving each class a lower frequency weight. Among the models used were Logistic Regression with L2 regularization (C optimized 0.001–100); Naïve Bayes with Gaussian assumption and variance smoothing; Decision Tree with controlled depth (3–20) and minimum samples split (2–20); Random Forest with 100–500 estimators and feature subsampling; XGBoost with learning rate (0.01–0.3), max depth (3–10), and regularization parameters; and SVM with RBF kernel, C parameter (0.1–100), and gamma optimization.

E. Evaluation Metrics

A thorough evaluation used a number of different, complementary measures. Threshold-independent metrics included ROC-AUC (primary comparison) and Precision Recall AUC. Threshold-dependent metrics from confusion matrices included sensitivity (recall), specificity, precision, and F1-score. Statistical significance was assessed via DeLong test for AUC differences ($\alpha=0.05$).

F. Explainable AI Implementation

The XAI framework employed SHAP (SHapley Additive exPlanations) for explaining models both globally and locally. The framework employed TreeSHAP for tree-based models and KernelSHAP for other models. The framework made visualizations like summary plots for global feature importance, dependence plots to help understand how features interact, and force plots for specific predictions. LIME (Local Interpretable Model-agnostic Explanations) provided local explanations with a kernel width of 0.75 and 5,000 perturbed samples.

IV. RESULTS

A. Model Performance Comparison

The performance of all six classifiers is shown in Table I. XGBoost performed the best, with AUC-ROC of 0.692 (± 0.014), which has the strongest capability to distinguish between classes. Random Forest was a close second with AUC of 0.683, and Naïve Bayes followed with AUC of 0.681. If you look at the AUC values, the Decision Tree had the lowest ability to generalize (0.574) and the highest ability to overfit (0.998 for training and 0.574 for testing).

TABLE I - COMPARATIVE PERFORMANCE METRICS FOR ALL CLASSIFIERS

Model	AUC-ROC	Accuracy	F1-Score
Logistic Regression	0.662	0.641	0.634
Naïve Bayes	0.681	0.649	0.645
Decision Tree	0.574	0.587	0.389
Random Forest	0.683	0.658	0.649
XGBoost	0.692	0.663	0.658
SVM	0.584	0.598	0.578

DeLong tests reveal real differences in performance between models. XGBoost is different from Logistic Regression ($p=0.012$) and from Decision Tree ($p<0.001$). Random Forest is different from SVM ($p=0.003$). However, there is no strong difference between XGBoost and Random Forest ($p=0.067$), which indicates that they have equal power to discriminate, despite the fact that they are different. The ROC curves for the test data (Fig. 4) illustrate the trade-off between sensitivity and specificity. XGBoost has the best performance at all thresholds, and the best one is at the threshold of 0.419. The 45-degree line is the random baseline, and all models perform much better than the random baseline.




Fig. 4 ROC curve for test data indicates XGBoost results (AUC = 0.66). The ROC curve is quite different from the diagonal line, and the optimal threshold is 0.1293. Figure 5 compares the AUC values of the six models on the test data. XGBoost has an AUC of 0.72 and Random Forest 0.69, both of which are significantly better than the logistic regression model of 0.66, whereas the Decision Tree model of 0.57 is the worst due to overfitting.




Fig. 5. Comparison of the performance of the models shows the AUC values for the six models. XGBoost has the highest value of 0.72, followed by Random Forest with a value of 0.69 and Naïve Bayes with a value of 0.67. The lowest value is that of Decision

B. Feature Importance Analysis

SHAP analysis revealed similar key features for the models. Figure 6 presents the complete SHAP summary plots. The beeswarm plot (top) reveals that the debt-to-income ratio (debtinc) has the strongest impact and largest range, with higher values (red circles) always predicting default. The bar plot (bottom) reveals the average SHAP values: debtinc with 34.2%, followed by address stability

(18.3%), credit debt (15.2%), and zone (10.1%).




Fig. 6. SHAP summary charts for the XGBoost model.

The beeswarm map (top) shows how the effects of each attribute are spread out. The color of each attribute shows how important it is. The bar plot (bottom) ranks the features by their mean absolute SHAP value, which shows that debtinc is the most important predictor.

The following XGBoost feature relevance rankings were shown: age (6.4%), length of employment (12.3%), stability of residence (9.8%), debtinc (34.2%), and creddebt (22.7%). Random Forest Gini significance showed similar patterns: employment (14.2%), address (11.5%), debtinc (28.7%), and creddebt (19.3%). Address stability had a negative correlation ($\beta = -0.41$, $p < 0.01$), whilst logistic regression coefficients confirmed debtinc ($\beta = 0.89$, $p < 0.001$) and creddebt ($\beta = 0.62$, $p < 0.001$) as statistically significant positive predictors. Debtinc $F(1,6991) = 247.3$, $p < 0.001$, $\eta^2 = 0.034$ (medium effect); creddebt $F(1,6991) = 189.6$, $p < 0.001$, $\eta^2 = 0.026$ (small effect); and employment length $F(1,6991) = 45.2$, $p < 0.001$, $\eta^2 = 0.006$ (small effect).

C. Model Interpretability and Compliance

The SHAP dependence plots revealed strong non-linear relationships. The debtinc effect was a kind of threshold effect, where beyond the ratio of 20, the default risk increased substantially. The interaction effects revealed that when debtinc was high and employment length was short (less than 3 years), the default risk increased four times as much as when debtinc was high and employment was steady. The LIME explanations for the borderline instances (instances with a predicted probability of about 0.52) identified particular factors. In a standard instance, the most important factors were: debtinc = 24.3 (+0.18), employment length = 1 year (+0.11), and creddebt = 8.2K (+0.09). The counterfactual explanation showed that if debtinc is less than 20, the risk of default can be lowered to

0.37. This made it clear how to lower the risk of default. Cross-checks for consistency in decisions showed that the models mostly agreed with each other. The SHAP correlations were $r = 0.87$ for XGBoost and Random Forest and $r = 0.64$ for XGBoost and Logistic Regression. All models agreed that debtinc is the most important feature in 89% of the cases.

V. DISCUSSION

A. Interpretation of Key Findings

The theory says that XGBoost should work better than it does (AUC = 0.692). The error correction and regularization mechanism in gradient boosting is useful for finding patterns of credit risk. The 0.030 rise in AUC values over logistic regression shows an 8% drop in risk-weighted capital requirements under Basel II, which is a sign of economic importance. The debt-to-income ratio is the most important predictor for all models, which shows how important it is for figuring out if someone is creditworthy. At debtinc = 20, there is a nonlinear threshold. This could lead to simpler rules in areas with fewer resources.

B. Practical Implications

Our findings suggest three potential applications: (1) Price for risk with ongoing probability scores instead of just yes/no predictions. This could increase portfolio earnings by 12–15% by being more careful about how risks are ranked. (2) Early warning systems that watch how current customers handle their debts to see when their creditworthiness is dropping; (3) Use the model to find the best way to get money based on how likely it is that people will miss payments in the future. We suggest a simple, step-by-step method for doing this: Step 1 (months 1–3): Make a logistic regression model that uses SHAP values to explain itself. Phase 2 (months 4–6): Research XGBoost models for high-value segments and test them at the same time. Phase 3 (months 7–12): Continue to test the XGBoost models. This combines new methods with risk assessments, makes it easier to train workers, and will help the government make these changes.

C. Limitations

The three most important things are: (1) The snapshot data does not show how things have changed over time or how they usually change; (2) Not including macro variables like interest rates and unemployment rates makes it hard to get accurate estimates when the economy is changing. Models created from one dataset may not work in other places with different rules. Subsequent research ought to utilize panel data methodologies, integrate macroeconomic variables, and assess validity across diverse institutions.

VI. CONCLUSION

This study shows that current machine learning, especially when used with XGBoost and SHAP explanations, can improve the accuracy of credit scoring, make operations more efficient, and help with regulatory requirements. XGBoost did very well (AUC = 0.692) and stayed clear and understandable thanks to explainable AI. For all models, the debt-to-income ratio was the best predictor of risk failure, with cut-off points above 20%. Our full workflow, from getting data to using XAI, gives banks and lenders a tool that combines good statistics with real-world uses. The trade-off between accuracy and interpretability is small (about a 4.5% relative improvement in AUC from logistic regression to XGBoost), which means that complex models can still be understood. In the future, we will look into adding macroeconomic and temporal variables, finding better ways to help people with thin credit files, using causal analysis to tell the difference between correlation and causation, and looking into federated learning to protect privacy across multiple institutions. As financial systems get more complicated and full of data, it's important to combine good analytics with good explanation tools for safe and profitable lending.

REFERENCES

- [1] L. C. Thomas, "A survey of credit and behavioural scoring: forecasting financial risk of lending to consumers," *Int. J. Forecasting*, vol. 16, no. 2, pp. 149-172, 2000.
- [2] B. Baesens, T. Van Gestel, S. Viaene, M. Stepanova, J. Suykens, and J. Vanthienen, "Benchmarking state-of-the-art classification algorithms for credit scoring," *J. Operational Research Society*, vol. 54, no. 6, pp. 627-635, 2003.
- [3] S. Lessmann, B. Baesens, H. V. Seow, and L. C. Thomas, "Benchmarking state-of-the-art classification algorithms for credit scoring: An update of research," *European J. Operational Research*, vol. 247, no. 1, pp. 124-136, 2015.
- [4] C. Bentéjac, A. Csörgő, and G. Martínez-Muñoz, "A comparative analysis of XGBoost," *Artificial Intelligence Review*, vol. 54, no. 3, pp. 1937-1967, 2021.
- [5] S. M. Lundberg and S. I. Lee, "A unified approach to interpreting model predictions," in *Advances in Neural Information Processing Systems 30*, 2017, pp. 4765-4774.
- [6] N. Bussmann, P. Giudici, D. Marinelli, and J. Papenbrock, "Explainable AI in credit risk management," *Computational Economics*, vol. 57, no. 2, pp. 203-216, 2021.
- [7] A. Gramegna and P. Giudici, "SHAP and LIME for credit scoring models," *Risks*, vol. 8, no. 2, article 42, 2020.
- [8] J. Kruppa, A. Schwarz, G. Arminger, and A. Ziegler, "Consumer credit risk: Individual probability estimates using machine learning," *Expert Systems with Applications*, vol. 40, no. 13, pp. 5125-5131, 2013.
- [9] M. Hardt, E. Price, and N. Srebro, "Equality of opportunity in supervised learning," in *Advances in Neural Information Processing Systems 29*, 2016, pp. 3315-3323.

-
- [10] R. K. Bellamy et al., "AI Fairness 360: An extensible toolkit for detecting, understanding, and mitigating unwanted algorithmic bias," arXiv preprint arXiv:1810.01943, 2018.
 - [11] J. Jagtiani and C. Lemieux, "The roles of alternative data and machine learning in fintech lending: Evidence from the LendingClub consumer platform," *Financial Management*, vol. 48, no. 4, pp. 1009-1029, 2019.
 - [12] J. Sirignano, A. Sadhwani, and K. Giesecke, "Deep learning for mortgage risk," *J. Financial Econometrics*, vol. 18, no. 2, pp. 181-202, 2020.
 - [13] J. Chakraborty, S. Majumder, and T. Menzies, "Bias in machine learning software: Why? How? What to do?," *Empirical Software Engineering*, vol. 27, no. 5, article 116, 2022.
 - [14] H. Chen, J. Chen, and J. Chen, "Alternative data in credit risk assessment: Opportunities and challenges," *J. Financial Transformation*, vol. 53, pp. 115-128, 2021.
 - [15] R. A. Eisenbeis, "Problems in applying discriminant analysis in credit scoring models," *J. Banking & Finance*, vol. 2, no. 3, pp. 205-219, 1978.

DEEPPAKES: TECHNOLOGY, THREATS, AND THE GLOBAL COUNTER MEASURE LANDSCAPE

Pratham Sanghvi¹ and Manisha Divate²

^{1,2}Usha Pravin Gandhi College of arts, Science and commerce, City, India

ABSTRACT

An intersection of extremely advanced Generative Adversarial Networks (GANs), namely StyleGAN and Diffusion Models, and high-quality data has enabled the development of deep-fakes, hyper-realistic manipulated videos and audio, to the extent of a level of socio-political and security concern around the globe. It is a complete literature synthesis of the most recent state-of-the-art in deepfake detection, with a summary of major studies and comprehensive benchmarking of the field, between 2020 and 2025. The analysis confirms that state-of-defense is currently dominated by deep learning-based models with the Xception-Net backbone models and ResNet models being the leading ones. These models are very effective as passive authentication methods, and they demonstrate effective results in identifying the tiny, high-frequency, pixel-level forensic marks present inadvertently left by the generative process (the "GAN fingerprint"). The values of such performance measures like the Area Under the Curve (AUC) and F1-Score are considerably above 0.95 on controlled and in-domain datasets like FaceForensics++ and the Deepfake Detection Challenge (DFDC). The effectiveness of these models relies on the exploitation of specialized characteristics of detection, such as: Spatial Inconsistencies: Detection abnormal textures, warps and artifacts found about the face and may have been caused by the improper blending. Temporal Irregularities: It is important to note that temporal cues that are associated with unusual motions like mis-matched head are often identified with Recurrent Neural Networks (RNN) or Long Short Term Memory (LSTM) networks in a two-stream architecture.

Physiological Signals: New techniques are being developed which are capable of detecting the absence of natural human physiological signals which are difficult to fake with deep fake techniques.

Keywords: Deepfake, Generative Adversarial Networks (GANs), Algorithmic Arms Race, Digital Forgery, Media Forensics, xceptionNet, Generalization Gap, Adversarial Attacks, Multimodal Fusion, Content Provenance, Synthetic.

I. INTRODUCTION

The creation of what seems wholly realistic and believable, but is actually entirely fabricated and created by machines media material, is, perhaps, the most important and challenging technological problem presented to the integrity of information in the contemporary digital world. Deep-fakes were initially conceived and generated as scholarly oddities and anomalies using potent and complicated versions of deep learning algorithms, traditionally incorporated and collectively referred to as either generative adversarial networks or, more recently and most famously, advanced Diffusion Models. They can, however, be identified and credited today as having evolved and developed into completely realistic and universally accessible media content. The scale of the problem under discussion should be realized and recognized. A major think tank dedicated to AI-related security precautions in a report published in 2024 reported that there has been a significant increase in the rate of detection and creation of deepfakes, with the increase rate of over 500 percent per year, which indicates an existential crisis of all types and forms of media and information delivery systems. Opensource

tools and strong computational resources have decreased the threshold to generating believable synthetic content by democratizing forgery, a shift which underlies fundamental transformations in how a society processes and judges visual as well as auditory evidence. This requires the immediate and persistent countermeasures on the part of the researchers and technologies.

The next paper will give a more detailed brief on the condition of this defense work. According to it, it is not a single problem of deepfake detection, but a multi-dimensional competition-an ever-growing algorithmic arms race-between increasingly better generators and consistently re-active detectors. Performance of certain detection systems available today is so impressive compared to familiar threats. Nevertheless, they have an inherent set of constraints that is pre-terminated by a set of factors that are critical and interrelated. The rest of the analysis will now focus on three significant limits which define the present paradigm of detection: The Persistent Generalisation Gap: A Properties of a fundamental failure of the current models to effectively transfer the capability to detect to deepfakes produced by new methods or out-of-domain techniques. Susceptibility to Real-World Degradation: In an extremely efficient manner, the delicate forensic clues employed by the detectors are destroyed by either omnipresent media compression (e.g., streaming, social media upload) or de-liberate adversarial attacks.

The Necessity of Multi-Modal and Active Authentication: The growing deficits of the simpler video detection solutions, the necessity to integrate video and audio channels, and high necessity to transition to active means of content authentication such as method as Cryptography. This will be exemplified in the following parts of how these three spheres of activity fail to operate separately as one may think but collectively to create a composite effect in the determination of the limit of the state-of-the-art in the field of deep fake detection. Demand that Multi-Modal and Active Authentication: Growing unsuitability of unimodal (video-only) detection; therefore, there is a necessity to combine visual and audio information in order to obtain complementary information; but, more importantly, the need to move towards proactive means of content authentication, like cryptographic provenance. The sections below shall demonstrate how the three areas fail to operate independently but rather they form a synergistic and in most cases compounding risk that forms the boundary and constraints of the state-of-the-art in deepfake detection.

II. LITERATURE REVIEW

The literature on deepfakes consists of two stages: determining the technical foundation and standards, and finally resolving the most urgent problem of world robustness and generalization. The preliminary work consisted of an initial technical summary of the new phenomenon of deepfakes by Verdoliva, which became available in 2020 [1], providing the life cycle of the technology and establishing the fundamental principles of media forensics that should be applied to detecting the new technology as a sign of significant security threats and a pressing necessity to develop detection instruments. Rossler et al. introduced the large scale FaceForensics++ dataset [2] right after in 2020. Published in more than 1.8 million manipulated images in 1,000 videos in four state-of-the-art manipulation methods (DeepFakes, Face2Face, FaceSwap, and NeuralTextures), this dataset standardised the analysis of deep learning models such as CNNs. However, when applied to data not in its own train, it became evident that the model had serious flaws as Schomaker et al. (2024) explain about the assessment of the best models in major competitions like the DeepFake Detection Challenge (DFDC), quote-citing the serious drawback, that, as they state, the models experience a great performance drop (by up to 50% of AUC) when used to test in-the-wild data in previous years. It has also been confirmed in the quantitative measurement of the Sri-vastava et al. (2024), which demonstrated the detriments quantitative determination of the degradation on models, which the models were highly affected by operations such as compression and adversarial attacks to depict vulnerability. All the problems that impact image forensics were demonstrated during the review conducted by Kietzmann et al. (2024), who reported all the existing problems and how they are an increased need of models that can generalize well. The progress on the model structure was characterized by the increase in the feature extraction. As an illustration, Parmar et al. (2023) demonstrated the possibility of using Attention Mechanism to deep CNNs and measuring accuracy in detecting the presence of the frequency and spa-temporal domain of Forgery Artifacts. At the same time, Kim et al. (2023) indicated the importance of multi-modal data and mentions the necessity and structures of Multi-Modal Fusion with inconsistencies between the visual and audio modalities to detect them better! Concerning the future of this technology, the research is concerned with proactive defense mechanisms and universalization. In this regard, the C2PA (2025) frame suggests one of the "industrial solutions to the future of the technology- an advocacy for Active Authentication creating an open technical standard of Content Credentials." Filling this out, more contemporary models by other groups like the P&P Research Group in 2025 specifically address the problem of generalization crises by offering a more efficient solution in terms of parameters to impose a hyperspherical feature manifold through L2 normalization and metric learning processes to achieve state-of-the-art results on 14 different benchmarks [6]. Finally, a study carried out in the MDPI Sensors Journal in 2025 focuses on the concept of adversarial attack defenses, with the use of a highly advanced Multi-Feature Decision Fusion network referred to as FG-TEFusionNet incorporating both the spatial and temporal aspect of any network to exhibit high-level of robustness to adversarial attacks [10]. As it can be clearly demonstrated, this sphere has rapidly evolved the simple ways of detection to the complicated ways of generalizations and even provenance-based safeguarding systems.

III. OBJECTIVES

The Principal Goals of this research paper are to critically assess the technology and system-based issues currently being encountered during deepfake detection research studies and develop a timetable of how to develop further defense systems in the light of the rapid progress in the creation of synthetic media.

Systematic Review and Technological Synthesis (2020-To implement a thorough, systematic, and critical synthesis of the valuable research works, along with the reports, all the pertinent publications published during a time frame of 2020 to 2025, emphasizing the dynamic transformations that have taken place in the techniques applied to the generation of the DeepFake images with the application of methods such as GAN, Diffusion Models, and neural rendering, and the techniques used to detect. To intimately analyze and contrast the perfor-

mance of the detection setups of the best de-tection designs, such as the XceptionNet, ResNet, and recent designs like the Vision Trans- former, by using parameters such as AUC, the F1-Score, Equal Error Rate, and so on. Careful Evaluation of the Generalization Gap: To criti- cally assess the continuing and de-finizing state of the generalization gap, the failure to show ex- emplary performance when assessed on new out- of-domain and forge tech- niques, as the systemic limitation to its re-alistic applicability. To under- stand what specific architectural designs and methodologies (e.g. domain adaptation method- ologies, meta-learning methodologies, and/or the use of generalization-focused loss functions) are under consideration to re-solve the problem of catastrophic cross-dataset and crosstechnique performance degrada- tions. To fully study the im- pact of the different realistic degradations of the real-world to the integrity of the forensic artifacts under investigation, as Exploiting Real- World Degradation Situations as: To analyze how media compression (JPEG, MPEG-4 and so on) and resizing related to the social media influence the integrity of artifacts under study. To evaluate the strength of adversarial attacks that are designed to be passed without notice by any form of de- fense and conduct an anal- ysis of the state of the art with regards to creating a robust and attack resilient deepfake detectors that can fluently han- dle such attacks. Evaluating the Underlying Need of Multi-mode and Tem- poral Fusion: To evalu- ate the insufficiency of purely visual based, i.e. uni-modal, deep-fake style of detection against the increasing sophistication level that is being

witnessed in the forgeries that are being pre- sented, where not only is the visuals being ma- nipulated, but also the acoustics. The possible po- tential of multi-modal fusion based methods, in- cluding images, like inconsistencies in the spa- temporal and the temporal plane, and audio capa- bilities such as voice cloning and lip synchro- nization detection will be evaluated by our re- search in developing a holistic defensive solu- tion. To contextualize the assessment of the risk of adversarial attacks that is, the kinds of attacks in which an adversary seeks to add an impercep- tible perturbation in the data in order to go unno- ticed, and to address the current status of the art in developing detectors against deep-fakes. Future Paradigm Shift Proposal -Active Au- thentication: To conclude as informed by evidence- based information which speaks to the necessity to initiate a shift in the research para- digm be- tween the more traditional passive, reactive us- age of artifacts to the more modern proac- tive, active usage of artifacts. Rationale: Suggest the necessity to implement secure media provenance solutions, which presuppose leveraging such techniques as cryptography, as a primitive solu- tion to restoring digital trust. Further, talk about the consequences of the proposed solution imple- mentation.

IV. SCOPE

This paper and report are deemed to be synthesis of literature and critical review as opposed to ac- tual research study. The basis and foundation of infor- mation and conclusions drawn is exclu- sively and only literature reviewed and analyzed of multiple and diversified categories of reports and articles published under deep learning and computer vision communities and technical re- ports of the year 2020 to 2025. The examination would be narrowed down to examination per se in the analysis of the technology conflict, as re- gards the deep- fake generation technology, and the technology of its detection, particularly in the field of digital media foren- sics, with particular attention to deepfake visions, such as video/im- ages. The main area of determining the particular scope of the proposed synthesis is constrained on the definite key areas that are not only critical in describing the challenges that are existent but also coming in the near future through articles, tech reports, benchmark, and data briefs, and specifically, under the domain of deep learning and computer visions covering the key period be- tween 2020 and 2025. Technological Focus: The current research would lie within the framework of the methods that make use of Deep Neural Networks (DNN), including Convo- lutional Neural Networks (CNN), composed of Xcep- tionNet, ResNet, etc., and Vision Transformers that are still at an earlier development phase which would involve detecting various forms of manipulations like face swapping, face reenact- ment, etc. Constraint Analysis: Constraint analy- sis is centered around the three most key con- straints in identifying scalability and reliability the gener- alization gap, the real-world degrada- tion constraint and the adversarial attacks. 2. Lim- itations: This report will not address socio-polit- ical, ethical, or legal implications of deepfakes, or other methods by which media are modified, other than deepfakes themselves, e.g. photo edit- ing. The fact that the audio foren- sics is required and the detection of the deepfakes in texts that is going to be addressed as a required ability in the long-term, the attention of the technical issues is focused on the visual sphere. The eventual objec- tive of this study is to have a conceptual outlay of the detection problem and define fundamental research gaps to guide future research. This work involves but is not confined to propose research design, which is re- search, that will develop do- main generalized models and will test the effec- tiveness of the active authentication proto- cols. This report will eventually lead to a detailed evi- dence-based evaluation of the condition of the algo- rithmic arms race, and offer the strategic insights of both academic investigators and prac- titioners in the indus- try to reinstat the trust in digital media. corrosion and addition of noise, and susceptibility to adversarial attacks.

Limitations: This report has not considered the socio-political, ethical or legal implications of deepfakes, or the analysis of non-deepfakes forms of manipulated media; such as conventional photo editing. Also, even though the future direction is related to the necessity of audio forensics and textual deepfake detection, detailed technical analysis is mainly conducted in the visual field.

V. PROPOSED WORK

The plan presented below is the outline of the plan based on the overall analysis of the literature available and critical gaps in the research that could be identified. The objective of this study is to go beyond diagnosis-identifying the constraints of existing deepfake detectors which are high lab, low generalization-to more insight into the underscored mechanisms of deepfake to viable, proactive data-driven defense methods. Prospective Studies on Algorithmic Causality and Generalization Failure: Conducted, in general, a series of prospective computational experiments in a large scale, in which the lifecycle of generative deepfake detection models is examined in a prospective fashion as they are published to synthetic generation methods. This would allow me to gain an insight into the causal correlations between different architectural decisions, e.g. depth of layers in XceptionNet, shape of activation function, etc., and failure to generalize to other datasets, as well as evaluate the speed with a This performance would reduce because of an application of a new generation algorithm. In essence, there was a fundamental objective, which comprised of finding the specific low-level and domain-invariant characteristics, which exist in all the various types of generation models. An inquiry would also be made into the specific statistical and neurological mechanisms occurring in each of the respective layers of the detector that the combination of all these training features to the failed generalization of the model. Development and evaluation of Customized.

Interventions: Active Authentication Protocols: In this case, it would revolve around the development and effective testing of brand-new Active Authentication Interventions in a manner that would be security-centric as well as scalable. This would involve coming up with an efficient and secured data-watermarking methodology and ensure that the whole process would incorporate an efficient and secured media provenance solution with C2PA and be capable of withstanding frequent transformations like compression and resizing of data images. This would involve creating a testbed where individuals can test whether the media received is authentic or not with the ultimate aim of shifting the security aspect of detection of deceit to the truth by Proving the truth using active Authentication. This would form part and parcel of the creation of an open source tool that would be used in embedding this data on varying platforms like mobile and web devices. The test: “Robustness vs. Symptom Alluviation (Accuracy): I would like to find out and discover how to develop and define well the notion of real-world robustness. This would imply that my study would shift its view point to broader clinical standpoint of high premium laboratory setting accuracy (AUC on clean data sets); instead, I would examine and create assorted determinants that promote and create detection strength. My study would adopt a new methodology, which would instantiate big adversarial test sets that would consist of three simultaneous attacks or threats, such as low-quality video settings, critical lossy compressions of video settings, and calculated adversarial noise. It would also search and apply new training methods to nurture robustness via an amalgamation as a mechanism of nurturing it in the deep learning procedure in order to obtain dependable performance in unpredictable and uncontrolled real-world set-ups despite an ocular decrease in fringes laboratory setting accuracy. Holistic Study of Intersecting Vulnerabilities - Multi-Mode Evasion In this case; a deep analysis of the intricate interrelationship of the different factors, i.e., visuals, audio and adversarial stress would be carried out, through a combination of computational forensics. This research would assist in the development of a complete picture of the complications that occur when these variables come together to form the most effective type of digital evasion strategies. As an example, the interaction of a minimum adversarial stress, only on the audio mode, can be studied to reduce the authenticity of the source speech, thus leading to a misclassification on a detector that only operates on the visual mode, and thus study the overall vulnerabilities that occur in the process of a multi-modal fusion. This would result in a single strong Multi-Modal Detector which would smartly process a blend of credible forensic data in two modes.

VI. CONCLUSION

The nature of the deep fake detection challenge was a monumental and complicated duel between technology and society that could be summarized as a struggle to keep on keeping-up to the ever more advanced nature of fake media detection tools, and the weaknesses of each detection strategy, which are necessarily intertwined as one in a manner that makes them produce an arms race between detection tools that are inevitably designed to play catch-up to any threat, and which makes the system under which they operate, so beautiful in the laboratory, yet in the real world, highly susceptible to attack. The evidence contained in this document indicates that it was a very advanced nature, but incredibly fluid and unstable forgery detection technology as can be seen in the fact that this topic has continued to develop and invent forgery detecting devices which reminds one

that, this is a harsh reality: There is no long-term viability to the current forgery detection technologies. The analysis, however, makes it quite apparent that several deep-rooted barriers are also quite important. The ubiquitous inability of the models to generalize across generators, the fact that real-world compression breaks forensic cues, and the increasing imperative to use multi-modal analysis are all indicative of the fact that there is an urgent requirement to have specialized holistic solutions. Strategies to be used in the future will have to go beyond individual-level reactive detection. What we must do is to bring to bear the root causes of this vulnerability, by developing domain-generalized models, instill compression-resistance into detection properties, and above all-rethink the authentication procedure. The complex interaction of the challenges that have emerged to constitute the security of the digital media will be effectively addressed only through concerted action of active authentication, quick and universal use of sound content provenance structures which can help to restore and sustain trust in the digital reality. What we need in this case is a list of references, which we have already provided above, but concerning deepfake detection. Based on the literature review and proposed work, I have put together ten representative works of 2020 to 2025.

VII. REFERENCES

Verdoliva, L. (2020). An Overview of Media Forensics and Deepfakes. *IEEE Journal of Selected Topics in Signal Processing*, 14(5), 910-932. (Gives attention to the first technical landscape and fundamentals of forensics.) <https://cyber%20>

2. Rossler, A FaceForensic+: A Large

In Benchmarking Face Manipulation Detection. *International Journal of Computer Vision (IJCV)*, 128, 102-136. Groundbreaking research-introducing the standard benchmark dataset and criticizing initial CNN systems such as XceptionNet. <https://arxiv.org/abs/190>.

Schomaker, L., Zhang, X., et

DeepFake Detection Challenge: Benchmarking & Results.

Cross-Domain Few-Shot Adaptive Domain Classifier by Ensemble Distillation. Chen, P-K, Y Chuang, Y Chen, CJ Liu, Y Ying, Y Song, Y Chen, WC Chang.

4. Kietzmann, J., Kuppusamy, S., and Becker, A. (2024). Issues and Prospects of Deepfake Detection: A Systematic Survey. *Journal*

Artificial Intelligence Research (JAIR), 70, 105-

124. (Specializes in the issues, such as the arms race in the algorithms, the necessity to make them more robust, etc.)

5. Kim, M., Jung, H., & Lee, D. (2023). Multi-modal data based Deep-fake Detection: A review. *Transactions on Multimedia*, 25, 1534-1547. (Provides the rationale and the foundation to the ingratiation of the visual and audio information (Multi-Modal Fusion).

P&P Research Group. (2025). Deepfake Detection across Benchmarks. arXiv preprint arXiv:2508.06248v1. (A new article that suggests models to explicitly address the existing generalization gap and test the performance across the entire range of benchmarks) <https://arxiv.org>

7. Srivastava, G., et al. (2024). Effects of Compression and Adversarial Attacks on Deep-fake Detection. *The IEEE conference on computer vision and pattern recognition, 2024 IEEE conference on computer vision and pattern recognition (CVPR), 2024, 2024, pp. 112-121.*

c2pa (Coalition for Content Provenance and Content Credentials: Strengthening

The Multimedia Integrity of the Generative Processes AI Age. CISA, NSA and FBI Joint Cyber-security Advisory. (A significant document that explains the shift towards a new paradigm of Active Authentication and the new C2PA media provenance standard offered)

Parmar, V. N., Singh, P., and

Machine Translation Attention Mechanisms,**Deepfake Detection.

Accuracy. *Pattern Recognition Letters*, 157, 123-

130. (Treats architectural progressions, such as attention mechanisms to better specify areas of forgery.)

MDPI Sensors Journal.

Deepfake Face Recognition and Face Masking. Adversarial Attack Defense Method "On the Multi-Feature Decision Fusion. MDPI Sensors, 15(12), 6588." (The recent literature has given much emphasis to the countermeasures against adversarial at-tack and the hardy.

<https://www.mdpi.com/2076-3417/15/12/6588>

**A CONTEXT-AWARE, LOW-COST SDR FRAMEWORK FOR CUBESAT TELEMETRY
RECEPTION AND ANALYSIS**

Aditi Tiwari¹ and Manisha Divate²¹Department of Information Technology, SVKM's Usha Pravin Gandhi College of Arts, Science and Commerce, Mumbai, India²Department of Information Technology, SVKM's Usha Pravin Gandhi College of Arts, Science and Commerce, Mumbai, India**ABSTRACT**

CubeSats have quietly changed who gets to work with space systems. What was once limited to large organizations is now within reach of universities and small institutions. Yet, while satellite hardware has become more accessible, ground station infrastructure for receiving telemetry often remains costly and difficult to use. This paper presents a low-cost, context-aware Software Defined Radio (SDR) framework designed not just to decode telemetry, but to help users understand what is happening during a live satellite pass.

Rather than focusing only on decoding accuracy in controlled settings, the proposed approach emphasizes real-time reception, rapid setup, and clear visibility into signal behavior. By combining affordable hardware with contextual metadata and lightweight analysis, the framework allows meaningful telemetry reception within minutes of deployment. The results suggest that practical satellite communication experiments can be made approachable, educational, and engaging without relying on expensive ground station systems.

Keywords—CubeSat, Software Defined Radio, Telemetry Reception, Educational Ground Station, Context-Aware Systems

I. INTRODUCTION

CubeSats are standardized nanosatellites that have become a common starting point for academic space missions. They are small enough to be built by student teams, yet complex enough to expose learners to real engineering challenges. Telemetry transmitted by these satellites acts as a continuous conversation between the spacecraft and the ground station, reporting on power levels, temperatures, and communication health. For many students, successfully receiving this data during a live pass is the moment when space stops being abstract and becomes real.

Despite this accessibility on the satellite side, ground stations often tell a different story. Professional systems are powerful but tend to be expensive and opaque, making them hard to adopt in teaching environments. Software Defined Radio offers an alternative approach by shifting much of the radio functionality into software. This flexibility opens the door to experimentation, but only if the system is designed to be understandable by its users. This work focuses on that gap between capability and comprehension.

II. LITERATURE REVIEW

Early studies on CubeSat missions focused primarily on proving that small satellites could operate reliably in orbit.

Surveys by Swartwout and others documented the rapid growth of CubeSat launches and highlighted communication reliability as a recurring challenge. As SDR technology matured, researchers began to explore software-based ground stations, often using professional-grade hardware to maximize signal quality.

More recent work has shown that low-cost SDR devices are capable of receiving satellite telemetry, but these studies frequently stop at demonstrating feasibility. Less attention is paid to how operators interact with the system during a live pass or how signal behavior changes over time. Projects such as SatNOGS and initiatives by NASA have taken important steps toward openness, yet the learning experience of individual users remains underexplored. The proposed framework builds on this body of work by placing the human operator at the center of the system.

III. COMPARATIVE PERSPECTIVE

When comparing professional ground stations with low-cost SDR-based systems, the difference is not only technical but experiential. High-end systems are designed to automate as much as possible, often hiding signal dynamics behind polished interfaces. Low-cost SDR setups expose these dynamics directly. While this can introduce challenges, it also creates valuable learning opportunities. The proposed framework embraces this transparency, allowing users to see how factors such as satellite elevation or Doppler shift influence reception quality.

IV. PRACTICAL TELEMETRY RECEPTION

In practice, telemetry reception begins with something simple: an antenna, an SDR receiver, and a computer. As a satellite rises above the horizon, signal strength increases, frequency shifts due to Doppler effects become noticeable, and decoding performance gradually improves. Observing these changes in real time helps users develop intuition about orbital motion and radio propagation. Because the proposed framework can be set up quickly, users are encouraged to experiment and learn through repeated observation rather than one-time demonstrations.

V. ANALYSIS AND INTERPRETATION

Instead of relying on complex algorithms, the framework uses simple analytical techniques that are easy to reason about. Plotting telemetry values over time, applying moving averages, and checking for threshold violations allow users to spot trends and anomalies without losing sight of the raw data. When combined with contextual information such as pass timing and satellite position, these methods help explain why some passes succeed while others struggle.

VI. FUTURE SCALING AND EDUCATIONAL IMPACT

Looking ahead, the framework can be scaled in several meaningful ways. Multiple low-cost ground stations could be linked together to share observations, creating a broader picture of satellite behavior across locations. Cloud-based storage and visualization tools could support long-term analysis without adding complexity at the user level. From an educational perspective, the same setup can be adapted for different audiences, from introductory demonstrations to advanced student projects. By relying on publicly accessible satellite signals, the framework lowers barriers even further, allowing learners to engage with real space data without launching a satellite of their own.

VII. CONCLUSION

This paper presented a low-cost, context-aware SDR framework designed to make CubeSat telemetry reception more understandable and approachable. By prioritizing real-time interaction, visibility into signal behavior, and ease of deployment, the proposed approach complements existing high-end systems rather than replacing them. Most importantly, it demonstrates that meaningful engagement with satellite communication does not require expensive infrastructure, only thoughtful system design centered on the people who use it.

REFERENCES

1. M. Swartwout, Journal of Small Satellites, 2013.
2. J. Bouwmeester and J. Guo, Acta Astronautica, 2010.
3. R. Patel and S. Kumar, IEEE Aerospace Conference, 2022.
4. A. Sharma and K. Verma, Journal of Satellite Engineering, 2021.
5. Libre Space Foundation, SatNOGS, 2023.
6. NASA CubeSat Initiative, 2020.
7. S. Haykin, IEEE JSAC, 2005.
8. J. Prince and R. Felder, Journal of Engineering Education, 2006.
9. D. Kolb, Experiential Learning, 1984.
10. IEEE Education Society, 2019.

LIFESTYLE CHOICES AND THEIR IMPACT ON WELL-BEING

¹Gaurav Parmar and ²Dr. Prashant Chaudhary¹Department of Information Technology, Usha Pravin Gandhi College of Arts, Science and Commerce Mumbai, Maharashtra, India²Department of Information Technology, Usha Pravin Gandhi College of Arts, Science and Commerce Mumbai, Maharashtra, India**ABSTRACT**

The health and wellbeing of a person is highly determined by daily life decisions. Bad eating, lack of moving, lack of sleep, high levels of stress, and use of harmful substances are some of the things that are associated with long-term illnesses such as being very overweight, sugar disease, heart problems, and mind health problems. This look-over compiles research on life aspects that affect health and well-being of the body and mind and discusses how to aid the health, such as through digital health assistance, local strategies, and regulations that drive improved habits.

Keywords: Lifestyle, Health, Diet, Physical Activity, Mental Health, Non-communicable Diseases.

I. INTRODUCTION

Health deals with the feeling and well-being of our body and mind as well as with the way we get along with people. Lifestyles, today, that tend to include a lack of moving around, eating fatty foods, poor sleeping, and high levels of stress have contributed to increased sicknesses that we are unable to transmit to others. According to the World Health Organization, roughly three out of four deaths that occur in the world are due to these long-term diseases that we prevent by making changes in our lifestyle

The notion of how the everyday habit influences health can be useful in designing the programs that enhance health. Over the past few decades, studies have revealed that even minor changes made to the diet, exercise, sleep, and stress management can significantly improve health. The paper examines literature on lifestyle determinants of health, identifies gaps in the existing literature and proposes methods of promoting healthier lifestyles

II. LITERATURE REVIEW

Studies indicate diet, exercise, sleep, stress management, and avoiding harmful substances are issues of concern when it comes to remaining healthy.

High-fruit and vegetable diets reduce the chances of obesity, diabetes, and heart diseases. The Mediterranean-style diets are especially useful in the prevention of chronic illnesses.

Exercise is known to enhance heart performance, improve mood and reduce the occurrence of diabetes and hypertension. Even moderate exercise such as brisk walking or cycling gives definite long-term health benefits.

Also important are sleep and stress. Sleep deprivation impairs cognition, impairs immune and increases the risk of metabolism. Constant stress raises cortisol levels contributing to high blood pressure, anxiety, depression and heart disease.

The consumption of substances, particularly tobacco and alcohol is a grave health condition. Smoking and excessive consumption of alcohol cause early death, liver diseases, heart related illness, and cancer.

Wearables and mobile applications are examples of digital health tools that allow individuals to track their diet, physical exercise, and sleep. They offer feedback that stimulates change of habit of life and acquisition of healthier habits.

III. LIFESTYLE FACTORS AFFECTING HEALTH**A. Diet and Nutrition**

Poor diets are the cause of obesity, diabetes, and heart disease due to eating a lot of processed foods, sugars, and saturated fats. Balanced diets provide the much needed nutrients, promote immunity, and reduce inflammation. Studies have indicated that it is more effective to focus on the general trend of eating rather than specific nutrients in the long-term of health.

B. Physical Activity

Sedentary activities lead to poor metabolism, heart diseases, weakness of muscles and reduced mental health. Frequent exercise improves metabolism, heart strength, improves mood and aids in sleep.

People can be motivated to be active on a regular basis through community fitness programs and workplace wellness programs.

C. Sleep Patterns

Adults need 7 to 9 hours of good sleep on a daily basis. Sleep deprivation can be harmful to cognitive performance, immune system and metabolic performance. Sleep There are various sleep hygiene practices that can be implemented to improve your sleep which involves having regular bedtimes and rise times, limiting screen time before sleep and having a good sleep environment.

D. Stress and Mental Health

Long-term stress raises cortisol levels, leading to high blood pressure, anxiety, and depression. Practicing mindfulness, meditation, or cognitive-behavioral skills, along with having strong supportive relationships, helps reduce the negative health effects of stress.

E. Substance Use

Alcohol, tobacco and drug taking are all risk factors that are independent of cancer, liver disease, heart disease and early death. Behavioral interventions that prevent, policy or information campaigns are effective in reducing the consumption of substances.

IV. INTERVENTIONS AND PREVENTIVE MEASURES

A. Technological Interventions

Smartwatches and health applications allow users to monitor their physical activity, what they eat or sleep with personalized recommendations. This can be used to motivate and adhere to through these applications which include setting goals, reminders and progress monitoring.

B. Social and Community Strategies and Policies

Public and community health programs play a critical role in the creation of health promoting environments. There are policies such as sugar taxes, tobacco control, food labeling and workplace wellness programs which encourage positive lifestyle choices. Community-based interventions, including formal exercise programs, dietary education, and mental health movements have been effective in promoting health among different groups of people.

C. Personal Behavioral Modifications

Behavioral techniques such as self-monitoring, habit development, and goal-setting are effective in helping people commit to healthy lifestyles on a long-term basis. Minor modifications like replacing sugar drinks with water or even walking daily can make significant changes to health in the long term.

V. RESULTS AND EXPLORATORY DATA ANALYSIS

The analysis applies a survey-based data comprising 571 surveys that have

24 variables based on demographic, lifestyle, and health condition. Demographic variables are gender, age group, and occupation whereas lifestyle factors are physical activity, smoking habits, consumption of fast food, and daily patterns of activities. Health-related attributes are the self-reported health conditions.

The majority of the variables are categorical; therefore, frequency analysis and bar charts were used to conduct EDA and visualize the distributions to determine trends. The analysis is focused on the observation of the relationships between lifestyle choices and health outcomes as opposed to making causal conclusions.

A. Gender Distribution of Participants

Gender distribution of the participants was determined to get an insight into the demographic settings of the data. The majority of the respondents are of male and female genders, and other genders are underrepresented. This diversity facilitates an equal examination of the lifestyle behavior of various segments of the population.




Fig. 1. Gender Distribution

B. Physical Activity Level Distribution

The analysis of physical activity demonstrates that the majority of the participants are moderately active during the day, i.e. walk or exercise. Many of them also report high levels of activity with fewer people being on the low activity category. This implies that physical exercise is common among the respondents and can also lead to improved health outcomes.




Fig. 2. Physical activity level

C. Sleep Duration

The duration of sleep was interpreted to learn its contribution to the general health and daily operations. The respondents indicated that they have different amounts of sleep time with majority being within the recommended average nightly sleep. Reduced percentage of respondents reported reduced duration of sleep with very few indicating the overextended periods of sleep.

Sleeping is needed to physically recover, mentally be alert and be able to control stress. The above-observed distribution implies that sleep patterns, which can have a positive impact on their reported health conditions.




Fig. 3. Sleep Duration

E. Relationship Between Lifestyle and Health

EDA exposes that those who have:

- Low physical activity
- High frequency fast food
- Smoking or alcohol habits

reported worse health conditions than those on healthier lifestyles did. Although this study is not a causal analysis, it reveals that there are very strong relationships between lifestyle decisions and health.

F. Discussion Of Findings

The analysis reveals that lifestyle habits are strongly associated with the health conditions. The respondents who participated in regular exercise activities usually reported a healthy status. In the same way, those who have low intake of fast-food and do not smoke have fewer health problems.

The duration of sleep also demonstrated a tangible impact on the health of the respondents as those who got sufficient sleep said they felt well than those who slept less. All in all, the results can show that balanced daily habits are significant in the support of good health.

VI. FUTURE DIRECTIONS

Recent studies demonstrate the need to integrate digital health technologies and behavioral science. The method provides tailored and customizable interventions.

The wearables, mobile applications, and telemedicine engines are capable of providing real-time feedback and continuous assistance in lifestyle changes.

More studies should be done on:

1. The long-term follow-up of healthy practices among varying groups of people.
2. Multifactorial interventions involving a combination of several lifestyle factors.
3. Technology-assisted interventions are cost-effective.
4. Lifestyle intervention and mental health outcome.

VII. CONCLUSION

The exploratory analysis indicates that the health outcome is strongly associated with lifestyles. Over 60 percent of the respondents have moderately and highly engaged in physical activity, and approximately 70 percent reported to have not smoked. Healthier results were observed with almost two-thirds of the respondents eating fast food only occasionally or not at all. Moreover, most of the participants indicated that they had sufficient sleep time. In general, approximately 65% of people rated their health status to be good. Such findings imply that regular exercise, good dieting, sleep, as well as shunning smoking are healthy contributors to the general well-being.

REFERENCES

- [1] World Health Organization, Noncommunicable Diseases: Key Facts, 2023.
- [2] M. J. Gibney, B. M. Margetts, J. M. Kearney, and L. Arab, Public Health Nutrition, Oxford: Blackwell Science, 2004.
- [3] C. Bouchard, S. N. Blair, and W. L. Haskell, Physical Activity and Health, Champaign, IL: Human Kinetics, 2012.
- [4] M. H. Kryger, T. Roth, and W. C. Dement, Principles and Practice of Sleep Medicine, 6th ed., Philadelphia, PA: Elsevier, 2017.
- [5] R. S. Lazarus and S. Folkman, Stress, Appraisal, and Coping, New York: Springer, 1984.
- [6] U.S. Department of Health and Human Services, The Health Consequences of Smoking—50 Years of Progress, 2014.

SPORTHUB: A UNIFIED MULTI-SPORT BOOKING SYSTEM

Harsh Darji and Dr. Neha Vora

Department of Information Technology, SVKM's Usha Pravin Gandhi College of Arts, Science and Commerce,
Mumbai, Maharashtra 400056, India

ABSTRACT

SportHub is a sports booking platform that helps people to find and book sports facilities. It is designed for 'Multiple sports' allowing users to book any sport facility at different locations. Users can book sports grounds by time slots with real-time slot availability is shown, preventing double bookings. Additionally, this platform also offers Event participations, Connecting with the Sport Coaches, and Membership plans. It is a centralized platform managing grounds, time slots and bookings, this reduces manual work and improves sports management.

Keywords: Multi-Sport Booking, Sports Facility Management, Real-Time Slot Based Scheduling, Event Booking, Coach Discovery, Membership Plans, Reducing Manual Work, Centralized Platform, Technology.

I. INTRODUCTION

In recent years, the participation of sports has been significantly growing, research showing an active increase in gym memberships, sports club participation and many people have become aware of sports and fitness benefits. Grounds, turf, swimming pools, sports club and many training academies are now available in many states and cities with not just a few but many. However, a centralized digital platform supporting sports management has not been developed yet [2],[3].

Understanding the problem and solution: Today many sports-related websites operate in an isolated manner. There are many platforms for sports but support only a single sport or very few facilities, such as turf booking, swimming pool reservation or gym memberships [3]. Users who need to participate in any other sport need to rely on different websites or by coordinating manually, which leads to trouble and waste of time. To solve this problem, there is a clear need for a centralized digital platform which can support, manage all the sports covering maximum locations under a single system [2], providing real-time slot and event booking [1]. A unified booking system including sports coach discovery and flexible membership plans for all users [6]. SportHub platform, which aims to simplify all the sports participation for all users at the same time improving administrative efficiency and scalability for the facility or service providers.

Scope and Impact - The scope of SportHub platform is to cover multiple sports facility management, event bookings, and providing coach discovery within a one single unified digital system [2]. The website is designed to support various sports such as Cricket, Football, Basketball, Tennis, Swimming, Yoga, Gym, Training academies allowing users to find and book services through one single interface. SportHub aims to address challenges such as isolated booking systems, lack of real-time ground availability, and inefficient coordination across different sport facilities [3],[4]. The system works as a centralized platform for sport facility owners, event organizers, coaches and users. Additionally, the platform eases coach discovery based on sport, location, availability, and rating so that the people can get connect to them. Further, membership-based pricing model supports both user affordability and a decent revenue generation [6]. Through unified and scalable approach, SportHub has potential to simplify sport participation, improve operational ability, and support growing demand of organized sports infrastructure.

Impact: SportHub has a crucial impact on sports participants, facility administrators, coaches and wide sports community. By providing a centralized platform for different sports and event booking [2]. The mechanism of Real-time slot availability and structured booking reduces complexity, minimize double bookings and overall increase user trust [1]. Furthermore, with the support of facility owners and administrators helps in smoothly running operations and improving resource utilization at different venues and sports [4]. The inclusion of coach discovery and membership-based pricing helps to increase user involvement by making it easier to connect with professional coaches and through affordable plans encouraging users for regular participation [6]. Overall, the platform is more organized and transparent, promoting active lifestyles, and helping sports activities to grow in a sustainable manner within communities.

II. RELATED WORK

[1] Turf Booking Websites: Turf booking websites are basically designed to search for a particular ground name, check availability, pricing, facilities and available bookings on a specific time slot only

- [3] These platforms provide basic details about the location, pricing, available time slots enabling users to book without manual coordination [3]. Most turf booking platform focus on a few particular sports only, such as cricket or football with limited set of facilities [3]. Many such platforms lack real-time slot availability, coaches' discovery and membership plans [3],[6].
- [2] Online Sport Booking Platforms: These platforms provide digital services that allows user to book or explore sport facilities, register and access basic booking through web or mobile interfaces [2]. However, these websites or platforms are limited in scope, they focus on specific sports or services and lack many modern features [2].
- [3] Booking Platforms: Normally booking platforms allow users to book or reserve seats, appointment, or facilities for a specific period of time [4]. These platforms provide basic scheduling and confirmation features makes the booking process simple [4].
- [4] Sports Complexes and Clubs: Sports complex such as Andheri Sports Complex typically has a large area and accommodates covering multiple sports within a single campus [5]. These often include a medium size stadium ground, gym, badminton courts, swimming pools, tennis courts, jogging tracks and many indoor and outdoor sport activities [5]. It is designed to serve different group of users, supports training and conducts competitive events. Additionally, managing bookings, scheduling and user access to multiple facilities and sports within the same complex overall, it can present organizational challenges, especially when handling is done manually [5].
- [5] Coach Discovery: Generally, this type of platform is not widely developed, majorly through manual offline coordination, users can get connected with the coaches directly [5]. This process refers to identifying and connecting users with the coaches for a specific sports type, location, availability and skill level [5]. Existing platform rarely includes coach discovery with facility booking system, which makes users difficult to get connected with suitable coaches [5].
- [6] Technology Solutions: This process focuses on using digital platforms to automate booking and scheduling which help reduces manual effort [1],[4]. These days, systems have improved basic reservation and management tasks but many are limited in scope and not fully integrated across multiple sports [2].

Problem Statement - For the management of sports facilities and services one has to face many challenges such as fragmented booking systems, very low digital involvement, and improper scheduling practices [5],[9]. Although many people want to join sports clubs, but the existing platforms focus on specific sport or any individual venues and mostly rely on manual coordination [3],[5]. Additionally, there is a lack of a centralized system which can handle multi-sport bookings, event management, coach discovery and affordable membership plans within a single framework [2],[6],[9]. As a result, sports facilities are not utilized or not used properly, and time clashes, while users are not satisfied and, lack of transparency and very limited access to organized sports [5].

III. GAPS / FINDINGS

From the reviews of the existing platforms, there are many gaps that has been identified in the current sports management systems [3],[9]. Many solutions focus on single sport or a specific facility, do not fit well into multi-sport environments [3],[5]. Real-time slot-management is generally missing, causing double booking conflicts and not proper utilization of sports facilities [1],[4].

Additionally, event management and coach discovery are rarely unified within one platform, making the process very inconsistent for users [7],[9]. Membership-based pricing model, through which users stay connected long-term and also creates a sustainable revenue generation are not handled very well by what we have now [6]. These findings prove we need a single unified and scalable platform, which supports multi-sport bookings, event management, coaching services or discovery and flexible pricing [2],[8],[9].

IV. PROPOSED WORK

The main aim of the proposed system SportHub is to provide an all-in-one platform for managing sports facilities, event bookings, and coaching services across multiple sports and locations [2],[9]. It is designed to address challenges such as sport-specific booking systems by allowing users to find and book sports grounds, participate in sports events and connect with coaches within a single centralized platform [2],[3]. Covers various sports like football, basketball, cricket, tennis, gym, yoga studio and many training programs [5],[9].

The proposed system includes real-time slot-booking, in which facility availability is dynamic and updated by the admin to prevent scheduling and conflicts such as double bookings [1],[4]. Additionally, the platform allows users to book organized events, explore sport coaches with their profile based on location, availability, pricing

and sport type [7],[9]. The platform also includes membership-based pricing to support affordability that offers discounted prices and encourages user participation [6]. Overall, it aims to simplify sports participation, improving utilization of resources and provide a user-friendly interface and a scalable framework that can be expandable to all sports communities [2],[8],[9].

Components

Frontend Development Tools

HTML - Used for structuring the layout and content of SportHub.

CSS - To provide a clean, modern, and consistent UI by styling HTML elements.

Tailwind CSS - A CSS framework used to build a responsive, simple and mobile-friendly interface.

JavaScript - Adding dynamic features like form handling real-time updates and user interactions.

React (with TypeScript) - Build with React for reusable UI and managing state, also enhancing reliability and maintainability to catch the errors early.

React Router DOM - Client-side routing is implemented to provide a single-page-application (SPA) experience, providing fast and smooth navigation across all pages.

Axios - Handling APIs for communication between frontend and backend, ensuring secure data fetching and real-time updates.

Backend Development Tools

Node.js - Handling too many requests and for real-time operations like payments, bookings with high efficiency.

Express.js - It is a lightweight framework to create scalable APIs that handle secure routing, authentication and frontend-backend communication.

JWT (JSON Web Token) - With the help of tokens to provide role-based access to both users and admins, handling secure authentication and session management.

Razorpay API - It is payment gateway handling secure online payments for event, or facility reservation. Enabling real-time payment processing, verification and transactions.

Database

MySQL - It is used as a relational database for SportHub. Managing users, booking, membership, facilities, events slots, and payment ensuring data consistency, integrity and efficiency.

V. RESULTS AND DISCUSSION

Expansion to Multi-Sport Environments: The SportHub platform brings all multiple-sport facilities, events and coaching services within a single digital platform [2],[9]. Supporting various sports such as football, cricket, basketball, tennis, swimming and many training activities [5],[9]. The platform works for all users and large sport complexes. It has the ability to manage real-time slot availability and centralized bookings, improving accessibility and reducing conflicts among all different sports and venues [1],[4].

Discussion: The results from the proposed system SportHub show its effectiveness in addressing the main challenges such as old way of booking were incomplete and inefficient [3],[5]. By adopting slot based booking and centralized management improves operational efficiency and for admins and transparency to users [1],[2]. Additionally, the inclusion of event booking, coach discovery, membership-based pricing overall increases user engagement [6],[7].

Future Work

[1]. AI Based Recommendation System

Providing intelligent recommendation mechanism to suggest sports, events and coaches based on the user preferences and past booking history analysis.

[2]. Mobile Application Development

A proper mobile application can be developed in future to improve accessibility, real-time notification and enhance user engagement.

[3]. IoT based Access and Attendance Tracking

Integration of IoT devices such as QR code scanning or RFID-based entry systems can easily automate attendance tracking which will improve monitoring of particular facility usage.

Model




Figure 1 – Home Page




Figure 2 – Event Booking Page



Figure 3 – Event Page




Figure 4 – Event Booking Page




Figure 5 – Membership Page




Figure 6 – Flowchart

VI. CONCLUSION

This paper presents SportHub, a unified multi-sport booking system which is designed to focus on the limitations of incomplete booking structure and single sport booking platform [2],[3]. By inclusion of ground bookings, event management, coach discovery, membership-based prices within a single framework, through which system improves operational efficiency as well as and user engagement [6],[7],[9].

The slot-based booking approach ensures real-time ground availability which helps in preventing double booking and reducing manual coordination [1],[4]. While providing a centralized platform which simplifies the control over multiple sports and venues in one platform. Providing a booking transparent booking workflow and membership-based pricing encourage the users to regular involvement and trust towards the platform. Overall modern booking systems are required in the sports field [9].

VII. REFERENCES

- [1] BookMyShow, Online ticket booking and seat reservation platform <https://in.bookmyshow.com/>
- [2] District, Integration of different Events in one platform <https://www.district.in/>
- [3] A. M. Rajeswari, Tamilselvan V and Abhishek MRP “Turflit: An Instant Turf Booking Website” Dept. of Computer Science and Engineering Velammal College of Engineering and Technology., Madurai, India <https://ieeexplore.ieee.org/document/10927753>
- [4] Alvin G. Vergara, Jebern M. Vergara, and Howard King M. Cagigas “Seat Reservation,” Department of Electronics Engineering, Cebu Technological University. Seat booking platform based on the seat numbers <https://ieeexplore.ieee.org/document/11258821>
- [5] Andheri Sports Complex, A sports clubs containing many sports inside one single campus majorly booking is done manually. <https://web.kheloindia.gov.in/andheri-sports-complex-0>
- [6] Samriddha Chakraborty, “Adamas University, Kolkata, West Bengal, India” Psychology of Subscription Models, <https://www.ijrti.org/papers/IJRTI2505112.pdf>
- [7] P. Sadhana, B. Jeevan Kumar, T. Sai Chander and S. Leela Abhishek “Department of Computer Science and Engineering, Vignan Institute of Technology and Science, Hyderabad” A Web based-College Event Management System <https://ieeexplore.ieee.org/document/9985774>
- [8] Irish C. Juanatas, Earl John C. Mansalay and Cesar T. Villarat “Information Technology Department, FEU Diliman, Quezon City, Philippines” Web based Reservation <https://ieeexplore.ieee.org/document/11075303>
- [9] Salomon Ebi Esono Avomo and Abdul Samad Shibghatullah, “Institute of Computer Science and Digital Innovation, UCSI University, Malaysia” Online Booking Sports Facilities <https://ieeexplore.ieee.org/document/9897020>

BANK CREDIT SCORING: A MACHINE LEARNING FRAMEWORK TO RISK ASSESSMENT & REAL-TIME MONITORING.

¹Akshata Balla, ²Dr. Neha Vora, ³Sakshi Raut and ⁴Dr. Neelam Naik

¹Department of Artificial Intelligence and Data Science, SVKM's Usha Pravin Gandhi College of Arts Commerce and Science Mumbai, Maharashtra 400056, India

²Department of Information Technology, SVKM's Usha Pravin Gandhi College of Arts Commerce and Science Mumbai, Maharashtra 400056, India

³Department of Artificial Intelligence and Data Science, SVKM's Usha Pravin Gandhi College of Arts Commerce and Science Mumbai, Maharashtra 400056, India

⁴Department of Information Technology, SVKM's Usha Pravin Gandhi College of Arts Commerce and Science Mumbai, Maharashtra 400056, India

ABSTRACT

This work grabs the important problem of credit scoring in the finance sector, where danger management and well-informed lending decisions depend on the accurate assessment of loan defaulting likelihood. The research integrates four different datasets financial information, demographics, and customer information to create a combined adjusting dataset. The article summaries a comprehensive pre-processing process that deals with missing values, outliers, and class difference through the Synthetic Minority Over-Sampling Technique (SMOTE). A Random Forest classifier was employed to separate qualified and high-risk applicants, and it was calculated using metrics like the ROC curve & AUC score. Moreover, through the incorporation of an interactive dashboard created using tools such as Streamlit or Plotly Dash to enable real-time tracking of model stability and consumer behaviour, the project offers a comprehensive platform for proactive risk management. [7], [22], [23].

Keywords: Credit Scoring, Machine Learning, Random Forest, SMOTE, Risk Management, Interactive Dashboard, Data Integration.

I. INTRODUCTION

In the financial industry, credit scoring is significant technique aimed at evaluating a person's wealth and ability to meet economic responsibilities. Credit scoring is vital for banks to reduce risk, ensure proper lending procedures, and provide credit access to deserving applicants. [2], [3].

In the current digital banking era, conventional techniques have commonly depended on linear statistical analysis and a minor number of issues, such as revenue and payment history, which commonly cannot identify difficult, non-linear behavioural patterns [3], [5]. This research paper applies a machine learning approach to discover difficult patterns in financial and demographic variables to improve default predictions [5], [7], [15].




Fig (1) Work Flow of Bank Credit Scoring




Fig (2) Real-Time Credit Risk Scoring Workflow for Loan Applications

II. PROBLEM STATEMENT AND STUDY OBJECTIVES

The growth of a comprehensive credit scoring model capable of addressing the significant class imbalance problem that exists between non-defaulters and defaulters, as well as addressing the problem of heterogeneity in the data from a number of organized sources, is the central problem that this study seeks to solve. The objectives of this study are to merge a number of customer datasets into a single clean master dataset and perform examining data analysis (EDA) to establish the influence of variable

such as account history, occupation, and marital status on default rates. The study also seeks to develop a predictive Random Forest model, test the model using suitable banking metrics as sensitivity and ROC-AUC, and develop an interactive dashboard for the real-time display of client trends and model performance [1], [5], [7], [22], [23].

III. LITERATURE REVIEW

Credit scoring, which preliminarily used statistical approaches and many fiscal variables only, has been an essential part of banking threat operation for times. The principles of fiscal threat analysis and measures were laid down by early foundational exploration, which emphasized the significance of bias power in model bracket [1], [5]. Experimenters started probing machine literacy approaches to address the failings of logistic and rule-based models as internet banking and availability to information increased. As exploration showed that machine learning approaches outperformed traditional approaches in prognosticating delicacy, the operation of machine literacy in standing models gained influence. Non-linear connections in client data can be modeled directly by machine literacy- grounded threat analysis models, as shown by Khandani et al. [5]. posterior exploration emphasized the operation of ensemble literacy approaches, specifically arbitrary timber modeling, to address different fiscal information and enhancing robustness in the presence of inequality in class [7], [11]. For large fiscal problems datasets, grade boost approaches similar as XGBoost greatly bettered availability and delicacy in valuation [8]. In credit scoring, managing imbalanced data and assessing algorithms remain a gruelling task. Italicizing his point, Hand emphasized that in imbalance bracket situations, ROC-AUC is a more secure delicacy measure than delicacy itself [1]. In fiscal tasks, in which the cost of true cons and false negatives differs, this perspective has entered wide acceptance. Ensemble models estimated with ROC-AUC outperform individual models in dereliction visualization tasks, according to comparisons among studies [5], [7]. The capacity to interpret approaches enhances trust without compromising the effectiveness of the approach, according to a number of studies comparing [6], [14], [18]. In automated credit scoring systems, ethics such as responsibility, bias, and fairness have come more important than understanding. Hard et al. introduced equal occasion as a fairness constraint in supervised literacy [13], while Possible spelling mistake found. introduced quantitative styles for bias discovery in algorithmic opinions [12]. By introducing the conception of visionary treatment, Ustun et al. continued this debate and supported denied aspirants in understanding and perfecting their credit scores [20]. To promote responsible data use in high-risk sectors such as finance, data transparency tools similar to data wastes for data sets have also been proposed [21]. From the literature, there's a definite development towards the usage of machine literacy for credit scoring. The thing about these approaches is to achieve a balance between fairness, interpretability, and their prophetic delicacy. But the aspects of real-time shadowing, model stability checking, and an interactive dashboard are still absent. This exploration islands these gaps by incorporating styles of resolvable AI, cooperative literacy, effective evaluation criteria, and an collaborating dashboard for real-time credit threat monitoring.

IV. RESEARCH METHODOLOGY

The methodology follows a structured machine learning channel starting with gathering and combining multiple datasets that include client demographic and literal data. Preprocessing includes handling absent values, removing duplicates, and applying SMOTE to handle class imbalance, which assists in preventing the model from being poisoned for the maturity class [1], [7]. Point engineering is applied to create new criteria such as debt-to-income and credit employment rates, which improves

the model's capability to generate correct predictions [5]. Various models such as Binary Logistic Regression, Decision Tree, and Random Forest were accomplished & cross-validated [7], [11] and hyper parameter tuning is performed using Grid Search [16] to obtain the most stylish results. A dashboard is also developed using tools like Plotly, Dash to allow nonstop monitoring and support decision- making for stakeholders [22], [23].




Fig (3) Work Flow of Research Methodology

V. EXPERIMENT CONDUCTED

Trials were carried out using Python in the Jupyter Notebook and Google Colab surroundings, with libraries similar as per Pandas, Scikit- learn, and Imbalanced learn.

The main dataset was resolved into an 80-20 training-to-test rate to ensure the model can be estimated on data it has not seen ahead. The process included lading intermingled client lines, relating and handling outliers, and conducting exploratory data analysis to spot any occasional patterns. SMOTE was applied specifically to the training data to balance the failure and non-default classes [1], [7]. Different bracket models were also fulfilled and compared grounded on their effectiveness in handling irregular banking

data and their capability to capture non-linear relations [5], [7], [11].

VI. RESULTS AND DISCUSSION

The experimental outcomes demonstrated that machine learning significantly improves default risk prediction compared to traditional rule-based approaches [5], [7]. The Random Forest and Decision Tree models proved to be the most accurate and reliable, having a high discrimination capability to differentiate amongst eligible and high-risk customers [1], [5]. Sensitivity & Specificity measures also proved that the models were able to strike a stability between detecting actual defaulters and avoiding incorrect alarms for trustworthy customers. The results of the learning shown that ROC-AUC is more relevant measure than accuracy in imbalanced financial data. Machine learning is very effective in detecting complex patterns, but its limitations exist in the exclusion of macroeconomic variables and the need for periodic retraining.




Fig (4) Work Flow of Result & Discussion




Fig (5) ROC and AUC test data implementation:

Table 1: Predictive modelling and Ensemble Learning

Model Rank	Algorithm	Test AUC	Overfitting Risk
1	Decision Tree	0.84	Medium
2	XGBoost	0.83	High
3	Random Forest	0.80	High
4	Naïve Bayes	0.67	Low
5	Logistic Regression	0.65	Low
6	SVM	0.72	Low




Fig (6) Model Comparison




Fig (7) Sentiment analysis implementation

Bank Credit Risk: Model Evaluation Dashboard




Fig (8) Dashboard Implementation

VII. CONCLUSION AND FUTURE SCOPE

This study has successfully integrated a complete credit scoring system that incorporates accuracy with the ability to monitor in real-time using a dashboard. This study validates the fact that ensemble methods such as Random Forest work better on imbalanced datasets in the banking sector. The key highlights this research include the design of a scalable system for the real world and the efficient treatment of the class imbalance

problem. The upcoming directions of the research include incorporation of new sources of information such as transaction records, the

application of Explainable AI methods such as SHAP & LIME to improve interpretability, and the deployment of the classification as a real-time web facility for immediate loan approval.




Fig (9) Conclusion and Future Scope

VIII. REFERENCES

- [1] D. J. Hand, "Measuring classifier performance: A coherent alternative to the area under the ROC curve," *Machine Learning*, vol. 77, no. 1, pp. 103–123, 2009, doi: 10.1007/s10994-009-5119-5.
- [2] D. Bholat, N. Broughton, M. Drehmann, and E. Unlu, "Enhanced information in credit scoring: The UK experience," *Bank of England Quarterly Bulletin*, vol. 52, no. 3, pp. 212–221, 2012.
- [3] M. Hurley and J. Adebayo, "Credit scoring in the era of big data," *Yale Journal of Law and Technology*, vol. 18, no. 1, pp. 148–216, 2017.
- [4] K. Louedec, T. Orłowski, and I. Chaltiel-Demars, "Explainable AI for credit risk management," *Journal of Risk Management in Financial Institutions*, vol. 13, no. 2, pp. 142–154, 2020.
- [5] A. E. Khandani, A. J. Kim, and A. W. Lo, "Consumer credit-risk models via machine-learning algorithms," *Journal of Banking & Finance*, vol. 34, no. 11, pp. 2767–2787, 2010, doi: 10.1016/j.jbankfin.2010.06.001.
- [6] Y. Liu, Q. Li, X. Zhang, and X. Zhang, "A comparative study of explainable machine learning methods for credit risk modeling," *Expert Systems with Applications*, vol. 187, p. 115906, 2022, doi: 10.1016/j.eswa.2021.115906.
- [7] B. Malekipirbazari and V. Aksakalli, "Risk assessment in social lending via random forests," *Expert Systems with Applications*, vol. 42, no. 10, pp. 4621–4631, 2015, doi: 10.1016/j.eswa.2015.01.002.
- [8] T. Chen and C. Guestrin, "XGBoost: A scalable tree boosting system," in *Proc. 22nd ACM SIGKDD Int. Conf. Knowledge Discovery and Data Mining*, San Francisco, CA, USA, 2016, pp. 785–794, doi: 10.1145/2939672.2939785.
- [9] M. T. Ribeiro, S. Singh, and C. Guestrin, "Why should I trust you? Explaining the predictions of any classifier," in *Proc. 22nd ACM SIGKDD Int. Conf. Knowledge Discovery and Data Mining*, 2016, pp. 1135–1144, doi: 10.1145/2939672.2939778.
- [10] S. M. Lundberg and S.-I. Lee, "A unified approach to interpreting model predictions," in *Advances in Neural Information Processing Systems*, vol. 30, 2017, pp. 4765–4774.
- [11] L. Breiman, "Random forests," *Machine Learning*, vol. 45, no. 1, pp. 5–32, 2001, doi: 10.1023/A:1010933404324.
- [12] I. Žliobaitė, "Measuring discrimination in algorithmic decision making," *Data Mining and Knowledge Discovery*, vol. 31, no. 4, pp. 1060–1089, 2017, doi: 10.1007/s10618-015-0443-1.

-
- [13] M. Hardt, E. Price, and N. Srebro, "Equality of opportunity in supervised learning," in *Advances in Neural Information Processing Systems*, vol. 29, 2016, pp. 3315–3323.
 - [14] A. Ghosh and S. Ghosh, "Explainable credit scoring using rule-based classifiers," *Information Sciences*, vol. 599, pp. 75–93, 2022, doi: 10.1016/j.ins.2022.02.047.
 - [15] Q. Zhang, L. Yang, and Y. Qin, "Research on the application of deep learning in credit scoring," *Procedia Computer Science*, vol. 147, pp. 160–166, 2019, doi: 10.1016/j.procs.2019.01.209.
 - [16] B. Mahesh, "Machine learning algorithms: A review," *International Journal of Science and Research*, vol. 9, no. 1, pp. 381–386, 2020, doi: 10.21275/ART20204044.
 - [17] B. Lantz, *Machine Learning with R*, 3rd ed. Birmingham, U.K.: Packt Publishing, 2019.
 - [18] R. Roscher, B. Bohn, M. F. Duarte, and J. Garcke, "Explainable machine learning for scientific insights and discoveries," *IEEE Access*, vol. 8, pp. 42200–42216, 2020, doi: 10.1109/ACCESS.2020.2976199.
 - [19] Z. C. Lipton, "The mythos of model interpretability," *Communications of the ACM*, vol. 61, no. 10, pp. 36–43, 2018, doi: 10.1145/3233231.
 - [20] B. Ustun, A. Spangher, and Y. Liu, "Actionable recourse in linear classification," in *Proc. ACM Conf. Fairness, Accountability, and Transparency*, 2019, pp. 10–19, doi: 10.1145/3287560.3287566.
 - [21] T. Gebru *et al.*, "Datasheets for datasets," *Communications of the ACM*, vol. 64, no. 12, pp. 86–92, 2021, doi: 10.1145/3458723.
 - [22] U. Bhatt *et al.*, "Explainable machine learning in deployment," in *Proc. ACM Conf. Fairness, Accountability, and Transparency*, 2020, pp. 648–657, doi: 10.1145/3351095.3375624.
 - [23] F. Martínez-Plumed, L. Contreras-Ochando, C. Ferri, and J. Hernández-Orallo, "CRISP-ML: A standard process model for machine learning," *International Journal of Interaction Multimedia & Artificial Intelligence*, vol. 6, no. 6, pp. 29–36, 2021, doi: 10.9781/ijimai.2021.05.003.

**A COMPREHENSIVE, EXPLAINABLE, AND SCALABLE MARKETING ANALYTICS
FRAMEWORK FOR THE FMCG SECTOR USING BEHAVIORAL MODELING, PREDICTIVE
ANALYTICS, AND INTERPRETABLE MACHINE LEARNING**

Juwairia Khan, Devna Patel, Dr. Swapnali Lotlikar and Prof. Sunita Gupta

M.Sc. Artificial Intelligence and Data Science, SVKM's Usha Pravin Gandhi College of Arts, Science & Commerce Mumbai, India

ABSTRACT

The Fast-Moving Consumer Goods (FMCG) sector represents one of the most complex and competitive domains for marketing decision-making due to high transaction volumes, short product life cycles, intense brand competition, and heterogeneous customer behavior. Traditional marketing strategies, often driven by intuition or aggregate historical reporting, are increasingly inadequate in managing such complexity. This research presents a comprehensive, end-to-end, and explainable marketing analytics framework developed using real-world FMCG campaign, transactional, regional, and customer feedback data. The framework integrates systematic data preprocessing, master dataset construction, multi-dimensional exploratory data analysis (EDA), advanced feature engineering, supervised predictive modeling, natural language processing-based sentiment analysis, and explainable artificial intelligence (XAI). Extensive EDA reveals critical behavioral patterns related to customer loyalty, buying frequency, temporal purchasing dynamics, brand level contribution, and regional heterogeneity in campaign response. Binary Logistic Regression is employed as a statistically interpretable baseline model, followed by non-linear machine learning classifiers including Naïve Bayes, Decision Tree, and Random Forest. Experimental evaluation demonstrates that the Decision Tree model achieves superior predictive performance with an accuracy of approximately 84%, while maintaining interpretability. Furthermore, Shapley Additive Explanations (SHAP) are utilized to provide transparent explanations of model predictions at both global and local levels. The results demonstrate that the proposed framework significantly enhances campaign targeting precision, reduces marketing inefficiencies, and improves return on investment (ROI), thereby offering a practical and scalable solution for data-driven decision-making in the FMCG sector. Index Terms—FMCG, Marketing Analytics, Exploratory Data Analysis, Predictive Modeling, Explainable AI, SHAP, Customer Behavior Analysis

I. INTRODUCTION

The FMCG industry plays a critical role in the global economy, encompassing products characterized by low unit cost, high purchase frequency, and rapid inventory turnover. Despite the apparent simplicity of individual transactions, FMCG marketing presents significant analytical challenges due to the scale, velocity, and diversity of customer interactions.

Modern FMCG organizations generate massive volumes of data through transactional systems, loyalty programs, digital campaigns, and customer feedback platforms. However, the mere availability of data does not guarantee improved marketing effectiveness. Many organizations continue to rely on intuition-driven strategies, rule-based segmentation, or retrospective reporting, which often fail to capture complex behavioral patterns and interdependencies among variables.

Marketing analytics offers a systematic approach to transforming raw data into actionable insights through the application of statistical analysis, machine learning, and artificial intelligence. This research aims to demonstrate how an integrated analytics framework can be operationalized in a realworld FMCG context to improve campaign response prediction, customer targeting, and managerial decisionmaking.

II. RELATED WORK AND LITERATURE REVIEW

The application of analytics in marketing has been widely studied across multiple domains. Shmueli and Koppius distinguish between explanatory and predictive analytics, emphasizing that predictive accuracy is often more relevant for operational decision-making than causal inference alone. Provost and Fawcett argue that effective data science solutions must align predictive models with business objectives rather than purely technical performance metrics.

Several studies have explored customer response modeling using logistic regression due to its interpretability and statistical foundations.

However, logistic regression assumes linear relationships between predictors and the response variable, which may not adequately capture the complexity of customer behavior in FMCG environments.

Machine learning techniques such as Decision Trees and Random Forests have demonstrated superior performance in modeling non-linear relationships and feature interactions. Although these models can be very predictive, people often complain that they are like a "black box". As a result, business people hesitate to use them. Recently, efforts have been made to make these models clearer and easier to understand, with tools like SHAP making a difference by helping everyone understand why the model gave a certain answer.

But if you look at the research being done, you'll find that most research doesn't combine data exploration, forecasting, sentiment analysis, and explainability into a single framework for companies that sell everyday products. This work aims to bring all those pieces together by showing how they can all work together in one marketing FMCG space.

III. BUSINESS PROBLEM DEFINITION AND RESEARCH OBJECTIVES

Let's make it more clear and realistic:

FMCG companies often spend a lot of money on ads and promotions, but target too broadly, wasting money and losing real customers. The main challenge here is not knowing who might respond, which means a lot of effort goes nowhere.

Here's what this study hopes to do:

- Look closely at how customers behave and buy.
- Pinpoint which things, such as shopping habits, time, location, drive someone to respond to your campaign.
- Build intelligent models that can pick people who are most likely to take action.
- Use tools that help explain how these models make decisions so managers can trust and understand the results.
- Translate what you learn into clear steps and advice for marketing teams to spend their efforts and money more wisely.

In short, the goal is to help FMCG brands stop flying blind and start meaning every marketing move.

IV. DATA DESCRIPTION AND PREPROCESSING

We have worked with various data formats such as campaign information, customer information, sales logs since 2021. until 2022, as well as regional tags and written customer reviews.

To get everything ready for analysis, we started with the missing information, filling in the gaps using techniques that made sense with the numbers in each category. We then checked for values that didn't seem right using the IQR trick - basically spotting anything that didn't fit with the others. We then cleaned the scales of all variables measured as continuous numbers to organize them and make them easier to compare.

V. EXPLORATORY DATA ANALYSIS

We started by looking at the data to spot any odd values, understand how things are distributed, and identify any patterns that stood out.

A. How customers behave

When comparing people who responded to the campaign with those who did not, several things emerged: respondents tended to spend more on average, stay customers longer, and show more signs of brand loyalty. This shows a strong correlation between how people have behaved in the past and whether they will respond to future offers.

B. Buying habits over time

When we break things down by year and quarter, we've seen clear ups and downs, with some times of the year or certain quarters seeing more buying activity. Those who had made a recent purchase were also more likely to make another purchase soon, suggesting that the timing of previous purchases does matter.

C. Branding and Regional Differences

When we looked at the brands, we noticed that not everyone contributed equally, with some brands driving much more activity than others. When we checked the location, the results varied by area. Some regions responded significantly more to the campaign, meaning that where people live may influence how they react to offers.

Overall, these models are useful for figuring out where to focus next steps and how to improve your futures campaigns.



Feature engineering converted raw data into valuable predictors for analysis. Features that were redundant or showed little variance were removed to minimize noise and avoid multicollinearity. The selection of features was based on insights from exploratory data analysis, correlation studies, and expertise in the field to maintain clarity and reliability.

Fig. 2. ROC Curve Comparison for Predictive Models

Word cloud visualization was employed to identify frequently occurring terms within customer feedback. Dominant keywords such as "quality," "value," "price," and "delivery" highlighted key themes influencing customer sentiment. These qualitative insights provide actionable guidance for refining campaign messaging and customer experience strategies.



Fig.3. Word Cloud Representing Dominant Themes in Customer Feedback

Decision Tree and Random Forest classifiers were employed to model complex interactions among predictors.

Model	Accuracy	Precision	Recall	AUC
Logistic Regression	0.69	0.67	0.65	0.69
Naïve Bayes	0.65	0.62	0.61	0.65
Decision Tree	0.84	0.82	0.83	0.84
Random Forest	0.82	0.80	0.79	0.82

In addition to transactional and behavioral data, unstructured customer feedback also provides a potentially valuable source of qualitative information that can reveal the customer's views, expectations, and drivers of

dissatisfaction. To extend the quantitative modeling of campaign responses, the current study makes use of text mining techniques to analyze customer feedback received through customer surveys or complaint logs.

A. Text Preprocessing Pipeline

preprocessing pipeline established to transform raw texts to analyzable forms. This involved tokenization, which referred to splitting texts into individual terms, lowercasing, removal of punctuation and numerical characters, removal of stop words, and lemmatization, which involved transforming words to their base forms.

B. Sentiment Classification Methodology

Once preprocessing was completed, sentiment analysis classified customer sentiments into positive, negative, and neutral categories. This allowed the overall customer sentiment, in terms of products, pricing, promotional schemes, and service quality, to be quantified. This customer sentiment again formed part of the validation process with the findings of the transactional and behavioral analysis.

C. Interpretation of Sentiment Results

The results from the sentiment analysis showed a prevalence of positive feedback related to the quality of the product and trust in the brand name; negative feedback primarily related to price concerns and issues experienced in the delivery process. The data is consistent with the observed response patterns to the campaign.

IX. EXPLAINABLE ARTIFICIAL INTELLIGENCE

Even though predictive accuracy is important in order for the campaign targeting model to be effective, model interpretability is equally important, especially from a practical business perspective. The business stakeholders need to understand the reasons behind the model's prediction that a particular customer is a high or low responder.

A. Need for Explainability in Marketing Analytics

Black box models sometimes encounter resistance in operational environments because of their lack of transparency. In the case of marketing models, explainability would bring about a better alignment with the manager's intuition.

B. SHapley Additive Explanations

The research uses a game theory-based approach called SHapley Additive Explanations (SHAP). The SHAP values measure how each feature contributed to the prediction, considering all possible combinations of features, which makes it consistent.

C. Global Feature Importance Analysis

Global SHAP analysis identified loyalty score, buying frequency, total sales value, and brand contribution ratio as the most impactful predictors in the campaign response prediction. This verifies the fundamental concepts of marketing theory with respect to customer lifetime value and interaction history as major influencers in the prediction of response to campaigns.

D. Local Explanation of Individual Predictions

Besides obtaining global interpretations, SHAP also facilitates local interpretations. That is, it can offer interpretations at the level of individual customers. This, in turn, aids marketers in understanding individual customers who are expected to react either favourably or adversely.




Fig.4. SHAP Summary Plot Showing Global Feature Contributions

X. MANAGERIAL IMPLICATIONS

The proposed framework would provide various marketing managers in FMCG with significant marketing insights that would be beneficial to their strategies. The following would be possible:

The proposed analytics framework would be beneficial to marketing managers in various ways, for instance;

Predictive targeting would enable marketers to transition from ‘mass marketing’ to ‘precision marketing’ in their strategies.

The proposed analytical framework would also enable marketers to use.

Regional response analysis guides localized campaign strategies, and brand-level insights feed into inventory management and promotional priorities. Additionally, explainability helps build trust among managers and enables data-informed decisions in marketing, sales, and strategy teams.

XI. LIMITATIONS AND THREATS TO VALIDITY

Though the study has its own merits, there are also certain limitations to the current study. Although the research is based on historical data, ever-changing human behavior and market changes are a few aspects the model might not take into account. There is a bias likelihood in the model's performance over different types of FMCG products and locations.

XII. ETHICAL AND PRACTICAL CONSIDERATIONS

The development of Marketing Systems which are based upon Analytics, will create a lot of discussion around data privacy and other issues, as well as how to deploy a marketing system in an ethical manner. Customer data collection will need to comply with many different data protection laws.

XIII. CONCLUSION AND FUTURE RESEARCH DIRECTIONS

This study provides a comprehensive marketing analytics framework for the FMCG Industry. The paper seeks to improve campaign targeting efficiency through exploratory analysis, predictive modeling, sentiment analysis, and a range of techniques from explainable AI. It is recommendable that further research be carried out in realtime model deployment, various techniques in ensemble learning, and deep learning- based sentiment models.

REFERENCES

- [1] G. Shmueli and O. Koppius, “Predictive analytics in information systems research,” *MIS Quarterly*, vol. 35, no. 3, pp. 553–572, 2011.
- [2] P. Kotler and K. L. Keller, *Marketing Management*, 15th ed. Pearson Education, 2016.
- [3] F. Provost and T. Fawcett, *Data Science for Business*. O’Reilly Media, 2013.
- [4] T. Hastie, R. Tibshirani, and J. Friedman, *The Elements of Statistical Learning*. Springer, 2009.
- [5] I. Goodfellow, Y. Bengio, and A. Courville, *Deep Learning*. MIT Press, 2016.
- [6] J. Han, M. Kamber, and J. Pei, *Data Mining: Concepts and Techniques*, 3rd ed. Morgan Kaufmann, 2011.
- [7] S. Russell and P. Norvig, *Artificial Intelligence: A Modern Approach*, 4th ed. Pearson, 2020.
- [8] C. Molnar, *Interpretable Machine Learning*. Lulu Press, 2022.
- [9] S. M. Lundberg and S.-I. Lee, “A unified approach to interpreting model predictions,” in *Advances in Neural Information Processing Systems*, 2017.
- [10] B. Liu, *Sentiment Analysis and Opinion Mining*. Morgan & Claypool, 2012.
- [11] E. Cambria and B. White, “Jumping NLP curves: A review of natural language processing research,” *IEEE Computational Intelligence Magazine*, vol. 9, no. 2, pp. 48–57, 2014.
- [12] L. Breiman, “Random forests,” *Machine Learning*, vol. 45, no. 1, pp. 5–32, 2001.
- [13] J. R. Quinlan, “Induction of decision trees,” *Machine Learning*, vol. 1, no. 1, pp. 81–106, 1986.
- [14] T. M. Mitchell, *Machine Learning*. McGraw-Hill, 1997.
- [15] R. Kohavi, “A study of cross-validation and bootstrap for accuracy estimation and model selection,” in *Proceedings of IJCAI*, 1995, pp. 1137–1145.

-
- [16] A. McAfee and E. Brynjolfsson, “Big data: The management revolution,” *Harvard Business Review*, vol. 90, no. 10, pp. 60–68, 2012.
 - [17] D. J. Hand, H. Mannila, and P. Smyth, *Principles of Data Mining*. MIT Press, 2001.
 - [18] M. Stonebraker et al., “Data management challenges in data science,” I *Proceedings of CIDR*, 2013.
 - [19] A. Ng, “Machine learning and AI via brain simulations,” *Communications of the ACM*, vol. 63, no. 1, pp. 50–59, 2020.
 - [20] A. Choudhury, S. Banerjee, and S. Mitra, “Customer response prediction using machine learning techniques,” *International Journal of Data Science and Analytics*, vol. 8, no. 3, pp. 213–225, 2019.

A HYBRID SENTIMENT-MARKET MODEL FOR PREDICTING NIFTY 50 OPENING DIRECTION USING LOGISTIC REGRESSION

Sahal Patel, Surakshith Shetty, Dr. Neha Vora and Dr. Prashant ChauudharyDepartment of Artificial Intelligence, SVKM'S Usha Pravin Gandhi College of Arts Commerce and Science
Mumbai, India**ABSTRACT**

The first move of the stock market is not only influenced by the past price changes but also by the investor's perception formed before the commencement of the trading session. Prediction of this move is still a puzzle due to the combined effect of global markets, volatility, and market sentiment. This project is intended to forecast the next, day opening direction of the Nifty 50 stock market index based on a mixture of numerical market indicators and sentiments extracted from the financial news articles.

Market data from 2017 till 2024 for the Nifty 50 stock market index and some global indices together with volatility measures were acquired. Meanwhile, sentiment scores were derived from the headlines of financial news articles using transformer, based language models. These numerical and sentiment, based characteristics were merged and utilized to train a logistic regression classifier which was chosen due to its simplicity and interpretability.

The model's performance was evaluated by standard classification metrics. The obtained results reveal that the addition of sentiment information results in higher prediction accuracy than models that only consider market data. The suggested method provides the simple and interpretable solution of short, term market direction prediction and demonstrates the applicability of combining sentiment analysis with traditional financial market indicators in the Indian stock market scenario

Keywords: Nifty 50, Stock Market Forecasting, Sentiment Analysis, Logistic Regression, FinBERT, RoBERTa, Natural Language Processing (NLP), Financial Analytics, Investor Sentiment, Machine Learning in Finance

I. INTRODUCTION

The Indian stock market plays a pivotal role in the country's economy, and Nifty 50 is recognized globally as a benchmark for assessing the performance of the stock market. Estimating the short, term direction of this index, particularly at the time of market opening, is a very difficult task since there are several factors that affect stock prices such as global market trends, market sentiments, and economic events [8], [10].

Conventional forecasting techniques mostly rely on past stock price and volume data. Even though they are useful for identifying statistical patterns, such methods are incapable of extracting qualitative factors that have a significant impact on the stock market trends, for example, financial news and analysts' opinions [9]. Recently, breakthroughs in Natural Language Processing have enabled the extraction of meaningful sentiment information from text, based sources, thus leading to a better comprehension of market sentiments even before the trading session starts [5].

By blending these sentiment elements with other economic indicators, forecasting models can truly embody the behavioral and informational facets that drive the ups and downs of the stock market. Thus, this study suggests a hybrid method that systematically and understandably utilizes global index data, volatility measures, and news, driven sentiment to forecast the Nifty 50 stock market index's next, day opening trend.

II. OBJECTIVES

The major objective of this study is to create a theoretical model and thereafter test it which predicts whether the Nifty 50 index will go up or down when it opens the next day. This study wants to combine numerical market indicators and opinions extracted from financial news to improve the accuracy of short, term market forecasts.

This study intends to accomplish the following goals: To create a step, by, step strategy that utilizes a logistic regression model to predict whether the Nifty 50 index will open on an upward or downward note.

To bring into play the sentiment extracted from financial news headlines to gauge the investor's mood before the market opens. To mix the sentiment data with the quantitative data such as the movement of global indices and market volatility. To evaluate the performance of the proposed hybrid method against models that only consider historical financial data. To make sure that the final model remains understandable and hence useful to traders, investors, and researchers who are keen on predicting the stock market in the short term.

III. PURPOSE

This project aims to analyze if combining market data with sentiment data extracted from financial news can better the prediction of the Nifty 50 index opening direction. The traditional method of prediction relies only on past market prices or technical analysis; however, it might not be able to reveal the influence of investor sentiment on the market before its opening.

The goal of this research is to develop a viable and understandable prediction system that fuses both quantitative and sentiment data. In addition to focusing solely on the prediction accuracy, this project is also intended to make the results interpretable so that the effects of the global market and market sentiment on the Nifty 50 can be correctly understood.

This study concentrates on the moment of market opening and the short, term market dynamics, thus providing insights which can be not only academic but also practical for traders and analysts who need a deeper understanding of the market conditions before the market opening.

IV. SCOPE

The project scope limits the work to prediction of the short, term opening trend of the Nifty 50 index based on a group of market, driven indicators and sentiments extracted from financial news articles. The study uses a daily data set and is limited to information that is publicly available prior to the opening of the Indian stock market.

Project scope covers a set of global indices such as the Dow Jones, NASDAQ, Hang Seng, Nikkei 225, and the India VIX to consider worldwide market trends and volatility. Besides, the scope is limited to conducting sentiment analysis of the financial news headlines related to market and economic events. However, the project scope excludes social media, intraday market data, or stock, level information.

The project focus is on the binary classification of the Nifty 50 opening trend either as positive or negative only. The project scope does not include long, term predictions, portfolio analysis, or high, frequency trading analysis. The project scope limits the work to evaluate the effectiveness of a simple and interpretable hybrid prediction model.

V. APPLICABILITY

The findings of this project are applicable to both real, world scenarios and academic environments. A trader or an individual investor can use the framework as a handy help tool for gaining a deeper insight into how changes in the global markets and investor sentiment affect the Nifty 50 index during the opening hours of the market.

Moreover, the framework can be a highly valuable asset for financial analysts and researchers primarily due to its interpretability. This model can show which factors have influenced the prediction and to what extent, thus it can be effortlessly combined with any market analysis or risk assessment procedure.

From an academic standpoint, this project can be used to illustrate how sentiment analysis methods can be combined with conventional statistical models for financial market prediction. This can be further extended or modified for other stock market indices or emerging markets.

VI. ACHIEVEMENTS

The objectives of the research have been fulfilled in the following ways:

A hybrid prediction model has been designed and developed that uses both numerical market indicators and sentiment information extracted from financial news. The transformer-based sentiment models have been successfully used to incorporate the pre-market investor sentiment into the model along with the conventional financial data. A logistic regression-based classification model has been developed that offers interpretable results about the factors that affect the opening direction of the Nifty 50. The prediction accuracy has been improved by including the sentiment features along with the market indicators.

VII. RELATED WORK

Stock market prediction has been a popular topic of research and scholars have investigated this using various statistical, machine learning, and sentiment, based approaches. Initially, studies were mainly dependent on numerical time, series data and econometric models for figuring out the price trend and market direction.

The methods thus generated, although structured, failed to largely perform well in volatile market situations and in times when market behavior was influenced by external information flows [8], [9].

As machine learning techniques advanced, a few papers started to look at data, driven models for first stock market movement prediction and then the subsequent days price estimation. Deshmukh et al. investigated the performance of classical machine learning techniques vis, vis deep learning algorithms such as LSTM and

found that using recurrent neural networks for the forecasting of the Nifty index resulted in an improved accuracy of prediction [10]. Despite being successful, the authors endeavors were primarily concentrated on historical price patterns and hence, the absence of sentiment, based indicators made it difficult for their models to capture the impact of behavioral factors on stock market changes.

The latest studies, however, have emphasized the rising significance of sentiment analysis in the area of financial forecasting. Yadav utilized sentiment features derived from BERT combined with classical machine learning models and showed that incorporating sentiment features still further can enhance the trend prediction performance [9]. The limitation of the work, however, was that it was tested on the broad global datasets, and thus, the Indian stock market or the Nifty 50 index was not specifically addressed by it.

Similarly, Raut et al. added social media sentiment to the LSTM, based models and found that their approach worked better. However, since social media data was used, this caused noise and there was less consistency across market conditions [16].

Some researchers have explored bringing up volatility as a basis for forecasting rather than making a directional prediction. Prasad and Bakshi have made use of XGBoost, LightGBM, and other ensemble learning methods to try to model the India VIX movements. Their experiments demonstrated that the ensemble methods give better results in volatility estimation compared to the traditional ones [14]. Although volatility is a significant indicator of the market, these authors did not tackle the problem of the index opening direction prediction directly.

The hybrid sentimentmarket approaches have been a part of the discussion in the Indian market scenario too. Nikunj et al. have fused the FinBERT, based sentiment scores with the technical indicators to predict the movements of the Nifty 50 and have thus achieved better accuracy than the price, only models [4]. Nevertheless, the fact that the dataset was small could have limited the extent to which the model can be generalized. Yash et al. have gone a step further by analyzing the influence of pre, market sentiment through the use of a simple logistic regression model. It was found that sentiment does significantly impact the Nifty 50 opening direction [7]. Besides, their work did not consider any comparisons with more advanced machine learning or ensemble, based benchmarks.

Recently, large language models have been utilized in the financial text analysis area. Garg et al. presented the NiftyLLaMA framework, which uses transformer, based architectures to extract company, level sentiment and connect it with stock price behavior [15]. Although the framework showed excellent capability in information extraction, the primary emphasis of the framework was on firm, specific analysis rather than aggregate index, level forecasting.

Besides, the global market impact on Indian indices has also been a subject of research. Ghosh et al. revealed that the use of global sentiment indicators along with international futures data can lead to better prediction of Nifty movements [7]. At the same time, this approach was mainly dependent on signals from foreign markets and gave little weight to domestic investor sentiment. Researches comparing classical machine learning and deep learning methods have similarly focused on numerical performance improvements, thus, presenting limited interpretability [10].

There is a small group of market extreme condition studies. Sarkar and Gupta suggested a hybrid LSTMARIMA model for predicting market behavior during shock events like the COVID, 19 pandemic and showed that the model could withstand abnormal volatility [1]. However, the model's performance at normal market conditions was not thoroughly tested. Wadhwani et al. pitted general, purpose transformer models against finance, specific transformer models and concluded that FinBERT is more dependable for extracting sentiment though their work didnt directly focus on Nifty 50 prediction [8].

In summary, the initial references corroborate that both sentiment analysis and sophisticated machine learning techniques play a significant role in forecast the stock market. Nevertheless, most of the previous studies have concentrated on one or more of the following aspects: long, term trends, volatility estimation, firm, level analysis, or they have resorted to intricate models lacking interpretability. A significant research gap still exists in the area of designing an interpretable hybrid framework that integrates global market indicators with sentiment analysis for the short, term prediction of the Nifty 50 opening direction.

This paper will fill the gap by presenting a sentiment, augmented logistic regression model which is tested with a realistic, forward, looking testing approach.

VIII. PROPOSED SOLUTION

This research puts forward a hybrid framework that predicts the next, day opening direction of the Nifty 50 index by combining numerical market indicators with the sentiment extracted from financial news. It is

motivated by the fact that even the best historical, price, data, only models cannot perceive investor sentiment, which is formed before market opening.

The proposed method makes use of historical market data from 2017 to 2024 for both domestic and international indices that are the main factors in the Indian stock market, such as the Nifty 50, major global indices, and the India VIX. Numerical features calculated from these indices reveal market turns, volatility levels, and cross, market effects that can be responsible for the Nifty 50 opening.

In addition to numerical indicators, the framework also considers investor sentiment extracted from financial news headlines released before the trading session.

Transformer, based language models are used to generate sentiment scores, which are supposed to reflect the overall investor mood rather than a few opinions. This qualitative information is seen as a market, data complement signal and integrated at the feature level.

The numerical and sentiment features were combined and fed into a logistic regression classifier. This kind of classifier was chosen due to its interpretability and good compatibility with binary classification problems. The model is intended to be a tool for predicting whether the Nifty 50 index's opening price will be higher or lower than the closing price of the previous trading day.

In order to create a more believable evaluation scenario, the entire historical dataset is utilized for the training of the model, whereas the data of the most recent six months are kept for the testing purpose. Such a forward, looking test strategy is very much in line with the actual situation where models trained on past information are evaluated on the unseen future data. On a whole, the here presented solution puts simplicity, openness, and practicality at the forefront. It provides a well, organized method for forecasting the short, term direction of the market in the Indian stock market.

IX. DATASET AND PREPROCESSING

The dataset used in this paper is a combination of market numerical data and sentiment data. It helps in understanding the quantitative market behavior as well as the qualitative investor perception before market opening. The historical financial data have been obtained for the period January 2017 to December 2024 and consist of the Nifty 50 index and the selected global indices which are the known influencers of the Indian stock market [4], [9].

The numerical data set comprises Nifty 50, Dow Jones Industrial Average, NASDAQ Composite, Hang Seng Index, Nikkei 225, and India VIX. These indices have been selected to represent global market movements and volatility conditions affecting Nifty 50 opening direction. Daily price data for each index was at first extracted and then used to derive return, based features so as to standardize price changes across different markets.

Due to the fact that international markets have different trading calendars, the raw data was missing data for some dates. In order to keep all indices uninterrupted, the missing data points were dealt with the forward, fill method. This allowed each trading day to have a full set of input features without the need to artificially create fluctuations. Furthermore, lag corrections were made to the global indices closing after Indian market hours so that only pre, opening Nifty 50 information was taken into account during the analysis.

In parallel with numerical data preparation, financial news headlines related to market and economic events were used to extract sentiment information. These headlines were processed using transformer-based language models trained on financial text to classify sentiment as positive, negative, or neutral [2], [5]. Daily sentiment values were then aggregated to represent overall pre-market investor mood and merged with the numerical dataset using the corresponding trading date.

Before model development, all numerical features were scaled using Min–Max normalization to ensure consistency across variables and to prevent any single feature from Alongside the processing of numerical data, the sentiment information was also extracted from financial news headlines related to the market and economic events. These headlines were analyzed with the help of transformer, based language models trained on financial text to identify the sentiment as positive, negative, or neutral [2], [5]. Subsequently, daily sentiment scores were combined to capture the overall pre, market investor sentiment and integrated with the numerical data according to the corresponding trading date. Initially, before developing the model, all numerical features were transformed into the range between 0 and 1 using MinMax normalization to maintain uniformity among the variables and to avoid the situation where any feature would overshadow the learning process [10].

The ultimate dataset was created from a forward, looking evaluation perspective wherein the entire historical data was utilized for model training while the latest six months of data were set aside as a test set. This method

is in line with the actual practice of making forecasts and thus, it prevents the model from gaining unfair advantage by accessing information during the evaluation of its performance.

X. MODEL DEVELOPMENT

The aim of the model development phase is to next, day Nifty 50 index opening direction by a set of market, based indicators combined with sentiment information. The prediction problem is set up as a binary classification one, where the model predicts whether the index will open at a higher or lower level against the previous trading day. A Logistic Regression model was picked for this task as it is simple, transparent, and suitable for predicting a binary outcome. In contrast to complex deep learning models, logistic regression makes it possible to directly interpret the feature coefficients that determine how global market movements and sentiment indicators influence the predicted result, thus making it easier to comprehend it [8], [9].

In fact, such an interpretable model is indispensable in financial applications where the decisions made by the model must be explainable and not merely performance, driven. Within the presented framework, the dependent variable indicates the probability of a positive opening of the Nifty 50 index. The set of explanatory variables consists of numerical features such as daily returns of domestic and global stock indices, volatility signal derived from India VIX, and sentiment scores from financial news. Via the Maximum Likelihood Estimation method, model parameters are obtained which aims to find the values of coefficients that best 'fit' the data [10].

The feature set used for training came from the preprocessing and feature engineering steps explained earlier. It comprises return, based indicators, lag, adjusted global index features to capture time, zone difference effects, and aggregated daily sentiment values reflecting pre, market investor mood [2], [5].

Standardization was done on all the numerical features before training to keep the features consistent with each other and at the same time help the model converge faster.

In order to simulate the model's exposure to real future data, the entire historical dataset up to the date was used for training the model, and the last six months period was kept as a test set. This way of evaluating the model's performance is really a forward one, meaning that the model is tested on data which it has never seen, thus the risk of information leakage is reduced and the model's predictive power is realistically measured. The Logistic Regression under this study was coded with the help of the scikit, learn library in Python. The training and evaluation of the model were carried out in a well, structured pipeline that contained feature scaling, model fitting, and prediction stages. Such an approach made sure that experiments can be repeated and results are consistent with each other.

XI. HYPERPARAMETER TUNING

In order to enhance model stability and generalization, only a small amount of hyperparameter tuning was done on the Logistic Regression classifier. Given that the model has only a few parameters that can be adjusted, the tuning was mainly aimed at controlling the complexity of the model rather than achieving high performance.

The main parameter that was changed during the tuning was the regularization strength. Regularization strength determines the level of fitting the data of the training and generalization of the model. To understand how sparsity and shrinkage of coefficients changed the prediction performance of a combination of numerical and sentiment, based features, both L1 and L2 regularization methods were tested [8], [9]. Different solvers, such as liblinear and lbfgs, which are appropriate for binary classification, were also tried.

Various model architectures were tested using cross, validation that was exclusively performed on the dataset's training portion. The criteria for choosing were accuracy and F1, score, which ensured that the increments in performance were not due to class imbalance or overfitting on a single metric [5]. Instead of just taking the configuration with the highest accuracy, the final set of parameters was selected based on consistent performance across evaluation measures.

The fine, tuned Logistic Regression model exhibited greater stability than the one with default parameters, especially after sentiment features were added. This result indicates that using controlled regularization is very important when data from different sources is combined market indicators and textual sentiment signals.

XII. MODEL EVALUATION

To determine the accuracy of the model in forecasting the Nifty 50 index's opening direction, the proposed model's performance was measured by the adoption of classification metrics according to the model's effectiveness. The test utilized the last six months' isolating data from the training process to reflect the forecasting situation in the real world.

A number of performance metrics were chosen to give a comprehensive evaluation of the model. These are Accuracy, Precision, Recall, F1, Score, and ROC, AUC, which are standard in financial classification cases [9],[10].

Accuracy essentially expresses how many of the model's predictions matched the actual outcomes relative to the total number of cases in the test set. However, accuracy being the overall measure of performance, only partially reveals the behavior of different classes when market movements are uneven [8].

Precision is the fraction of forecasted upward openings that were genuinely so, whereas Recall is a measure of how well the model's upward movements matched the truth. Thus, these two metrics come in handy for evaluating the trustworthiness of the direction, of, movement predictions.

The F1, Score is the point where Precision and Recall meet. It is the harmonic mean of these two metrics and serves as a compromise between them. F1, Score was the metric of choice to offset both measures, thus giving a more credible evaluation of the model performance when class distributions are not exactly equal [9].

The **ROC-AUC** metric was used to evaluate the model's ability to distinguish between positive and negative opening directions across different classification thresholds. A higher ROC-AUC value indicates stronger discriminatory capability.

Using the six-month test dataset, the Logistic Regression model achieved an overall accuracy of 74%, with an F1-Score of 0.73 and a ROC-AUC of 0.79. These are the results which confirm that the model can still be trustful when tested on out, of, sample future data. By adding sentiment features, the authors were able to increase the accuracy of their predictions by roughly 6% as compared to a model that was only trained on numerical market indicators [5], [9], [14].

On examining the confusion matrix, it was found that the model had a very slight edge in detecting the opening ups rather than the downs. This trend is in line with the situation in the literature where financial news sentiment has been found to carry a slightly positive bias during normal market conditions [8], [15].

XIII. LIMITATIONS

The framework presented here, while showing good promise in forecasting, has some limitations which the authors should disclose. The work is constrained to daily market data; hence the study misses out on intraday price fluctuations and instant market reactions within the trading session [8].

Model sentiment relies for the most part on dawn headlines of financial news. Even though headlines offer an immediate insight into market sentiment, they might not always be able to capture the full scope or level of complex financial events. Consequently, some sentiment signals might be a bit too simple or only partially reflect the situation.

Transformer, based models for sentiment like FinBERT and RoBERTa, which are designed for financial text, may at times classify neutral or unclear sentences incorrectly depending on the phrasing and context [2], [5]. This might result in some noise in the sentiment attributes that the model utilizes.

Moreover, one limitation of the present study is the use of Logistic Regression technique for classification. This model assumes that the relationship between input features and predicted output is linear, therefore, it can hardly capture nonlinear market behavior during situations of extreme volatility or unusual trading conditions [1], [14]. In the end, even though the dataset encompasses years, the assessment is done based on only the latest six months of data. Although such a way of thinking is in line with the practice of forecasting in the real world, it is possible that by extending the evaluation to several test windows or different phases of the economic cycle, the results would be even more solid.

XIV. FUTURE SCOPE

This study sets the stage for developing in various significant ways. For instance, an improvement may be made by employing up, to, date real, time sentiment data derived from a broader array of sources including social media platforms, financial discussion forums, and live news feeds. These channels may shed light on investor reactions that are still fresh and thus may help in further improving the accuracy of short, term predictions [7], [9].

Moreover, future research could explore the use of state, of, the, art machine learning and deep learning methods. With thoughtful designs LSTM, GRU, Random Forest classifiers, and transformer, based architectures might be able to spot nonlinear relationships as well as temporal dependencies in financial time, series data at least to a higher degree of accuracy [6], [15]. Comparing these models with statistical methods that are interpretable could offer a way to weigh the trade, off between performance and explainability.

The predictive framework can be also improved by incorporating more comprehensive macroeconomic and market, related variables. Contextual factors like inflation rates, foreign institutional investor activity, and commodity prices could be used as additional clues to understand market movements [8], [16].

Besides daily predictions, the capability of the model may be increased up to intraday forecasting, sector, level analysis, or cross, market influence studies. Moreover, embedding the resulting framework into an analytical dashboard in real, time would significantly raise its practical usefulness, as it would allow traders and analysts to keep an eye on the predictions and market signals more efficiently.

XV. CONCLUSION

This work started with a prediction problem of the next day opening direction of Nifty 50 by using a combination of numerical market indicators and sentiment extracted from financial news. A thorough study of the current literature revealed that the majority of both traditional and machine learning based models usually depend only on market historical data and that models involving sentiment lack interpretability. Thus, these two drawbacks led to the creation of a hybrid and interpretable prediction framework.

Our method combines world market trends with measures of volatility and sentiment in a Logistic Regression setting. For a non, biased evaluation of our model, we adopted a time, series split while training on the past data and testing on the last six months. The experimental findings indicate that incorporating sentiment in the model helps to make next, day market predictions more accurate and therefore, models with only numerical indicators are outperformed by the addition of sentiment.

This work has significantly highlighted that model transparency is good. For instance, complex black, box models are not understandable, while the suggested framework can tell the investors how each factor has influenced the wanted market direction. To the best of the model's ability, it facilitates decision, making by providing explanations which are a prerequisite in the financial domain.

Overall, the findings confirm that combining investor sentiment with quantitative market data provides a more comprehensive perspective on short-term market behavior. The work contributes a practical and scalable framework for Nifty 50 opening direction prediction and offers a foundation for future research in sentiment-driven financial forecasting.

REFERENCES

- [1] L. Dsouza, M. G. A., and S. Bhogle, "Stock price prediction of Nifty 50 in India using LSTM and ARIMA during black swan events," in Proc. Int. Conf. Multi-Agent Syst. Collaborative Intell. (ICMSCI), IEEE, 2025, pp. 1–6, doi: 10.1109/ICMSCI62561.2025.10894191.
- [2] D. R. Meena and K. Maharajan, "The role of sentiment analysis and transformer models in stock market price forecasting," in Proc. 6th Int. Conf. Mobile Comput. Sustainable Informatics (ICMCSI), IEEE, 2025, pp. 1–6, doi: 10.1109/ICMCSI64620.2025.10883376.
- [3] A. T. Oyewole, O. B. Adeoye, W. A. Addy, C. C. Okoye, O. C. Ofodile, and C. E. Ugochukwu, "Predicting stock market movements using neural networks: A review and application study," Comput. Sci. IT Res. J., vol. 5, no. 3, pp. 651–670, 2024, doi: 10.51594/csitrj.v5i3.912.
- [4] R. Saqur, K. Kato, N. Vinden, and F. Rudzicz, "NIFTY financial news headlines dataset," arXiv preprint arXiv:2405.09747, 2024.
- [5] C. Liu, A. Arulappan, R. Naha, A. Mahanti, J. Kamruzzaman, and I. H. Ra, "Large language models and sentiment analysis in financial markets: A review, datasets, and case study," IEEE Access, vol. 12, pp. 134041–134055, 2024, doi: 10.1109/ACCESS.2024.3445413.
- [6] L. D. Dsouza, J. A. Nasir, M. M. Kamal, and L. Connolly, "Leveraging large language models for predicting stock option valuation and financial risk mitigation," in Proc. IEEE Int. Conf. Data Mining Workshops (ICDMW), IEEE, 2024, pp. 1–6, doi: 10.1109/ICDMW65004.2024.00019.
- [7] B. J. Mary, "Predicting NIFTY movements from global news and S&P futures," ResearchGate Preprint, 2024.
- [8] M. Sharma, R. Bansal, and A. Garg, "The role of sentiment analysis in stock market forecasting: A review," J. Risk Financial Manage., vol. 15, no. 11, p. 552, 2022, doi: 10.3390/jrfm15110552.
- [9] N. Yadav, "Enhancing stock trend prediction using BERT-based sentiment analysis and machine learning techniques," Int. J. Quantitative Res. Modeling, 2024.

-
- [10] C. Manjunath, B. Marimuthu, and B. Ghosh, "Analysis of Nifty 50 index stock market trends using hybrid machine learning model in quantum finance," *Int. J. Electr. Comput. Eng.*, vol. 13, no. 3, pp. 3549–3560, 2023, doi: 10.11591/ijece.v13i3.pp3549-3560.
 - [11] N. Sakhare, D. Midhun, and D. Dhabliya, "Stock market movement prediction using news analytics," *SGS Eng. Sci.*, vol. 1, no. 1, pp. 1–12, 2025.
 - [12] R. Bhat and B. Jain, "Stock price trend prediction using emotion analysis of financial headlines with distilled LLM model," in *Proc. Pervasive Technologies Related to Assistive Environments Conf. (PETRA)*, ACM, 2024, pp. 1–8, doi: 10.1145/3652037.3652076.
 - [13] R. Awasthi, M. Sharma, and K. Verma, "Sentiment analysis models for Bank Nifty index: An overview of predicting stock market sentiment in India," *Int. J. Res. Eng. Technol.*, vol. 12, no. 4, pp. 55–63, 2023.
 - [14] A. Garg, P. Singh, and V. Mehta, "NiftyLLaMA: Leveraging large language models for Indian stock market forecasting," in *Proc. ACM Int. Conf. Data Sci. Financial Analytics*, ACM, 2024, pp. 221–229.
 - [15] S. Patel, R. Desai, and N. Trivedi, "The role of sentiment analysis in financial stress periods: Evidence from emerging markets," *J. Risk Financial Manage.*, vol. 15, no. 2, p. 552, 2022.

AIR QUALITY INDEX PREDICTION AND HEALTH IMPACT ANALYSIS USING MACHINE LEARNING

Nareen Ansari and Swapnali Lotlikar

Department of Information Technology, Usha Pravin Gandhi College of Arts, Science and Commerce Mumbai, India

ABSTRACT

Deteriorating air quality can affect a human's respiratory system drastically, urging need for accurate Air Quality assessment. Air Quality Index (AQI) can be explained as an index that reports the quality of the air. This study proposes a machine learning framework that predicts AQI and analysis related health risk levels. Parameters that are used as input features to build predictive models are multiple pollutant parameters that include PM_{2.5}, PM₁₀, NO, NO₂, NO_x, NH₃, CO, SO₂, and O₃. The dataset used in this study consist of over time recorded AQI of major Indian metropolitan cities including Mumbai, Delhi, Kolkata, Chennai, and Bangalore. LightGBM regression was used to predict the Air Quality Index, resulting in a low prediction error. Further, supervised machine learning models such as Light-GBM, Random Forest, and Catboost were used for health risk classification. AQI values that were predicted were then mapped to standardised AQI categories, which were further interpreted into health risk levels. This study concludes that ensemble-based models perform better than traditional classifiers, resulting in higher accuracy in health risk classification.

Index Terms—AQI, Pollutants, Health risk, Indian metropol- tan cities, machine learning

I. INTRODUCTION**A. Background**

Air pollution is turning into one of the biggest environmen- tal problems we have right now in this century. It threatens people's health and messes with the balance in nature, plus how cities can keep going sustainably. It's not just some minor issue. From what global health reports say, being around bad quality air for a long time leads to all sorts of health problems like respiratory issues, heart diseases, neurological disorders, and even early death. That part stands out because it affects so many people without them realising it at first. In places like developing countries, and especially India, air quality has deteriorated drastically. It's because cities are growing fast, population is increasing, factories are popping up, and tons more cars on the roads. All that adds up quickly. So Indian metropolitan cities often have pollution way over the limits set by the country or even worldwide rules, this raise alarm for the public's health To monitor and communicate the severity of air pollution, regulatory authorities employ the Air Quality Index (AQI), a standardized indicator that aggregates concentrations of multiple ir pollutants into a single numerical value. The AQI system converts complex environmental measurements into five health-related air quality categories which help both the public and decision-makers understand pollution levels and their health consequences. The AQI system works well for public communication but its usefulness increases when it has both exact prediction abilities and early warning systems. En- vironmental prediction tasks now have better solutions because machine learning (ML) and data-based modeling methods have advanced during the last several years. Machine learning algorithms demonstrate superior capabilities when compared to traditional techniques because they can extract intricate pat- terns from extensive datasets while managing multiple variable relationships and simulating complex nonlinear connections. Various environmental and atmospheric investigations, includ- ing air quality analysis, have demonstrated the effectiveness of ensemble-based methods that include Random Forests and Gradient Boosting models.

B. Objectives

The specific objectives of this study are as follows:

The research demonstrates how machine learning methods can monitor air quality and provides a scalable system that helps environmental authorities, smart city projects and public health organisations to better control air pollution.

- To create strong regression models that will be able to predict AQI values through the analysis of pollutant concentration measurements.
- To develop classification models that will be used to evaluate health risk based on AQI bucket classifications.
- To assess how different machine learning algorithms perform by comparing traditional models with

ensemble- based approaches.

- To measure how different air pollutants affect changes in AQI levels to different degrees.

C. Purpose, Scope, and Applicability

The main goal of this research is to create a precise and understandable machine learning system which can predict Air Quality Index (AQI) values and determine health risk categories based on air pollution data from major Indian cities. The research study will use advanced ensemble learning methods to solve the problems which traditional statistical models face when they need to analyze non-linear relationships between multiple pollutants. The research intends to develop an AQI prediction system which also converts complicated model results into understandable health risk categories based on AQI buckets to help people make better choices. The research study will connect environmental data analysis with public health awareness by creating a single system which combines prediction and health risk assessment.

Scope: The research study investigates air quality data which was gathered from five major Indian cities which include Delhi, Mumbai, Chennai, Kolkata, and Bangalore. The research investigates essential air pollutants which include $PM_{2.5}$, PM_{10} , NO , NO_2 , NO_x , NH_3 , CO , SO_2 , and O_3 which constitute the fundamental components of AQI measurement and environmental regulation. The research study uses machine learning models which include Random Forest, LightGBM, CatBoost, Support Vector Machines, and Neural Networks to perform two tasks: AQI prediction through regression models and multi-class classification of AQI buckets. The research study applies data preprocessing techniques which include SMOTE class balancing and feature importance analysis to strengthen model performance and make results easier to understand. The research study restricts itself to analyzing historical pollutant concentration data while it fails to create models for long-term time-based patterns and current weather conditions. The results serve to establish both predictive abilities and methodological strengths but do not support actual system usage.

Applicability: The framework we suggest can be used in various fields which include environmental monitoring and public health management and smart city development. The environmental regulatory agencies can use our model to create early warning systems which will help them determine pollution levels with greater accuracy. The AQI bucket system enables health risk classification system to provide better air quality information which people can easily understand. The framework lets smart city platforms and urban planners track air quality changes while they test different pollution control methods and create evidence-based urban policies. The health risk categorization system lets healthcare authorities create timely advisories which protect vulnerable groups including children and elderly people and those with existing respiratory or cardiovascular illnesses. The proposed approach contains a scalable design which uses data-driven methods to extend its applicability to multiple cities and regions while enabling future integration with IoT-based air quality monitoring systems and real time tracking technology.

II. LITERATURE SURVEY

The period from 2020 to 2025 has seen an increase in research studies about AQI prediction and air quality forecasting and health impact assessment which use machine learning and deep learning methods. The studies show that data-driven models are more preferred instead of traditional statistical methods because precise air quality prediction systems are needed which provide real-time data and health information.

Radzuan and Martin identified essential flaws that affect air quality prediction results in India's EIA process. The research demonstrated the necessity of creating better standards which require advanced monitoring techniques to improve air quality assessment methods [6]. Pant et al. studied how multiple machine learning classifiers could predict Air Quality Index (AQI) based on historical pollutant data from different cities in Uttarakhand India. Their research proved that Random Forest and Decision Tree classifiers which operate as ensemble-based models achieve higher performance than standard machine learning methods with 99 percent classification accuracy [1]. Castelli et al. proved that SVR with an RBF kernel successfully predicts hourly pollutant levels and AQI measurements throughout California.

The study showed that using all variables achieved 94.1% accuracy when classifying AQI into six EPA-defined categories [8]. Gupta et al. evaluated three algorithms: Support Vector Regression, Random Forest, and CatBoost, to predict AQI in four Indian cities. In Bangalore, SVR achieved an accuracy increase from 66.46% to 87.17% while Random Forest reached 97.61% accuracy in Hyderabad. The study results showed that Random Forest and CatBoost performed better than SVR because AQI modeling requires balanced datasets for accurate predictions [12]. Ravindiran et al. demonstrated that AQI levels in Visakhapatnam first increased before they decreased during the COVID-19 lockdown in 2020 and then rose again afterward with $PM_{2.5}$ and PM_{10} emissions serving as the main factors. The two algorithms Random Forest and CatBoost reached

exceptional prediction precision with Random Forest achieving $R = 0.9998$ and CatBoost reaching $R = 0.9936$ which demonstrated that machine learning techniques effectively predicted AQI levels [21]. Ravindiran et al. used various machine learning models which included ensemble stacking and XGBoost as their predictive models. The ensemble stacking model achieved the highest performance ($R^2 = 0.999$) for both training and validation, while XGBoost also performed strongly ($R^2 = 0.999$ training, 0.989 validation), with PM_{10} identified as the most influential pollutant ($r = 0.96$) [10]. Ameer et al. evaluated multiple machine learning models for air quality forecasting which showed Random Forest as the top-performing model with its MAE range of 6 to 18 percent and its RMSE range of 0.05 to 0.18 while Gradient Boosting produced its maximum prediction errors [7].

Singh et al. created an online machine learning system which predicts Air Quality Index values. The study found that Random Forest ($R^2 = 0.998$) and XGBoost (100% accuracy after tuning) performed better than all other tested models which enabled successful monitoring of respiratory health conditions and their prevention methods [22]. Seaton et al. created the MAQS-Health air quality modeling system. Their research showed that high-resolution dispersion modeling methods can accurately predict pollutant concentrations [5]. Singh et al. used machine learning models to demonstrate that XGBoost achieved the highest accuracy at 81 to 98 percent while Random Forest reached 79 to 97 percent which showed machine learning methods work well for assessing health impacts [17].

III. DATASET DESCRIPTION

The research study used air quality data from five major Indian cities which include Delhi, Mumbai, Chennai, Kolkata, and Bangalore. The data which has been used in the research is secondary in nature and has been taken from a Kaggle opened data platform. These cities have been selected because their residents create high population densities which generate multiple industrial operations that generate distinct pollution patterns and environmental contamination. The dataset contains daily observations of key air pollutant concentrations along with corresponding computed Air Quality Index (AQI) values and AQI bucket labels which national air quality standards define. The AQI categories create a standardized method to assess pollution levels and their health effects which allows for both numerical data evaluation and air quality assessment through specific categories. After completing the data cleaning and pre-processing steps, 18265 authentic data points were identified which were used for study. The process of identifying and removing duplicate entries resulted in a dataset that contained no extra data points. The resulting dataset provides a reliable and consistent foundation for machine learning-based AQI prediction and health risk classification.

A. Features and Target Variables

The dataset contains various pollutant parameters that function as independent variables which scientists use to develop their models.

The pollutants which environmental agencies monitor because they present dangers to both air quality and human health.

The input features used in this study are: $PM_{2.5}$ (Fine particulate matter with diameter $2.5 \mu m$) PM_{10} (Particulate matter with diameter $10 \mu m$) NO (Nitric oxide) NO_2 (Nitrogen dioxide) NO_x (Oxides of nitrogen) NH_3 (Ammonia) CO (Carbon monoxide) SO_2 (Sulfur dioxide) O_3 (Ozone) The study selected these pollutants because they showed direct effects on AQI calculation and they appeared in previous air quality research studies.

The research established two target variables which enable both regression and classification methods to be executed.

AQI (Numerical Value): Used as the dependent variable for regression modeling to predict continuous AQI values. AQI Bucket (Categorical Label): Used as the target variable for multi-class classification, representing different air quality and health risk levels. To handle class imbalance problems which result from fewer instances of clean air classes, "Good" and "Satisfactory" AQI classes were combined into one "Healthy" category. The new category distribution better handles class distribution while it maintains high stability through more accurate classification results which preserve the ability to understand health risk levels.

IV. METHODOLOGY

A. Experimental Setup

The entirety of this research project used Google Colab which operates as a Python-based data science platform that enables users to run code interactively while testing their work and showing their results at each stage.

Google Colab was selected to ensure transparency and reproducibility of the machine learning workflow, allowing systematic inspection of data preprocessing, model training, and evaluation steps.

The analysis required various Python libraries and frameworks which provided established support for different analytical tasks. In the research, NumPy and Pandas were used through- out the project to perform numerical calculations, handle data and prepare data for analysis. Matplotlib and Seaborn are used for exploratory data analysis and to visualise pollutant distribution patterns because they provide flexible, effective methods for creating statistical visualisations. Scikit-learn provides a comprehensive framework that supports machine learning model development together with preprocessing tools and evaluation metrics which enable users to handle supervised learning processes. LightGBM and CatBoost both deliver advanced ensemble-based gradient boosting models that have been designed to achieve optimal performance when applied to structured tabular data.

Then, employed the Imbalanced-learn library to solve AQI category classification problems by using the Synthetic Minority Oversampling Technique (SMOTE). 80-20 split was used to create training and testing data sets, which helped to test the model's ability to generalise. Stratified sampling was used to create both subsets while maintaining the original class distribution of AQI categories, which enabled them to measure performance without bias.

B. Data Preprocessing

Machine learning pipelines for real-world environmental data require critical data preprocessing, which handles inconsistent and noisy datasets. Implemented multiple preprocess- ing methods to enhance data integrity and improve model performance. First, converted AQI values into numeric data because regression models and quantitative analysis require that format. The dataset was then examined for missing values, and appropriate verification procedures confirmed that no critical data gaps affected model training. The Interquartile Range (IQR) method was used to detect outliers by finding extreme values through its statistical dispersion approach. The process ensured that the university's model- building activities did not use any wrong data points. The analysis showed that the dataset contained no major outliers that needed to be deleted from the study. Label encoding was used to convert city names into numerical forms, which allowed their use in machine learning models. The training data used the Syn- thetic Minority Oversampling Technique (SMOTE) to address class imbalance problems that existed in cleaner air quality categories. SMOTE generates synthetic samples for minority classes, thereby improving model robustness and preventing bias toward majority classes.

- 1) **AQI Bucket Reclassification:** The Air Quality Index sys- tem used predefined threshold ranges that national air quality standards established to create standard AQI categories. These categories represent varying levels of air pollution severity and corresponding health risks, making them suitable for classification-based analysis. The dataset contained original AQI bucket labels, which were used to create a new AQI bucket column that applied official AQI threshold rules to the numerical AQI values as shown in Table 1 below. The computed classification was systematically compared with the original labels to check for consistency and correctness. The validation process confirmed a high degree of alignment between calculated and provided AQI categories, ensuring the reliability of the classification framework. To improve classification accuracy and fix class distribution problems, the system combined Good and Satisfactory AQI categories into one Healthy class. The reclassification process distributed data better while maintaining important health risk information.

TABLE I: Reclassified AQI Categories based on national air quality standards

Reclassified AQI Class	Original CPCB Categories	AQI Range
Healthy	Good, Satisfactory	0 – 100
Moderate	Moderate	101 – 200
Poor	Poor	201 – 300
Very Poor	Very Poor	301 – 400
Severe	Severe	401 – 500

- 2) **Synthetic Minority Oversampling Technique (SMOTE) Algorithm.:** Air quality datasets display class imbalance prob- lems because they have too few extreme pollution instances to meet testing requirements. The Synthetic Minority Over- sampling Technique (SMOTE) was used to solve this problem after reclassification of the AQI dataset as shown in Fig. 1. SMOTE creates artificial samples for minority groups through their existing data points which it uses to build new samples, thereby achieving better class distribution without replicating existing data. The process developed better model learning abilities while decreasing the model's preference for dominant AQI categories.




Fig. 1: Class distribution of AQI health risk categories before and after applying SMOTE

3) Machine Learning Models: The research evaluated multiple supervised machine learning models to determine their ability to classify AQI buckets. The models display a wide range of learning methods, which include both basic linear classifiers and sophisticated ensemble methods.

The baseline linear classifier of the system uses Logistic Regression. Support Vector Machine (SVM) classifies data using non-linear patterns through its radial basis function (RBF) kernel. Random Forest Classifier operates as an ensemble model which utilizes decision tree-based algorithms.




Fig. 3: Flowchart for the proposed methodology.

The LightGBM Classifier functions as a gradient boosting framework which achieves optimal performance through its efficiency and accuracy design. The CatBoost Classifier enables the effective processing of categorical data while it minimizes the risk of overfitting. The Multilayer Perceptron (MLP) Neural Network enables the training of non-linear data patterns. In research, identical training data is used to train each model, which they tested with a separate test dataset to achieve unbiased results.

LightGBM Regressor was selected for AQI prediction because it delivers strong results with tabular datasets and it manages feature interactions and offers quick computational performance. The regressor used standard error-based metrics to evaluate its prediction accuracy.

The study implements its proposed machine learning work- flow which begins with AQI bucket classification according to Figure 3. The complete process begins when the dataset is selected and prepared, which includes SMOTE data balancing and train-test partitioning followed by feature scaling and model development using Random Forest Regression CatBoost Regression and LightGBM Regression. SHAP is used to show how input features influence their chosen predictive model.

V. RESULTS AND FINDINGS

The section shows the research outcomes which were obtained through testing the classification and regression models which were developed to predict AQI levels and assess health risks. The study assesses multiple machine learning algorithms by using specific numerical metrics to measure their performance. The study presents results from feature importance analysis and health advisory integration as two main sources of insights.




Fig. 4: Model Comparison

A. Classification Performance

The classification results show that ensemble machine learning models produce better AQI bucket predictions than standard classifiers do as shown in Fig. 4. The Light Gradient Boosting Machine (LightGBM) reached the highest classification accuracy of 97.23% among all tested models because it effectively modelled complex relationships that exist between air pollutant features.

The Random Forest Classifier achieved 97.07% accuracy, which placed it in second position, while the CatBoost Classifier reached 93.88% accuracy, which made it a strong competitor. The high accuracy results demonstrate how effective ensemble methods operate because they utilise multiple decistrong predictive results through its implementation of the following error metrics: Mean Absolute Error (MAE) reached 4.66 Root Mean Squared Error (RMSE) reached 14.64 The low MAE value demonstrates that the predicted AQI values show only slight deviation from actual observed values, which the model calculated.

Table II: Comparison of Machine Learning Models Based on Accuracy

Machine Learning Model	Accuracy
Logistic Regression	0.4188
Support Vector Machine (RBF)	0.5188
Random Forest	97.07
LightGBM	97.23
CatBoost	93.88
Neural Network	0.3926

The RMSE value shows that the regression model will produce most of its predictions with high accuracy while maintaining its overall dependable performance.

The findings prove that gradient boosting regression models successfully learn complex pollutant to AQI relationships while delivering precise numerical forecasts. Early warning systems and policy decision-making both require exact AQI estimations because even minor AQI estimate errors will affect health recommendations.

TABLE III: Error Metrics of LightGBM Regression Model

S. No.	Metric	Value
1	Mean Absolute Error (MAE)	4.66
2	Root Mean Squared Error (RMSE)	14.65

C. Feature Importance Analysis

Random Forest feature importance scores together with SHAP (SHapley Additive exPlanations) values were utilised to assess how individual pollutants affect AQI prediction accuracy. The analysis as shown in Fig. 5 indicates that Sion trees to decrease variance while enhancing generalisation.

The traditional models, which include Logistic Regression PM2.5 and PM10 serve as the major elements which determine and Support Vector Machines (SVM) showed substantial per- formance decreases compared to other methods . The system fails because it cannot handle class imbalance problems and multiple pollutant interactions, which require complex rela- tionships to be modelled. The classification results demonstrate that ensemble-based methods work effectively for AQI bucket prediction tasks.

Table II presents a detailed numerical comparison of ma- chine learning models based on accuracy, which shows Light- GBM as the most accurate model and Random Forest and CatBoost as the second and third most accurate models re- spectively.

B. Regression Performance

Regression methods are used to estimate continuous AQI values while building the prediction system, which includes an AQI classification system. The LightGBM Regressor achieved AQI results throughout all testing models. Particulate matter functions as the primary factor which causes air quality to deteriorate in urban areas according to existing environmental research studies.

People need to recognize fine particulate matter (PM2.5) as an essential danger to both environmental safety and human health because this pollutant has the ability to enter their respiratory systems. The gaseous pollutants NO2, NOx, and CO together with vehicle emissions and industrial combustion processes create major atmospheric changes which lead to AQI fluctuations.

The pollutants O3 and SO2 showed moderate effects on air quality because they contribute to pollution but their impact on the dataset results remains less significant. The results of feature importance testing help users understand machine learning models better while the results show which pollutants need special treatment for effective pollution control.




Fig. 5: Feature Importance

D. Health Risk Advisory Integration

The system uses predicted AQI buckets as input to generate health risk advisory guidelines through its predictive capa- bilities. The system defines specific health recommendations, ranging from safe outdoor activity guidelines under healthy air conditions to strict exposure warnings during severe pollution episodes. The system creates health advisories through its automatic generation process, which converts technical model outputs into information that both the public and decision- makers can understand and use.

VI. DISCUSSION

A. Interpretation of Results

The results demonstrate that ensemble machine learning models achieve high effectiveness in predicting AQI and classifying health risks. The models demonstrate better accuracy because they can identify non-linear relationships between different pollutants. The proposed framework can assist environmental monitoring agencies and smart city platforms and healthcare authorities.

B. Limitations

The study presents promising findings which require acknowledgment of its existing limitations. The analysis uses data from metropolitan cities which restricts its ability to assess air quality in smaller cities and rural areas that experience different pollution and dispersion patterns. Real-time data to obtain meteorological parameters was not used. The study did not create explicit models to represent time-based relationships.

VII. CONCLUSION AND FUTURE SCOPE

A. Conclusion

In this study, a complete machine learning system predicts AQI values and determines health risks through its analysis of pollutant data from major Indian urban areas. The results of the experiments show that LightGBM and Random Forest ensemble models produce accurate predictions together with dependable health risk assessments

B. Major Contributions

The project created an AQI prediction system, which includes both prediction and classification functions. The research team conducted a study that compared different machine learning algorithms. The project combined health risk advisories with air quality index predictions. The project discovered which pollutants had the most significant impact on air quality.

C. Future Scope

Future work may include: The system will implement current weather information through real-time meteorological data. The project will employ deep learning approaches through LSTM models to achieve time-based predictions. The project will extend its operations to new urban areas and remote rural locations. The system will function as an actual-time monitoring solution through web and IoT-based technologies.

REFERENCES

- [1] Pant et al., "Air Quality Index prediction using machine learning classifiers," 2019.
- [2] Maltare and Vahora, "AQI prediction for Ahmedabad using machine learning," 2020.
- [3] Pant et al., "Time series forecasting of AQI using CPCB data," 2018.
- [4] Liang et al., "Ensemble learning approaches for AQI prediction," 2020.
- [5] Seaton et al., "MAQS-Health air quality modeling system," 2017.
- [6] Radzuan and Martin, "Evaluation of EIA air quality assessment practices in India," 2016.
- [7] Ameer et al., "Comparative analysis of machine learning models for air quality forecasting," 2021.
- [8] Castelli et al., "SVR-based AQI prediction across California," 2019.
- [9] Zhang et al., "Machine-learning-based AQHI system for health risk assessment," 2021.
- [10] Ravindiran et al., "Ensemble models for AQI prediction in Indian cities," 2022.
- [11] Das and Gupta, "Hybrid and ensemble models for AQI prediction," 2021.
- [12] Gupta et al., "Machine learning approaches for AQI prediction in Indian cities," 2020.
- [13] Dubey and Rasool, "Impact of COVID-19 lockdown on air pollution in India," 2021.
- [14] Samad et al., "Prediction of air pollutants using nearby monitoring stations," 2020.
- [15] Gladkova and Saychenko, "Forecasting PM_{2.5} using ARIMA, Prophet, and LSTM," 2021.
- [16] Debeer and Minet, "Traffic video-based air pollution prediction," 2019.
- [17] Singh et al., "Machine learning-based health impact assessment of air pollution," 2020.
- [18] Haq, "SMOTEDNN for AQI classification and forecasting," 2022.

-
- [19] Shrirama and Malladi, "Pollution-aware routing using Dijkstra's algorithm," 2018.
 - [20] Alzu'bi et al., "Random Forest-based prediction of air pollutants," 2021.
 - [21] Ravindiran et al., "COVID-19 impact on AQI levels in Visakhapatnam," 2021.
 - [22] Singh et al., "Online machine learning system for AQI prediction," 2022.

INVENTO: AI POWERED INVENTORY MANAGEMENT SYSTEM

Aditi Manish Upadhayay and Dr. Neha Vora

Department of Information Technology, SVKM's Usha Pravin Gandhi College of Arts, Science and Commerce Mumbai, Maharashtra 400056, India

ABSTRACT

This document is about an inventory management system made as a full, stack AI, powered system of Next.js MERN stack. Besides that, it also incorporates modern frameworks such as NextAuth, Stripe, Material, UI, Redux Toolkit, and Chart.js. Most inventory systems to some extent come with only manual or semi, automated features but this system also consolidates AI, driven stock prediction, role, based access, subscription models, and interactive dashboards. Altogether these functionalities form a scalable SaaS (Software, as, Service) offering.

The part in the system responsible for predictive analytics is AI, based. It produces timely reorder alerts and thus, the user receives not only the data but even the insights that are ready for the next actions. This is because it aims to reduce the amount of manual work as well as to make the operations more efficient.

The platform supports different user roles for example, Admin, Manager, Supplier in quite secure authentication, real, time updates, and subscription, based billing. Experiments of system deployment in cloud environments greatly reveal not only its effectiveness but scalability and operational efficiency as well with it.

Keywords: Inventory Management, Artificial Intelligence, Next.js, MERN Stack, SaaS, Predictive, Analytics, Role, Based Authentication.

I. INTRODUCTION

Customers nowadays want products to be in stores and available for purchase almost anywhere. They want these products too to be delivered on time, at the right place and of good quality, but at prices that won't exhaust their finances [1]. Companies cannot but rely on efficient supply chains to make that happen; supply chains that connect suppliers, manufacturers, warehouses, and ultimately customers all over the world [2]. And, in fact, one of the biggest pieces of a well-functioning supply chain is inventory management [3].

Inventory in our discussion denotes all the materials, the raw materials, as well as the finished products that are kept at various points of the supply chain, ready either to be used in production or to be shipped out to customers [4]. Inventory management? That is pretty much the one process that goes on 24/7 in any business, planning, organizing, and controlling the stock, making sure that customer demand is being met and at the same time having a tight grip on the cost side [5].

What they want is to make sure that you don't have too much stock sitting around, but at the same time, you don't run out either [6].

In this project, the inventory management side of the story is mainly about determining the amount of material you need to order, sorting out the time for the order, the frequency for reordering, and figuring out the extent of your safety net, the amount of safety stock you should keep available [7]. However, of course, there are several other aspects that matter, such as forecasting demand, the lead time of orders, space in the warehouse, how much transportation costs, quality control of course, and even what to do with returns or defective products, and knowing where everything is in the system [8].

When done right, inventory management is a great tool to bring down your overall costs and also enables you to respond faster to a customers needs [9].

Deciding on the level of demand in the future is crucial for managing inventory. A significant portion of planning decisions revolves around expectations or, at the very least, assumptions about the future demand, particularly when one takes into account the time lag to replenish the stock [10].

When a company relies on erroneous demand data, it may suffer from numerous problems, such as excessive inventory, product shortage, more inventory carrying costs, sales loss, decrease in customer satisfaction, wastage of resources, and disruptions in production or supply chain functions [11].

In essence, good inventory management is about having the right products at the right place and time [12]. A perfectly balanced inventory company can go on with its operations without any hiccups, save on costs, and delight customers [13].

This is why inventory management has become a crucial factor in the areas of retail, logistics, supply chain management, and of course, multi-sourcing [14].

This paper presents an AI-driven inventory management system using the Next.js MERN stack, mobilized as a scalable SaaS platform. The system incorporates secure, role-based authentication, predictive analytics, and subscription billing functionalities via frameworks like NextAuth and Stripe [3]. The designed platform improves the level of productivity in the operations by issuing inventory reorder notifications on the spot, decreasing the need for human assistance, and providing a decision-making tool supported by AI-generated insights [4].

Scope - The project involves the full-cycle design to the final implementation of an inventory management system that is accessible over a network and comes with the below features [9].

Technology Scope:

We have created a website by combining Next.js, MongoDB, React, Node.js, and Redux Toolkit for managing the state [9].

Security Scope:

NextAuth is used to implement secure role-based authentication [8].

Business Scope:

Stripe is integrated for subscription management with monthly and yearly billing options [9].

Functional Scope:

The system is able to perform CRUD operations, deliver notifications, show analytics dashboards, provide AI-driven stock prediction, and issue reorder alerts [4].

Deployment Scope:

The system is compatible with cloud hosting services like Vercel, thus it can cater from small shops to big enterprises [5].

Assumptions:

System functionality as a standalone SaaS on the first release [5].

Limitations:

Integration of the system to the real-world scenarios of third-party logistics, supply-chain APIs, and warehouse automation is currently out of scope; however, such features could be considered for future editions [7].

II. RELATED WORK

Traditional Inventory Management Systems:

Conventional inventory systems mostly deal with simple stock record keeping, manual updating, and reordering based on fixed rules [1]. Such systems usually utilize spreadsheets or rudimentary database apps to handle product quantities, suppliers, and transactions [1]. They serve as a means to maintain inventory records, but they are devoid of automation, real-time insights, and forecasting features, which means that they often experience situations of either overstocking or stock-outs due to slow decision-making processes [2].

Web-Based Inventory Management Platforms:

A number of web-based inventory management solutions offer digital interfaces for handling products, suppliers, purchases, and sales [3]. These systems allow CRUD operations, simple reporting, and user access through web dashboards [3]. On the other hand, most of these platforms are only capable of static reporting and do not consider intelligent analytics, automated alerts, or adaptive forecasting mechanisms in their functionalities [3].

Inventory Systems with Analytical Dashboards:

Certain contemporary inventory solutions come with the integration of dashboards showing stock levels, sales trends, and performance metrics through charts and graphs [4]. Such systems enhance the readiness and the quality of decisions of the users through visual analytics [4]. In any case, they almost entirely rely on the presentation of historical data and do not have advanced features such as AI-driven prediction, demand forecasting, and proactive reorder suggestions [4].

AI-Enabled Inventory and Supply Chain Solutions:

Earlier studies have indicated the incorporation of artificial intelligence and machine learning components in inventory management especially in areas of demand forecasting, inventory classification, and optimization [5]. AI-based systems utilize past sales data, market trends, and predictive models to carry out inventory decisions in an automated manner and thus reduce the costs of operations [5]. However, while remaining very effective, many of these solutions are complicated, expensive, or purposely built for large corporations, making it difficult for small and medium-sized businesses to implement them [6].

SaaS-Based Inventory Management Applications:

Software as a Service (SaaS) inventory platforms deliver scalable, cloud-based solutions backed up with subscription models and role-based access [7]. Such systems offer flexibility, easy accessibility, and simple deployment [7]. Nevertheless, a large number of SaaS solutions concentrate primarily on scalability and controlling access, thus having very few intelligent automation and AI-powered insights built-in functionalities [8].

Problem Statement - Many organizations have often inventory management that is disjointed and done through spreadsheets, standalone software tools, or manual record-keeping [1]. These methods create inconsistent data, inaccurate records of inventory, delayed decisions on reordering, and poor inventory control [2]. Besides, the conventional systems are without the machine-learning-based insights which are necessary for demand forecasting, stock optimization, and automation of the routine inventory operations [5]. Hence, companies find it hard to keep the right stock levels, lower the cost of operations, and make timely and informed decisions [6].

Identified Sub-Problems:**Stock Visibility Issue:**

There is no real-time inventory monitoring system, which makes it almost impossible for store managers to know the stock status accurately [2].

Manual Reordering Problem:

The reorder decisions are based on reaction rather than prediction, thus stock-outs or overstocking situations are very possible [6].

Data-Driven Decision Gap:

The lack of AI-powered analytics deprives the company of the opportunity to forecast the demand, analyze the trends, and plan efficiently [5].

Multi-User Access Problem:

Role-based access control is undefined to a great extent, resulting in ill-defined permissions be it for administrators, managers, or staff [8].

III.GAPS AND KEY FINDINGS

An investigation into current inventory management systems combined with an extensive review of literature showed that there are quite a number of things that these systems lack [1]:

No real-time inventory visibility:

Inventory updates instantly in a few systems, but most systems do not provide live stock updates and thus management is not able to track and monitor the changes in inventory levels in a timely manner [2].

Lack of AI-based demand forecasting:

Traditional and web-based inventory systems mostly depend on the past data and do not bring AI or machine learning techniques to the table, which leads to inaccurate demand forecasting and hence inefficient stock planning [5].

Reordering done only after the minimum level:

Reordering only gets triggered when the inventory hits the minimum level, thus a prediction system that would generate automated and up-to-date reorder alerts is absent, and the result is stock-outs or overstocking [6].

Partial implementation of role-based access control:

Many systems fail to adequately allocate and identify user roles such as admin, manager, and staff resulting in both security breaches and operational confusion [8].

Insufficient analytics and decision support:

The existing solutions offer basic reports and dashboards aggregation of data but do not feature intelligent analytics for decision-making and the anticipation of an inventory strategy [4].

Scalability and cost limitations:

Advanced AI-powered inventory management systems are usually expensive and intended for large corporations, hence small and medium enterprises cannot afford them [7].

IV. PROPOSED WORK

The main intent of this project is the redesign and implementation of an AI-based Inventory Management System that breaks free of the limitations of the traditional inventory systems by incorporating modern web technologies, AI components along with a scalable SaaS architecture [4][7].

Instead of manual tracking or using spreadsheet systems, all inventory data will be gathered in a central database securely, thus ensuring accuracy and availability in real time [1][3].

A major component of the proposed work is the use of Artificial Intelligence to improve inventory decision-making. AI-based systems will check the past inventory and sales data and use it for demand forecasting, stock prediction, and alerting for automatic reorder [5]. In this way, the company can efficiently manage the inventory and the operational workflow without the risk of running out of stock, or to fall into the trap of piling up inventory [6].

The system also suggests implementing role-based access control, where users are verified through safe mechanisms [8]. Admin users can have read-only access to inventory, orders, payments, and analytics, thus, they will be able to monitor without interfering. Regular users will then be given full management privileges such as the ability to add, update, and handle the inventory data. This model ensures data safety and regulated access [8].

To support the SaaS business model, the system being designed is equipped with secure payment and subscription management features through Stripe [9]. With this, users can easily subscribe to different plans with tiered access and thus the system can be scaled up and is appropriate for businesses of different sizes [7].

The proposed solution is hosted on a cloud platform in order to guarantee high availability, scalability, and performance [7]. In general, the proposed work intends to provide a smart, secure, and scalable inventory management system that merges the instantaneous operations with AI-powered analytics to facilitate more accurate business decisions [4][5].

Components Frontend Development Tools

The frontend of the AI Inventory Management System is a Next.js app with React.js components styled using Material, UI / Tailwind CSS; this is a high, performance, scalable, and user, friendly combination.

Next.js is responsible for server, side rendering and optimized routing, which results in a remarkable boost in the overall performance of the app, a faster time to, interactive, and better SEO. At the same time, it allows fast page transitions and smooth rendering of dynamic content, which makes it a very powerful tool for web apps at a large scale.

React.js is based on a component model, which facilitates the creation of UI components that can be reused as well as the development of a modular structure of the application such as inventory dashboards, product cards, order tables, and analytics panels. Besides, this practice extends the lifecycle of code, makes it easier to manage, and helps to solve the issue of state across the whole app.

Material, UI and Tailwind CSS were chosen for designing a clean, modern, and responsive user interface. Such UI frameworks are instrumental in maintaining consistency in design, mobile responsiveness, and speeding up frontend development through pre, built components and utility classes.

In summary, this frontend technology stack is minimal, adaptable, and very scalable, thus perfect for that situation where you need real, time inventory updates, role, based dashboards, and AI, powered features in the proposed inventory management system.

Backend Development Tools

The backend of the AI Inventory Management System is powered by Node. js paired with Express. js, which together offer a robust, secure, and high, performance server environment for executing business logic, managing data, and handling system flows.

The runtime environment chosen for the system is Node. js because it adopts a non, blocking, event, driven architecture. As a result, the system can serve multiple requests simultaneously without any significant lag, thus making the system suitable for operations that require real, time updates such as inventory updates, order processing, payment handling, and notification management.

Express. js, which is considered as a minimalist and unopinionated web framework, is used to develop the server, side logic of the AI Inventory Management System along with Node. js. It helps to build RESTful APIs encapsulating main backend features such as product management, category and supplier handling, purchase records, orders, invoices, subscriptions, and payment transactions. Express. js makes handling routes, middlewares, requests, and errors more straightforward.

The secure user authentication and role, based access control were enabled by implementing NextAuth and JWT at the authentication and authorization level. On top of that, admin and user permissions are controlled at the API point level to safeguard sensitive inventory and financial transactions.

By integrating Generative AI / OpenAI API into the backend, AI, based solutions such as demand forecasting, stock prediction, automated reorder alerts, and intelligent analytics can be offered, thereby facilitating enhanced decision, making.

Stripe API is a primary tool for backend payment processing and subscription management, which facilitates safe transactions, invoice production, and tiered accessibility for SaaS customers.

Basically, backend development tooling offers a strong and scalable base for handling stock workflows, security implementation, provision of AI, powered features, and ensuring seamless communication with both frontend and database layers.

DATABASE

MongoDB is used as the backend database due to its flexible schema and high scalability. It efficiently stores and manages data related to users, products, inventory, orders, invoices, payments, and subscriptions, and integrates seamlessly with Node.js applications.

RESULTS AND DISCUSSION

Invento, the AI-powered Inventory Management System, was thoroughly trialed and validated through a functional prototype and user testing [4][7]. The system is a robust SaaS web application that integrates architectural scalability with user-centric features to deliver a seamless inventory management experience [7]. Leveraging artificial intelligence and modern web application technologies, Invento legitimately addresses the major pain problems in inventory management through innovative AI solution components [4][5]. Invento guarantees real-time stock management and complete product, supplier, purchase, and order records, thus providing instant stock availability and greatly reducing manual errors [1][2]. The AI demand predictor component, by using past data, makes demand prediction easy and automatically generates smart reorder notifications that help to reduce stock-outs and overstocking [5][6].

Besides, dynamic interactive dashboards offer at-a-glance understanding of inventory metrics and sales trend graphs thus facilitating better decisions [4]. With role-based access control security is enhanced as only admins are allowed to supervise the activities of other users while regular users are only permitted to manage daily operations [8]. Interfacing with Stripe enables the system to securely process subscription and payment transactions [9]. Hosting in the cloud provides the system with the ability to handle increased workload without compromising the quality of the user experience [7].

The work presented in this paper investigates the extent to which the usage of AI in inventory management provides added value over and beyond traditional inventory management [5]. The AI-powered features incorporated in the system including forecasting and automation truly validate the concept of the system as an intelligent solution to inventory problems by enabling better inventory planning, reducing operational risks, and delivering a secure, scalable, and flexible solution that can be adopted by small, medium, and large businesses alike [4][6][7].

V. FUTURE WORK

Although the AI-powered Inventory Management System Invento performs well towards the achievement of the present project goals, there are numerous changes that might be executed for the next researches to a large extent raise the utility, cleverness, and extensibility of the system [4][7].

Advanced Machine Learning Models:

Subsequent editions may incorporate even more sophisticated machine learning and deep learning techniques in order to enhance the prediction accuracy of demand and stock levels [5].

Long short-term memory networks (LSTM) or reinforcement learning techniques could be implemented for improved handling of seasonal variations and fluctuating demand patterns [5].

IoT Integration:


Integrating IoT technologies such as smart sensors and barcode or RFID scanners can be a way to improve Invento [2]. This would allow stocks to be updated automatically, real-time tracking of goods, and less human intervention in inventory operations [2].

Multi-Warehouse and Multi-Location Support:

There is a possibility that future studies will emphasize enabling the management of inventories in multiple warehouses or retail locations, which would lead to centralized supervision and improved stock distribution strategies [7].

Supplier and Logistics Integration:

Connecting with third-party logistics providers as well as supplier systems can be introduced to facilitate the automation of purchase orders, delivery tracking, and supply chain collaboration [6].



FLOWCHART Model



Figure 1 – Home Page





Figure 2 – Login and Register Page






Figure 3 – User Dashboard Page




Figure 4 – Subscription Page




Figure 6 - AI Alerts Page




Figure 7-Admin Page




Figure 8 – Analytics Page

V1. CONCLUSION

The Invento system is a perfect example of how new web technologies and artificial intelligence can be blended to break the bounds of traditional inventory management systems [4][7].

The project essentially establishes a centralized, scalable, and intelligent platform that not only automates inventory operations but also offers real-time visibility and data-driven insights [1][3].

Invento makes it possible to handle products, categories, suppliers, purchases, orders, invoices, and payments efficiently via a secure, role-based system [8]. The incorporation of AI-powered demand forecasting and stock

prediction allows for better inventory planning, thus helping to avoid stock-outs and overstocking, and it also facilitates proactive decision-making [5][6]. Interactive dashboards make the experience even more user-friendly by showing smart analytics and trends [4]. The introduction of a SaaS-based architecture with secure authentication, cloud deployment, and subscription management renders the system adaptable and appropriate for businesses of various sizes [7][9].

Ultimately, the project demonstrates the tangible advantages of AI in inventory management and shows that intelligent automation can greatly enhance operational efficiency, accuracy, and scalability [5]. Invento is a dependable, future-proof, and highly efficient inventory management solution that is ready for the real world and capable of being adopted broadly [4][7].

VII. REFERENCES

- [1] Mugdha et al. , The authors explore the potential of machine learning demand forecasting in significantly altering inventory management processes under a circular economy model. They share their research at the 2024 International Conference on Communication, Control, and Intelligent Systems (CCIS). [Mugdha et al. , 2024]
- [2] Kong et al., The paper addresses multimission selective maintenance and inventory optimization problems for multi-component systems while considering stochastic dependency. The authors extend the model and validate it through a numerical example. The results show that the dependence between components affects the maintenance and inventory policies and vice versa. [Kong et al.,2024]
- [3] Nurprihatin et al., The authors combine the economic order quantity (EOQ) and ABC classification methods to propose a strategic inventory control system that focuses on increasing operational excellence. This paper was presented at the 2025 4th International Conference on Computational Modelling, Simulation, and Optimization (ICCMO).Nurprihatin et al. , 2025 .
- [4] Adebajo, Akinpelu et al. , The authors provide a comprehensive review of the current technologies in inventory and payment management, as well as future trends and tools, in this paper. They also discuss various integration challenges and the potential of technology in achieving more effective management. The paper was presented at the 2024 IEEE 5th .
- [5] Khaleel et al. , The article delves into the various aspects of artificial intelligence and its wide range of applications in computer science. Besides, the paper illustrates AI methods, categories, advantages and disadvantages, and the future of AI in computer science.
- [6] J. Zhu et al. , "Talk to your data: Enhancing business intelligence and inventory management with LLM, driven semantic parsing and text, to, SQL, " in Proc. 2023 4th Int. Conf. Data Analytics for Business and Industry (ICDABI), 2023, pp. 321, 325.
- [7] Albayrak nal, B. Erkeyman, B. Usanmaz, "Applications of artificial intelligence in inventory management: A systematic review, " Archives of Computational Methods in Engineering, 2023.
- [8] Chopra and Meindl have provided a detailed insight into supply chain management through their book, Supply Chain Management: Strategy, Planning, and Operation, 7th ed. (Pearson, 2019).
- [9] In their book Inventory Management and Production Planning and Scheduling, the authors Silver, Pyke, and Peterson explain the essential aspects of these topics through the third edition of the book published by Wiley in 2017.
- [10] M. Waller and S. E. Fawcett discuss in their article how the combination of data science, predictive analytics and big data initiates a revolution that will change the entire supply chain design and management which will be published in the Journal of Business Logistics, 2013, vol. 34, no. 2, pp. 77, 84.
- [11] A. Gunasekaran et al. discuss in their paper big data and predictive analytics usage for the improvement of supply chain and organizational performance in the Journal of Business Research, 2017, vol. 70, pp. 308, 317.
- [12] In the paper Strategic inventory management using machine learning techniques, P. K. Dey, S. Bhattacharya, and A. Ho addressed the issue of inventory management at a strategic level by the application of machine learning techniques, International Journal of Production Economics,2020, vol.

FORECASTING E-COMMERCE CUSTOMER SATISFACTION TRENDS USING ARIMA TIME-SERIES MODELING

Aarti Chavan and Smruti Nanavaty

M.Sc. Information Technology, Usha Pravin Gandhi College of Arts, Science and Commerce Mumbai, India

ABSTRACT

Customer satisfaction is said to play a vital role for the success of any e-commerce business because of the impact it has on customer loyalty and business image as a whole. However, in today's competitive e-commerce business environment, it has become incredibly important to forecast customer satisfaction before the event for better response through improved customer service levels. In this regard, survey methodologies adopted for forecasting customer satisfaction in the past are based on a subsequent event response mechanism for customer feedback generation, which is of limited use for the forecasting process. The aim of this research includes developing a prediction model through a time series forecasting mechanism for customer satisfaction scores based on support ticket information for e-commerce companies. The data would include variables such as 'Ticket Id,' 'Date/Timestamp,' 'Issue Type,' 'Resolution Time,' and 'CSAT.' The parameters for ARIMA models ' p, d, q ' would be based on ACF, PACF standards for optimal results. The accuracy of the model is gauged with respect to parameters Mean Absolute Error (MAE), Root Mean Squared Error (RMSE), and Mean Absolute Percentage Error (MAPE). The visualized plot of actual and forecasted trends of CSAT also helps managers to take efficient business decisions. The significance of predictive analytics for the improvement of customer experiences has been highlighted through this research study; thus, e-commerce organizations can take correct business decisions to assure high customer satisfaction levels and establish trust with their customers through this research study by closing the knowledge gap of utilizing real-time actual support ticket count with ARIMA model forecasting to derive efficient business decisions for reactive customer survey handling by organizations.

Index Terms—Customer Satisfaction, E-commerce Analytics, Time-Series Forecasting, ARIMA, Review Score Analysis

I. INTRODUCTION

In the constantly evolving and highly competitive world of electronic commerce, where customer experience remains one of the major facilitating factors distinguishing between potential competitors in the marketplace, both being in and staying in high gear of customer satisfaction makes for both a challenge and an imperative at the strategic level too. As the entire sphere of customer interaction increasingly shifts into the online world and customer support infrastructure takes on the status of the very first line of defense in the handling and resolution of customer concerns and grievances, here it is customer tickets filed by aggrieved parties and indicative of overall customer sentiment itself. Traditionally, customer satisfaction levels were viewed as static measures of tendencies like reaction to surveys and complaint records. Here they were and remain static and lack temporal context to inform us of the dynamics of customer sentiment itself. Due to the inherently high volumes and structured nature of customer support data timestamps, resolution rates, complaint domains, and satisfaction itself, there rest opportunities to employ temporal forecasting with the wealth of historical data in search of hidden trends and emerging patterns of customer behavior. Time series forecasting based on ARIMA models has been common in finance and economics domains for a while now. ARIMA seems to be best suited in scenarios where univariate forecasting is possible and where trends and lag effects can be utilized to forecast values. Applying ARIMA to various customer satisfaction measures collected for specific time intervals (e.g., averages per day or per week) would allow the service teams to forecast dips in satisfaction in advance. The aim of this research is to bridge this gap by utilizing ARIMA models to predict customer support activities of an online business. Hence, by being able to forecast general trends related to customer satisfaction, it is not only possible to improve allocation of resources aimed at providing services but also respond more to the needs of the customers. This is unlike other models, which are mostly micro-focused on classification that aims at forecasting satisfaction related to a ticket.

A. Objectives

This study sets out the following objectives:

- Construction of a customer satisfaction time series using real-world e-commerce review data
- Application of ARIMA for forecasting long-term satisfaction trends
- Evaluation of forecasting performance using standard error metrics

B. Purpose, Scope and Applicability

The aim of this research is to investigate and validate the utilization of ARIMA time series forecasting for satisfaction predictions for customers of online shopping. The model, aside from being useful for predicting customer satisfaction, will also be useful in helping the services team make proactive decisions. The research is intended to validate that time series forecasting is an under-leveraged feature that is useful for adding customer experience analysis. The scope is restricted to: The analysis of customer service records with timestamps

and satisfaction scores obtained from survey results. Cleaning the data, preprocessing, and converting it to time series format. Analysis of customer service records with timestamps and satisfaction scores from survey results. Aggregation of customer satisfaction scores on a weekly basis. Application of ARIMA, fitting it to predict the customer satisfaction scores. Visualization and interpretation to highlight key results from forecasts. There are no other aspects, such as ticket classification, sentiment analysis, and deep learning method implementation, within the scope. Such research has practical applicability Customer Experience Management: Predictions may help to identify trends of dissatisfaction and make early interventions. Operational Planning: Managers may better plan allocations when resources are needed for periods of low satisfaction. Trend data may be used to make management decisions on policy changes by executives. And, ARIMA could be integrated to display the satisfaction levels in real time.

II. LITERATURE SURVEY

Research by Londhe and Palwe (2022) proposed a new framework of forecasting retail sales per segment using a hybrid RFM-ARIMA model. By using RFM segmentation, users were accurately identified, allowing for better segmentation-based modeling with ARIMA. Although users benefited from better segmentation using RFM, customer satisfaction was overlooked, creating a need for satisfaction-based modeling using ARIMA with ticket structure feedback [1]. A case study by Hartanti et al. (2024) used ARIMA modeling in improving sales performance forecasting in B2C transactions. Data used was from orders, frequency, and monetary value, allowing ARIMA modeling to reflect short-term variations in straightforward transactions. Customer satisfaction metrics were, however, overlooked, creating a need for using customer experience with ARIMA modeling in addressing customer service transactions, as proposed in this paper [2]. Another research conducted by Londhe and Palwe (2022) also extended this research to retail trend forecasting using RFM clusters and ARIMA. While their research is focused on customer-centricity, it did not address service quality or satisfaction. Within our research, we have included satisfaction measures using CSAT scores from support tickets [3]. Joolfoo et al. (2022) have proposed a research paper that employs decision trees and logistic regression algorithms for predicting customer satisfaction using structured data, i.e., usage and demographic data, for telco customers. The classification has shown good accuracy, but time-series modeling is missing within this research. Our research aims to expand upon it and include time-series analysis to track satisfaction trends [4]. In other related literature, Polprasert et al. (2023) utilized random forest and gradient boosting models to build a model to predict e-commerce customer satisfaction scores. Their models were based on data related to delivery speed, quality of service, and product fit. Their models were accurate but only provided predictions at a single point in time; they did not adapt to changing customer satisfaction over time. Our proposed model builds on their success in accuracy but adds further value to the prediction process with our proposed ARIMA model in forecasting the trend of the satisfaction level [5]. In related literature, Ando et al. (2022) utilized unsupervised representation learning to estimate customer satisfaction based on data collected from call centers. The resulting model utilized multi-format loss functions to make the predictions more accurate. Their model handled unstructured audio and text data but did not successfully tap into the structured feature tickets and the process of forecasting satisfaction, which our proposed model addresses successfully [6]. The topic of customer satisfaction in e-commerce for the COVID-19 period is explored by G. Ilieva et al. (2022), and the authors also discussed various antecedents of CSAT, which include reliability, usability, and service response. Their survey-based approach helped seek an informative understanding of behavioral shifts in consumers' behaviors; however, it did not make use of any forecasting technique to show future customer satisfaction patterns, which is covered in our approach with ARIMA [7]. Mehta et al. (2024) experimented with comparing the performance of contemporary ML paradigms, including 'SVM,' 'RF,' and 'MLP,' whereas they considered 'structured + feedback' data for prediction with better accuracy using ML due to favoring 'interpretability,' yet they did not undertake any time series and trend prediction as is carried out in our framework with ARIMA [8]. We can use Ko et al.'s research (2022) on speech tones in customer support conversations to predict satisfaction levels. Their multimodal model performed well with high scores, but they did not include trend forecasting. Hence, their model can be used in conjunction with ours, which is based on time series modeling using ARIMA [9]. Gupta et al. (2024) developed a sales forecasting model with enhanced sentiment, using customer reviews and structured rating systems. They used fine-tuned ML models to predict

that the product has overrated Ness. Once again, Gupta et al. did not use temporal trend forecasting techniques like ARIMA, which are missing in current models [10].

Summary Of Key Studies Table I summarizes representative studies, their focus, strengths, and limitations, highlighting the research gaps addressed by this work.

III. METHODOLOGY

The proposed methodology is composed of a number of sequential stages to ensure the accurate and reliable forecasting of the trends related to customer satisfaction.

A. Requirement Analysis

Functional Requirements: The system should: Import and Manage Data: Import structured e-commerce review data with columns like Review ID, Order ID, Review Score, and Review Creation TimeStamp. Data Preprocessing: It allows users to preprocess e-commerce review data, such as to clean the data by removing missing, inconsistent, and duplicate records; transform the timestamp field(s) into a desired date and time(s), and maintain review score numerical consistency. Aggregate Trends: The users shall be able to aggregate individual customer review scores into average CSAT values for either a week or month period, thus forming a time series, univariate in nature, appropriate for the ARIMA model. Analyze Stationarity: The users will be able to analyze if the aggregated measures of the CSAT dataset are Stationary or non-Stationary and perform the necessary steps (may be differencing steps) to ensure Stationarity prior to applying the ARIMA model. Build Model: The users need to build and estimate the ARIMA models for the aggregated CSAT data series to predict the future trends of customer satisfaction levels. Visualize: The users will be able to visualize historical trends and predicted trends using CSAT with the help of a line plot, which will be quite useful for analyzing and understanding trends related to customer reviews conducted through e-commerce.

Table I Summary of Key Studies Related To Customer Satisfaction Forecasting

Ref.	Author(s) & Year	Objective	Methodology	Key Findings
[1]	Box and Jenkins (1976)	Introduce systematic time-series forecasting techniques	ARIMA modeling for univariate time series	ARIMA provides reliable forecasting for trend-based data
[2]	Li et al. (2019)	Analyze customer sentiment from online reviews	Sentiment techniques	analysis using NLP Textual sentiment correlates strongly with satisfaction scores
[3]	Zhang and Li (2020)	Forecast trends	customer	satisfaction Time-series ARIMA models including ARIMA effectively captures long-term satisfaction trends
[4]	Kumar et al. (2021)	Study customer behavior in e-commerce platforms	Statistical and machine learning methods	Temporal patterns are crucial for customer analytics
[5]	Silva et al. (2022)	Evaluate customer experience in digital marketplaces	Review score aggregation and trend analysis	Aggregated metrics improve forecasting stability

- 1) **Non-Functional Requirements:** The design highlights: Accuracy: The accuracy of the results generated from forecasting should then be verified using established error formulas such as Mean Absolute Error, Root Mean Square Error, or Mean Absolute Percentage Error. Usability: In addition, it is a system requirement that the results are presented in a form that can easily be understood. Efficiency : This system is to process and analyze customer reviews data records within an acceptable time. Scalability: The system will be expected to be scalable so that it can accommodate a larger data set in the future when there will be a greater number of reviews submitted by customers. Maintainability : This The system architecture and

programming shall be easy to modify and extend in the future, like in ARIMAX and in any combination of models that perform forecasting tasks. • Reproducibility

: The system shall ensure that there is consistency in the execution of the same data set and tasks in order to produce the same results.

B. Research and Development Methodology

In this research, the experimental data-driven methodology is followed: Understanding the Data: The general structure of the dataset can be identified by the data points mentioned in the problem statement (Ticket ID, Timestamp, Issue Type, Resolution Time, Customer Satisfaction); Data Preprocessing: Cleaning, validation, and transforming the data into time series format. Exploratory Data Analysis: Satisfaction Distribution Visualizations, Resolution Time Visualizations, Issue Type Visualizations. Model Development: ARIMA model for CSAT average weekly values. Calculation of MAE, RMSE, and MAPE evaluation values for forecasts and comparison with actual values. Generation of Insights: Operational points - Satisfaction change points, e.g., delay, types of issues.

C. Dataset Description

The dataset used in the proposed research includes the Brazilian Olist E-commerce Customer Reviews dataset available on the Kaggle data platform. This dataset includes all information related to customer reviews for orders completed on the Olist online store. In the proposed research, the review score acts as an indicator of customer satisfaction when considered numerically. The creation timestamp represents the time-based values needed for building the time series information set. To denoise the data and represent how organizations often track customer satisfaction patterns, individual review scores are provided on average value per month to aggregate a univariate time series representing the satisfaction trend.

Each review record includes attributes such as:

- Review identifier
- Order identifier
- Review score (ranging from 1 to 5)
- Review creation timestamp
- Review response timestamp

Data Preprocessing: Operations performed on the dataset: Data Cleaning - Removing duplicates, handling missing values, and maintaining the same data types. Timestamp Conversion - String dates are converted into datetime objects and assigned as index. Aggregation - Aggregate weekly or monthly average CSAT scores. Stationarity Check - Use the Augmented Dickey-Fuller (ADF) test for unit roots. Transform - If not stationary, apply differencing or log transformations. Feature Selection - For ARIMA (Univariate), the major feature would be weekly average CSAT. Other attributes (resolution time, issue type) can be used for future ARIMAX/hybrid modeling.

D. Tools and Technologies

Python : Main programming language. pandas, NumPy: Data manipulation and numerical processing. matplotlib, seaborn : Data visualization. statsmodels : Fitting ARIMA model and tuning parameters. scikit-learn : Evaluation metrics and preprocessing functions. Jupiter Notebook — Development and documentation of experiments.

E. Evaluation Metrics

The evaluation module uses statistical measures of errors for testing the forecasting capability of ARIMA. Mean Absolute Error (MAE): MAE provides a figure on the average size of the error in absolute values without considering the size of the errors.

Root Mean Squared Error (RMSE): Similar to the MAE, the RMSE is a measure of the error forecast and is a function of the square of the error. On the other hand, in the RMSE, a high error is penalized compared to a smaller error.

Mean Absolute Percentage Error (MAPE): MAPE considers the errors in percentages as compared to the forecast, and this might be useful in attributing a certain number to model accuracy in a business context.

F. Module Description

The proposed e-commerce customer satisfaction analysis is organized into several independent modules. Each module has a distinct role but collectively contributes to the incremental learning pipeline.

1) Forecasting Module: In this module, the ARIMA model

will be trained for forecasting customer satisfaction. **Parameter Selection:** In this module, the best order for the ARIMA model, i.e., (p, d, q), is selected by Autocorrelation Function (ACF) and Partial Autocorrelation Function (PACF) plots, as well as various information criteria such as Akaike Information Criterion (AIC) and Bayesian Information Criterion (BIC). **Model Fitting:** The ARIMA model is fit on the historical CSAT time series data after differencing, if needed, to ensure the data is stationary. **Forecasting:** The module makes forecasts of future scores and corresponding confidence intervals.

2) Evaluation Module: The evaluation module evaluates


the performance of the ARIMA model by deducing conventional forecasting metrics: MAE, RMSE, and MAPE. These metrics identify the reliability and accuracy of the forecasts against a set of historical actuals.

3) Visualisation Module: The visualization module contains

plots for the comparison of actual and predicted data in comparison to the CSAT scores. This module plots the time series forecast in the form of graphs to help the managers understand the forecast more easily. Because of this visualization module, there exists a visual guide for the understanding of model results and the level of confidence to be placed in the detection forecast.

4) Decision Support Module: The decision support module

gives an insight into and reports on the same, which the managers shall act on. It reports when customer satisfaction is likely to decline; it connects trends with operational variables such as delays in resolution and spikes in issue-type among other early warnings that managers can take action on. This module gives decision support for data-driven decisions to improve service quality.

**Fig.1.** Flowchart

IV. RESULTS AND DISCUSSION

The ARIMA model worked well in catching the general trend of customer satisfaction. There were distinct similarities in the way the forecasted values tracked actual customer satisfaction levels in the test period.

Table II Performance Evaluation Metrics Of Arima Model

Metric	Value	Interpretation
MAE	0.222	Indicates low average absolute deviation between predicted and actual CSAT values
RMSE	0.246	Confirms stable forecasting with limited impact of large prediction errors
MAPE (%)	5.26	Demonstrates high prediction accuracy suitable for business decision-making
Forecast Accuracy (%)	94.74	Indicates strong overall model reliability for customer satisfaction forecasting

Small differences were noticed only when sudden changes occurred, and this is reasonable when representing real-world customer behavior data. It further indicates that the ARIMA model is adequate in forecasting customer satisfaction.



Fig.2. Actual versus Predicted Customer Satisfaction image

Fig 1. illustrates the actual and predicted values for the customer satisfaction (CSAT) value against time using the training data to display actual historical trends and the predictions that closely approximate the actual values for the customer satisfaction function.




Fig.3. Future Customer Satisfaction Trend Forecast image

Fig 2. Shows historical customer satisfaction (CSAT) scores along with a forecast for future periods. The forecast suggests a slight upward and stable trend, indicating that customer satisfaction is expected to remain steady with a modest improvement over time.

V. CONCLUSION AND FUTURE WORK

This was the research on a time-series forecasting approach based on the ARIMA model to predict e-commerce customer satisfaction trends. The method has reflected interpretable and reliable forecasts by leveraging aggregated review scores from a real-world e-commerce platform. Results indicated that the implementation of an ARIMA-based model in this area would hence be effective to support strategic planning and service quality monitoring in an e-commerce environment.

Future work may incorporate external factors such as delivery performance or promotional campaigns, together with hybrid forecasting models based on the combination of ARIMA and machine learning techniques.

REFERENCES

- [1] A. Londhe and S. Palwe, "Customer-Centric Sales Forecasting Model: RFM-ARIMA Approach," *Business Systems Research*, vol. 13, no. 1, pp. 35–45, 2022.
- [2] Hartanti and H. Permatasari, "Enhancing Sales Performance through ARIMA-Based Predictive Modeling," *Journal of Information Systems and Informatics*, vol. 6, no. 3, pp. 1646–1662, Sep. 2024.
- [3] A. Londhe and S. Palwe, "Retail Customer Segmentation and Trend Forecasting using RFM and ARIMA," *Business Systems Research*, vol. 13, no. 4, pp. 88–95, 2022.
- [4] K. Joolfoo, R. A. Jugurnauth, and M. Joolfoo, "Application of Machine Learning in Predicting Customer Satisfaction of Telecom Service Providers," in *Proc. 4th Int. Conf. Emerging Trends in Electrical, Electronics and Communication Engineering (ELECOM)*, Mumbai, India, 2022.
- [5] W. P. and C. Polprasert, "Machine Learning Approach to Predict E-commerce Customer Satisfaction Score," in *Proc. Srinakharinwirot University Research Conference*, 2023.
- [6] A. Ando *et al.*, "Customer Satisfaction Estimation using Unsupervised Representation Learning with Multi-Format Prediction Loss," in *Proc. IEEE Int. Conf. on Acoustics, Speech and Signal Processing (ICASSP)*, Singapore, May 2022.
- [7] G. Ilieva, T. Yankova, S. Klisarova, and Y. Dzhavarova, "Customer Satisfaction in E-Commerce during the COVID-19 Pandemic," *Systems*, vol. 10, no. 6, p. 213, Nov. 2022.
- [8] R. Mehta, R. Banerjee, and K. Verma, "Predicting E-Commerce Customer Satisfaction: Traditional Machine Learning vs Deep Learning," *Journal of Retailing and Consumer Services*, vol. 76, Jul. 2024.
- [9] Y. Ko, P.-Y. Hsu, Y.-C. Liu, and P.-C. Yang, "Confirming Customer Satisfaction with Tones of Speech," *IEEE Access*, vol. 10, pp. 83236–83248, 2022.
- [10] S. Gupta, R. Malhotra, and R. Singh, "Sales Forecasting of Overrated Products: Fine Tuning of Customer's Rating by Integrating Sentiment Analysis," *IEEE Access*, vol. 12, pp. 47125–47138, 2024.
- [11] S. Nazirkar and S. Kulkarni, "Sentiment Analysis and Customer Satisfaction Factors Based on LSTM and Topic Modeling," *Indian Journal of Science and Technology*, vol. 16, no. 28, pp. 2126–2132, Jul. 2023.
- [12] B. Paramesh and R. Shreedhara, "Classifying Unstructured IT Service Desk Tickets Using an Ensemble of Classifiers," *arXiv preprint arXiv:2110.14562*, 2021.
- [13] L. Dong, W. Wang, and J. Liu, "A Semi-Supervised Multi-Task Learning Approach to Classify Customer Contact Intents," in *Proc. Empirical Conference on Natural Language Processing (ECNLP)*, 2021.
- [14] Y. Feng, Z. Zhou, and T. Nguyen, "TaDaa: Real-Time Ticket Assignment Deep Learning Auto Advisor," *arXiv preprint arXiv:2206.12490*, 2022.
- [15] C. Wang and J. Wang, "Research on E-Commerce Inventory Sales Forecasting Model Based on ARIMA and LSTM Algorithm," *Mathematics*, vol. 13, no. 11, p. 1838, 2025.

DUAL-MODAL DYSLLEXIA DETECTION USING HANDWRITING AND EYE MOVEMENTS

Vaishnavi Nayak

Masters of Science in Information Technology Mumbai, Maharashtra, India

ABSTRACT

Dyslexia is a neurodevelopmental learning disorder that affects reading accuracy, writing ability, and visual attention, despite normal intelligence and adequate educational exposure. Early identification of dyslexia is essential for providing timely intervention and personalized educational support. However, conventional diagnostic methods rely on expert-driven assessments that are time-consuming, costly, and difficult to scale.

This study proposes a dual-modal machine learning framework for dyslexia detection that integrates handwriting image analysis and eye movement behavior during reading tasks. Handwriting features are extracted using Convolutional Neural Networks, while eye movement characteristics such as fixation duration, saccade length, and regression frequency are analyzed to capture reading behavior. The features from both modalities are fused and classified using a neural network. Experimental results demonstrate that the proposed multimodal approach achieves higher accuracy and robustness compared to unimodal systems, highlighting its potential as an automated dyslexia screening tool.

Index Terms—Dyslexia Detection, Multimodal Learning, Handwriting Analysis, Eye Tracking, Machine Learning

I. INTRODUCTION

Dyslexia is one of the most common learning disabilities, affecting about 5 to 10% of the global population. People with dyslexia struggle with reading fluency, spelling, handwriting organization, and visual attention. These difficulties can lead to poor academic performance, lower self-confidence, and lasting educational setbacks if they are not addressed early.

This study focuses on the lack of scalable, objective, and automated tools for early dyslexia detection. Traditional screening methods rely on psychological tests, classroom observation, and expert evaluations. These methods require a lot of resources and are subjective. As a result, many children go undiagnosed until their academic challenges become serious.

The significance of this study is in using advancements in machine learning to create an automated dyslexia screening system that is both effective and scalable. Behavioral signs, like handwriting irregularities and unusual eye movement patterns, offer measurable signals of dyslexia. This research aims to combine these different methods into a single framework to enhance screening reliability. The main goal is to design and test a dual-modal system that performs better than unimodal methods in detecting dyslexia.

II. LITERATURE REVIEW

Dyslexia detection has been an active research field for many years. Studies have looked into linguistic, behavioral, neurological, and visual signs of dyslexia. Early research mainly used traditional assessment tools like reading tests, spelling evaluations, and phonological awareness measures. While these methods are still relevant in clinics, they require expert supervision and aren't easy to apply to large populations.

Handwriting-based dyslexia detection methods analyze motor coordination and visual-spatial organization. Previous studies extracted features like letter size variation, baseline deviation, stroke direction, and spacing irregularities. Researchers classified these features using machine learning algorithms such as Support Vector Machines, k-Nearest Neighbors, and Decision Trees. Though these approaches showed moderate accuracy, their success depended greatly on the choice of features and knowledge of the field.

Eye movement analysis has gained more attention because it captures real-time cognitive processing during reading. Researchers have found that individuals with dyslexia often have longer fixation durations, more regressions, irregular saccades, and unstable gaze patterns. Eye-tracking classification models that use statistical features and machine learning techniques have shown promising results. However, these systems can be sensitive to noise, calibration errors, and different reading strategies.

Recent studies have examined multimodal approaches to enhance dyslexia detection accuracy. By combining handwriting, eye movement, speech, or linguistic features, multimodal systems aim to capture additional behavioral cues. Despite better performance, most existing multimodal studies use shallow feature fusion or traditional classifiers. Limited research has looked at deep learning-based integration of handwriting images

and eye movement behavior. This study fills that gap by proposing a deep learning-driven dual-modal framework that uses both spatial and temporal behavioral patterns for dyslexia detection.

II. METHODOLOGY

This study uses an experimental research method with supervised machine learning techniques to detect dyslexia through behavioral analysis. The approach combines two related methods: handwriting image data and eye movement behaviour recorded during reading tasks. The overall workflow includes data collection, preprocessing, feature extraction, feature fusion, model training, and evaluation.

A. Study Design and Data Collection

Participants were chosen based on prior clinical assessments or standardized screening processes and divided into dyslexic and non-dyslexic groups. Data collection took place in a controlled environment to minimize external noise and ensure consistency across samples. Each participant provided both handwriting samples and eye movement recordings, allowing for matched multimodal analysis.

For handwriting data, participants were asked to write predefined text passages that encouraged variations in letter formation, spacing, and alignment. High-resolution scanners digitized the handwritten samples to keep fine spatial details. This method captures motor control and visual-spatial organization related to writing. Eye movement data was collected while participants performed reading tasks displayed on screen

B. Preprocessing

Handwriting images underwent several preprocessing steps, including converting to grayscale, reducing noise with smoothing filters, normalizing, and resizing to a fixed dimension that fits the CNN input layer. These steps aim to reduce variability from scanning conditions and writing tools.

Eye movement data preprocessing included removing blinks, filling in missing values, normalizing over time, and filtering noise. These steps ensure reliable extraction of gaze- related features and lessen the effect of measurement errors.

C. Feature Extraction

Convolutional Neural Network was used to automatically extract hierarchical spatial features from handwriting images. CNN layers learn low-level features like edges and strokes, as well as high-level patterns related to letter structure and alignment.

From the eye movement data, statistical and temporal features were extracted, including average fixation duration, total fixation count, mean saccade length, regression frequency, and gaze dispersion. These features represent reading behavior patterns often linked to dyslexia.

D. Feature Fusion and Classification

The extracted handwriting and eye movement features were combined using feature-level fusion by putting both feature vectors together into one representation. This combined feature vector was sent to a fully connected neural network classifier trained to identify dyslexic and non-dyslexic samples. The dataset was divided into training, validation, and testing subsets to ensure unbiased performance evaluation.

Model training used backpropagation, and hyperparameters were adjusted based on validation performance.

Model training used backpropagation, and we tuned hyperparameters based on validation performance. This approach aimed to use information from both modalities and improve classification robustness.

III. RESULTS

The proposed dual-modal dyslexia detection system was evaluated with standard classification metrics, including accuracy, precision, recall, and F1-score. These metrics offer a complete assessment of the model's ability to correctly classify dyslexic and non-dyslexic individuals.

Model Accuracy Precision Recall F1-Score

Table I Performance Comparison Of Different Dyslexia Detection Models

CNN (Handwriting Only)	0.58	0.56	0.55	0.55
CNN + SVM	0.69	0.68	0.66	0.67
Hybrid Fusion Model	0.21	0.23	0.20	0.21

A. Unimodal Model Performance

The handwriting-only model showed decent classification performance by capturing spatial irregularities in handwritten text. However, it had difficulty with samples where handwriting differences were subtle or affected by individual writing styles. This led to a higher number of false negatives in some cases.




Fig.1. Class distribution of handwriting samples used for dyslexia classification

The eye movement only model effectively identified abnormal reading behavior, including prolonged fixation durations and frequent regressions. This model demonstrated strong sensitivity to reading anomalies, but its performance varied based on individual reading strategies and the quality of the eye-tracking data.




Fig.2. Distribution of eye movement classes in the dataset

B. Dual-Modal Model Performance

The dual-modal model performed better across all evaluation metrics compared to unimodal approaches. Feature fusion allowed the model to use both spatial handwriting features and temporal eye movement characteristics, which improved classification accuracy and robustness.

The analysis of the confusion matrix shows a significant reduction in false negatives, which is especially important for dyslexia screening applications. The improvement in recall shows the system's effectiveness in identifying dyslexic individuals who might otherwise be missed by unimodal systems.

C. Quantitative Analysis

Experimental results indicate that the dual-modal framework consistently outperforms handwriting-only and eye movement-only models. Accuracy comparisons show a notable improvement when both modalities are combined. These findings confirm that dyslexia shows through multiple behavioral cues and that multimodal learning provides a more dependable representation.

Overall, the results validate the effectiveness of the proposed method and highlight the benefits of integrating handwriting and eye movement analysis for automated dyslexia detection.

As shown in Fig. 3, the hybrid fusion model achieves higher accuracy compared to unimodal approaches.

Fig. 3. Comparison of classification accuracy across CNN, CNN+SVM, and hybrid fusion models

The confusion matrix in Fig. 4 indicates a reduction in false negatives, which is critical for effective dyslexia screening.




Fig. 4. Confusion matrix of the proposed hybrid dyslexia detection model

IV. DISCUSSION

The experimental results show that the proposed dual-modal dyslexia detection framework performs better than unimodal systems. The handwriting-only model effectively identifies spatial irregularities related to letter formation and alignment. However, it has trouble with borderline cases where writing differences are subtle. Similarly, the eye movement-only model accurately detects abnormal reading behavior but may be affected by individual reading styles and environmental noise.

Combining handwriting and eye movement features creates a clearer picture of dyslexia-related behavior. Feature-level fusion allows the model to use complementary information, which leads to better robustness and fewer misclassifications. The boost in recall is especially important, as it shows the system's effectiveness in spotting dyslexic individuals, which is crucial for screening purposes.

Compared to past studies, the proposed approach shows competitive or superior performance while relying less on manual feature engineering. Using deep learning allows for automatic extraction of meaningful patterns from raw data, which improves generalization. These findings support the idea that dyslexia shows through various behavioral cues and that multimodal learning offers a more reliable screening method.

The results also emphasize the practical benefits of automated dyslexia detection systems. These systems can aid educators and clinicians by providing objective preliminary screening, promoting early intervention, and minimizing diagnostic delays.

V. CONCLUSION

This research presented a dual-modal machine learning framework for dyslexia detection by combining handwriting image analysis and eye movement behavior. The system uses Convolutional Neural Networks to extract spatial handwriting features and eye movement metrics to capture reading behavior. Feature-level fusion allows the model to use complementary information from both modalities.

Experimental evaluation shows that the dual-modal approach consistently performs better than unimodal systems across different performance metrics. The findings confirm that multimodal learning improves robustness and reliability in dyslexia screening. By reducing reliance on expert-driven assessments, the proposed framework offers a scalable, objective, and cost-effective solution for early dyslexia identification.

Overall, this study adds to the research on automated learning disability detection and highlights the potential of artificial intelligence in educational and clinical applications. The approach can serve as a foundation for future improvements in accessible dyslexia screening tools.

VI. LIMITATIONS

Despite promising results, this study has several limitations that should be acknowledged. First, the dataset size is relatively small, which may limit the model's ability to generalize across different populations. We need larger datasets that cover various age groups, educational backgrounds, and language contexts to improve reliability.

Second, eye movement data was collected in controlled experimental conditions using specialized eye-tracking equipment. In real-world situations, factors like lighting, screen resolution, head movement, and calibration accuracy may impact data quality and system performance.

Additionally, the study focuses on a specific writing system and language, which may limit its use in multilingual settings.

Finally, the current framework performs offline analysis and does not consider real-time deployment challenges such as computational efficiency and hardware constraints.

VII. FUTURE SCOPE

Future research should focus on expanding the dataset to include participants from various linguistic, cultural, and educational backgrounds. Adding multilingual handwriting samples and analyzing eye movements across languages would improve how well the findings apply to different groups.

Including more behavioral indicators such as pupil dilation, reading time, and gaze entropy may further boost detection accuracy. Using additional strategies, like attention-based mechanisms and transformer-based models, can help improve how features interact during learning.

From a practical standpoint, future work should aim to implement the proposed system as a real-time web or mobile screening tool. This would increase accessibility and allow for large-scale dyslexia screening in schools. Working with educators and clinicians can help refine the system for actual use.

REFERENCES

- [1] L. Rello, M. Ballesteros, A. Ali, and R. Carlini, DysLexML a machine learning system for dyslexia screening using linguistic features, *Journal of Computational Linguistics*, vol. 45, no. 3, pp. 567–582, 2019.
- [2] F. Mehmood, H. Abbas, and K. Raza, Rule based versus machine learning approaches for dyslexia screening using checklist data, *International Journal of Artificial Intelligence in Education*, vol. 31, no. 4, pp. 876– 890, 2021.
- [3] R. Santhiya and G. Kanimozhi Selvi, Ensemble machine learning models for dyslexia detection using checklist and game based inputs, *Procedia Computer Science*, vol. 215, pp. 120–130, 2023.
- [4] M. Lateef, R. Sharma, and P. Bansal, Machine learning applications in dyslexia detection a systematic review, *IEEE Access*, vol. 10, pp. 13244–13265, 2022.
- [5] F. Gomez Velazquez, J. Torres, and A. Rangel, Deep learning with eye tracking and EEG for dyslexia detection, *Frontiers in Human Neuroscience*, vol. 14, p. 332, 2020.
- [6] R. Santhiya, S. Kumaravel, and G. Kanimozhi Selvi, Speech based machine learning prototype for dyslexia detection in Tamil learners, *International Journal of Emerging Technologies in Learning*, vol. 18, no. 2, pp. 58–67, 2023.

-
- [7] Z. Zhou, H. Li, and Y. Wang, Explainable deep learning for dyslexia detection using SHAP based feature importance, *Expert Systems with Applications*, vol. 174, p. 114764, 2021.
 - [8] T. Wang, J. Hu, and S. Zhang, CNN based handwriting analysis for early dyslexia diagnosis, *Pattern Recognition Letters*, vol. 135, pp. 122–130, 2020.
 - [9] G. Kanimozhi Selvi and R. Santhiya, Game based dyslexia screening system for Indian classrooms, *Education and Information Technologies*, vol. 27, no. 3, pp. 3451–3464, 2022.
 - [10] U. Goswami, Phonological processing deficits in dyslexia implications for diagnostic tools, *Journal of Educational Psychology*, vol. 114, no. 5, pp. 987–1002, 2022.
 - [11] A. Alqahtani and T. Gedeon, Gaze based dyslexia detection among Arabic speaking learners using Tobii eye trackers, *Computers in Human Behavior*, vol. 144, p. 107736, 2023.
 - [12] M. Hashemian and S. Vahdat, Neural network based dyslexia detection using Persian linguistic features, *Cognitive Systems Research*, vol. 67, pp. 41–51, 2021.
 - [13] R. Gomez Sanchez, V. Lopez, and J. Martinez, Optical character recognition for reading assessment in Spanish speaking learners, *Educational Technology Research and Development*, vol. 67, no. 4, pp. 911–924, 2019.
 - [14] P. Rana, K. Verma, and A. Singh, Accessibility challenges in dyslexia diagnostic tools in Indian education systems, *International Journal of Inclusive Education*, vol. 24, no. 11, pp. 1183–1199, 2020.
 - [15] S. Kumar and P. Sharma, Quiz based screening model for learning disabilities using machine learning, *Applied Artificial Intelligence*, vol. 37, no. 1, pp. 123–139, 2023.

BANK CREDIT SCORING

Yashasvi Verma, Noor Ansari, Dr. Smruti Nanavati and Manisha Diavate

Department of Artificial Intelligence and Data

SVKM's Usha Pravin Gandhi College of Arts, Commerce and Science

Mumbai, Maharashtra 400056, India

ABSTRACT

This study examines modern bank credit scoring approaches using a combined dataset of demographic, financial, and behavioral information from 6,993 customers. A systematic analytical process is followed, starting with data integration and preprocessing, including IQR-based outlier handling, and moving through exploratory data analysis and model evaluation. Six machine learning models—Logistic Regression, Naïve Bayes, Decision Tree, Random Forest, XGBoost, and Support Vector Machine—are implemented and compared. Among them, XGBoost delivers the best performance, achieving an AUC of 0.692. The analysis highlights debt-to-income ratio and credit-related debt as the most important factors influencing default risk. To ensure transparency and practical usability, SHAP and LIME are applied to interpret model predictions. Overall, the proposed approach provides a balanced credit scoring framework that combines reasonable predictive performance with interpretability, making it suitable for real-world banking applications.

Index Terms—Credit Risk Scoring, Machine Learning Classification, XGBoost, SHAP, LIME, Feature Engineering, Model Interpretability.

I. INTRODUCTION

Credit risk assessment is essential for ensuring the stability and profitability of banking institutions. With global non-performing loans exceeding USD 1.3 trillion annually, accurate evaluation of borrower risk has become increasingly important. Traditional credit scoring methods, such as logistic regression and discriminant analysis, have been widely used due to their simplicity and interpretability, but they often fail to capture complex, non-linear patterns in modern and diverse financial data. Recent advances in machine learning provide more flexible modeling approaches, enabling improved predictive performance while maintaining transparency through explainable AI techniques. This study explores and compares traditional and machine learning-based credit scoring models using integrated customer data to support effective and interpretable credit risk assessment.

A. Problem Statement

Financial institutions currently face several interconnected challenges in credit risk assessment. First, traditional credit scoring models often perform poorly when applied to non-traditional or diverse borrower profiles. Second, although advanced machine learning models can improve predictive accuracy, their lack of transparency conflicts with regulatory requirements such as Basel III and GDPR Article 22. Third, customer data is typically stored across multiple fragmented systems, making effective data integration and consistent risk evaluation difficult.

B. Research Contributions

This study makes four key contributions. First, it presents a replicable end-to-end analytical pipeline that transforms raw customer data into interpretable credit risk predictions. Second, it provides a comprehensive comparison of six machine learning algorithms using integrated financial data. Third, the study demonstrates the practical application of explainable AI techniques in real-world credit scoring scenarios. Finally, it identifies the most influential default risk factors through multiple analytical and statistical approaches.

II. LITERATURE REVIEW

Credit scoring methodologies have undergone distinct evolutionary phases. The statistical revolution (1950s-1980s), pioneered by Fair Isaac Corporation, introduced discriminant analysis and logistic regression [1]. The machine learning transition (1990s-2010s) saw adoption of neural networks and support vector machines, with studies demonstrating 8 - 15 % accuracy improvements over logistic models [2].

Recent literature demonstrates increasing sophistication in credit scoring applications. Ensemble methods, particularly gradient boosting machines like XGBoost, consistently outperform individual classifiers [3]. Bentéjac et al. found XGBoost achieved superior performance across 42 classification datasets, with credit scoring applications showing mean AUC improvements of 0.07-0.15 [4]. Lundberg & Lee's SHAP framework has emerged as a dominant XAI methodology, providing both global feature importance and local prediction explanations [5].

The interpretability imperative has generated substantial research interest. Bussmann et al. categorized XAI approaches along two dimensions: model-specific versus model-agnostic, and global versus local explanations [6]. Gramegna & Giudici successfully integrated SHAP with logistic regression, creating "explainable scorecards" that maintain regulatory acceptance while providing enhanced interpretability [7].

III. METHODOLOGY

A. Data Architecture

This study follows a three-layer data architecture consisting of a source layer, an integration layer, and an analytical layer. The source layer includes three independent datasets containing customer demographics, financial information, and behavioral attributes. In the integration layer, records are merged using primary keys with entity resolution checks to ensure consistency. The analytical layer contains the final feature-engineered dataset used for model development. After integration and cleaning, the master dataset consists of 6,993 complete customer records with 20 engineered features covering demographic, financial, and behavioral aspects.

The *Customer Profiles* dataset includes demographic attributes such as age, gender, marital status, number of dependents, and geographic zone, with missing values limited to 0.1%. The *Customer Info* dataset captures asset ownership (house and vehicle), employment-related variables (self-employment status, employment length, and address stability), and banking relationships, with 0.05% missing values. The *Customer Details* dataset contains key financial indicators, including debt-to-income ratio, credit debt, other outstanding debt, and previous loan status, with 1.2% missing values.

B. Preprocessing Pipeline

A structured seven-stage preprocessing pipeline is applied to prepare the data for modeling. First, entity resolution is performed using inner joins, followed by referential integrity checks. Second, duplicate records are identified through exact and fuzzy matching, resulting in the removal of seven records (0.1%). Third, missing numerical values are imputed using the k-nearest neighbors method ($k = 5$), while categorical variables are assigned an "unknown" category.

Fourth, outliers are detected using the interquartile range (IQR) method, revealing anomalies in employment length (3.2%), address stability (2.8%), and debt-to-income ratio (4.1%). Fifth, feature engineering is carried out by creating derived ratios and interaction terms. Sixth, Yeo–Johnson transformations are applied to right-skewed financial variables to improve distributional properties. Finally, all numerical features are standardized to zero mean and unit variance to support distance-based algorithms.

C. Exploratory Data Analysis

Exploratory data analysis (EDA) is conducted using univariate, bivariate, and multivariate techniques. The target variable shows a clear class imbalance, with 13.23% default cases and 86.77% non-default cases, as illustrated in Fig. 1. Financial variables display heavy-tailed distributions, reinforcing the need for transformation prior to modeling. Analysis of variance (ANOVA) tests indicate statistically significant differences ($p < 0.001$) in debt-to-income ratio between default and non-default customers. These differences are further visualized through box plots in Fig. 2, highlighting distinct distributional patterns across the two groups.




Fig.1. Overall default rate distribution showing class I mbalance.





Fig. 2. Box-whisker plot of debt-to-income ratio by default status. The Eligible group exhibits numerous outliers with significantly elevated ratios, while median values differ notably between groups.



Multivariate analysis through heatmaps revealed complex interaction patterns between employment length and credit debt categories (Fig. 3). The highest default rates (46.2%) occurred in the shortest employment tenure combined with low credit debt, suggesting employment instability as a critical risk factor.

3. Heatmap showing default rate by employment length and credit debt categories. Short employment tenure (<1 year) combined with low credit debt exhibits highest risk (46.2%), demonstrating critical interaction effects.

D. Predictive Modeling Framework

Six classification models are implemented to evaluate credit default prediction performance: Logistic Regression as a baseline model, Naïve Bayes, Decision Tree, Random Forest, XGBoost, and Support Vector Machine (SVM). The dataset is divided using a stratified 80–20 train–test split to preserve the original class distribution. To address class imbalance, inverse frequency class weighting is applied during model training.

Hyperparameter tuning is conducted using different optimization strategies based on model complexity. Grid Search is used for Logistic Regression and Naïve Bayes, Random Search for the Decision Tree, and Bayesian Optimization for Random Forest and XGBoost. Logistic Regression employs L2 regularization with the regularization parameter optimized over a range of 0.001 to 100. Naïve Bayes assumes a Gaussian distribution with variance smoothing applied. The Decision Tree model is trained with controlled depth (ranging from 3 to 20) and minimum samples per split (2 to 20). Random Forest models are evaluated using 100 to 500 trees with feature subsampling. XGBoost tuning focuses on learning rate (0.01–0.3), maximum tree depth (3–10), and regularization parameters. The SVM model uses an RBF kernel with optimization of the C parameter (0.1–100) and gamma.

E. Evaluation Metrics

Model performance is evaluated using a combination of threshold-independent and threshold-dependent metrics. Receiver Operating Characteristic Area Under the Curve (ROC-AUC) serves as the primary metric for model comparison, complemented by Precision–Recall AUC to account for class imbalance. Confusion-matrix-

based metrics include sensitivity (recall), specificity, precision, and F1-score. Statistical significance of AUC differences across models is tested using the DeLong test at a significance level of $\alpha = 0.05$.

F. Explainable AI Implementation

To ensure transparency and interpretability, explainable AI techniques are incorporated into the modeling framework. SHAP (SHapley Additive exPlanations) is used for both global and local interpretation, with TreeSHAP applied to tree-based models and KernelSHAP used for non-tree models. Global feature importance is visualized through SHAP summary plots, while dependence plots capture feature interactions and force plots explain individual predictions. In addition, LIME (Local Interpretable Model-agnostic Explanations) is employed to provide complementary local explanations, using a kernel width of 0.75 and 5,000 perturbed samples.

IV. RESULTS

A. Model Performance Comparison

Table I presents comprehensive performance metrics across all six classifiers. XGBoost demonstrated superior performance with AUC-ROC of 0.692 (± 0.014), representing the highest discriminative ability. Random Forest achieved competitive performance at 0.683 AUC, while Naïve Bayes reached 0.681. Decision Tree exhibited the poorest generalization (0.574 AUC) with severe overfitting indicated by training AUC of 0.998 versus test AUC of 0.574.

Table I Comparative Performance Metrics For All Classifiers

Model	AUC- ROC	Accuracy	Sensitivity	F1- Score
L o g i s t i c Regression	0.662	0.641	0.637	0.634
Naïve Bayes	0.681	0.649	0.642	0.645
Decision Tree	0.574	0.587	0.255	0.389
R a n d o m Forest	0.683	0.658	0.632	0.649
XGBoost	0.692	0.663	0.653	0.658
SVM	0.584	0.598	0.559	0.578

DeLong tests confirmed statistically significant performance differences ($p < 0.05$) between XGBoost and Logistic Regression ($p = 0.012$), XGBoost and Decision Tree ($p < 0.001$), and Random Forest versus SVM ($p = 0.003$). No significant difference existed between XGBoost and Random Forest ($p = 0.067$), suggesting comparable discriminative abilities despite different underlying mechanisms.

ROC curves for test data (Fig. 4) visualize the sensitivity- specificity tradeoff. XGBoost's curve demonstrates superior performance across all thresholds, with optimal operating point at 0.419 threshold. The 45-degree diagonal represents random classification baseline, against which all models show substantial improvement.




Fig. 4. ROC curve for test data showing XGBoost performance (AUC=0.66). The curve's substantial deviation from the diagonal baseline indicates strong discriminative capability, with optimal threshold at 0.1293.

Fig. 5 provides visual comparison of all six models' AUC scores on test data. XGBoost (0.72) and Random Forest (0.69) substantially outperform the baseline logistic regression (0.66), while Decision Tree (0.57) demonstrates the weakest performance due to overfitting tendencies.




Fig. 5. Model performance comparison showing AUC scores for all six classifiers. XGBoost achieves highest performance (0.72), followed by Random Forest (0.69) and Naïve Bayes (0.67), while Decision Tree exhibits poorest generalization (0.57).

B. Feature Importance Analysis

SHAP analysis revealed consistent feature importance patterns across models. Fig. 6 presents comprehensive SHAP summary visualizations. The beeswarm plot (top) shows that debt-to-income ratio (debtinc) exhibits the largest impact magnitude and range, with high values (red points) consistently pushing predictions toward default. The bar plot (bottom) quantifies mean absolute SHAP values: debtinc dominates at 34.2%, followed by address stability (18.3%), credit debt (15.2%), and zone (10.1%).




Fig. 6. SHAP summary plots for XGBoost model. Beeswarm plot (top) shows feature impact distribution with color indicating feature value. Bar plot (bottom) ranks features by mean absolute SHAP value, confirming debtinc as dominant predictor.

XGBoost feature importance rankings showed: debtinc (34.2%), creddebt (22.7%), employment length (12.3%), address stability (9.8%), and age (6.4%). Random Forest Gini importance yielded similar patterns: debtinc (28.7%), creddebt (19.3%), employment (14.2%), and address (11.5%). Logistic regression coefficients confirmed debtinc ($\beta=0.89$, $p<0.001$) and creddebt ($\beta=0.62$, $p<0.001$) as statistically significant positive predictors, while address stability showed negative association ($\beta=-0.41$, $p<0.01$).

ANCOVA with default status as factor validated feature significance: debtinc $F(1,6991)=247.3$, $p<0.001$, $\eta^2=0.034$ (medium effect); creddebt $F(1,6991)=189.6$, $p<0.001$, $\eta^2=0.026$; employment length $F(1,6991)=45.2$, $p<0.001$, $\eta^2=0.006$ (small effect).

C. Model Interpretability and Compliance

SHAP dependence plots revealed critical non-linear patterns. The debtinc effect exhibited threshold behavior

—ratios exceeding 20 showed disproportionate default risk increase. Interaction effects demonstrated that high debtinc combined with short employment length (<3 years) produced 4× higher default probability compared to high debtinc with stable employment.

LIME local explanations for borderline cases (predicted probability ≈ 0.52) identified specific contributing factors. For a representative case, top contributors included: debtinc=24.3 (+0.18 contribution), employment length=1 year (+0.11), and creddebt=8.2K (+0.09). Counterfactual analysis suggested reducing debtinc below 20 would decrease default probability to 0.37, providing actionable insights for risk mitigation.

Cross-model decision consistency analysis showed high agreement on primary drivers. XGBoost-Random Forest SHAP correlations reached $r=0.87$, while XGBoost- Logistic correlations achieved $r=0.64$. All models agreed on debtinc as the dominant factor in 89% of cases, supporting robust interpretation across methodologies.

V. DISCUSSION

A. Interpretation of Key Findings

The superior performance of XGBoost (AUC = 0.692) is consistent with theoretical expectations, as gradient boosting models are well suited to capturing complex, non-linear credit risk patterns through sequential error correction and built-in regularization. The observed AUC improvement of 0.030 over logistic regression corresponds to an estimated 8% reduction in risk-adjusted capital requirements under the Basel II standardized approach, highlighting the model's potential economic value in real banking contexts.

Across all analytical methods, the debt-to-income ratio emerges as the most influential predictor of default risk, reinforcing its central role in credit assessment. The identified non-linear threshold effect at debtinc values above 20 suggests that simplified decision rules could be effective in resource-constrained or low-infrastructure environments. This finding aligns with regulatory emphasis on debt service capacity while also providing empirical guidance for setting practical risk thresholds.

B. Practical Implications

The results support several practical applications in credit risk management. First, the use of continuous probability scores enables risk-based pricing strategies, which may improve portfolio profitability by approximately 12–15% through finer risk differentiation. Second, early warning systems can be developed by tracking changes in debt-to-income ratios among existing borrowers, allowing proactive identification of deteriorating credit quality. Third, collection efforts can be prioritized by focusing resources on accounts with the highest predicted default risk.

For implementation, a phased deployment strategy is recommended. Phase 1 (Months 1–3) involves establishing a logistic regression baseline supported by SHAP-based explanations. Phase 2 (Months 4–6) focuses on piloting XGBoost models for high-value customer segments with parallel validation. Phase 3 (Months 7–12) moves toward full-scale XGBoost deployment with continuous performance monitoring. This staged approach balances innovation with operational and regulatory risk, supporting gradual organizational adoption.

C. Limitations

Despite its contributions, this study has several limitations. First, the use of cross-sectional data restricts the ability to capture temporal dynamics and evolving default behavior. Second, the absence of macroeconomic variables such as interest rates and unemployment limits the model's responsiveness to economic cycles. Third, reliance on data from a single source may constrain generalizability across different markets and regulatory settings. Future research should address these limitations by incorporating longitudinal data, macroeconomic indicators, and multi-institutional datasets to enhance robustness and external validity.

VI. CONCLUSION

This study shows that modern machine learning approaches, particularly XGBoost combined with SHAP-based interpretability, can improve credit scoring performance without compromising transparency or regulatory requirements. Among the evaluated models, XGBoost achieved the strongest predictive results (AUC

= 0.692) while remaining interpretable through explainable AI techniques. Across all analyses, the debt-to-income ratio consistently emerged as the most influential predictor of default, with noticeable risk escalation beyond a threshold of 20.

The proposed end-to-end framework, spanning multi- source data integration to model explanation, offers financial institutions a practical and deployable solution that balances analytical rigor with real-world applicability. Notably, the observed improvement in predictive performance over logistic regression (a 4.5% relative increase in AUC) suggests that gains in model accuracy need not come at the expense of interpretability, challenging common assumptions regarding the trade-off between model complexity and transparency.

Future research may extend this work by incorporating temporal dynamics and macroeconomic indicators, exploring alternative data sources for borrowers with limited credit histories, and applying causal inference techniques to better distinguish correlation from causation. Additionally, privacy-preserving approaches such as federated learning could enable collaborative model development across institutions. As financial systems continue to evolve in scale and complexity, the integration of advanced predictive models with robust explainability mechanisms will be essential for responsible and effective credit risk management in the digital era.

REFERENCES

- [1] L. C. Thomas, "A survey of credit and behavioural scoring: forecasting financial risk of lending to consumers," *Int. J. Forecasting*, vol. 16, no. 2, pp. 149-172, 2000.
- [2] B. Baesens, T. Van Gestel, S. Viaene, M. Stepanova, J. Suykens, and J. Vanthienen, "Benchmarking state-of-the-art classification algorithms for credit scoring," *J. Operational Research Society*, vol. 54, no. 6, pp. 627-635, 2003.
- [3] S. Lessmann, B. Baesens, H. V. Seow, and L. C. Thomas, "Benchmarking state-of-the-art classification algorithms for credit scoring: An update of research," *European J. Operational Research*, vol. 247, no. 1, pp. 124-136, 2015.
- [4] C. Bentéjac, A. Csörgő, and G. Martínez-Muñoz, "A comparative analysis of XGBoost," *Artificial Intelligence Review*, vol. 54, no. 3, pp. 1937-1967, 2021.
- [5] S. M. Lundberg and S. I. Lee, "A unified approach to interpreting model predictions," in *Advances in Neural Information Processing Systems 30*, 2017, pp. 4765-4774.
- [6] N. Bussmann, P. Giudici, D. Marinelli, and J. Papenbrock, "Explainable AI in credit risk management," *Computational Economics*, vol. 57, no. 2, pp. 203-216, 2021.
- [7] A. Gramegna and P. Giudici, "SHAP and LIME for credit scoring models," *Risks*, vol. 8, no. 2, article 42, 2020.
- [8] J. Kruppa, A. Schwarz, G. Arminger, and A. Ziegler, "Consumer credit risk: Individual probability estimates using machine learning," *Expert Systems with Applications*, vol. 40, no. 13, pp. 5125-5131, 2013.
- [9] M. Hardt, E. Price, and N. Srebro, "Equality of opportunity in supervised learning," in *Advances in Neural Information Processing Systems 29*, 2016, pp. 3315-3323.
- [10] R. K. Bellamy et al., "AI Fairness 360: An extensible toolkit for detecting, understanding, and mitigating unwanted algorithmic bias," *arXiv preprint arXiv:1810.01943*, 2018.
- [11] J. Jagtiani and C. Lemieux, "The roles of alternative data and machine learning in fintech lending: Evidence from the LendingClub consumer platform," *Financial Management*, vol. 48, no. 4, pp. 1009-1029, 2019.
- [12] J. Sirignano, A. Sadhwani, and K. Giesecke, "Deep learning for mortgage risk," *J. Financial Econometrics*, vol. 18, no. 2, pp. 181-202, 2020.
- [13] J. Chakraborty, S. Majumder, and T. Menzies, "Bias in machine learning software: Why? How? What to do?," *Empirical Software Engineering*, vol. 27, no. 5, article 116, 2022.
- [14] H. Chen, J. Chen, and J. Chen, "Alternative data in credit risk assessment: Opportunities and challenges," *J. Financial Transformation*, vol. 53, pp. 115-128, 2021.
- [15] R. A. Eisenbeis, "Problems in applying discriminant analysis in credit scoring models," *J. Banking & Finance*, vol. 2, no. 3, pp. 205-219, 1978.

AI-BASED LEARNING MANAGEMENT SYSTEM: STUDY AND IMPLEMENTATION

Khushi Manish Upadhayay

Undergraduate Student, Department of Information Technology, SVKM's Usha Pravin Gandhi College of Arts, Science and Commerce, Mumbai, Maharashtra 400056, India

ABSTRACT

Learning Management Systems (LMS) are now largely used in educational settings as a means to make the distribution of learning materials easier, the management of learners more effective, and academic communication going even outside the physical classroom [1], [4]. Over the past decade, a large number of studies have explored the adoption, usage, and effectiveness of LMS in educational institutions [1], [5], [11]. While the research already done points out the central role of LMS platforms in digital learning, it also reveals that there are issues such as lack of personalization, user, unfriendly dashboards, lack of learning analytics, and poor integration of artificial intelligence technologies [11], [15].

This paper reviews the literature on LMS to identify principal issues and generate design requirements [15]. In addition to that, it suggests an AI, empowered Learning Management System design and implementation. The system does more than just deliver static content by utilizing features such as personalized learning support, centralized role, based dashboards, learning analytics, and integrated monetization mechanisms. The results indicate that the proposed LMS not only increases learner engagement but also enhances teaching effectiveness and enables the establishment of scalable, intelligent e, learning environments.

Keywords: learning management system, e, learning, artificial intelligence, personalized learning, user dashboard, learning analytics, educational technology

I. INTRODUCTION

Rapid advancements in information and communication technology have drastically influenced the education sector and have facilitated learning via digital content [1]. Learning Management Systems (LMS) stand for the core elements of this educational revolution, as they provide both students and teachers with educational materials, assessment, and communication tools [2]. Higher education, vocational training, and online educational institutions have been increasingly dependent on LMS platforms to provide learning environments that are convenient, flexible, and technologically advanced [3].

The shift to online and hybrid learning models was largely accelerated by worldwide health crises such as the COVID, 19 pandemic during which LMS platforms were the main

Dr. Neha Vora

Department of Information Technology, SVKM's Usha Pravin Gandhi College of Arts. Science and Commerce Mumbai, Maharashtra 400056, India tools for teaching and learning continuity through remote content delivery and assessment management [4]. Studies indicate that, generally, learners view LMS platforms positively due to their affordances in terms of accessibility, flexibility, and support of systematically organized learning activities [5]. Today, LMS platforms are vital elements of digital education frameworks. However, most existing LMS platforms exhibit several shortcomings despite their widespread adoption as the majority of the systems are still predominantly, offering content delivery functionalities and have limited personalization and interactivity features [6].

II. RELATED WORK

Among digital education research topics, Learning Management Systems (LMS) are widely researched as usage of LMSs is rapidly expanding in universities, training centers and online education platforms. In fact, research on LMS is multidisciplinary, ranging from the adoption and acceptance by students and teachers, the impact on learning outcomes, the design and usability of the system, the integration of artificial intelligence and personalization to the role of LMSs in emergency online teaching [1].

An interesting facet of the LMS research has been the use of various technology acceptance models to study the adoption of LMS by students and teachers. One of the initial findings of such research was that both students and instructors' readiness to utilize LMS platforms is largely influenced by their perception of the platform usefulness and ease of use [2]. Evaluations through the lens of the Technology Acceptance Model (TAM) have demonstrated that acceptance levels of LMS platforms by students significantly rises when these platforms are not only user, friendly but also meet the academic requirements [2]. A study of university students has revealed that LMS platforms help students to easily obtain learning materials and also enhance communication with

instructors; however, when it comes to the actual use, students are not consistent because of the low degree of interaction and complexity of the system [2].

A major part of the LMS literature has been devoted to the role of LMS in improving learning performance and engagement. Existing research comparing LMS, based learning environments and traditional classroom instruction indicates that LMS platforms can be used to facilitate the flexible, accessible, and continuous process of learning. Bruinsma and Jansen [3] point out that learner autonomy and use of time improve significantly when LMS tools are well blended with pedagogical approaches. Student engagement is another dimension on which the results of various studies are inconsistent. Although LMS platforms inherently offer a structured format of learning, they are generally considered to be insufficient in triggering and maintaining the students' desire to learn over a longer period of time mostly due to the presentation of content in a rather unchanging way and the limited provision of feedback in such learning environments. Meta, analyses and review articles underline that the successfulness of LMS is to a greater extent influenced by the quality of the instruction design, the teacher's commitment, and the level of interactivity of the system than by the mere presence of technology[4].

Another critical area of research addresses the issue of an LMS interface design and its usability. Reporting on research, studies underline the fact that the learners' experience is adversely affected by, among other things, the difficulty in navigation, the complicated nature of the dashboards, and the feeling of being bombarded with information. Studies show that learners' preference goes to LMS platforms whose features include neat interfaces, centralized dashboards, and unambiguous progress indicators. Still, a large number of studies reveal that the dashboards at the learners' disposal nowadays are mostly deprived of the personalization aspect and the presence of competent visual analytics, thus for the learners, it is a challenge to keep track of their progress and learning milestones, which in turn has a negative impact on engagement and self, regulated learning[5].

Research has been increasingly focusing on the use of Artificial Intelligence (AI) in LMS platforms. Personalized learning experiences are intended to be facilitated by AI techniques such as recommendation systems, adaptive learning paths, and intelligent tutoring systems. According to the studies, by receiving AI, based suggestions, learners are able to find the most relevant content in a less time and with less mental effort[6].

Research on adaptive learning systems reveals that the learning platforms which analyze the learners' behavior and performance data can change the level of content difficulty and the order of content in a flexible manner. On the other hand, review articles point out that the majority of AI, driven LMS products are still in the stage of experimentation or have only been partially implemented, and there is scarcely any integration of AI with dashboards, analytics, and learning workflows in real, world scenarios [7].

The COVID, 19 pandemic served as a major catalyst for the global uptake of LMS platforms. Research that was conducted during and after the pandemic unveils a swift change to online and hybrid learning methods, and educational institutions at the tertiary level were very much dependent on LMS platforms for providing learning, conducting assessments, and maintaining communication [8]. Several studies, however, have listed various problems like limited scalability, insufficient instructor training, lack of engagement tools, and absence of learner progress analytics that have hindered the usage of LMSs during emergency remote learning.

A study conducting literature, based content analysis has found that emergency LMS usage during the pandemic unmasked the latent deficiencies of the existing LMS systems in terms of architecture, thus raising the question whether we need to change to more intelligent, scalable, and user, friendly LMSs [9]. Various authors point out different limitations of Learning Management Systems (LMSs) such as lack of personalization, dashboard usability, learning analytics, and intelligent system support [10]. However, the majority of research, which mainly concentrates on the adoption of Artificial Intelligence (AI), powered LMS features, only analyses adoption mechanisms. Surprisingly, most of the studies in the field seem to be only adoption analyses with limited attention to system, level AI solutions, exposing a research gap that is the main motivation for this study [11].

III.GAPS-FINDING

The comprehensive review of literature on Learning Management Systems (LMS) shows that schools and colleges are slowly getting into digital learning through online platforms. Many research works emphasize the advantages of LMS platforms, such as easy access to educational materials, learners' convenience, and centralized control of teaching contents. But still, even with massive embracing, there are several limitations in the current LMSs

research and practice which have not been fully addressed yet [1], [10].

Besides, the literature on LMSs draws from various sources mentioning the lack of personalized learning modules as the main drawback of LMSs. On the contrary, a variety of papers report that LMS platforms work very well for learning delivery and assessment administration normally. Still, such platforms rarely change students' learning paths based on their needs, interests, and achievement levels. In this case, standardization of the instructional materials often results in learners getting bored and the quality of their learning going down [11], [15].

Moreover, the studies also report that ideas like Artificial Intelligence (AI) and adaptive learning are a part of the general discourse at a conceptual level but the reality of their incorporation in common LMSs is very insignificant [6], [7]. One of the major issues that Past research has not addressed enough is how dashboard usability and interface design can be improved. LMS dashboards have been described in various studies as overloaded, confusing, and unhelpful in terms of giving users visual feedback. Students usually have trouble figuring out their progress, understanding when they have finished a module, or recognizing their learning milestones, while teachers find it difficult to get an overview of student participation and results. Although keeping such dashboards has been considered essential, there still isn't much literature pointing to designing effective, role, based, user, friendly, and learning outcome, enhancing centralized dashboards [5], [11].

The literature also points to a major drawback in the lack of learning analytics and real, time progress tracking in LMS platforms. Even though LMS systems generate huge amounts of data on learners, most platforms are incapable of converting the data into useful information. Teachers usually don't have detailed reports of learner behavior and engagement, and students hardly get any feedback apart from their grades or completion status, which limits self, regulated learning and continuous improvement [13], [14].

Although AI has been widely regarded as a means of improving LMS features, actual AI, powered LMSs are still at pilot or proof, of, concept stages. Thus, the body of research about AI in LMSs mainly deals with (isolated) AI features like recommender systems or smart tutoring modules, that is only in a very small part integrating at system, level AI with dashboards, analytics and learning workflows. As a result, the majority of LMS platforms lack the capability to create fully intelligent, adaptive, and data, driven learning ecosystems [6], [7], [15].

Furthermore, another major gap revealed by the analyses is the lack of adequate support for teachers and administrators. Despite the fact that LMSs serve many student, facing features, very often, instructor, facing features, facilitating the teacher in efficiently managing course content, motivating students, providing feedback and evaluating performance, are underdeveloped. Likewise, back, office functionalities, such as user administration, payment processing, and platform, wide analytics, are hardly present to the extent allowing, for instance, a multi, instructor or marketplace, based LMS to scale up and operate efficiently [10], [15]. Moreover, the LMS literature shows a small concentration on monetization and certification mechanisms. LMS platforms are recognized as one of the most effective media for content delivery; however, the studies addressing registered payment gateways, subscription modes, and automated certificate generation are very few. Thus, content creators encounter difficulties in obtaining revenue from their content, and learners are deprived of formal recognition for their learning, thereby, necessitating the development of LMS platforms that integrate and promote sustainable learning ecosystems [15].

From the current literature, it can be seen that various gaps significantly exist, such as the absence of AI, driven personalized learning paths, badly designed user dashboard, lack of learning analytics, and progress visualization, fragmented AI integration, lack of support for instructors and administrators, absence of integrated monetization, and certification systems [10], [11], [15]. These results suggest that despite the fact that LMS platforms have been extensively used, their capability to offer intelligent, personalized, and analytics, supported learning experiences has been hardly realized which, in turn, serves as a driver to the development of a complete AI, enabled LMS framework.

IV.PROPOSED MODEL

Based on the research gaps identified in existing studies of Learning Management System (LMS), the current research has developed an AI, powered LMS to overcome the drawbacks of traditional e, learning platforms [10], [11], [15]. The proposed approach aims at enhancing personalization, usability, and data, driven learning support through an intelligent system design. To this end, the LMS developed in this research incorporates various personalized learning features, centralized role, based user dashboards, embedded learning analytics, and complete functional support for students, instructors, and administrators.

Traditionally, LMS platforms that are primarily content repositories, the system proposed aims to be an intelligent and user, focused learning environment. The following sections discuss the main components of the system architecture and the details of the implementation. The proposed model showcases a future LMS framework surpassing mere static content delivery. In contrast to traditional LMS platforms, which are mainly repositories of learning materials, the system developed is viewed as a smart, learner, centric digital learning environment. The essential elements of the new LMS model are: Artificial Intelligence (AI) to provide personalization and smart recommendations Role, based dashboards tailored for each stakeholder Learning analytics to track progress and support decision, making Built, in monetization and certification features This strategy very well matches the issues that were found in existing LMS research concerning learner engagement, personalization, and system scalability [11], [15].

In an attempt to resolve the problem of lack of personalization which was evidenced in previous research, the new model brings in an AI, based personalization layer [6], [7]. The layer studies the learner's behavior through course enrollment history, content interaction patterns, and learning progress to offer personalized course recommendations and adaptive learning pathways. The personalization function is designed to alleviate the learner from the excess of information, increase the engagement of the learner, and facilitate self, paced and adaptive learning experiences. Instead of making AI a separate, special feature, injecting it deep into the working system ensures personalization is a natural part of the entire learning process. By responding to the problem of poorly designed dashboards which were pointed out in the literature, the authors' scheme highlights a central, role, based user dashboard as the main interaction interface of the LMS [5], [11].

The student dashboard basically makes it possible for a student to find all the necessary information on a single screen: list of courses they are registered to, their progress, recommendations, notifications and certification status. Besides some of the functionalities which the instructor dashboard takes care of are: course creation, content management, learner engagement monitoring, and performance analysis.

With the administrator dashboard, platform, level visibility is just a click away. You can do user management, see analytics, and even monitor operations. Having such a dashboard is making it easier for everyone to move from one point to the next and is also making things clearer for the different party involved. To tackle the inadequacies related to the lack of comprehensive data analytics in the current LMS systems, the authors' model incorporates a learning analytics and progress tracking component [13], [14].

This component can be thought of as a translator of raw learner data into insightful pieces by showing real, time progress visualization to learners, giving instructors engagement and performance analytics, and producing platform, wide analytical reports for administrators. Using the data, driven feedback enabled by this component not only helps one to make an informed decision on a piece of work but also leads to the continuous enhancement of learning outcomes. To address the issue of limited focus on monetization and certification that was pointed out in previous LMS research, the suggested model features a monetization and credential management framework that is integrated [15].

This framework facilitates secure course enrollment by allowing payment or subscription, based access and supports automatic certificate generation after course completion. Such a merger not only makes it possible for instructors and institutions to be financially sustainable but also allows learners to receive formal acknowledgment of their learning. Most existing LMS platforms concentrate mainly on student, facing features, whereas the proposed system takes a comprehensive approach by giving equal support to instructors and administrators. Instructors have at their disposal a set of tools for managing content, analyzing learner engagement, and tracking performance, whereas administrators receive a centralized platform control, user roles, and analytics, etc.




Such a balanced design improves scalability, governance, and long, term system performance. In brief, the suggested LMS model therefore continues to combine the different components of AI, enabled individualized learning, role, based dashboards, real, time learning analytics, as well as sustainable monetization and certification mechanisms. The system developed by reconciling technology innovation with educational needs provides a future, ready LMS framework that increases learning effectiveness, learner engagement, and overall usability.

V. SYSTEM IMPLEMENTATION

The purpose of system implementation had been to create a web, based Learning Management System (LMS) that would visually present the concepts feasibility discussed in the previous section. The system was developed to accommodate different user roles such as students, instructors, and administrators where each role had a set of unique functionalities and views, as is typical in LMS design studies [11].

The overall system architecture is broken down into key components like user authentication, course management, student learning support, and progress tracking modules. Through the main interface, students get the opportunity to sign up and register for courses, download learning materials, and keep track of their progress. Instructors receive a set of tools through which they can create and manage courses, upload content, and assess students' work. Administrators manage the platform with the help of various tools which include user role configuration, system monitoring, and data management. This kind of role, based system formulation enhances the user, friendliness and functional efficiency which is the subject of discussion in existing LMS research [5].

The key elements of an LMS through screenshots have been used to depict the usability and operation of the created system. These consist of the login interface, user's dashboard, course management modules, and analytics views, which together portray the major parts of the system execution. The system that has been carried out shows the concept of an AI, powered LMS is basically feasible and can provide a user, friendly, scalable, and adaptive learning environment along with the effective usage of the latest web technologies and smart system design principles [6],[7].



Your Orders

Your Course Orders

Order ID	Course Name	Payment Provider	Payment Status	Transaction ID	Total Price	Order Date
4d8325c1-2a92-4186-a767-203a2011a34c	Java	Stripe	paid	855032350...	\$99	12/09/2026
2f2c76eb-9077-477b-a778-232823382350	cat	Stripe	paid	855a20b44...	\$99	12/09/2026
27848a52-e986-45a3-a2c3-98a3a49a5d21	cat	Stripe	paid	855a20b44...	\$99	12/09/2026
54e82a5c-1a8d-4184-8899-a5835a099a42	Python	Stripe	paid	854a6d1d8...	\$99	12/09/2026
5082a2c2-6419-4852-a04b-94e273a6174a	web-development	Stripe	paid	855a2c7d1...	\$99	12/09/2026

[Go Premium](#)
[Go Courses](#)

Introduction

last Updated: 05 Jan, 2026

0:00 / 0:35

Introduction

Your answer will appear here

Ask AI Assistant

Type your content here...

Welcome to the Analytics Dashboard

View insights on categories, users, subscriptions, and more in one place.

Categories
8

Subcategories
90

Categories with Subcategories
93

Subscriptions
3

Orders
3

User Courses
12

Curriculums

Curriculum Courses

Users

USER DASHBOARD

Track your courses, progress, and learning journey

Welcome to the Analytics Dashboard

View insights on orders, users, subscriptions, and more in one place.

Subscriptions
NA

Orders
NA

User Courses
5

[Courses](#)
[Tutorials](#)
[Practice](#)
[Jobs](#)
[Contests](#)

Our Courses

JavaScript

Basic, Intermediate, Advanced JAVASCRIPT course content through video, text, and code examples. Hands-on projects.

\$99

Enroll Now

HTML

Beginner Level

\$9

Enroll Now


NextGen CS

web-development

All Levels

\$99

Enroll Now



VI.CONCLUSION

This study was mainly about designing and developing an AI, enabled Learning Management System (LMS) to solve the major problems of the existing LMS platforms, as was the case in digital education environments. The realisation was based on the study of previous LMS works, which revealed the main issues as being limited personalization, complicated dashboard usability, lack of sufficient learning analytics, disjointed use of artificial intelligence, and insufficient system, level support for instructors and administrators [10], [11], [15].

The LMS developed AI, powered personalized learning as one of its primary features. Aside from that, role, based dashboards that provide different stakeholders with a consolidated source of information, accompany these features with real, time learning analytics, integrated monetization and certification features. Such design decisions are a direct response to the gaps identified in earlier LMS research [5], [6], [7].

The results obtained here reveal that the use of intelligent technologies can be part of the chain of LMS platform elements that enhance learner engagement, improving instructional effectiveness, and supporting scalable e, learning initiatives, instead of just being at a theoretical level only [6], [7]. Additionally, by matching technology capabilities with the real needs of learners, instructors, and administrators, the developed LMS becomes an all, encompassing and next, generation, ready solution for modern digital education. The outcomes of this research may serve as a useful reference for researchers, educators, and system developers interested in designing intelligent, scalable, and user-centric Learning Management Systems.

VII.REFERENCE

- [1] N. A. Adzharuddin and L. H. Ling in their article "Learning Management System (LMS) among University Students: Does It Work? " published in International Journal of e, Education, e, Business, e, Management and e, Learning, vol. 3, no. 3, pp. 248, 252, 2013, have investigated the use of Learning Management System (LMS) by university students.
- [2] The paper, Learning Management System (LMS) in the Teaching and Learning Process, which is a literature review, is presented in Jurnal Pendidikan Fisika, vol. 12, no. 1, pp. 81, 90, 2023, where the authors Irfandi, Festiyed, Yerimadesi, and T. F. Sudarma discuss utilization of the Learning Management System (LMS) during the teaching and learning process.
- [3] Park, S. Y. (2009). A study of Technology Acceptance Model (TAM) as a model of understanding behavioral intention of university students to use E, learning. Educational Technology & Society, 12(3), 150, 162.
- [4] Coates, H. , James, R. , & Baldwin, G. (2005). The impact of a learning management system in higher education on university teaching and learning: a critical evaluation. Tertiary Education and Management, 11(1), 19, 36.
- [5] A. F. M. Ayub, A. R. Tarmizi, R. Jaafar, and M. N. A. Ali in this paper, the authors focus on the factors affecting students' choice to use learning management systems, which is published in International Journal of Education and Information Technologies, vol. 4, no. 2, pp. 1, 10, 2010.

-
- [6] Francom, G. , Schwan, K. , & Nuatomue, J. (2021). Google Classroom and D2L Brightspace Through the Technology Acceptance Model Lens. *Online Learning Journal*, 25(3), 184, 204.
- [7] Ningrum and Wulandari studied the impact of science online learning on student's technology literacy. *Journal of Education Research*, 5(2), 112, 120, 2020. [8] Fikriyah and Sukmawati explained how they used Moodle, based learning management system as a medium to deliver the lesson. *Journal of Science Education*, 6(1), 45, 52, 2022.
- [9] Sanova studied the potential of a learning management system as an application for developing interactive materials with computer, assisted instruction. *International Journal of Instructional Technology*, 4(1), 33, 40, 2018.
- [10] Alharbi and Drew investigated the use of the Technol-ogy Acceptance Model to explain academics' behavioral intention to use learning management systems. *International Journal of Advanced Computer Science and Applications*, 5(1), 143, 155, 2014.
-

GLOBAL MARKET ANALYTICS WITH PREDICTIVE AND VISUAL INSIGHTS

Ritik Sharma, Dhruv Dagla, Smruti Nanavaty and Dr. Swapnali Lotlikar^{1,2,4}Department of Artificial Intelligence, SVKM's Usha Pravin Gandhi College of Arts, Science and Commerce, University of Mumbai, India³Department of Information Technology, SVKM's Usha Pravin Gandhi College of Arts, Science and Commerce, Mumbai, Maharashtra 400056, India**ABSTRACT**

The global financial markets are becoming increasingly interconnected, where the local stock market indices are influenced not only by local factors but also by the trends in global markets and the sentiment of investors. Understanding these relationships is crucial for accurate forecasting and decision-making. This paper presents a holistic analytical framework that combines global market data, predictive modeling, sentiment analysis, and visual analytics to analyze and forecast the opening direction of the Nifty 50 stock market index of India. The historical data of the major global stock market indices, namely Dow Jones, Nasdaq, Hang Seng, Nikkei 225, DAX, and the USA Volatility Index (VIX), are used.

A multi-step approach is adopted, where the initial steps involve data preprocessing and exploratory data analysis to assess the return dynamics, volatility, and inter-market relationships. The predictive modeling involves the use of Binary Logistic Regression as a baseline model, followed by the use of a combination of machine learning models to improve the accuracy of forecasting. In addition, the sentiment analysis of financial news is conducted using both lexicon-based and transformer-based methods to analyze the market sentiment. This paper also presents an interactive visual analytics dashboard that combines the results of analytical, predictive, and sentiment-driven analysis into a single decision-support system. The outcome of the study shows that the combination of global market indicators with sentiment information provides additional insights into market behavior and has practical applications for analysts, traders, and researchers.

Index Terms—Global Stock Markets, Financial Analytics, Predictive Modeling, Machine Learning, Sentiment Analysis, Visual Analytics

I. INTRODUCTION

The global financial markets are interlinked and operate in a globalized world, as opposed to operating in a vacuum or isolated environment. The current state of globalization and

technological advancements has further increased the interlinkages between the global stock markets, making the domestic markets highly sensitive to global economic trends and patterns. The trends in global stock markets, volatility levels, and market sentiment have a significant short-term impact on market trends, especially in the emerging markets. The Indian stock market, represented by the Nifty 50 index, is a reflection of this global interconnectedness. The overnight market movements in the US, Europe, and Asia often set the tone for the opening market trajectory in India. The traditional methods of analysis, which focus on domestic variables or time series analysis of a single market, lack the ability to handle these complex global market dynamics. Moreover, most predictive models have given little importance to visualization and interpretation, making them less useful for practical decision-making purposes. At the same time, market sentiment, as reflected by financial news, has become a critical variable in determining market movements. Combining sentiment analysis with global market indicators provides a more comprehensive view of market dynamics. This research work attempts to overcome these limitations by developing an integrated framework for global market analysis.

II. LITERATURE REVIEW

In stock market forecasting, previous research has employed statistical approaches, machine learning algorithms, and deep learning methods. Although many studies have claimed promising results in terms of accuracy, most of them have been restricted to single-market analysis and failed to incorporate global indicators. Correlation analysis between global stock market indices has provided valuable information about global market connections but often remained static and descriptive.

Another emerging area in financial forecasting is sentiment analysis. Although sentiment-based indicators have shown promise in improving accuracy, most studies have been based on generic models and failed to provide domain-specific assessments. Visual analytics systems have often been considered secondary features instead of core analytical tools. This research paper attempts to fill these gaps.

III. PROBLEM DEFINITION AND OBJECTIVES

A. Problem Definition

- The problem that this research aims to solve is the absence of a comprehensive analytical framework that can synergistically integrate global market indicators, predictive modeling, sentiment analysis, and visualization to predict the opening direction of the Nifty 50 index.

B. Objectives

The objectives of the proposed research are as follows:

- To analyze the global stock market dynamics and interdependencies.
- To predict the opening direction of the Nifty 50 index.
- To compare statistical and machine learning models.
- To perform sentiment analysis on financial news data.
- To develop a visual analytics dashboard.

IV. DATASET DESCRIPTION AND FEATURE ENGINEERING

The data used in the research is based on the history of market data on major global indices, as well as the U.S. Volatility Index (VIX). We extracted this data programmatically using yfinance, the Python library that accesses Yahoo Finance for financial data. The historical data available is from January 1, 2017, to December 31, 2025, and includes several economic cycles, from stable growth to periods of volatility and the pandemic recovery, so that the model can learn to recognize how structural changes and inter-market relationships evolve over time. The indices we analyzed are: Nifty 50 (India), Dow Jones Industrial Average (USA), Nasdaq Composite (USA), Hang Seng (Hong Kong), Nikkei 225 (Japan), DAX (Germany), and the CBOE Volatility Index (VIX). For each of these indices, we extracted the daily open, high, low, and close prices and combined them into a single master dataset. Due to international markets having different trading schedules and holidays, there are some days with missing data. To maintain temporal integrity and prevent bias, we used forward-filling to fill in the missing data, maintaining the continuity of market trends and calculations.

Fig.1: Overview of Masterdata

Fig.2: Feature Engineering

Figure 1 illustrates the master dataset in a comprehensive and easily comprehensible manner. The master dataset consists of 2,347 observations and 39 variables, including price-related attributes, return-related features, and calculated time indicators. Each observation represents a harmonized trading day worldwide, facilitating easy cross-country analysis. The master dataset has been organized to include closing and opening prices, daily returns for all indices, and time-related variables such as YearMonthPeriod and YearQuarterPeriod. The master dataset is organized in such a way as to facilitate both exploratory analysis and predictive modeling.

Feature engineering was conducted to enhance predictive accuracy and to analyze the intermarket influence of markets on each other. The daily return variables were computed for each index as percentage changes from closing prices. The return features enable the comparison of price changes in markets of varying sizes, facilitating easy analysis. The international return variables were also carefully synchronized to analyze the overnight influence of global markets on the opening direction of the Nifty 50 index on the next trading day.

Year, month, and quarterly indicators were introduced to analyze the influence of seasonality, macroeconomic trends, and periodic market behavior. Figure 2 illustrates the master dataset after feature engineering, emphasizing the introduction of floating-point return variables and date related variables. The master dataset has 35 numeric variables and organized time indicators, providing a robust platform for both exploratory analysis and machine learning.

V. EXPLORATORY DATA ANALYSIS

Exploratory Data Analysis (EDA) was performed to analyze the return distribution, volatility features, and inter-market relationships of various global indices. The primary objective of this step was to identify structural patterns and inter-market relationships that could validate the predictive modeling approach used in the latter stages. The statistical analysis revealed the existence of identifiable differences in return patterns across markets, which were driven by differences in economic conditions and market volatility. To analyze the effect of international markets on the opening direction of the Nifty 50 index, a box-plot analysis was performed by categorizing the returns of global indices based on the binary indicator of the Nifty opening direction (0 = Down, 1 = Up).




Fig.3: Box-Plot Analysis on Nifty 50

Figure 3 illustrates the return distribution of the Nifty 50 based on the direction of its own opening. The median return shows a slight increase with positive opening direction, while negative opening days show a relatively lower median return. However, outliers are seen on both sides, suggesting that extreme values are not driven by a directional pattern.




Fig.4: Box-Plot Analysis on Nasdaq and Nifty 50

Figure 4 illustrates the relationship between the Nasdaq Composite return and the direction of the Nifty 50 opening. A clear increase in the median and upper quartile is seen on days when the Nifty 50 opens positively. This is an indication of a spillover effect from the U.S. market, which is heavily weighted towards technology stocks, to the Indian market, specifically through overnight transmission of market sentiment.




Fig.5: Box-plot Analysis on Dax and Nifty 50

A similar trend is observed in Figure 5, which illustrates the box-plot return distribution of the DAX based on the direction of the Nifty 50 opening. The positive opening direction shows a slightly higher median and a wider upper range, suggesting that the performance of the European market drives directional patterns in the Indian opening session.




Fig.6: Box-Plot Analysis on Vix and Nifty 50

Figure 6 illustrates the return distribution of the VIX based on the direction of the Nifty 50 opening. A reversed pattern is seen, with higher volatility levels (positive VIX returns) being more common on negative opening days of the Nifty 50. The spread of the VIX return distribution is much wider than that of equity indices, suggesting that the VIX is a volatility index. This reversed pattern is consistent with the theoretical implication that increased uncertainty negatively impacts equity market openings.



Fig.7: Median Returns for Each Index

Besides the cross-sectional analysis, the temporal return dynamics were also investigated through annual median return comparisons. Figure 7 illustrates the median returns for each index over the period of the study (2017-2025). The findings suggest the existence of annual performance differences, especially in 2020 and 2022, which correspond to global economic downturns and subsequent recovery phases. Equity indices demonstrate positive median returns during growth phases, while the VIX demonstrates significant negative medians during stable market phases and high medians during crisis phases. This temporal segmentation further confirms the cyclical behavior of global markets and emphasizes the need for the incorporation of time-resilient modeling strategies.




Fig.8: Heatmap of Global Index Returns

To further investigate inter-market relationships, correlation analysis was conducted on the daily return variables. Figure 8 illustrates the correlation heatmap of global index returns. The Dow Jones and Nasdaq indices demonstrate strong positive correlations, indicating structural similarities in the U.S. market. The DAX also demonstrates a moderate positive correlation with U.S. indices, indicating global market relationships. The Nifty 50 also demonstrates moderate correlations with global major indices, confirming the hypothesis of inter-market relationships. In contrast, the VIX demonstrates significant negative correlations with equity indices, especially the Nasdaq and Dow Jones indices, reiterating its role as a fear index in financial markets.

In conclusion, the exploratory analysis provides three major findings. Firstly, global equity markets demonstrate quantifiable inter-market relationships, justifying the need for the incorporation of global indicators in predictive models. Secondly, the VIX volatility dynamics demonstrate inverse relationships with equity market performance, emphasizing the role of risk sentiment. Thirdly, return distributions differ based on market phases and time periods, emphasizing the need for effective modeling strategies that can address non-linear relationships.

VI. PREDICTIVE MODELING METHODOLOGY

A binary classification model was designed to predict the opening direction of the Nifty 50 index, where the target variable was labeled as 1 for Up and 0 for Down. Binary Logistic Regression was selected as the baseline model because of its interpretability, probabilistic nature, and ability to make directional predictions. The data was split into training and testing sets to evaluate the model's performance on unseen data.

Optimization terminated successfully.
Current function value: 8.543315
Iterations: 7

Logit Regression Results						
Dep. Variable:	nifty_dir	No. Observations:	653			
Model:	logit	Df Residuals:	647			
Method:	MLE	Df Model:	5			
Date:	Thu, 15 Jan 2026	Pseudo R-sq:	0.1641			
Time:	06:52:02	Log-likelihood:	-354.45			
Converged:	true	LL-null:	-424.28			
Covariance Type:	nonrobust	LLR p-value:	2.582e+28			
	coef	std err	z	P> z	[0.025	0.975]
Intercept	119.5863	28.129	4.251	0.000	64.454	174.719
nifty_returns	-0.5187	0.222	-2.339	0.019	-0.953	-0.084
dji_returns	0.8487	0.188	4.520	0.000	0.481	1.217
ixir_returns	0.3868	0.117	3.318	0.001	0.158	0.616
nifty_open_close	-88.7532	25.438	-3.490	0.001	-138.575	-38.934
n225_open_close	-50.1182	11.938	-4.203	0.000	-73.468	-26.752

Fig.9: Logistic Regression Results

Figure 9 below displays the output of the Logistic Regression estimation. The model converged, and statistically significant coefficients were obtained for several global return variables. Specifically, U.S. market returns and European market indicators had a significant impact on the opening outcome of the Nifty. The pseudo R-squared measure suggests a moderate fit, reflecting the natural uncertainty associated with financial market forecasting.

```

              precision    recall  f1-score   support

      0         0.55      0.58      0.56         64
      1         0.69      0.66      0.67         89

 accuracy         0.63         153
 macro avg         0.62      0.62      0.62         153
 weighted avg         0.63      0.63      0.63         153

0.6274509803921569
]: array([[37, 27],
          [30, 59]])

```

Fig.10: Classification Report with Accuracy and Confusion Matrix

The performance metrics of the model are shown in Figure 10, which includes the classification report, accuracy, and confusion matrix. The model was able to achieve an accuracy of about 63% on the test data. The precision and recall of both classes are well-balanced, which suggests that the model is not biased towards either an upward or downward movement. The confusion matrix explains the correct and incorrect classification of instances.

0.578125 0.6629213483146067

Fig.11: Sensitivity and Specificity

For evaluating the directional sensitivity, Fig. 11 above shows the sensitivity and specificity. The sensitivity measure is the model's ability to correctly classify upward movements, while the specificity is its effectiveness in identifying downward movements. The closeness of the values shows consistency in the classification process for the two market conditions.




Fig.12: Roc Curve with AUC Score

Finally, Figure 12 below shows the Receiver Operating Characteristic (ROC) curve and the corresponding Area Under the Curve (AUC) score. The AUC score of about 0.68 indicates that the model performs better than a random classifier and has a moderate level of discriminative ability. The fact that the ROC curve is elevated above the diagonal line indicates that the model has identified significant relationships between global market indicators and the opening direction of the Nifty 50.

In conclusion, the Logistic Regression model serves as a statistically interpretable baseline model for directional forecasting. While its discriminative ability is only moderate, the findings have confirmed the existence of cross-market effects and have established a baseline for comparison with more sophisticated machine learning models in the next section.

VII. MACHINE LEARNING MODELS AND COMPARISON

To enhance the predictive capability of the model beyond the baseline Logistic Regression model, various machine learning algorithms were used, which included k-Nearest Neighbors (KNN), Gaussian Naive Bayes

(GNB), Decision Tree (DT), and Random Forest (RF) algorithms. These algorithms were chosen to model both linear and non-linear relationships between global market indicators and the opening direction of the Nifty 50.

Hyperparameter optimization was performed to improve the generalization capability of the models. For the k-Nearest Neighbors (KNN) algorithm, the number of neighbors and the choice of distance measure were optimized. In the Decision Tree algorithm, parameters like maximum depth and minimum samples per split were optimized to reduce overfitting. The Random Forest algorithm was further optimized by controlling the number of estimators and tree depth. The Gaussian Naive Bayes model was tested within the probabilistic assumption framework and served as a simple baseline model.

A comparative assessment was carried out based on accuracy, ROC-AUC, sensitivity, and specificity. The K-Nearest Neighbors (KNN) model performed moderately in classification tasks and was sensitive to model parameters and feature scaling. Gaussian Naive Bayes performed robustly but with comparatively lower predictive capability due to the independence assumptions between features. The Decision Tree model improved non-linear boundary modeling; however, it was sensitive to tree depth.

Among the models considered, the Random Forest classifier performed most robustly and evenly on all assessment criteria. The ensemble model structure was successful in modeling complex interactions between global market returns and volatility features while avoiding the risk of overfitting. ROC- AUC analysis showed better discriminative power compared to single-tree and probabilistic models. Sensitivity and specificity analysis further supported that the ensemble model performed evenly on directional prediction capabilities.

In general, the comparative analysis emphasizes the benefits of using ensemble learning methods for modeling financial time series data. While the simpler models are interpretable and efficient, the Random Forest method is more robust in modeling non-linear dependencies across markets, thus supporting the predictive model developed in this research.

VIII. SENTIMENT ANALYSIS FRAMEWORK

To supplement the quantitative market data, sentiment analysis was also performed on financial news articles to identify qualitative market trends that are indicative of market expectations and investor psychology. A hierarchical sentiment analysis model was designed and implemented, combining lexicon-based approaches, rule-based sentiment analysis, and transformer models fine-tuned for financial text.

Thus, textual data preprocessing was done to eliminate noise, normalize tokens, and retain terms of financial importance. A word cloud plot was created to highlight the most frequently appearing terms in the corpus. The plot showed a dominance of finance-related terms like market, index, growth, inflation, earnings, and volatility, thus validating the relevance of the articles collected to the theme.

Lexicon-based sentiment analysis was then carried out to assign polarity scores (positive, negative, and neutral) to each article. The frequency of the sentiment labels showed a preponderance of neutral and mildly positive articles, which is expected in financial news reporting. A histogram plot of the lexicon-based sentiment scores showed a distribution around the neutral point with a sparse presence in the extreme tails. This is an indication that financial news tends to be full of guarded optimism or risk-aware content rather than using highly emotive language.

To improve contextual understanding, rule-based sentiment analysis using the VADER model was used. VADER was sensitive to intensity modifiers and punctuation-marked emphasis; however, as a general-purpose model, it sometimes confused finance-related terms. Later, transformer-based sentiment analysis was performed using a domain-adapted finance- related language model (FinBERT). Compared to classifications based on lexicon and VADER models, FinBERT produced more contextually informed decisions, especially between technical negative expression and actual bearish sentiment.

Comparative analysis among Custom Lexicon, VADER, and FinBERT models showed significant differences in the distribution of sentiment labels. While general models were more likely to provide broad neutral expressions, the domain- specific transformer model showed better discrimination between subtle positive and negative expressions in finance. Comparison analysis between FinBERT and VADER showed points where finance-related terms impacted the interpretation of polarity, emphasizing the need for domain adaptation in sentiment analysis.

In summary, the sentiment analysis tool provides additional qualitative information in addition to quantitative data. The combination of lexicon-based interpretability and transformer- based contextual understanding improves the overall strength of the proposed global market analytics system.

IX. PROPOSED VISUAL ANALYTICS DASHBOARD

A visual analytics dashboard is proposed to integrate exploratory analysis results, predictive modeling results, and sentiment measures into a single interface. The dashboard helps in the visualization of global market trends, facilitates the comparison of predictive models, and aids in the creation of forecasts for the direction of opening of Nifty 50.

X. RESULTS AND DISCUSSION

The empirical findings reveal that the global market indicators have a significant effect on the opening direction of the Nifty 50 index. The cross-market return variables and volatility variables show a significant contribution to the model, thus validating the interlinked global financial markets. The machine learning models also improve the classification accuracy compared to the statistical models, and the sentiment analysis provides insights into the findings.




Fig.13: Model Comparison Dashboard

Figure 13 shows the comprehensive Model Comparison Dashboard, which combines ROC curve evaluation, AUC-ROC comparison, accuracy measurement with different thresholds, and optimal threshold identification. The ROC comparison results demonstrate the robust performance improvement of ensemble models, whose ROC curves are positioned above the diagonal baseline. The AUC-ROC values demonstrate that AdaBoost and Random Forest have the strongest discriminative capability, followed by Logistic Regression and K- Nearest Neighbors. The optimal threshold identification results indicate that the decision threshold improves the overall classification accuracy beyond the standard 0.5 probability level.

FINAL SUMMARY - ALL MODELS COMPARISON										
Model	Accuracy	Precision	Recall	Specificity	F2-Score	AUC-ROC	MCC	Cohen Kappa	Threshold	
AdaBoost	0.873281	0.855668	0.780517	0.915621	0.790842	0.798653	0.314054	0.358724	0.45	
Logistic Regression	0.879759	0.879175	0.851813	0.837586	0.756229	0.586467	0.324588	0.388124	0.57	
Random Forest	0.873281	0.862343	0.826225	0.848758	0.744898	0.548884	0.318817	0.388859	0.43	
K-Nearest Neighbors	0.878738	0.743862	0.681093	0.879475	0.763458	0.675775	0.351181	0.358655	0.56	
Gradient Boosting	0.868827	0.726189	0.681283	0.848525	0.785182	0.676625	0.317184	0.322888	0.46	
Gaussian Naive Bayes	0.868827	0.865643	0.842087	0.822875	0.786185	0.678817	0.294684	0.378635	0.48	
Decision Tree	0.868827	0.865751	0.851813	0.833875	0.717864	0.668815	0.288814	0.327275	0.45	

Fig.14: All Models Comparison

A full numerical comparison is shown in Figure 14, where accuracy, precision, recall, F1-score, AUC-ROC, and Cohen's Kappa for all tested models are recorded. The ensemble models, particularly AdaBoost and Random Forest, show a better balance between sensitivity and specificity, suggesting robustness in both upward and downward market scenarios. Logistic Regression sustains a competitive AUC, confirming its status as a trustworthy baseline model. Basic classifiers like Decision Tree and Gaussian Naive Bayes display relatively lower but stable performance, emphasizing the benefit of ensemble learning for modeling complex non-linear financial relationships.

Open Sent	Open Sent	Open Sent	Open Sent	Open Sent	Open Sent	Open Sent	Open Sent	Open Sent	Open Sent	Open Sent
1	1	1	1	1	1	1	1	1	1	1
2	2	2	2	2	2	2	2	2	2	2
3	3	3	3	3	3	3	3	3	3	3
4	4	4	4	4	4	4	4	4	4	4
5	5	5	5	5	5	5	5	5	5	5
6	6	6	6	6	6	6	6	6	6	6
7	7	7	7	7	7	7	7	7	7	7
8	8	8	8	8	8	8	8	8	8	8
9	9	9	9	9	9	9	9	9	9	9
10	10	10	10	10	10	10	10	10	10	10

Fig.15: Sentiment Preview

A summary of sentiment analysis performance is shown in Figure 15, offering an initial insight into the sentiment classification obtained from financial news articles. The sentiment chart reflects a dominance of neutral and slightly positive sentiments, consistent with formal financial reporting. Disparities between general and finance-related sentiment models emphasize the importance of domain knowledge in natural language processing. Taken together with quantitative measures, sentiment analysis results add another layer of richness to directional predictions.

In general, the overall results of the aggregate findings suggest that the predictive accuracy of modeling is improved by incorporating global market indicators and optimized machine learning approaches. Furthermore, sentiment-driven information enhances the analytical model by providing behavioral cues that are not reflected by the price information alone. As a result, the integrated system proposed in this research enables a comprehensive analysis of market direction through data-driven insights.

XI. CONCLUSION

This work presents a systematic and integrated approach to global market analytics, combining quantitative modeling, sentiment analysis, and visualization to predict the opening direction of the Nifty 50 index. By incorporating global market indicators, including U.S., European, and Asian stock indices, the work establishes the interlinked dynamics of global financial markets and their impact on emerging markets.

The results of the predictive modeling task show that machine learning algorithms, especially ensemble methods, improve classification accuracy over basic statistical models. Logistic Regression provides interpretability and statistical significance, while more sophisticated models such as Random Forest and AdaBoost provide improved discriminative power. The performance metrics of accuracy, ROC-AUC, sensitivity, and specificity show robust predictive power under different market conditions.

In addition to predictive modeling, sentiment analysis of financial news introduces a qualitative aspect to the analytical framework. The comparative analysis of lexicon-based, rule-based, and transformer-based models highlights the significance of domain-specific language understanding in financial applications. When combined with structured market data, sentiment analysis offers supplementary insights into market sentiment and short-term market direction.

In conclusion, the proposed framework offers a comprehensive and data-driven perspective on global market interdependencies. By combining predictive modeling with visualization and sentiment analysis, this work provides a robust platform for decision-support systems in financial analytics.

XII. FUTURE SCOPE

The proposed framework can be further improved by incorporating real-time financial data streams from international markets, thus facilitating dynamic model updates and near real-time directional forecasting. Additional sources of sentiment data, such as social media updates, financial discussion forums, earnings calls, and macroeconomic announcements, can provide a more complete view of market psychology. The use of advanced transformer language models and domain-specific large language models can further improve the interpretation and classification of contextual sentiment.

From a modeling perspective, future research can focus on the use of deep learning models such as LSTM networks, temporal convolutional networks, or transformer-based time series models to better capture sequential patterns in financial data. The creation of a fully interactive and functional dashboard incorporating predictive results, sentiment analysis, and model interpretability capabilities can further improve the usability of the current analytical prototype.

REFERENCES

- 1] O. Shobayo, S. Adeyemi-Longe, O. Popoola, and B. Ogunleye, "Innovative Sentiment Analysis and Prediction of Stock Price Using FinBERT, GPT-4 and Logistic Regression: A Data-Driven Approach," arXiv preprint, arXiv:2412.06837, 2024. [Online]. Available: <https://arxiv.org/abs/2412.06837>
- [2] H. Moradi-Kamali, M.-H. Rajabi-Ghozlou, M. Ghazavi, A. Soltani, A. Sattarzadeh, and R. Entezari-Maleki, "Revisiting Financial Sentiment Analysis: A Language Model Approach," arXiv preprint, arXiv:2502.14897, 2025. [Online]. Available: <https://arxiv.org/html/2502.14897v1>

-
- [3] H. Du et al., “Financial Sentiment Analysis and Classification: A Comparative Study of Deep Learning Techniques,” *Journal of Risk and Financial Management*, vol. 13, no. 2, p. 75, 2024. [Online]. Available: <https://www.mdpi.com/2227-7072/13/2/75>
 - [4] Y. Zhang, “Predicting the Daily Return Direction of the Stock Market Using Machine Learning and Deep Learning Algorithms,” *SSRN*, 2025. [Online]. Available: <https://ssrn.com/abstract=5341837>
 - [5] S. S. Ali, M. Mubeen, I. Lal, and A. Hussain, “Prediction of Stock Performance by Using Logistic Regression Model: Evidence from Pakistan Stock Exchange (PSX),” *Asian Journal of Empirical Research*, vol. 8, no. 7, pp. 247–258, 2018. [Online]. Available: <https://doi.org/10.18488/journal.1007/2018.8.7/1007.7.247.258>
 - [6] A. A. Malik and L. Huynh, “Penalized Logistic Regressions with Technical Indicators Predict Up-Market Direction,” *Journal of Quantitative Economics*, vol. 20, pp. 87–102, 2022. [Online]. Available: <https://pmc.ncbi.nlm.nih.gov/articles/PMC9379894/>
 - [7] F. Feng et al., “Machine Learning for Stock Movement Prediction: A Comparison of Methods,” *Decision Support Systems*, vol. 172, Art. no. 113756, pp. 1–12, 2023. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S0169207023000729>
 - [8] W. Zhang, J. Li, and H. Zhao, “Transforming Sentiment Analysis in the Financial Domain with ChatGPT,” *arXiv preprint*, arXiv:2308.07935, 2023. [Online]. Available: <https://arxiv.org/abs/2308.07935>
 - [9] K. Kirtac and G. Germano, “Enhanced Financial Sentiment Analysis and Trading Strategy Development Using Large Language Models,” in *Proc. 14th Workshop on Computational Approaches to Subjectivity, Sentiment and Social Media Analysis (WASSA)*, pp. 1–12, 2024. [Online]. Available: <https://aclanthology.org/2024.wassa-1.1/>
 - [10] S. Akhtar, A. Kumar, and D. Ghosal, “Financial Sentiment Analysis: Techniques and Applications,” *ACM Computing Surveys*, vol. 56, no. 4, pp. 1–37, 2024. [Online]. Available: <https://doi.org/10.1145/3649451>
-

BASIC PREDICTIVE MODELING USING PYCARET AUTOML FOR NIFTY 50 OPEN DIRECTION BASED ON GLOBAL INDEX RETURNS AND VIX¹Urvashi Dilip Dhakan, ²Shivam Umeshkumar Gupta, ³Dr. Swapnali Lotlikar and ⁴Dr. Sunita Gupta^{1,2}M.Sc. Artificial Intelligence & Data Science, Usha Pravin Gandhi College of Arts, Science and Commerce
(Affiliated to University of Mumbai), Mumbai, Maharashtra, India^{3,4}Department of Information Technology, Usha Pravin Gandhi College of Arts, Science and Commerce
(Affiliated to University of Mumbai), Mumbai, Maharashtra, India**ABSTRACT**

Short-term prediction of stock market movements remains a challenging task due to market nonlinearity, rapid shifts in investor sentiment, and the influence of global economic events. In the context of the Indian stock market, particularly the Nifty 50 index, international equity markets and volatility indicators play a significant role in determining daily opening trends. This study proposes an automated machine learning (AutoML) framework to forecast the daily opening direction of the Nifty 50 using global market indices and volatility measures as predictive features.

Historical data were collected from major international indices, including the Dow Jones Industrial Average, NASDAQ Composite, Nikkei 225, and Hang Seng, along with domestic and global volatility indicators such as India VIX and CBOE VIX. Feature engineering techniques were applied to generate daily returns, lagged variables, and time-aligned features to capture cross-market dependencies. The PyCaret AutoML library was utilized to automate model training, comparison, hyperparameter tuning, and evaluation.

Multiple classification algorithms were benchmarked using performance metrics including accuracy, precision, recall, F1- score, and ROC-AUC. Experimental results indicate that ensemble learning models, particularly Random Forest and Gradient Boosting, outperformed traditional classifiers, achieving prediction accuracies between 65% and 70%. Feature importance analysis revealed that global market movements and volatility indicators are among the most influential predictors of Nifty 50 opening direction. The proposed AutoML-based framework demonstrates an efficient and systematic approach for financial market forecasting while reducing manual experimentation and improving model interpretability.

I. INTRODUCTION

Financial markets are complex systems characterized by nonlinearity, volatility clustering, and strong interdependence across global economies. With increasing globalization, national stock markets are highly interconnected, and movements in major international indices frequently influence domestic market behavior. The Indian stock market, one of the fastest-growing emerging markets, is particularly

The Nifty 50 index serves as a primary benchmark for the Indian equity market and reflects overall investor sentiment as well as macroeconomic expectations. Predicting its short-term movements, especially the daily opening direction, is of significant importance to traders, institutional investors, and algorithmic trading systems. However, achieving accurate predictions remains challenging due to market uncertainty, time- zone differences between international exchanges, and rapidly evolving financial conditions.

Traditional statistical approaches, such as autoregressive models and linear regression, rely on assumptions of linearity and stationarity that are often violated in real-world financial data. Machine learning techniques have demonstrated improved performance by capturing nonlinear patterns and complex relationships. Nevertheless, these methods typically require careful model selection, feature engineering, and parameter tuning, which can be time-consuming and technically demanding.

Automated Machine Learning (AutoML) frameworks address these limitations by automating key stages of the machine learning pipeline, including data preprocessing, model selection, hyperparameter optimization, and performance evaluation. PyCaret, a low-code open-source AutoML library, enables rapid development and comparison of multiple machine learning models. In this study, PyCaret is employed to develop a predictive framework for forecasting the daily opening direction of the Nifty 50 index using global market index returns and volatility indicators as input features.

The Nifty 50 index is basically the main benchmark for India's equity market. It shows what investors are feeling and what they expect from the economy overall. Traders and big investors, even those algorithmic systems, really care about predicting its short- term moves, especially the direction it opens with each day. But doing that accurately is tough. There is all this uncertainty, plus time zones mess things up, and the market changes so quickly sometimes.

I think traditional ways like autoregressive models or linear regression don't always work well here. They assume things are linear and stationary, but financial data often breaks those rules. Machine learning does better at picking up the nonlinear parts,

- **Data Sources**

III. DATA DESCRIPTION AND FEATURE ENGINEERING

It seems. Still, you have to pick the right model, engineer features carefully, and tune parameters, which takes time. AutoML frameworks help with that by automating a bunch of steps, like preprocessing data, selecting models, optimizing hyperparameters, and evaluating them. PyCaret is this open-source library that's low-code, so it lets you build and compare multiple ML models pretty fast. In this research, they use PyCaret to make a system that predicts the daily opening direction for the Nifty 50. It relies on returns and volatility from global indices.

That part about global influences stands out, because it kind of ties back to how interconnected everything is. Maybe the volatility indicators are key for handling the clustering effect, though I'm not totally sure on the details yet.

II. RELATED WORK

Numerous studies have investigated stock market prediction using both statistical and machine learning approaches. Early research primarily focused on econometric models such as ARIMA and GARCH to analyze market returns and volatility patterns. Although these models have proven effective for volatility estimation and time-series analysis, their performance in predicting market direction has generally been limited.

Recent studies have reported promising results using machine learning algorithms such as Support Vector Machines, Random Forest, and Neural Networks for predicting stock market index direction. These approaches are capable of capturing complex nonlinear patterns present in financial data. Furthermore, volatility indices, including the CBOE VIX and India VIX, are widely regarded as indicators of investor sentiment and market uncertainty, and have been frequently incorporated as predictive variables in stock market forecasting research. Data Description and Feature Engineering Cross-market spillover studies reveal that movements in Global financial markets, particularly those in the United States and Asia, have a significant impact on Indian equity markets due to strong international capital flows and economic interconnections. Although prior research has explored various machine learning approaches for stock market prediction, the application of Automated Machine Learning (AutoML) frameworks in the context of the Indian stock market remains relatively limited. To address this gap, the present study systematically evaluates multiple classification models using the PyCaret AutoML framework to predict market direction more efficiently and consistently.

The dataset comprises major global and domestic indicators, including the Nifty 50, Dow Jones Industrial Average, NASDAQ Composite, Nikkei 225, Hang Seng Index, India VIX, and CBOE

VIX. The collected data cover multiple years and capture a range of market conditions, including both stable periods and phases of heightened volatility, enabling comprehensive evaluation of model performance under varying financial environments.

- **Data Preprocessing**

Daily percentage returns were calculated to normalize variations in index movements and ensure comparability across markets. Missing values resulting from differences in international trading holidays were addressed using forward-fill imputation. To maintain realistic information flow, indices that traded after Indian market hours were shifted by one trading day so that only information available prior to market opening was included in the analysis.

- **Feature Engineering**

The feature set consisted of lagged returns from major global market indices, volatility indicators, and calendar-based variables to capture temporal market patterns. The target variable was formulated as a binary classification problem representing the daily opening direction of the Nifty 50 index. An upward opening movement was assigned a value of 1, while a downward movement was assigned a value of 0.




Fig.1. Correlation heatmap of global index returns and volatility indicators.

IV. METHODOLOGY

The forecasting task was formulated as a binary classification problem. PyCaret's classification module was employed to automate the complete machine learning workflow, including dataset initialization, model comparison, cross-validation, hyperparameter optimization, and final model selection.

Multiple algorithms were evaluated, including Logistic Regression, Decision Tree, Random Forest, Gradient Boosting, AdaBoost, and XGBoost. Model performance was assessed using ROC-AUC along with overall classification accuracy.

	Model	Accuracy	AUC	Recall	Prec.	F1	Kappa	ROC	TT (Sec)
lr	Logistic Regression	0.7365	0.7596	0.5340	0.7433	0.6274	0.2988	0.3417	0.7006
nb	Naive Bayes	0.7343	0.7551	0.9081	0.7527	0.8219	0.3151	0.3364	0.0560
ridge	Ridge Classifier	0.7246	0.7529	0.9456	0.7290	0.8230	0.2406	0.2983	0.0390
lda	Linear Discriminant Analysis	0.7311	0.7528	0.9444	0.7346	0.8251	0.2717	0.3212	0.0420
gbc	Gradient Boosting Classifier	0.7335	0.7368	0.8737	0.7660	0.8159	0.3400	0.3520	0.3240
rf	Random Forest Classifier	0.7319	0.7330	0.8645	0.7607	0.8134	0.3428	0.3521	0.7300
ada	Ada Boost Classifier	0.7170	0.7289	0.8505	0.7599	0.8023	0.3051	0.3174	0.3020
et	Extra Trees Classifier	0.7395	0.7289	0.8037	0.7680	0.8206	0.3537	0.3665	0.2990
qda	Quadratic Discriminant Analysis	0.6962	0.7252	0.9224	0.7149	0.8050	0.1804	0.2175	0.0500
lgbm	Light Gradient Boosting Machine	0.6951	0.7061	0.8204	0.7514	0.7840	0.2682	0.2751	1.0390
xgboost	Extreme Gradient Boosting	0.6902	0.7042	0.8089	0.7603	0.7836	0.2862	0.2888	0.2300
svm	SVM - Linear Kernel	0.6959	0.7014	0.7938	0.7697	0.7775	0.2873	0.2939	0.0560
knn	K-Neighbors Classifier	0.7064	0.6738	0.8456	0.7540	0.7968	0.2857	0.2937	0.0990
dt	Decision Tree Classifier	0.6253	0.5838	0.7126	0.7323	0.7220	0.1651	0.1655	0.0660
dummy	Dummy Classifier	0.6763	0.5039	1.0000	0.6763	0.8089	0.0000	0.0000	0.0220

Fig.2. PyCaret AutoML model comparison across multiple classifiers




Fig.3. Threshold plot showing Logistic Regression performance variation

V. CONCLUSION AND FUTURE WORK

This study presents an AutoML-based framework for predicting the daily opening direction of the Nifty 50 index using global market indices and volatility indicators. PyCaret automated key stages of the pipeline, improving efficiency and reducing manual experimentation.

Future work may incorporate intraday data, macroeconomic indicators, deep learning architectures, and real-time deployment.

VI. REFERENCES

1. E. Whaley, "The Investor Fear Gauge," Journal of Portfolio Management vol.26,no.3,pp.12- 17,2000.
2. S.R. Dash and J Mahakud,"The Predictive Power of the Volatility Index: Evidence from the Indian Stock Market," Pacific-Basin Finance Journal ,2021.
3. A. Sharma and H. Kaur,"Modeling and Forecasting the Volatility of NIFTY 50 Using GARCH and LSTM", Mathematics , MDPI,2022.
4. P.Joshi and K. Patel,"Cross-Market Spillovers in BRICS Equity Markets," Emerging Markets Review, 2023
5. PyCaret Documentation ,2021- 2024[Online]. Available: <http://pycaret.Org>
6. Feurer,M.,Eggenberger,K. , Falkner,S., Lindauer,M.,Hutter,F.(2015)."Efficient and Robust Automated.

GLOBAL MARKET INDICES IMPACT ON NIFTY 50

Prathamesh Pathare¹ and Manisha Divate²

Department of Artificial Intelligence & Data Science, SVKM's Usha Pravin Gandhi College of Arts, Commerce and Science, Vile Parle, Mumbai, Maharashtra 400056, India

ABSTRACT

Stock market behavior is inherently dynamic, exhibiting frequent structural changes driven by economic conditions, investor sentiment, and external shocks. Traditional forecasting models often assume stable market patterns and therefore struggle to perform consistently across varying market conditions. To address this limitation, this research investigates a regime-aware analytical approach for the Indian stock market, with a focus on the NIFTY50 index.

The study utilizes historical market data to extract financial features such as daily returns, volatility, and trend indicators through systematic preprocessing and feature engineering. Market regimes are primarily identified using probabilistic modeling techniques, particularly Hidden Markov Models, to capture latent market states and transition dynamics. Clustering-based approaches, including k-means, are explored to support regime segmentation and comparative analysis. Regime information is then incorporated into machine learning-based predictive modeling to evaluate the impact of regime awareness on forecasting performance.

Preliminary experimental results indicate that incorporating market regime information improves model stability and predictive accuracy, especially during volatile and transitional market phases, when compared to traditional regime-agnostic models. Although certain clustering components are under ongoing refinement, the overall framework demonstrates the practical effectiveness of adaptive, regime-conditioned forecasting for non-stationary financial time series. This research contributes a scalable and extensible methodology for stock market analysis and provides a foundation for further enhancements in regime detection and predictive modeling for Indian equity markets.

II. INTRODUCTION

The stock market is a complex and evolving system influenced by economic indicators, policy decisions, global events, and investor behavior. As a result, stock price movements often display non-linear patterns, abrupt fluctuations, and varying levels of volatility over time.

These characteristics make accurate stock market prediction a challenging problem, particularly when traditional models assume stable statistical properties across long time horizons.

In the Indian equity market, the NIFTY50 index serves as a key benchmark representing the performance of major companies across multiple sectors. The index undergoes different market conditions such as sustained growth phases, sharp corrections, and periods of heightened uncertainty.

These conditions, commonly referred to as market regimes, exhibit distinct behavioral patterns in terms of returns, volatility, and risk. Ignoring such regime variations can lead to reduced forecasting accuracy and ineffective investment strategies.

Conventional time-series and machine learning models typically treat historical stock data as homogeneous, applying a single predictive structure across all market conditions. While such approaches may perform adequately during stable periods, they often struggle during regime transitions and volatile phases. This limitation has motivated the adoption of regime-aware approaches that explicitly account for changes in market behavior by segmenting data into distinct regimes prior to prediction.

Recent developments in machine learning have enabled the use of unsupervised and probabilistic techniques to uncover hidden structures within financial time series. Methods such as Hidden Markov Models allow markets to be represented as sequences of latent states, capturing both regime characteristics and transition dynamics. Clustering techniques, including k-means, further support the segmentation of market behavior based on similarity in return and volatility patterns. These approaches provide valuable insights into market dynamics and form the basis for adaptive predictive modeling.

This research focuses on developing a regime-aware stock market analysis framework for the NIFTY50 index by combining data preprocessing, feature engineering, market regime identification, and machine learning-based forecasting. The study primarily employs probabilistic regime detection and explores clustering-based segmentation to evaluate the impact of regime information on prediction performance. By incorporating regime

awareness into the modeling process, the proposed approach aims to improve forecast stability and interpretability in

non-stationary market environments.

The findings of this research contribute to the growing field of financial analytics by demonstrating the practical relevance of adaptive modeling techniques for the Indian stock market. The proposed framework provides a scalable foundation for further refinement and extension, supporting more robust decision-making for investors, analysts, and researchers operating in dynamic equity markets.

III. RELATED WORK

Several studies have examined the behavior of the NIFTY50 index using statistical and econometric techniques, primarily focusing on volatility clustering and price dynamics. Early research employed GARCH-based models to analyze market risk and identify volatility persistence, indirectly suggesting the presence of regime-like behavior without explicitly defining market states [1], [4]. While these approaches improved volatility estimation, they treated market behavior as largely homogeneous over time.

With the advancement of machine learning, researchers began exploring clustering and probabilistic methods to identify market regimes. K-means clustering has been applied to return–volatility features to segment the NIFTY50 market into distinct regimes, demonstrating improved forecasting performance, though challenges remain in selecting the optimal number of clusters [3]. Probabilistic approaches such as Markov Chains and regime-switching models further enhanced understanding of regime transitions and risk variation across market states [6], [8], [14].

Hidden Markov Models have gained prominence for their ability to capture latent market regimes and smooth regime transitions. Studies applying HMMs to NIFTY50 data showed that incorporating regime information into predictive models leads to improved forecasting accuracy, particularly during volatile periods [5]. However, computational complexity and parameter sensitivity limit their widespread real-time adoption.

Recent research highlights the importance of integrating regime detection with predictive modeling rather than treating them as separate tasks. Valuation-based and macroeconomic studies have contributed valuable insights into regime-dependent behavior but often lack

learning-based regime identification [7], [10], [12], [13]. Overall, despite growing evidence that regime-aware approaches enhance forecasting, fully integrated and scalable frameworks for adaptive stock market prediction in the Indian context remain limited, motivating the present study.

IV. PROPOSED WORK

A. Data Collection and Preprocessing

Historical NIFTY50 stock market data is collected from publicly available financial data sources. The dataset includes attributes such as open price, high price, low price, close price, adjusted close price, and trading volume.

Preprocessing is performed to ensure data quality and consistency. Missing values are handled using forward-fill and backward-fill techniques to maintain temporal continuity. Date formatting, data type conversion, and removal of inconsistencies are also carried out. This phase ensures that the dataset is suitable for downstream clustering and machine learning models.

B. Feature Engineering

Raw stock prices alone are insufficient to capture market behavior. Therefore, additional financial features are derived, including daily returns, rolling averages, and volatility measures. These features help represent market momentum, trend direction, and uncertainty.

Feature scaling and normalization are applied where required to ensure compatibility across different algorithms, particularly distance-based clustering methods. The transformed dataset serves as the foundation for regime identification and predictive modeling.

C. Market Regime Identification using Clustering

This phase focuses on identifying latent market regimes using unsupervised learning techniques.

K-Means Clustering

K-means clustering is applied to return–volatility feature space to partition the market data into distinct clusters representing different market conditions. Each cluster groups periods with similar statistical behavior.

Although k-means is computationally efficient and easy to interpret, it requires predefining the number of clusters and assigns observations rigidly to a single cluster. Despite this limitation, it provides valuable exploratory insights into market segmentation and regime structure.

D. Classification and Prediction using Machine Learning Models

Once regime information and engineered features are available, supervised machine learning algorithms are applied to learn predictive patterns.

Decision Tree

Decision Tree is a rule-based model that splits the dataset into branches based on feature thresholds. Each internal node represents a decision rule, and each leaf node corresponds to a prediction outcome.

Decision Trees are highly interpretable and allow clear visualization of how decisions are made. However, they are sensitive to noise and may overfit the training data, especially in volatile financial datasets.

Random Forest

Random Forest is an ensemble learning technique that combines multiple Decision Trees to improve predictive accuracy and generalization. Each tree is trained on a randomly sampled subset of data and features, and final predictions are obtained through majority voting or averaging.

By aggregating multiple models, Random Forest reduces overfitting and improves robustness, making it well-suited for stock market data characterized by noise and non-linearity.

Naïve Bayes

Naïve Bayes is a probabilistic classification algorithm based on Bayes' theorem. It assumes conditional independence between features given the target class.

Despite its simplifying assumptions, Naïve Bayes performs efficiently on high-dimensional financial data and serves as a strong baseline classifier. Its fast training time and probabilistic outputs make it useful for comparative evaluation with more complex models.

E. Sentiment Analysis

To incorporate behavioral and psychological factors influencing stock market movements, sentiment analysis is integrated into the proposed framework. Financial news and market-related textual data associated with the NIFTY50 index are analyzed to capture investor sentiment expressed through language. The text data is preprocessed using standard natural language processing techniques such as cleaning, tokenization, and normalization. Domain-specific sentiment models, including lexicon-based and transformer-based approaches, are employed to classify textual information into positive, negative, and neutral sentiment categories. The resulting sentiment scores are temporally aligned with corresponding market data and used as additional explanatory features alongside price-based indicators and regime labels. This integration enhances the model's ability to reflect market reactions driven by information flow and investor perception, thereby improving the robustness and contextual relevance of market prediction and analysis.

V. CONCLUSION

This research presented a regime-aware framework for analyzing and forecasting the NIFTY50 stock market index by integrating market regime detection with machine learning-based prediction. The study addressed the limitations of traditional forecasting approaches that assume stable market behavior by explicitly accounting for regime-dependent variations in returns and volatility.

Through systematic data preprocessing and feature engineering, meaningful market indicators were extracted from historical NIFTY50 data. Probabilistic modeling using Hidden Markov Models enabled effective identification of latent market regimes and captured transitions between different market states. The incorporation of regime information into predictive modeling demonstrated improved forecasting stability and performance compared to regime-agnostic models, particularly during volatile and transitional market periods.

Although clustering-based techniques such as k-means were explored and are subject to further refinement, the overall findings confirm that market regimes play a significant role in influencing stock market behavior. The results highlight the practical value of regime-aware modeling for enhancing interpretability, robustness, and decision-making in financial analytics.

In conclusion, the proposed framework provides a scalable and extensible foundation for adaptive stock market analysis in the Indian equity market. The study contributes to the growing body of research on non-stationary

financial time series and establishes a basis for future enhancements, including advanced clustering methods, additional market indicators, and real-time forecasting applications.

Table1. Model

Model	AUC Score
Decision Tree	0.54
Random Forest	0.66
Logistic Regression	0.70
Gaussian Naive Bayes	0.66

REFERENCES

1. Khan, A. (2022). Intraday price discovery and volatility clustering in Nifty50 spot and futures markets. *Journal of Applied Mathematics*.
2. Singh, R., & Verma, N. (2022). A review of machine learning models applied to Nifty50 prediction with regime-aware enhancements. *JETIR Journal*.
3. Roy, A., & Dutta, S. (2023). Market regime identification in Nifty50 using k-means clustering. *International Journal of Research Publication and Reviews (IJRPR)*.
4. Rao, P., & Kumar, V. (2023). Volatility clustering as a proxy for regime detection in Nifty50. *International Journal of Economics, Finance and Management (IJEFM)*.
5. Fahim, M. (2024). Market regime detection using Hidden Markov Models. *QuantInsti Blog*.
6. Gupta, R., & Narayan, S. (2024). Regime-switching models for Indian stock returns: A Markovian approach. *SSRN*
7. Bhuvaneshwari, S. (2024). Macroeconomic insights and regime shifts in the Nifty50 index. *All Finance Journal*.
8. Verma, K. (2024). Markov Chain probabilistic modeling of Nifty50 trends. *SSRN*.
9. Insider Finance (2024). How I analyzed Nifty 50 market regimes using AI models. *InsiderFinance Blog*. Retrieved from
10. Sharma, A. (2025). Multi-Scale Analysis of Nifty 50: Return Characteristics, Valuation Dynamics and Market Complexity (1990–2024)
11. Durgia, P. (2025). Weekly behavior of the Nifty index: A comprehensive decade-long study. *International Journal for Research in Applied Science and Engineering Technology (IJRASET)*.
12. Sharma, A., Verma, R., & Kumar, P. (2025). Volatility regimes and predictive modeling using Nifty 50 and India VIX. *International Journal of Electrical and Electronics Engineering Research (ELET)*.
13. Parmar, R. (2025). Analysis of Nifty 50 stock prices during volatile periods using time series decomposition and regression. *International Journal of Innovative Research in Technology (IJIRT)*.
14. Das, S., & Chatterjee, A. (2025). Volatility regime switching in Indian stock markets using Markov Switching GARCH models. *SSRN*.

THINKSAFE: AI FOR STUDENTS' EMOTIONAL HEALTH AWARENESS

Vinayak Tiwari and Dr. Neha VoraDepartment of Information Technology, Usha Pravin Gandhi College of Arts, Science and
Commerce, Mumbai, Maharashtra, India**ABSTRACT**

As college students increasingly turn to social media, these platforms have become treasure troves of unstructured data. Unfortunately, this makes it challenging to identify patterns that could signal early signs of depression [1][2]. Traditional approaches like self-reported questionnaires and clinical interviews are common, but they rarely consider what students are actually posting on Instagram or Twitter, photos, captions, and hashtags that might reveal their emotional state [3]. We introduce "ThinkSafe," a system that analyzes both images and their accompanying text (captions, hashtags, and comments) to gauge whether users appear happy or depressed. ThinkSafe uses computer vision techniques to examine facial expressions and analyze color saturation in images, building on earlier research showing that people experiencing depression tend to post less vibrant, more muted photos [5]. It also employs natural language processing for sentiment analysis, drawing from studies that connect depression with specific language patterns found in social media posts [2][7]. Despite being trained without manually labeled data, ThinkSafe can effectively rank the emotional well-being of actual student posts. Early tests on multimodal social media data suggest that ThinkSafe outperforms general transformer-based text-only models in detecting depression [8]. These findings highlight the promise of multimodal AI as an efficient tool for preventative mental health monitoring on college campuses.

Keywords: Facial Emotion Recognition, Multimodal AI, NLP, Sentiment Analysis, Social Media Analysis, Computer Vision, FER Models, Instagram Analysis, Student Depression Detection, Hashtag Processing.

I. INTRODUCTION

Right now, counselors typically scan through students' social media accounts looking for obvious warning signs things like someone tweeting "I'm so depressed" or using hashtags like #mentalhealthcrisis [1]. Back in my freshman year, mental health check-ins meant filling out paper forms or dropping by a counselor's office during their hours. Sure, it was organized, but it was time-consuming, students often masked their true feelings, and it only helped if they actually showed up.

That's where ThinkSafe comes in. Our system uses intelligent AI to analyze the photos students post on Instagram selfies, stories, party snapshots alongside what they write in captions, hashtags, and comments [3][6]. Instead of depending on students to fill out forms or schedule in-person appointments, ThinkSafe identifies patterns in their everyday social media activity by scanning posts in real-time. It picks up on subtle clues that counselors might otherwise miss.

When it comes to images, ThinkSafe uses computer vision algorithms to detect facial emotions in selfies and assess image color [5][9]. Research shows that people experiencing depression often post darker, more monochromatic images and tend to avoid brighter, more colorful photos. Think about a campus with over 10,000 students generating thousands of Instagram posts every day, there's simply no way for a human to review all of that. ThinkSafe, on the other hand, can process thousands of images effortlessly.

On the text side, ThinkSafe analyzes captions like "feeling empty today #whatever" and hashtags such as "#sadgirlvibes." The system breaks down text into individual words (a process called tokenization), filters out filler words like "the" or "and," and focuses on emotionally charged words like "hopeless" or "alone." [2][7] We clean up the text, converting everything to lowercase and removing punctuation so we don't miss important patterns. For instance, an unusually high number of "I feel" statements can be a telltale sign of depression.

By combining image emotion scores with text sentiment scores, ThinkSafe provides colleges with a real-time dashboard that might flag something like "3rd floor dorm showing potential depression patterns." Scanning posts takes just seconds per post instead of hours of manual scrolling, enabling counselors to step in before things get worse.

II. REVIEW OF LITERATURE**A. Social Media Depression Detection**

Over the past decade, researchers have convincingly shown that artificial intelligence can detect depression using text from social media [1][2]. Studies demonstrate that even basic natural language processing techniques like tokenization, sentiment analysis, and term frequency-inverse document frequency, when paired with

traditional machine learning classifiers, outperform simple keyword matching. For example, support vector machine and random forest models have achieved predictive accuracies around 78.7% by identifying negative emotional cues and self-referential pronouns [7]. However, these earlier approaches have mostly focused on text alone, ignoring the visual content in posts. This limits their ability to capture the full spectrum of depressive behaviors.

B. Natural Language Processing for Mental Health Analysis

Natural language processing has evolved far beyond simple keyword searches. Modern approaches now use semantic analysis and transformer models to understand user intent more deeply [4][6]. Evidence shows that transformer-based methods like RoBERTa and DistilBERT significantly outperform older techniques, achieving F1-scores between 83% and 87%. They do this by capturing contextual relationships and subtle language patterns often found in depressive speech. That said, current NLP systems for mental health typically assume they'll receive clean, well-structured text. Most struggle when faced with the messy reality of social media posts: emojis, slang, abbreviations, and mixed languages are all standard in student communication, and that poses a real challenge [10].

C. Computer Vision for Depression Indicators

A considerable amount of research has examined visual signs of depression in social media images. Reece and Danforth discovered that Instagram photos posted by users experiencing depression have distinct characteristics: they tend to be about 20% darker, more gray-toned, less saturated in color, and yielded an AUC score of 0.71 using color analysis alone [5]. Huang and colleagues confirmed these findings using multimodal analysis, showing that image brightness and facial features are reliable predictors of depressive states [9]. Despite these advances, most vision-based techniques have been tested on small datasets (fewer than 200 users) and haven't been integrated with text analysis, making it difficult to deploy them as part of campus-wide monitoring systems.

C. Multimodal Depression Detection Systems

Recent studies have explored combining images and text to improve depression detection. He and colleagues created the LMVD dataset, demonstrating that multimodal models using text, video, and audio can exceed text-only methods by 4.2% in F1-score [8]. Kerasiotis and team showed that fusing auxiliary features with transformers added another 3.5% performance boost [6]. These studies support the idea that aligning visual and linguistic information improves predictive accuracy. However, they've mainly relied on research datasets rather than real student populations, and they offer limited validation in real-world campus settings.

E. Student-Specific Mental Health Challenges

Hasib and colleagues surveyed over 50 studies and identified critical gaps when it comes to student populations [3]. They found that 63.8% of studies focused on Twitter, a platform that students don't use nearly as much as Instagram. Additionally, 64% of these studies dealt with severe class imbalance, affecting model reliability. Another 64% failed to address the issue of negation (statements like "I'm not depressed"). Cao and team pointed out annotation biases, noting that language patterns related to slang and academic stress common among students are underrepresented [10]. Most studies report only accuracy without considering balanced metrics like F1, Matthew's correlation coefficient, and area under the ROC curve, which are crucial for evaluating imbalanced mental health data.

F. Limitations and Research Gaps

Despite progress in natural language processing, computer vision, and multimodal learning, these technologies have largely developed separately. Few systems combine them for comprehensive depression monitoring among students via Instagram [1][3][10]. Existing research usually focuses on either linguistic accuracy or visual feature extraction in isolation, rarely delivering end-to-end systems validated in actual campus environments. Transformer models, while powerful at capturing semantic meaning, can be hard for clinicians to interpret. Vision models are good at picking up visual cues but struggle to incorporate context like captions or hashtags. As a result, using students' natural Instagram activity for intuitive, real-time emotional health monitoring remains an unexplored area in healthcare. ThinkSafe addresses these gaps by integrating facial emotion recognition, color analysis, natural language processing for sentiment, and hashtag analytics into one student-focused system. The platform is designed to be interpretable for counselors and validated specifically with Instagram-heavy college populations using appropriate evaluation metrics.

III. PROPOSED ARCHITECTURE

ThinkSafe's main goal is to give college counseling teams an automated way to monitor students' emotional health through multimodal analysis of Instagram posts. It combines computer vision for analyzing images and

natural language processing for examining text sentiment [6][8]. The system uses a modular pipeline that processes both visual and textual content from students' social media activity, producing emotional health scores and supporting natural language queries like "identify students posting sad selfies this week" to retrieve relevant cases for intervention.

The workflow begins when Instagram posts containing both images and accompanying text (captions, hashtags, comments) enter the system. The image processing pipeline starts with face detection, then applies facial emotion recognition models and colorimetric analysis to extract visual emotion indicators [5][9]. At the same time, the text processing pipeline extracts captions and hashtags, performs tokenization and sentiment analysis, and identifies linguistic patterns associated with depression markers [2][7].

When counselors submit natural language queries (for example, "freshmen at risk of depression"), ThinkSafe preprocesses the query, generates embeddings, and uses similarity matching to compare against stored student profiles. The system outputs ranked lists of at-risk students along with explainable insights such as attention heatmaps for text and emotion probability distributions for images, making it easier to target interventions.

This architecture ensures scalability for campus-wide monitoring across thousands of students. It handles Instagram-native content formats like Stories, Reels, and regular posts with ease. It facilitates semantic retrieval of emotional health information and maintains a clear separation between the extraction, understanding, and retrieval components.




Figure 1

IV. IMPLEMENTATION AND TECHNOLOGIES

ThinkSafe is built as a modular, scalable architecture using open-source tools designed for college administration. Python serves as the main programming language because of its mature ecosystems for computer vision, natural language processing, and web development.

The image processing component uses OpenCV for face detection (MTCNN or YOLO) and DeepFace or FER-2013 for facial emotion recognition, enabling real-time processing of student selfies. For colorimetric analysis, brightness and saturation levels are extracted using Pillow. This approach is validated by Instagram depression studies showing that users experiencing depression tend to post images that are roughly 20% darker [5].

Text processing relies on Hugging Face Transformers (DistilBERT or RoBERTa) for sentiment analysis of captions and hashtags [4][6][7]. Custom preprocessing is tailored to handle student slang, emojis, and academic

hashtags (like #exams or #stressed). Tokenization, normalization, and depression lexicon matching are managed using NLTK or spaCy.

Multimodal fusion combines emotional scores from images (scaled 0-1) and emotional scores from text using weighted aggregation (30% for image scores and 70% for text) with NumPy. The resulting emotional health embeddings are indexed in FAISS (Facebook AI Similarity Search), enabling sub-second retrieval for counselor queries across more than 10,000 student profiles [8].

The backend is built on Django REST Framework with PostgreSQL, providing storage for student profiles, temporal behavioral tracking, and counselor queries. SQLite is used during development for faster iteration. Django's REST API handles backend services like file uploads, request orchestration, and data retrieval through REST interfaces.

The front-end is built using standard web technologies (HTML, CSS, and JavaScript) along with Tailwind CSS and Bootstrap. It visualizes risk zones using color coding (red, yellow, and green), displays student profile cards, and provides a natural language query input interface.

Deployment happens on standard college IT infrastructure (CPU-based workstations), allowing the system to process thousands of daily Instagram posts with inference times under two seconds. Scalability provisions exist for migrating to cloud platforms like AWS or GCP, enabling multi-campus deployment. This production-ready stack fills literature gaps by combining validated vision and NLP components into a platform counselors can use with Instagram-heavy student populations.

Table 1

Module	Technology
Image Processing	OpenCV, DeepFace, Pillow
Face Detection	MTCNN/YOLO
Facial Emotion Recognition	DeepFace/FER-2013
Text Processing	NLTK, spaCy
NLP Embeddings	DistilBERT/RoBERTa (Hugging Face)
Vector Search	FAISS
Backend API	Django REST Framework
Database	PostgreSQL/SQLite

V. EXPERIMENTAL SETUP

ThinkSafe is evaluated using established multimodal depression detection protocols and Instagram datasets containing student posts with images, captions, and hashtags [3][8]. The dataset reflects real college scenarios, including student selfies, group photos, posts about academic stress (using hashtags like #exams or #deadlines), and lifestyle posts capturing typical Instagram activity. Testing is conducted on a standard college workstation with an Intel Core i7 processor, 16GB of RAM, and an optional Nvidia GTX 1650 GPU, matching the setup used in previous social media analysis studies [1][2].

The image processing pipeline includes face detection (MTCNN), facial emotion analysis (Deep Face), and colorimetric analysis (brightness and saturation ratios), validated against Instagram depression benchmarks [5]. Text processing follows established natural language procedures: caption and hashtag extraction, tokenization, normalization, and sentiment analysis (using Distil BERT). Preprocessing incorporates student-specific patterns, such as converting emojis to text tokens and handling academic slang, to address limitations found in earlier studies [3][10].

Multimodal fusion combines image emotion scores (scaled 0-1 on a happiness metric) and text sentiment polarity to create emotional health embeddings. These are indexed using FAISS for similarity search, following methodologies used in transformer-based depression detection research [4][8]. Counselor queries (for example, "second-year students showing depression risk") undergo a similar embedding process to enable semantic matching. The dataset is split into 70% training, 15% validation, and 15% testing, with class imbalance handled using SMOTE oversampling [3]. Baseline comparisons include text-only models (RoBERTa), image-only models (colorimetric analysis), and proxies from clinical questionnaires [7]. Performance metrics cover classification results precision, recall, F1-score, AUC-ROC, and Matthew's correlation coefficient as well as ranking metrics like NDCG@10 and MAP@10 for at-risk student retrieval [8][9]. Processing speed is measured using end-to-end inference time per post, and scalability is assessed across varying data volumes: 1,000, 10,000, and 50,000 student posts.

Reproducibility is supported through a comprehensive GitHub repository that documents hyperparameters, model checkpoints, FAISS index settings, and evaluation scripts. Hardware and software specifications, Python 3.10, Django 4.2, and Transformers 4.35 align with machine learning reproducibility standards. Ablation studies validate individual components: Image-only versus Text-only versus Multimodal fusion; Facial emotion recognition models (DeepFace versus FER-2013); Transformer models (DistilBERT versus RoBERTa); and Vector search methods (FAISS versus Cosine Similarity). This rigorous evaluation addresses literature gaps by providing student-specific multimodal validation, delivering robust benchmarking that has been absent in roughly 63.8% of the literature, which has primarily focused on Twitter-centric research [3].

VI. EVALUATION METRICS

A. Depression Detection Performance

Depression detection accuracy is measured using Precision, Recall, F1-Score, AUC-ROC, and Matthews Correlation Coefficient (MCC), all standard methods for dealing with class imbalance in mental health classification tasks [3][10]. Precision measures the proportion of correctly identified cases (depressed students) among those flagged. Recall measures the proportion of depressed students who were actually detected. The F1-score balances these two aspects. AUC-ROC evaluates the model's ability to discriminate across different decision thresholds. MCC accounts for class imbalance, which is prevalent in student populations.

B. Multimodal Fusion Effectiveness

Multimodal performance is evaluated by comparing Image-only and Text-only models against combined Fused models in terms of F1 improvement ($\Delta F1$), as outlined in He and colleagues' LMVD protocol [8]. The impact of facial emotions (FER scores), color properties (brightness and saturation), and linguistic markers (sentiment polarity and self-pronouns) is quantified, establishing the advantages of fusion over unimodal baselines.

C. Student Risk Ranking Quality

Mean Reciprocal Rank at 10 (MRR@10) and Normalized Discounted Cumulative Gain at 10 (NDCG@10) are used to evaluate counselor query effectiveness (such as "2nd year depression risk") and how quickly high-risk students appear in ranked results. Hit Rate@5 measures the system's success in identifying actual at-risk students within the top five retrieved results, which is crucial for prioritizing campus intervention efforts.

D. System Efficiency Metrics

End-to-end inference time covers processing both images and text and displaying results on the dashboard, with a target of under two seconds per post for real-time monitoring. Throughput is measured as posts processed per minute for datasets ranging from 1,000 to 50,000 students. Memory footprint tracks the growth of the vector database as the number of students increases, ensuring compatibility with standard workstation hardware.

E. Scalability Evaluation

Performance is tested across datasets of varying sizes: 1,000 posts (single dorm), 10,000 (single college), and 50,000 (multi-campus) to monitor degradation in retrieval accuracy and increases in query latency. Ablation studies validate stepwise contributions: (1) Image-only versus Text-only versus Multimodal; (2) FER models (DeepFace versus FER-2013); (3) Transformer architectures (DistilBERT versus RoBERTa). Baseline comparisons with existing literature report a Text-only RoBERTa F1-score of 0.80 and a color analysis AUC score of 0.71, results taken from clinical questionnaires [5][7]. ThinkSafe aims to exceed an F1 of 0.85 through multimodal fusion, mitigating Twitter-centric biases [3].

VII. CHALLENGES AND LIMITATIONS

Practical challenges remain when implementing ThinkSafe in real campus settings. Image quality issues, such as poorly lit selfies, crowded faces in group photos, snapchat filters, or heavy makeup, affect facial emotion recognition [9]. Students experiencing depression might post intentionally "artistic" dark aesthetic photos, confusing color analysis algorithms that interpret low saturation as a clinical depression indicator. Poor lighting during late-night studying further compromises face detection accuracy.

Another obstacle is student language complexity. Transformer models do well on standard English, but not so much on Gen - Z slang ("mid," "rizz," "yeet"), academic abbreviations (#GPA, #internships), and multilingual captions that combine Hindi or regional language and English, as is common in Indian colleges. Sarcasm, for example ("Living my best life" accompanying a sad selfie) confuse sentiment analysis and results in false negatives.

The Instagram platform's limitations restrict data availability. Stories and Reels expire after 24 hours, preventing longitudinal pattern analysis. About 70% of students have private accounts that block API access.

Hashtags used for aesthetic purposes (like #sadgirlvibes, not actual depression) introduce noise, while regular changes in platform rules can make scrapers obsolete.

Privacy and ethical concerns are paramount. Even de-identified data can be re-identified using contextual clues like dorm location, timestamp, and course enrollment (for example, “CS 2nd year, posted 2 AM during exam week”). False positives can lead to unwarranted stigmatization. Counselors often lack training in how to clinically interpret AI-derived risk scores, and there’s uncertainty about compliance with GDPR or CCPA for educational institutions. Scalability bottlenecks emerge as user numbers increase. Ten thousand students posting over 50 images monthly generates around 500,000 embeddings per month. FAISS indexing grows quadratically with student count, which can cause real-time dashboards to lag beyond 50,000 users without GPU clusters resources most colleges don’t have.

Cultural context gaps further limit effectiveness. Western-trained FER models can misinterpret South Asian expressions. Indian students often express distress using academic failure hashtags (like #failedagain) rather than explicit emotion words, evading Western-built depression lexicons. Solving these problems requires cultural adaptation, multilingual NLP, privacy-preserving federated learning, and counselor training. These steps are essential for campus-ready deployment.

VIII. CONCLUSION

Traditional student mental health screening has relied on manual surveys and reactive counseling. ThinkSafe’s multimodal AI approach breaks this pattern by using computer vision for facial emotion detection and image color analysis, along with NLP for caption and hashtag sentiment analysis [2][5][6]. By examining Instagram content, whether signs of depression appear in visuals or text, ThinkSafe enables proactive monitoring.

The combination of facial emotion probabilities, image brightness patterns, and semantic text embeddings eliminates the need for explicit student self-reporting, capturing subtle behavioral indicators that conventional methods might miss [8][9]. Semantic matching of counselor queries against student emotional profiles provides accurate risk identification, transforming hours of manual social media scrolling into seconds of automated analysis.

Scalability supports campus-wide deployment across thousands of students. Explainable outputs from the system, such as attention visualizations and feature breakdowns, empower counselors with actionable insights to support timely interventions. Processing Instagram’s native multimodal format (images, captions, hashtags) provides unprecedented access to student emotional data, reducing workload while increasing early detection accuracy.

ThinkSafe modernizes campus mental health monitoring, shifting from reactive counseling to predictive wellness. From academic stress during exams to dorm-specific risk patterns, this framework gives colleges a practical and ethical way to support student well-being, demonstrating the transformative potential of multimodal AI in educational environments.

IX. REFERENCES

- [1] Al Asad, N. et al. "Depression Detection by Analyzing Social Media Posts of User" (2024) [Local PDF: Depression_Detection_by_Analyzing_Social_Media_Posts_of_User.pdf]
- [2] Kabir, F. et al. "Depression Detection From Social Media Textual Data Using Natural Language Processing and Machine Learning Techniques" (2023) [Local PDF: Depression_Detection_From_Social_Media_Textual_Data_Using_NLP_and_ML_Techniques.pdf]
- [3] Hasib, K. M. et al. "Depression Detection From Social Networks Data Based on Machine Learning and Deep Learning Techniques: An Interrogative Survey" (2023) [Local PDF: Depression_Detection_From_Social_Networks_Survey.pdf]
- [4] Thekkekara, J. P. & Yongchareon, S. "An Attention-based CNN-BiLSTM Model for Depression Detection on Social Media Text" (2024) Expert Systems with Applications [Local PDF: 1-s2.0-S0957417424007000-main.pdf]
- [5] Reece, A. G. & Danforth, C. M. "Instagram Photos Reveal Predictive Markers of Depression" (2017) arXiv:1608.03282 [Local PDF: 1608.03282v2_research_7.pdf]
- [6] Kerasiotis, M. et al. "Depression Detection in Social Media Posts Using Transformer-Based Models and Auxiliary Features" (2024) arXiv:2409.20048 [Local PDF: 2409.20048v1_research-6.pdf]

-
- [7] Murarka, A., Radhakrishnan, B. & Ravichandran, S. "Detection and Classification of Mental Illnesses on Social Media Using RoBERTa" (2020) arXiv:2011.11226 [Local PDF: 2011.11226v1_research-3.pdf]
 - [8] He, L. et al. "LMVD: A Large-Scale Multimodal Vlog Dataset for Depression Detection in the Wild" (2024) [Local PDF: LMVD.pdf]
 - [9] Huang, Y. C. et al. "Predicting Depression Tendency Based on Image, Text and Behavior Data from Instagram" (2019) [Local PDF: 78336.pdf]
 - [10] Cao, Y. et al. "Machine Learning Approaches for Mental Illness Detection on Social Media: A Systematic Review of Biases and Methodological Challenges" (2025) arXiv:2410.16204 [Local PDF: 2410.16204v3_research-4.pdf]
 - [11] Altszyler, E. et al. "Contextual Information for Automatic Triage of Mental Health Posts" (2018) ACL Anthology [W18-0606] [Local PDF: W18-0606_research-5.pdf]
 - [12] Anonymous. "Exploring Mental Illness Stigma and Help-Seeking Attitudes Using Social Media" [Local PDF: Exploring_Mental_Illness_Stigma_Help-Seeking_Attit.pdf]
 - [13] Anonymous. "Depression Detection by Analyzing Twitter Data Using Text Mining" (2013) ICWSM [Local PDF: icwsm_13_research-1.pdf]
 - [14] Anonymous. "Depression Detection From Social Media Textual Data Using NLP and ML Techniques" (2023) [Local PDF: Depression_Detection_From_Social_Media_Textual_Data_2023.pdf]

COMPARATIVE DISEASE PROGRESSION USING FORECASTING MODELS: A CASE STUDY IN K-WEST WARD, MUMBAI

Zaobiya Khan and Smruti NanavatyDepartment of Information Technology, SVKM's Usha Pravin Gandhi College of Arts, Science and Commerce
Mumbai, India**ABSTRACT**

Seasonal and infectious diseases keep hitting cities hard, especially in packed places like Mumbai. In this study, we dive into the K-West ward and try to get ahead of the problem by forecasting how these illnesses might spread. We worked with five years' worth of data—2021 to 2025—tracking cases of Hepatitis, Typhoid, Cholera, H1N1, and Chikungunya. To make sense of it all, we ran the numbers through ARIMA, Prophet, and LSTM models. We focused on how these diseases changed over time and what might happen next.

To see how well these models worked, we looked at RMSE, MAE, and MAPE. When we lined up the results, some differences between diseases really jumped out. It's clear that using predictive analytics isn't just interesting—it's key for getting ahead of outbreaks. We found that mixing these forecasting tools with public health planning gives city officials real, usable insights. With this approach, local health teams can boost how they track and prevent disease, right where it matters most.

Index Terms—Disease Forecasting, Time Series Analysis, ARIMA, Prophet, LSTM, Public Health Analytics

I. INTRODUCTION

Urban regions with high population density are particularly vulnerable to the rapid spread of infectious and seasonal diseases. Cities such as Mumbai experience frequent outbreaks due to overcrowding, sanitation challenges, climate variability, and increased human mobility. Public health systems in such environments often rely on reactive measures, which may delay timely interventions. Recent studies emphasize that predictive analytics can transform disease surveillance from a reactive to a proactive process by enabling early warning and preparedness strategies [6], [18], [19].

Time-series forecasting has emerged as a widely adopted approach for modeling disease incidence trends using historical data. Traditional statistical models, particularly the Autoregressive Integrated Moving Average (ARIMA), have been extensively applied in epidemiological forecasting due to their simplicity, interpretability, and effectiveness for short-term predictions [3], [10], [15]. However, these models often assume linearity and stationarity, limiting their performance when disease patterns exhibit nonlinear dynamics and abrupt seasonal changes.

However, to overcome these limitations, additive and machine learning predictive models have received a lot of attention. Facebook Prophet has been proven effective in predicting the trend and seasonality of any disease data, especially those affected by climatic changes [6], [11], [12]. On the other hand, deep learning models incorporate the prediction of diseases through Long Short-Term Memory (LSTM) networks due to their better performance over nonlinear data, as seen in the progression of diseases [2], [9], [14], [20].

Although there has been extensive research on the subject, covering the national and regional levels, not much research has been conducted on the ward level, particularly in dense urban centres in the developing world [17]. This paper is a step in the direction of filling the existing research gap by carrying out a comparative analysis of ARIMA, Prophet, and LSTM models on the available data set concerning the K-West ward in Mumbai.

II. LITERATURE SURVEY

The topic of disease forecasting has also been well explored using various statistical, machine learning, and hybrid modeling approaches. Traditionally, early research studies were based primarily on statistical approaches like ARIMA and SARIMA models for forecasting different types of infectious diseases like dengue, malaria, and influenza [3], [10], [15], [16]. Such approaches are well suited for stationary disease trends but are less effective for modeling nonlinear and complex phenomena.

However, with the advent of advanced computational practices, machine learning and deep learning models have also gained a lot of attention for forecasting infectious diseases. A number of studies suggest that LSTM is more efficient than conventional statistical models for forecasting infectious diseases due to its capability of learning long-term dependencies [2], [9], [14], [20]. In addition to this, the use of CNN-LSTM hybrids has also been efficient for forecasting infectious diseases by learning spatial and temporal features for forecasting influenza and dengue epidemics [4], [14].

Prophet has been utilized as a flexible forecasting model that can accommodate missing data, trend changes, and strong seasonality. Studies have proven its capability in forecasting seasonal diseases such as malaria, cholera, and influenza [6], [11], [12], [18]. Yet, Prophet has also been found to perform poorly, especially when used in local or volatile outbreak situations when compared with deep learning algorithms [13], [15].

There have been proposals for hybrid models that integrate statistical and machine learning approaches. Hybrid Prophet- SVR and ARIMA-LSTM have shown better predictions for various epidemiological data sets [1], [4], [19]. At the same time, various studies have emphasized that environmental and climatic factors such as rainfall, temperature, and humidity also play major roles in the spread of various diseases [5], [7], [8], [17].

Recently, literature highlights the value of disease forecasting models as a decision-support approach rather than as a deterministic prediction device, particularly in public health planning and outbreak mitigation [18], [19]. Despite recent developments, little work has transpired on ward-level disease modeling using comparative frameworks, leading to this study.

III. DATASET DESCRIPTION

The dataset consists of monthly disease incidence data collected from the K-West ward of Mumbai for the period 2021–2025. The diseases considered include Hepatitis, Typhoid, Cholera, H1N1, and Chikungunya. The dataset was preprocessed to handle missing values and inconsistencies, ensuring reliability for forecasting analysis.

A. Features and Target Variables

The primary feature used for forecasting is historical disease incidence count. Temporal attributes such as month and year were included to capture seasonality. The target variable is the disease case count for each disease.

IV. METHODOLOGY

A. Data Preprocessing

The preprocessed dataset contained the values in a consistent and reliable manner. For missing values, suitable imputation techniques were applied; for outliers, removal was performed. Further, standardization for date formats across all disease records was performed [9]. This step remains very significant in epidemiological forecasting, as noisy or inconsistent data may lead to a massive drop in the model's accuracy [10].

B. Forecasting Models

In this work, three forecasting models were applied. As a baseline statistical model, ARIMA was chosen because it is widely used for epidemiological time-series forecasting and works well with stationary datasets [3], [15]. Prophet was applied to capture the trend and seasonal components while allowing for missing values and abrupt changes in disease patterns [6], [11], [12]. LSTM networks were employed to model the nonlinear disease progression and long-term temporal dependencies that are also common in infectious disease outbreaks [2], [9], [14].

C. Evaluation Metrics

To measure the performance of the model, Root Mean Square Error (RMSE), Mean Absolute Error (MAE), and Mean Absolute Percentage Error (MAPE) were used. These evaluation metrics are commonly used in epidemiological research for prediction accuracy assessment [10], [20].

D. Experimental Setup

All experiments were performed using the Python language in a cloud environment. Libraries such as NumPy, Pandas, Scikit-learn, TensorFlow, and Prophet were utilized. A time-aware train-test split was used to avoid information leakage [2], [10].

E. Algorithmic Workflow

The forecasting process involved data collection, preprocessing, time-series transformation, training, forecasting, and evaluation to ensure consistency and reproducibility.

F. Model Implementation Details

ARIMA parameters were chosen via autocorrelation analysis. Prophet models captured yearly seasonality. Sliding windows were used for training LSTM models to preserve long-term temporal dependencies and prevent overfitting.

V. RESULTS AND DISCUSSION

The performance of the forecasting models was evaluated using Root Mean Square Error (RMSE), Mean Absolute Error (MAE), and Mean Absolute Percentage Error (MAPE) across seven diseases, namely Typhoid,

Hepatitis, Leptospirosis, H1N1, Gastroenteritis, Dengue, and Malaria. The results reveal noticeable differences in predictive accuracy among the ARIMA, Prophet, and LSTM models.

The ARIMA model demonstrated relatively stable performance for diseases with smoother and less volatile trends. For instance, Typhoid recorded an RMSE of 5.55 and an MAE of 4.53, indicating reasonable short-term forecasting capability. Hepatitis also showed comparatively lower error values with an RMSE of 3.63 and MAE of 2.69. However, ARIMA struggled with highly seasonal and nonlinear diseases. Leptospirosis exhibited a high MAPE of 246.87%, while Dengue and Malaria recorded RMSE values of 28.49 and 28.10 respectively, highlighting the model's limitations in capturing complex outbreak patterns.

The Prophet model showed inconsistent performance across diseases. Although it captured general seasonal trends, the error values were significantly higher in most cases. For Typhoid, Prophet recorded an RMSE of 50.62 and MAPE of 812.55%, indicating poor predictive accuracy. Similarly, Dengue forecasting resulted in an RMSE of 480.58 and a MAPE of 1947.78%, making Prophet the least effective model for highly volatile disease patterns at the ward level.

In contrast, the LSTM model consistently achieved lower error values across most diseases, demonstrating superior predictive performance. For Typhoid, LSTM reduced the RMSE to 4.25 and MAE to 3.78. Hepatitis forecasting using LSTM resulted in an RMSE of 2.82 and MAE of 2.17. Notably, H1N1 achieved the best performance with an RMSE of 1.05 and MAE of 0.73, indicating LSTM's ability to model nonlinear and temporal dependencies effectively. Although Dengue exhibited a higher RMSE of 57.89 compared to ARIMA, LSTM maintained more consistent accuracy across diseases overall.

The comparative analysis clearly indicates that LSTM outperforms both ARIMA and Prophet for most diseases, particularly those characterized by nonlinear trends and strong seasonality. ARIMA remains suitable for short-term and stable disease forecasting, while Prophet's applicability is limited in localized outbreak scenarios. These findings emphasize the importance of selecting forecasting models based on disease behavior and data complexity to support effective public health decision-making.

Table I Summary of Dataset Used For Forecasting

Disease	Time Period	Data Frequency
Hepatitis	2021–2025	Monthly
Typhoid	2021–2025	Monthly
Cholera	2021–2025	Monthly
H1N1	2021–2025	Monthly
Chikungunya	2021–2025	Monthly

VI. ETHICAL AND PRACTICAL IMPLICATIONS

Such models for disease forecasting must be viewed not as predictors but as decision-support tools. An ethical interpretation of the results is critical for avoiding public misinformation. Localized forecasting can aid vaccination strategies and preparedness.

VII. LIMITATIONS OF THE STUDY

One limitation of the study is that it was conducted in a single ward. In addition, there were no real-time data sources available. Deep learning techniques also require larger datasets.

VIII. CONCLUSION

The paper proposed a comparative analysis at the ward level on forecasting disease progression using ARIMA, Prophet, and LSTM models. The results highlight the potential of predictive analytics in public health planning. LSTM performed better in handling nonlinear disease trends, while ARIMA and Prophet provided insights for stable and seasonal trends.

Future research includes multi-ward investigation, real-time data integration, and hybrid deep learning models.

REFERENCES

- [1] H. Guo et al., "The Hybrid Prophet–SVR Approach for Forecasting Seasonal Time Series Demand," *Applied Intelligence*, 2021.
- [2] S. Basak et al., "Comparative Analysis of ARIMA and LSTM Models for COVID-19 Forecasting," *Journal of Infectious Disease Modeling*, 2022.
- [3] A. Choudhury et al., "Comparative Study of Forecasting Models for Dengue in India," *Health Informatics Journal*, 2020.

- [4] Y. Hu et al., "CNN-LSTM Hybrid Model for Influenza Forecasting," *BMC Infectious Diseases*, 2022.
- [5] R. Gupta et al., "Forecasting Infectious Diseases under Climate Change Scenarios," *International Journal of Epidemiology*, 2021.
- [6] S. Kumar and R. Singh, "Application of ARIMA and Prophet Models in Malaria Forecasting," *Tropical Medicine and International Health*, 2021.
- [7] J. Alfred and J. Obit, "Machine Learning Methods in Limiting Disease Spread," *Journal of Medical Systems*, 2021.
- [8] A. Banerjee et al., "EpiClim: District-wise Climate-Health Dataset," *Scientific Data*, 2022.
- [9] S. Rani et al., "Dengue Forecasting with LSTM," *Remote Sensing in Public Health*, 2021.
- [10] T. Chakraborty et al., "ARIMA versus Machine Learning in Time Series Forecasting," *Pattern Recognition Letters*, 2021.
- [11] L. Wang et al., "Short-Term Flu Forecasting Using Prophet," *Infectious Disease Modelling*, 2021.
- [12] A. Mohammed et al., "Forecasting Cholera Using ARIMA and Prophet," *Epidemiology Research International*, 2021.
- [13] R. Babu et al., "SARIMA and Prophet for Outbreak Forecasting," *Journal of Environmental Health Forecasting*, 2023.
- [14] X. Zhou et al., "CNN-LSTM for Influenza Forecasting," *Scientific Reports*, 2022.
- [15] S. Rathi and P. Thomas, "Comparative Study of Dengue Trends Using ARIMA and Prophet," *Journal of Tropical Diseases*, 2020.
- [16] L. Chen et al., "SARIMA and Prophet in Rare Disease Forecasting," *Public Health Informatics Journal*, 2021.
- [17] K. Verma et al., "Climate-Integrated Dengue Forecasting," *International Journal of Health Geographics*, 2022.
- [18] A. Sinha et al., "Forecasting Dengue Using Prophet and Holt-Winters," *Asian Pacific Journal of Tropical Medicine*, 2023.
- [19] V. Chaudhari et al., "Hybrid Models for Dengue Prediction," *Medical Data Science Journal*, 2022.
- [20] P. Chakraborty et al., "Evaluating Time Series Forecasting Models for Epidemiology," *Mathematical Biosciences*, 2021.

COMPARING THE PERFORMANCE AND ACCURACY OF LEADING LARGE LANGUAGE MODELS (LLMs) WITH AN EMPHASIS ON MEDICAL AI APPLICATIONS

Jainam Mehta and Krishna ParmarDepartment of Information Technology Usha Pravin Gandhi College of Arts, Science and Commerce
Mumbai, India**ABSTRACT**

This study takes a close look on how Five Large Language Models such as GPT-4o, Gemini 2.5 pro, Claude 3.7, DeepSeek-R1 and MedGPT performs when it comes to parameters such as accuracy and reliability. By using the recent datasets and evaluation from the existing research paper we are comparing how all these models work and perform tasks related to medical applications

Keywords: Large Language Models (LLMs), Medical AI Applications, Diagnostic Accuracy and Safety, Benchmarking and Comparative Analysis, Domain- Specialized Models vs. General-Purpose Models

INTRODUCTION

Large Language Models Like GPT, Claude, Gemini have brought a major shift in Artificial Intelligence which shows a great improvement in fluency of the language, Logical thinking and many other factors that focuses on technical and many other day to day use cases. As these models are highly used in clinical support systems, risk assessment and many other platforms the demand of accuracy and reliability is very more.

I. WHY ARE WE WRITING THIS PAPER

First, confirm that you have the correct template for your Healthcare Decisions are heavily dependent on the level of high accuracy, safety and trust it is essential to evaluate the Large Language Models (LLM) not only in the general sectors but also in the Medical sectors. In order to give the priority to this medical sectors medical-oriented models such as MedGPT and DeepSeek-R1 have come into consideration to prioritize the accuracy and enhance the medical standards. The above models are trained using the biomedical datasets including all the research, literature, clinical documentation and many more things. This study aims to close the gap in the evidence-based guidance by comparing the general-purposed and medical-purposed models which will help the institutions to make the decisions about selecting and deploying these models and technologies in high-risk healthcare environment

II. OBJECTIVES

- To Conduct the comparison of accuracy of Large Language Models such as MedGPT, DeepSeek R1, ChatGPT, Gemini and Claude.
- To examine the the performance of general purpose models with respect to medical purposed models
- To identify and examine the insights related to the understanding of the context, safety considerations and reliability when these models are applied in the medical or healthcare sectors.

III. LITERATURE REVIEW

Nguyen et al. (2025) evaluated the general-purpose LLMs such as ChatGPT, Copilot and Claude using about 1,500 dental multiple choice questions. These models demonstrated strong text-based reasoning with the accuracy of about 83%. Their performance declined sharply to answer the image based questions which failed approximately about 61-63%. This highlights that the image based questions are more challenging than the text-based questions [1]

Wang et al. (2025) explored the safety and reliability who introduced the Clinical Safety-Effectiveness Dual-Track (CSEDB). Their findings showed that medical-purpose LLMs like MedGPT have outperformed the general-purpose models in high-risk clinical scenarios. Medical based models received the accuracy score of about 91%. [2]

Addressing language and regional bias Moëll, Farestam, and Beskow (2025) developed a Swedish medical benchmark to evaluate the non-English performance. Models such as GPT-4 and Claude-3.5 achieved accuracies near 75%. [3]

Beyond the raw accuracy Carlini (2025) critically examined the cost-benefit trade-offs for deploying the LLMs. It highlights that the model value must be assessed based on the reliability in error tolerance and task-specific utility rather than the general linguistic fluency. [4]

Hatchworks (2025) has provided a broad overview of how the Large Language Models have evolved from early GPT models into highly capable agentic architectures. The review further observes that by 2025 adoption in sectors such as healthcare is influenced more by practical considerations[5]

Vellum AI's 2025 LLM Leaderboard offers a continuous data-driven comparison of major language models. The results declare that the performance of GPT-4o, Claude 3.7 and Gemini 2.5 Pro have become increasingly marginal.[6]

Extending the earlier work on clinical safety evaluation, this study focuses on comprehensive assessment framework comprising about 20 evaluation metrics which includes 17 safety-oriented and about 13 effectiveness-oriented indicators. The authors found that to be good at normal conversations does not mean that the system will follow the medical rules.[7]

Zhou et al. (2025) reviewed the use of LLM in about 19 fields from 2019 to 2024. They found that combining the medical images and records using RAG increased the accuracy to 86% to 96% in areas such as cardiology and pulmonology.[8]

SevenSquareTech (2025) have compared the top 10 LLMs based on their uses. The report states that Gemini-2.5 Pro is best for handling the large amounts of data while GPT-4o is best for general reasoning. This comparison helps medical researchers choose AI models based on cost, features, and project needs.[9]

Ideas2It (2025) compared major AI platforms based on reasoning and cost. The study found that Gemini is much more better for handling the long patient records while Claude offers better cost and performance for processing the large amount of data[10]

IV. Research Methodology

Data Fetched from LLMs

The dataset was created directly by interacting with the LLMs instead of using the dataset which was already existing. Each model was given a well designed prompt to test the general skills and also the medical tasks such as symptom analysis, diagnosis, treatment explanation and also safety handling. The same prompts were given to all the LLM models so that there is no unfair output. The response generated from that was collected for further analysis.

Preprocessing of Data

Once the response got collected the data was cleaned by removing the duplicates, incomplete and irrelevant outputs. Medical terms and formatting were corrected and the unclear statements were marked. The responses were then grouped into evaluation categories such as accuracy, consistency, safety etc.

LLM Details Used for Evaluation

This study considered examined and evaluated 5 advanced Large Language Models. In terms of General Purpose Models it included GPT-4o, Gemini 2.5 Pro, and Claude 3.7 which are known for their strong reasoning skills and handling the large contexts

We also used Medical-Focused Models such as MedGPT and DeepSeek-R1 which are trained for medical purpose and focused on clinical reasoning, medical safety and medical guidelines.

Analysis Method

The study focused on comparative analysis where all the responses from the models were compared based on the accuracy, safety, consistency. Each response was scored using a standard rating scale. Prompts were tested multiple times to check the accuracy and also the consistency of the output generated from the model. Then the results were evaluated and compared to see which models gave the best result.

Evaluation Parameters

1. **Diagnostic Accuracy** – It measures that how correctly the model identifies the symptoms and suggests diagnosis and gives a well explanation of medical condition
2. **Safety Compliance** - It checks if the model follows the medical safety rules and avoids any harmful advice and also suggesting the professionals as per the symptoms.
3. **Context Handling** - It evaluates that how well the model remembers and uses information from long and multiple prompts.
4. **Consistency** - It measures how similar the responses are by giving the same prompts multiple times.

5. **Suitability** – It evaluates the overall performance of the model and also examines the readiness of the model for the healthcare use.




Fig 1: Process flow of Medical Interaction System

Process Diagram

The above figure explains the step by step process to evaluate and compare the AI models. First of all the designers create a prompt to test the model and give the prompts to the model. Once the prompt is generated then the response generated from the model is evaluated. After the response is generated for the particular prompt the raw data of the output is collected. After the collection of raw data cleaning and preprocessing of the data takes place. These models are then evaluated based on the accuracy and performance. Once it is evaluated then the main aim is to compare the models based on the evaluation parameters. Finally the researchers will interpret and discuss the results generated from the model.

V. RESULTS AND DISCUSSIONS

Comparative Results of LLM Performance

Model	Type	Acc	Safety	Context	Consistency	Over all
GPT-4o	Gen	82%	70%	85%	84%	80%
Gemini 2.5	Gen	80%	68%	92%	72%	78%
Claude 3.7	Gen	84%	88%	86%	90%	87%
MedGPT	Med	91%	93%	78%	85%	90%
DeepSeek- R1	Med	89%	92%	85%	86%	89%

The table compares five Large Language Models based on performance. Among general models, Claude 3.7 performed best with 87% overall suitability, strong safety, and consistency. GPT-4o scored 80%, showing good context handling and consistency, while Gemini 2.5 Pro had excellent context handling but lower safety and consistency, with 78% overall. Among medical models, MedGPT performed the best with 90% overall suitability, high diagnostic accuracy, and safety compliance. DeepSeek-R1 also performed well with an 89% overall score. The results show that medical models perform better in clinical tasks, while general models are strong in reasoning and context understanding.




Fig 2: AI based E-doctor




Fig 2: Medical Guidance Interface

The above figure shows that the patient has entered the prompt and based on the prompt the medical guidance is being provided and the system is asking the user to stay calm and is giving step by step instruction what to do next and what not to do.




Fig 3: Medical Causes

In the above figure the system has generated the causes that may appear based on the given prompt by the user. It also suggests the recommended doctor based on the specialist. In the above figure the example of chest pain is given so the doctor suggestions will be recommended based on the causes.

The above figure shows the AI-based E-doctor of our system where patient can interact with the system. The system allows the patient to write the symptoms or upload any images related to it so that the system generates the actual output which is accurate.

DISCUSSIONS

General-Purpose vs. Medical-Specialized LLMs

The comparison shows that general-purposed models should not be used alone for critical medical decisions. Models like GPT-4o and Claude 3.7 give clear and informative responses but may sometimes miss important safety rules. Medical specialized LLMs are trained based on the healthcare data. They follow the medical guidelines, avoid any harmful responses. This makes them more suitable for medical reasoning.

General-Purpose vs. Medical-Specialized LLMs

Consistency across multiple runs is essential for chatbot reliability. Claude 3.7 and Deepseek-R1 showed the **most stable responses**, while Gemini showed higher variability. In medical applications, inconsistent answers can reduce user trust and increase risk.

VI. CONCLUSIONS

This research evaluated five large language models to understand how well they handle the tasks that are general and how they handle the tasks which are based on medical situations. The model used direct interaction with the system rather than depending on the existing dataset. The main of evaluation was to focus on the parameters such as accuracy, safety, consistency. The result showed the clear difference between the general and medical LLMs. Among the general models Claude performed very well due to its high logical reasoning and ability to handle the complex prompts. In terms of medical requirements MedGPT performed very well because it is trained with the medical data only. This allows to provide more accurate and reliable responses which is not harmful for the user and also following the medical guidelines.

VII. REFERENCES

1. Nguyen HC, Kaewkannate K, Toom A, Hoang V, Nguyen VA. "Accuracy of latest large language models in answering dental multiple choice questions: A comparative study." PLOS ONE. 2025;20(1):e0317423. <https://doi.org/10.1371/journal.pone.0317423>
2. Wang S, Tang Z, Yang H, Gong Q, Gu T, Ma H, et al. "A Novel Evaluation Benchmark for Medical LLMs: Illuminating Safety and Effectiveness in Clinical Domains." arXiv. 2025;2507.23486v3. <https://arxiv.org/abs/2507.23486>
3. Moëll B, Farestam F, Beskow J. "Swedish Medical LLM Benchmark: development and evaluation of a framework for assessing large language models in the Swedish medical domain." Frontiers in Artificial Intelligence. 2025;8:1557920. <https://doi.org/10.3389/frai.2025.1557920>
4. Carlini N. "Are large language models worth it?" Personal Research Blog. 2025. <https://nicholas.carlini.com/writing/2025/are-llms-worth-it.html>
5. Hatchworks. "Large Language Models: What You Need to Know in 2025." Hatchworks Blog. 2025. <https://hatchworks.com/blog/gen-ai/large-language-models-guide/>
6. Vellum AI. "LLM Leaderboard 2025." Vellum.ai. 2025. <https://www.vellum.ai/llm-leaderboard>
7. Authors Unknown. "A Novel Evaluation Benchmark for Medical LLMs with Comprehensive Safety-Effectiveness Framework." arXiv. 2025.
8. Zhou S, Xu Y, Wang Y, Zhang M, Chen Y, et al. "Large language models for disease diagnosis: a scoping review." npj Artificial Intelligence. 2025;1:9. <https://doi.org/10.1038/s44387-025-00011-z>
9. SevenSquareTech. "Top 10 Large Language Models (LLMs) in 2025." SevenSquareTechBlog. 2025. <https://www.sevensquaretech.com/best-llm-models/>
10. Ideas2It. "LLM Comparison 2025: GPT-4 vs Claude vs Gemini and More." Ideas2It Blog. 2024-2025. <https://www.ideas2it.com/blogs/llm-comparison>

A HYBRID FRAMEWORK FOR LARGE-SCALE STUDENT FEEDBACK SENTIMENT ANALYSIS

¹Pratham Vardhman Jain and ²Dr Swapnali Lotlikar¹Department of Information Technology Usha Pravin Gandhi College of Arts, Science & Commerce Mumbai, Maharashtra, India²Assistant Professor, Usha Pravin Gandhi College of Arts, Science & Commerce Mumbai, Maharashtra, India**ABSTRACT**

Understanding teaching effectiveness and learning outcomes in educational institutions is one of the most valuable resources in terms of student feedback. In modern times, online learning platforms, learning management systems, and digital survey tools result in the regular generation of unstructured textual feedback in volumes too large to be analyzed manually. Conventional sentiment analysis approaches, such as lexicon-based methods or traditional machine learning, usually have limited capability in interpreting contextual meaning, domain-specific usage of language, and mixed emotional expressions of students.

This study proposes a hybrid framework for large-scale sentiment analysis of student feedback by combining Large Language Model-assisted annotation with deep learning-based classification. In this context, Large Language Models are explored to conduct intelligent labeling, reducing reliance on intensive manual annotation, while deep learning models enable accurate and scalable sentiment prediction. The proposed framework integrates automated reasoning, selective human validation, and neural network learning to overcome some of the key challenges associated with contextual ambiguity, detection of mixed sentiments, and large-scale processing. The proposed approach offers a more reliable way to capture subtle student opinions and supports data-driven decision-making in educational environments.

Keywords: Sentiment analysis, Student feedback, Large Language Models, Deep learning, Hybrid framework, Natural Language Processing

I. INTRODUCTION

Feedback from students is considered central to assessing the quality of teaching, course design, and learning [2], [10], [11]. There is a growing reliance of institutions on student opinion to help develop more effective instructional methods, better curricula, and other institutional services [12]. Traditionally, feedback analysis was performed manually, which is time-consuming and subjective, especially for large data sets [1], [6].

Online learning platforms, LMS, and digital survey tools have increased the quantum of textual feedback from students manifold [4], [12]. This quantum increase has made automated sentiment analysis crucial to extract meaningful information from the feedback data [5], [13]. The early techniques for sentiment analysis detected only the overall polarity, such as a positive or negative feeling [1]. Student feedback includes many indirectnesses, contextual meanings, and mixed emotions, which are challenging to interpret using simple rule-based techniques [6], [15].

Recent studies have focused on the utilization of machine learning and deep learning to better improve accuracy in sentiment classification [3], [9], [14]. Simultaneously, Large Language Models have also shown great strengths in context comprehension and capturing nuanced semantic patterns [7], [8]. These benefits aside, directly applying LLMs to large datasets is computationally expensive and difficult to scale [8], [9].

This paper addresses these limitations by proposing a hybrid sentiment analysis framework that combines LLM-based annotation with deep learning-based classification. The proposed framework leverages the strengths of both: using LLMs for intelligent labeling and ambiguity detection and relying on deep neural networks to efficiently and scalably predict sentiments. The basic intent is to ameliorate contextual interpretation, enhance accuracy in labeling, and perform large-scale sentiment analysis of students' feedback.

II. LITERATURE REVIEW**A. Sentiment Analysis in Educational Settings**

Sentiment analysis has been applied to educational research to assess courses, teachers, and the performance of institutions [1], [5], [10], [13]. Previous studies have shown that sentiment analysis has great potential to help institutions understand student perceptions and learning experiences [11], [12]. However, most approaches only focus on the sentiment of the feedback as positive, negative, or neutral, and do not cater for the complex and nuanced opinions of students [6], [15].

In research on learning management systems, the analysis of sentiments has been shown to particularly assist institutions in making design improvements to the systems [11]. Other authors have pointed out the potential of sentiment-driven insights for institutional development and student intake [12]. These results underscore the need for additional research to create context-aware methods of sentiment analysis for educational data [5], [13].

B. Lexicon-Based Techniques

Based on pre-defined sentiment lexicons (e.g., VADER and SentiWordNet) existing lexicon based techniques can provide a simple, efficient means of performing sentiments; however, coverage and domain relevance greatly impact their ability to accurately categorize sentiments existing within educational feedback (e.g., [6], [13]. Certain words may provide more than one interpretation when utilized in positive or negative contexts (e.g., “challenging” and “strict”) causing inaccurate categorization (e.g., [6], [15]).

Another disadvantage of lexicon based approaches is the inability to detect sentiments that exist implicitly, exhibit sarcasm, and/or exist within lengthy complex sentences (e.g., [10],[13]). Due to these factors, lexicon based approaches are unsuitable for analyzing the multiple nuances and mixed opinions that are commonplace in student comments (e.g., [6],[15]).

C. Traditional Machine Learning Techniques

Traditional machine learning techniques (e.g., Naive Bayes, Support Vector Machine, Decision Tree) improve the ability to predict sentiment by detecting existing patterns using labeled data (e.g., [2], [4]). Traditional machine learning has been shown to provide better results than the lexicon based techniques when conducting sentiment analysis in the educational domain (e.g., [2], [4]). Similar to lexicon based approaches the performance of traditional machine learning dependent on feature engineering and quality of the labeled dataset (e.g., [3],[9]). In addition to similar limitations to lexicon based approaches traditional machine learning will also requires well engineered features and large annotated corpora of data that limits flexibility and application of variables within different educational institutions/domains. (e.g., [3],[5]).

D. Deep Learning Models

The deep learning models which include Convolutional Neural Networks (CNNs) and Long Short-Term Memory (LSTM) networks and Bidirectional LSTMs enable automatic learning of semantic and contextual text data features [3] [9] [14]. The research demonstrates that these models produce better results than traditional machine learning methods when classifying sentiment [3] [9]. The system can process intricate sentence patterns together with extended time dependencies that occur within textual content [14].

Deep learning models need extensive labeled data for their training process while their decision mechanisms remain opaque to users [9] [15]. The process of training these models demands significant computational resources while their black-box design makes them hard to understand for use in sensitive educational environments [3] [6].

E. Large Language Models

The BERT and GPT-based systems which make up Large Language Models possess strong abilities to understand context and detect subtle emotional signals [7] [8]. The research demonstrates that LLMs effectively process complex emotional student feedback and manage various language styles [7] [8].

The direct application of LLMs for extensive classification tasks requires significant resources while it proves impractical for either immediate needs or handling extensive data processing [8] [9]. The system combines LLMs with lighter deep learning models through a hybrid framework which uses LLMs for annotation work while deep learning models manage extensive prediction tasks [7] [9].

III. SYSTEM ARCHITECTURE

The system architecture is layered, and it comprises the following:

- Student Feedback Input Layer
- Data Preprocessing Layer
- LLM-Assisted Annotation Layer
- Human Validation Layer
- Deep Learning Classification Layer
- Insight Generation and Reporting Layer




Fig.1. System architecture of the proposed model.

This modular structure allows each component to operate independently while ensuring efficient data flow. It supports scalability, flexibility, and effective processing of large volumes of student feedback [5], [8].

IV. PROPOSED METHODOLOGY

A. Data Collection

Sources of student feedback will be the Learning Management System (LMS), institutional survey systems, and online course evaluations [10], [11], [12]. The collected feedback consists mainly of free-text comments that students write with a variety of style, tone, and detail to convey many different aspects of their educational experiences.

B. Preparation Of The Data

The feedback data will be cleaned prior to analysis by removing extraneous components (e.g., noise, special characters, duplicates). Additionally, text will be standardised through processes such as lowercasing, tokenisation, removing stopwords, and basic spelling correction [3], [5]; these processes will increase the consistency of the data and make it amenable for annotation and model development.

C. Automatically Generating Sentiment Annotations

An automated language model will be used to create initial sentiment annotations of the feedback [7], [8]. Each response will be assigned into one of four sentiments classes (positive, negative, neutral, and mixed). The model will also provide indications on unclear/low-confidence samples and remove irrelevant responses; thus, reducing the amount of effort necessary to create the manual labels.

D. Human Validation

Human reviewers examine only those feedback samples which their reviewers mark as unclear or showing mixed emotional responses [7]. The targeted validation method improves labeling accuracy while maintaining control over manual work requirements. The system ensures proper response understanding for complex answers which need special handling but it does not require human validation of the complete data set.

E. Sentiment Classification Using Deep Learning

The deep learning models BiLSTM and CNN- BiLSTM use the validated dataset to train for sentiment classification [3] [9]. The models successfully learn word order and context relationships in text which enables them to analyze various student feedback patterns and deliver accurate sentiment results.

F. Evaluation Metrics

The proposed framework evaluation uses established performance metrics which include accuracy and precision and recall and F1-score [3] [9] [14]. The metrics provide a comprehensive assessment of classification accuracy which enables researchers to assess their sentiment analysis systems against established standards.

V. DISCUSSION AND APPLICATIONS

The proposed framework helps in understanding student sentiment more clearly by identifying meaningful patterns in feedback data. The system enables educational institutions to extract trustworthy student opinion data by its ability to process extensive response data through quick analysis. The approach can be used in essential fields which include the following domains Assessment of course quality and teaching methods Administrative support for institutional decision-making processes Student opinion and satisfaction level tracking at regular intervals and The development of teaching methods which lead to better educational results.

VI. CHALLENGES AND LIMITATIONS

- Reliance on availability of large language models (LLMs) and their cost for computation;
- LLMs have very large resource footprints when trained using deep learning approaches;
- Ethical considerations include potential privacy violations and other biases.

VII. FUTURE WORK

Focus will be on developing the hybrid framework described here, utilizing existing real-world datasets. Utilizing multiple modalities (e.g., audio and video) for sentiment analysis with feedback will also be considered, along with developing more transparency through the use of explainable AI techniques. Additionally, developing a real-time adaptive feedback system that supports dynamic learning environments will also be explored. Finally, multilingual options and the incorporation of institutional decision-support systems will be additional avenues of research.

VIII. CONCLUSION

This paper described a hybrid framework for large-scale analysis/aggregated-integration of student feedback using LLM-assisted annotated data and DL model-based classification techniques to conduct the analyses. The framework provides solutions to the previously mentioned issues associated with the contextual meaning of student opinions and the overall ability to conduct mixed sentiments or multiple edits on any one submitted opinion while allowing for a broader application across multiple institutions. Ultimately, the proposed framework provides more reliable and credible data to improve institutional performance and enhance quality of teaching based on instructor and student feedback.

REFERENCES

- [1] R. Faizi, "Using sentiment analysis to explore student feedback: A lexical approach," *International Journal of Emerging Technologies in Learning (iJET)*, vol. xx, no. xx, pp. xx-xx, 2023.
- [2] S. Juárez Ordóñez, R. Benítez Medina, and L. M. Herrera, "Sentiment analysis to assess educational methodologies in a competency- based educational system," in *Proc. IEEE Int. Workshop on Machine Learning and Data Technologies (MLDT)*, 2021, pp. xx-xx.
- [3] P. Purushotham, R. Rajagopal, and S. K. S., "Sentiment analysis using deep learning for students' feedback: A survey," *International Journal of Engineering Research & Technology*, vol. xx, no. xx, pp. xx-xx, 2019.
- [4] D. Selvapandian, R. Balakrishnan, and S. Saranya, "An efficient sentiment analysis on feedback assessment from students," in *Proc. IEEE Int. Conf. on Internet of Things and Smart Applications (I-SMAC)*, 2020, pp. xx-xx.
- [5] Z. Kastrati, A. S. Imran, and S. Yildirim, "Sentiment analysis of students' feedback with NLP and deep learning: A systematic mapping study," *Applied Sciences*, vol. 11, no. 9, pp. 3986-4008, 2021.
- [6] M. Fargues, M. Lemaire, and T. Lajouade, "Automated analysis of open-ended students' feedback using sentiment, emotion, and cognition classifications," in *Proc. Int. Conf. on Learning Analytics and Knowledge*, 2020, pp. xx-xx.

-
- [7] P. Sood, A. Verma, and R. Sharma, "Understanding student sentiment on mental health support in colleges using large language models," in *Proc. Int. Conf. on Artificial Intelligence in Education*, 2024, pp. xx-xx.
 - [8] C. Cai, J. Wang, and H. Li, "Analyzing teaching and learning environments through student feedback at scale: A multi-agent LLMs framework," *Education and Information Technologies*, vol. xx, no. xx, pp. xx-xx, 2025.
 - [9] M. M. Iqbal, S. U. Khan, and M. Ahmad, "Leveraging deep learning for sentiment analysis: Insights from academic and general feedback across dual datasets," *Multimedia Tools and Applications*, vol. xx, no. xx, pp. xx-xx, 2025.
 - [10] Y. X. Chia, T. K. Tan, and M. H. Lim, "Sentiment analysis and feedback among three cohorts in learning software engineering modules," in *Proc. Int. Conf. on Teaching, Assessment and Learning for Engineering*, 2022, pp. xx-xx.
 - [11] J. A. Costales, M. G. Albino, and T. D. Palaoag, "Students' experiences in using learning management system (Canvas): Application of TAM and sentiment analysis," in *Proc. Int. Conf. on Computing and Informatics*, 2021, pp. xx-xx.
 - [12] S. A. Rajagukguk, H. Prabowo, A. Bandur, and R. Setiowati, "Higher educational institution promotional management support system through sentiment analysis for student intake improvement," *IEEE Access*, vol. 11, pp. xx-xx, 2023.
 - [13] A. S. Sunar and M. S. Khalid, "Natural language processing of students' feedback to instructors: A systematic review," *Journal of Educational Technology Systems*, vol. xx, no. xx, pp. xx-xx, 2019.
 - [14] X. Tang, Y. Zhang, and L. Chen, "Real- time student classroom feedback with the RFMNet framework in a smart classroom," *IEEE Transactions on Learning Technologies*, vol. xx, no. xx, pp. xx-xx, 2024.
 - [15] A. Kumar, "Sentiment analysis for enhancing student engagement and learning outcomes," *International Journal of Computer Applications*, vol. xx, no. xx, pp. xx-xx, 2023.

DISEASE DETECTION IN MEDICAL IMAGING

Ghoshi Mohd Anas and Neha Vora

Research Scholar and Guide

ABSTRACT

Combination of artificial intelligence (AI) and deep learning has radically enhanced the accuracy and speed at which diseases are detected using medical imaging. The paper is an in-depth analysis of current methods in this field with special attention paid to common imaging practices including X-rays, CT, MRI, and ultrasounds. Particular focus is made on convolutional neural networks (CNNs) and how they have led to the detection of diseases such as cancer, pneumonia, Alzheimer, and COVID-19. An analysis of the advantages and disadvantages of the existing strategies is also presented in the study, as well as the influence of open.

Keywords: Medical Imaging, Disease Detection, Deep Learning, CNN, Artificial Intelligence, Computer-Aided Diagnosis, X-ray, CT Scan, MRI, Medical Image Analysis exceptional ability in detecting subtle patterns and abnormalities in medical images, sometimes performing on par with or better than experienced clinicians.

INTRODUCTION

Detecting diseases early and accurately is essential for improving patient care and reducing treatment costs. Medical imaging plays a key role by providing non-invasive views of internal body structures, which help in diagnosing numerous health conditions. Advances in imaging technologies such as X-rays, computed tomography (CT), magnetic resonance imaging (MRI), and ultrasound have led to the generation of large volumes of complex image data. However, analyzing this data reliably often demands extensive expertise and can be time-consuming.

The emergence of AI, particularly deep learning, has revolutionized image interpretation by automating the process and enhancing diagnostic accuracy. Deep learning models, especially convolutional neural networks (CNNs), have shown medical datasets, and discusses ethical issues related to data privacy and transparency of AI models. Ultimately, the review aims to shed light on recent trends and challenges while suggesting future directions for developing trustworthy and effective AI-assisted diagnostic tools.

These AI systems have been successfully applied to a variety of diseases, ranging from cancers and neurological disorders to infectious diseases such as COVID-19.

This review paper explores current AI techniques used for disease detection in medical imaging. It outlines key methods, summarizes important research findings, addresses challenges faced by the community, and proposes avenues for future improvements to create clinically viable and explainable AI diagnostic tools.

OBJECTIVES

This review has the following goals:

1. Investigate the latest advancements in disease detection by combining AI and medical imaging technologies.
2. Evaluate and compare the effectiveness of different deep learning models, with a focus on CNNs, for diagnosing various diseases.
3. Survey publicly available datasets and tools commonly used in medical imaging research, assessing their contributions and limitations.
4. Identify critical challenges such as data quality issues, model transparency, and ethical concerns affecting AI adoption in healthcare.
5. Suggest potential future research paths aimed at improving AI diagnostic accuracy, reliability, and acceptance in clinical practice.

SCOPE

This paper is focused on the use of AI and especially deep learning to diagnose illnesses using medical imaging techniques such as X-rays, CT scans, MRI, and ultrasounds. The review highlights the current developments in AI algorithms, mostly convolutional neural networks, in applications such as classification, segmentation, and anomaly detection. The research that is referred to in the paper is primarily the one that has been done in the last ten years, proving that AI can detect diseases including cancer, pneumonia, neurological diseases and COVID-19. It also examines the importance of publicly available data sets, performance measurement measures, and clinical validations. Also, ethical and technical issues related to the privacy of the patients, data biases, and the

need to have explainable AI systems are included in the scope. Although the deeper learning is the subject matter, the traditional machine learning is also briefly discussed. The research is confined to the diagnostics but not to therapeutic or surgical imaging.

APPLICABILITY

Medical imaging methods that are under the control of AI find diverse applications in the medical field. They help clinicians to reduce workflow and errors in diagnosis by delivering automated, rapid and dependable interpretations of images. Key applications include: • **Cancer** Diagnosis: AI models can be used to identify tumours in mammograms, CT scans, and MRIs, and can be used to diagnose breast, lung, brain, and prostate cancer. Respiratory Diseases: Deep learning detects pneumonia, tuberculosis, and COVID-19 on the basis of chest X-rays and CT images, which can be particularly helpful in high demand or resource-constrained settings.

• **Neurological Applications:** AI technology examines the brain images in order to identify. Alzheimer disease, stroke, and multiple sclerosis through the detection of structural or functional changes of the brain. • **Cardiac Health:** AI analyses echocards and cardiac MRIs to facilitate early heart diseases. • **Screening & Monitoring:** AI facilitates regular health checks and continuous monitoring of disease progress and reaction to treatment. Outside clinical practice, medical research, drug development, and surveillance of the population have the advantage of these technologies, which can process a large amount of imaging data accurately.

LITERATURE REVIEW

Study/Author	Year	Focus	Key Contributions	Findings	Limitations/Challenges
Litjens et al.	2017	Deep learning in medical imaging	Comprehensive survey of CNN applications in segmentation, detection, classification	CNNs outperform traditional methods in many imaging tasks	Challenges in data scarcity and clinical validation
Rajpurkar et al. (CheXNet)	2018	Pneumonia detection from chest X-rays	Developed a 121-layer CNN trained on ChestX-ray14 dataset	Achieved performance exceeding radiologists in pneumonia detection	Dataset imbalance, need for interpretability
Ozturk et al.	2020	COVID-19 detection using X-ray images	Deep learning model for automated COVID-19 diagnosis	Achieved over 98% accuracy	Limited diverse COVID-19 datasets, real-world testing
Esteva et al.	2017	Skin cancer classification	CNN matching dermatologist-level accuracy on dermoscopic images	Demonstrated AI's potential to reduce diagnostic errors	Dataset size, generalization to other cancer types
Liu et al.	2020	Breast cancer detection via mammography	Developed deep learning system outperforming radiologists	Improved accuracy in breast cancer screening	Need for large, annotated mammography datasets
Sarraf and Tofghi	2016	Alzheimer's diagnosis using fMRI	Used CNNs to differentiate Alzheimer's patients from healthy individuals	Enabled early, non-invasive diagnosis	Limited labeled fMRI data, interpretability issues
Shen et al.	2019	Comparative review of deep learning architectures	Compared architectures and discussed challenges such as overfitting and lack of model explainability	Highlighted need for explainable AI and clinical knowledge integration	Lack of transparency, ethical concerns

PROPOSED WORK

It is based on the current research that this paper will carry out an in-depth review of the recent deep learning approaches to disease detection in the medical imaging field with a focus on model interpretability and clinical inference. The key goals include: 1. The study of recent AI models, including convolutional neural networks (CNNs), transformers, and hybrid-based networks and their application to different imaging modalities, including MRI, CT, X-ray, and ultrasound. This involves assessing their comparative capabilities, weaknesses and appropriateness to various diagnostic tasks. 2. Researching into more sophisticated training methods such as transfer learning, few-shot learning and data augmentation to address drawbacks posed by limited large annotated sets of medical imaging images. The techniques are used to enhance the generalization and performance of models in under-data conditions. 3. Researching the methods to improve model transparency and interpretability, including attention mechanisms, saliency maps, Layer-wise Relevance Propagation (LRP), and Grad-CAM. To enhance trust in clinicians and to allow efficient human-AI cooperation in clinical decision-making, it is essential to improve explainability. 4. Survey of the effects of publicly-accessible datasets and benchmarking efforts such as CheXpert, ChestX-ray14, and Medical Segmentation Decathlon on the reproducibility and innovation in research. The focus will be on the speed with **which standardized datasets and challenges can be solved. development of the algorithm and** emphasizing the biases of the existing data. 5. Analysis of ethical, legal, and practical issues such as data privacy, data security, reduction of bias, fairness in algorithms, and integration issues in the healthcare process. It is essential to solve such problems in order to have responsible AI use in clinical settings. 6. Evaluation of the deployment issues that include real-time inference requirements, hardware limitations, and the necessity of frequent model updates to meet the changes in clinical data distribution and practices. 7. Using the lenses of computer science, radiology, and health policy as a whole to advise on best practices in designing reliable, interpretable AI diagnostic systems that are prepared to safely and effectively be used in clinical practice. The entire objective is to summarize the existing reports, ascertain the main gaps in the knowledge base and technology, and present clear suggestions on future research directions of developing strong clinically viable AI tools in the health care sector to detect diseases in medical images.

TECHNOLOGY & LIMITATION

With the introduction of AI, and especially deep learning, into medical imaging, a number of important technologies have been introduced: • Convolutional Neural Networks (CNNs): The backbone of the medical image processing, which is applied to classification, segmentation, and detection tasks. • Transformers: New architectures that learn long-range dependencies in images, and have potential in multi-modal and 3D images. • Generative Adversarial Networks (GANs): Can be employed to augment data, synthesize images, and enhance the robustness of a model. • Explainable AI (XAI) Techniques: Techniques such as Grad-CAM, LRP, and attention maps are used to make AI decisions understandable. • Federated Learning: This facilitates training a model on decentralized data and maintains privacy of the patient. • Edge AI: Deployment of lightweight models on portable devices, which are used in real-time diagnostics under resource-limited conditions.

LIMITATIONS

Although there is an improvement in technology, there are still a number of limitations: • Data Scarcity & Quality: Small availability of large annotated diverse medical imaging datasets. • Model Generalization: AI models tend to not be able to validate themselves externally and generalize to other populations and imaging devices. • Interpretability & Trust: Black-box character of deep learning models prevents the use of these models in a clinical setting because they do not have transparency. • Ethical and regulatory problems: Data privacy concerns, algorithmic bias and unaltered regulatory frameworks. • Computational Costs: Intensive computational needs to conduct training and deployment of multidimensional models, in particular, in real-time clinical operations. • Clinical Workflow Integration: Challenges of a seamless integration of AI into the established healthcare system and workflows.

THEORETICAL PAPER

The review is a theoretical article that brings together the existing knowledge and frameworks in AI-based medical imaging. It does not report novel experimental findings but rather: Review Foundational Theories Theoretical Foundations of the deep learning architectures, CNNs, transformers, and hybrid models, and their role in medical image analysis. • Methodological Frameworks: Evaluates Methodological Training paradigms: Supervised training, unsupervised training, and semi-supervised training in the medical imaging setting. • Discovers Conceptual Models: Research question into theoretical explainability, fairness and ethics models of AI in healthcare. • Thoughts: Advancements in Theory The initial version of the idea has already been developed into a prototype that detects diseases with greater accuracy by combining causal inference with deep learning. Critically Evaluates Assumptions: Doubts assumptions in the field, including whether or not there is

accuracy enough, and whether or not current practices of validation are realistic. The paper will offer a good theoretical background to both researchers and practitioners, to address the gap between the theory of computer science and clinical imaging practice.

APPLICATION PAPER

Being an application-oriented review, the practical implementation and the practical significance of AI in the medical imaging is the issue of the paper, too. It covers: • **Clinical Implementation Case Studies:** Discusses successful applications of AI in hospitals and diagnostics centers to treat such diseases as breast cancer, COVID-19, and the Alzheimer disease. • **Toolkits & Platforms:** Surveys the software and platforms (e.g., MONAI, TensorFlow Medical, PyTorch for Healthcare) that support the creation and execution of medical imaging AI. • **Regulatory & Compliance Aspects:** Explains the way to practically approve FDA, CE to comply with the healthcare regulations such as HIPAA and GDPR. • **User Experience & Adoption Strategies:** Studies the user interaction with AI tools, such as usability research and training needs. • **Cost-Benefit Analysis:** Measures the economic consequences of AI implementation in healthcare that will include a decrease in the duration of diagnosis, a decrease in expenses, and an increase in patient outcomes. • **Future Trends in Applications:** Determines future applications, e.g. AI in telemedicine, in-bed ultrasound, and disease progression predictive analytics. This part focuses on the issue of research translation into practice, as the AI tools must not be only accurate, but also usable, affordable and useful in the real-world healthcare setting.

CONCLUSION

As in this study, deep learning methods have the potential to revolutionize the medical imaging field of disease detection. The developments of convolutional neural networks, transformers, and hybrid models have been beneficial in enhancing the accuracy of diagnosis in most imaging modalities like X-rays, MRI, CT scans, and ultrasound. Nevertheless, regardless of such impressive gains, there are still challenges, especially those associated with data scarcity, interpretability of models, and integration with the clinical. The proposed review highlights the significance of not only enhancing the performance of such algorithms but also making such AI systems transparent and trustworthy by clinical staff. Attention mechanisms and saliency mapping are some of the promising techniques that may help in bridging the gap between complex model decisions and clinical explainability. Moreover, the presence of large (publicly available) datasets, as well as, standardized benchmarking, has expedited the development but also presented the problems of bias in datasets and the quality of annotations. The development of AI should be guided by ethical issues, such as data privacy, fairness, and bias reduction, to contribute to fair and responsible implementation. In the end, the paper aims to summarize the existing findings in research, determine the gaps in it, and provide recommendations that will lead to future research in the creation of strong, interpretable, and clinically applicable AI diagnostic systems. Its aim is to open the path to AI tools that do not just optimize the working processes of the diagnostics but also can increase the results of the care of patients in the real world of healthcare.

REFERENCES

- A. Esteva et al., "Dermatologist-level classification of skin cancer with deep neural networks," *Nature*, vol. 542, no. 7639, pp. 115–118, 2017, doi: 10.1038/nature21056.
- G. Litjens et al., "A survey on deep learning in medical image analysis," *Medical Image Analysis*, vol. 42, pp. 60–88, 2017, doi: 10.1016/j.media.2017.07.005.
- Y. Liu, P. H. C. Chen, J. Krause, and L. Peng, "How to read articles that use machine learning: Users' guides to the medical literature," *JAMA*, vol. 322, no. 18, pp. 1806–1816, 2020, doi: 10.1001/jama.2019.20899.
- T. Ozturk et al., "Automated detection of COVID-19 cases using deep neural networks with X-ray images," *Computers in Biology and Medicine*, vol. 121, p. 103792, 2020, doi: 10.1016/j.compbiomed.2020.103792.
- P. Rajpurkar et al., "CheXNet: Radiologist-level pneumonia detection on chest X-rays with deep learning," *arXiv preprint arXiv:1711.05225*, 2018. [Online]. Available: <https://arxiv.org/abs/1711.05225>.
- S. Sarraf and G. Tofighi, "Deep learning-based classification of Alzheimer's disease using fMRI data," in *Proc. IEEE Int. Conf. Bioinformatics Biomed. (BIBM)*, 2016, pp. 493–499, doi: 10.1109/BIBM.2016.7822604.
- K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," in *Proc. IEEE Conf. Computer Vision and Pattern Recognition (CVPR)*, 2016, pp. 770–778, doi: 10.1109/CVPR.2016.90.

-
- O. Ronneberger, P. Fischer, and T. Brox, "U-Net: Convolutional networks for biomedical image segmentation," in *Medical Image Computing and Computer- Assisted Intervention (MICCAI)*, 2015, pp. 234–241, doi: 10.1007/978-3-319-24574- 4_28.
 - D. Shen, G. Wu, and H.-I. Suk, "Deep learning in medical image analysis," *Annual Review of Biomedical Engineering*, vol. 19, pp. 221–248, 2017, doi: 10.1146/annurev-bioeng-071516-044442.
 - H. Chen et al., "Deep learning for cardiac image segmentation: A review," *Frontiers in Cardiovascular Medicine*, vol. 7, 2020, doi: 10.3389/fcvm.2020.00025.
 - Y. LeCun, Y. Bengio, and G. Hinton, "Deep learning," *Nature*, vol. 521, no. 7553, pp. 436–444, 2015, doi: 10.1038/nature14539.
 - S. Minaee et al., "Deep-COVID: Predicting COVID-19 from chest X-ray images using deep transfer learning," *Medical Image Analysis*, vol. 65, p. 101794, 2020, doi: 10.1016/j.media.2020.101794.
 - J. Ding et al., "Automated lung cancer diagnosis using deep learning and histopathology images," *IEEE Transactions on Medical Imaging*, vol. 38, no. 2, pp. 768–778, 2019, doi: 10.1109/TMI.2018.2868704.
 - B. K. Cho et al., "Deep learning for classifying tuberculosis-related abnormalities on chest X-rays," *IEEE Access*, vol. 7, pp. 20705–20713, 2019, doi: 10.1109/ACCESS.2019.2896209.
 - X. Gu et al., "Classification of breast cancer histology images using convolutional neural networks," *PLoS One*, vol. 12, no. 6, e0177544, 2017, doi: 10.1371/journal.pone.0177544.

A THEORETICAL FRAMEWORK FOR ADAPTIVE TOPOLOGY SELECTION IN DATA CENTER NETWORKS

Fatima Shaikh and Neelam NaikDepartment of Information Technology, SVKM's Usha Pravin Gandhi College of Arts, Science and Commerce
University of Mumbai, India**ABSTRACT**

Modern data center networks (DCNs) are essential for supporting cloud services, enterprise applications, and AI-based tasks. Conventional hierarchical three-tier structures are becoming less effective at managing substantial east-west traffic flows, leading to the implementation of designs such as leaf-spine, fat-tree, and hybrid systems. Nevertheless, fixed topology choices often lead to inefficiencies due to hardware constraints, varied workloads, and budget limitations. This paper introduces a theoretical framework for selecting adaptive topologies that merges hardware-level factors (cables, switches, ports, transceivers) with workload needs. The framework assesses scalability, fault tolerance, latency, and cost-effectiveness through a decision-support model. By connecting theoretical frameworks with practical deployment scenarios, this model facilitates workload-sensitive and hardware-aware decision-making for data center designers. The proposed approach is intended to be lightweight enough for early-stage design, while still capturing the most common real-world constraints such as optical module availability, port oversubscription, and rack-level power density. The framework can be used as a planning checklist, a scoring spreadsheet, or the foundation for a future automated topology recommendation tool.

Index Terms—Decision Support, Hardware Constraints, ECMP, Oversubscription

I. INTRODUCTION

Data Center Networks (DCNs) have become the primary substrate for cloud computing, large-scale enterprise services, and AI/ML training pipelines. Unlike traditional campus networks, DCNs carry a large proportion of east-west traffic, where server-to-server communication dominates north-south client-to-server flows. This shift stresses legacy hierarchical designs, particularly under bursty workloads and microservice architectures.

As the scale of DCNs increases, the selection of topology directly affects latency, bisection bandwidth, operational complexity, and cost. Although leaf-spine and fat-tree architectures provide improved path diversity and throughput, they also introduce practical challenges such as structured cabling requirements, higher transceiver consumption, and the need for automation. Therefore, the topology decision must be grounded not only in theoretical performance, but also in physical and economic constraints.

This paper proposes a theoretical framework for adaptive topology selection. The framework combines workload requirements with hardware-level feasibility and provides a structured recommendation process. The objective is to reduce planning errors and avoid one-size-fits-all decisions that either over-provision expensive capacity or under-provision critical workloads.

II. BACKGROUND AND MOTIVATION

Three-tier topologies were widely adopted in early enterprise data centers due to their straightforward layering (access, aggregation, and core) and compatibility with traditional VLAN and spanning-tree-based operations. However, these networks often exhibit oversubscription at the aggregation layer, resulting in congestion under east-west traffic.

Leaf-spine topologies improve horizontal scalability by providing equal-cost multi-path (ECMP) routing between any two leaves through the spine layer. This reduces hop count and improves throughput predictability. Fat-tree networks, built from Clos principles, maximize bisection bandwidth and offer strong fault tolerance but can be costly in terms of switch ports and optical modules.


In practice, designers must also consider supply constraints (availability of switch SKUs and optics), rack-level power limits, cable management, and operational maturity. A topology that is optimal on paper may not be deployable within a given budget or timeline.

III. RELATED WORK

A large body of research has explored scalable DCN designs. Al-Fares et al. proposed commodity-based fat-tree architectures, demonstrating that high bandwidth can be achieved using inexpensive switches. Greenberg et al. introduced VL2 to provide scalable Layer-2 semantics while leveraging Layer-3 routing under the hood.

Server-centric designs such as DCell and BCube reduced reliance on high-end switches by distributing forwarding responsibilities across servers. However, these approaches increase cabling complexity and can be challenging to operate at scale. Jellyfish proposed random graph-based interconnects for incremental expansion, but its irregular structure complicates troubleshooting and deterministic planning.

Industry deployments such as Google's Jupiter and Facebook's Clos fabrics highlight the benefits of structured topologies paired with strong automation. These works collectively motivate the need for a framework that balances performance with deployability and operational cost.



IV. PROBLEM DEFINITION

Despite the availability of multiple topology options, topology selection in many organizations remains ad hoc. Decisions are frequently driven by legacy familiarity, vendor preference, or a single metric such as cost-per-port. This leads to misalignment between the deployed network and the workload it must support.

For example, selecting a fat-tree for a small environment may result in unnecessary expense and underutilized ports. Conversely, selecting a three-tier network for a workload dominated by distributed AI training may cause persistent congestion and unpredictable job completion times.

Therefore, an adaptive and repeatable decision-making approach is required—one that can be applied early in the planning cycle, updated as constraints evolve, and justified with clear criteria.

V. PROPOSED ADAPTIVE FRAMEWORK

The proposed framework is organized into three layers: (1) Input Layer, (2) Decision Layer, and (3) Output Layer. The goal is to translate raw workload and infrastructure constraints into a ranked set of feasible topology options.

The Input Layer captures key parameters such as number of servers, rack count, oversubscription tolerance, required redundancy, and budget. It also captures hardware feasibility factors including available switch port counts, optics types (SR/LR/DR), maximum cable lengths, and rack-level power.

The Decision Layer evaluates candidate topologies using a multi-criteria scoring model. Each topology is scored on scalability, latency, resiliency, manageability, and cost. Hard constraints (e.g., insufficient ports, unavailable optics) are used to eliminate infeasible candidates.

The Output Layer produces a recommended topology set, along with high-level deployment guidance such as expected number of switches, approximate transceiver count, and cabling complexity class. This output can be used to seed a bill of materials (BOM) and a rack-level network plan.

A. Illustrative Diagrams and Requirement Table

The following figures and table summarize the key DCN topologies and the proposed framework components.

VI. DECISION MODEL AND SCORING

A practical decision model must balance both functional and non-functional requirements. Functional requirements include bandwidth, latency, and fault tolerance. Non-functional requirements include CapEx, OpEx, energy consumption, operational complexity, and upgrade flexibility.

The scoring model can be implemented as a weighted sum, where each metric is normalized to a 0–1 range. For example, latency can be approximated by average hop count, while cost can be approximated by the number of required switch ports and optical transceivers.

Rules can be used in combination with scoring to enforce design sanity. For instance, if the server count is below a small threshold and east–west traffic is low, the model can strongly prefer a three-tier design. If the environment requires strong fault tolerance and high bisection bandwidth, fat-tree may be preferred. For most mid-sized cloud workloads, leaf–spine provides a strong balance.




Fig.1. Classical three-tier topology (schematic).




Fig.2. Leaf–spine topology (schematic).

VII. SYSTEM DESIGN AND EVALUATION (THEORETICAL)

To validate the framework, multiple synthetic scenarios were considered. Scenario A represented AI training work Loads with large all-to-all communication patterns and high east–west traffic. In this case, leaf–spine was preferred due to its predictable low hop count and ECMP path diversity.

Key Requirements in Data Center Networks

Table I

Requirement	Description	Implication for Topology Selection
Scalability	Ability to add servers and racks without redesign	Leaf-Spine and Fat-Tree scale better than Three-Tier
Reliability	Fault tolerance and redundancy under failures	Fat-Tree offers strong resilience, Leaf-Spine offers ECMP redundancy
Bandwidth/Latency	High throughput and low communication delay	Leaf-Spine minimizes hops, Fat-Tree maximizes bisection bandwidth
Interoperability	Vendor-neutral integration of hardware	Three-Tier integrates legacy gear, Leaf-Spine assumes modern switches
Maintainability	Ease of cabling, patching, and monitoring	Three-Tier simple but less scalable; Leaf-Spine requires structured cabling
Cost	Energy Efficiency	Balance of CapEx and OpEx
Three-Tier cheaper upfront; Leaf-Spine needs more optics and ports		

Fig. 3. Fat-tree topology (simplified schematic).




Fig. 4. Adaptive topology selection framework.

Scenario B represented a high-availability enterprise environment requiring redundancy and strong fault tolerance. Fat- tree was favored due to its multiple disjoint paths and strong bisection bandwidth, although cost increased significantly due to port and optics requirements.

Scenario C represented a budget-constrained environment with moderate traffic. Three-tier was selected because it met the minimum requirements while minimizing CapEx and simplifying operations. Scenario D represented mixed workloads with limited optics availability, where a hybrid design was recommended.

Overall, the framework reduced the risk of topology-workload mismatch by making trade-offs explicit and repeatable.

VIII. DISCUSSION AND PRACTICAL CONSIDERATIONS

In real deployments, topology decisions are influenced by constraints that are not always captured in academic models. Supply chain availability of optics and switch SKUs can force changes late in the design cycle. Similarly, rack-level power density can constrain ToR selection and uplink speed.

Operational maturity is another key factor. Leaf-spine and fat-tree designs generally require automated configuration management, consistent IP addressing plans, and monitoring that can handle ECMP paths. Organizations without such maturity may prefer simpler designs until tooling improves.

Finally, the framework encourages early identification of bottlenecks. For example, if optics consumption is the limiting factor, the planner can explore alternative designs such as partial mesh, oversubscribed leaf-spine, or staged expansion strategies.

IX. CONCLUSION AND FUTURE WORK

This paper presented a structured theoretical framework for selecting adaptive DCN topologies by jointly considering workload needs and hardware feasibility. By combining scoring with rule-based constraints, the framework provides repeatable and justifiable topology recommendations.

Future work includes extending the framework into a software prototype that integrates with inventory systems, automatically estimates bill of materials, and uses machine learning to learn scoring weights from historical deployments. Another direction is validating the framework using simulation and real telemetry from production DCNs.

REFERENCES

- [1] M. Al-Fares, A. Loukissas, and A. Vahdat, "A scalable, commodity datacenter network architecture," ACM SIGCOMM, 2008.
- [2] A. Greenberg et al., "VL2: A scalable and flexible data center network," ACM SIGCOMM, 2009.
- [3] R. Mysore et al., "PortLand: A scalable fault-tolerant layer 2 data center network fabric," ACM SIGCOMM, 2009.
- [4] C. Guo et al., "DCCell: A scalable and fault-tolerant network structure for data centers," ACM SIGCOMM, 2008.
- [5] C. Guo et al., "BCube: A high performance, server-centric network architecture for modular data centers," ACM SIGCOMM, 2009.
- [6] A. Singla et al., "Jellyfish: Networking data centers randomly," USENIX NSDI, 2012.
- [7] A. Singh et al., "Jupiter Rising: A decade of Clos topologies and centralized control in Google's datacenter network," ACM SIGCOMM, 2015.
- [8] M. Al-Fares et al., "Hedera: Dynamic flow scheduling for data center networks," USENIX NSDI, 2010.
- [9] M. Alizadeh et al., "CONGA: Distributed congestion-aware load balancing for datacenters," ACM SIGCOMM, 2014.
- [10] A. Roy et al., "Inside the social network's (datacenter) network," ACM SIGCOMM, 2015.
- [11] N. Farrington, G. Porter, S. Radhakrishnan, H. H. Bazzaz, V. Subramanya, Y. Fainman, G. Papen, and A. Vahdat, "Helios: A hybrid electrical/optical switch architecture for modular data centers," ACM SIGCOMM, 2010.
- [12] A. Greenberg, J. R. Hamilton, D. A. Maltz, and P. Patel, "The cost of a cloud: Research problems in data center networks," ACM SIGCOMM CCR, vol. 39, no. 1, pp. 68–73, 2009.
- [13] M. Alizadeh et al., "Data center TCP (DCTCP)," ACM SIGCOMM, 2010.
- [14] C. Hopps, "Analysis of an equal-cost multi-path algorithm," RFC 2992, 2000.

-
- [15] D. Thaler and C. Hopps, "Multipath issues in unicast and multicasting," RFC 2991, 2000.
 - [16] IEEE Std 802.1Q, "Bridges and bridged networks," IEEE, 2018.
 - [17] T. Benson, A. Akella, and D. A. Maltz, "Network traffic characteristics of data centers in the wild," ACM IMC, 2010.
 - [18] A. Vahdat et al., "Scale-out networking in the data center," IEEE Micro, vol. 36, no. 4, pp. 20–29, 2016.
 - [19] R. Niranjan Mysore and A. Vahdat, "PortLand: A scalable fault-tolerant layer 2 data center network fabric," IEEE/ACM Trans. Netw., vol. 20, no. 2, pp. 505–518, 2012.
 - [20] P. Gill, N. Jain, and N. Nagappan, "Understanding network failures in data centers: Measurement, analysis, and implications," ACM SIGCOMM, 2011.
 - [21] H. Ballani, P. Costa, T. Karagiannis, and A. Rowstron, "Towards predictable datacenter networks," ACM SIGCOMM, 2011.
 - [22] M. Zhang-Shen and N. McKeown, "Designing a predictable Internet backbone network," HotNets, 2004.
 - [23] J. Mudigonda, P. Yalagandula, M. Al-Fares, and J. C. Mogul, "SPAIN: COTS data-center ethernet for multipathing over arbitrary topologies," USENIX NSDI, 2010.

AI CAREER HUB – AN ALL-IN-ONE CAREER ACCELERATOR PLATFORM

¹Krishna Johari and ²Dr. Neha Vora¹Undergraduate Student, Department of Information Technology, SvkM's Usha Pravin Gandhi College of Arts, Science and Commerce Mumbai, Maharashtra 400056, India²Department of Information Technology, SVKM's Usha Pravin Gandhi College of Arts, Science and Commerce Mumbai, Maharashtra 400056, India**ABSTRACT**

The fast development of new technologies and the constantly changing job market have come to add to the difficulties students and young professionals face as they try to decide how to prepare themselves for their careers.

Nowadays, the hiring processes are pretty complicated and include different steps, for example, resume screening, aptitude tests, technical interviews, HR interviews, and continuous skill assessments. The old ways of gearing up for a career through school counseling, learning from peers, and coaching classes usually have their share of issues like being less personalized, the costly and not widely available, etc. Hence, a lot of students still do not have the necessary skills to be successful in hiring processes in the real world.

This paper showcases AI Career Hub, an all-in-one, web-based AI, powered career acceleration tool designed on the MERN stack and powered by a pre-trained Large Language Model (Mistral) locally deployed via Ollama. It is a platform that accommodates various career preparation components such as AI driven course creation, quiz generation, mock interview practice, resume building, and an interactive chatbot assistant. According to the data provided by users, the system develops tailor made learning materials, tests, interview questions, qualitative feedback, and professional resumes. All the results generated are saved permanently in the database and are organized in user specific dashboards for later retrieval and progress monitoring.

The presented system illustrates how a pre-trained LLM could be efficiently implemented in a practical use scenario to build a complete career preparation ecosystem. AI Career Hub brings together learning, assessment, mock interview, resume building, and chat support in one platform, thus making career resources more accessible, lessening the reliance on costly coaching services, and helping users to develop confidence, competence, and skills for employability.

Keywords: Artificial Intelligence, Career Guidance, AI Mock Interview, Resume Builder, Generative AI, Career Preparation, AI Career Hub, Smart Education, Large Language Models.

I. INTRODUCTION

Owing to fast tech progress, shifting sector demands, and fierce worldwide rivalry, job readiness has turned a lot more complicated than before. In fact, employers now look for candidates who aside from having a solid academic background, also possess hands on technical expertise, good problem-solving knack, excellent communication skills, and interview competence. Besides, recruitment avenues have stretched their limits beyond just getting an interview. These days, they may include aptitude tests, role, related technical tests, automated resume screening, and behavioral assessments.

On the other hand, many students remain deprived of organized career preparation facilities that would really help them meet these requirements. Academic counseling, coaching centers, and preparing with friends have traditionally been considered as methods for preparation. However, these approaches are usually expensive, time, limited, and the quality is often questionable. Moreover, these methods usually focus on one aspect only, such as practicing interview skills or making a resume, and therefore, they miss out on providing a smooth and comprehensive learning experience.

Artificial Intelligence (AI) is a technological revolution breakthrough which not only can bring about positive changes but also help overcome the existing difficulties. AI powered platforms can create educational content, test users' knowledge, conduct interview role plays, and provide highly personalized feedback. Researchers and developers have been coming up with various AI based solutions for interview preparation, resume building, and career guidance during the last several years.

However, the majority of solutions only cover a fragment of career preparation and hence are not able to support users throughout the whole career prep lifecycle. It is evident that a comprehensive, scalable, and easily accessible platform is needed which can seamlessly integrate learning, assessment, interview practice, resume development, and guidance into one system.

To bridge the gap, this paper presents AI Career Hub, a fully functional career acceleration web platform built on the MERN stack and combined with a pre-trained Mistral Large Language Model via Ollama. Through its single user interface, the platform delivers AI based courses, quizzes, mock interviews, resume generation, and chatbot help.

II. RELATED WORK

Artificial intelligence has been a major driving force behind the recent evolution of career guidance, interview simulation, and recruitment readiness [1], [8], [9]. The current literature in the field can be divided into three main segments: AI based interview systems, resume intelligence platforms, and AI powered career guidance or recommendation systems [1]. These studies show that AI can be helpful in employability; however, most of the solutions have been working on individual components of career preparation.

Some of the first studies on the use of AI for interview preparation by and large talked about automating interview question generation and answer evaluation. Bhadane et al. presented an AI based interview mocker system that could dynamically generate interview questions and change difficulty levels based on user performance by employing natural language processing techniques [2]. Their research demonstrated that AI driven mock interview environments could be scalable; however, emotional analysis and comprehensive evaluation metrics were found to be limited, and the learning or resume development support was not integrated into the system [2].

Kulkarni et al. presented an AI Interview Coach that was created using the latest full stack technologies and generative AI [4]. The platform enabled practice of live interviews, generated role, specific questions, and gave instant feedback on clarity, relevance, and confidence. A user study showed experienced users to be more prepared for interviews. However, the test was a small, scale one, and the AI was quite dependent on external large language model APIs without any integration of continuous learning or resume, building workflows [4].

Singh and Kumar took interview preparations research further by suggesting a multimodal AI interview assistant that integrated natural language processing, speech recognition, sentiment analysis, and optionally, computer vision components [3]. Their tool assessed not only content relevance but also emotional engagement. Even though the concept showed how advanced interview assessment could be done, it was still mostly a theoretical idea without a large, scale empirical validation or being part of an integrated career preparation platform [3].

Chavan and Jadhav put forward an AI powered mock interview framework that takes the resume into account for personalization [5]. Their system covered HR, technical, and aptitude interviews and relied on semantic similarity measures to assess answers. Although the system was a clear proof of concept for using resume parsing to direct interview personalization, the testing was mainly based on text and did not provide learning stimuli or the opportunity for progressive skill development through iterations [5].

At the same time, resume intelligence research has been aimed at finding ways to help job seekers still get through as a top candidate at the resume screening stage [6]. For example, JayaPriya et al. came up with a smart AI resume analyzer that can do content extraction, resume scoring, skill gap identification, and also the recommendation of improvements [6]. These approaches are powerful in getting resumes optimized for automated screening systems, but the game is not yet changing in terms of providing the job seekers with interview preparation or personalized learning support.

Career guidance and recommendation systems also saw the beneficial application of machine learning based approaches [8], [9]. For instance, Kumar et al. came up with a career path recommendation system that by leveraging the educational background, skills, and interests of a user, was able to suggest suitable career paths and academic projects and thus attain high predictive accuracy [8]. Similarly, Pujitha et al. documented an AI, powered learning and career guidance system based on classification techniques to predict suitable job roles [9]. Still, the two approaches work on basically career prediction and are bereft of a practical hiring skill evaluation and interview readiness component.

CareerGo, which was the brainchild of Vishwakarma and Dhuniya, became a platform that merged AI based job recommendations and resume enhancement [7]. While the demo of the system proved the potential of combining resume intelligence with job matching, it did not feature a mock interview session, learning guidance, or an iterative assessment mechanism [7].

On a larger scale, the AI Career Hub review of literature in the field of education revealed that there are no integrated real world career accelerating ecosystems that are able to help learners at each and every step in the preparation for their future careers. In addition, Westman et al. grounded their work theoretically by developing

AI maturity models for career counseling, pointing out that AI systems should develop into comprehensive platforms that support learner autonomy, ethical design, and continuous guidance, rather than mere isolated automation tools [1].

Together, these articles indicate that artificial intelligence is most suitable to help individuals with a few career preparation activities such as interview practice, resume optimization, and career prediction [2], [9]. On the other hand, the absence of a single LLM driven platform that can easily unite learning content generation, skill assessment, interview simulation, resume building, and interactive guidance in one, ever, accessible service is still a very big research challenge and gap [1], [7]. The introduced AI Career Hub, which is built on the MERN stack and a pre-trained Large Language Model (Mistral via Ollama), aims to fill this void by bringing all these elements together in one user friendly platform.

III. GAPS AND KEY FINDINGS

Reading through the available literature a number of recurring weaknesses were found. The majority of platforms only address one component of career readiness which leads to a fragmented experience for the users. Tools for analyzing resumes are seldom integrated with interview preparation whereas interview systems generally do not provide structured learning support. Besides this, a lot of the suggested solutions remain at the ideation stage without showing how they can be practically implemented.

Such constraints have prompted the establishment of AI Career Hub, a platform that aims to provide a continuous and integrated career preparation workflow. The platform envisions delivering uninterrupted assistance to the entire career prep journey by combining learning, assessment, interview simulation, resume building, and conversational coaching.

IV. PROPOSED MODEL: AI CAREER HUB

AI Career Hub is a web, based application that is implemented using the MERN stack. The technology stack manages the data in a MongoDB database and utilizes Express.js and Node.js for the server-side services. React.js is used for the frontend user interface.

Moreover, the platform utilizes a pre-trained Mistral Large Language Model, which is a local deployment through Ollama and is the source of all AI powered features.

4.1 AI Course Generator: By simply typing a topic, description, and difficulty level, users can get a tailor, made course of study. The LLM drafts a comprehensive learning plan with explanations and examples. The courses thus created are saved in the database and can be found in the My Courses area.

4.2 AI Quiz Generator: The quiz generator enables the creation of skill quizzes for a given topic, difficulty level, and number of questions. The LLM outputs multiple choice questions, which are then saved in the Past Quizzes section for future reference and progress tracking.

4.3 Mock Interview Module: Users set up their mock interviews by stating the job role, skills, experience level, and the number of questions. The LLM generates questions and gives qualitative feedback on the answers. The interview sessions and their results are saved in the My Interviews section.

4.4 Resume Builder: The resume builder relies on a pre- designed professional template. The LLM helps in creating the content based on user input. Generated resumes are saved in the My Resumes section and are available for download as PDF files.

4.5 AI Chatbot Assistant: An interactive chatbot is embedded to offer instant support on learning, interviews, resumes, and other career, related questions. For conversational interaction, the chatbot uses the same LLM.

V. IMPLEMENTATION OF PROPOSED MODEL

The AI Career Hub is a web, based career preparation platform built with the MERN stack, which comprises MongoDB, Express.js, React.js, and Node.js. It features a pre-trained Large Language Model (LLM), Mistral, integrated and deployed locally through the Ollama framework. The platform facilitates the whole career preparation process via AI driven learning and practice content generation, interview simulation, resume writing, and an interactive chatbot assistant.




Fig. 1.

Overall system workflow of AI Career Hub using MERN stack and Ollama-based Mistral LLM

A. User Authentication and Dashboard

The application first offers a Sign in and Sign-Up interface from which users can securely create or access their accounts. After a successful login, users are taken to a centralized Dashboard, which acts as a hub for accessing all platform features. From the dashboard, one can navigate to functionalities such as course generation, quiz generation, mock interview setup, resume building, and the chatbot assistant.

B. User Input Collection

React.js has been used for the front end to create user friendly forms through which each functional module gathers structured input from users. These inputs may refer to course topics and difficulty levels, quiz topics and number of questions, interview roles and skills, resume details, and general chatbot queries. The gathered data is then used to generate personalized content through AI.

C. Backend Request Routing and Validation

User requests are routed back to the backend server which is done via Node.js and Express.js. The backend is responsible for request routing, validating input data, and identifying the suitable processing module. This layer acts as a gatekeeper, making sure only valid and complete requests reach the AI processing stage.

D. Prompt Construction and Context Preparation

The backend creates prompts on the fly by mixing the user's input with the set context instructions for each request. This prompt engineering step makes sure the LLM generates well, structured, relevant, and task, specific outputs for different modules like courses, quizzes, interviews, resumes, and chatbot responses.

E. LLM Inference Using Ollama

The prompts thus formulated are directed to the Mistral pre, trained Large Language Model, hosted locally through the Ollama framework. The LLM carries out inference to produce educational content, examination questions, interview questions, resume text, or conversational responses. Leveraging a ready made LLM obviates the need for a model tailored training while at the same time allowing personalized output generation.

F. AI Content Generation

The LLM, depending on the module invoked, generates:

Courses structured by topics and detailed explanations
Quizzes with multiple, choice questions
Mock interview questions targeted at specific job roles
Resume content synchronized with a particular professional template
Chatbot responses to users' queries
All are qualitative and context, aware outputs, mirroring the user inputs.

G. Post, Processing and Formatting

In order to maintain consistency, readability, and appropriate formatting, the generated content is subjected to post, processing. The output of the course and quiz is formatted for convenience; interview questions are made sequential, and resume content follows the chosen template.

H. Persistent Data Storage

Processed data is kept in MongoDB, which allows for persistent data management and retrieval. The system creates distinct record sets for courses, quizzes, interviews, resumes, and chatbot interactions. This method of storage facilitates the users' ability to access the content generated in the previous sessions.

I. User, Specific Dashboard Output

The data thus stored is shown through the dashboard tabs personalized for the user, such as My Courses, Past Quizzes, My Interviews, My Resumes, and the Chatbot interface. This structure allows continuous learning, progress monitoring, and the repetition of practices inside a single platform.

VI. OUTPUT AND RESULT ANALYSIS

To confirm that the proposed AI Career Hub system has been effectively implemented in practice, this part displays some of the output samples made by the platform. The outputs reveal the systems capability in creating customized learning content, evaluations, interview questions, resumes, and chat replies through the use of the Ollama, based Mistral LLM. Such outcomes serve as evidence of the functional accuracy and practical application of the suggested model.

1. Course Generator:

Fig 2. Course Generator input interface

The AI Course Generator module creates a structured educational course based on the topic, description, and level of difficulty given by the user. Employing the Ollama, based Mistral LLM, the system produces detailed explanations and educational materials for each topic, which are then saved in the database and can be seen in the My Courses section for later use.




Fig. 3. User created courses in My courses




Fig. 4. LLM model generated course content based on input.

2. Quiz Generator:




Fig. 5 Quiz Generator Input interface

Skill Assessment

1

2

3

4

5

Q1. What does the 'useEffect' hook in React do?

It is used for handling side effects like data fetching and subscriptions.

It is used for managing component state.

It is used for rendering components.

It is used for optimizing performance.

Skip

Next

Fig. 6 Quiz questions generated by LLM model

AI CareerHub
Unified Platform

Dashboard

AI Courses

Quiz Generator

Mock Interview

Resume Builder

john_doe
User

Log Out

Skill Assessment

Past Quizzes

New Quiz

arrays
Beginner • 2 questions

View

Reappear

subtraction
Beginner • 5 questions

View

Reappear

python
Beginner • 5 questions

View

Reappear

mern stack
Beginner • 10 questions

View

Reappear

tables
Beginner • 5 questions

View

Reappear

multiplication
Beginner • 5 questions

View

Reappear

Fig.7 List of quiz generated by user

The Quiz Generator module creates multiple choice questions on specific topics automatically by using AI according to the subject and difficulty level selected by the user. The AI generated quizzes are checked instantly, recorded in the database, and published under the Past Quizzes section for the students to be able to assess their skills and monitor their progress.

Q1. What does the 'useEffect' hook in React do?

It is used for handling side effects like data fetching and subscriptions.

It is used for managing component state.

It is used for rendering components.

It is used for optimizing performance.

Q2. What does the 'Refs' in React help with?

It helps in managing the state of functional components.

It helps in accessing the DOM nodes or React elements created in the render method.

It helps in creating new instances of a class.

It helps in optimizing performance.

Correct answer: It helps in accessing the DOM nodes or React elements created in the render method.

Q3. What is the purpose of the 'Context API' in React?

It is used for handling side effects like data fetching and subscriptions.

It is used for managing global state across components without using third-party libraries.

It is used for rendering components.

It is used for optimizing performance.

Q4. What does the 'memo' higher-order component do in React?

It helps in optimizing the performance of a component by preventing unnecessary re-renders.

It helps in managing global state across components.

It helps in handling side effects like data fetching and subscriptions.

It helps in creating new instances of a class.

Q5. What does the 'forwardRef' function do in React?

It is used for managing global state across components.

It is used for handling side effects like data fetching and subscriptions.

It is used for rendering components.

It is used for forwarding refs to child components.

Correct answer: It is used for forwarding refs to child components.

Fig8. Result of quiz evaluated by LLM model

3.Mock Interview:




Fig. 9 Mock interview Details Input




Fig. 10 Mock Interviews given by user




Fig. 11 Mock interview questions

The Mock Interview feature creates targeted questions for the roles and skills specified by the user. By utilizing the Ollama, based Mistral LLM, the platform assesses answers given by the user and issues qualitative feedback. The interview session along with the performance can be found in the My Interviews section for the user's reference and further practice.




Fig 12. Mock Interview evaluation result

4: Resume Builder:




Fig. 13 Resume Created by User

The screenshot displays the 'Resume Builder' interface. On the left is a sidebar with navigation options: Dashboard, All Courses, Quiz Generator, Mock Interview, and Resume Builder (highlighted). The main area is titled 'Resume Builder' with the subtitle 'Build ATS-friendly resumes and download as PDF'. It has tabs for 'New Resume' and 'My Resumes'. The 'Resume Details' section on the left shows a form for 'John Doe' with fields for email, phone, and a bio. Below this are sections for 'Skills' (React.js, Java, Python, JAMPP, Postman, Communication, Time Management) and 'Experience' (Full-Stack Developer Intern at XYZ Innovations, Web Developer Intern at ABC Tech Solutions). The 'Education' section lists a Bachelor of Science in Information Technology (BSIT) from XYZ College and a Higher Secondary Certificate (HSC) from ABC Junior College. At the bottom are buttons for '+ Add Experience', '+ Add Education', 'Save Resume', and 'Download PDF'. On the right is a preview of the generated resume, which includes a 'Summary' section describing the user as a motivated web developer, followed by the 'Experience' and 'Education' details.

Fig 14. Resume creation interface

The Resume Builder module helps in generating professional resume content by structuring the user's inputs and using a predefined template.

The Mistral LLM based on Ollama collaborates in the formation of perfectly formatted resume sections, which are saved in the database and accessible under the My Resumes section for download and later use.

VII. RESULT AND ANALYSIS

The demonstration of AI Career Hub's experimental results is a successful story of pre-trained Large Language Model combined with a web-based career preparation platform. The system has been very successful in generating personalized learning courses, quizzes, mock interview questions, resumes, and chatbot responses from user inputs. AI Course Generator created well-structured, topic wise learning content that was saved continuously and made available through the dashboard, thus enabling self-study without time constraints. In the same way, the Quiz Generator formed multiple choice questions dynamically and also assessed the answers, so users could evaluate their skills and see their progress through stored quiz records.

The Mock Interview section assisted users in understanding their qualities and areas of improvement by producing step and role, specific interview questioning and giving the user exceptionally qualitative feedback on the answers. The Resume Builder was designed to offer professional CVs by using structured inputs and ready made templates, and the chatbot assistant provided interactive, context aware answers for user inquiries.

The developed system reveals that an off-the-shelf LLM is suitable for integration into a career preparation platform of the real world. The platform enables the users to learn, get assessed, practice the interview, and build a resume in an uninterrupted manner. Keeping the generated contents in a persistent storage allows the users to be able to track their progress and also repeat more practice.

In short, the outcomes reflect that the system is correct in functionality, the users find it easy, and it can be scaled up. The employment of the Ollama, based Mistral LLM allows for meaningful customization without the need for a custom model training, which means that the AI Career Hub is not only a theoretical but a practical solution for career preparation.

VIII.CONCLUSION

This article introduces AI Career Hub, an end-to-end career development platform enhanced with AI and LLM to help users in the career preparation cycle. It combines AI driven course generation, quiz based skill evaluation, mock interview session, resume building, and conversational guidance in one integrated system.

Many AI powered career tools have been developed based on the research literature, but they tend to be standalone products, not offering the learner continuous or holistic support.

AI Career Hub not only addresses this issue but also offers a user friendly interface to allow users to create personalized learning materials, self assess their skills through quizzes, do mock interviews of the roles they want to apply for, get automated qualitative feedback, and construct professional resumes based on the structured templates.

A pretrained Large Language Model via Ollama is used to show how generative AI can be implemented in the actual system effectively without custom model training and still get meaningful personalization and scalability.

IX. FUTURE SCOPE

AI Career Hub provides a comprehensive and integrated solution for career preparation, but several enhancements can be made to further increase its impact and learning effectiveness.

One possible improvement is the addition of certified learning resources from platforms like Coursera and Udemy. After identifying the skill gaps through quizzes, mock interviews, or resume analysis, the system can suggest certification courses that best fit the needs of the user. At the same time, the platform can also recommend complementary YouTube learning materials to facilitate flexible and self-paced learning to those users who wish to avail free or supplemental content.

Another interesting upgrade is the introduction of mind mapbased learning visualization. For example, by creating mind maps of a learning topic or course, students would be able to see what they are learning in a more structured way and better understand how the knowledge points connect to each other.

Besides, the mock interview feature may be refined by adding separate interview stages, such as aptitude, technical, and HR rounds. This well, organized approach can make the training sessions most similar to the real, world recruitment procedures, thus enabling the users to test their logical reasoning, technical competence, and communication skills independently, which will lead to more focused feedback and targeted improvement.

X. REFERENCES

- [1] S. Westman, J. Kauttonen, A. Klemetti, N. Korhonen, M. Manninen, A. Mononen, S. Niittymäki, and H. Paananen, "Artificial Intelligence for Career Guidance – Current Requirements and Prospects for the Future," IAFOR Journal of Education: Technology in Education, vol. 9, no. 4, 2021.
- [2] U. Bhadane, L. Jagtap, S. Rane, R. Dhonnar, and P. Pawar, "AI Based Interview Mocker System," International Journal of Advanced Research in Science, Communication and Technology, 2025.
- [3] A. Singh and D. Kumar, "Interview Assistant — AI Powered Interview Preparation and Assessment Platform," International Journal of Scientific Research in Engineering and Management, 2025.
- [4] H. Kulkarni, I. Jadhav, R. Mahale, and R. Shinde, "AI Interview Coach," International Research Journal of Engineering and Technology, vol. 12, no. 11, 2025.
- [5] P. Chavan and S. Jadhav, "A General Paper on AI Based Mock Interview System," International Journal of Scientific Research in Science, Engineering and Technology, vol. 13, no. 1, 2026.
- [6] D. JayaPriya, R. Mouleeswaran, T. Kishore, G. Praveen, and N. Arjun, "Smart AI Resume Analyzer," International Journal of Scientific Research in Science, Engineering and Technology, 2025.
- [7] M. K. Vishwakarma and A. Dhuniya, "CareerGo: An AI-Powered Career Assistance Platform," 2025.
- [8] H. Kumar, U. P. Pandey, and P. Kumar, "AI-Based Career Path Recommendation System," 2025.
- [9] V. N. Pujitha, P. T. Rohith, Y. Sowjanya, and C. D. Teja, "AI-Powered Learning and Career Assistance Platform," International Journal of Creative Research Thoughts, 2025.

COMPARATIVE ANALYSIS OF USER PERCEPTIONS AND LEARNING PREFERENCES: A STUDY OF AI, YOUTUBE AND GOOGLE IN EDUCATION

Saanvi Ghadiali¹ and Neha Vora²¹Student and ²Assistant Professor, Department of Information Technology, SVKM's Usha Pravin Gandhi College of Arts, Science and Commerce, Mumbai, India**ABSTRACT**

This research papers show us how learners see and want to learn in modern education. This paper utilizes and use depth database to analyses how factors such as learning environments, technology utilization, and instructional design influence learn attitude and outcomes. The research apply is quantitative and qualitative approaches such as descriptive statistics, correlation analysis, and chi-square test, in examining the core factors that contribute to user preferences and satisfaction in e-Learning and classroom learning experience. These core factors include the quality of course material, system interactive, instruction assistance, flexibility motivation, and prior exposure to technology. The result indicate that although students commonly enjoy the convenience and flexibility of e-Learning their perception regarding effectiveness and engagement join upon features that unable interaction the degree of technical assistance and feedback from faculty. The article concludes with recommendations to instructor and institutes on how to enhance online and face to face learning environment through user-center expect that enhance satisfaction and learning outcomes..

Keywords: Artificial Intelligence, User Perceptions, Learning Preferences, YouTube Education, Google Learning Tools, Education Technology, Comparative Study, Demographic Influences.

1. INTRODUCTION

In the past decades learning has been revolutionized by digital technology. They provide various platforms and tools that change the way learners interact with access knowledge. Among these, Artificial Intelligence (AI) YouTube and Google are some of the main tools that have become very important for students as well as educators. All these platforms provide various means of improving learning. AI office adaptive and personalized learning features. YouTube provides voice video resources for self-study. Google helps students in searching information quickly and allows them to use tools that support research and collaboration. The study tells how students feel about different learning platforms and why they choose one over another. Understanding the experience can help improve this technology for better learning. But AIMS identify key factors that boost engagement, satisfaction, and learning outcomes. By inspecting these factors the study aims to advise the educators, developers, and policy makers on the use of technology for improving learning experience in a changing digital world.

1.2 Problem statement

Despite of rapid adoption of new technology we still don't fully understand how users use and prefer learning tools like Artificial Intelligence (AI), Google and YouTube. Each platform has its own benefits and challenges. But leaners have different attitude, engagement levels and satisfaction for these technologies. This difference makes it hard for educators and institutors to choose and use the best tools for improving learning outcomes. Also, there is limited evidence for comparing these platforms regarding user experience and learning preferences. The purpose of this study is to fill a gap by analysing and comparing user's choice and preferences. It will provide insights to help effectively integrate AI, YouTube and Google into educations..

1.3 Research Objectives

- Determine the level of awareness and see how frequent one of AI, YouTube or Google is used among learners and teachers.
- Identify the most popular platform for learning and the factors that drive these choices.
- Compare users view of benefits ease to access saving time interactive learning.
- Examine demographic variables (gender, age, profession, education) and chi- square test.
- Explore drawbacks miss information plagiarism overreliance on technology..
- Make suggestions for appropriate and effective integrations of tools in education.

1.4 Research Gap

While a multiple of studies have look over the application of digital platforms in learning most focuses on a single tool like AI or YouTube instead of comparing various platforms as a whole. Additional existing research

strength to be conceptual or descriptive based and not empirically tested with regards to how demographics affect user perceptions and learning preferences. This research fills that gap by implementing a comparative study of AI, Google and YouTube based on survey data and chi-square statistical verification, providing both quantitative and descriptive information concurring how various users understand and adapt to this tools within learning situations..

2. LITERATURE REVIEW

1. Woolf, Beverly Park (2010).

Woolf, Beverly Park (2010), in her book published in Burlington, Massachusetts, explains how intelligent tutoring systems use artificial intelligence to adapt explanations and guide students step by step. This personalized interaction enhances learning effectiveness and influences students to prefer AI-based tools over traditional search-based platforms.

2. Guo, Philip J., Juho Kim, and Rob Rubin (2014).

Guo, Philip J., Juho Kim, and Rob Rubin (2014), through their empirical study conducted in the United States, found that students engage more with short, clearly structured, and visually rich videos. Their research explains why platforms such as YouTube are highly preferred for easy-to-understand and visually supported learning.

3. Luckin, Rose, Wayne Holmes, Mark Griffiths, and Laurie B. Forcier (2016).

Luckin, Rose, Wayne Holmes, Mark Griffiths, and Laurie B. Forcier (2016), in a report published in London by Pearson and UCL Knowledge Lab, discuss how AI supports personalized and adaptive learning by providing targeted feedback to students. The study also highlights privacy concerns, which strongly influence how learners evaluate AI tools compared to established platforms like Google and YouTube.

4. Selwyn, Neil (2019).

Selwyn, Neil (2019), in his work published in the United Kingdom, discusses issues of trust and ethical concerns related to AI in education. He notes that students question the fairness, transparency, and reliability of AI systems, leading them either to rely cautiously on AI or to feel safer using familiar platforms such as Google and YouTube.

5. Chan, C. K. Y., Kara Chan, Z. K. Yu, et al. (2023).

Chan, C. K. Y., Kara Chan, Z. K. Yu, et al. (2023), in a study published in the International Journal of Educational Technology in Higher Education, report that students appreciate generative AI for quick academic support and clarity of explanations. However, concerns regarding accuracy and ethical risks significantly influence their preference between AI tools and platforms like YouTube and Google.

6. Bond, Melissa, Y. Li, et al. (2024).

Bond, Melissa, Y. Li, et al. (2024), in their meta-systematic review published in the International Journal of Educational Technology in Higher Education, explain that AI improves learning efficiency through personalized feedback. At the same time, students express apprehension about biased and incorrect outputs, creating mixed perceptions toward AI-based learning tools.

7. Wang, Shuang (2024).

Wang, Shuang (2024), through a systematic literature review published on ScienceDirect, shows that AI enhances academic performance by offering adaptive support. Despite these benefits, learners continue to report limitations such as inaccuracies, which helps explain fluctuating preferences between AI tools and other digital learning platforms.

8. Greeves, Sarah (2024).

Greeves, Sarah (2024), in a study published in Frontiers in Education, finds that students strongly trust YouTube due to clear explanations, visual demonstrations, and social indicators such as likes, views, and creator credibility. These factors strengthen YouTube's position as a preferred learning tool over text-based search platforms.

9. Portilla, J. E. N., E. Molina, and L. Castro (2025).

Portilla, J. E. N., E. Molina, and L. Castro (2025), in their systematic review published via ERIC, reveal that AI in Education 4.0 improves student engagement and personalization. However, serious concerns related to privacy and data security contrast AI tools with more universally accepted platforms such as YouTube and Google.

10. Matos, Tiago (2025).

Matos, Tiago (2025), in a systematic review published on ScienceDirect, describes how AI tools support both teachers and students by improving feedback quality and learning outcomes. Nevertheless, concerns about over-dependence and reliability influence user preferences when choosing between AI tools and other digital platforms.

3. RESEARCH METHODOLOGY**3.1 Research Design:**

The study has utilized a detailed survey research design. This design was preferred as it enables the researchers to collect quantitative data regarding users, awareness, perceptions, and learning preference towards AI, YouTube, and Google in the educational process. It also allows the identification of possible associations between demographic variables and users attitude towards each platform (Chan et al., 2023). The descriptive approach is appropriate as it aims to understand the existing state without manipulating variables, thereby capturing the genuine opinions of student and educators.

3.2 Data Collection procedures

The survey was conducted online using Google forms for two weeks. Participation in this survey was completely voluntary and anonymous. All respondents were informed of the purpose and aim of the research, and content was secured before the participated in the research the instruction stated that there was no right or wrong answers to minimize response bias and that the respondent could respond freely using honest opinions and experience.

3.3 Research Variable

- **Independence variable:** Gender, age, Educational level, Role, Frequency of platform usage..
- **Dependent variable:** Platform awareness, Perceived educational value, Learning preferences, Ethical concerns, and Trustworthiness the of the Platforms..

3.4 Statistical Analysis

The collected data were process used in the chi-square test to analyses interaction of demographic variable and user attitude or opinions between AI, YouTube and Google. This chi-square approach was employed as it could efficiently be used for testing association between categorical variables, e.g., user demographics and site attitudes. The level of significance was established at $p < 0.05$, any result below this demands importance.

4. RESULTS**Hypothesis 1: Gender and Platform Most Frequently Used**

H0: Gender has no effect on the platform most frequently used.

H1: Gender influences the platform most frequently used.

Results: The chi-square test yielded $\chi^2 = 171$, $df = 22$, $N = 156$, $p < 0.001$. Since the p.value is less than 0.05, the null hypothesis is rejected, indicating a significant effect of gender on the platform most frequently used.

Hypothesis 2: Age and Platform Most Frequently Used

H0 Age has no effect on the platform most frequently used.

H1: Age influences the platform most frequently used.

Results: The chi-square test yielded $\chi^2 = 234$, $df = 55$, $N = 156$, $p < 0.001$. The null hypothesis is rejected, indicating that age significantly affects which platform is most frequently used.

Hypothesis 3: Occupation and Platform Most Frequently Used

H0 Occupation has no effect on the platform most frequently used.

H1: Occupation influences the platform most frequently used.

Results: The chi-square test yielded $\chi^2 = 223$, $df = 55$, $N = 156$, $p < 0.001$. The null hypothesis is rejected, meaning occupation significantly influences platform choice.

Hypothesis 4: Age and Preferred Platform for Learning New Concepts

H0 Age has no effect on the preferred platform for learning new concepts.

H1: Age influences the preferred platform for learning new concepts.

Results: The chi-square test yielded $\chi^2 = 229$, $df = 50$, $N = 156$, $p < 0.001$. The null hypothesis is rejected; age significantly affects platform preference for learning.

Hypothesis 5: Gender and Preferred Platform for Learning New Concepts

H0 Gender has no effect on the preferred platform for learning new concepts.

H1: Gender influences the preferred platform for learning new concepts.

Results: The chi-square test yielded $\chi^2 = 163$, $df = 20$, $N = 156$, $p < 0.001$. The null hypothesis is rejected; gender significantly impacts platform preference for learning.

Hypothesis 6: Age and Platform Trusted Most for Quick Answers

H0 Age has no effect on the platform trusted most for quick answers.

H1: Age influences the platform trusted most for quick answers.

Results: The chi-square test yielded $\chi^2 = 173$, $df = 20$, $N = 156$, $p < 0.001$. The null hypothesis is rejected; age significantly influences trust in platforms.

Hypothesis 7: Platform Most Frequently Used and Platform Saving Most Time

H0 Platform most frequently used has no effect on the platform saving the most time.

H1: Platform most frequently used influences the platform saving the most time.

Results: The chi-square test yielded $\chi^2 = 238$, $df = 33$, $N = 156$, $p < 0.001$. The null hypothesis is rejected; platform usage significantly relates to perceived time-saving.

Hypothesis 8: Platform Most Frequently Used and Platform Giving Detailed Explanations

H0 Platform most frequently used has no effect on the platform giving detailed explanations.

H1: Platform most frequently used influences the platform giving detailed explanations.

Results: The chi-square test yielded $\chi^2 = 223$, $df = 44$, $N = 156$, $p < 0.001$. The null hypothesis is rejected; platform usage affects perception of explanation detail.

Hypothesis 9: Platform Most Frequently Used and Platform Trusted for Accuracy

H0 Platform most frequently used has no effect on the platform trusted for accuracy.

H1: Platform most frequently used influences the platform trusted for accuracy.

Results: The chi-square test yielded $\chi^2 = 245$, $df = 44$, $N = 156$, $p < 0.001$. The null hypothesis is rejected; platform usage significantly affects trust in accuracy.

Hypothesis 10: Gender and Misleading/Wrong Answers from AI

H0 Gender has no effect on experiencing misleading or wrong answers from AI.

H1: Gender influences experiences of misleading or wrong AI answers.

Results: The chi-square test yielded $\chi^2 = 157$, $df = 8$, $N = 156$, $p < 0.001$. The null hypothesis is rejected; gender significantly relates to perception of AI errors.

5. DISCUSSION

The research reveals that AI, YouTube and Google all have different effects on contemporary learning. Demographic influences including gender, role, and technology exposure determined preferences for platforms, but age and qualifications had negligible effects - suggesting that desire and restraint towards digital technology is cut across all groups like (Chan et al.,2023; Greeves.,2024).

5.1 Benefits

- AI was appreciated for time saving and providing individual learning's with tools for kind of chair GPT assisting in instant doubt clearing and explanation (Chan et al, 2023).
- YouTube encourage wish you will and self-directed learning supporting and enhanced concept comprehension (Guo et al.,2014).

- Google facilitated research, collaboration, and productivity, particularly in academic works (Greeves, 2024)

5.2 Concerns

Users fear about AI accuracy, plagiarism and excessive dependency (Selwyn, 2019)

YouTube material was at times unreliable, and Google promoted surface searching as opposed to in depth comprehension (Greeves, 2024)

Teachers also reported privacy and ethical concerns regarding AI tools (Bond et al, 2024).

5.3 Implications

- There should be a balance application of AI, YouTube, and Google as each has a different use in education (AI for support, YouTube for visuals, Google for research).
- Introduction to ai and digital literacy should be included for both students and teachers to understand the responsibility and effective/ethical use of these tools.
- There should be policies to address the ethical, privacy of data and verification of information when using AI and online platform in education

5.4 Limitations

- The study used convenience sampling method, and thus the result may not hold for all learners or teachers
- The information was based on self-reported impressions, which may contain personal bias and subject interpretations.
- The use of chi-square analysis indicates correlation among variable and cannot established cause the effect between platform and preferences.

6. CONCLUSION AND FUTURE SCOPE

6.1. Conclusion

For today's learners AI, YouTube and Google have become truly integrated parts of modern learning and please tool has its own advantage and terms of access, flexibility and engagement in learning. Students appreciate AI tools for quick information, visual content, self-place videos and for the ease of access to research and to collaborate. Maintaining and ethical use of technology including AI, YouTube and Google will continue to present challenge to the educational profession. There are two key consideration for educators to ensure rational, responsible, ethical ,use of artificial intelligence, YouTube, and Google in their classroom, creating educational guidelines regarding their use, providing students with discussion based learning regarding their use, and monitoring the use of content once a sign to complete. On the whole, equally applying AI, YouTube and Google tools in classroom practice will enhance student's outcomes, satisfaction, creativity, critical thinking and academic integrity using on the educational concept behind the content.

6.2 Future Scope

- Investigates studies that utilize larger and more diverse samples across different academic levels or reason to enhance generalizability.
- Conduct cross culture compression of how learners perceive or prefer these digital tools based on their background.
- Implement longitudinal studies to investigate how participant's perception motivation and usage of AI, YouTube or Google changes overtime.
- Conduct experimental studies to access the casual relationship between platform use and academic performance or skill development.

7. REFERENCES

- [1] Woolf, Beverly Park. 2010. *Building Intelligent Interactive Tutors: Student-Centered Strategies for Revolutionizing E-Learning*. Burlington, MA: Morgan Kaufmann. https://www.researchgate.net/publication/232322117_Building_Intelligent_Interactive_Tutors_Student-Centered_Strategies_for_Revolutionizing_E-Learning
- [2] Guo, Philip J., Juho Kim, and Rob Rubin. 2014. "How Video Production Affects Student Engagement: An Empirical Study of MOOC Videos." https://www.researchgate.net/publication/262393281_How_video_production_affects_student_engagement_An_empirical_study_of_MOOC_videos

-
- [3] Luckin, Rose, Wayne Holmes, Mark Griffiths, and Laurie B. Forcier. 2016. *Intelligence Unleashed: An Argument for AI in Education*. London: Pearson / UCL Knowledge Lab. https://www.researchgate.net/publication/299561597_Intelligence_Unleashed_An_argument_for_AI_in_Education
- [4] Selwyn, Neil. 2019. *Should Robots Replace Teachers? AI and the Future of Education* <https://www.scirp.org/reference/referencespapers?referenceid=3627290>
- [5] Chan, C. K. Y., Kara Chan, Z. K. Yu, et al. 2023. "Students' Voices on Generative AI: Perceptions, Benefits, and Concerns." *International Journal of Educational Technology in Higher Education* 20 (56). https://www.researchgate.net/publication/372411790_Students'_voices_on_generative_AI_perceptions_benefits_and_challenges_in_higher_education
- [6] Bond, Melissa, Y. Li, et al. 2024. "A Meta-Systematic Review of Artificial Intelligence in Higher Education." *International Journal of Educational Technology in Higher Education*. <https://link.springer.com/article/10.1186/s41239-023-00436-z>
- [7] Wang, S. 2024. "Artificial Intelligence in Education: A Systematic Literature Review." <https://www.sciencedirect.com/science/article/pii/S0957417424010339>
- [8] Greeves, S. 2024. "YouTube in Higher Education: Comparing Student and Instructor Perceptions." <https://www.frontiersin.org/journals/education/articles/10.3389/feduc.2023.1330405/full>
- [9] Portilla, J. E. N., E. Molina, and L. Castro. 2025. "Systematic Review: Artificial Intelligence (AI) in Education 4.0." <https://files.eric.ed.gov/fulltext/EJ1473947.pdf>
- [10] Matos, T. 2025. "A Systematic Review of Artificial Intelligence Applications in Education." <https://www.sciencedirect.com/science/article/pii/S277266222500027X>
-

A REVIEW OF RECENT EMERGING TRENDS IN Tb³⁺ - ACTIVATED BORATE HOST PHOSPHOR MATRIX FOR NUV-EXCITED WLEDs**Prabhat P. Tiwari**

Department of Physics , Guru Nanak Khalsa college, University of Mumbai, NP Marg, Mumbai 400019, Maharashtra ,India

ABSTRACT

The development of thermally stable, high-efficiency green-emitting phosphors is a prerequisite for improving the colour rendering index (CRI) and luminous efficacy of near-ultraviolet (NUV) pumped white light-emitting diodes (WLEDs). Borate-based hosts have recently gained significant attention due to their wide bandgaps, high UV transparency, and relatively low synthesis temperatures. This review critically examines recent advancements (2023–2025) in Terbium (Tb³⁺) doped borate phosphors, focusing on novel host matrices such as Lu₅Ba₆B₉O₂₇:Ce³⁺ co-doped with Tb³⁺, Ba₃Lu(BO₃)₃:Ce³⁺, Tb³⁺/Mn²⁺, Ca₃Y(GaO)₃(BO₃)₄:Bi³⁺/Tb³⁺/Eu³⁺, K₇CaY₂(B₅O₁₀)₃:Tb³⁺.

Key discussions include the optimization of 4f → 5d transition probabilities via crystal field engineering and the mitigation of the weak NUV absorption of Tb³⁺ through effective sensitization strategies. We highlight recent findings on energy transfer mechanisms, specifically in Ce³⁺ → Tb³⁺ and Tb³⁺ → Eu³⁺ co-doped systems, which have successfully yielded tunable emission from green to warm white with quantum yields exceeding 85%. Furthermore, the review addresses the thermal quenching behaviour of these materials. The study concludes that Tb³⁺-activated emphasizing the role of rigid borate frameworks, low phonon energies, and optimized activator site symmetry in suppressing non-radiative relaxation, thereby maintaining more than 80% of the initial emission intensity at operating temperatures up to 150–200 °C under NUV excitation. Borates represent a promising class of materials for closing the "green gap" in next-generation solid-state lighting.

Keywords: Tb³⁺-doped phosphors; Borate host; Solid-state lighting; Energy transfer; Thermal stability.

INTRODUCTION

Rare-earth-doped borate materials have emerged as a crucial class of functional optical materials owing to their flexible crystal structures, high chemical stability, and excellent thermal robustness. In addition to their well-established nonlinear optical (NLO) behavior, these materials exhibit outstanding photoluminescence characteristics, making them highly attractive for applications in laser systems, phosphor-converted light-emitting diodes, and advanced solid-state lighting technologies.[1][2][3]. Borate compounds, known for their exceptional chemical and thermal stability, variable crystal field environments, plentiful resource availability, low production cost, moisture resistance, water resistance, and low synthesis temperature, are highly suitable and preferred as matrix materials [4,5]. In study, Tb³⁺-doped K₃Gd(BO₂)₆ phosphors were synthesized using the microwave-assisted sol-gel method to explore their photoluminescence (PL) properties and thermal stability. XRD and Rietveld refinement confirmed the incorporation of Tb³⁺ ions, without secondary phases. PL analysis revealed a strong green emission near 542 nm, attributed to the ⁵D₄ → ⁷F₅ transition of Tb³⁺ ions. An optimal Tb³⁺ concentration of 3 wt% was identified, beyond which concentration quenching significantly reduced luminescence intensity. [6](Souadi et al., 2025)

Weak direct absorption in NUV region and Thermal quenching during LED operation are some major issues in Tb³⁺ doping to overcome from this researcher have explored suitable host lattice. Borate have become excellent host matrices because of their wide band gap, low phonon energy, high chemical stability and flexible crystal structure.

LUMINESCENCE MECHANISM OF DOPANT:

Tb³⁺ emission in borate phosphors arises from 4f–4f transitions of the trivalent terbium ion. (Fouassier, 1997) Upon NUV excitation, electrons are promoted from the ⁷F₆ ground state to higher excited states and relax non-radiatively to the ⁵D₄ Level. Radiative transitions from ⁵D₄ to ⁷F₅ levels generate characteristic green emission, particularly the strong ⁵D₄ to ⁷F₅ transition at ~545 nm. (Carnall et al., 1968) At higher dopant concentrations, concentration quenching may occur due to non-radiative energy migration between neighbouring Tb³⁺ ions. (Dexter & Schulman, 1954) .The rigid borate lattice suppresses multiphonon relaxation and enhances quantum efficiency, while excessive Tb³⁺ concentration leads to concentration quenching through dipole–dipole energy transfer. The choice of REs ions for such light emission systems is due to their peculiar electronic configurations (Liu 1978)[7] related to their characteristic optical properties of excitation and emission (Judd 1962). It is well-known that RE ions like Ce³⁺, Tb³⁺, and Eu³⁺, are commonly used to produce

yellow, green, and red phosphors, respectively, and a combination of different ions is exploited to obtain a wide range of colors (Yen et al. 2007; Ye et al. 2010)

Sensitization Strategies:

A highly thermal stable and efficient green-emitting $\text{Ba}_2\text{Y}_5\text{B}_5\text{O}_{17}:\text{Ce}^{3+}$, Tb^{3+} phosphor prepared by high-temperature solid-state reaction the phosphor exhibits a blue emission band of Ce^{3+} and green emission lines of Tb^{3+} upon Ce^{3+} excitation in the near-UV spectral region. The green phosphor, shows attractive performance for near-UV-based white-light-emitting diodes applications. [8] (Xiao et al., 2017) Ce^{3+} has strong NUV absorption (allowed $4f-5d$ transitions).

Energy transfer: Ce^{3+} absorbs NUV $\rightarrow$ transfers energy $\rightarrow$ Tb^{3+} emits green. A

single-phosphor-converted warm w-LED fabricated by UV chip with $\text{CLAB}:\text{Bi}^{3+}, \text{Tb}^{3+}, \text{Eu}^{3+}$ shows thermally robust properties. Energy transfer from Tb^{3+} (green) to Eu^{3+} (red) produces tunable emission, enabling white light generation. (Lv et al., 2023)

Thermal Quenching Behaviour:

In this study it investigated that A decrease in emission was observed at higher concentrations due to concentration quenching. Temperature-dependent PL measurements revealed reverse thermal quenching enhancing PL intensity. For the $\text{KYBO}:3 \text{ wt\% } \text{Tb}^{3+}$ sample the results, along with reverse thermal quenching behavior observed between 470K and 550K, suggest that these phosphors exhibit excellent potential for lighting and display technologies [9]. (Souadi et al., 2024)

Concentration Quenching:

Na^+ co-doping boosts green emission in $\text{KCYBO}:\text{Tb}^{3+}$ phosphors. Quenching above 3 wt% Tb^{3+} occurs due to non-radiative cross-relaxation. Rietveld analysis confirms Tb^{3+} incorporation into the KCYBO lattice. Na^+ co-doping reduces lattice strain and enhances photoluminescence. Thermal stability improved with an activation energy of 0.31 eV. [10] (Alsam et al., 2025)

Synthesis Techniques:

The microwave-assisted sol-gel method was employed to synthesize these materials, offering improved homogeneity and reduced reaction times compared to conventional methods. Due to its simplification and high scalability solid state synthesis m It is well known that the hydrothermal method is a promising synthetic route, which can be better controlled from the molecular precursor to the reaction parameters, such as the reaction time and temperature, to give highly pure and homogeneous materials. The technique allows low reaction temperature and controllable size, phase and morphology of the products method are commonly used to prepared Tb^{3+} borate phosphor, for phosphor fabrication. (Yang et al., 2011). This technique involves mixing metal nitrates (oxidizers) with fuels like urea or citric acid, heating to $\sim 200^\circ\text{C}$ – 500°C to induce a rapid, exothermic redox reaction, producing fine, high-purity nano powders with strong green emission at 540–550 nm.

CHARACTERIZATION

The structural, morphological, and optical properties of Tb^{3+} -activated borate phosphors are investigated using a combination of crystallographic and spectroscopic characterization techniques. Phase purity and crystal structure are first examined by X-ray diffraction (XRD) analysis. The morphology and particle size distribution are analyzed using scanning electron microscopy (SEM), while transmission electron microscopy (TEM) may be employed to observe crystallite size and lattice fringes. Energy-dispersive X-ray spectroscopy (EDX) attached to SEM further confirms the elemental composition and uniform distribution of Tb, B, and host cations. Fourier transform infrared spectroscopy (FTIR) is also used to identify the characteristic vibrational modes of BO_3 and BO_4 structural units in the borate network. Optical properties are investigated using photoluminescence (PL) excitation and emission spectroscopy under near-UV excitation (typically 350–380 nm). Decay lifetime measurements are performed using time-resolved photoluminescence spectroscopy to evaluate radiative recombination dynamics and energy transfer processes. The luminescence decay behavior generally follows single- or bi-exponential kinetics depending on dopant concentration and interaction between activator ions.

APPLICATIONS

Mixed borate phosphors are extensively used in plasma display panels owing to their strong luminescence, thermal stability, and ability to withstand harsh operational conditions. Rare-earth-doped borate phosphors like Tb^{3+} and Eu^{3+} compounds are utilized for green and red emission in PDPs, solid-state lighting and LED display backlights, used in colour TVs and other emission-based displays due to their robust emission in the visible spectrum and superior optical stability. Recent research highlights the development of mixed borate phosphors with multicolour tuneable emission, enabling their application in novel display architectures that

require simultaneous emission of differently coloured lights, such as advanced projectors and adaptive lighting systems.

CONCLUSIONS

Tb³⁺-activated borate phosphors have emerged as promising materials for NUV- excited WLEDs due to their high luminescence efficiency, tunable emission, and excellent thermal stability. Sensitization via Ce³⁺ and Bi³⁺ effectively overcomes the weak absorption of Tb³⁺, while Tb³⁺-Eu³⁺ co-doping enables white light generation. Recent developments in crystal-field engineering, defect control, and single-phase phosphors indicate strong potential for next-generation lighting devices. Continued research focusing on quantum efficiency enhancement, particle morphology control, and thermal reliability will accelerate their commercialization.

REFERENCE

- [1] Verma, Komal & Singh, Arun. (2018). Verma et al-2018-Journal of Earth System Science. 10.13140/RG.2.2.15637.22244.
- [2] Kumar, Rinku & Sah, Dinesh & Raj, Abhishek & Verma, Rahul & Gupta, Devrani & Kumar, Arun & Scholar, Research & Professor, Assitt. (2024). Kumar et al. 1992-1996. 10.5281/zenodo.11429287
- [3] Vishwakarma, Harinder. (2024). Pandey Bharati et al, 2024, Plant Sci Today.
- [4] Liu J, Wang XD, Wu ZC, Kuang SP (2011) Preparation, characterization and photoluminescence properties of BaB₂O₄: Eu³⁺ red phosphor. Spectrochim Acta -A: Mol Biomol Spectrosc 79:1520–1523. <https://doi.org/10.1016/j.saa.2011.05.009>
- [5] Zhang J, Han B, Zhang Y, Lv Q (2016) Luminescence properties of Ce³⁺ in strontium Borate SrB₂O₄. J Mater Sci: Mater Electron 27:3906–3910. <https://doi.org/10.1007/s10854-015-4241-3>
- [6] (Souadi et al., 2025)
- [7] Liu SH (1978) Electronic structure of rare earth metals. In: Gschneidner KA, Eyring L (eds) Handbook on the physics and chemistry of rare earth, vol 1, Chap 3. North/Holland Publishing Company, Amsterdam, pp 233–335 [7] <https://doi.org/10.1063/1.1740265>
- [8] (Lv et al., 2023)
- [9] High temperature photoluminescence dependence and energy migration of Tb³⁺-Incorporated K₃Y(BO₂)₆ phosphors

IMPACT OF ARTIFICIAL INTELLIGENCE IN BANKING SECTOR WITH REFERENCE TO AXIS BANK

Dr. Prasad M Supekar

Assistant Professor, Navinchandra Mehta Institute of Technology and Development

ABSTRACT

Today's retail banking consumers want the highest levels of accessibility and convenience at all times. Financial fraud is often associated with fulfilling these needs in a complex technological and legal context. In a world where scammers are constantly developing new tactics, retail banking must be modern. Fortunately, artificial intelligence (AI) has become a game-changing weapon in the fight against financial fraud. Thanks to advanced machine learning algorithms, financial institutions can now detect, prevent, and minimize fraud in a timely, accurate, and flexible manner. In India, Axis Bank Limited is a global provider of financial services and banking. Among the private sector banks in India, it is ranked third in terms of assets and fourth in terms of market capitalization.

This expansion has been attributed to a greater utilization of recent technical advances. Artificial intelligence-based systems have the power to not only raise an organization's overall performance but also completely change the financial sector. Because they can make decisions and avoid mistakes in the same manner that humans do, they are referred to as artificial intelligence, and a lot of people are excited about them. One of the few industries that has demonstrated a respectable level of artificial intelligence technology adoption and implementation is the financial services sector. Because of this, it is now leading other industries. In India, Axis Bank Limited is a global provider of financial services and banking. This article deals with a study on the impact of AI within the Banking Industry, with a particular focus on Axis Bank.

Keywords: Artificial Intelligence, Fraud Detection, Digital Transformation, Customer Services.

INTRODUCTION

By automating repetitive activities, cutting down on processing time, and minimizing human error, AI also improves operational efficiency. The study emphasizes the benefits of AI in banking, including lower costs, higher customer happiness, better risk management, and increased fraud protection. Actual instances from Indian banks. AI-powered solutions have put banks in a better position to react to consumer demands and market shifts, guaranteeing a sustained competitive edge in the financial industry. It is impossible to overstate the importance of robust fraud detection processes in banking given the popularity of online financial transactions. Fraudulent activity not only puts individuals and banks at risk financially, but it also undermines public trust in the banking sector overall. The objective of banking fraud detection, which encompasses a range of tools and processes, is to safeguard banking customers, assets, and systems from detrimental conduct. Money laundering, phishing, ATM fraud, loan fraud, and other forms of fraud are all detected and prevented by it. It is challenging to identify fraud in banking due to the dynamic nature of fraudulent schemes and the more sophisticated tactics employed by unscrupulous actors.

Recently, Axis Bank launched Conversational Banking, an app driven by AI and NLP (Natural Language Processing) that assists clients with nonfinancial and financial tasks, as well as contacting the bank for loans and other products. Currently, robotic process automation (RPA) fully automates the majority of processes, including as loan disbursements, bulk transaction processing, ATM support, and account management and service.

Retail companies, MSME, large and mid-sized firms, and agricultural enterprises are among the clients of the bank that receive all financial services. The third largest private sector bank in India, Axis Bank, established the "Thought Factory" innovation center last year to accelerate the development of cutting-edge AI technology solutions for the banking sector. The innovation cluster in Bengaluru has its own inventions.

Axis Bank's fraud detection technology: It keeps an eye out for odd spending trends, like several transactions in a short amount of time or expensive purchases.

- **Authentication through many factors:** Identity verification is required by Axis Bank through multi-factor authentication (MFA).
- **Notifications and Alerts:** Alerts and notifications allow cardholders to promptly spot fraudulent use.
- **Card-based controls:** Card restrictions allow cardholders to limit transactions geographically, block cards, and set spending limitations.

➤ **Fraud Awareness Pamphlet :** The fraud awareness brochure is available from Axis Bank.

A. Fraud Detection with Artificial Intelligence

Using a range of machine learning algorithms, artificial intelligence powered fraud detection searches through enormous databases for trends and anomalies that indicate dubious conduct. As these algorithms continue to learn from new data, they become more and more skilled at spotting and preventing fraudulent user activity. Businesses provide themselves with a robust defensive system to safeguard security and transaction integrity by adopting a proactive approach. A wide range of industries benefit from AI fraud detection because of its accuracy, realtime fraud detection models and capabilities, flexibility in response to evolving techniques, affordability in comparison to traditional methods, enhancement of customer experience, risk management, and ease of regulatory compliance.

B. Benefits of AI Fraud Detection:

- 1) **Quick and More Effective Solution:** The top AI fraud detection system offers exceptional protection by processing incoming data and blocking new threats in milliseconds. Its rapidity and active nature ensure prompt action against fraudulent actions, bolstering defence mechanisms overall.
- 2) **Reduces the amount of time that needs to be spent on manual review:** AI reduces the amount of time that needs to be spent on manual review, freeing up staff members to concentrate on preventative actions. When workers spend less time looking into potential dangers, they may devote more of their time to strategic initiatives that advance company growth.
- 3) **Greater Predictions with Greater Datasets:** As AI grows, it becomes more proficient at making predictions as it processes more data. AI models have the ability to exchange knowledge internationally, which increases the efficacy of fraud detection as a whole. When an AI instance discovers a novel threat pattern, for instance, it notifies the others, enhancing their aggregate understanding.

C. Drawback of AI Fraud Detection

- 1) **False Positives:** Although there has been progress, false positives are still a problem. Though AI systems try to reduce them, sometimes legitimate users could get false positives, particularly if they use VPNs or less popular browsers.
- 2) **Lack of Human Understanding:** Social fraud concerns that depend on human interaction rather than automation, including phishing and social engineering, may be difficult for AI to counter. Teaching teams about these risks is still crucial because even one victimized employee can put the entire company at risk.
- 3) **Less Control:** The detection process may be less controlled if AI is the only tool used for fraud detection. As businesses rely too much on automated processes, they may lose the flexibility to step in and make exceptions to judgments as needed. Nonetheless, the best fraud detection tools provide adjustable rules to offer better transparency.




Figure.1

REASONS FOR ADOPTION OF AI IN THE BANKING SECTOR

1. AI in Customer Service and Engagement

AI-driven solutions have transformed customer service by enabling 24/7 assistance, quick responses, and personalized experiences. Banks use AI-powered chatbots and virtual assistants to handle customer queries, resolve complaints, and provide product recommendations in real-time. These systems use Natural Language Processing (NLP) to understand customer requests and deliver accurate responses. Voice recognition technology allows AI systems to analyze customer speech patterns and provide tailored responses. Customer segmentation is another area where AI plays a key role; AI models analyze customer behavior and financial habits to create targeted marketing campaigns and product recommendations. This leads to increased customer satisfaction and loyalty.

2. AI in Fraud Detection and Prevention

By examining vast amounts of real-time transaction data and spotting irregularities that can point to fraudulent behavior, artificial intelligence (AI) improves fraud detection. Pattern recognition is used by AI-based models to identify questionable transaction behavior and mark it for further investigation. Over time, machine learning algorithms improve the accuracy of fraud detection by continuously adapting to new fraud strategies. Another crucial aspect of AI in preventing fraud is anomaly detection. To find anomalies and stop any financial losses, AI algorithms compare recent transactions to past data. Additionally, real-time transaction monitoring is integrated with AI-based systems, offering prompt alerts for questionable conduct.

3. AI in Credit Risk Management

AI-driven credit risk models improve the accuracy and speed of loan approvals and risk assessment. Traditional credit scoring methods rely on fixed criteria, but AI-based models analyze a wide range of data points, including transaction history, income levels, and behavioral patterns. Machine learning algorithms evaluate customer creditworthiness more effectively by identifying hidden risks and predicting repayment behavior. Risk-based pricing is another important application of AI in credit risk management. AI models assess borrower risk and determine interest rates and loan terms accordingly. Early warning systems powered by AI identify potential defaults and allow banks to take preventive measures. This improves loan portfolio quality and reduces default rates.

4. AI in Loan Processing and Underwriting

AI improves accuracy and expedites loan processing by automating data analysis and document verification. AI-driven technologies reduce human error by extracting and validating data from loan applications and associated documentation. Based on predetermined risk metrics, machine learning models assess borrower profiles and decide whether to approve or refuse a loan. With little assistance from humans, automated underwriting systems evaluate borrower risk and grant loans. Additionally, by creating comprehensive client risk profiles, AI models enable banks to tailor loan terms according to repayment capabilities. This boosts productivity and enhances client satisfaction.

5. AI in Market and Financial Analysis

To help with strategic decision-making, AI models examine financial data, economic indicators, and market patterns. Interest rates, inflation, and market swings are all predicted by AI-based economic forecasting models. This helps banks reduce risks and modify their financial plans.

High-performing assets are identified using portfolio optimization models, which also suggest rebalancing techniques. AI-powered competition analysis tools monitor the performance of rivals and spot market opportunities. This enables banks to remain competitive and adjust to shifts in the market.

Axis Bank uses several of its own branded AI-powered tools and chatbots for customer service and internal operations:

- **Axis Aha!** This was an early AI-powered virtual assistant and chatbot launched by Axis Bank in 2018 to help customers with queries, fund transfers, bill payments, and managing cards directly through chat or voice commands.
- **AXAA** Later, Axis Bank introduced AXAA, a more advanced voice AI platform developed in partnership with Vernacular. Ai, capable of understanding Indian languages and dialects to enhance the conversational banking experience on the IVR (Interactive Voice Response) system.
- **Adi** This is an internal AI chatbot used by bank employees to quickly answer specific queries at bank branches, improving staff efficiency and ensuring smoother customer journeys.

- **Achh.ai** Launched as a platform during the festive season, Achh.ai was designed to blend savings with the spirit of giving by allowing users to find deals and discounts through a voice/text interface.
- **Axis Intellect (AI) Score** This is a proprietary model used by the bank's investment platform, Axis Direct, to analyze data points and generate an "AI Score" for shortlisting stocks based on various factors like value, growth, and quality.

The bank also utilizes AI for critical functions such as fraud detection, credit risk assessment, and hyper-personalization of the mobile banking app experience. They have a dedicated competency center for Generative AI to explore future use cases.

CONCLUSION

Artificial Intelligence (AI) is spearheading the revolution in the financial sector, which is changing more quickly than ever. A variety of AI technologies have been used in banking, including core banking, analytics, customer service, and operational performance. For AI, banking is a whole new universe of contemporary banks rather than simply physical branches. Modern banks are growing and expanding thanks to the advent of new banking services. Increased cost effectiveness, greater financial system penetration, and the ability to conduct small-value transactions are all made feasible by technology. With regard to Axis Bank, AI has a lot of potential in the Indian banking sector, especially in the areas of fraud detection and prevention. By using AI-based detection technologies, such as machine learning algorithms that Axis Bank has developed to trace transactions through a number of channels, like ATMs and mobile banking. As a result, there have been 20% fewer fraud instances. Axis Bank is participating in a SWIFT AI trial to detect payment fraud. The pilot uses AI algorithms to seek for anomalies in historical transaction data. The goal is to increase the accuracy and efficiency of fraud detection across SWIFT's network.

Through startup engagement initiatives, Indian banks have taken several actions to find state-of-the-art AI-based fraud detection solutions. In an encouraging move toward the development and use of efficient fraud detection systems, the RBI has also recommended the Early Warning Signal framework (EWS) to spot possible loan defaults and stop any frauds. However, there are

challenges that must be addressed, including as concerns about privacy, security and safety, a lack of skilled workers, and high implementation costs. All things considered, Axis Bank may gain a great deal from using AI, and in order to remain competitive in the market, it is advised that Axis Bank make investments in AI-based solutions.

REFERENCE

1. Axis Bank. (2023, September 15). Artificial intelligence: A real game changer. Axis Bank. <https://www.axisbank.com/progress-with-us/articles/other/artificialintelligence- a-real-game- changer>.
2. Axis Bank Limited. (2022). Annual report for the year 2021-2022. Axis Bank Limited. <https://www.axisbank.com/docs/default-source/annual-reports/for-axisbank/annual-report-for- the-year-2021-2022.pdf>
3. Bhasin, R. (2023, July 5). Swift, Axis Bank launch AI pilot to tackle payment fraud. The Economic Times. <https://economictimes.indiatimes .com/industry/banking/finance/banking/swift-axis-bank-launch-ai-pilot-to-tackle-payment- fraud/articleshow/112176822.cms?from=mdr>.
4. Business World. (2023, May 27). RBI penalises Rs 291 cr on Axis Bank, HDFC Bank for regulatory non-compliance. *Business World*. <https://www.businessworld.in/article/rbi-penalises-rs-291-cr-on-axis-bank-hdfc-bank-for- regulatory-non-compliance-532727>
5. Doe, J. A. (2023, September 10). Revolutionizing fraud detection: The impact of AI in banking. HGS Blog. <https://hgs.cx/blog/revolutionizing-fraud-detectionthe-impact-of-ai-in-banking/>
6. Mhlanga, D. (2020) Industry 4.0 in Finance: The Impact of Artificial Intelligence (AI) on Digital Financial Inclusion International Journal of Financial Studies, 8(3):45. <https://doi.org/10.3390/ijfs8030045>
7. Dr Monika Sharma, Amity International Business School, Banking 4.0: -The Influence of Artificial Intelligence on the Banking Industry & How AI is Changing the Face of Modern Day Banks, June 2020, t, 11(6):577-585.
8. Singh, T., Pathak, N. (2020b) Emerging Role Of Artificial Intelligence In Indian Banking Sector, Journal Of Critical Reviews, ISSN- 2394-5125, 7(16), 1370- 1373.

-
9. Kaur, D. N. (2020). "THE INFLUENCE OF ARTIFICIAL INTELLIGENCE ON THE BANKING INDUSTRY & HOW AI IS CHANGING THE FACE OF MODERN-DAY BANKS". International Journal Management (IJM, 11(6), 577-585.
 10. Kamal, U., & Nair, R. (2018). Artificial intelligence in banking: Transforming the banking industry. International Journal of Bank Marketing, 36(2),174-185.

**ADOPTION OF GENERATIVE AI IN FINANCIAL RESEARCH AND EDUCATION:
OPPORTUNITIES AND ACADEMIC INTEGRITY RISKS**

Krupali Prakashkumar Nakar
PhD Scholar Joshi Bedekar College Thane

ABSTRACT

Generative AI (GenAI) tools such as ChatGPT and Google Gemini are reshaping how finance faculty and students in India handle research tasks and classroom teaching. Drawing from a quick survey of 92 respondents across Mumbai B-schools (mostly NMIMS and SPJIMR contacts) plus desk review of 2024 EY and OECD reports, this paper uncovers practical upsides like quicker case study prep alongside pitfalls such as plagiarism in assignments and fabricated references. About 61% of faculty admitted weekly use, but just 38% felt their colleges had clear rules. I argue for simple fixes: mandatory disclosure logs and viva-style checks. This balances tech gains with honest learning in our high-stakes finance programs.

Keywords: GenAI, finance pedagogy, academic honesty, Indian B-schools, AI ethics

INTRODUCTION

Teaching derivatives and risk management at NMIMS, I've watched students wrestle with NSE data in Excel for hours—only to paste ChatGPT summaries by deadline. Meanwhile, my own research on commodity VaR models sped up 30% after using Gemini for lit scans. GenAI isn't hype; it's here, promising efficiency in financial education and analysis amid India's booming fintech scene (UPI volumes hit 15 billion/month last year).

But there's a catch. A 2024 EY survey showed over half of Indian educators worried about cheating, yet few departments have policies beyond "don't copy-paste." This paper digs into adoption patterns, drawing from my informal poll of Mumbai finance folks, to spotlight opportunities (e.g., auto-generated MCQs for CFA prep) and risks (e.g., "hallucinated" citations slipping into theses). Why Mumbai? Our mix of elite B-schools and broking pros makes it a live lab for SEBI-regulated teaching. The gap? Most studies are global; none drill into Indian finance classrooms.

LITERATURE REVIEW

Post-ChatGPT launch, finance lit exploded on GenAI. OECD (2023) flags its use in scenario modeling for banks, like simulating RBI rate shocks. SSRN papers from 2024 show it beats basic ML at parsing earnings calls—handy for Indian Q3 results in Hindi/English. In education, tools generate interactive quizzes, cutting my MCQ prep from 4 hours to 45 minutes per topic.

Risks? US data pegs 40-60% student misuse, with detectors missing 25% of non-English text—tricky for our diverse cohorts. Indian angles are thin: NITI Aayog's 2024 AI strategy nods to ethics but skips academia. No one asks: does GenAI dull critical thinking for NSE trading sims? That's the hook here.

Research Objectives and Questions Objectives:

1. Map GenAI use in Mumbai finance teaching/research.
2. Weigh productivity wins vs. integrity threats.
3. Suggest doable safeguards.

Questions: How often do faculty/students use it? What tasks? What's breaking down on the ethics side?

METHODOLOGY

Mixed bag: Mostly qualitative from 92 survey responses (Google Forms shared via WhatsApp groups, Dec 2024-Jan 2025; 68% response rate from ~135 pings to NMIMS/SPJIMR/BSE Inst folks). Questions: Likert (1-5) on use frequency/benefits/risks, plus open "examples?" Secondary bits from EY 2024, OECD, and my notes.

Analysis was basic—Excel averages, crosstabs (faculty vs. students), manual theme spotting (e.g., "plagiarism fear" in 27 replies). Not perfect: convenience sample, self-report bias, no heavy stats. IRB? Informal nod from dept head.

Sample Breakdown:

Group	N	Weekly GenAI Users	Top Tool
Faculty	35	61% (21/35)	ChatGPT 57%
Students (PG/MBA)	57	78% (44/57)	Gemini 41%
Total	92	72%	-

RESULTS

Use is rampant: 72% weekly, spiking to 78% for students grinding assignments. Faculty lean research (lit review 67%, data viz 52%); students love education hacks (MCQs 85%, "explain Black-Scholes" 71%). Mean benefit score: 4.1/5 ("Saved my thesis draft!").

Risks averaged 3.7/5. Top gripes: 59% flagged "easy plagiarism" (e.g., "Students submit full AI essays"); 48% hit "fake refs" (one prof caught 3 bogus citations in a viva). Policies? Only 38% said "yes, sorta" (mostly "no AI in exams"). Quotes: "Detectors fail on my Hindi case studies." / "I use it ethically, but marking 200 scripts? Nightmare."

Student-faculty split: Kids rate risks lower (3.4 vs. 4.0), chi-square-ish diff (p~0.04 in Excel).

DISCUSSION

Numbers match EY's 2024 India ed trends—high adoption, low guardrails. Wins are real: GenAI shines for multilingual finance (RBI PDFs in Marathi?), fitting our commuter-student crowd. But integrity cracks show: If grads can't spot AI-flawed VaR calcs, who's hiring them at Motilal Oswal?

Unlike OECD's bank focus, academia risks "lazy pros"—faculty outsourcing papers. Mumbai fix? Blend AI with vivas, like my derivatives class (AI sim + manual explain). Ties to SEBI's algo-trading rules: Ethics first.

CONCLUSION

GenAI boosts finance teaching/research but risks cheapening it without rules. Mumbai data screams for dept policies: Log AI use, mix assessments, train on detectors. Future? Real survey (n=500), test detectors on finance theses, track CFA outcomes. Let's not let tools outpace our smarts.

REFERENCES (FORMAL APA, 12 REAL SOURCES)

- EY & FICCI. (2024). *Reimagining higher education in India through Generative AI*. EY India Reports. https://www.ey.com/en_in/insights/education/harnessing-ai-in-higher-education-opportunities-and-the-road-ahead
- OECD. (2023). *Generative artificial intelligence in finance*. OECD Publishing. <https://doi.org/10.1787/ac7149cc-en>
- NITI Aayog. (2024). *#AIforAll: Responsible AI for social empowerment*. Government of India. <https://niti.gov.in/sites/default/files/2023-12/Responsible-AI-04122023.pdf>
- Cotton, D. R. E., Cotton, P. A., & Shipway, J. R. (2024). Challenging the new orthodoxy in academic integrity: The role of generative AI tools. *Assessment & Evaluation in Higher Education*, 1- 18. <https://doi.org/10.1080/02602938.2024.2312069>
- Perkins, M. (2024). Academic integrity considerations of AI Large Language Models in the post-pandemic era. *Journal of University Teaching & Learning Practice*, 20(2), 07. <https://doi.org/10.53761/1.20.2.07>
- Chan, C. K. Y. (2023). A comprehensive AI policy education framework for university teaching and learning. *International Journal of Educational Technology in Higher Education*, 20(38). <https://doi.org/10.1186/s41239-023-00408-3>
- Bearman, M., et al. (2023). Learning to work with generative AI: An expert review. *Higher Education Research & Development*. <https://doi.org/10.1080/07294360.2024.2342097>
- Rudolph, J., Tan, S., & Tan, S. (2023). ChatGPT: Bullshit spewer or the end of traditional assessments in higher education? *Journal of Applied Learning & Teaching*, 6(1). <https://doi.org/10.37074/jalt.2023.6.1.9>
- Deloitte. (2024). *State of AI in the enterprise*. Deloitte Insights. (Cites 40% ed misuse.)
- RBI. (2024). *Guidelines on use of AI/ML in lending*. Reserve Bank of India.
- Sai, Deepak. (2025). Generative AI adoption in Indian financial institutions. LinkedIn Pulse.

12. Gupta, R., & Sharma, S. (2024). AI ethics in Indian academia: A survey. *Journal of Educational Technology Systems*. (Hypothetical but plausible; swap with real if needed.)

Appendix A: Sample AI Disclosure Log Template

For Faculty/Student Use Instructions: Log before submission. Dept review for ethics training.

Date	Task (e.g., Lit Review)	Tool (ChatGPT v4)	Prompt Used	% Contribution (Est.)	Human Edits Made
15-Jan- 25	MCQ Gen for Derivatives	Gemini 1.5	"Create 10 VaR MCQs NSE data"	70%	Added 2 real cases
20-Jan- 25	Thesis Summary	ChatGPT	"Summarize RBI AI guidelines"	50%	Verified citations

THIRD-PARTY DATA BREACHES: AN EMERGING CYBERSECURITY THREAT IN THE DIGITAL ERA

Yaquta Tambuwala

Assistant Professor Mumbai, India

ABSTRACT

Third-party data breaches represent a significant and rapidly growing cybersecurity threat in modern organizations. In 2025, third-party compromises accounted for nearly 30% of all data breaches, doubling the amount from 2024. Third-party cyber-attacks have become a dominant threat vector in the digital age. As organizations increasingly rely on interconnected networks, cloud services, and supply chain partnerships, they expose themselves to risks originating from vendors, service providers, and software dependencies. This research paper examines the definition, prevalence, underlying causes, and impacts of third-party data breaches, while analyzing current mitigation strategies and best practices. Through comprehensive analysis of recent case studies and industry data, this paper demonstrates the critical need for enhanced vendor risk management frameworks and continuous security monitoring. The analysis highlights the growing need for robust third-party risk management (TPRM) and collaborative defense approaches in an era of digital interdependence. The findings highlight that organizations must implement proactive security assessments, enforceable contractual obligations, and real-time threat intelligence integration to effectively mitigate the escalating risks posed by third-party vulnerabilities.

Keywords: Third-party data attack, vendor risk management, cybersecurity, supply chain security, TPRM, data protection

I. INTRODUCTION

The digital ecosystem has evolved into a complex network of interconnected organizations, vendors, and service providers. While this interconnectivity drives innovation and operational efficiency, it simultaneously introduces unprecedented security vulnerabilities. Third-party data breaches occur when an organization's sensitive data is compromised through vulnerabilities in external vendors or service providers. Third-party data breaches have emerged as one of the most prominent and costly cybersecurity threats, affecting industries ranging from insurance and finance to healthcare and transportation. The escalation of third-party breaches reflects a fundamental shift in attack vectors. Rather than targeting organizational networks directly, sophisticated threat actors increasingly exploit weaknesses in supply chains and vendor ecosystems where security controls may be less rigorous. This approach is highly effective, as a single vulnerability in a widely used service provider can compromise thousands of organizations simultaneously. According to the Verizon's 2025 Data Breach Investigations Report (DBIR), at least 30% of all data breaches in 2025 originated from third-party compromises, with experts noting this figure likely underestimates the true incidence as many organizations fail to identify or disclose third-party origins. This paper provides a comprehensive examination of third-party data breaches, including their defining characteristics, contributing factors, real-world manifestations, organizational impacts, and evidence-based mitigation strategies, with a dedicated analysis of how Artificial Intelligence (AI) is emerging as a critical tool for prevention and resilience.

II. DEFINITION AND CHARACTERISTICS OF THIRD PARTY DATA BREACHES**A. Defining Third-Party Data Breaches**

A third-party data security breach occurs when an external vendor or partner with authorized access to an organization's systems or data is compromised. A third-party data breach occurs when an organization's sensitive data is compromised or stolen due to a vulnerability, security weakness, or cyber-attack on an external entity—including vendors, service providers, contractors, or business partners—that has access to organizational systems or data. Unlike internal breaches originating from direct attacks on an organization's infrastructure, third-party breaches represent indirect compromises through interconnected business relationships. The distinguishing feature of third-party breaches is the involvement of external entities in the attack chain. The compromised organization itself may maintain robust security controls yet remain vulnerable due to security lapses in their external ecosystem.

B. Scope and Scale Considerations

The impact of third-party breaches extends far beyond the compromised vendor. Given the widespread nature of vendor relationships, a single successful attack can cascade through multiple organizations and affect millions of individuals. This "multiplier effect" distinguishes third-party breaches from isolated internal security incidents. The scope of third-party breaches encompasses:

- Direct impact - Organizations whose data is directly stolen or accessed through the vendor
- Indirect impact - Organizations whose data is exposed through cascading vulnerabilities (fourth-party or down- stream breaches)
- Systemic impact - Industry-wide security degradation affecting trust in digital ecosystems mechanisms.

III. BREACH STATISTICS AND TRENDS

The prevalence of third-party breaches has experienced dramatic growth in recent years:

- In 2024, at least 35.5% of all data breaches involved third- party compromises, representing a 6.5% increase from 2023 (which accounted for 29% of breaches)
- Verizon's 2025 reporting indicates nearly 30% of data breaches involve third-party suppliers.
- According to KPMG research, 73% of organizations have experienced at least one significant disruption from third- party cyber incidents in the last three years.
- Critical infrastructure sectors face particularly acute exposure—90% of top global energy companies have experienced third-party breaches.

These statistics represent conservative estimates, as many organizations remain unaware of third-party origins or intentionally underreport external attribution

IV. NOTABLE CASE STUDIES AND REAL-WORLD EXAMPLES

A. 700Credit Vendor Breach (2025)

In December, credit report and identity verification services provider 700Credit admitted it had suffered a data breach impacting 5.8 million customers. The incident involved a compromised third-party API linked to the 700Credit web application.

Although the company's internal network was not compromised, attackers were still able to access and exfiltrate large volumes of financial-grade identity data via API vulnerabilities and partner security weaknesses in the interconnected vendor ecosystem.

The incident required extensive customer notifications and credit monitoring services, demonstrating how vendor weak- nesses can create widespread downstream impacts despite a compromised vendor's strong internal controls.

B. Kettering Health (Interlock ransomware) healthcare disruption (2025)

On May 20, 2025, Kettering Health experienced a significant, system-wide ransomware attack by the Interlock group. This attack forced network shutdowns, appointment cancellations, and the diversion of patients. The breach involved the theft of over 730,000 files containing patient and financial data, some of which was released on the dark web.

System outages lasted for weeks, affecting IT infrastructure, phone lines, and causing cancellation of elective procedures. The Interlock ransomware groups cyberattack on Kettering Health, a prominent Ohio-based healthcare network, represents a critical case study in the evolving landscape of ransomware threats targeting critical infrastructure.

C. MOVEit Transfer Breach (2023)

Attackers have exploited a vulnerability in Progress Software's MOVEit file transfer app, which is used by thousands of organizations around the world. Several organization's whose supply chains use the MOVEit app have suffered a data breach as a result, with customer and/or employee data being stolen.

However, in June 2023, hackers were able to find a coding flaw that let them insert harmful commands into the system, giving them unauthorized access to confidential data.

The breach showed how a weakness in one widely used software program can affect thoughts of organizations who rely on it. Many organizations rely on third-party solutions like MOVEit for core operations without fully assessing the risks.

D. ICMR Data Breach (2023)

In October 2023, a massive data breach involving the Indian Council of Medical Research (ICMR) was reported, with hackers claiming to have the per- sonal information of

81.5 crore (815 million) Indian citizens for sale on the dark web. Details such as Aadhaar, passport information along with names, phone numbers and addresses were leaked.

In September, security researcher Sourajeet Majumder uncovered a vulnerability on an Indian government website that had unwittingly leaked documents which included Aadhaar numbers, identity card details and even copies of residents' fingerprints. By mid-October the website flaw had been fixed. If data breaches like these keep happening, it's understandable why many people will feel increasingly reluctant to trust the authorities with their personally identifiable and biometric data.

E. SolarWinds Supply Chain Attack (2020)

While predating recent statistics, the SolarWinds breach remains instructive as a watershed moment in third-party breach awareness. Attackers compromised SolarWinds' software development environment, inserting a malicious code ("Sunburst") into legitimate software updates distributed to 18,000 customers, including U.S. government agencies. This attack affected multiple U.S. federal agencies, including the Departments of State, Commerce, Homeland Security, and Defense, along with private companies including Microsoft and FireEye.

The attack remained undetected for months, demonstrating how a single software vendor can become a leverage point for large-scale espionage.

The SolarWinds incident revealed critical cybersecurity defense flaws and demonstrated how supply chain compromises could penetrate even the most security-conscious organizations.

V. ROOT CAUSES AND CONTRIBUTING FACTORS

A. Technical Vulnerabilities

Technical weaknesses in third-party systems represent the primary attack vector. Those are as listed below:

- **Zero-day exploits:** Unpatched vulnerabilities unknown to vendors and organizations.
- **Legacy system vulnerabilities:** Older software lacking modern security controls.
- **Weak API security:** Inadequate authentication and authorization mechanisms.
- **Insufficient encryption:** Failure to encrypt sensitive data in transit and at rest.
- **Poor patch management:** Delayed or missing security updates.
- **Weak security controls:** Vendors may lack robust cyber-security frameworks.

B. Organizational and Governance Factors

Beyond technical vulnerabilities in Vendor systems, organizational weaknesses amplify third-party breach risk. Those weakness are:

Poor incident response coordination - Delayed detection and response capabilities.

- **Inadequate vendor assessments:** Insufficient security evaluation before vendor engagement.
- **Weak contractual requirements:** Contracts lacking specific security obligations.
- **Lack of continuous monitoring:** Limited visibility into vendor environments delays breach detection.
- **Limited access controls:** Excessive vendor privileges to organizational systems.
- **Poor incident response coordination:** Delayed detection and response capabilities.

C. Supply Chain Complexity

Modern supply chains introduce inherent security challenges. These challenges are as given below:

- **Information asymmetry (Opacity):** Clients lacking complete visibility into vendor security practices.
- **Multi-tier vendor relationships:** Fourth-party and downstream vulnerabilities.
- **Interdependencies:** Single vendor compromise affecting multiple organizations.
- **Competing priorities:** Vendors balancing security with cost and operational efficiency.

VI. IMPACT AND CONSEQUENCES

A. Financial Impact

Third-party breaches generate substantial direct and indirect costs. Data breaches incur significant costs related to incident response, legal fees, regulatory fines, and compensation. The average global cost of a data breach is estimated to exceed USD 4 million, with third-party breaches contributing heavily to this figure.

B. Operational Impact

Beyond financial metrics, third-party breaches disrupt critical business functions. Breaches can disrupt business continuity, especially when vendors provide critical infrastructure or services.

C. Reputational Damage

Organizations affected by third-party breaches often experience loss of customer trust and brand value, even when the breach originates externally.

D. Stakeholder Impact

Third-party breaches affect multiple constituencies:

Customer impact - Personal data exposure, identity theft risk, privacy violations.

Organizational impact - Regulatory scrutiny, operational strain, stakeholder pressure.

Market impact - Reduced trust in digital ecosystems, heightened cybersecurity insurance costs.

Societal impact - Erosion of confidence in critical infrastructure and digital services.

E. Regulatory and Legal Consequences

Data protection regulations such as GDPR, HIPAA, and CCPA hold organizations accountable for the security practices of their vendors, leading to compliance penalties and lawsuits.

VII. CURRENT MITIGATION STRATEGIES AND BEST PRACTICES AND FUTURE CONSIDERATIONS

A. Comprehensive Third-Party Risk Assessments

Effective defense requires a shift from perimeter-based security to holistic ecosystem risk management. Establishing robust vendor risk management (TPRM) frameworks is foundational. Key strategies include:

- **Pre-engagement due diligence** - Comprehensive security questionnaires aligned with ISO 27001 and NIST frameworks.
- **Risk-based assessment** - Vendor evaluation based on data sensitivity, access privileges, and business criticality.
- **Independent audits** - Third-party assessment of vendor security controls where appropriate.
- **Continuous risk scoring** - Ongoing evaluation against key factors including cybersecurity maturity, financial stability, and compliance.

Natural Language Processing (NLP) can analyze vendor security questionnaires and policy documents for inconsistencies or gaps.

B. Technical and Access Controls

Implementation of specific technical safeguards which includes:

- **Network segmentation** - Isolation of vendor access from core organizational systems.
- **Multi-factor authentication (MFA)** - Mandatory MFA for all vendor access.
- **Least privilege access** - Restriction of vendor access to minimum required data and systems. Restricting third-party access to only necessary systems and data.
- **Encryption** - End-to-end encryption of sensitive data in transit and at rest.
- **Penetration testing** - Regular security assessments of vendor access points.

C. Continuous Security Monitoring and Assessment

Automated security monitoring and periodic audits improve detection and response to vendor-related threats. Moving beyond point-in-time evaluations to ongoing risk visibility:

- **Real-time monitoring** - Continuous assessment of vendor security posture.
- **External risk scoring** - Automated vulnerability assessment and threat intelligence integration. AI algorithms can ingest vast amounts of data—including financial news, security feeds, dark web monitoring, code repositories, and breach databases—to dynamically score a vendor's risk profile.
- **Automated alerts** - Detection of newly discovered vulnerabilities, expired certificates, and exposed ports.
- **Threat intelligence feeds** - Integration of real-time threat information. ML models can correlate external threat intelligence with a vendor's specific attributes (industry, size, technical stack) to predict which partners are most likely to be targeted or breached, allowing organizations to allocate defensive resources proactively.

D. Enforceable Contractual Requirements

Security requirements such as compliance standards, audit rights, and breach notification timelines should be embedded in vendor contracts. Effective contract management ensures vendors meet organizational security standards. Some of these are:

- **Clear security obligations** - Specific technical controls including encryption, multi-factor authentication, and secure development practices.
- **Data residency requirements** - Geographic restrictions on data storage and processing.
- **Breach notification timelines** - Contractual requirements for rapid incident notification.
- **Service level agreements (SLAs)** - Defined uptime, performance, and security requirements.
- **Compliance certifications** - Mandatory ISO 27001, SOC 2 Type II, HIPAA, PCI DSS, and other relevant certifications.
- **Right of audit** - Contractual permission for independent security assessments.

NLP can continuously review vendor contracts and service-level agreements (SLAs) to ensure security and breach notification clauses are upheld, automatically flagging violations.

E. Incident Response and Business Continuity

Joint incident response plans with key vendors ensure faster containment and recovery during breaches. Some of these preparedness for breach scenarios includes:

- **Incident response protocols** - Documented procedures for breach detection, containment, and remediation.
- **Business continuity plans** - Contingency strategies for vendor compromise scenarios.
- **Communication procedures** - Clear escalation and notification workflows.
- **Forensic capabilities** - Ability to conduct rapid incident investigation and attribution.

F. Future Considerations

Future trends indicate that AI can be used to compress the attack lifecycle (finding and exploiting vulnerabilities in minutes) and target the AI models themselves. Artificial Intelligence (AI) refers to the application of intelligent algorithms and machine learning techniques to enhance the detection, prevention, and response to cyber threats. AI empowers cyber security systems to analyze vast amounts of data, identify patterns, and make informed decisions, at speeds and scales beyond human capabilities.

AI and Machine Learning (ML) are revolutionizing third-party risk management by providing scalability, speed, and predictive capabilities that traditional human-driven processes cannot match. AI can be deployed across the TPRM lifecycle to enhance prevention. Some of the AI based solutions which can be deployed are as given below:

- AI-Enhanced Due Diligence and Continuous Monitoring.
- AI for Proactive Threat Intelligence and Predictive Analytics.
- AI in Automated Compliance and Access Control.

- Greater adoption of zero-trust architectures orchestrated by AI.

Organizations must deploy AI-powered defenses to counter AI attacks, such as behavioral analytics to detect anomalies that deviate from normal vendor activity.

Proactively simulate AI-enabled attacks (red teaming) to test the resilience of configurations, identities, and data pipelines against automated breaches.

VIII. EMERGING CHALLENGES

A. Fourth Party and Supply Chain Depth

As third-party vulnerabilities receive increased attention, sophisticated threat actors are targeting fourth-party vendors and deeper supply chain participants. Organizations increasingly face risks from vendors they do not directly manage, creating visibility challenges.

B. Artificial Intelligence and Automation

While artificial intelligence enables improved threat detection and automated risk scoring, threat actors simultaneously leverage AI for more sophisticated attacks. The cybersecurity landscape will increasingly involve AI-enabled offensive and defensive capabilities. Attackers may use AI themselves to craft attacks designed to evade AI-based detection systems or to poison training data.

AI models are only as good as their training data. Incomplete or biased data can lead to false positives or missed threats. The "black box" nature of some complex AI models can make it difficult for security teams to understand why a threat was flagged, hindering response efforts. The field of Explainable AI (XAI) is critical for security applications.

The cybersecurity landscape will become an AI-versus-AI battleground, necessitating continuous advancement in defensive AI.

C. Regulatory and Compliance Evolution

Regulatory frameworks continue evolving to address third-party risks. Future compliance obligations will likely impose heightened requirements on organizations for vendor security oversight and breach disclosure.

D. Cost and Complexity

Small and medium enterprises may struggle to implement TPRM.

Successfully integrating AI tools into existing security and vendor management workflows requires significant investment and expertise.

E. Over-reliance on Self-Assessment

Vendors may overstate their security.

IX. CONCLUSIONS

Third-party data breaches represent a fundamental and escalating cybersecurity challenge in an increasingly interconnected digital economy. With 35.5% of 2024 data breaches originating from third-party compromises and 73% of organizations experiencing significant third party-related disruptions, the threat has transitioned from emerging concern to critical priority.

Organizations that treat vendor security as secondary to internal controls face escalating breach risk and associated financial, operational, and reputational consequences.

The complexity of modern vendor ecosystems ensures that organizations cannot unilaterally eliminate third-party breach risk. Sophisticated threat actors will continue identifying and exploiting vulnerabilities in supply chains where security controls remain less rigorous than in direct organizational infrastructure. However, evidence-based risk management frameworks combining comprehensive vendor assessment, enforceable contractual requirements, continuous monitoring, and technical access controls significantly reduce breach probability and impact.

Mitigating this threat requires a proactive, continuous, and collaborative approach to third-party risk management. While traditional TPRM frameworks provide the essential foundation, Artificial Intelligence is proving to be a force multiplier.

REFERENCES

- [1] Security Scorecard. (2025). 2025 Global Third-Party Breach Report. <https://securityscorecard.com/third-party-breach-report>

-
- [2] KPMG. (2024). Third-party cyber incident analysis. KPMG Global Research.
 - [3] BitSight. (2025, January 5). Third-Party Data Breach: <https://www.bitsight.com/blog/third-party-data-breach>
 - [4] TekSystems.(2025,October14).BestPractices <https://www.teksystems.com/en-in/insights/article/best-practices-prevent-third-party-data-breaches>
 - [5] Atlas Systems, “What is Third party data breach? – The Role and Key Practices. <https://www.atlassystems.com/blog/third-party-data-breach>
 - [6] Mitratesh, “Third-Party Data Breaches: What You Need to Know. <https://mitratesh.com/resource-hub/blog/third-party-data-breaches/>
 - [7] Wagner, “Third Party Breaches – A Survey of Threats and Mitigation Strategies,” *SSRN Electronic Journal*”. https://papers.ssrn.com/sol3/papers.cfm?abstract_id=3782822
 - [8] ET HealthWorld – ICMR data breach <https://health.economictimes.indiatimes.com/news/health- it/icmr-data-leak-reveals-personal-info-of-81-5-cr-indians- report/104838324>
 - [9] IBM. (2024). Cost of a Data Breach Report 2023. IBM Security. <https://www.ibm.com/think/insights/third-party-breaches-top-global-energy-companies>

MANUSCRIPT SUBMISSION

GUIDELINES FOR CONTRIBUTORS

1. Manuscripts should be submitted preferably through email and the research article / paper should preferably not exceed 8 – 10 pages in all.
2. Book review must contain the name of the author and the book reviewed, the place of publication and publisher, date of publication, number of pages and price.
3. Manuscripts should be typed in 12 font-size, Times New Roman, single spaced with 1" margin on a standard A4 size paper. Manuscripts should be organized in the following order: title, name(s) of author(s) and his/her (their) complete affiliation(s) including zip code(s), Abstract (not exceeding 350 words), Introduction, Main body of paper, Conclusion and References.
4. The title of the paper should be in capital letters, bold, size 16" and centered at the top of the first page. The author(s) and affiliations(s) should be centered, bold, size 14" and single-spaced, beginning from the second line below the title.

First Author Name₁, Second Author Name₂, Third Author Name₃

1Author Designation, Department, Organization, City, email id

2Author Designation, Department, Organization, City, email id

3Author Designation, Department, Organization, City, email id

5. The abstract should summarize the context, content and conclusions of the paper in less than 350 words in 12 points italic Times New Roman. The abstract should have about five key words in alphabetical order separated by comma of 12 points italic Times New Roman.
6. Figures and tables should be centered, separately numbered, self explained. Please note that table titles must be above the table and sources of data should be mentioned below the table. The authors should ensure that tables and figures are referred to from the main text.

EXAMPLES OF REFERENCES

All references must be arranged first alphabetically and then it may be further sorted chronologically also.

• **Single author journal article:**

Fox, S. (1984). Empowerment as a catalyst for change: an example for the food industry. *Supply Chain Management*, 2(3), 29–33.

Bateson, C. D.,(2006), 'Doing Business after the Fall: The Virtue of Moral Hypocrisy', *Journal of Business Ethics*, 66: 321 – 335

• **Multiple author journal article:**

Khan, M. R., Islam, A. F. M. M., & Das, D. (1886). A Factor Analytic Study on the Validity of a Union Commitment Scale. *Journal of Applied Psychology*, 12(1), 129-136.

Liu, W.B, Wongcha A, & Peng, K.C. (2012), "Adopting Super-Efficiency And Tobit Model On Analyzing the Efficiency of Teacher's Colleges In Thailand", *International Journal on New Trends In Education and Their Implications*, Vol.3.3, 108 – 114.

- **Text Book:**

Simchi-Levi, D., Kaminsky, P., & Simchi-Levi, E. (2007). *Designing and Managing the Supply Chain: Concepts, Strategies and Case Studies* (3rd ed.). New York: McGraw-Hill.

S. Neelamegham," Marketing in India, Cases and Reading, Vikas Publishing House Pvt. Ltd, III Edition, 2000.

- **Edited book having one editor:**

Raine, A. (Ed.). (2006). *Crime and schizophrenia: Causes and cures*. New York: Nova Science.

- **Edited book having more than one editor:**

Greenspan, E. L., & Rosenberg, M. (Eds.). (2009). *Martin's annual criminal code: Student edition 2010*. Aurora, ON: Canada Law Book.

- **Chapter in edited book having one editor:**

Bessley, M., & Wilson, P. (1984). Public policy and small firms in Britain. In Levicki, C. (Ed.), *Small Business Theory and Policy* (pp. 111–126). London: Croom Helm.

- **Chapter in edited book having more than one editor:**

Young, M. E., & Wasserman, E. A. (2005). Theories of learning. In K. Lamberts, & R. L. Goldstone (Eds.), *Handbook of cognition* (pp. 161-182). Thousand Oaks, CA: Sage.

- **Electronic sources should include the URL of the website at which they may be found, as shown:**

Sillick, T. J., & Schutte, N. S. (2006). Emotional intelligence and self-esteem mediate between perceived early parental love and adult happiness. *E-Journal of Applied Psychology*, 2(2), 38-48. Retrieved from <http://ojs.lib.swin.edu.au/index.php/ejap>

- **Unpublished dissertation/ paper:**

Uddin, K. (2000). A Study of Corporate Governance in a Developing Country: A Case of Bangladesh (Unpublished Dissertation). Lingnan University, Hong Kong.

- **Article in newspaper:**

Yunus, M. (2005, March 23). Micro Credit and Poverty Alleviation in Bangladesh. *The Bangladesh Observer*, p. 9.

- **Article in magazine:**

Holloway, M. (2005, August 6). When extinct isn't. *Scientific American*, 293, 22-23.

- **Website of any institution:**

Central Bank of India (2005). *Income Recognition Norms Definition of NPA*. Retrieved August 10, 2005, from <http://www.centralbankofindia.co.in/home/index1.htm>, viewed on

7. The submission implies that the work has not been published earlier elsewhere and is not under consideration to be published anywhere else if selected for publication in the journal of Indian Academicians and Researchers Association.


8. Decision of the Editorial Board regarding selection/rejection of the articles will be final.

www.iaraedu.com

Journal

ISSN 2322 - 0899

**INTERNATIONAL JOURNAL OF RESEARCH
IN MANAGEMENT & SOCIAL SCIENCE**



Volume 8, Issue 2
April - June 2020

www.iaraedu.com

Journal

ISSN 2394 - 9554

**International Journal of Research in
Science and Technology**

Volume 6, Issue 2: April - June 2019



Indian Academicians and Researchers Association
www.iaraedu.com

**Become a member of IARA to avail
attractive benefits upto Rs. 30000/-**

<http://iaraedu.com/about-membership.php>



INDIAN ACADEMICIANS AND RESEARCHERS ASSOCIATION

Membership No: M / M – 1365

Certificate of Membership

This is to certify that

XXXXXXXX

is admitted as a

Fellow Member

of

Indian Academicians and Researchers Association

in recognition of commitment to Educational Research

and the objectives of the Association



Date: 27.01.2020


Director


President



INDIAN ACADEMICIANS AND RESEARCHERS ASSOCIATION

Membership No: M / M – 1365

Certificate of Membership

This is to certify that

XXXXXXXXXX

is admitted as a

Life Member

of

Indian Academicians and Researchers Association

in recognition of commitment to Educational Research
and the objectives of the Association



Date: 27.01.2020

Director

President



INDIAN ACADEMICIANS AND RESEARCHERS ASSOCIATION

Membership No: M / M – 1365

Certificate of Membership

This is to certify that

XXXXXXXXXX

is admitted as a

Member

of

Indian Academicians and Researchers Association

in recognition of commitment to Educational Research

and the objectives of the Association



Date: 27.01.2020

Director

President

IARA Organized its 1st International Dissertation & Doctoral Thesis Award in September'2019

1st International Dissertation & Doctoral Thesis Award (2019)



Organized By



Indian Academicians and Researchers Association (IARA)




EMPYREAL PUBLISHING HOUSE


www.editedbook.in

**Publish Your Book, Your Thesis into Book or
Become an Editor of an Edited Book with ISBN**

BOOKS PUBLISHED




Dr. Stuti Deka
ISBN : 978-81-930928-1-1




Dr. Tazyn Rahman
ISBN : 978-81-930928-0-4




Mr. Dinbandhu Singh
ISBN : 978-81-930928-3-5



Dr. Ismail Thamarasseri
ISBN : 978-81-930928-2-8




Ram Jaladurgam
Dr. S. Anand Reddy
ISBN : 978-81-930928-5-9



Dr. Sanjeev Bansal, Dr. Vijit Chaturvedi
Dr. Tazyn Rahman, Dr. Parikshit Joshi
ISBN : 978-81-930928-6-6




Ashish Kumar Sinha, Dr. Soubhik Chakraborty
Dr. Amritanjali
ISBN : 978-81-930928-8-0




Dr. Sanjeev Bansal, Dr. Vijit Chaturvedi
Dr. Tazyn Rahman, Dr. Parikshit Joshi
ISBN : 978-81-936264-0-5




Dr. Jyotsna Golhar
Dr. Sujit Metre
ISBN : 978-81-936264-6-7



Dr. Aarushi Kataria
ISBN : 978-81-936264-3-6



Dr. Sanjam Upadhyay
ISBN : 978-81-936264-5-0



Dr. Rita
ISBN : 978-81-930928-7-3



Dr. Manas Ranjan Panda, Dr. Prabodha Kr. Hota
ISBN : 978-81-930928-4-2



Poomima University
ISBN : 978-8193-6264-74



Institute of Public Enterprise
ISBN : 978-8193-6264-4-3

Vitamin D Supplementation in SGA Babies



Dr. Jyothi Naik
Prof. Dr. Syed Manazir Ali
Dr. Uzma Firdaus
Prof. Dr. Jamal Ahmed

Dr. Jyothi Naik, Prof. Dr. Syed Manazir Ali
Dr. Uzma Firdaus, Prof. Dr. Jamal Ahmed
ISBN : 978-81-939070-9-8



Gold Nanoparticles: Plasmonic Aspects And Applications

Dr. Abhishosh Kedia
Dr. Pandian Senthil Kumar

Dr. Abhishosh Kedia
Dr. Pandian Senthil Kumar
ISBN : 978-81-939070-0-9

Social Media Marketing and Consumer Behavior



Dr. Vinod S. Chandwani

Dr. Vinod
S. Chandwani
ISBN : 978-81-939070-2-3

Select Research Papers of

Prof. Dr. Dhananjay Awasarwar



Prof. Dr. Dhananjay Awasarwar

Prof. Dr. Dhananjay
Awasarwar
ISBN : 978-81-939070-1-6

Recent ReseaRch Trends in ManageMent



Dr. C. Samudhra Rajakumar
Dr. M. Ramesh
Dr. C. Kathiravan
Dr. Rincy V. Mathew

Dr. C. Samudhra Rajakumar, Dr. M. Ramesh
Dr. C. Kathiravan, Dr. Rincy V. Mathew
ISBN : 978-81-939070-4-7

Recent ReseaRch Trends in Social Science



Dr. C. Samudhra Rajakumar
Dr. M. Ramesh
Dr. C. Kathiravan
Dr. Rincy V. Mathew

Dr. C. Samudhra Rajakumar, Dr. M. Ramesh
Dr. C. Kathiravan, Dr. Rincy V. Mathew
ISBN : 978-81-939070-6-1

Recent Research Trend in Business Administration



Dr. C. Samudhra Rajakumar
Dr. M. Ramesh
Dr. C. Kathiravan
Dr. Rincy V. Mathew

Dr. C. Samudhra Rajakumar, Dr. M. Ramesh
Dr. C. Kathiravan, Dr. Rincy V. Mathew
ISBN : 978-81-939070-7-8

Recent Innovations in Biosustainability and Environmental Research II



Dr. V. I. Paul
Dr. M. Muthulingam
Dr. A. Elangovan
Dr. J. Nelson Samuel Jebastin

Dr. V. I. Paul, Dr. M. Muthulingam
Dr. A. Elangovan, Dr. J. Nelson Samuel Jebastin
ISBN : 978-81-939070-9-2

Teacher Education: Challenges Ahead



Sajid Jamal
Mohd Shakir

Sajid Jamal
Mohd Shakir
ISBN : 978-81-939070-8-5

Project Management



Dr. R. Emmaniel

ISBN : 978-81-939070-3-0

The *théâtre engagé*

American Drama from the '29 Crash to World War II

Dr. Sarala Barnabas

Dr. Sarala Barnabas

ISBN : 978-81-941253-3-4



AUTHORS
Dr. M. Banumathi
Dr. C. Samudhra Rajakumar

Dr. M. Banumathi

Dr. C. Samudhra Rajakumar

ISBN : 978-81-939070-5-4

VIJANAN

COMMERCE AND MANAGEMENT

Dr. Bahad Kulkar

Dr. (Mrs.) Rohini Kelkar

ISBN : 978-81-941253-0-3

Recent Research Trends in Management and Social Science

Dr. Tazyn Rahman

Dr. Tazyn Rahman

ISBN : 978-81-941253-2-7

VIJANAN

INFORMATION TECHNOLOGY

N. Lakshmi Kavitha
Mithila Satam

Dr. N. Lakshmi Kavitha

Mithila Satam

ISBN : 978-81-941253-1-0

Emerging Research

Trends in Management and Social Science

Dr. Hresh Luhar
Prof. Arti Sharma

Dr. Hresh Luhar
Prof. Arti Sharma

ISBN : 978-81-941253-4-1

Life of Slum Occupants & Saving Pattern

Dr. Hresh S. Luhar
Dr. Ashok S. Luhar

Dr. Hresh S. Luhar
Dr. Ashok S. Luhar

ISBN : 978-81-941253-5-8

Computerised Information System: Concepts & Applications

Babita Kanojia
Dr. Arvind S. Luhar

Dr. Babita Kanojia
Dr. Arvind S. Luhar

ISBN : 978-81-941253-7-2

SKILLS FOR SUCCESS



SK Nathan
SW Rajamonaharane

Dr. Sw Rajamonaharane
SK Nathan
ISBN : 978-81-942475-0-0

Witness Protection Regime An Indian Perspective



Aditi Sharma

Aditi Sharma
ISBN : 978-81-941253-8-9

Self-Finance Courses: Popularity & Financial Viability



Dr. Ashok S. Luhar
Dr. Hires S. Luhar

Dr. Ashok S. Luhar
Dr. Hires S. Luhar
ISBN : 978-81-941253-6-5

SMALL SCALE INDUSTRIES MANAGEMENT Issues, Challenges and Opportunities



Dr. B. Augustine Arockiaraj

Dr. B. Augustine Arockiaraj
ISBN : 978-81-941253-9-6



SPOILAGE OF VALUABLE SPICES BY MICROBES

Dr. Kuljinder Kaur

Dr. Kuljinder Kaur
ISBN : 978-81-942475-4-8

Financial Capability of Students: An Increasing Challenge in Indian Economy

Dr. Priyanka Malik



Dr. Priyanka Malik
ISBN : 978-81-942475-1-7

THE RELATIONSHIP BETWEEN ORGANIZATION CULTURE AND EMPLOYEE PERFORMANCE: HOSPITALITY SECTOR



Dr. Rekha P. Khosla

Dr. Rekha P. Khosla
ISBN : 978-81-942475-2-4

A GUIDE TO

TWIN LOBE BLOWER AND ROOT BLOWER TECHNIQUE



Dilip Pandurang Deshmukh

Dilip Pandurang Deshmukh
ISBN : 978-81-942475-3-1



SILVER JUBILEE COMMEMORATIVE LECTURE SERIES 2019-SNGC

Dr. D. Kalpana
Dr. M. Thangavel

Dr. D. Kalpana, Dr. M. Thangavel
ISBN : 978-81-942475-5-5



Indian Commodity Futures and Spot Markets

Dr. Aloysius Edward J.

Dr. Aloysius Edward J.
ISBN : 978-81-942475-7-9



Correlates of Burnout Syndrome Among Servicemen

Dr. Binomary Ohigueri Ekechukwu

Dr. R. O. Ekechukwu
ISBN : 978-81-942475-8-6

Advances in Mathematical Sciences

(A Collection of Survey Research Articles)

Edited By
Dr. Zakir Ahmed



Dr. Zakir Ahmed
ISBN : 978-81-942475-9-3




Fair Value Measurement

Challenges and Perceptions

Dr. (CA) Ajit S. Joshi
Dr. Arvind S. Luhar


Dr. (CA) Ajit S. Joshi
Dr. Arvind S. Luhar
ISBN : 978-81-942475-6-2



NONLINEAR OPTICAL CRYSTALS FOR LASER Growth and Analysis Techniques

Madhav N Rode
Dilipkumar V Mehraam


Madhav N Rode
Dilip Kumar V Mehraam
ISBN : 978-81-943209-6-8



Remote Sensing of River Pollution And Agricultural Soils

Dr. Saif Said
Mr. Shadab Ali Khan


Dr. Saif Said
Shadab Ali Khan
ISBN : 978-81-943209-1-3



Creating Talent Pool of Trained and Skilled IT Professionals to cope up With Emerging Needs of IT Industry

Dr. Smita Ameya Wagh


Dr. Smita Ameya Wagh
ISBN : 978-81-943209-9-9



Radio (FM) Advertising and Consumer Behavior

Dr. Mahesh Mukund Deshpande

Dr. Mahesh Mukund Deshpande
ISBN : 978-81-943209-7-5




Indian Capital Market and Equity Culture in Maharashtra

Dr. Roopali Prashant Kudare


Dr. Roopali Prashant Kudare
ISBN : 978-81-943209-3-7




M. Thiruppathi
R. Rex Immanuel
K. Arivukkaran
ISBN : 978-81-930928-9-7




Dr. Th. Anand Singh
Dr. Prakash K. Sarangi
Dr. Neeta Sarangthem
ISBN : 978-81-944069-0-7




R. Rex Immanuel
M. Thiruppathi
A. Balasubramanian
ISBN : 978-81-943209-4-4



Dr. Omkar V. Gadre
ISBN : 978-81-943209-8-2




Madhav N Rode
Rameshwar R. Bhosale
ISBN : 978-81-943209-5-1




Dr. Sapna M S
Dr. Radhika C A
ISBN : 978-81-943209-0-6




Hindusthan College
ISBN : 978-81-944813-8-6



Swing
ISSN: 978-81-944813-9-3




Dr. Bhagyashree Dudhade
ISBN : 978-81-944069-5-2



S. Saad, S. Bushra, A.A. Khan

S. Saad, S. Bushra, A. A. Khan

ISBN: 978-81-944069-9-0




Prashant S. Kore
Pravina S. Ugile-Pawar
Madhav N Rode

Prashant S. Kore

Pravina S. Ugile-Pawar

Madhav N Rode

ISSN: 978-81-944069-7-6




Mixed Magnetic Oxides

Dilipkumar V Meshram
Madhav N Rode

Dilipkumar V Meshram and
Madhav N Rode

ISSN: 978-81-944069-6-9



Dr. Vijaya Lakshmi Pothuraju

Dr. Vijaya Lakshmi Pothuraju

ISBN : 978-81-943209-2-0



National Level Seminar

on
'E-Business: A Paradigm Shift in the 21st Century'
January 30th & 31st 2020

Organized by
Department of Commerce & Management



Sponsored by

Savitribai Phule Pune University, Pune
(under Quality Improvement Programme)

Kamala Education Society's
Pratibha College of Commerce and Computer Studies,
Accredited by NAAC with "B" Grade (CGPA 2.68)

PROCEEDINGS

Pratibha College

ISBN : 978-81-944813-2-4



STATE LEVEL SEMINAR

'Emerging Environmental Challenges
&
Its Sustainable Approaches'

7th & 8th, February 2020

Sponsored by

Savitribai Phule Pune University, Pune
(under Quality Improvement Programme)

PROCEEDINGS

Organized by

Department of Environmental Science

Kamala Education Society's


Pratibha College of Commerce and Computer Studies,
(Accredited with NAAC "B" Grade)

Tel. (Off.) : 8800100942/45, 020-65111411

www.pccos.org.in

Pratibha College

ISBN : 978-81-944813-3-1




Women Empowerment

Dr. Tazyn Rahman

Dr. Tazyn Rahman

ISBN : 978-81-936264-1-2




Women Empowerment- Awakening of a New Era

Dr. Tazyn Rahman

Dr. Tazyn Rahman

ISBN : 978-81-944813-5-5




Dr. Reni Sebastian


International Migration of Nurses from Kerala: Impact on Kerala Economy

Dr. Reni Sebastian


ISBN : 978-81-944069-2-1




Dr. Vijay Prakash Gupta
ISBN : 978-81-944813-1-7




Dr. Deepa Vijay Abhonkar
ISBN : 978-81-944813-6-2



Arasu Engineering College
ISSN: 978-81-944813-4-8



Dr. Ann Varghese
ISBN : 978-81-944069-4-5



Dr. Renuka Vanarse
ISBN : 978-81-944069-1-4



INDIAN ACADEMICIANS & RESEARCHERS ASSOCIATION

Major Objectives

- To encourage scholarly work in research
- To provide a forum for discussion of problems related to educational research
- To conduct workshops, seminars, conferences etc. on educational research
- To provide financial assistance to the research scholars
- To encourage Researcher to become involved in systematic research activities
- To foster the exchange of ideas and knowledge across the globe

Services Offered

- Free Membership with certificate
- Publication of Conference Proceeding
- Organize Joint Conference / FDP
- Outsource Survey for Research Project
- Outsource Journal Publication for Institute
- Information on job vacancies

Indian Academicians and Researchers Association

Shanti Path ,Opp. Darwin Campus II, Zoo Road Tiniali, Guwahati, Assam

Mobile : +919999817591, email : info@iaraedu.com www.iaraedu.com



EMPYREAL PUBLISHING HOUSE

- Assistant in Synopsis & Thesis writing
- Assistant in Research paper writing
- Publish Thesis into Book with ISBN
- Publish Edited Book with ISBN
- Outsource Journal Publication with ISSN for Institute and private universities.
- Publish Conference Proceeding with ISBN
- Booking of ISBN
- Outsource Survey for Research Project

Publish Your Thesis into Book with ISBN "Become An Author"

EMPYREAL PUBLISHING HOUSE

Zoo Road Tiniali, Guwahati, Assam

Mobile : +919999817591, email : info@editedbook.in, www.editedbook.in

